U.S. Department of Justice National Institute of Justice




# **National Institute** of **Justice**

**American Correctional Association** 

# **National Directory of Corrections Construction**

**Second Edition** 



## About the National Institute of Justice

The National Institute of Justice is a research branch of the U.S. Department of Justice. The Institute's mission is to develop knowledge about crime, its causes and control. Priority is given to policy-relevant research that can yield approaches and information that State and local agencies can use in preventing and reducing crime. The decisions made by criminal justice practitioners and policymakers affect millions of citizens, and crime affects almost all our public institutions and the private sector as well. Targeting resources, assuring their effective allocation, and developing new means of cooperation between the public and private sector are some of the emerging issues in law enforcement and criminal justice that research can help illuminate.

Carrying out the mandate assigned by Congress in the Justice Assistance Act of 1984, the National Institute of Justice:

- Sponsors research and development to improve and strengthen the criminal justice system and related civil justice aspects, with a balanced program of basic and applied research.
- Evaluates the effectiveness of justice improvement programs and identifies programs that promise to be successful if continued or repeated.
- Tests and demonstrates new and improved approaches to strengthen the justice system, and recommends actions that can be taken by Federal, State, and local governments and private organizations and individuals to achieve this goal.
- Disseminates information from research, demonstrations, evaluations, and special programs to Federal, State, and local governments, and serves as an international clearinghouse of justice information.
- Trains criminal justice practitioners in research and evaluation findings, and assists practitioners and researchers through fellowships and special seminars.

The Director of the Institute is appointed by the President of the United States, and upon confirmation by the Senate, serves at the President's pleasure. The Director establishes the research and development objectives of the Institute. The Director has final authority to approve grants, contracts, and cooperative agreements, and maintains responsibility for fiscal operations of the Institute. In establishing its research agenda, the Institute is guided by the priorities of the Attorney General and the needs of the criminal justice field. The Institute actively solicits the views of police, courts, and corrections practitioners as well as the private sector to identify the most critical problems and to plan research that can help resolve them.

James K. Stewart Director

## **About the American Correctional Association**

The American Correctional Association (ACA) is a multidisciplinary organization consisting of individuals, agencies, and organizations involved in the entire spectrum of correctional activities. A membership organization, the ACA is committed to the needs of its members. It serves as a forum and clearinghouse on correctional issues, is a leading publisher of correctional publications, promotes the professional development of persons working in all aspects of corrections, and is the accrediting body for correctional facilities, agencies, and programs.

The American Correctional Association was founded in 1870 as the National Prison Association and was later called the American Prison Association. Congresses of Correction have been held every year since 1870. At the 1954 Annual Congress of Correction, the name was changed to the American Correctional Association to reflect the expanding philosophy of corrections and its increasingly important role in society.

As the national voice of corrections, the American Correctional Association is committed to exerting a positive influence on the shaping of national and international correctional policy. Perhaps ACA's most pervasive influence has been in its nationally recognized and accepted standards and accreditation program for adult and juvenile facilities.

The ACA is a leading publisher of correctional materials, including correspondence courses, books, a magazine, and newsletters. ACA also trains correctional personnel at all levels through onsite workshops and correspondence courses. ACA sponsors two meetings annually: the Congress of Correction in August, and the Winter Conference in January. Both include lectures, seminars, workshops, and exhibits addressing a wide variety of correctional issues.

**Su Cunningham** *President* 

## U.S. Department of Justice

National Institute of Justice
Office of Communication and Research Utilization

# **National Directory of Corrections Construction**

## **Second Edition**

by

Charles B. DeWitt

National Institute of Justice

April 1988

#### **National Institute of Justice**

James K. Stewart

Director

#### **American Correctional Association**

Su Cunningham President

published by the American Correctional Association 4321 Hartwick Road, Suite L-208 College Park, MD 20740 301-699-7600

This project was supported by the U.S. Department of Justice, National Institute of Justice grant number 84–IJ–CS–0019, awarded to Charles B. DeWitt, Research Fellow, National Institute of Justice. This Second Edition of the *National Directory of Corrections Construction* was prepared by Aspen Systems Corporation under contract number OJP–87–C–002, and published by the American Correctional Association. Points of view or opinions stated in this document are those of the author and do not necessarily represent the official position or policies of the U.S. Department of Justice or the American Correctional Association.

The facility design and management concepts illustrated by the projects published in this directory do not necessarily reflect the official policy or recommendations of the National Institute of Justice or the American Correctional Association nor is any endorsement of particular designs, firms, or products implied. In particular, it is not possible to determine if all facilities shown here are in full compliance with the Federal Juvenile Justice and Delinquency Prevention Act.

Copyright © 1988 by Charles B. DeWitt.

## **Foreword**

## **National Institute of Justice**

Corrections policymakers and administrators face difficult choices today. Should they spend scarce resources on expensive prison and jail construction to accommodate growing jail and prison populations or must they release convicted offenders into the community as a way of easing crowded conditions?

Space shortages distort and subvert our justice system. In 1985, for example, more than 18,000 prisoners were released before completing their sentences because of space limitations. At the same time, prison construction and operating costs have risen enormously, making corrections the fastest growing component of State budgets. Investment in building has tripled over the past 3 years—to \$3 billion in 1986. States are expected to spend an estimated \$20 billion on prison construction in the next 10 years.

Now there has been an important advance that can help State and local jurisdictions get the best return on their investment and build the corrections facilities they need to protect their communities. The National Institute of Justice created the Construction Information Exchange to share practical information on new technology and modern construction techniques that can mean quicker and more economical expansion of corrections capacity.

A key element of the program is this *National Directory* of Corrections Construction. Based on results of a national survey by the National Institute of Justice, the directory is a catalog of up-to-date designs, construction methods, and costs for 262 jails and prisons built since 1978. State and local officials can turn to this compendium for a wide range of options to help them make the most informed decisions on corrections construction in the next decade and beyond.

The information in the directory is maintained and regularly updated in the Construction Information Exchange data base. This computerized data base includes even greater detail on construction projects nationwide. With just a phone call, State and local officials can get the most current information on new design, materials, and construction techniques, tailored to the specific building issues and concerns of a particular jurisdiction.

The National Institute of Justice also publishes Construction Bulletins highlighting State and local projects that have implemented swifter and less costly building techniques. The bulletins offer step-by-step descriptions of how jurisdictions solved their construction problems through progressive management and innovative methods.

Attorney General Edwin Meese III, in announcing the new Construction Information Exchange, said the effort will provide much-needed help to States and localities in addressing the problem of prison and jail crowding through more efficient construction.

Solutions to the challenges facing our prisons and jails as we move toward the 21st century require the energy and initiative of all those concerned about corrections. The National Institute of Justice is indebted to the American Correctional Association, whose support makes possible the publication of this directory. This cooperative venture between the National Institute of Justice and the American Correctional Association exemplifies the benefits of public-private partnerships in achieving a common objective: helping State and local officials build or expand corrections facilities better, faster, and more economically.

James K. Stewart
Director
National Institute of Justice

## **Foreword**

## **American Correctional Association**

The impact of design on the efficiency of a correctional program is tremendous. History is replete with the evolution of jail and prison design solutions that correspond to the penal philosophy of the era.

This change of correctional design has evolved from the Bridewell Houses of 1557 in England through the periods of Workhouses, Banishment, Convict Ships, Wymondham Penitentiaries, and the Pennsylvania and Auburn systems, which were popularized in the 1880's.

The 19th century was generally a period of reformation that required prison designers to place increasing emphasis on the use of prisoner labor with minimal concern for the health and safety of either prisoner or prison employee, a condition that inspired the founders of the American Correctional Association Congress in 1870 to declare a basic principle of the association to be the development of more adequate prison architecture.

These ideals were followed by correctional officials with varying degrees of success until the decades of 1960 and 1970 when the courts imposed a series of orders requiring increased attention to prison and jail conditions.

The American Correctional Association is proud to be associated with the National Institute of Justice in the publication of this directory. It clearly represents the current status of correctional design and is in keeping with the contemporary thinking as expressed by Chief Justice Warren Burger in 1981: "To put people behind bars and do little or nothing to change them is to win a battle and lose a war."

Correctional design plays an important role in our society, and careful review of the information contained herein can have great impact on the future of imprisonment as we approach the 21st century.

Anthony P. Travisono
Executive Director
American Correctional Association

## **Acknowledgments**

Many people offered support and assistance for this publication. Special thanks go to the following:

## **National Institute of Justice**

Paul Cascarano, Assistant Director

#### **American Institute of Architects**

Tony R. Lang, AIA, Chairman, Committee on Architecture for Justice
Michael D. Cohn, Design Department
Allen Patrick, AIA, Past Chairman, Committee on Architecture for Justice
W. Gene Williams, AIA, Past Chairman, Committee on Architecture for Justice
Wantland J. Smith, AIA, C.E., Committee on

#### **National Institute of Corrections**

Raymond Brown, Director Michael O'Toole, Chief, Jails Division Coralie Whitmore, Information Center

## **Federal Bureau of Prisons**

Architecture for Justice

 J. Michael Quinlan, Director
 Wade B. Houk, Assistant Director for Administration
 Loy Hayes, Deputy Assistant Director for Administration
 Mary Galey, AIA, Architect, Facilities Development and Operations
 Jon Irwin, AIA, Architect, Facilities Development and Operations

## **National Sheriffs' Association**

L. Cary Bittick, Executive Director Thomas Finn, Assistant Executive Director

## **National Criminal Justice Reference Service**

The following NCJRS staff provided many hours of support in gathering, editing, and verifying the information in this directory as well as in design and production.

Marita Menaker, Senior Writer-Editor Timothy H. Matthews, Information Specialist Cheryll Bissell, Information Specialist Ann Gardner, Artist Janet Rosenbaum, Reference Supervisor Mary Zitello, Supervisor of Editorial Services Special thanks should also be given to all of the architects, facility administrators, and local government officials who contributed information about their projects.

We are also grateful to the architectural firm of Hansen Lind Meyer, Inc., of Orlando, Florida, which provided illustrations of the Federal Correctional Institution at Marianna, Florida, for our cover.

Charles B. DeWitt Project Director

## **American Correctional Association**

This publication was made possible by support from the American Correctional Association. The National Institute of Justice welcomes this cooperation and assistance in publishing the results of an important Federal initiative. We are grateful for the professionalism and dedication shown by ACA staff who worked on this project.

Anthony P. Travisono, Executive Director W. Hardy Rauch, Director, Standards and Accreditation

Patricia L. Millard, Director, Communications and Publications

# **Contents**

Foreword (NIJ) iii	Maximum Security Unit, Tucker Unit 102
Foreword (ACA) iv	Saline County Detention Facility 104 California
Acknowledgments v	Alameda County North County Jail 106 California Correctional Institution 108
Section I Introduction 3 Policy research 5 NIJ survey 7	California Medical Facility—South 110 California State Prison—Sacramento County/ Folsom 112 Contra Costa County Detention Facility 114 Elmwood—Barracks 24 116
Section II  How to use this directory 11 Terms used in this directory 17  Section III Index by State/county/city 27	Foothill Communities Law & Justice Center 118 Kings County Branch Jail 120 Lacy Security Facility 122 Nevada County Detention Center 124 Orange County Sheriff's Intake Release Center 126 Placer County Jail 128
Index by inmate design capacity 33 Index by category of construction 39 Index by facility name 47	Plumas County Sheriff's Department & Detention Facility 130 Pre-Trial Detention Facility 132 Richard J. Donovan Correctional Facility at Rock
Section IV Facility profiles: Alabama Federal Correctional Institution, Talladega 54 Jefferson County Jail 56 West Jefferson Correctional Facility 58	Mountain 134 San Joaquin County Honor Farm Women's Minimum Security Facility 136 Santa Barbara County Main Jail 138 Santa Cruz County Jail (Phase I) 140 Sequoia Field Detention Facility 142
Alaska  Cook Inlet Pre-Trial Facility 60 Cook Inlet Pre-Trial Facility Phase II 62 Fairbanks Correctional Center 64 Hiland Mountain Correctional Center 66 Mat-su Pre-Trial Facility 68 Meadow Creek Correctional Center 70 Palmer Correctional Center Medium Security Facility 72 Wildwood Correctional Center 74 Yukon Kuskokwim Correctional Center 76	Shasta County Justice Center 144 Sonoma North County Detention Facility 146 Stanislaus County Jail 148 Sunnyvale Public Safety Temporary Holding Facility 150 Torrance Police Department 152 Tuolumne County Jail 154 Yuba County Jail 156 Colorado Adams County Detention Facility 158 Alamosa County Law Enforcement Center 160 Arkansas Valley Correctional Facility 162
Arizona Arizona State Prison—Florence 78 Arizona State Prison—Perryville 80 Cochise County Jail 82 Federal Correctional Institution, Phoenix 84 Federal Correctional Institution, Tucson 86 Pima County Adult Detention Center 88 Pima County Adult Detention Center (Addition) 90 Pinal Mountain Juvenile Institution 92 Sacaton Juvenile Rehabilitation Center 94	Delta County Criminal Justice Facility 164 Garfield County Jail 166 Pitkin County Jail 168 Summit County Justice Center 170 Connecticut Bridgeport Correctional Center: Modular Units 172 J. Bernard Gates Correctional Unit 174 Delaware Delaware Correctional Center (Maximum
Arkansas Clark County Detention Facility 96 Cummins Unit—Medium Security 98 Garland County Detention Facility 100	Security) 176  Florida  Alachua County Corrections Facility 178  Federal Correctional Institution, Tallahassee 180

## Contents (continued)

Leon County Jail 182 Leon County Justice Complex 184 Marion County Detention Center 186 Martin Correctional Institution 188 Pinellas County Jail—Medium Security Facility 190 Santa Rosa County Jail 192 Seminole County Correctional Facility 194 South Florida Reception Center 196 Union Correctional Institution 198	Louisiana Dixon Correctional Institute 258 Federal Detention Center, Oakdale 260 Feliciana Forensic Facility 262 Hunt Correctional Center 264 Louisiana Correctional Institute for Women 266 Washington Correctional Institute 268 Maine Franklin County Detention/Law Enforcement Facility 270
Georgia Clarke County Correctional Institution 200 Dooly County Jail 202 Richmond County Law Enforcement and Justice Center 204 Hawaii Maui Community Correctional Center 206 Illinois	Maryland Baltimore City Correctional Center 272 Baltimore City Jail 274 Eastern Correctional Institution 276 Montgomery County Detention Center 278 Prince George's County Correctional Center 280 Somerset County Detention Center 282 Washington County Detention Center 284
Centralia Correctional Center 208 Cook County Medical and Psychiatric Facility—RTU Building 210 Danville Correctional Center 212 Dixon Correctional Center 214 Douglas County Jail 216 DuPage County Jail and Sheriff's Department 218 Dwight Correctional Center (1979 Addition) 220 Dwight Correctional Center (1984 Addition) 222 East Moline Correctional Center 224 Graham Correctional Center 226 Illinois Youth Center—Kankakee (Dining Facility) 228 Illinois Youth Center—Kankakee (Housing Unit) 230 Peoria County Adult Detention and Work Release Facility 232	Massachusetts Longwood Treatment Center 286 Massachusetts Correctional Institution Norfolk 288  Michigan Correction Camp Cusino 290 Grand Traverse County Correctional Facility 292 Macomb County Jail 294 State Prison of Southern Michigan 296  Minnesota Hennepin County Juvenile Detention Center 298 Minnesota Supervised Living Facility 300  Mississippi Jackson County Adult Detention Center 302 Mississippi State Penitentiary—Unit 29 304 Tunica County Jail and Sheriff's Department 306
Rock Island County Jail 234 Shawnee Correctional Center 236 Sheridan Correctional Center (Kitchen/Dining Facility) 238 Sheridan Correctional Center (Medical/Security Services) 240 Indiana	Missouri Clay County Detention Center 308 Farmington Correctional Center 310 Fulton Reception and Diagnostic Center, Phase I 312 Jackson County Detention Center 314 Missouri Eastern Correctional Center 316
Marion County Jail 242  Iowa Polk County Jail 244 Woodbury Law Enforcement Center 246  Kansas Johnson County Juvenile Hall 248 Kansas State Penitentiary (Phase One) 250 Shawnee County Department of Corrections 252  Kentucky Federal Correctional Institution, Ashland 254 Knox County Jail 256	Montana Chouteau County Law Enforcement Facility 318 Jefferson County Criminal Justice Center 320 Lewis and Clark County Criminal Justice Facility 322 Pondera County Jail 324 Yellowstone County Detention Facility 326 Nebraska Dodge County Judicial Center 328 Douglas County Correctional Center 330 Nebraska State Penitentiary 332

## Contents (continued)

Clark County Detention Center 334 New Jersey Camden County Correctional Facility 336 Gerald L. Gormley Justice Facility 338 Middlessex County Correctional Facility 340 Ocean County Justice Complex 342 Southern State Correctional Facility Modular Units (Phase I and II) 344 Trenton State Prison 346 Warren County Correctional Facility Modular Units (Phase I and II) 344 Trenton State Prison 346 Warren County Correctional Center 348 New Mexico Bernalillo County Detention Center (South Tower) 350 Central New Mexico Correctional Facility 352 Penitentiary of New Mexico 354 Southern New Mexico Correctional Facility 356 Western New Mexico Correctional Facility 356 Western New Mexico Correctional Facility 358 Youth Diagnostic and Development Center—Phase III 360 New York Brooklyn Correctional Facility 364 Elmira Correctional Facility 368 Eric County Holding Center 370 Federal Correctional Institution, 01swille 372 Federal Correctional Institution, 01swille 372 Federal Correctional Institution, 01swille 372 Federal Correctional Center 376 Masten Park Secure Center 378 North Facility 380 Riker Island: Modular Units 382 North Facility 380 North Carolina Craven County Law Enforcement Center 384 Eastern Correctional Center 390 Ohio Ashtabula County Justice Center 392 Clermont County Sail 394 Hamilton County Justice Complex 396 Madison Correctional Institution 400 Ohio Reformatory or Women 402 Ohio Reformatory or Women 403 Ohio Reformatory		
New Jersey Carnden County Correctional Facility 336 Gerald L. Gormley Justice Facility 338 Middlesex County Correctional Facility 338 Middlesex County Justice Complex 342 Southern State Correctional Facility: Modular Units (Phase I and II) 344 Trenton State Prison 346 Warren County Correctional Center 348 New Mexico Bernalillo County Detention Center (South Tower) 350 Central New Mexico Correctional Facility 352 Penitentiary of New Mexico 534 Southern New Mexico Correctional Facility 356 Western New Mexico Correctional Facility 366 Erie County Correctional Facility 364 Elmira Correctional Agency and Correctional Facility 368 Erie County Correctional Institution, 400 Crederal Correctional Center 370 Federal Correctional Center 370 Masten Park Secure Center 378 Masten Park Secure Center 378 Masten Park Secure Center 378 Morth Facility 360 Rikers Island: Modular Units 382 North Carolina Craven County Law Enforcement Center 484 Eastern Correctional Center 392 Clemment County Jail 394 Hamilton County Justice Center 392 Clemment County Jail 394 Hamilton County Justice Center 392 Clemment County Jail 394 Hamilton County Justice Center 392 Clemment County Jail 394 Hamilton County Justice Center 408 Wayne County Justice Center 410 Kay County Detention Center 410 Kay County Detention Facility 412 Lexington Assessment & Reception Center 410 Kay County Detention Center 410 Kay C	Nevada	Lexington Assessment & Reception Center, Phase
Camden County Correctional Facility 336 Gerald L. Gormley Justice Facility 338 Middlesex County Correctional Facility 340 Ocean County Justice Complex 342 Southern State Correctional Facility: Modular Units (Phase I and II) 344 Trenton State Prison 346 Warren County Correctional Center 348 New Mexico Bernalillo County Detention Center (South Tower) 350 Central New Mexico Correctional Facility 352 Penitentiary of New Mexico Correctional Facility 352 Penitentiary of New Mexico Correctional Facility 358 Western New Mexico Correctional Facility 358 Wouth Diagnostic and Development Center—Phase III 362 New York Brooklyn Correctional Facility 364 Elmira Correctional Reception Center Food Service & Dining Facility 368 Eric County Holding Center 376 Masten Park Secure Center 378 North Facility 380 Rikers Island: Modular Units 382 Rikers Island: Modular Units 382 Rikers Island: Modular Units 382 Rorth Facility 380 Rikers Island: Modular Units 382 North Carolina Central Prison 388 Southern Correctional Institution, Pass Brook 374 Kirby Forensic Psychiatric Center 376 Masten Park Secure Center 386 North Carolina Central Prison 388 Southern New Mexico Orrectional Institution, Augustic Center 450 Beto I Unit 462 Beto I Unit 462 Beto I Unit 472 Coman County Justic Center 470 Chambers County Jail 476 Darrington Unit 478 Diagnostic Unit 480 Ellis I Unit (Phase I and II) 482 Federal Correctional Institution, Bastrop 486 Ferguson Unit 488 Federal Correctional Institutio	Clark County Detention Center 334	
Gerald L. Gormley Justice Facility 338 Middlesex County Correctional Facility 340 Ocean County Justice Complex 342 Southern State Correctional Facility: Modular Units (Phase I and II) 344 Trenton State Prison 346 Warren County Correctional Facility 352 Bernalillo County Detention Center (South Tower) 350 Central New Mexico Bernalillo County Detention Center (South Tower) 350 Central New Mexico Correctional Facility 352 Penitentiary of New Mexico 354 Southern New Mexico Correctional Facility 355 Youth Diagnostic and Development Center—Phase III 362 New York Brooklyn Correctional Facility 364 Elmira Correctional Facility 364 Elmira Correctional Facility 368 Erie County Correctional Facility 368 Erie County Holding Center 376 Masten Park Secure Center 378 North Facility 380 Nikers Island: Modular Units 382 North Carolina Craven County Law Enforcement Center 384 Hamilton County Justice Center 386 North Carolina Central Prison 388 Southern Correctional Institution, and Southern Correctional Center 390 Ohio Ashtabula County Justice Center 392 Clermont County Justice Center 392 Clermont County Justice Center 392 Madison Correctional Institution 402 Ohio Reformatory for Wemen 402 Ohtawa County Detention Facility 404 Ross Correctional Institution 400 Ohio Reformatory for Wemen 402 Ohtawa County Justice Center 408 Oklahoma Cleveland County Justice Center 408 Oklahoma Cleveland County Detention Facility 412 Lexington Assessment & Reception Center  40 Kay County Detention Facility 412 Lexington Assessment & Reception Center  40 Correctional Center 40 Correctional Institution 40 Oklahoma Cleveland County Detention Center 410 Kay County Detention Facility 412 Lexington Assessment & Reception Center  40 Correctional Center 408 County Detention Facility 412 Lexington Assessment & Reception Center  410 Correctional Center 410 County Justice Center 408 County Detention Facility 412 Lexington Assessment & Reception Center  410 County Justice Center 408 County Detention Facility 412 County Detention Center 410 County Justice Cente	New Jersey	
Middlesex County Correctional Facility Ocean County Justice Complex 342 Southern State Correctional Facility: Modular Units (Phase I and II) 344 Trenton State Prison 346 Warren County Correctional Center 348 New Mexice Bernalillo County Detention Center (South Tower) 350 Central New Mexico Correctional Facility 352 Penitentiary of New Mexico St4 Southern New Mexico Correctional Facility 356 Western New Mexico Correctional Facility 364 Elmira Correctional & Reception Center Food Service & Dining Facility 368 Eric County Correctional Facility 368 Eric County Holding Center 370 Federal Correctional Institution, Otisville 372 Federal Correctional Institution, Otisville 372 Federal Correctional Institution, Otisville 372 Federal Correctional Institution, 382 North Facility 380 Rikers Island: Modular Units 382 Rikers Island: Modular Units 382 North Carolina Craven County Law Enforcement Center 384 Eastern Cornety Jail 446 Wyoming County Jail 446 Bear County Justice Center 376 North Carolina Center 380 Ohio Ohio Ashtabula County Justice Center 392 Clermont County Jail 394 Hamilton County Justice Center 392 Clermont County Justice Center 392 Clermont County Justice Center 392 Clermont County Justice Complex 398 Madison Correctional Institution 400 Ohio Reformatory for Women 402 Ottawa County Detention Facility 404 Ross Correctional Institution 400 Ohio Reformatory for Women 402 Ottawa County Justice Center 408 Oklahoma Cleveland County Justice Center 410 Kay County Detention Facility 412 Lexington Assessment & Reception Center 410 Kay County Detention Facility 412 Lexington Assessment & Reception Center 410 Kay County Detention Facility 412 Lexington Assessment & Reception Center 410 Kay County Detention Facility 412 Lexington Assessment & Reception Center 410 Kay County Detention Facility 412 Lexington Assessment & Reception Center 410 Kay County Detention Facility 412 Lexington Assess	Camden County Correctional Facility 336	
Ocean County Justice Complex 342 Southern State Correctional Facility 364 Trenton State Prison 346 Warren County Correctional Facility 352 Penitentiary of New Mexico 354 Southern New Mexico Correctional Facility 352 Penitentiary of New Mexico 354 Southern New Mexico Correctional Facility 358 Youth Diagnostic and Development Center—Phase III 362 New York Brooklyn Correctional Facility 364 Elmira Correctional Facility 364 Elmira Correctional Facility 368 Eric County Correctional Facility 368 Eric County Holding Center 370 Federal Correctional Institution, Otisville 372 Federal Correctional Institution, Otisville 372 Federal Correctional Institution, Otisville 374 Kirby Forensic Psychiatric Center 376 Masten Park Secure Center 378 North Facility 380 Rikers Island: Modular Units 382 North Carolina Center 380 North Carolina Office Complex 366 North Carolina Center 380 North Carolina Institution 400 Ohio Reformatory for Women 402 Ottawa County Justice Center 408 Oklahoma Cleveland County Justice Center 408 Oklahoma Cleveland County Detention Center 410 Kay County Detention Facility 412 Lexington Assessment & Reception Center 410 Kay County Detention Facility 412 Lexington Assessment & Reception Center 410 Kay County Detention Facility 412 Lexington Assessment & Reception Center 410 Kay County Detention Facility 412 Lexington Assessment & Reception Center 410 Kay County Detention Facility 412 Lexington Assessment & Reception Center 410 Kay County Detention Facility 412 Lexington Assessment & Reception Center	Gerald L. Gormley Justice Facility 338	
Southern State Correctional Facility: Modular Units (Phase I and II) 344 Trenton State Prison 346 Warren County Correctional Center 348 New Mexico Bernalillo County Detention Center (South Tower) 350 Central New Mexico Correctional Facility 352 Pentineturary of New Mexico 354 Southern New Mexico Correctional Facility 358 Western New Mexico Correctional Facility 358 Wostern New Mexico Correctional Facility 364 Elmira Correctional Encility 364 Elmira Correctional Facility 368 Eric County Correctional Facility 368 Eric County Holding Center 370 Federal Correctional Institution, Ray Brook 374 Kirby Forensic Psychiatric Center 376 Masten Park Secure Center 378 Mostern Park Secure Center 378 North Facility 380 Rikers Island: Modular Units 382 North Carolina Center 386 North Carolina Center 386 North Carolina Center 390 Ohio Ashtabula County Justice Center 392 Clermont County Justice Complex 398 Madison Correctional Institution 400 Ohio Reformatory for Women 402 Ottawa County Detention Facility 412 Hamilton County Justice Center 408 Oklahoma Cleveland County Detention Center 440 Kay County Detention Center 410 Kay County Detention Facility 412 Lexington Assessment & Reception Center  Jackson County Jail Annex 430 Blair County Prison 432 Lycoming County Prison 438 State Correctional Institution at Smithfield 440 State Regional Correctional Institution 446 State Regional Correctional Institution 448 Gilliam Psychiatric Center 448 Gilliam Psychiatric Center 454 Tremessee Nashville Community Service Center 458 Texas Austin County Justice Center 458 Texas Austin County Justice Center 456 Shelby County Justice Center 458 Texas Austin County Justice Center 470 Chambers County Juvenile Center 470 Chambers County Law Enforcement Center 472 Coffield Unit 474 Comal County Jail 496 Betail Unit 478 Darrington Unit 478 Diagnostic and Development Center 484 Federal Correctional Institution 490 Hidelphoy County Justice Center 470 Chambers County Juvenile Center 470 Chambers County Juvenile Center 470 Chambers County Juvenile Center 4		
(Phase I and II) 344 Trenton State Prison 346 Warren County Correctional Center 348 New Mexico Bernalillo County Detention Center (South Tower) 350 Central New Mexico Correctional Facility 352 Penitentiary of New Mexico 354 Southern New Mexico Correctional Facility 358 Youth Diagnostic and Development Center—Phase III 362 New York Brooklyn Correctional Facility 364 Elmira Correctional & Reception Center 370 Federal Correctional Facility 368 Eric County Correctional Facility 368 Eric County Holding Center 370 Federal Correctional Institution, Otisville 372 Kirby Forensic Psychiatric Center 376 Masten Park Secure Center 378 North Carolina Center 380 Rikers Island: Modular Units 382 North Carolina Central Prison 388 Southern Correctional Center 390 Ohio Ashtabula County Justice Center 392 Clermont County Justice Complex 396 Logan County Jail and Office Complex 396 Logan County Jail and Office Complex 396 Logan County Jail and Office Complex 396 Logan County Justice Center 408 Oklahoma Cleveland County Detention Facility 412 Rentification 348 Pennnsylvania Allegheny County Prison 432 Pennnsylvania Allegheny County Prison 432 Pennnsylvania Allegheny County Prison 432 Philadelphia Industrial Correctional Center 436 Schuyklill County Prison 438 State Correctional Institution at Smithfield 440 State Regional Correctional Institution 452 Warren County Jail 444 Worning County Jail 444 Worning County Jail 444 Worning County Jail 445 South Carolina Clemson Police Department 448 Gilliam Psychiatric Center 450 Lieber Correctional Institution 452 Myrtle Beach Low Enforcement Center 454 Tennessee Nashville Community Service Center 458 Fexas Austin County Jail 460 Beto I Unit 462 Beto I Unit 464 Bexar County Just Ender 470 Chambers County Jail 490 Chambers County Jail 490 Port Bend County Jail 490 Port Bend County Jail 490 Port Bend County		•
Trenton State Prison 346 Warren County Correctional Center 348 New Mexico Bernalillo County Detention Center (South Tower) 350 Central New Mexico Correctional Facility 352 Peninentiary of New Mexico Correctional Facility 354 Southern New Mexico Correctional Facility 358 Youth Diagnostic and Development Center— Phase III 362 New York Brooklyn Correctional Facility 364 Elmira Correctional Reception Center Food Service & Dining Facility 366 Eric County Correctional Facility 368 Eric County Holding Center 370 Federal Correctional Institution, Ray Brook 374 Kirby Forensic Psychiatric Center 376 Masten Park Secure Center 378 Morth Facility 380 Rikers Island: Modular Units 382 North Carolina Craven County Law Enforcement Center 384 Eastern Correctional Center 386 North Carolina Central Prison 388 Southern Correctional Center 390 Ohio Ashtabula County Justice Center 392 Clermont County Justice Center 392 Clermont County Justice Complex 398 Madison Correctional Institution 400 Ohio Reformatory for Women 402 Ottawa County Detention Facility 412 New Youth Diagnostic and Development Center 410 Kay County Detention Center 410 Kay County Detention Pacility 412 Lexington Assessment & Reception Center  Pennsylvania Allegheny County Jisin Correctional Center 436 Schuykill County Prison 432 Lycoming County Prison 432 Lycoming County Prison 432 Lycoming County Prison 438 State Correctional Facility a 444 Wyoming County Jiail 446 State Regional Correctional Facility a 44 Wyoming County Jiail 446 South Carolina Clemson Police Department 448 Gilliam Psychiatric Center 456 Shelby County Justice Center 458 Tennessee Nashville Community Service Center 458 Tennessee Nashville Community Service Center 456 Shelby County Justice Center 456 Shelby County Juvenile Center 456 Shelby County Juvenile Detention Center 470 Chambers County Justice		
Warren County Correctional Center 348 New Mexico Bernalillo County Detention Center (South Tower) 350 Central New Mexico Correctional Facility 352 Penitentiary of New Mexico 354 Southern New Mexico Correctional Facility 356 Western New Mexico Correctional Facility 358 Youth Diagnostic and Development Center—Phase III 362 New York Brooklyn Correctional Facility 364 Elmira Correctional Facility 368 Eric County Holding Center 370 Federal Correctional Institution, Otisville 372 North Carolina Craven County Law Enforcement Center 376 Masten Park Secure Center 378 North Facility 380 Rikers Island: Modular Units 382 North Carolina Craven County Law Enforcement Center 384 Eastern Correctional Center 390 Ohio Ashtabula County Justice Center 392 Clermont County Justice Complex 396 Logan County Jail and Office Complex 398 Madison Correctional Institution 400 Ohio Reformatory for Women 402 Ottawa County Detention Facility 412 Namilton Correctional Institution 400 Ohio Reformatory for Women 402 Ottawa County Detention Facility 412 Kay County Detention Facility 412 Exington Assessment & Reception Center  410 Blair County Jail Annex 430 Blair County Jail Annex 430 State Correctional Institution at Smithfield 440 State Regional Correctional Institution at Smithfield 440 State Reg		
New Mexico Bernalillo County Detention Center (South Tower) 350 Central New Mexico Correctional Facility 352 Penitentiary of New Mexico Correctional Facility 358 Southern New Mexico Correctional Facility 358 Western New Mexico Correctional Facility 358 Youth Diagnostic and Development Center— Phase III 362 New York Brooklyn Correctional Facility 364 Elmira Correctional Facility 368 Eric County Correctional Facility 368 Eric County Holding Center 370 Federal Correctional Institution, Otiswille 372 Federal Correctional Institution, Ray Brook 374 Kirby Forensic Psychiatric Center 376 Masten Park Secure Center 378 North Facility 380 Rikers Island: Modular Units 382 North Carolina Craven County Law Enforcement Center 384 Eastern Correctional Center 386 North Carolina Central Prison 388 Southern Correctional Center 390 Chio Ashtabula County Justice Center 392 Clermont County Justice Complex 396 Logan County Jail and Office Complex 396 Logan County Jail and Office Complex 396 Logan County Justice Center 408 Ohio Reformatory for Women 402 Ottawa County Detention Facility 404 Ross Correctional Institution 406 Wayne County Detention Facility 410 Ross Correctional Institution 406 Wayne County Detention Facility 410 Ross Correctional Institution 406 Wayne County Detention Facility 412 Eventgon Assessment & Reception Center  436 Schuylkill County Prison 438 State Correctional Institution at Smithfield 440 State Regional Correctional Facility at Mercer 442 Warren County Jail 444 Wyoming County Jail 446 South Carolina Clemson Police Department 448 Gilliam Psychiatric Center 450 Lieber Correctional Institution 452 Myrtle Beach Law Enforcement Center 454 Tennessee Rashville Community Service Center 458 Feaster County Justice Center 458 Easter County Justice Center 458 Cameron County Law Enforcement Center 470 Comal County Jail 460 Beto I Unit 462 Beaz County Justice Center 470 Comal County Jail 476 Darrington Unit 478 Diagnostic Unit 488 Eilis II Unit (Phase I and II) 482 Eayette County Detention Endity 410 Comal County Jail (E		
Bernalillo County Detention Center (South Tower) 350 Central New Mexico Correctional Facility 352 Penitentiary of New Mexico 354 Southern New Mexico Correctional Facility 356 Western New Mexico Correctional Facility 360 Youth Diagnostic and Development Center— Phase III 362 New York Brooklyn Correctional Facility 364 Elmira Correctional & Reception Center Food Service & Dining Facility 366 Erie County Correctional Facility 366 Erie County Holding Center 370 Federal Correctional Institution, Otisville 372 Federal Correctional Institution, Ray Brook 374 Kirby Forensic Psychiatric Center 376 Masten Park Secure Center 378 North Facility 380 Rikers Island: Modular Units 382 North Carolina Craven County Law Enforcement Center 384 Eastern Correctional Center 386 North Carolina Centeral Prison 388 Southern Correctional Center 390 Ohio Ashtabula County Justice Center 392 Clermont County Justice Complex 396 Logan County Jail and Office Complex 396 Logan County Jail and Office Complex 398 Madison Correctional Institution 400 Ohio Reformatory for Women 402 Ottawa County Detention Facility 404 Ross Correctional Institution 406 Wayne County Detention Facility 410 Ross Correctional Institution 406 Wayne County Detention Facility 404 Ross Correctional Institution 406 Wayne County Detention Facility 412 Lexington Assessment & Reception Center  410  Lycoming County Prison 434 Philadelphia Industrial Correctional Institution at Smithfield 440 State Reggional Correctional Institution 440 Wyoming County Jail 446 Wister Regional Correctional Institution 452 Mercer 442 Warren County Justice Center 450 Lieber Correctional Institution 452 Myrtle Beach Law Enforcement Center 456 State Regional Cornet 430 Lieber Correctional Institution 448 Gilliam Psychiatric Center	•	
Central New Mexico Correctional Facility 352 Penitentiary of New Mexico 354 Southern New Mexico Correctional Facility 356 Western New Mexico Correctional Facility 358 Youth Diagnostic and Development Center 360 Youth Diagnostic and Development Center—Phase III 362 New York Brooklyn Correctional Facility 364 Elmira Correctional Facility 364 Elmira Correctional Reception Center Food Service & Dining Facility 366 Eric County Correctional Facility 368 Eric County Holding Center 370 Federal Correctional Institution, Otisville 372 Federal Correctional Institution, Otisville 372 Federal Correctional Institution, Ray Brook 374 Kirby Forensic Psychiatric Center 376 Masten Park Secure Center 378 North Facility 380 Rikers Island: Modular Units 382 North Carolina Craven County Law Enforcement Center 384 Eastern Correctional Center 386 North Carolina Central Prison 388 Southern Correctional Center 390 Ohio Ashtabula County Justice Center 392 Clermont County Jail 394 Hamilton County Justice Complex 396 Logan County Justice Complex 396 Madison Correctional Institution 406 Wayne County Dustice Center 408 Olahoma Cleveland County Detention Facility 404 Ross Correctional Institution 406 Wayne County Detention Facility 404 Ross Correctional Institution 406 Wayne County Detention Center 410 Kay County Detention Facility 404 Cleveland County Detention Facility 404 Cleveland County Detention Facility 404 Cleveland County Detention Center 48 Reception Center 500 Fhiladelphia Industrial Correctional Institution 440 State Regional Correctional Institution 440 Wyoming County Jail 444 Wyoming County Jail 446 South Carolina Clemson Police Department 448 Gilliam Psychiatric Center 450 Lieber Correctional Institution 452 Myrtle Beach Law Enforcement Center 456 Shelby County Justice		
Central New Mexico Correctional Facility Penitentiary of New Mexico 354 Southern New Mexico Correctional Facility Western New Mexico Correctional Facility Youth Diagnostic and Development Center—Phase III 362 New York Brooklyn Correctional Facility 364 Elmira Correctional & Reception Center Food Service & Dining Facility 368 Eric County Correctional Facility 368 Eric County Holding Center 370 Federal Correctional Institution, Otisville 372 Federal Correctional Institution, Otisville 372 Federal Correctional Institution, Otisville 372 Kirby Forensic Psychiatric Center 378 Masten Park Secure Center 378 Morth Facility 380 Rikers Island: Modular Units 382 North Carolina Craven County Law Enforcement Center 384 Eastern Correctional Center 386 North Carolina Central Prison 388 Southern Correctional Institution 400 Ohio Ashtabula County Justice Center 390 Chioo Ashtabula County Justice Complex 398 Madison Correctional Institution 400 Ohio Reformatory for Women 402 Ottawa County Justice Complex 398 Madison Correctional Institution 400 Ohio Reformatory for Women 402 Ottawa County Justice Center 408 Wayne County Justice Center 408 Clabanoa Cleveland County Detention Facility 404 Ross Correctional Institution at Smithfield 440 State Regional Country Jail 444 Wyoming County Jail 444 Wyoming County Jail 446 South Carolina Clemson Police Department 448 Gilliam Psychiatric Center 450 Lieber Correctional Institution 452 Myrtle Beach Law Enforcement Center 454 Tennessee Nashville Community Service Center 458 Texas Austin County Justice Center 458 Texas Austin County Jurenile Center 466 Brazoria County Sheriff's Department Detention Center 470 Chambers County Law Enforcement Center 472 Comfield Unit 474 Comal County Justice Center 408 Diagnostic Unit 488 Federal Correctional Institution at Smithfield 440 South Carolina Center 448 Gilliam Psychiatric Center 450 Lieber Correctional Institution 452 Myrtle Beach Law Enforcement Center 456 Shelby County Justice Center 456 Shelby County Justice Center 456 Feasa Austin County Justice C		
Penitentiary of New Mexico 354 Southern New Mexico Correctional Facility 356 Western New Mexico Correctional Facility 358 Youth Diagnostic and Development Center—Phase III 362 New York Brooklyn Correctional Facility 364 Elmira Correctional Facility 368 Eric County Correctional Facility 368 Eric County Correctional Facility 368 Eric County Holding Center 370 Federal Correctional Institution, Otisville 372 Richer Secure Center 378 North Facility 380 Rikers Island: Modular Units 382 North Carolina Craven County Law Enforcement Center 384 Eastern Correctional Center 386 North Carolina Centeral Prison 388 Southern Correctional Center 390 Ohio Ashtabula County Justice Center 392 Clermont County Jail 394 Hamilton County Justice Complex 396 Logan County Justice Complex 396 Logan County Justice Complex 396 Madison Correctional Institution 406 Wayne County Detention Facility 404 Ross Correctional Institution 406 Wayne County Detention Center 410 Kay County Detention Facility 412 Lexington Assessment & Reception Center  State Regional Correctional Institution at Smithfield 440 State Regional Correctional Institution 466 Warren County Jail 444 Wyoming County Jail 446 Wyoming County Jail 446 Wyoming County Justice Center 450 Lieber Correctional Institution 452 Myrtle Beach Law Enforcement Center 450 Lieber Correctional Institution 452 Myrtle Beach Law Enforcement Center 458 Tennessee Nashville Community Service Center 458 Texas  Austin County Justice Center 458 Easter County Juvenile Center 466 Brazoria County Sheriff's Department 448 Bcilliam Psychiatric Center 450 South Carolina Clemson Police Department 448 Gilliam Psychiatric Center 450 Lieber Correctional Institution 452 Myrtle Beach Law Enforcement Center 458 Texas  Austin County Justice Center 458 Easter County Justice Police 466 Brazoria County Sheriff's Department Detention Center 470 Chambers County Law Enforcement Center		
Southern New Mexico Correctional Facility 356 Western New Mexico Correctional Facility 358 Youth Diagnostic and Development Center— Phase III 362 New York Brooklyn Correctional Facility 364 Elmira Correctional Facility 364 Elmira Correctional Facility 368 Erie County Correctional Facility 368 Erie County Holding Center 370 Federal Correctional Institution, Otisville 372 Federal Correctional Institution, Ray Brook 374 Kirby Forensic Psychiatric Center 378 Morth Facility 380 Rikers Island: Modular Units 382 North Facility 380 Rikers Island: Modular Units 382 North Carolina Centeral Prison 388 Southern Correctional Center 390 Ohio Ashtabula County Justice Center 390 Chio Ashtabula County Justice Complex 398 Madison Correctional Institution 400 Ohio Reformatory for Women 402 Ottawa County Justice Complex 398 Madison Correctional Institution 406 Wayne County Justice Center 408 Oklahoma Cleveland County Detention Facility 412 Lexington Assessment & Reception Center  State Regional Correctional Facility at Mercer 442 Waren County Jail 444 Wyoming County Jail 444 Wyoming County Jail 446 South Carolina Clemson Police Department 448 Gilliam Psychiatric Center 450 Lieber Correctional Institution 452 Myrtle Beach Law Enforcement Center 456 Shelby County Justice Center 458 Tennessee Nashville Community Service Center 458 Texas Austin County Juil 460 Beto Il Unit 462 Beto Il Unit 474 Comal County Seriff's Department Detention Center 470 Chambers County Law Enforcement Center 472 Coffield Unit 474 Comal County Jail 446 South Carolina Clemson Police Department 448 Gilliam Psychiatric Center 450 Lieber Correctional Institution 452 Myrtle Beach Law Enforcement Center 456 Shelby County Jail 446 Beto Il Unit 462 Beto Il Unit 474 Comal County Seriff's Department Detention Center 470 Chambers County Law Enforcement Center 470 Chambers County Jail 47		
Western New Mexico Correctional Facility Youth Diagnostic and Development Center Phase III 362 New York Brooklyn Correctional Facility 364 Elmira Correctional & Reception Center Food Service & Dining Facility 368 Erie County Holding Center 370 Federal Correctional Institution, Otisville Frederal Correctional Institution, Otisville Federal Correctional Institution, Otisville Masten Park Secure Center 376 Masten Park Secure Center 377 Masten Park Secure Center 378 North Facility 380 Rikers Island: Modular Units 382 North Carolina Craven County Law Enforcement Center 384 Eastern Correctional Center 386 North Carolina Center 390 Ohio Ashtabula County Justice Center 392 Clermont County Jail 394 Hamilton County Justice Complex 396 Logan County Jail and Office Complex Madison Correctional Institution 400 Ohio Reformatory for Women 402 Ottawa County Detention Facility 404 Ross Correctional Institution 406 Wayne County Detention Center 410 Kay County Detention Facility 412 Lexington Assessment & Reception Center  Merce* 442 Warren County Jail 446 South Carolina Clemson Police Department 448 Gilliam Psychiatric Center 450 Lieber Correctional Institution 452 Myrtle Beach Law Enforcement Center 456 Shelby County Justice Center 456 Shelby County Justice Center 458 Tenessee Nashville Community Service Center 456 Shelby County Justice Center 456 Beto I Unit 460 Bear County Jail 460 Bear County Juvenile Center 466 Brazoria County Detention Center 470 Chambers County Law Enforcement Center 472 Coffield Unit 474 Comal County Justice Center 472 Comal County Justice Center 473 Diagnostic Unit 488 Fort Bend County Justice Center 484 Federal Correctional Institution, 918 Federal Correctional Institution, 918 Federal Correctional Institution, 918 Federal Correctional Institution 400 Fort Bend County Jail 490 Fort Bend County Jail 498		
Youth Diagnostic and Development Center 360 Youth Diagnostic and Development Center—Phase III 362 New York Brooklyn Correctional Facility 364 Elmira Correctional & Reception Center Food Service & Dining Facility 366 Erie County Holding Center 370 Federal Correctional Institution, Otisville 372 Federal Correctional Institution, Otisville 372 Federal Correctional Institution, Ray Brook Xirby Forensic Psychiatric Center 376 Masten Park Secure Center 378 North Facility 380 Rikers Island: Modular Units 382 North Carolina Craven County Law Enforcement Center 384 Eastern Correctional Center 386 North Carolina Central Prison 388 Southern Correctional Center 390 Ohio Ashtabula County Justice Center 392 Clermont County Jail 394 Hamilton County Justice Complex 396 Madison Correctional Institution 400 Ohio Reformatory for Women 402 Ottawa County Detention Facility 404 Ross Correctional Institution 406 Wayne County Justice Center 408 Oklahoma Cleveland County Detention Facility 412 Lexington Assessment & Reception Center  Warren County Jail 444 Wyoming County Jail 446 South Carolina Clemson Police Department 448 Gilliam Psychiatric Center 450 Lieber Correctional Institution 452 Myntle Beach Law Enforcement Center 456 Shelby County Justice Center 458 Texas Austin County Jail 460 Beto I Unit 464 Bexar County Juvenile Center 470 Chambers County Law Enforcement Center 470 Chambers County Law Enforcement Center 472 Comal County Jail 476 Cameron County Jail 476 Cameron County Jail 476 Cameron County Law Enforcement Center 472 Comal County Jail 476 Darrington Unit 480 Ellis II Unit (Phase I and II) 482 Federal Correctional Institution, Bastrop 486 Ferguson Unit 488 Fort Bend County Jail (Expansion) 492 Freeport Police and Courts Building 494 Harris County Juvenile Detention Home 496 Hidalgo County Jail 498 Hunt County Criminal Justice Center 500 Jester Unit Number 3 502		
Youth Diagnostic and Development Center—Phase III 362  New York  Brooklyn Correctional Facility 364 Elmira Correctional & Reception Center Food Service & Dining Facility 366 Erie County Correctional Institution, 368 Erie County Holding Center 370 Federal Correctional Institution, Ray Brook 374 Kirby Forensic Psychiatric Center 378 Mosten Park Secure Center 378 North Facility 380 Rikers Island: Modular Units 382  North Carolina Craven County Law Enforcement Center 384 Eastern Correctional Center 386 North Carolina Central Prison 388 Southern Correctional Center 390  Ohio Ashtabula County Justice Center 392 Clermont County Justice Center 392 Clermont County Justice Complex 396 Madison Correctional Institution 400 Ohio Reformatory for Women 402 Ohio Reformatory for Women 402 Ottawa County Detention Facility 404 Ross Correctional Institution 406 Wayne County Justice Center 408  Oklahoma Clevand County Detention Center 410 Kay County Detention Facility 412 Lexington Assessment & Reception Center  Wyoming County Jail 446  South Carolina Clemson Police Department 448 Gilliam Psychiatric Center 450 Lieber Correctional Institution 452 Myrtle Beach Law Enforcement Center 454 Tennessee Nashville Community Service Center 458  Texas Austin County Jail 460 Beto I Unit 464 Bexar County Juvenile Center 470 Chambers County Law Enforcement Center 470 Comal County Jail 476 Darrington Unit 478 Diagnostic Unit 480 Ellis II Unit (Phase I and II) 482 Fayette County Detention Center 484 Federal Correctional Institution, Bastrop 486 Fort Bend County Jail 490 Fort Bend County Jail (Expansion) 492 Freeport Police and Courts Building 494 Harris County Juvenile Detention Home 496 Hidalgo County Jail 498 Hunt County Criminal Justice Center 500 Jester Unit Number 3 502		
New York Brooklyn Correctional Facility 364 Elmira Correctional & Reception Center Food Service & Dining Facility 368 Eric County Correctional Facility 368 Eric County Holding Center 370 Federal Correctional Institution, Otisville 372 Federal Correctional Institution, Ray Brook 374 Kirby Forensic Psychiatric Center 376 Masten Park Secure Center 378 Masten Park Secure Center 378 Morth Facility 380 Rikers Island: Modular Units 382 North Carolina Craven County Law Enforcement Center 384 Eastern Correctional Center 386 North Carolina Central Prison 388 Southern Correctional Center 390 Ohio Ashtabula County Justice Center 392 Clermont County Jail 394 Hamilton County Justice Complex 396 Madison Correctional Institution 400 Ohio Reformatory for Women 402 Ottawa County Detention Facility 404 Ross Correctional Institution 406 Wayne County Justice Center 408 Oklahoma Clewson Police Department 448 Gilliam Psychiatric Center 450 Lieber Correctional Institution 452 Myrtle Beach Law Enforcement Center 456 Shelby County Justice Center 458 Texas Austin County Jail 460 Bexar County Sheriff's Department Detention Center II 468 Cameron County Law Enforcement Center 470 Chambers County Detention Center 470 Coffield Unit 474 Comal County Jail 476 Darrington Unit 478 Diagnostic Unit 480 Ellis II Unit (Phase I and II) 482 Federal Correctional Institution, Bastrop 486 Ferguson Unit 488 Federal Correctional Institution, Bastrop 486 Fort Bend County Jail (Expansion) 492 Freeport Police and Courts Building 494 Harris County Juvenile Detention Home 496 Hidalgo County Jail 498 Hunt County Criminal Justice Center 500 Jester Unit Number 3 502		
Rrooklyn Correctional Facility 364 Elmira Correctional & Reception Center Food Service & Dining Facility 368 Eric County Correctional Facility 368 Eric County Holding Center 370 Federal Correctional Institution, Otisville 372 Federal Correctional Institution, Ray Brook 374 Kirby Forensic Psychiatric Center 376 Masten Park Secure Center 378 Morth Facility 380 Rikers Island: Modular Units 382 North Carolina Craven County Law Enforcement Center 384 Eastern Correctional Center 386 North Carolina Central Prison 388 North Carolina Central Prison 388 Southern Correctional Center 390 Ohio Ashtabula County Justice Center 392 Clermont County Jail 394 Hamilton County Justice Complex 396 Logan County Jail and Office Complex 398 Madison Correctional Institution 406 Ohio Reformatory for Women 402 Ottawa County Detention Facility 404 Ross Correctional Institution 406 Wayne County Justice Center 408 Oklahoma Cleveland County Detention Center 410 Kay County Detention Facility 412 Lexington Assessment & Reception Center  Celmson Police Department 448 Gilliam Psychiatric Center 450 Lieber Correctional Institution 452 Myrtle Beach Law Enforcement Center 456 Shelby County Justice Center 458 Texas Austin County Jail 460 Bexar County Sheriff's Department Detention Center II 468 Cameron County Law Enforcement Center 472 Coffield Unit 474 Comal County Jail 476 Darrington Unit 478 Diagnostic Unit 480 Ellis II Unit (Phase I and II) 482 Federal Correctional Institution, Bastrop 486 Ferguson Unit 488 Federal Correctional Institution, Bastrop 486 Ferguson Unit 489 Fort Bend County Jail (Expansion) 492 Freeport Police and Courts Building 494 Harris County Juvenile Center 500 Jester Unit Number 3 502		
Elmira Correctional & Reception Center Food Service & Dining Facility 366 Erie County Correctional Facility 368 Erie County Holding Center 370 Federal Correctional Institution, Otisville 372 Federal Correctional Institution, Ray Brook 374 Kirby Forensic Psychiatric Center 376 Masten Park Secure Center 378 North Facility 380 Rikers Island: Modular Units 382 North Carolina Craven County Law Enforcement Center 384 Eastern Correctional Center 386 North Carolina Center 390 Ohio Ashtabula County Justice Center 392 Clermont County Justice Center 392 Clermont County Jail 394 Hamilton County Justice Complex 396 Logan County Jail 394 Hamilton County Justice Complex 398 Madison Correctional Institution 400 Ohio Reformatory for Women 402 Ottawa County Detention Facility 404 Ross Correctional Institution 406 Wayne County Justice Center 408 Oklahoma Cleveland County Detention Center 410 Kay County Detention Center 410 Kay County Detention Facility 412 Lexington Assessment & Reception Center	New York	
Center Food Service & Dining Facility 366 Erie County Correctional Facility 368 Erie County Holding Center 370 Federal Correctional Institution, Otisville 372 Federal Correctional Institution, Ray Brook 374 Kirby Forensic Psychiatric Center 376 Masten Park Secure Center 378 North Facility 380 Rikers Island: Modular Units 382 North Carolina Craven County Law Enforcement Center 384 Eastern Correctional Center 386 North Carolina Central Prison 388 Southern Correctional Center 390 Ohio Ashtabula County Justice Center 392 Clermont County Jail 394 Hamilton County Justice Complex 396 Logan County Jail and Office Complex 398 Madison Correctional Institution 400 Ohio Reformatory for Women 402 Ottawa County Detention Facility 404 Ross Correctional Institution 406 Wayne County Justice Center 408 Oklahoma Cleveland County Detention Center 410 Kay County Detention Facility 412 Lexington Assessment & Reception Center	Brooklyn Correctional Facility 364	
Eric County Correctional Facility 368 Eric County Holding Center 370 Federal Correctional Institution, Ray Brook 374 Kirby Forensic Psychiatric Center 376 Masten Park Secure Center 378 North Facility 380 Rikers Island: Modular Units 382 North Carolina Craven County Law Enforcement Center 384 Eastern Correctional Center 386 North Carolina Central Prison 388 Southern Correctional Center 390 Ohio Ashtabula County Justice Center 392 Clermont County Jail 394 Hamilton County Justice Complex 396 Logan County Jail and Office Complex 398 Madisson Correctional Institution 400 Ohio Reformatory for Women 402 Ottawa County Detention Facility 404 Ross Correctional Institution 406 Wayne County Justice Center 408 Oklahoma Cleveland County Detention Center 410 Kay County Assessment & Reception Center		
Eric County Holding Center 370 Federal Correctional Institution, Otisville 372 Federal Correctional Institution, Ray Brook 374 Kirby Forensic Psychiatric Center 376 Masten Park Secure Center 378 North Facility 380 Rikers Island: Modular Units 382 North Carolina Craven County Law Enforcement Center 384 Eastern Correctional Center 386 North Carolina Central Prison 388 Southern Correctional Center 390 Ohio Ashtabula County Justice Center 392 Clermont County Justice Complex 396 Logan County Jail 394 Hamilton County Justice Complex 398 Madison Correctional Institution 400 Ohio Reformatory for Women 402 Ottawa County Detention Facility 404 Ross Correctional Institution 406 Wayne County Justice Center 410 Kay County Detention Facility 412 Lexington Assessment & Reception Center  Tennessee Nashville Community Service Center 458 Shelby County Justice Center 458  Texas Austin County Jail 460 Beto I Unit 462 Beto II Unit 468 Cameron County betention Center 470 Comal County Jail 476 Darrington		
Federal Correctional Institution, Otisville 372 Federal Correctional Institution, Ray Brook 374 Kirby Forensic Psychiatric Center 376 Masten Park Secure Center 378 North Facility 380 Rikers Island: Modular Units 382 North Carolina Craven County Law Enforcement Center 384 Eastern Correctional Center 386 North Carolina Central Prison 388 Southern Correctional Center 390 Ohio Ashtabula County Justice Center 392 Clermont County Jail 394 Hamilton County Justice Complex 396 Logan County Justice Complex 396 Madison Correctional Institution 400 Ohio Reformatory for Women 402 Ottawa County Detention Facility 404 Ross Correctional Institution 406 Wayne County Justice Center 410 Kay County Detention Facility 412 Lexington Assessment & Reception Center  Nashville Community Service Center 458 Shelby County Justice Center 458 Texas Austin County Jail 460 Beto I Unit 462 Beto II Unit 464 Bexar County Juvenile Center 466 Brazoria County Sheriff's Department Detention Center II 468 Cameron County Law Enforcement Center 472 Coffield Unit 474 Comal County Jail 476 Darrington Unit 478 Diagnostic Unit 480 Ellis II Unit (Phase I and II) 482 Fayette County Detention Center 484 Federal Correctional Institution, Bastrop 486 Ferguson Unit 488 Fort Bend County Jail (Expansion) 492 Freeport Police and Courts Building 494 Harris County Juvenile Detention Home 496 Hidalgo County Juil 498 Hunt County Criminal Justice Center 500 Jester Unit Number 3 502		•
Federal Correctional Institution, Ray Brook Kirby Forensic Psychiatric Center 376 Masten Park Secure Center 378 North Facility 380 Rikers Island: Modular Units 382 North Carolina Craven County Law Enforcement Center 384 Eastern Correctional Center 386 North Carolina Central Prison 388 Southern Correctional Center 390 Ohio Ashtabula County Justice Center 392 Clermont County Jail 394 Hamilton County Justice Complex 396 Logan County Justice Complex 398 Madison Correctional Institution 400 Ohio Reformatory for Women 402 Ohio Reformatory for Women 402 Ohio Reformatory Detention Facility 404 Ross Correctional Institution 406 Wayne County Justice Center 408 Oklahoma Cleveland County Detention Center 410 Kay County Detention Facility 412 Lexington Assessment & Reception Center  374  Austin County Jail 460 Bexar County Juvenile Center 466 Brazoria County Juvenile Center 466 Brazoria County Sheriff's Department Detention Center II 468 Cameron County Detention Center 470 Coffield Unit 474 Comal County Jail 476 Darrington Unit 478 Diagnostic Unit 480 Ellis II Unit (Phase I and II) 482 Fayette County Detention Center 484 Federal Correctional Institution, Bastrop 486 Fort Bend County Jail (Expansion) 492 Freeport Police and Courts Building 494 Harris County Juvenile Detention Home 496 Hidalgo County Jail 498 Hunt County Criminal Justice Center 500 Jester Unit Number 3 502		
Kirby Forensic Psychiatric Center 376 Masten Park Secure Center 378 North Facility 380 Rikers Island: Modular Units 382 North Carolina Craven County Law Enforcement Center 384 Eastern Correctional Center 386 North Carolina Central Prison 388 Southern Correctional Center 390 Ohio Ashtabula County Justice Center 392 Clermont County Jail 394 Hamilton County Justice Complex 396 Logan County Jail and Office Complex 398 Madison Correctional Institution 400 Ohio Reformatory for Women 402 Ottawa County Detention Facility 404 Ross Correctional Institution 406 Wayne County Justice Center 408 Oklahoma Cleveland County Detention Center 410 Kay County Detention Facility 412 Lexington Assessment & Reception Center  Texas Austin County Jail 460 Beto I Unit 462 Beto II Unit 462 Beto II Unit 464 Bexar County Juvenile Center 466 Brazoria County Sheriff's Department Detention Center II 468 Cameron County Law Enforcement Center 470 Chambers County Law Enforcement Center 472 Comal County Jail 476 Darrington Unit 478 Diagnostic Unit 480 Ellis II Unit (Phase I and II) 482 Fayette County Detention Center 484 Federal Correctional Institution, Bastrop 486 Ferguson Unit 488 Fort Bend County Jail (Expansion) 492 Freeport Police and Courts Building 494 Harris County Juvenile Detention Home 496 Hidalgo County Jail 498 Hunt County Criminal Justice Center 500 Jester Unit Number 3 502		
Masten Park Secure Center 378 North Facility 380 Rikers Island: Modular Units 382  North Carolina Craven County Law Enforcement Center 384 Eastern Correctional Center 386 North Carolina Central Prison 388 Southern Correctional Center 390  Ohio Ashtabula County Justice Center 392 Clermont County Jail 394 Hamilton County Justice Complex 396 Logan County Jail and Office Complex 398 Madison Correctional Institution 400 Ohio Reformatory for Women 402 Ohio Ross Correctional Institution 406 Wayne County Justice Center 408  Oklahoma Cleveland County Detention Center 410 Kay County Detention Facility 412 Lexington Assessment & Reception Center  Austin County Jail 460 Beto I Unit 462 Beto I Unit 464 Bexar County Juvenile Center 466 Brazoria County Juvenile Center 466 Brazoria County Sheriff's Department Detention Center II 468 Cameron County Detention Center 470 Chambers County Law Enforcement Center 472 Comal County Jail 474 Comal County Jail 476 Darrington Unit 478 Diagnostic Unit 480 Ellis II Unit (Phase I and II) 482 Fayette County Detention Center 484 Federal Correctional Institution, Bastrop 486 Ferguson Unit 488 Fort Bend County Jail (Expansion) 492 Freeport Police and Courts Building 494 Harris County Juvenile Center 500 Leaven County Detention Facility 412 Lexington Assessment & Reception Center		•
North Facility 380 Rikers Island: Modular Units 382  North Carolina Craven County Law Enforcement Center 384 Eastern Correctional Center 386 North Carolina Central Prison 388 Southern Correctional Center 390  Ohio Ashtabula County Justice Center 392 Clermont County Jail 394 Hamilton County Justice Complex 396 Logan County Jail and Office Complex 398 Madison Correctional Institution 400 Ohio Reformatory for Women 402 Ottawa County Detention Facility 404 Ross Correctional Institution 406 Wayne County Justice Center 408  Oklahoma Cleveland County Detention Center 410 Kay County Detention Facility 412 Lexington Assessment & Reception Center  Beto I Unit 462 Beto II Unit 464 Bexar County Juvenile Center 466  Bexar County Juvenile Center 466  Cameron County Juvenile Center 470 Chambers County Law Enforcement Center 472 Comal County Law Enforcement Center 472 Comal County Jail 476 Darrington Unit 478 Diagnostic Unit 480 Ellis II Unit (Phase I and II) 482 Fayette County Detention Center 484 Federal Correctional Institution, Bastrop 486 Ferguson Unit 488 Fort Bend County Jail 490 Fort Bend County Jail (Expansion) 492 Freeport Police and Courts Building 494 Harris County Juvenile Detention Home 496 Hidalgo County Jail 498 Hunt County Criminal Justice Center 500 Jester Unit Number 3 502		
Rikers Island: Modular Units 382  North Carolina Craven County Law Enforcement Center 384 Eastern Correctional Center 386 North Carolina Central Prison 388 Southern Correctional Center 390  Ohio Ashtabula County Justice Center 392 Clermont County Jail 394 Hamilton County Jail and Office Complex 396 Madison Correctional Institution 400 Ohio Reformatory for Women 402 Ottawa County Detention Facility 404 Ross Correctional Institution 406 Wayne County Justice Center 408  Oklahoma Cleveland County Detention Center 410 Kay County Detention Facility 412 Lexington Assessment & Reception Center  384 Beto II Unit 464 Bexar County Juvenile Center 466  Brazoria County Juvenile Center 470 Camter II 468 Cameron County Detention Center 470 Chambers County Law Enforcement Center 472 Comal County Jail 476 Darrington Unit 478 Diagnostic Unit 480 Ellis II Unit (Phase I and II) 482 Fayette County Detention Center 484 Federal Correctional Institution, Bastrop 486 Ferguson Unit 488 Fort Bend County Jail 490 Fort Bend County Jail (Expansion) 492 Freeport Police and Courts Building 494 Harris County Juvenile Detention Home 496 Hidalgo County Jail 498 Hunt County Criminal Justice Center 500 Jester Unit Number 3 502		Austin County Jail 460
North Carolina Craven County Law Enforcement Center 384 Eastern Correctional Center 386 North Carolina Central Prison 388 Southern Correctional Center 390 Ohio Ashtabula County Justice Center 392 Clermont County Jail 394 Hamilton County Jail 394 Hamilton County Jail and Office Complex 398 Madison Correctional Institution 400 Ohio Reformatory for Women 402 Ottawa County Detention Facility 404 Ross Correctional Institution 406 Wayne County Justice Center 408 Oklahoma Cleveland County Detention Center 410 Kay County Detention Facility 412 Lexington Assessment & Reception Center  384 Brazoria County Juvenile Center 470 Chambers County Law Enforcement Center 470 Chambers County Law Enforcement Center 472 Coffield Unit 474 Comal County Jail 476 Darrington Unit 478 Diagnostic Unit 480 Ellis II Unit (Phase I and II) 482 Federal Correctional Institution, Bastrop 486 Ferguson Unit 488 Fort Bend County Jail 490 Fort Bend County Jail (Expansion) 492 Freeport Police and Courts Building 494 Harris County Juvenile Detention Home 496 Hidalgo County Jail 498 Hunt County Criminal Justice Center 500 Lexington Assessment & Reception Center		
Craven County Law Enforcement Center 384 Eastern Correctional Center 386 North Carolina Central Prison 388 Southern Correctional Center 390  Ohio Ashtabula County Justice Center 392 Clermont County Jail 394 Hamilton County Justice Complex 396 Logan County Jail and Office Complex 398 Madison Correctional Institution 400 Ohio Reformatory for Women 402 Ottawa County Detention Facility 404 Ross Correctional Institution 406 Wayne County Justice Center 408  Oklahoma Cleveland County Detention Facility 412 Lexington Assessment & Reception Center  384 Brazoria County Sheriff's Department Detention Center II 468 Cameron County Detention Center 470 Chambers County Law Enforcement Center 472 Coffield Unit 474 Comal County Jail 476 Darrington Unit 478 Diagnostic Unit 480 Ellis II Unit (Phase I and II) 482 Fayette County Detention Center 484 Federal Correctional Institution, Bastrop 486 Ferguson Unit 488 Fort Bend County Jail 490 Fort Bend County Jail (Expansion) 492 Freeport Police and Courts Building 494 Harris County Juvenile Detention Home 496 Hidalgo County Jail 498 Hunt County Criminal Justice Center 500 Jester Unit Number 3 502		
Eastern Correctional Center 386 North Carolina Central Prison 388 Southern Correctional Center 390 Chambers County Law Enforcement Center 472 Coffield Unit 474 Comal County Jail 476 Darrington Unit 478 Diagnostic Unit 480 Ellis II Unit (Phase I and II) 482 Fayette County Detention Center 484 Federal Correctional Institution, Bastrop 486 Ohio Reformatory for Women 402 Ottawa County Detention Facility 404 Ross Correctional Institution 406 Wayne County Justice Center 408 Oklahoma Cleveland County Detention Center 410 Kay County Detention Facility 412 Lexington Assessment & Reception Center  Center II 468 Cameron County Detention Center 470 Chambers County Law Enforcement Center 472 Coffield Unit 474 Comal County Jail 476 Darrington Unit 478 Diagnostic Unit 480 Ellis II Unit (Phase I and II) 482 Fayette County Detention Center 484 Federal Correctional Institution, Bastrop 486 Fort Bend County Jail 490 Fort Bend County Jail (Expansion) 492 Freeport Police and Courts Building 494 Harris County Juvenile Detention Home 496 Hidalgo County Jail 498 Hunt County Criminal Justice Center 500 Jester Unit Number 3 502		
North Carolina Central Prison 388 Southern Correctional Center 390  Ohio Ashtabula County Justice Center 392 Clermont County Jail 394 Hamilton County Justice Complex 396 Logan County Jail and Office Complex 398 Madison Correctional Institution 400 Ohio Reformatory for Women 402 Ottawa County Detention Facility 404 Ross Correctional Institution 406 Wayne County Justice Center 408  Oklahoma Cleveland County Detention Center 410 Kay County Detention Facility 412 Lexington Assessment & Reception Center  Cameron County Detention Center 470 Chambers County Law Enforcement Center 472 Comal County Law Enforcement Center 472 Comal County Jail 476 Darrington Unit 478 Diagnostic Unit 480 Ellis II Unit (Phase I and II) 482 Fayette County Detention Center 484 Federal Correctional Institution, Bastrop 486 Fort Bend County Jail 490 Fort Bend County Jail 490 Fort Bend County Jail (Expansion) 492 Freeport Police and Courts Building 494 Harris County Juvenile Detention Home 496 Hidalgo County Jail 498 Hunt County Criminal Justice Center 500 Jester Unit Number 3 502		
Southern Correctional Center 390  Ohio  Ashtabula County Justice Center 392 Clermont County Jail 394 Hamilton County Justice Complex 396 Logan County Jail and Office Complex 398 Madison Correctional Institution 400 Ohio Reformatory for Women 402 Ottawa County Detention Facility 404 Ross Correctional Institution 406 Wayne County Justice Center 408  Oklahoma Cleveland County Detention Center 410 Kay County Detention Facility 412 Lexington Assessment & Reception Center  Coffield Unit 474 Comal County Law Enforcement Center 472 Coffield Unit 474 Comal County Jail 476 Darrington Unit 480 Ellis II Unit (Phase I and II) 482 Fayette County Detention Center 484 Federal Correctional Institution, Bastrop 486 Ferguson Unit 488 Fort Bend County Jail 490 Fort Bend County Jail (Expansion) 492 Freeport Police and Courts Building 494 Harris County Juvenile Detention Home 496 Hidalgo County Jail 498 Hunt County Criminal Justice Center 500 Jester Unit Number 3 502		
Ohio Ashtabula County Justice Center 392 Clermont County Jail 394 Hamilton County Justice Complex 396 Logan County Jail and Office Complex 398 Madison Correctional Institution 400 Ohio Reformatory for Women 402 Ottawa County Detention Facility 404 Ross Correctional Institution 406 Wayne County Justice Center 408  Oklahoma Cleveland County Detention Center 410 Kay County Detention Facility 412 Lexington Assessment & Reception Center  Coffield Unit 474 Comal County Jail 476 Darrington Unit 478 Diagnostic Unit 480 Ellis II Unit (Phase I and II) 482 Fayette County Detention Center 484 Federal Correctional Institution, Bastrop 486 Ferguson Unit 488 Fort Bend County Jail 490 Fort Bend County Jail (Expansion) 492 Freeport Police and Courts Building 494 Harris County Juvenile Detention Home 496 Hidalgo County Jail 498 Hunt County Criminal Justice Center 500 Jester Unit Number 3 502		
Ashtabula County Justice Center 392 Clermont County Jail 394 Hamilton County Justice Complex 396 Logan County Jail and Office Complex 398 Madison Correctional Institution 400 Ohio Reformatory for Women 402 Ottawa County Detention Facility 404 Ross Correctional Institution 406 Wayne County Justice Center 408  Oklahoma Cleveland County Detention Center 410 Kay County Detention Facility 412 Lexington Assessment & Reception Center  Comat County Jail 476 Darrington Unit 478 Diagnostic Unit 480 Ellis II Unit (Phase I and II) 482 Fayette County Detention Center 484 Federal Correctional Institution, Bastrop 486 Ferguson Unit 488 Fort Bend County Jail 490 Fort Bend County Jail (Expansion) 492 Freeport Police and Courts Building 494 Harris County Juvenile Detention Home 496 Hidalgo County Jail 498 Hunt County Criminal Justice Center 500 Jester Unit Number 3 502		
Clermont County Jail 394 Hamilton County Justice Complex 396 Logan County Jail and Office Complex 398 Madison Correctional Institution 400 Ohio Reformatory for Women 402 Ottawa County Detention Facility 404 Ross Correctional Institution 406 Wayne County Justice Center 408 Oklahoma Cleveland County Detention Facility 412 Lexington Cint 478 Diagnostic Unit 480 Ellis II Unit (Phase I and II) 482 Fayette County Detention Center 484 Federal Correctional Institution, Bastrop 486 Ferguson Unit 488 Fort Bend County Jail 490 Fort Bend County Jail (Expansion) 492 Freeport Police and Courts Building 494 Harris County Juvenile Detention Home 496 Hidalgo County Jail 498 Hunt County Criminal Justice Center 500 Jester Unit Number 3 502		Comal County Jail 476
Hamilton County Justice Complex 396 Logan County Jail and Office Complex 398 Madison Correctional Institution 400 Ohio Reformatory for Women 402 Ottawa County Detention Facility 404 Ross Correctional Institution 406 Wayne County Justice Center 408 Oklahoma Cleveland County Detention Facility 412 Lexington Assessment & Reception Center  398 Ellis II Unit (Phase I and II) 482 Fayette County Detention Center 484 Federal Correctional Institution, Bastrop 486 Ferguson Unit 488 Fort Bend County Jail 490 Fort Bend County Jail (Expansion) 492 Freeport Police and Courts Building 494 Hidalgo County Juvenile Detention Home 496 Hidalgo County Jail 498 Hunt County Criminal Justice Center 500 Jester Unit Number 3 502		
Logan County Jail and Office Complex 398 Madison Correctional Institution 400 Ohio Reformatory for Women 402 Ottawa County Detention Facility 404 Ross Correctional Institution 406 Wayne County Justice Center 408 Oklahoma Cleveland County Detention Facility 412 Lexington Assessment & Reception Center  398 Fayette County Detention Center 484 Federal Correctional Institution, Bastrop 486 Ferguson Unit 488 Fort Bend County Jail 490 Fort Bend County Jail (Expansion) 492 Freeport Police and Courts Building 494 Hidalgo County Juvenile Detention Home 496 Hidalgo County Jail 498 Hunt County Criminal Justice Center 500 Jester Unit Number 3 502		
Madison Correctional Institution 400 Ohio Reformatory for Women 402 Ottawa County Detention Facility 404 Ross Correctional Institution 406 Wayne County Justice Center 408 Oklahoma Cleveland County Detention Facility 412 Lexington Assessment & Reception Center  A00 Federal Correctional Institution, Bastrop 486 Ferguson Unit 488 Fort Bend County Jail 490 Fort Bend County Jail (Expansion) 492 Freeport Police and Courts Building 494 Hidalgo County Juvenile Detention Home 496 Hidalgo County Jail 498 Hunt County Criminal Justice Center 500 Jester Unit Number 3 502		
Ohio Reformatory for Women 402 Ottawa County Detention Facility 404 Ross Correctional Institution 406 Wayne County Justice Center 408  Oklahoma Cleveland County Detention Center 410 Kay County Detention Facility 412 Lexington Assessment & Reception Center  Pedetal Coffectional Institution, Bastrop 480 Ferguson Unit 488 Fort Bend County Jail (Expansion) 492 Freeport Police and Courts Building 494 Harris County Juvenile Detention Home 496 Hidalgo County Jail 498 Hunt County Criminal Justice Center 500 Jester Unit Number 3 502	<u> </u>	
Ottawa County Detention Facility 404 Ross Correctional Institution 406 Wayne County Justice Center 408  Oklahoma Cleveland County Detention Center 410 Kay County Detention Facility 412 Lexington Assessment & Reception Center  Ottawa County Detention Facility 404 Fort Bend County Jail 490 Fort Bend County Jail (Expansion) 492 Freeport Police and Courts Building 494 Harris County Juvenile Detention Home 496 Hidalgo County Jail 498 Hunt County Criminal Justice Center 500 Jester Unit Number 3 502		
Ross Correctional Institution 406 Wayne County Justice Center 408  Oklahoma Cleveland County Detention Center 410 Kay County Detention Facility 412 Lexington Assessment & Reception Center  Ross Correctional Institution 406 Fort Bend County Jail (Expansion) 492 Freeport Police and Courts Building 494 Harris County Juvenile Detention Home 496 Hidalgo County Jail 498 Hunt County Criminal Justice Center 500 Jester Unit Number 3 502		
Wayne County Justice Center 408  Oklahoma  Cleveland County Detention Center 410  Kay County Detention Facility 412  Lexington Assessment & Reception Center  Freeport Police and Courts Building 494  Harris County Juvenile Detention Home 496  Hidalgo County Jail 498  Hunt County Criminal Justice Center 500  Jester Unit Number 3 502		
Oklahoma  Cleveland County Detention Center 410  Kay County Detention Facility 412  Lexington Assessment & Reception Center  Harris County Juvenile Detention Home 496  Hidalgo County Jail 498  Hunt County Criminal Justice Center 500  Jester Unit Number 3 502		
Cleveland County Detention Center 410  Kay County Detention Facility 412  Lexington Assessment & Reception Center  Hidalgo County Jail 498  Hunt County Criminal Justice Center 500  Jester Unit Number 3 502	Oklahoma	
Kay County Detention Facility 412 Lexington Assessment & Reception Center  Hunt County Criminal Justice Center 500  Jester Unit Number 3 502		
Lexington Assessment & Reception Center Jester Unit Number 3 502		
(Madrion)	(Addition) 414	Katy Police Department 504

## Contents (continued)

Lew Sterrett Justice Center 506 Liberty County Jail 508 Missouri City Police Department 510 Mountain View Unit 512 Orange County Jail 514 Pearland Public Safety Building 516 San Patricio County Sheriff's Department 518 Smith County Jail 520 Starr County Jail 522 TDC Hospital at Galveston 524 Victoria County Jail 526 Wallace Pack Unit I 528 Wallace Pack Unit II 530 Westside Police Area Command Station 532 Utah Orange Street Community Correctional Center 534 Uintah County Jail 536 Young Adult Correctional Facility 538 Vermont Northwest State Correctional Facility 540 St. Johnsbury Community Correctional Center 542	Pittsylvania County Jail 550 Roanoke City Jail 552  Washington Benton County Justice Center 554 Forks City Jail 556 Jefferson County Correctional Facility 558 Thurston County Corrections Facility 560 Twin Rivers Corrections Center 562 Washington Corrections Center Intensive Management Unit 564 Whitman County Correctional Facility 566  West Virginia Ohio County Correctional Center 568  Wisconsin Burnett County Government Center 570 Columbia Correctional Institution 572 Oshkosh Correctional Institution 574 Rusk County Law Enforcement Facility 576  Appendix A ACA standards for adult correctional institutions and
Virginia	local detention facilities 579
Alexandria Detention Center 544 Augusta County Jail 546	Appendix B
Fairfax County Adult Detention Center and Pre- Release Center 548	Reference: Architects and construction managers 589

**Section I** 

Introduction

Policy research

NIJ survey

## Introduction

# The National Directory of Corrections Construction contains:

- 262 correctional facilities
- 239 architectural and construction manager firms
- 145 jail projects
- 99 prison projects
- Facilities from 44 States

## The projects include:

- 96,178 inmates
- 34,256 employees in correctional facilities
- \$3,297,051,430 in total construction costs
- \$980,613,870 in annual operating budgets

The National Directory of Corrections Construction has been developed by the National Institute of Justice to assist State, local, and Federal officials who are planning to build correctional facilities. The directory is a key element of a new Federal program that promotes exchange of information about building jails and prisons more cost effectively and in a timely fashion.

The first of its kind, the directory is a reference guide to correctional institutions built after 1978. It is based on a survey conducted by the National Institute of Justice and represents a comprehensive sample of projects built since that year. Never before has so much information been assembled to assist corrections agencies with construction of jails and prisons.

Officials embarking upon construction of correctional facilities now have a comprehensive guidebook to help them along the way, a volume that contains the lessons learned by officials who have already faced this challenge. Readers will find success stories ready to be replicated and colleagues eager to share their experiences. By referring to the directory, readers can learn about facilities where new technologies and efficient construction methods have been employed to save time and money. In this way, jurisdictions can avoid "reinventing the wheel," a problem that has too often characterized the process of building jails and prisons. Through the directory, officials who are planning construction can review data gathered about comparable projects and contact experts who have important information concerning already completed facilities.

As the title "directory" implies, this volume includes projects accepted without evaluation. The directory includes both positive and negative experiences—examples of what to do and what not to do.

The National Directory of Corrections Construction is a catalog of designs and resources. Readers can easily locate facilities that may be comparable to their own needs. With the construction cost index, readers may then adjust the costs to match those prevailing in their own jurisdiction at the current time. Following these simple steps, it is possible to estimate the approximate time and cost requirements for construction of the same or similar facility at the reader's location. When used in this way, the directory can be a valuable tool for planners, budget analysts, and corrections administrators. For every design, the responsible architect has been identified, and information is provided on how to contact officials at the site.

Although it is a highly complex undertaking, the successful transfer of design concepts has been demonstrated by several jurisdictions. In the State of South Carolina, officials decided to utilize the design of the Federal Correctional Institution at Phoenix, Arizona, as a model for up to five prisons in their State. The Phoenix institution was shown on the cover of the first edition of the directory, as it represents the purpose of NIJ efforts—to transfer proven methods from one agency to another.

The most recent stage of development is represented by the cover of this edition. The new Federal Correctional Institution at Marianna, Florida, illustrates current design concepts adopted by the Federal Bureau of Prisons. While incorporating the innovations illustrated by the Phoenix design, the new project offers an alternative approach and exhibits complementary design concepts. Like its counterpart in Phoenix, the new institution at Marianna may serve as a model for other agencies to consider.

## **Construction Information Exchange**

The National Directory of Corrections Construction is an element of the Construction Information Exchange, a program recently initiated by the National Institute of Justice. Through the Construction Information Exchange, agencies planning to build, remodel, or expand correctional facilities may contact other jurisdictions that have solved comparable problems and can exchange detailed information about the facilities and current plans. In this way, project management and building technologies can be transferred from agency to agency.

#### **Construction data base**

The heart of the National Institute of Justice program is the construction data base, a computerized library that permits State, local, and Federal officials to share

lessons learned from recent jail and prison construction projects. Information for the directory has been drawn from the comprehensive files already contained in the construction data base. Updates of the directory will be drawn from the expanding data base to ensure availability of the most current information on recently completed jails and prisons.

The data base serves criminal justice practitioners in several ways by offering services that are tailored to their individual interests and needs. A sheriff, for example, who is planning to build a combined jail and court facility may contact the Construction Information Exchange to obtain a special search of the data base describing facilities of this type. The sheriff will receive a computer printout providing a wealth of detail on projects like the planned facility, and persons to contact for further information. In addition, many of the architects responsible for designing facilities included in the data base have agreed to provide a package of descriptive materials on their projects.

## **Construction Bulletins**

Another element in the program is a publication series, the NIJ Construction Bulletins. These special reports provide indepth case studies of selected projects, giving State and local officials a closer look at noteworthy

facilities. The Construction Bulletins explain in more detail selected projects for which officials have reported substantial time and cost savings in constructing correctional facilities. They report on innovative features of new jails and prisons, such as new techniques of corrections planning and progressive methods of construction. Each bulletin gives concise details on individual projects that demonstrate particularly helpful approaches. Bulletins can be obtained by contacting the Construction Information Exchange.

Those jurisdictions whose projects have been published in the *Construction Bulletins* have agreed to provide more detailed information on the design and building of their facilities and to host site visits of their facilities by officials currently involved in new construction projects.

For more information on the Construction Information Exchange, see the inside back cover of this directory.

## Policy research

Research at the National Institute of Justice is aimed at reducing crime and improving the criminal justice system. The National Directory of Corrections Construction is an important part of this research, because it documents the Nation's response to a critical area of need—expansion of jail and prison capacity. Although much has been written about crowding in correctional facilities and the need to improve our Nation's jails and prisons, this volume represents the first compendium of information on what has actually been built.

Extensive efforts have been made to gather detailed quantitative information, and virtually every aspect of correctional facility construction has been systematically compiled and reported. Construction cost indexes have been developed to adjust cost data for selected dates and geographic areas, thereby permitting comparisons among different facilities. Every step has been taken to ensure the accuracy and comparability of the data. These measures make it possible for the directory to serve as a reference for researchers as well as officials who are planning new facilities.

## The decision to build

It is perhaps the most difficult decision for State and local corrections agencies—to build or not to build? A commitment to construction is rarely the first response to crowded conditions. It may follow years of struggle and agonizing debate. Only after each alternative has been exhausted and funds have been raised will officials finally commence the difficult process of design and construction.

Once the decision to build has been made, officials must then consider many critical questions that will determine what their new jail or prison is to become. The National Institute of Justice has created this directory to help answer those questions, by referring officials to the lessons learned from completed correctional facilities across the Nation.

The National Directory of Corrections Construction provides the information that officials need to know before they begin construction, not after—when it is too late. Using the directory, State and local officials may find answers to the following questions:

- What is the likely cost of construction for a correctional facility of the type we have planned?
- How many staff will be required and what will it cost to operate the new facility?
- Should we build a new institution or an addition to our existing facility?
- How do institutions with dormitories compare to those with single occupancy cells?

- Have other jurisdictions had favorable experience with prefabrication and modular construction?
- Could we have both courts and jails in the same building?
- Who should I call to obtain information concerning "fast track" and construction management?
- How long should it take to build the type of prison our State has in mind?
- Which agencies have had experience with electronic security perimeters?
- Who should I call to ask about construction costs for "new generation" jails?
- Should we expect higher costs or special problems with a high-rise facility?
- Which jurisdictions have used lease-purchase to pay for jail and prison construction?

## **Highlights**

Each profile page describes how an individual jurisdiction has addressed these issues. Although research is just beginning, preliminary findings may give readers a glimpse of the priorities established by those who have completed new jail or prison facilities.

Costs of construction. While great strides have been made to reduce the costs of corrections construction, many projects were very costly to build. The directory illustrates dramatic contrasts, as costs range from a low of \$2,048 to a high of \$149,425 per inmate. For minimum security facilities, the average cost per prisoner was \$22,263; medium security projects were \$36,430 per bed; and maximum security construction was \$39,695 per inmate.

Types of construction represent important determinants of cost. For example, new institutions are almost always more costly than additions to existing facilities. The average cost for an addition to an existing facility was \$32,102 per inmate, while the average cost for a new, independent facility was \$37,367 per inmate. To ensure valid comparisons, the directory is indexed by category of construction, and the actual cost per square foot is also shown for each project.

**Design options.** The directory displays a wide variety of alternative designs. For example, "new generation" concepts are evident throughout this volume. Direct

<sup>1.</sup> This range excludes construction costs for prison hospitals, which are as high as \$270,762 per inmate. However, the following averages do include costs for all facilities in the directory.

<sup>2.</sup> Because most facilities have a combination of two or three security levels, only facilities with greater than 50 percent of a particular level (maximum, medium, or minimum) were used for these calculations.

supervision management was reported in 23 percent of the institutions. At the same time, traditional approaches may be found in the majority of facilities, with linear designs representing 33 percent of the projects.

Both innovation and compromise have been employed to bring about greater economy. Many jurisdictions have opted for multiple occupancy cells and dormitories over the more costly design of single person cells. New inmate management concepts have produced designs with more economical features. Sixtynine projects utilized less costly building materials and security hardware and 93 facilities selected commercial grade fixtures as an alternative to institutional steel.

**Building methods.** Progressive building techniques are illustrated throughout this volume. In order to accelerate construction schedules, architects and contractors have utilized a number of alternatives to conventional building methods. When asked how time was saved in the construction process, 65 respondents cited prefabrication methods as an explanation for their positive results.

Use of inmate labor is viewed as a method for reducing construction costs. While the nature and extent of inmate participation varied widely, 33 projects utilized inmate labor.

Conventional building methods remain dominant, as the majority of jails and prisons, 178 out of 262, were built primarily with concrete block.

Construction process. Officials at all levels of government are searching for new ways to conduct the process of construction, and this volume documents the innovative techniques now being tested in these highly specialized public works projects. Although well established in the private sector, several of the procedures are new to corrections.

Construction management services were employed in 19 percent of the projects, and in 38 percent of the projects that cost more than \$10 million. Likewise, "fast track" construction was reported for 38 of the facilities and noted as an explanation of reduction in construction time.

**Future needs.** The directory offers disturbing evidence that crowding will not soon disappear, as many of the new jails and prisons report that they have already exceeded capacity. Thirty percent of the completed facilities shown in the directory have reported a current population in excess of their designed capacity.

Although billions of dollars have been invested in expansion of jail and prison capacity, it is apparent that construction is not keeping pace with the rapid growth of the inmate population.

## **NIJ** survey

The information contained in this volume is the result of a national survey of architects who have specialized in constructing correctional facilities. A comprehensive survey instrument was provided to each architectural firm, requiring responses to 32 different questions concerning more than 150 types of information.

Detailed survey forms were also sent to facility administrators, whose time and attention ensured that data were both current and accurate. A number of key questions concerning management and operations could be answered only by facility administrators. This separate verification process has ensured that this survey is both rigorous and comprehensive.

This second edition of the directory incorporates the projects shown in the first edition along with the new projects. This edition also has several new features. Cost indexes have been added, along with floorplans and other materials not previously available. The number of facility profiles is now more than two-and-a-half times that in the first edition.

#### **American Institute of Architects**

The National Directory of Corrections Construction has been developed by the National Institute of Justice with cooperation from the American Institute of Architects (AIA), and may be used as a reference guide

to architects specializing in correctional institutions. Further information is available from the AIA's Committee on Architecture for Justice, including a yearly catalog of criminal justice projects. Readers are encouraged to contact their local chapter of the AIA or the national office:

Committee on Architecture for Justice American Institute of Architects 1735 New York Avenue NW. Washington, DC 20006 202-626-7366

## **Ongoing efforts**

The National Institute of Justice intends to make the Construction Information Exchange as comprehensive as possible and to expand the number of facilities included in the program. Any architect who has designed a correctional facility since 1978 is invited to contact the Construction Information Exchange to enter that facility into the data base. Likewise, administrators of facilities constructed since 1978 but not listed in the directory may request the Construction Information Exchange to mail a survey form to the architect of their facility.

# **Section II**

How to use this directory

Terms used in this directory

## How to use this directory

## Order of facility profiles

Facility profile pages are presented alphabetically by the State in which they are located, and within each State they appear alphabetically by facility name.

## Reference indexes

Indexes serve as locators for particular facilities and are provided in Section III. Each construction project in the directory is classified by facility type, location, and inmate design capacity. An alphabetical listing by facility name is also provided. Readers considering construction should first look for facilities of comparable size, type, and category of construction (whether new or an addition, for instance) to see how these projects compare to their needs. It also may be helpful to examine facilities in the same State or region of the country. This will reveal which designs and construction methods have been used in the reader's geographical area and also may help to determine if visits to completed facilities would be helpful. A list of architectural firms and construction managers responsible for facilities in this directory is provided in Appendix B.

## **Facility profiles**

All facility profiles that appeared in the first edition of the *National Directory of Corrections Construction* are included in this second edition, along with the new additions to the construction data base. Contact persons and telephone numbers for the first edition profiles have been updated, but operational data (such as "Total annual operating costs") are as of the date given for the population, under "Inmate housing areas."

Profiles are included for jail and prison construction projects completed since 1978 and contained in the data base of the Construction Information Exchange. Information entered into the data base is gathered from survey forms completed by architects, facility administrators, and local government officials. Although each facility profile in this directory contains more than 70 items of information, many more information items are contained in the data base. Those wishing further details about a specific facility should contact the Construction Information Exchange. However, for a review of operating costs, current populations, and other operational details, readers should call or write the facility contact person.

The word "Unknown" indicates items not completed by survey respondents. In some instances, however, "N/A" appears because the item is not applicable to the particular project. For example, the profile will not show the total cost per inmate for a complex that includes courts, since the calculation would be invalid.

**Floorplans.** On the right-hand side of each facility profile, a floorplan of a typical housing unit has been provided. The floorplans were provided by the architects and are the best available at time of publication. They provide the reader with a clearer understanding of the design of the facility. In a few cases, floorplans were not available.

## **Comparisons**

Comparisons between construction projects can be both interesting and useful, but they should be made cautiously with the following issues in mind.

Category of construction. Comparisons of different jails or prisons may be inappropriate when the facilities to be examined do not share common characteristics. For example, a jail or prison categorized as a "new, ancillary building" may not have complete support spaces such as kitchen or administration. If such a building were compared to a "new, independent facility" with complete support services, the appearance of a reduced cost might be misleading. For this reason, it is most appropriate to compare facilities in the same construction category.

Costs. Cost comparisons can be especially difficult. To facilitate comparison of construction costs alone, the total cost excludes costs of land acquisition and architects' fees. Moreover, several factors can influence the project costs shown, and comparisons should be made with caution. For example, readers will find that jails and prisons with multiple occupancy cells are invariably less expensive (per inmate) than facilities designed with single occupancy cells. Such contrasts may be informative, but this does not mean that the facilities are truly comparable. Another important example: the building cost of highrise facilities is almost always higher than lowrise buildings even when capacities are the same.

Dimensions. In comparing dimensions, readers are strongly encouraged to examine "gross square feet per inmate." This statistic has been computed by dividing the "gross square feet/corrections" by the inmate design capacity. This statistic may show that some buildings provide much more space per inmate than otherwise comparable projects. However, it simply may be the policy of a particular jurisdiction to provide more space for vocational training, counseling, and other support activities rather than larger cells. An example of a common difference is where one institution has dayrooms contiguous to cells and another facility has only corridors.

**Housing areas.** To facilitate comparisons of different types of correctional facilities, the profile includes a special series of housing statistics. For readers interested primarily in those portions of a construction project that relate to custody and housing of prisoners, it is important to note terms such as: "Costs: Housing area"; "Costs: Housing per inmate"; "Dimensions: Housing area square feet"; and "Dimensions: Size of cells." These statistics allow comparisons that might otherwise be impossible.

Ordinarily, a jail cannot be compared to a prison because of the substantial square footage that prisons may allocate for the support functions associated with long-term custody. Since jails seldom provide extensive support areas (e.g., educational, vocational, counseling, or inmate industries) even a prison with the same number of inmates as a jail will almost always be a substantially larger facility. For this reason, the housing statistics focus on only those portions of the jail or prison that relate to the housing of inmates, and exclude those areas that ordinarily make it inappropriate to draw comparisons. In the case of a campusstyle prison, the term "housing" describes only the building that actually houses inmates. This permits readers to examine those portions of a prison that are comparable to a jail.

Construction cost indexes. Construction cost indexes are provided to assist you in comparing construction projects. If you wish to determine the current cost of construction in your region, use the indexes to adjust dollar amounts so costs are appropriate for your area.

Cost indexes enable readers to make detailed cost comparisons. They permit comparisons between different years and geographic areas. Because construction costs

vary from one part of the United States to another, the regional adjustment will permit valid comparisons of construction projects under the same market conditions. Different regions of the country may exhibit sharp contrasts in the cost of materials and prevailing labor rates. For example, a facility built in Florida will almost always cost less than the same project built in California. By providing for regional adjustments, cost comparisons may be made within a common frame of reference. Cost indexes can be useful when comparing projects built during different years. Since the cost of construction has increased over the years, jail or prison costs in this directory should be adjusted to the same period to be accurately compared.

The cost indexes are based on a 54-city national average, with a 1978 base of 100. To estimate or compare costs, use the index factors for the cities closest to the geographic areas you wish to compare, or closest to the area in which you wish to construct a new facility. The cost indexes are in alphabetical order by State for your convenience. The table does not list any cities in Alaska, Delaware, Hawaii, Idaho, Maine, New Hampshire, North Dakota, Rhode Island, South Carolina, South Dakota, Vermont, West Virginia, or Wyoming.

The three main uses of the cost indexes involve the estimation and comparison of costs for:

- 1. Construction in different regions for different years (Example 1 below).
- 2. Construction in a particular region for different years (Example 2 below).
- 3. Construction in different regions for a particular year (Example 3 below).

The formula:

Index factor for date and place desired Index factor for date and place known

known cost = estimated cost

## Example 1

You are interested in adapting the Knox County Jail, constructed in 1984 in Barbourville, Kentucky, for construction in your own region. The total construction cost for the Knox County Jail in 1984 was \$666,000. Your new facility is to be built in Billings, Montana.

#### **Procedure**

(a) Divide the 1987 Billings index factor by the 1984 Louisville (closest city to Barbourville, Kentucky) index factor.

- (b) Multiply the Knox County Jail known cost (\$666,000) by the result of (a).
- (c) The result of (b) is the total projected cost for your new jail in Billings.

#### Calculation

1987 Billings index factor 151.8 1984 Louisville index factor 135.7

\$666,000 \$745,017 135.7

**Example 1 formula:** (1987 Billings index factor) (1984 Louisville index factor) Knox County Jail \_ projected cost known cost

for Billings

## Example 2

A replacement cost is needed for a State prison located near Birmingham, Alabama. You would like to model the new prison after the Federal Correctional Institution constructed in 1979 in Talladega, Alabama. The total construction cost for that facility was \$10,069,300.

## **Procedure**

- (a) Divide the 1987 Birmingham index factor by the 1979 Birmingham (closest to Talladega) index factor.
- (b) Multiply the Federal Correctional Institution known construction cost (\$10,069,300) by the result of (a).

(c) The result of (b) is the total projected cost for the replacement prison near Birmingham.

## Calculation

1987 Birmingham index factor 136.1 1979 Birmingham index factor 101.3

<u>136.1</u> \$10,069,300 \$13,528,446 101.3

**Example 2 formula:** (1987 Birmingham index factor) (1979 Birmingham index factor)

Federal Correctional Institution known cost projected cost for Birmingham

## Example 3

Duval County, Florida, intends to build a jail in Jacksonville. They would like to make it similar to the Camden County Correctional Facility in Camden, New Jersey, completed in 1987. Even though the design is similar, costs will vary for a number of reasons. The construction cost for the Camden facility was \$28,300,000.

## **Procedure**

- (a) Divide the 1987 Jacksonville index factor by the 1987 Newark (closest to Camden) index factor.
- (b) Multiply the Camden County Correctional Facility known cost (\$28,300,000) by the result of (a).

(c) The result of (b) is the projected construction cost for the new Duval County Jail in Jacksonville.

## Calculation

1987 Jacksonville index factor = 142.1 1987 Newark index factor 192.3

\$28,300,000 \$20,912,272 × <del>192.3</del>

**Example 3 formula:** (1987 Jacksonville index factor)

(1987 Newark index factor)

Camden County Correctional Facility known cost

projected cost for Jacksonville

The National Institute of Justice is grateful to Marshall & Swift, 1617 Beverly Boulevard, Los Angeles, CA 90026, who provided these cost indexes. They are intended only for general guidance and preliminary planning purposes. They should not be used in lieu of a professionally prepared cost estimate. For more specific indexes, please refer to the Marshall Valuation Service, or contact Stanley Strychaz, Marshall & Swift, at 213-250-2222 or 800-421-8042.

## **Construction cost indexes**

	1978	1979	1980	1981	1982	1983	1984	1985	1986	1987
Alabama										
Birmingham	93.2	101.3	111.7	118.0	118.5	121.4	129.0	133.9	134.7	136.1
Arizona										
Phoenix	104.2	116.5	136.5	145.0	150.8	153.4	155.6	160.9	159.6	159.4
Arkansas										
Little Rock	87.9	94.9	106.2	113.7	116.9	118.5	124.2	128.7	126.6	124.7
California										
Fresno	115.4	128.0	140.9	149.9	159.1	167.8	173.7	179.3	183.0	183.4
Los Angeles	112.5	126.2	144.5	156.1	163.4	169.8	179.5	185.9	190.6	191.6
San Diego San Francisco	111.5 122.0	126.5 133.3	143.0 150.0	153.1 159.9	163.1 173.5	165.4 181.0	171.3 192.1	178.7 201.1	183.0 210.2	186.6 213.7
Colorado	.22.0		120.0	.57.7	.,		.,2	20	2.0.2	2.5.7
Denver	102.5	116.0	130.5	135.5	144.5	151.7	159.3	160.6	154.6	156.2
Connecticut										
Hartford	100.1	108.6	119.0	128.6	133.5	142.9	151.9	162.3	172.7	182.0
District of Columbia	100.4	106.2	118.4	123.8	130.3	138.5	145.3	150.1	159.4	163.1
Florida	100.4	100.2	110.4	125.0	150.5	150.5	145.5	150.1	137.4	105.1
Jacksonville	90.3	98.2	108.0	112.7	117.2	121.0	131.0	133.6	139.6	142.1
Miami	94.3	102.5	111.8	119.8	126.7	127.7	135.3	143.0	145.4	145.8
Tampa	90.8	99.3	110.6	118.3	118.8	125.0	135.6	143.3	149.0	150.7
Georgia										
Atlanta	90.9	98.6	109.4	113.2	117.2	122.3	129.6	135.0	140.8	142.1
Illinois										
Chicago	102.0	113.7	126.5	134.8	139.4	142.6	151.2	157.4	157.4	164.2
Indiana										
Indianapolis	99.5	109.1	119.2	124.5	126.9	130.0	139.7	143.1	147.1	150.1
Iowa										
Des Moines	97.6	106.6	119.7	122.8	129.0	129.7	135.2	137.0	140.1	139.9
Kansas										
Wichita	93.1	101.0	110.0	116.8	119.8	121.7	130.9	127.5	128.3	132.6
Kentucky										
Louisville	98.7	109.5	116.1	123.0	126.1	124.9	135.7	135.0	135.8	138.7
Louisiana										
New Orleans	94.3	103.5	114.1	119.3	123.0	130.5	140.0	145.7	143.6	142.8
Maryland										
Baltimore	98.1	104.3	114.1	122.6	126.4	132.9	142.5	146.6	155.4	161.0
Massachusetts										
Boston	105.4	111.6	122.1	129.4	140.8	148.5	158.7	168.5	181.3	194.7
Michigan										
Detroit	106.9	116.5	128.0	136.8	142.1	143.7	151.0	154.5	158.6	161.8
Minnesota										
Minneapolis	100.7	111.3	121.4	128.8	136.3	138.6	151.5	154.6	159.5	162.7
Mississippi										
Jackson	83.2	93.3	105.8	112.2	113.6	117.1	122.7	127.0	126.9	126.7

	1978	1979	1980	1981	1982	1983	1984	1985	1986	1987
Missouri										
Kansas City St. Louis	98.3 98.4	108.4 110.1	118.7 121.4	124.0 125.6	131.6 130.0	135.1 134.6	141.4 145.6	144.8 151.1	146.8 157.2	152.5 161.9
Montana										
Billings	99.4	109.6	121.6	129.5	136.8	143.8	149.2	149.4	153.3	151.8
Nebraska										
Omaha	97.6	109.9	116.5	125.3	131.1	134.0	138.5	136.2	139.0	143.1
Nevada										
Las Vegas	112.7	125.1	139.6	151.8	155.4	160.4	167.2	174.0	174.1	175.5
New Jersey										
Newark	105.9	116.2	126.0	133.7	139.0	146.6	161.6	173.5	184.3	192.3
New Mexico										
Albuquerque	101.3	109.3	124.9	130.3	136.2	138.8	148.6	151.6	153.9	152.1
New York										
Buffalo	108.9	115.9	128.6	135.9	137.9	149.1	157.9	164.6	174.5	178.9
New York	112.1	119.8	129.8	141.0	148.6	159.3	173.9	185.7	198.0	211.2
Rochester	106.2	112.9	124.9	134.2	142.4	146.9	156.4	160.8	169.4	173.3
North Carolina		0- 0			105.5				126 =	
Charlotte	84.0	92.8	100.4	107.4	107.3	113.4	122.2	127.3	130.7	135.2
Ohio										
Cincinnati Cleveland	101.7 107.6	112.7 118.0	123.5 132.4	127.1 137.1	129.8 141.5	132.9 143.7	143.9 156.9	145.4 159.1	144.7 164.1	150.7 167.7
Columbus	96.4	108.2	118.5	127.6	131.6	137.5	142.2	142.2	147.1	151.3
Oklahoma										
Oklahoma City	93.1	102.0	111.7	121.0	126.1	127.6	131.5	139.6	135.0	130.5
Oregon										
Portland	108.5	120.5	133.8	145.1	153.7	154.0	157.8	160.3	161.2	160.3
Pennsylvania										
Philadelphia	106.8	114.0	123.5	129.9	135.0	144.7	153.9	162.3	170.6	179.8
Pittsburgh	103.6	111.8	125.1	132.2	132.1	138.8	148.7	154.9	159.9	161.6
Tennessee										
Memphis	92.5	100.9	115.4	118.6	124.5	128.7	135.2	136.8	138.7	138.7
Nashville	87.9	97.9	107.1	115.3	118.0	118.2	125.0	129.6	130.3	131.7
Texas										
Dallas	92.3	101.6	114.5	118.5	123.2	129.7	140.3	142.5	137.3	135.5
El Paso Houston	87.4 96.6	98.0 109.2	107.2 117.7	112.0 128.2	117.0 129.5	121.7 137.3	126.4 144.8	128.1 142.5	126.6 139.0	130.5 132.9
San Antonio	88.4	99.2	108.1	115.0	119.1	122.2	126.7	130.4	130.9	129.7
Utah										
Salt Lake City	101.1	110.8	123.6	129.0	133.0	139.0	148.0	148.1	152.1	149.3
Virginia										
Richmond	93.6	99.7	107.8	117.8	120.6	128.3	133.3	138.0	145.7	146.7
Washington										
Seattle	109.7	123.0	140.2	. 149.9	163.7	163.4	169.1	170.3	171.9	170.8
Spokane	108.6	119.5	133.9	145.3	152.5	156.6	163.6	167.8	169.7	171.1
Wisconsin										
Milwaukee	104.1	115.4	124.9	136.3	140.5	140.7	149.2	152.2	155.7	161.8

## Terms used in this directory

The order of these terms follows the order in which they appear in the facility profiles.

## **Facility**

The name of the facility as indicated by the architect and facility administrator. The name also may reflect whether the project was a phased one, or an addition, expansion, or remodeling/renovation project. (See Category of construction for definitions.)

#### State

The name of the State in which the facility is located.

## Location

For a county jail, the name of the county in which it is located. For a city, State, or Federal facility, the name of the town or city in which the facility is located.

## Jurisdiction official

The name and title of the senior official (e.g., sheriff or commissioner) responsible for the corrections or law enforcement agency at the time of data verification in late 1987.

## **Contact**

The name, title, address, and phone number of the official designated as a contact for further information (e.g., captain, jail administrator, or warden).

## **Architect**

The name, address, and phone number of the primary architectural firm(s) responsible for the project design. This may also reflect architectural consultants.

## **Construction manager**

The name, address, and phone number of the construction manager for the project. Where the project is a turn-key design and build, the name of the contractor or joint venture will be shown here.

## Groundbreaking

The date when work actually began at the site. As a general rule for new buildings, the first activities are groundclearing and excavation.

## Finish date

The date of substantial completion of the facility. Substantial completion is defined by the American Institute

of Architects as the date certified by the architect when the work is sufficiently complete, in accordance with the contract documents, so officials can occupy the facility for the use for which it is intended.

## **Construction time**

The elapsed months from groundbreaking to substantial completion of the facility.

## **Design capacity**

The total number of general population and special housing inmates for whom the facility was designed. (This number may differ from the actual population shown.)

## **Total cost**

The total cost of building and site improvements, plus all approved change orders. However, this figure does not include the cost of acquiring the land/site, the time of public employees, and administrative expenses for the project. Since it is intended to show the cost of construction, it does not include fees for architects and other consultants.

## **Total annual operating costs**

The latest fiscal year budget for the facility. For facilities reproduced from the first edition, this budget is from the year identified by the population date of inmate housing areas. Costs shown are those that relate to the construction project. In the case of an addition, this figure represents the operating costs for that portion of the facility only. Where "N/A (addition)" appears, the operating costs for the addition are not available separately.

## Category

The category of construction for the specific project. Several types of projects are included in this directory and each has different characteristics.

New, independent facility: an entirely new facility with complete support services, not relying upon other facilities.

New, ancillary building: an entirely new building, but reliant upon already existing buildings for some or all support services. This addition does not provide a complete array of "core" spaces. Data refer to the new addition only and do not include existing or original building information.

**Remodeling/renovation project:** improvements within the shell of an existing facility, typically to modernize an older jail or prison and to bring the design into compliance with current codes and standards.

**Expansion project:** extension or new wing added to an already existing facility. Data refer to the expansion only and do not include existing or original building information (except where noted).

**Phased project (future):** project where costs invested in construction relate to future expansion/addition in a master plan.

**Phased project (past):** project that completes previously "master planned" space(s) "shelled out" earlier.

**Temporary facility/housing:** relocatable or portable units not intended for permanent use. Facility may be disassembled and moved to another location.

## Facility type

Jail: facility operated by county, city, or a combination thereof. Jails operated by these units of local government typically house inmates for 1 year or less, although some States permit consecutive sentences. Jails may house both pretrial detainees and sentenced prisoners. Inmates may be held on both felony and misdemeanor charges. It should also be noted that several States permit inmates from State prison systems to be housed in local jail facilities. The State of Alaska has no counties; therefore all inmates are housed in State facilities.

**Prison:** facility operated by any of 50 States, the District of Columbia, or the Federal Government. Prisoners in State institutions are held for periods of longer than 1 year. Unlike local jails, State prisons house only sentenced offenders. Some States will permit units of local government to board jail prisoners in State facilities, but this practice is most unusual.

**Complex:** buildings with multiple purposes. Typically, in a local facility, jail space may be combined with courts, law enforcement, or other related uses. Cost comparisons are discouraged for this type of facility, as it is impossible to isolate corrections costs from the costs for other portions of the building.

## **Building configuration** (See Figure 1)

The physical arrangement of individual buildings.

**Integrated structure:** one building.

**Highrise:** one building, more than four stories in height.

Ladder, telephone pole: linear cell blocks arranged in parallel off a central connecting corridor.

Wheel, spoke or radial: linear cell blocks that emanate from one central control area like spokes from the hub of a wheel.

**Courtyard:** linear cell blocks interconnected around a central enclosed courtyard.

Clusters: a number of individual buildings that are interconnected.

Campus style: a number of individual buildings that are not interconnected.

## **Costs**

**Total:** the total cost of building and site improvements, plus all approved change orders. However, this figure does not include the cost of acquiring the land/site, the time of public employees, and administrative expenses for the project. Since it is intended to show the cost of construction, it does not include fees for architects and other consultants.

**Building only:** the cost for the facility only, as the figure excludes all site work. Costs such as grading, paving, and providing utilities are not included here. This figure represents what it would cost to build the same facility at another site, provided that site costs for the new location are added and impact of the site on the design has been considered.

Housing area: the cost for those areas of the correctional facility designed for housing inmates. This includes the total gross square footage of the entire housing building unit or level, as well as the contiguous and/or associated spaces for mechanical, circulation, storage, visiting, control, counseling, multipurpose room, dayrooms, exercise, interview, etc. Excluded from this figure are costs of independent or unrelated areas and buildings such as intake, medical, special housing, administration, food service, vocational, educational, agricultural, etc.

Housing per inmate: the housing costs per general population inmate. This figure is computed by dividing the total number of general population inmates (design capacity) into the housing costs.


**Housing per cell:** the housing costs per general population cell. This figure is computed by dividing the total number of general population cells into the housing costs.

**Total per inmate:** the total construction costs per inmate. This figure is computed by dividing the total number of inmates (design capacity) into total construction costs. In the case of a multiuse/complex type facility, "N/A (complex)" appears, as it would not be appropriate to compute an inmate cost when the facility includes other than correctional uses.

**Total per GSF:** the total construction costs per gross square foot. This figure is computed by dividing the total gross square feet into total construction costs.

**Total annual operating costs:** the latest fiscal year budget for the facility. For facilities reproduced from

Figure 1 **Building configuration** 



the first edition, this budget is from the year identified by the population date under inmate housing areas. Costs shown are those that relate to the construction project. In the case of an addition, this figure represents the operating costs for that portion of the facility only. Where "N/A (addition)" appears, the operating costs for the addition are not available separately.

## **Security**

**Perimeter:** the types of perimeter used in a facility, including building exterior only; single fence; double fence; triple fence; alarm/detection systems; razor wire on fence(s); razor wire on and between fences; towers; and patrols.

Inmate security level: the division of the facility according to levels of security for housing inmates. Categories include: maximum (most secure construction and highest level of staff supervision in system); medium (although not as restricted as maximum, this category requires a locked unit and a security perimeter); and minimum (greatest freedom of movement for inmates, may have dormitories, living areas may not be locked, and perimeter security is limited).

## **Inmate cells**

This describes the finishes, fixtures, and furnishings that were selected for general population cells. These aspects of special custody, isolation, medical, and other special population areas of a jail or prison may be different.

**Doors/material:** may be steel or wood, and may be solid (without bars or windows).

**Doors/type:** may be swinging or sliding.

**Doors/locking:** may be motor driven and remote locking; remote locking only; or manual locking.

**Floor surface:** materials of the floor surface. Options include linoleum; carpet; epoxy coating; sealed concrete; or vinyl tile.

**Intercom:** the type of communications system between officers and inmates. Options include either one- or two-way systems to cells or common areas, or no system.

HVAC: heating, ventilation, and air conditioning. Describes the environmental systems included in the facility. While all facilities have some form of heating, not every jail or prison has an air conditioning system. Solar systems, steam, gas, or other specialized energy recycling systems are indicated here.

**Plumbing:** inmate plumbing fixtures. Indicates whether the lavatory and toilet are a combination unit or separate units, and are made of stainless steel, china, or aluminum.

Furniture: chairs, beds, tables, and other furniture in cells and dayrooms. Choices include steel; wood; vinyl/plastic; or concrete.

Fire protection: fire protection systems used in inmate housing areas. Hardware may include smoke detectors for cells, common areas, or both; sprinklers for cells, common areas, or both; or manual alarm stations.

## **Dimensions**

Gross square feet/corrections: the gross square feet (as defined under "Gross square feet/total" below) of all spaces relating to corrections purposes in the construction project shown in the profile. In the case of an addition or expansion, this figure represents the square footage of that addition or expansion only.

Gross square feet/other: in the case of a multiuse or complex type facility, the gross square feet assigned for purposes other than corrections, law enforcement, or courts (e.g., city hall, communications center, or other government offices).

Gross square feet/total: the total square footage of the construction project. If the project was an addition or expansion, this figure represents the square footage of that addition or expansion only. Gross square feet is defined by the American Institute of Architects as the sum of the areas of the several floors of the building, including basements, mezzanine, and intermediate floored tiers and penthouses of headroom height, measured from the exterior faces of exterior walls or from the centerline of walls separating buildings. Covered walkways, open roofed-over areas that are paved, porches, and similar spaces shall have the architectural area multiplied by an area factor of 0.50. The architectural area does not include such features as pipe trenches, exterior terraces, or steps, chimneys, roof overhangs, etc. (See AIA Document D101.)

Housing area square feet: the size of spaces devoted to the custody of inmates, not the entire facility. Included are those spaces directly related to the housing of inmates. The figure includes total gross square footage of the housing building, unit, or level including the contiguous and/or associated spaces for mechanical, circulation, storage, visiting, control, staff areas, multipurpose rooms, dayrooms, exercise, interview, etc. Excluded are independent areas not contiguous to inmate housing, such as intake, medical, special housing, administration, food service, vocational, educational, and other support activities not directly associated with housing. In construction projects that are additions or expansions, it is possible that only housing areas were added. In such instances, the square footage shown for housing may be almost equal to the total square footage, since support spaces were not provided.

**Gross square feet per inmate:** the gross square feet assigned to an inmate based on design capacity. This

figure is computed by dividing the number of inmates in general population (design capacity) into the gross square feet/corrections. However, if the current population is greater than the design capacity, the gross square feet per inmate will be fewer.

Size of cells: space inside a typical cell. This figure is the useful space and does not include areas consumed by a plumbing chase or protruding walls. The type of cell (single, double, etc.) is indicated.

Net/gross square feet: this percentage is an expression of building efficiency. Because spaces not used by staff and/or inmates are excluded from net space, this percentage represents how much of the total square footage is actually devoted to everyday useful purposes. The remaining space is the amount consumed by spaces necessary for the building but not utilized by its occupants.

## **Construction type**

**Structural:** the frame that carries the building's weight and provides structural support for the facility. This describes the type of structural system, such as steel frame, load-bearing precast panels, cast-in-place concrete frame, or precast concrete frame.

**Exterior walls:** the construction materials that make up outside walls of the building, forming the security "shell" or "envelope." Options include precast panels, cast-in-place concrete, CMU block, brick, or architectural precast.

Interior walls: the construction materials that make up inside walls or partitions used to divide cells and rooms within the building. Options include precast panels, cast-in-place concrete, CMU block, or brick.

Exterior surface/facade: the exterior finish, resulting in the completed outside appearance. Sometimes called the building's "skin," examples include stucco, brick, paint, natural wall, and textured or colored concrete.

## Inmate design capacity

Single occupancy: number of inmates for whom single cells were designed. In some facilities, bunks have been permanently attached to the walls in single cells thereby converting them to double cell use. However, because they were originally designed for single occupancy, these cells are counted as single occupancy in this directory. (Extra bunks are shown as "Means to handle crowding," defined below.)

**Double occupancy:** number of inmates for whom double cells were designed.

**Dorms:** number of inmates for whom dormitories were designed.

**Special housing:** number of inmates for whom medical, psychiatric, isolation, holding, and other special cells were designed.

General population: total number of inmates for whom cells other than special housing were designed.

**Total:** total number of general population and special housing inmates for whom the facility was designed. (This number may differ from the actual population given under "Inmate housing areas.")

## **Current staff**

Facility administrators have reported the number of full-time staff assigned to the facility. In the case of an addition or expansion, only staff provided for that addition or expansion are listed, and when those figures were not available, the profile indicates "N/A (addition)." To ensure comparable responses, the survey included definitions for each staffing category.

Administration: chief executives including wardens, superintendents, directors, administrators, colonels, captains, majors, lieutenants, and their assistants. Also includes all supervisory personnel above the level of first line supervisor; administrative and budget staff; clerical support; secretaries; typists; stenographers; bookkeepers; clerks; and switchboard operators.

**Security:** all line staff and first line supervisors, both sworn and unsworn; correctional officers; deputies; guards; sergeants; and security supervisors.

**Programs/treatment:** medical, dental, psychiatric, counseling, and therapy personnel; and technicians.

Maintenance: engineers, electricians, plumbers, janitors, and repair and grounds personnel. Also includes kitchen/culinary and food preparation workers, cooks, and dishwashers.

**Total:** total number of full-time staff members as reported by the facility administrator.

Current inmate/staff ratio: the number of inmates per staff member based on the current population. This figure is computed by dividing the total number of current staff into the current population, not the inmate design capacity.

## **Inmate housing areas**


**Design:** the options for layout or arrangement of the inmate cells. Options include linear-outside cells, where cells have windows on outside walls, permitting direct light into cells; linear-inside cells, where cells are not on outside walls and light to cells is indirect; and module/pod, where cells are arranged around a common dayroom with cell doors opening into this activity area. (See Figure 2.)

Cells per unit: the number of cells in each block, pod, or module—the number of cells included in one housing unit of the facility.


Inmates per unit: the number of inmates (design capacity) in a typical block, pod, or module.

Figure 2 **Design of inmate housing areas** 


Linear; cells are on outside walls.



Linear; cells are inside.



Module/pod type; cells are on outside walls.



Management type: the type of surveillance utilized for a typical housing unit per design. Options include intermittent surveillance, where officers may walk periodically down hallways lined with cells and do not have constant view of all inmate areas; remote surveillance, where officers have inmates under constant observation but are separated from inmates by a security enclosure or barrier; or direct supervision, where officers are in constant contact with inmates and not enclosed in a workstation or separated by other barriers.

**Date of population given:** the date by which facility administrators reported the current population.

Facility commitment: the type of inmate housed in the facility. Several States permit inmates from State prison systems to be housed in local jail facilities, and while some States will permit units of local government to board jail prisoners in State facilities, the practice is most unusual.

Means to handle crowding: the means by which the facility handles, or plans to handle, crowding of its facility. Options include bunk beds in cell; mattresses on floor; beds in dayroom; and second bunk permanently attached to wall. Some facilities do not permit crowding.

## **Construction process**

Finance method: the method of payment for the construction project and the source of funds. Options include General Obligation Bonds (G.O. Bonds); Lease Revenue Bonds; revenue sharing; other Federal funds; special election; floating or variable rate; Certificates of Participation; local funds; State funds; shared cost from multiple jurisdictions; and facility leased from private entity.

Contract method: the legal and financial steps used in the building process. Options include conventional design and bid; construction management (CM) fast track; and turn-key design and build. For methods involving firms other than the architect, such as construction management fast track or turn-key design and build, the name of the responsible firm will be shown at the top of the profile page.

Use of inmate labor: participation by prisoners in any aspect of the construction process and the specific activities in which they may have been engaged. This also reflects whether the use of inmate labor was limited, moderate, or extensive.

Use of prefabrication: techniques that may have been used to manufacture portions of the facility away from the construction site. If plant manufacturing was utilized, the nature of the components is described here, as is whether use was limited, moderate, or extensive.

## Architect's reported analyses

Architects have reported the factors which, in their opinion, strongly influenced both costs and length of time that were required for completion of the facility. Architects have reported the positive and negative points for each project in separate categories for cost issues and time factors. Examples of positive cost factors might be favorable market conditions or repetitiveness of design. Under time issues, positive factors could include advanced order of materials and hardware or use of prefabricated components. Negative cost and time factors include such issues as difficult site conditions or labor problems.

			,

# **Section III**

Index: State/county/city

Index: Inmate design capacity

Index: Category of construction

Index: Facility name

State	County/City	Facility type	Facility name	Page
AK	Anchorage	State detention facility	Cook Inlet Pre-Trial Facility	60
AK	Anchorage	State pre-trial facility	Cook Inlet Pre-Trial Facility Phase II	62
ΑK	Bethel	State prison	Yukon-Kuskokwim Correctional Center	76
ΑK	Eagle River	State prison	Hiland Mountain Correctional Center	66
ΑK	Eagle River	State prison	Meadow Creek Correctional Center	70
ΑK	Fairbanks	State prison	Fairbanks Correctional Center	64
ΑK	Kenai	State prison	Wildwood Correctional Center	74
AK	Palmer	State prison	Mat-su Pre-Trial Facility	68
ΑK	Palmer	State prison	Palmer Correctional Center Medium Security Facility	72
AL	Bessemer	State prison	West Jefferson Correctional Facility	. 58
AL	Jefferson County	County jail	Jefferson County Jail	56
AL	Talladega	Federal prison	Federal Correctional Institution	54
AR	Clark County	County complex	Clark County Detention Facility	96
AR	Garland County	County jail	Garland County Detention Facility	100
AR	Grady	State prison	Cummins Unit—Medium Security	98
AR	Saline County	County jail	Saline County Detention Facility	104
AR	Tucker	State prison	Maximum Security Unit, Tucker Unit	102
ΑZ	Cochise County	County jail	Cochise County Jail	82
ΑZ	Florence	State prison	Arizona State Prison—Florence	78
ΑZ	Gila	Juvenile correctional facility	Pinal Mountain Juvenile Institution	92
ΑZ	Goodyear	State prison	Arizona State Prison—Perryville	80
ΑZ	Phoenix	Federal prison	Federal Correctional Institution	84
ΑZ	Pima County	County jail	Pima County Adult Detention Center	88
ΑZ	Pima County	County jail	Pima County Adult Detention Center (Addition)	90
ΑZ	Sacaton	Juvenile rehabilitation center	Sacaton Juvenile Rehabilitation Center	94
ΑZ	Tucson	Federal prison	Federal Correctional Institution	86
CA	Alameda County	County jail	Alameda County North County Jail	106
CA	Contra Costa County	County complex	Contra Costa County Detention Facility	114
CA	Kings County	County jail	Kings County Branch Jail	120
CA	Nevada County	County restitution center	Nevada County Detention Center	124
CA	Orange County	County jail	Lacy Security Facility	122
CA	Orange County	County jail	Orange County Sheriff's Intake Release Center	126
CA	Placer County	County complex	Placer County Jail	128
CA	Plumas County	County jail	Plumas County Sheriff's Department & Detention Facility	130
CA	Represa	State prison	California State Prison—Sacramento County/Folsom	112
CA	•	<del>-</del>	Foothill Communities Law & Justice Center	112
CA	San Bernardino County	County complex	Richard J. Donovan Correctional Facility at Rock Mountain	134
	San Diego	State prison County jail		154
CA	San Joaquin County	County Jan	San Joaquin County Honor Farm Women's Minimum Security Facility	136
CA	Santa Barbara Cauntu	County ioil	Santa Barbara County Main Jail	
CA	Santa Barbara County	County jail	· · · · · · · · · · · · · · · · · · ·	138
CA	Santa Clara County	County jail	Elmwood—Barracks 24 Sonto Courty Loil (Phase I)	116
CA	Santa Cruz County	County jail	Santa Cruz County Jail (Phase I)	140
CA	Shasta County	County complex	Shasta County Justice Center	144
CA	Sonoma County	County jail	Sonoma North County Detention Facility	146
CA	Stanislaus County	County complex	Stanislaus County Jail	148
CA	Sunnyvale	City complex	Sunnyvale Public Safety Building and Temporary Holding	150
<b>~</b> .	m 1 1 1	G	Facility	150
CA	Tehachapi	State prison	California Correctional Institution	108
CA	Torrance	City complex	Torrance Police Department	152
CA	Tulare County	County jail	Sequoia Field Detention Facility	142

State	County/City	Facility type	Facility name	Page
CA	Tuolumne County	County jail	Tuolumne County Jail	154
CA	Vacaville	State prison	California Medical Facility—South	110
CA	Ventura County	County complex	Pre-Trial Detention Facility	132
CA	Yuba County	County jail	Yuba County Jail	156
CO	Adams County	County jail	Adams County Detention Facility	158
CO	Alamosa County	County complex	Alamosa County Law Enforcement Center	160
CO	Crowley	State prison	Arkansas Valley Correctional Facility	162
CO	Delta County	County complex	Delta County Criminal Justice Facility	164
CO	Garfield County	County jail	Garfield County Jail	166
CO	Pitkin County	County complex	Pitkin County Jail	168
CO	Summit County	County complex	Summit County Justice Center	170
CT	Bridgeport	State prison	Bridgeport Correctional Center: Modular Units	172
CT	Niantic	State jail	J. Bernard Gates Correctional Unit	174
DE	Smyrna	State prison	Delaware Correctional Center (Maximum Security)	176
FL	Alachua County	County jail	Alachua County Corrections Facility	178
FL	Indiantown	State prison	Martin Correctional Institution	188
FL	Leon County	County jail	Leon County Jail	182
FL	Leon County	County complex	Leon County Justice Complex	184
FL	Marion County	County jail	Marion County Detention Center	186
FL	Miami	State prison	South Florida Reception Center	196
FL	Pinellas County	County jail	Pinellas County Jail—Medium Security Facility	190
FL	Raiford	State prison	Union Correctional Institution	198
FL	Santa Rosa County	County complex	Santa Rosa County Jail	192
FL	Seminole County	County jail	Seminole County Correctional Facility	194
FL	Tallahassee	Federal prison	Federal Correctional Institution	180
GA	Clarke County	County jail	Clarke County Correctional Institution	200
GA	Dooly County	County jail	Dooly County Jail	202
GA	Richmond County	County complex	Richmond County Law Enforcement and Justice Center	204
HI	Maui County/Wailuku	County and city jails/State		
		prison	Maui Community Correctional Center	206
ΙA	Polk County	County jail	Polk County Jail	244
ΙA	Woodbury County	County complex	Woodbury Law Enforcement Center	246
IL.	Centralia	State prison	Centralia Correctional Center	208
IL	Cook County	County jail	Cook County Medical and Psychiatric Facility—RTU Building	210
IL	Danville	State prison	Danville Correctional Center	212
IL	Dixon	State prison	Dixon Correctional Center	214
IL.	Douglas County	County complex	Douglas County Jail	216
IL	DuPage County	County complex	DuPage County Jail and Sheriff's Department	218
IL	Dwight	State prison	Dwight Correctional Center (1979 Addition)	220
IL	Dwight	State prison	Dwight Correctional Center (1984 Addition)	222
IL	East Moline	State prison	East Moline Correctional Center	224
IL	Hillsboro	State prison	Graham Correctional Center	220
IL	Manteno	Juvenile correctional facility	Illinois Youth Center—Kankakee (Dining Facility)	228
IL	Manteno	Juvenile correctional facility	Illinois Youth Center—Kankakee (Housing Unit)	230
IL	Peoria County	County complex	Peoria County Adult Detention and Work Release Facility	232
IL	Rock Island County	County complex	Rock Island County Jail	234
IL IL	Sheridan	State prison	Sheridan Correctional Center (Kitchen/Dining Facility)	238
IL IL	Sheridan	State prison	Sheridan Correctional Center (Medical/Security Services)	240
IL	Vienna	State prison	Shawnee Correctional Center	236
	* 1×11114	Dune Pribon		_5,

State	County/City	Facility type	Facility name	Page
KS	Johnson County	Juvenile detention facility	Johnson County Juvenile Hall	248
KS	Lansing	State prison	Kansas State Penitentiary (Phase One)	250
KS	Shawnee County	County complex	Shawnee County Department of Corrections	252
KY	Ashland	Federal prison	Federal Correctional Institution	254
KY	Knox County	County jail	Knox County Jail	256
LA	Angie	State prison	Washington Correctional Institute	268
LA	Oakdale	Federal complex	Federal Detention Center	260
LA	Jackson	State prison	Dixon Correctional Institute	258
LA	Jackson	State complex	Feliciana Forensic Facility	262
LA	St. Gabriel	State prison	Hunt Correctional Center	264
LA	St. Gabriel	State prison	Louisiana Correctional Institute for Women	266
MA	Jamaica Plain	State treatment facility	Longwood Treatment Center	286
MA	Norfolk	State prison	Massachusetts Correctional Institution Norfolk	288
MD	Baltimore	City jail	Baltimore City Jail	274
MD	Baltimore	State prison	Baltimore City Correctional Center	272
MD	Montgomery County	County complex	Montgomery County Detention Center	278
MD	Prince George's County	County jail	Prince George's County Correctional Center	280
MD	Somerset County	County jail	Somerset County Detention Center	282
MD	Washington County	County jail	Washington County Detention Center	284
MD	Westover	State prison	Eastern Correctional Institution	276
ME	Franklin County	County complex	Franklin County Detention/Law Enforcement Facility	270
MI	Grand Traverse County/	county complex	Training County Determined Law Emotechnical activity	270
1411	Traverse City	County and city complex	Grand Traverse County Correctional Facility	292
MI	Jackson	State prison hospital	State Prison of Southern Michigan	296
MI	Macomb County	County jail	Macomb County Jail	294
MI	Shingleton	State prison	Correction Camp Cusino	290
MN	=	County juvenile detention	Correction Camp Cusino	250
IVIIA	Hennepin County		Hannanin County Invanila Detention Contar	298
MAI	C4 Datas	facility	Hennepin County Juvenile Detention Center	300
MN	St. Peter	State prison	Minnesota Supervised Living Facility	308
MO	Clay County	County jail	Clay County Detention Center	
MO	Farmington	State prison	Farmington Correctional Center	310
MO	Fulton	State prison	Fulton Reception and Diagnostic Center, Phase I	312
MO	Jackson County	County complex	Jackson County Detention Center	314
MO	Pacific	State prison	Missouri Eastern Correctional Center	316
MS	Jackson County	County jail	Jackson County Adult Detention Center	302
MS	Parchman	State prison	Mississippi State Penitentiary—Unit 29	304
MS	Tunica County	County complex	Tunica County Jail and Sheriff's Department	306
MT	Chouteau County	County complex	Chouteau County Law Enforcement Facility	318
MT	Jefferson County	County complex	Jefferson County Criminal Justice Center	320
MT	Lewis and Clark County	County complex	Lewis and Clark County Criminal Justice Facility	322
MT	Pondera County	County complex	Pondera County Jail	324
MT	Yellowstone County	County complex	Yellowstone County Detention Facility	326
NC	Craven County	County complex	Craven County Law Enforcement Center	384
NC	Maury	State prison	Eastern Correctional Center	386
NC	Raleigh	State prison	North Carolina Central Prison	388
NC	Troy	State prison	Southern Correctional Center	390
NE	Dodge County	County complex	Dodge County Judicial Center	328
NE	Douglas County	County jail	Douglas County Correctional Center	330
NE	Lincoln	State prison	Nebraska State Penitentiary	332
NJ	Atlantic County	County complex	Gerald L. Gormley Justice Facility	338

State	County/City	Facility type	Facility name	Page
NJ	Camden County	County jail	Camden County Correctional Facility	336
NJ	Delmont	State prison	Southern State Correctional Facility: Modular Units (Phase I	
			and II)	344
NJ	Middlesex County	County jail	Middlesex County Correctional Facility	340
NJ	Ocean County	County complex	Ocean County Justice Complex	342
NJ	Trenton	State prison	Trenton State Prison	346
NJ	Warren County	County jail	Warren County Correctional Center	348
NM	Albuquerque	Youth detention facility	Youth Diagnostic and Development Center	360
NM	Albuquerque	Youth detention facility	Youth Diagnostic and Development Center—Phase III	362
NM	Bernalillo County	County jail	Bernalillo County Detention Center (South Tower)	350
NM	Grants	State prison	Western New Mexico Correctional Facility	358
NM	Las Cruces	State prison	Southern New Mexico Correctional Facility	356
NM	Los Lunas	State prison	Central New Mexico Correctional Facility	352
NM	Santa Fe	State prison	Penitentiary of New Mexico	354
NV	Clark County	County jail	Clark County Detention Center	334
NY	Buffalo	State center for youth	Masten Park Secure Center	378
NY	Elmira	State prison	Elmira Correctional & Reception Center Food Service & Dining Facility	366
NY	Erie County	County jail	Erie County Correctional Facility	368
NY	Erie County	County jail	Erie County Holding Center	370
NY	New York	City jail	Brooklyn Correctional Facility	364
NY	New York	City jail	North Facility	380
NY	New York	City jail	Rikers Island: Modular Units	382
NY	New York	State treatment center	Kirby Forensic Psychiatric Center	376
NY	Otisville	Federal prison	Federal Correctional Institution	372
NY	Ray Brook	Federal prison	Federal Correctional Institution	374
HC	Ashtabula County	County complex	Ashtabula County Justice Center	392
ЭН	Chillicothe	State prison	Ross Correctional Institution	40€
HC	Clermont County	County jail	Clermont County Jail	394
HC	Hamilton County	County complex	Hamilton County Justice Complex	396
HC	Logan County	County complex	Logan County Jail and Office Complex	398
HC	London	State prison	Madison Correctional Institution	400
HC	Marysville	State prison	Ohio Reformatory for Women	402
HC	Ottawa County	County complex	Ottawa County Detention Facility	404
HC	Wayne County	County complex	Wayne County Justice Center	408
OK	Hodgen	State prison	Ouachita Correctional Center	424
OK	Lexington	State prison	Lexington Assessment & Reception Center	414
OΚ	Lexington	State prison	Lexington Assessment & Reception Center, Phase I and II	416
ЭK	McAlester	State prison	Oklahoma State Penitentiary	422
OK	Cleveland County	County complex	Cleveland County Detention Center	410
ЭK	Kay County	County complex	Kay County Detention Facility	412
ЭK	Muskogee County/Muskogee	County and city jails	Muskogee County/City Detention Facility	420
OΚ	Oklahoma City	State prison	Mabel Bassett Correctional Center	418
OR	Jackson County	County jail	Jackson County Jail	426
OR	Multnomah County	County complex	Justice Center	428
PA	Allegheny County	County jail	Allegheny County Jail Annex	430
PA	Blair County	County jail	Blair County Prison	432
PA	Huntington	State prison	State Correctional Institution at Smithfield	440
PA	Lycoming County	County jail	Lycoming County Prison	434
PA	Mercer	State prison	State Regional Correctional Facility at Mercer	442

State	County/City	Facility type	Facility name	Page
PA	Philadelphia County/			
	Philadelphia	County and city jails	Philadelphia Industrial Correctional Center	436
PA	Schuylkill County	County jail	Schuylkill County Prison	438
PA	Warren County	County jail	Warren County Jail	444
PA	Wyoming County	County jail	Wyoming County Jail	446
SC	Clemson	City complex	Clemson Police Department	448
SC	Columbia	State prison	Gilliam Psychiatric Center	450
SC	Myrtle Beach	City complex	Myrtle Beach Law Enforcement Center	454
SC	Ridgeville	State prison	Lieber Correctional Institution	452
ΓN	Nashville	State prison	Nashville Community Service Center	456
ΓN	Shelby County/Memphis	County and city complex	Shelby County Justice Center	458
ГΧ	Austin County	County complex	Austin County Jail	460
ГΧ	Bastrop	Federal prison	Federal Correctional Institution	486
ГΧ	Bexar County	County complex	Bexar County Juvenile Center	466
ГΧ	Brazoria County	County jail	Brazoria County Sheriff's Department Detention Center II	468
ГΧ	Cameron County	County jail	Cameron County Detention Center	470
ГХ	Chambers County	County complex	Chambers County Law Enforcement Center	472
ГХ	Comal County	County complex	Comal County Jail	476
ГХ	Dallas County/Dallas	County and city jails	Lew Sterrett Justice Center	506
ГХ	Fayette County	County complex	Fayette County Detention Center	484
ГХ	Fort Bend	County complex	Fort Bend County Jail	490
ГХ	Fort Bend	County jail	Fort Bend County Jail (Expansion)	492
ГХ	Freeport	City complex	Freeport Police and Courts Building	494
ГХ	Galveston	State prison hospital	TDC Hospital at Galveston	524
ГХ	Gatesville	State prison	Mountain View Unit	512
ГХ	Harris County	County complex	Harris County Juvenile Detention Home	496
ГХ	Hidalgo County	County jail	Hidalgo County Jail	498
ГХ	Houston	City complex	Westside Police Area Command Station	532
ГХ	Hunt County	County complex	Hunt County Criminal Justice Center	500
ГХ	Huntsville	State prison	Diagnostic Unit	480
ГХ	Huntsville	State prison	Ellis II Unit (Phase I and II)	480
ГХ	Katy	City complex	Katy Police Department	504
ГХ	Liberty County	County complex	Liberty County Jail	508
ГХ	Midway	State prison	Ferguson Unit	488
ГХ	Missouri City	City complex	Missouri City Police Department	510
ГХ	Navasota	State prison	Wallace Pack Unit I	528
ΓX	Navasota	State prison	Wallace Pack Unit II	530
ΓX	Orange County	County complex	Orange County Jail	514
ΓX	Palestine	· •	Beto II Unit	464
ГХ	Pearland	State prison		
	Richmond	City complex	Pearland Public Safety Building Jester Unit Number 3	516
ΓX ΓX	Rosharon	State prison		502 478
		State prison	Darrington Unit San Patricio County Sheriff's Department	
ΓX ΓX	San Patricio County Smith County	County complex	•	518 520
	•	County jail	Smith County Jail	
ΓX	Starr County Tennesses Colony	County jail	Starr County Jail	522
ΓX	Tennessee Colony	State prison	Beto I Unit	462
ΓX	Tennessee Colony	State prison	Coffield Unit	474
ΓX	Victoria County	County complex	Victoria County Jail	526
UT	Draper	State prison	Young Adult Correctional Facility	538
UT	Salt Lake City	State correctional facility	Orange Street Community Correctional Center	534

State	County/City	Facility type	Facility name	Page
UT	Uintah County	County jail	Uintah County Jail	536
VA	Alexandria	City complex	Alexandria Detention Center	544
VA	Augusta County	County jail	Augusta County Jail	546
VA	Fairfax County	County complex	Fairfax County Adult Detention Center and Pre-Release Center	548
VA	Pittsylvania County	County jail	Pittsylvania County Jail	550
VA	Roanoke	City complex	Roanoke City Jail	552
VT	St. Albans	State prison	Northwest State Correctional Facility	540
VT	St. Johnsbury County	County jail/State prison	St. Johnsbury Community Correctional Center	542
WA	Benton County	County complex	Benton County Justice Center	554
WA	Forks	City complex	Forks City Jail	556
WA	Jefferson County	County complex	Jefferson County Correctional Facility	558
WA	Monroe	State prison	Twin Rivers Corrections Center	562
WA	Shelton	State prison	Washington Corrections Center Intensive Management Unit	564
WA	Thurston County	County complex	Thurston County Corrections Facility	560
WA	Whitman County	County complex	Whitman County Correctional Facility	566
WI	Burnett County	County complex	Burnett County Government Center	570
WI	Oshkosh	State prison	Oshkosh Correctional Institution	574
WI	Portage	State prison	Columbia Correctional Institution	572
WI	Rusk County	County complex	Rusk County Law Enforcement Facility	576
wv	Ohio County/Wheeling	County and city complex	Ohio County Correctional Center	568

Inmates	Facility name	County/City	State	Facility type	Page
7	Youth Diagnostic and Development Center—Phase III	Albuquerque	NM	Youth detention facility	362
8	Pondera County Jail	Pondera County	MT	County complex	324
10	Sheridan Correctional Center (Medical/Security Services)	Sheridan	IL	State prison	240
11	Dooly County Jail	Dooly County	GA	County jail	202
13	Clemson Police Department	Clemson	SC	City complex	448
14	Forks City Jail	Forks	WA	City complex	556
14	Jefferson County Criminal Justice Center	Jefferson County	MT	County complex	320
16	Garfield County Jail	Garfield County	CO	County jail	166
20	Douglas County Jail	Douglas County	IL	County complex	216
20	Sunnyvale Public Safety Building and Temporary Holding Facility	Sunnyvale	CA	City complex	150
21	Freeport Police and Courts Building	Freeport	TX	City complex	494
21	Katy Police Department	Katy	TX	City complex	504
21	Tuolumne County Jail	Tuolumne County	CA	County jail	154
24	Franklin County Detention/Law Enforcement Facility	Franklin County	ME	County complex	270
24	Missouri City Police Department	Missouri City	TX	City complex	510
25	Pitkin County Jail	Pitkin County	CO	County complex	168
27	Burnett County Government Center	Burnett County	WI	County complex	570
27	Logan County Jail and Office Complex	Logan County	ОН	County complex	398
27	Saline County Detention Facility	Saline County	AR	County jail	104
29	Rusk County Law Enforcement Facility	Rusk County	WI	County complex	576
30	Meadow Creek Correctional Center	Eagle River	AK	State prison	70
32	Clark County Detention Facility	Clark County	AR	County complex	96
33	Jefferson County Correctional Facility	Jefferson County	WA	County complex	558
33	Tunica County Jail and Sheriff's Department	Tunica County	MS	County complex	306
34	Johnson County Juvenile Hall	Johnson County	KS	Juvenile detention facility	248
35	Chouteau County Law Enforcement Facility	Chouteau County	MT	County complex	318
35	Plumas County Sheriff's Department & Detention Facility	Plumas County	CA	County jail	130
36	Cook Inlet Pre-Trial Facility Phase II	Anchorage	AK	State pre-trial facility	62
36	Pearland Public Safety Building	Pearland	TX	City complex	516
37	Knox County Jail	Knox County	KY	County jail	256
38	Whitman County Correctional Facility	Whitman County	· WA	County complex	566
39	Pittsylvania County Jail	Pittsylvania County	VA VA	County jail	550
40	Sacaton Juvenile Rehabilitation Center	Sacaton Sacaton	AZ	Juvenile rehabilitation center	94
40	San Joaquin County Honor Farm Women's Minimum				74
	Security Facility	San Joaquin County	CA	County jail	136
40	Stanislaus County Jail	Stanislaus County	CA	County complex	148
41	Ottawa County Detention Facility	Ottawa County	OH	County complex	404
43	Dodge County Judicial Center	Dodge County	NE	County complex	328
46	Summit County Justice Center	Summit County	CO	County complex	170
47	Delta County Criminal Justice Facility	Delta County	CO	County complex	164
48	Lewis and Clark County Criminal Justice Facility	Lewis and Clark County	MT	County complex	322
48	Nevada County Detention Center	Nevada County	CA	Restitution center	124
50	Baltimore City Jail	Baltimore	MD	City jail	274
50	Dixon Correctional Center	Dixon	IL	State prison	214
50	Illinois Youth Center—Kankakee (Housing Unit)	Manteno	IL	Juvenile correctional facility	230
50	Warren County Jail	Warren County	PA	County jail	444
50	Wyoming County Jail	Wyoming County	PA	County jail	446
51	Alamosa County Law Enforcement Center	Alamosa County	CO	County complex	160
51	Leon County Justice Complex	Leon County	FL	County complex	184

Inmates	Facility name	County/City	State	Facility type	Page
51	Northwest State Correctional Facility	St. Albans	VT	State prison	540
51	Somerset County Detention Center	Somerset County	MD'	County jail	282
52	Austin County Jail	Austin County	TX	County complex	460
53	Mabel Bassett Correctional Center	Oklahoma City	OK	State prison	418
56	Mat-su Pre-Trial Facility	Palmer	AK	State prison	68
58	Torrance Police Department	Torrance	CA	City complex	152
61	Augusta County Jail	Augusta County	VA	County jail	546
61	Fayette County Detention Center	Fayette County	TX	County complex	484
61	Ohio County Correctional Center	Ohio County/Wheeling	WV	County and city complex	568
62	Orange Street Community Correctional Center	Salt Lake City	UT	State correctional facility	534
64	Delaware Correctional Center (Maximum Security)	Smyrna	DE	State prison	176
64	Orange County Jail	Orange County	TX	County complex	514
68	Masten Park Secure Center	Buffalo	NY	State center for youth	378
68	Santa Barbara County Main Jail	Santa Barbara County	CA	County jail	138
68	Uintah County Jail	Uintah County	UT	County jail	536
72	Fairbanks Correctional Center	Fairbanks	AK	State prison	64
74	Ashtabula County Justice Center	Ashtabula County	OH	County complex	392
75	Chambers County Law Enforcement Center	Chambers County	TX	County complex	472
75	Feliciana Forensic Facility	Jackson	LA	State complex	262
76	Warren County Correctional Center	Warren County	NJ	County jail	348
78	Craven County Law Enforcement Center	Craven County	NC	County complex	384
78	Wayne County Justice Center	Wayne County	OH	County complex	408
80	Kay County Detention Facility	Kay County	OK	County complex	412
83	Maui Community Correctional Center	Maui County/Wailuku	HI	County and city jails/State	206
				prison	206
87	Hennepin County Juvenile Detention Center	Hennepin County	MN	Juvenile detention facility	298
87	Liberty County Jail	Liberty County	TX	County complex	508
90	Lexington Assessment & Reception Center (Addition)	Lexington	OK	State prison	414
90	Ouachita Correctional Center	Hodgen	OK	State prison	424
94	Foothill Communities Law & Justice Center	San Bernardino County	CA	County complex	118
94	State Prison of Southern Michigan	Jackson	MI	State prison hospital	296
96	Dwight Correctional Center (1984 Addition)	Dwight	IL	State prison	222
96	Garland County Detention Facility	Garland County	AR	County jail	100
96	Gilliam Psychiatric Center	Columbia	SC	State prison	450
96	Mountain View Unit	Gatesville	TX	State prison	512
96	Santa Cruz County Jail (Phase I)	Santa Cruz County	CA	County jail	140
96	St. Johnsbury Community Correctional Center	St. Johnsbury County	VT	County jail/State prison	542
98	Federal Correctional Institution	Tallahassee	FL	Federal prison	180
98	Yukon-Kuskokwim Correctional Center	Bethel	AK	State prison	76
99	Jackson County Adult Detention Center	Jackson County	MS	County jail	302
100	Bridgeport Correctional Center: Modular Units	Bridgeport	CT	State prison	172
100	Dixon Correctional Institute	Jackson	LA	State prison	258
100	Dwight Correctional Center (1979 Addition)	Dwight	IL	State prison	220
100	Federal Correctional Institution	Ashland	KY	Federal prison	254
100	Leon County Jail	Leon County	FL	County jail	182
100	Louisiana Correctional Institute for Women	St. Gabriel	LA	State prison	266
100	Youth Diagnostic and Development Center	Albuquerque	NM	Youth detention facility	360
103	Benton County Justice Center	Benton County	WA	County complex	554
104	Bexar County Juvenile Center	Bexar County	TX	County complex	466
104	J. Bernard Gates Correctional Unit	Niantic	CT	State jail	174

Inmates	Facility name	County/City	State	Facility type	Page
104	Palmer Correctional Center Medium Security Facility	Palmer	AK	State prison	72
108	Woodbury Law Enforcement Center	Woodbury County	IA	County complex	246
109	Hunt County Criminal Justice Center	Hunt County	TX	County complex	500
112	Myrtle Beach Law Enforcement Center	Myrtle Beach	SC	City complex	454
120	Nashville Community Service Center	Nashville	TN	State prison	456
123	Starr County Jail	Starr County	TX	County jail	522
124	Washington Corrections Center Intensive Management				
	Unit	Shelton	WA	State prison	564
125	Longwood Treatment Center	Jamaica Plain	MA	State treatment facility	286
126	Grand Traverse County Correctional Facility	Grand Traverse County/			
		Traverse City	MI	County and city complex	292
126	Santa Rosa County Jail	Santa Rosa County	FL	County complex	192
127	Fort Bend County Jail (Expansion)	Fort Bend County	TX	County jail	492
128	Kings County Branch Jail	Kings County	CA	County jail	120
131	Montgomery County Detention Center	Montgomery County	MD	County complex	278
132	Clarke County Correctional Institution	Clarke County	GA	County jail	200
132	San Patricio County Sheriff's Department	San Patricio County	TX	County complex	518
132	Victoria County Jail	Victoria County	TX	County complex	526
133	Clermont County Jail	Clermont County	OH	County jail	394
134	Cleveland County Detention Center	Cleveland County	OK	County complex	410
134	Yuba County Jail	Yuba County	CA	County jail	156
136	Muskogee County/City Detention Facility	Muskogee County/			
		Muskogee	OK	County and city jails	420
139	Sonoma North County Detention Facility	Sonoma County	CA	County jail	146
140	Schuylkill County Prison	Schuylkill County	PA	County jail	438
141	Blair County Prison	Blair County	PA	County jail	432
144	Pinal Mountain Juvenile Institution	Gila	AZ	Juvenile correctional facility	92
144	TDC Hospital at Galveston	Galveston	TX	State prison hospital	524
150	Lycoming County Prison	Lycoming County	PA	County jail	434
152	Washington County Detention Center	Washington County	MD	County jail	284
158	Thurston County Corrections Facility	Thurston County	WA	County complex	560
160	Correction Camp Cusino	Shingleton	MI	State prison	290
160	Hiland Mountain Correctional Center	Eagle River	AK	State prison	66
161	Clay County Detention Center	Clay County	MO	County jail	308
162	Cochise County Jail	Cochise County	ΑZ	County jail	82
164	Minnesota Supervised Living Facility	St. Peter	MN	State prison	300
166	Fort Bend County Jail	Fort Bend County	TX	County complex	490
174	Yellowstone County Detention Facility	Yellowstone County	MT	County complex	326
176	Westside Police Area Command Station	Houston	TX	City complex	532
180	Lacy Security Facility	Orange County	CA	County jail	122
180	State Regional Correctional Facility at Mercer	Mercer	PA	State prison	442
183	Jackson County Jail	Jackson County	OR	County jail	426
184	Comal County Jail	Comal County	TX	County complex	476
184	Cummins Unit—Medium Security	Grady	AR	State prison	98
184	Hidalgo County Jail	Hidalgo County	TX	County jail	498
190	Federal Correctional Institution	Tucson	ΑZ	Federal prison	86
190	Shawnee County Department of Corrections	Shawnee County	KS	County complex	252
194	Pinellas County Jail—Medium Security Facility	Pinellas County	FL	County jail	190
196	Elmwood—Barracks 24	Santa Clara County	CA	County jail	116
198	Harris County Juvenile Detention Home	Harris County	TX	County complex	496

Inmates	Facility name	County/City	State	Facility type	Page
200	East Moline Correctional Center	East Moline	IL	State prison	224
200	Rock Island County Jail	Rock Island County	IL	County complex	234
200	Wildwood Correctional Center	Kenai	AK	State prison	74
201	Roanoke City Jail	Roanoke	VA	City complex	552
204	Douglas County Correctional Center	Douglas County	NE	County jail	330
209	Ocean County Justice Complex	Ocean County	NJ	County complex	342
210	Polk County Jail	Polk County	IA	County jail	244
212	Placer County Jail	Placer County	CA	County complex	128
228	Cook Inlet Pre-Trial Facility	Anchorage	AK	State detention facility	60
240	Richmond County Law Enforcement and Justice Center	Richmond County	GA	County complex	204
250	Shasta County Justice Center	Shasta County	CA	County complex	144
252	Brazoria County Sheriff's Department Detention Center II	Brazoria County	TX	County jail	468
258	Western New Mexico Correctional Facility	Grants	NM	State prison	358
264	Fulton Reception and Diagnostic Center, Phase I	Fulton	MO	State prison	312
264	Smith County Jail	Smith County	TX	County jail	. 520
274	Allegheny County Jail Annex	Allegheny County	,PA	County jail	430
282	Pima County Adult Detention Center	Pima County	AZ	County jail	90
288	Kansas State Penitentiary (Phase One)	Lansing	KS	State prison	250
289	Cameron County Detention Center	Cameron County	TX	County jail	470
292	Alachua County Corrections Facility	Alachua County	FL	County jail	178
292	Young Adult Correctional Facility	Draper	UT	State prison	538
300	Bernalillo County Detention Center	Bernalillo County	NM	County jail	350
300	Fairfax County Adult Detention Center and Pre-Release Center	Fairfax County	VA	County complex	548
312	Oshkosh Correctional Institution	Oshkosh	WI	State prison	574
320	Nebraska State Penitentiary	Lincoln	NE	State prison	332
324	Federal Correctional Institution	Talladega	AL	Federal prison	54
330	Middlesex County Correctional Facility	Middlesex County	NJ	County jail	340
336	Union Correctional Institution	Raiford	FL	State prison	198
337	Marion County Jail	Marion County	IN	County complex	242
345	Peoria County Adult Detention and Work Release Facility	Peoria County	IL	County complex	232
346	Alexandria Detention Center	Alexandria	VA	City complex	544
354	DuPage County Jail and Sheriff's Department	DuPage County	IL	County complex	218
356	Kirby Forensic Psychiatric Center	New York	NY	State treatment center	376
368	Gerald L. Gormley Justice Facility	Atlantic City	NJ	County complex	338
384	Baltimore City Correctional Center	Baltimore	MD	State prison	272
386	Contra Costa County Detention Facility	Contra Costa County	CA	County complex	114
390	Marion County Detention Center	Marion County	FL	County jail	186
402	Erie County Correctional Facility	Erie County	NY	County jail	368
402	Ohio Reformatory for Women	Marysville	OH	State prison	402
428	Lexington Assessment & Reception Center, Phase I and II	Lexington	OK	State prison	416
430	Justice Center	Multnomah County	OR	County complex	428
434	Pre-Trial Detention Facility	Ventura County	CA	County complex	132
436	Sequoia Field Detention Facility	Tulare County	CA	County jail	142
448	Diagnostic Unit	Huntsville	TX	State prison	480
463	Macomb County Jail	Macomb County	MI	County jail	294
480	Southern New Mexico Correctional Facility	Las Cruces	NM	State prison	356
485	Adams County Detention Facility	Adams County	CO	County jail	158
486	Central New Mexico Correctional Facility	Los Lunas	NM	State prison	352
488	Eastern Correctional Center	Maury	NC	State prison	386

Inmates	Facility name	County/City	State	Facility type	Page
488	Southern Correctional Center	Troy	NC	State prison	390
492	Maximum Security Unit, Tucker Unit	Tucker	AR	State prison	102
499	Camden County Correctional Facility	Camden County	NJ	County jail	336
499	Pima County Adult Detention Center	Pima County	AZ	County jail	88
500	Federal Correctional Institution	Otisville	NY	Federal prison	372
500	Oklahoma State Penitentiary	McAlester	OK	State prison	422
501	Federal Correctional Institution	Bastrop	TX	Federal prison	486
511	Columbia Correctional Institution	Portage	WI	State prison	572
516	Erie County Holding Center	Erie County	NY	County jail	370
520	Jackson County Detention Center	Jackson County	MO	County complex	314
524	Cook County Medical and Psychiatric Facility—				
	RTU Building	Cook County	IL	County jail	210
534	Federal Correctional Institution	Ray Brook	NY	Federal prison	374
540	Arizona State Prison—Florence	Florence	AZ	State prison	78
545	Twin Rivers Corrections Center	Monroe	WA	State prison	562
560	Missouri Eastern Correctional Center	Pacific	MO	State prison	316
560	State Correctional Institution at Smithfield	Huntingdon	PA	State prison	440
575	Federal Correctional Institution	Phoenix	AZ	Federal prison	84
576	Penitentiary of New Mexico	Santa Fe	NM	State prison	354
588	North Carolina Central Prison	Raleigh	NC	State prison	388
596	Alameda County North County Jail	Alameda County	CA	County jail	106
596	Prince George's County Correctional Center	Prince George's County	MD	County jail	280
623	Jefferson County Jail	Jefferson County	AL	County jail	56
624	South Florida Reception Center	Miami	FL	State prison	196
650	Philadelphia Industrial Correctional Center	Philadelphia County/			
		Philadelphia	PA	County and city jails	436
656	Ferguson Unit	Midway	TX	State prison	488
696	Lieber Correctional Institution	Ridgeville	SC	State prison	452
739	Seminole County Correctional Facility	Seminole County	FL	County jail	194
742	Arkansas Valley Correctional Facility	Crowley	CO	State prison	162
744	Hunt Correctional Center	St. Gabriel	LA	State prison	264
786	Graham Correctional Center	Hillsboro	IL	State prison	226
800	Centralia Correctional Center	Centralia	IL	State prison	208
800	North Facility	New York	NY	City jail	380
810	Brooklyn Correctional Facility	New York	NY	City jail	364
837	Trenton State Prison	Trenton	NJ	State prison	346
848	Hamilton County Justice Complex	Hamilton County	OH	County complex	396
850	Clark County Detention Center	Clark County	NV	County jail	334
907	Federal Detention Center	Oakdale	LA	Federal complex	260
926	Shawnee Correctional Center	Vienna	IL	State prison	236
929	Martin Correctional Institution	Indiantown	FL	State prison	188
941	Danville Correctional Center	Danville	IL	State prison	212
994	West Jefferson Correctional Facility	Bessemer	AL	State prison	58
1,000	California Correctional Institution	Tehachapi	CA	State prison	108
1,034	Madison Correctional Institution	London	OH	State prison	400
1,060	Jester Unit Number 3	Richmond	TX	State prison	502
1,100	Farmington Correctional Center	Farmington	MO	State prison	310
1,101	Wallace Pack Unit I	Navasota	TX	State prison	528
1,103	Beto II Unit	Palestine	TX	State prison	464
1,106	Southern State Correctional Facility: Modular Units (Phase I and II)	Delmont	NJ	State prison	344

Inmates	Facility name	County/City	State	Facility type	Page
1,139	Orange County Sheriff's Intake Release Center	Orange County	CA	County jail	126
1,162	Lew Sterrett Justice Center	Dallas County/Dallas	TX	County and city jails	506
1,182	Washington Correctional Institute	Angie	LA	State prison	268
1,200	Arizona State Prison—Perryville	Goodyear	AZ	State prison	80
1,224	Shelby County Justice Center	Shelby County/Memphis	TN	County and city complex	458
1,274	Ross Correctional Institution	Chillicothe	OH	State prison	406
1,344	Darrington Unit	Rosharon	TX	State prison	478
1,364	Wallace Pack Unit II	Navasota	TX	State prison	530
1,440	Eastern Correctional Institution	Westover	MD	State prison	276
1,576	Mississippi State Penitentiary—Unit 29	Parchman	MS	State prison	304
1,900	Rikers Island: Modular Units	New York	NY	City jail	382
2,200	Richard J. Donovan Correctional Facility at Rock				
	Mountain	San Diego	CA	State prison	134
2,358	Ellis II Unit (Phase I and II)	Huntsville	TX	State prison	482
2,404	California Medical Facility—South	Vacaville	CA	State prison	110
3,264	California State Prison—Sacramento County/Folsom	Represa	CA	State prison	112
3,783	Coffield Unit	Tennessee Colony	TX	State prison	474
4,188	Beto I Unit	Tennessee Colony	TX	State prison	462

Category	State	Facility name	Facility type	Page
Expansion project	AK	Cook Inlet Pre-Trial Facility Phase II	State pre-trial facility	62
Expansion project	AK	Fairbanks Correctional Center	State prison	64
Expansion project	AR	Cummins Unit—Medium Security	State prison	98
Expansion project	AR	Clark County Detention Facility	County complex	96
Expansion project	AZ	Arizona State Prison—Perryville	State prison	80
Expansion project	CA	Orange County Sheriff's Intake Release Center	County jail	126
Expansion project	CA	San Joaquin County Honor Farm Women's Minimum Security Facility	County jail	136
Expansion project	CA	Santa Barbara County Main Jail	County jail	138
Expansion project	CO	Garfield County Jail	County jail	166
Expansion project	FL	Alachua County Corrections Facility	County jail	178
Expansion project	FL	Leon County Jail	County jail	182
Expansion project	FL	Santa Rosa County Jail	County complex	192
Expansion project	GA	Dooly County Jail	County jail	202
Expansion project	MD	Montgomery County Detention Center	County complex	278
Expansion project	MI	Grand Traverse County Correctional Facility	County and city complex	292
Expansion project	MI	Macomb County Jail	County jail	294
Expansion project	MT	Pondera County Jail	County complex	324
Expansion project	NM	Youth Diagnostic and Development Center—Phase III	Youth detention facility	362
Expansion project	NY	Erie County Holding Center	County jail	370
Expansion project	NY	Masten Park Secure Center	State secure center for	2,70
			youth	378
Expansion project	OK	Oklahoma State Penitentiary	State prison	422
Expansion project	PA	Blair County Prison	County jail	432
Expansion project	TX	Darrington Unit	State prison	478
Expansion project	TX	Ferguson Unit	State prison	488
Expansion project	TX	Fort Bend County Jail	County jail	490
Expansion project	TX	Harris County Juvenile Detention Home	County complex	496
Expansion project	TX	Hidalgo County Jail	County jail	498
Expansion project	TX	Liberty County Jail	County complex	508
Expansion project	VA	Augusta County Jail	County jail	546
Expansion project	VA	Fairfax County Adult Detention Center and Pre-Release		
		Center	County complex	548
Expansion project	VT	Northwest State Correctional Facility	State prison	540
Expansion project	WA	Thurston County Corrections Facility	County complex	560
New, ancillary building	AK	Hiland Mountain Correctional Center	State prison	66
New, ancillary building	AK	Meadow Creek Correctional Center	State prison	70
New, ancillary building	AZ	Arizona State Prison—Florence	State prison	78
New, ancillary building	AZ	Pima County Adult Detention Center	County jail	90
New, ancillary building	AZ	Sacaton Juvenile Rehabilitation Center	Juvenile rehabilitation center	94
New, ancillary building	CA	Elmwood—Barracks 24	County jail	116
New, ancillary building	CA	Lacy Security Facility	County jail	122
New, ancillary building	CA	Orange County Sheriff's Intake Release Center	County jail	126
New, ancillary building	CA	Placer County Jail	County complex	128
New, ancillary building	CA	Sonoma North County Detention Facility	County jail	146
New, ancillary building	CO	Delta County Criminal Justice Facility	County complex	164
New, ancillary building	CO	Pitkin County Jail	County complex	168
New, ancillary building	CT	Bridgeport Correctional Center: Modular Units	State prison	172
New, ancillary building	CT	J. Bernard Gates Correctional Unit	State jail	174
New, ancillary building	DE	Delaware Correctional Center (Maximum Security)	State prison	176

Category	State	Facility name	Facility type	Page
New, ancillary building	FL	Leon County Justice Complex	County complex	184
New, ancillary building	FL	Pinellas County Jail—Medium Security Facility	County jail	190
New, ancillary building	FL	Seminole County Correctional Facility	County jail	194
New, ancillary building	FL	Union Correctional Institution	State prison	198
New, ancillary building	HI	Maui Community Correctional Center	County and city jails/State	
			prison	206
New, ancillary building	IL	Centralia Correctional Center	State prison	208
New, ancillary building	IL	Cook County Medical and Psychiatric Facility— RTU Building	County jail	210
New, ancillary building	IL	Dixon Correctional Center	State prison	214
New, ancillary building	IL	Dwight Correctional Center (1979 Addition)	State prison	220
New, ancillary building	IL	Dwight Correctional Center (1984 Addition)	State prison	222
New, ancillary building	IL	East Moline Correctional Center	State prison	224
New, ancillary building	IL	Graham Correctional Center	State prison	226
New, ancillary building	IL	Illinois Youth Center—Kankakee (Dining Facility)	Juvenile correctional	220
<b>37</b>	**		facility	228
New, ancillary building	IL	Illinois Youth Center—Kankakee (Housing Unit)	Juvenile correctional	220
<b>ST</b> 211 1 21 12	**		facility	230
New, ancillary building	IL V	Shawnee Correctional Center	State prison	236
New, ancillary building	IL	Sheridan Correctional Center (Kitchen/Dining Facility)	State prison	238
New, ancillary building	IL	Sheridan Correctional Center (Medical/Security	2 mil F1-10-11	
		Services)	State prison	240
New, ancillary building	IN	Marion County Jail	County complex	242
New, ancillary building	KS	Kansas State Penitentiary (Phase One)	State prison	250
New, ancillary building	KY	Federal Correctional Institution	Federal prison	254
New, ancillary building	LA	Feliciana Forensic Facility	State complex	262
New, ancillary building	LA	Hunt Correctional Center	State prison	264
New, ancillary building	LA	Louisiana Correctional Institute for Women	State prison	266
New, ancillary building	MA	Massachusetts Correctional Institution Norfolk	State prison	288
New, ancillary building	MD	Baltimore City Jail	City jail	274
New, ancillary building	MI	State Prison of Southern Michigan	State prison hospital	296
New, ancillary building	MN	Minnesota Supervised Living Facility	State prison	300
New, ancillary building	MO	Farmington Correctional Center	State prison	310
New, ancillary building	MT	Jefferson County Criminal Justice Center	County complex	320
New, ancillary building	NC	North Carolina Central Prison	State prison	388
New, ancillary building	NE	Nebraska State Penitentiary	State prison	332
New, ancillary building	NJ	Trenton State Prison	State prison	346
New, ancillary building	NM	Youth Diagnostic and Development Center—Phase III	Youth detention facility	362
New, ancillary building	NY	Rikers Island: Modular Units	City jail	382
New, ancillary building	OH	Ohio Reformatory for Women	State prison	402
New, ancillary building	OK	Lexington Assessment & Reception Center	State prison	414
New, ancillary building	OK	Mabel Bassett Correctional Center	State prison	418
New, ancillary building	OK	Oklahoma State Penitentiary	State prison	422
New, ancillary building	OK	Ouachita Correctional Center	State prison	424
New, ancillary building	PA	State Regional Correctional Facility at Mercer	State prison	442
New, ancillary building	SC	Gilliam Psychiatric Center	State prison	450
New, ancillary building	TN	Nashville Community Service Center	State prison	456
New, ancillary building	TX	Darrington Unit	State prison	478
New, ancillary building	TX	Diagnostic Unit	State prison	480
New, ancillary building	TX	Mountain View Unit	State prison	512 514
New, ancillary building New, ancillary building	TX TX	Orange County Jail	County complex	514 526
riew, andmary building	17	Victoria County Jail	County complex	526

Category	State	Facility name	Facility type	Page
New, ancillary building	WA	Forks City Jail	City complex	556
New, ancillary building	WA	Washington Corrections Center Intensive Management Unit	State prison	564
New, independent facility	AK	Cook Inlet Pre-Trial Facility	State detention facility	60
New, independent facility	AK	Mat-su Pre-Trial Facility	State prison	68
New, independent facility	AK	Palmer Correctional Center Medium Security Facility	State prison	72
New, independent facility	AK	Yukon-Kuskokwim Correctional Center	State prison	76
New, independent facility	AL	Federal Correctional Institution	Federal prison	54
New, independent facility	AL	Jefferson County Jail	County jail	56
New, independent facility	AL	West Jefferson Correctional Facility	State prison	58
New, independent facility	AR	Garland County Detention Facility	County jail	100
New, independent facility	AR	Maximum Security Unit, Tucker Unit	State prison	102
New, independent facility	AR	Saline County Detention Facility	County jail	104
New, independent facility	AZ	Arizona State Prison—Perryville	State prison	80
New, independent facility	AZ	Cochise County Jail	County jail	82
New, independent facility	ΑZ	Federal Correctional Institution (Phoenix)	Federal prison	84
New, independent facility	AZ	Federal Correctional Institution (Tucson)	Federal prison	86
New, independent facility	AZ	Pima County Adult Detention Center	County jail	88
New, independent facility	ΑZ	Pinal Mountain Juvenile Institution	Juvenile correctional	
•			facility	92
New, independent facility	CA	Alameda County North County Jail	County jail	106
New, independent facility	CA	California Correctional Institution	State prison	108
New, independent facility	CA	California Medical Facility—South	State prison	110
New, independent facility	CA	California State Prison—Sacramento County/Folsom	State prison	112
New, independent facility	CA	Contra Costa County Detention Facility	County complex	114
New, independent facility	CA	Foothill Communities Law & Justice Center	County complex	118
New, independent facility	CA	Kings County Branch Jail	County jail	120
New, independent facility	CA	Pre-Trial Detention Facility	County complex	132
New, independent facility	CA	Richard J. Donovan Correctional Facility at Rock Mountain	State prison	124
New independent feeility	CA	Santa Cruz County Jail (Phase I)	_	134
New, independent facility New, independent facility	CA CA	Sequoia Field Detention Facility	County jail County jail	140 142
New, independent facility	CA	Shasta County Justice Center	County jan  County complex	142
=	CA	•	County complex	144
New, independent facility	CA	Sunnyvale Public Safety Building and Temporary Holding Facility	City complex	150
New, independent facility	CA	Torrance Police Department	City complex	152
New, independent facility	CO	Adams County Detention Facility	County jail	158
New, independent facility	CO	Alamosa County Law Enforcement Center	County complex	160
New, independent facility	CO	Arkansas Valley Correctional Facility	State prison	162
New, independent facility	CO	Summit County Justice Center	County complex	170
New, independent facility	FL	Marion County Detention Center	County jail	186
New, independent facility	FL	Martin Correctional Institution	State prison	188
New, independent facility	FL	South Florida Reception Center	State prison	196
New, independent facility	GA	Clarke County Correctional Institution	County jail	200
New, independent facility	GA	Richmond County Law Enforcement and Justice Center	County complex	204
New, independent facility	IA	Polk County Jail	County jail	244
New, independent facility	IA	Woodbury Law Enforcement Center	County complex	246
New, independent facility	IL	Danville Correctional Center	State prison	212
New, independent facility	IL.	Douglas County Jail	County complex	216
New, independent facility	IL	DuPage County Jail and Sheriff's Department	County complex	218
New, independent facility	IL	Peoria County Adult Detention and Work Release		
		Facility	County complex	232

Category	State	Facility name	Facility type	Page
New, independent facility	IL	Rock Island County Jail	County complex	234
New, independent facility	KS	Johnson County Juvenile Hall	Juvenile detention	
			facility	248
New, independent facility	KS	Shawnee County Department of Corrections	County complex	252
New, independent facility	KY	Knox County Jail	County jail	256
New, independent facility	LA	Federal Detention Center	Federal complex	260
New, independent facility	LA	Washington Correctional Institute	State prison	268
New, independent facility	MD	Baltimore City Correctional Center	State prison	272
New, independent facility	MD	Eastern Correctional Institution	State prison	276
New, independent facility	MD	Prince George's County Correctional Center	County jail	280
New, independent facility	MD	Somerset County Detention Center	County jail	282
New, independent facility	MD	Washington County Detention Center	County jail	284
New, independent facility	ME	Franklin County Detention/Law Enforcement Facility	County complex	270
New, independent facility	MI	Correction Camp Cusino	State prison	290
New, independent facility	MN	Hennepin County Juvenile Detention Center	Juvenile detention	
			facility	298
New, independent facility	MO	Clay County Detention Center	County jail	308
New, independent facility	MO	Fulton Reception and Diagnostic Center, Phase I	State prison	312
New, independent facility	MO	Jackson County Detention Center	County complex	314
New, independent facility	MO	Missouri Eastern Correctional Center	State prison	316
New, independent facility	MS	Jackson County Adult Detention Center	County jail	302
New, independent facility	MS	Mississippi State Penitentiary—Unit 29	State prison	304
New, independent facility	MS	Tunica County Jail and Sheriff's Department	County complex	306
New, independent facility	MT	Chouteau County Law Enforcement Facility	County complex	318
New, independent facility	MT	Lewis and Clark County Criminal Justice Facility	County complex	322
New, independent facility	MT	Yellowstone County Detention Facility	County complex	326
New, independent facility	NC	Craven County Law Enforcement Center	County complex	384
New, independent facility	NC	Eastern Correctional Center	State prison	386
New, independent facility	NC	Southern Correctional Center	State prison	390
New, independent facility	NE	Dodge County Judicial Center	County complex	328
New, independent facility	NE	Douglas County Correctional Center	County jail	330
New, independent facility	NJ	Camden County Correctional Facility	County jail	336
New, independent facility	NJ	Gerald L. Gormley Justice Facility	County complex	338
New, independent facility	NJ	Middlesex County Correctional Facility	County jail	340
New, independent facility	NJ	Ocean County Justice Complex	County complex	342
New, independent facility	NJ	Southern State Correctional Facility: Modular Units		
		(Phase I and II)	State prison	344
New, independent facility	NJ	Warren County Correctional Center	County jail	348
New, independent facility	NM	Bernalillo County Detention Center (South Tower)	County jail	350
New, independent facility	NM	Central New Mexico Correctional Facility	State prison	352
New, independent facility	NM	Penitentiary of New Mexico	State prison	354
New, independent facility	NM	Southern New Mexico Correctional Facility	State prison	356
New, independent facility	NM	Western New Mexico Correctional Facility	State prison	358
New, independent facility	NM	Youth Diagnostic and Development Center	Youth detention facility	360
New, independent facility	NV	Clark County Detention Center	County jail	334
New, independent facility	NY	Erie County Correctional Facility	County jail	368
New, independent facility	NY	Federal Correctional Institution (Otisville)	Federal prison	372
New, independent facility	NY	Federal Correctional Institution (Ray Brook)	Federal prison	374
New, independent facility	NY	North Facility	City jail	380
New, independent facility	ОН	Ashtabula County Justice Center	County complex	392

Category	State	Facility name	Facility type	Page
New, independent facility	ОН	Clermont County Jail	County jail	394
New, independent facility	OH	Hamilton County Justice Complex	County complex	396
New, independent facility	ОН	Logan County Jail and Office Complex	County complex	398
New, independent facility	OH	Madison Correctional Institution	State prison	400
New, independent facility	OH	Ottawa County Detention Facility	County complex	404
New, independent facility	OH	Ross Correctional Institution	State prison	406
New, independent facility	OH	Wayne County Justice Center	County complex	408
New, independent facility	OK	Cleveland County Detention Center	County complex	410
New, independent facility	OK	Kay County Detention Facility	County complex	412
New, independent facility	OK	Lexington Assessment & Reception Center, Phase I and II	State prison	416
New, independent facility	OK	Muskogee County/City Detention Facility	County and city jails	420
New, independent facility	OR	Jackson County Jail	County jail	426
New, independent facility	OR	Justice Center	County complex	428
New, independent facility	PA	Lycoming County Prison	County jail	434
New, independent facility	PA	Philadelphia Industrial Correctional Center	County and city jails	436
New, independent facility	PA	Schuylkill County Prison	County jail	438
New, independent facility	PA	State Correctional Institution at Smithfield	State prison	440
New, independent facility	PA	Warren County Jail	County jail	444
New, independent facility	PA	Wyoming County Jail	County jail	446
New, independent facility	SC	Lieber Correctional Institution	State prison	452
New, independent facility	SC	Myrtle Beach Law Enforcement Center	City complex	454
New, independent facility	TN	Shelby County Justice Center	County complex	458
New, independent facility	TX	Austin County Jail	County complex	460
New, independent facility	TX	Beto I Unit	State prison	462
New, independent facility	TX	Beto II Unit	State prison	464
New, independent facility	TX	Bexar County Juvenile Center	County complex	466
New, independent facility	TX	Brazoria County Sheriff's Department Detention Center II	County jail	468
New, independent facility	TX	Cameron County Detention Center	County jail	470
New, independent facility	TX	Chambers County Law Enforcement Center	County complex	472
New, independent facility	TX	Coffield Unit	State prison	474
New, independent facility	TX	Comal County Jail	County complex	476
New, independent facility	TX	Ellis II Unit (Phase I and II)	State prison	482
New, independent facility	TX	Fayette County Detention Center	County complex	484
New, independent facility	TX	Federal Correctional Institution	Federal prison	486
New, independent facility	TX	Fort Bend County Jail	County complex	490
New, independent facility	TX	Freeport Police and Courts Building	City complex	494
New, independent facility	TX	Hunt County Criminal Justice Center	County complex	500
New, independent facility	TX	Jester Unit Number 3	State prison	502
New, independent facility	TX	Katy Police Department	City complex	504
New, independent facility	TX	Lew Sterrett Justice Center	County and city jails	506
New, independent facility	TX	Missouri City Police Department	City complex	510
New, independent facility	TX	Pearland Public Safety Building	City complex	516
New, independent facility	TX	San Patricio County Sheriff's Department	County complex	518
New, independent facility	TX	Smith County Jail	County jail	520
New, independent facility	TX	Starr County Jail	County jail	522
New, independent facility	TX	TDC Hospital at Galveston	State prison hospital	524
New, independent facility	TX	Wallace Pack Unit I	State prison	528
New, independent facility	TX	Wallace Pack Unit II	State prison	530

Category	State	Facility name	Facility type	Page
New, independent facility	TX	Westwide Police Area Command Station	City complex	532
New, independent facility	UT	Orange Street Community Correctional Center	State correctional facility	534
New, independent facility	UT	Uintah County Jail	County jail	536
New, independent facility	UT	Young Adult Correctional Facility	State prison	538
New, independent facility	VA	Alexandria Detention Center	City complex	544
New, independent facility	VA	Pittsylvania County Jail	County jail	550
New, independent facility	VA	Roanoke City Jail	City complex	552
New, independent facility	VT	St. Johnsbury Community Correctional Center	County jail/State prison	542
New, independent facility	WA	Benton County Justice Center	County complex	554
New, independent facility	WA	Jefferson County Correctional Facility	County complex	558
New, independent facility	WA	Twin Rivers Corrections Center	State prison	562
New, independent facility	WA	Whitman County Correctional Facility	County complex	566
New, independent facility	WI	Burnett County Government Center	County complex	570
New, independent facility	WI	Columbia Correctional Institution	State prison	572
New, independent facility	WI	Oshkosh Correctional Institution	State prison	574
New, independent facility	WI	Rusk County Law Enforcement Facility	County complex	576
New, independent facility	WV	Ohio County Correctional Center	County and city complex	568
Phased project (future)	CA	Placer County Jail	County complex	128
Phased project (future)	CA	Sonoma North County Detention Facility	County jail	146
Phased project (future)	CO	Pitkin County Jail	County complex	168
Phased project (future)	KS	Kansas State Penitentiary (Phase One)	State prison	250
Phased project (future)	OH	Ottawa County Detention Facility	County complex	404
Phased project (future)	MI	Correction Camp Cusino	State prison	290
Phased project (future)	PA	Philadelphia Industrial Correctional Center	County and city jails	436
Phased project (future)	TX	Lew Sterrett Justice Center	County and city jails	506
Phased project (future)	TX	Orange County Jail	County complex	514
Phased project (future)	TX	Victoria County Jail	County complex	526
Phased project (future)	VA	Roanoke City Jail	City complex	552
Phased project (past)	AK	Cook Inlet Pre-Trial Facility Phase II	State pre-trial facility	62
Phased project (past)	AZ	Arizona State Prison—Perryville	State prison	80
Phased project (past)	NY	Elmira Correctional & Reception Center Food Service & Dining Facility	State prison	266
Dhacad project (past)	SC	Clemson Police Department	City complex	366
Phased project (past)	AK	Fairbanks Correctional Center	State prison	448 64
Remodeling/renovation Remodeling/renovation	AK	Wildwood Correctional Center	State prison	74
Remodeling/renovation	AR	Cummins Unit—Medium Security	State prison	98
Remodeling/renovation	CA	Nevada County Detention Center	Restitution center	124
Remodeling/renovation	CA	Orange County Sheriff's Intake Release Center	County jail	124
Remodeling/renovation	CA	Plumas County Sheriff's Department & Detention		
D 111 / /	C.A	Facility	County jail	130
Remodeling/renovation	CA	Sonoma North County Detention Facility	County jail	146
Remodeling/renovation	CA	Stanislaus County Jail	County complex	148
Remodeling/renovation	CA	Tuolumne County Jail	County jail	154
Remodeling/renovation	CA	Yuba County Jail	County jail	156
Remodeling/renovation	FL	Alachua County Corrections Facility	County jail	178
Remodeling/renovation	FL	Santa Rosa County Jail	County complex	192
Remodeling/renovation	FL	Seminole County Correctional Facility	County jail	194
Remodeling/renovation	IN	Marion County Jail	County complex	242
Remodeling/renovation	LA	Dixon Correctional Institute	State prison	258
Remodeling/renovation	MA	Longwood Treatment Center	Treatment facility	286

Category	State	Facility name	Facility type	Page
Remodeling/renovation	MD	Montgomery County Detention Center	County complex	278
Remodeling/renovation	MI	Grand Traverse County Correctional Facility	County and city complex	292
Remodeling/renovation	MI	Macomb County Jail	County jail	294
Remodeling/renovation	MO	Farmington Correctional Center	State prison	310
Remodeling/renovation	MT	Pondera County Jail	County complex	324
Remodeling/renovation	NJ	Trenton State Prison	State prison	346
Remodeling/renovation	NY	Brooklyn Correctional Facility	City jail	364
Remodeling/renovation	eling/renovation NY Elmira Correctional & Reception Center Food Service &			
		Dining Facility	State prison	366
Remodeling/renovation	NY	Erie County Holding Center	County jail	370
Remodeling/renovation	NY	Kirby Forensic Psychiatric Center	State treatment center	376
Remodeling/renovation	NY	Masten Park Secure Center	State center for youth	378
Remodeling/renovation	OK	Oklahoma State Penitentiary	State prison	422
Remodeling/renovation	PA	Allegheny County Jail Annex	County jail	430
Remodeling/renovation	PA	Schuylkill County Prison	County jail	438
Remodeling/renovation	SC	Clemson Police Department	City complex	448
Remodeling/renovation	TX	Darrington Unit	State prison	478
Remodeling/renovation	TX	Ferguson Unit	State prison	488
Remodeling/renovation	TX	Harris County Juvenile Detention Home	County complex	496
Remodeling/renovation	TX	Liberty County Jail	County complex	508
Remodeling/renovation	WA	Thurston County Corrections Facility	County complex	560
Temporary housing	AZ	Arizona State Prison—Perryville	State prison	80
Temporary housing	CA	Placer County Jail	County complex	128
Temporary housing	CT	J. Bernard Gates Correctional Unit	State jail	174
Temporary housing	FL	Alachua County Corrections Facility	County jail	178

Facility name Index

Facility name	State	Facility type	Page
Adams County Detention Facility	CO	County jail	158
Alachua County Corrections Facility	FL	County jail	178
Alameda County North County Jail	CA	County jail	106
Alamosa County Law Enforcement Center	CO	County complex	160
Alexandria Detention Center	VA	City complex	544
Allegheny County Jail Annex	PA	County jail	430
Arizona State Prison—Florence	ΑZ	State prison	78
Arizona State Prison—Perryville	ΑZ	State prison	80
Arkansas Valley Correctional Facility	CO	State prison	162
Ashtabula County Justice Center	ОН	County complex	392
Augusta County Jail	VA	County jail	546
Austin County Jail	TX	County complex	460
Baltimore City Correctional Center	MD	State prison	272
Baltimore City Jail	MD	City jail	274
Benton County Justice Center	WA	County complex	554
Bernalillo County Detention Center (South Tower)	NM	County jail	350
Beto I Unit	TX	State prison	462
Beto II Unit	TX	State prison	464
Bexar County Juvenile Center	TX	County complex	466
Blair County Prison	PA	County jail	432
Brazoria County Sheriff's Department Detention Center II	TX	County jail	468
Bridgeport Correctional Center: Modular Units	CT	State prison	172
Brooklyn Correctional Facility	NY	City jail	364
Burnett County Government Center	WI	County complex	570
California Correctional Institution	CA	State prison	108
California Medical Facility—South	CA	State prison	110
California State Prison—Sacramento County/Folsom	CA	State prison	110
Camden County Correctional Facility	NJ	County jail	336
Cameron County Detention Center	TX	County jail	470
Central New Mexico Correctional Facility	NM	State prison	352
Centralia Correctional Center	IL	State prison	208
Chambers County Law Enforcement Center	TX	County complex	472
Chouteau County Law Enforcement Facility	MT	County complex  County complex	318
Clark County Detention Center	NV	County jail	334
Clark County Detention Facility	AR	County jan  County complex	96
Clark County Detention Facility  Clarke County Correctional Institution	GA	County jail	200
Clay County Detention Center	MO		308
Clemson Police Department	SC	County jail City complex	448
Clermont County Jail	OH	City complex  County jail	
Cleveland County Detention Center	OK	County complex	394
Cochise County Jail	AZ	• •	410
Coffield Unit	TX	County jail	82 474
	WI	State prison	
Columbia Correctional Institution	TX	State prison	572
Comal County Jail		County jail	476
Contra Costa County Detention Facility  Cook County Medical and Psychiatric Facility  PTI Puilding	CA	County complex	114
Cook County Medical and Psychiatric Facility—RTU Building	IL AK	County jail State detention facility	210
Cook Inlet Pre-Trial Facility	AK	State detention facility	60
Cook Inlet Pre-Trial Facility Phase II	AK MI	State pre-trial facility	62
Correction Camp Cusino	MI NC	State prison County complex	290 384
Craven County Law Enforcement Center	INC	County complex	384

Facility name	State	Facility type	Page
Cummins Unit—Medium Security	AR	State prison	98
Danville Correctional Center	IL	State prison	212
Darrington Unit	TX	State prison	478
Delaware Correctional Center (Maximum Security)	DE	State prison	176
Delta County Criminal Justice Facility	CO	County complex	164
Diagnostic Unit	TX	State prison	480
Dixon Correctional Center	IL	State prison	214
Dixon Correctional Institute	LA	State prison	258
Dodge County Judicial Center	NE	County complex	328
Dooly County Jail	GA	County jail	202
Douglas County Correctional Center	NE	County jail	330
Douglas County Jail	IL	County complex	216
DuPage County Jail and Sheriff's Department	IL	County complex	218
Dwight Correctional Center (1979 Addition)	IL	State prison	220
Dwight Correctional Center (1984 Addition)	IL	State prison	222
East Moline Correctional Center	IL	State prison	224
Eastern Correctional Center	NC	State prison	386
Eastern Correctional Institution	MD	State prison	276
Ellis II Unit (Phase I and II)	TX	State prison	482
Elmira Correctional & Reception Center Food Service & Dining			
Facility	NY	State prison	366
Elmwood—Barracks 24	CA	County jail	116
Erie County Correctional Facility	NY	County jail	368
Erie County Holding Center	NY	County jail	370
Fairbanks Correctional Center	AK	State prison	64
Fairfax County Adult Detention Center and Pre-Release Center	VA	County complex	548
Farmington Correctional Center	MO	State prison	310
Fayette County Detention Center	TX	County complex	484
Federal Correctional Institution	AL	Federal prison	54
Federal Correctional Institution (Phoenix)	AZ	Federal prison	84
Federal Correctional Institution (Tucson)	AZ	Federal prison	86
Federal Correctional Institution	FL	Federal prison	180
Federal Correctional Institution	KY	Federal prison	254
Federal Correctional Institution (Otisville)	NY	Federal prison	372
Federal Correctional Institution (Ray Brook)	NY	Federal prison	374
Federal Correctional Institution	TX	Federal prison	486
Federal Detention Center	LA	Federal complex	260
Feliciana Forensic Facility	LA	State complex	262
Ferguson Unit	TX	State prison	488
Foothill Communities Law & Justice Center	CA	County complex	118
Forks City Jail	WA	City complex	556
Fort Bend County Jail	TX	County complex	490
Fort Bend County Jail (Expansion)	TX	County jail	492
Franklin County Detention/Law Enforcement Facility	ME	County complex	270
Freeport Police and Courts Building	TX	City complex	494
Fulton Reception and Diagnostic Center, Phase I	MO	State prison	312
Garfield County Jail	CO	County jail	166
Garland County Detention Facility	AR	County jail	100
Gerald L. Gormley Justice Facility	NJ	County complex	338
Gilliam Psychiatric Center	SC	State prison	450

Facility name	State	Facility type	Page
Graham Correctional Center	IL	State prison	226
Grand Traverse County Correctional Facility	MI	County and city complex	292
Hamilton County Justice Complex	ОН	County complex	396
Harris County Juvenile Detention Home	TX	County complex	496
Hennepin County Juvenile Detention Center	MN	Juvenile detention facility	298
Hidalgo County Jail	TX	County jail	498
Hiland Mountain Correctional Center	AK	State prison	66
Hunt Correctional Center	LA	State prison	264
Hunt County Criminal Justice Center	TX	County complex	500
Illinois Youth Center—Kankakee (Dining Facility)	IL	Juvenile correctional facility	228
Illinois Youth Center—Kankakee (Housing Unit)	IL	Juvenile correctional facility	230
J. Bernard Gates Correctional Unit	CT	State jail	174
Jackson County Adult Detention Center	MS	County jail	302
Jackson County Detention Center	MO	County complex	314
Jackson County Jail	OR	County jail	426
Jefferson County Correctional Facility	WA	County complex	558
Jefferson County Criminal Justice Center	MT	County complex	320
Jefferson County Jail	AL	County jail	56
Jester Unit Number 3	TX	State prison	502
Johnson County Juvenile Hall	KS	Juvenile detention facility	248
Justice Center	OR	County complex	428
Kansas State Penitentiary (Phase One)	KS	State prison	250
Katy Police Department	TX	City complex	504
Kay County Detention Facility	OK	County complex	412
Kings County Branch Jail	CA	County jail	120
Kirby Forensic Psychiatric Center	NY	State treatment center	376
Knox County Jail	KY	County jail	256
Lacy Security Facility	CA	County jail	122
Leon County Jail	FL	County jail	182
Leon County Justice Complex	FL	County complex	184
Lew Sterrett Justice Center	TX	County and city jails	506
Lewis and Clark County Criminal Justice Facility	MT	County complex	322
Lexington Assessment & Reception Center	OK	State prison	414
Lexington Assessment & Reception Center, Phase I and II	OK	State prison	416
Liberty County Jail	TX	County complex	508
Lieber Correctional Institution	SC	State prison	452
Logan County Jail and Office Complex	ОН	County complex	398
Longwood Treatment Center	MA	Treatment facility	286
Louisiana Correctional Institute for Women	LA	State prison	266
Lycoming County Prison	PA	County jail	434
Mabel Bassett Correctional Center	OK	State prison	418
Macomb County Jail	MI	County jail	294
Madison Correctional Institution	ОН	State prison	400
Marion County Detention Center	FL	County jail	186
Marion County Jail	IN	County complex	242
Martin Correctional Institution	FL	State prison	188
Massachusetts Correctional Institution Norfolk	MA	State prison	288
Masten Park Secure Center	NY	State center for youth	378
Mat-su Pre-Trial Facility	AK	State prison	68
Maui Community Correctional Center	HI	County and city jails/State prison	206

Facility name	State	Facility type	Page
Maximum Security Unit, Tucker Unit	AR	State prison	102
Meadow Creek Correctional Center	AK	State prison	70
Middlesex County Correctional Facility	NJ	County jail	340
Minnesota Supervised Living Facility	MN	State prison	300
Mississippi State Penitentiary—Unit 29	MS	State prison	304
Missouri City Police Department	TX	City complex	510
Missouri Eastern Correctional Center	MO	State prison	316
Montgomery County Detention Center	MD	County complex	278
Mountain View Unit	TX	State prison	512
Muskogee County/City Detention Facility	OK	County and city jails	420
Myrtle Beach Law Enforcement Center	SC	City complex	454
Nashville Community Service Center	TN	State prison	456
Nebraska State Penitentiary	NE	State prison	332
Nevada County Detention Center	CA	Restitution center	124
North Carolina Central Prison	NC	State prison	388
North Facility	NY	City jail	380
Northwest State Correctional Facility	VT	State prison	540
Ocean County Justice Complex	NJ	County complex	342
Ohio County Correctional Center	WV	County complex	568
Ohio Reformatory for Women	ОН	State prison	402
Oklahoma State Penitentiary	OK	State prison	422
Orange County Jail	TX	County complex	514
Orange County Sheriff's Intake Release Center	CA	County jail	126
Orange Street Community Correctional Center	UT	State correctional facility	534
Oshkosh Correctional Institution	WI	State prison	574
Ottawa County Detention Facility	ОН	County complex	404
Ouachita Correctional Center	OK	State prison	424
Palmer Correctional Center Medium Security Facility	AK	State prison	72
Pearland Public Safety Building	TX	City complex	516
Penitentiary of New Mexico	NM	State prison	354
Peoria County Adult Detention and Work Release Facility	IL	County complex	232
Philadelphia Industrial Correctional Center	PA	County and city jails	436
Pima County Adult Detention Center	AZ	County jail	88
Pima County Adult Detention Center (Addition)	AZ	County jail	90
Pinal Mountain Juvenile Institution	AZ	Juvenile correctional facility	92
Pinellas County Jail—Medium Security Facility	FL	County jail	190
Pitkin County Jail	CO	County complex	168
Pittsylvania County Jail	VA	County jail	550
Placer County Jail	CA	County complex	128
Plumas County Sheriff's Department & Detention Facility	CA	County jail	130
Polk County Jail	IA	County jail	244
Pondera County Jail	MT	County complex	324
Pre-Trial Detention Facility	CA	County jail	132
Prince George's County Correctional Center	MD	County jail	280
Richard J. Donovan Correctional Facility at Rock Mountain	CA	State prison	134
Richmond County Law Enforcement and Justice Center	GA	County complex	204
Rikers Island: Modular Units	NY	City jail	382
Roanoke City Jail	VA	City complex	552
Rock Island County Jail	IL	County complex	234
Ross Correctional Institution	ОН	State prison	406

Facility name	State	Facility type	Page
Rusk County Law Enforcement Facility	WI	County complex	576
Sacaton Juvenile Rehabilitation Center	AZ	Juvenile rehabilitation center	94
Saline County Detention Facility	AR	County jail	104
San Joaquin County Honor Farm Women's Minimum Security	<b>C</b> A	Country in it	104
Facility	CA	County jail	136
San Patricio County Sheriff's Department	TX	County complex	518
Santa Barbara County Main Jail	CA	County jail	138
Santa Cruz County Jail (Phase I)	CA	County jail	140
Santa Rosa County Jail	FL	County complex	192
Schuylkill County Prison	PA	County jail	438
Sequoia Field Detention Facility	CA	County jail	142
Seminole County Correctional Facility	FL	County jail	194
Shasta County Justice Center	CA	County complex	144
Shawnee Correctional Center	IL	State prison	236
Shawnee County Department of Corrections	KS	County complex	252
Shelby County Justice Center	TN	County and city complex	458
Sheridan Correctional Center (Kitchen/Dining Facility)	IL	State prison	238
Sheridan Correctional Center (Medical/Security Services)	IL .	State prison	240
Smith County Jail	TX	County jail	520
Somerset County Detention Center	MD	County jail	282
Sonoma North County Detention Facility	CA	County jail	146
South Florida Reception Center	FL	State prison	196
Southern Correctional Center	NC	State prison	390
Southern New Mexico Correctional Facility	NM	State prison	356
Southern State Correctional Facility: Modular Units (Phase I and II)	NJ	State prison	344
St. Johnsbury Community Correctional Center	VT	County jail/State prison	542
Stanislaus County Jail	CA	County complex	148
Starr County Jail	TX	County jail	522
State Correctional Institution at Smithfield	PA	State prison	440
State Prison of Southern Michigan	MI	State prison hospital	296
State Regional Correctional Facility at Mercer	PA	State prison	442
Summit County Justice Center	CO	County complex	170
Sunnyvale Public Safety Building and Temporary Holding Facility	CA	City complex	150
TDC Hospital at Galveston	TX	State prison hospital	524
Thurston County Corrections Facility	WA	County complex	560
Torrance Police Department	CA	City complex	152
Trenton State Prison	NJ	State prison	346
Tunica County Jail and Sheriff's Department	MS	County complex	306
Tuolumne County Jail	CA	County jail	154
Twin Rivers Corrections Center	WA	State prison	562
Uintah County Jail	UT	County jail	536
Union Correctional Institution	FL	State prison	198
Victoria County Jail	TX	County complex	526
Wallace Pack Unit I	TX	State prison	528
Wallace Pack Unit II	TX	State prison	530
Warren County Correctional Center	NJ	County jail	348
Warren County Jail	PA	County jail	444
Washington Correctional Institute	LA	State prison	268
Washington Corrections Center Intensive Management Unit	WA	State prison	564
Washington County Detention Center	MD	County jail	284

<b>Facility name</b>	State	Facility type	Page
Wayne County Justice Center	ОН	County complex	408
West Jefferson Correctional Facility	AL	State prison	58
Western New Mexico Correctional Facility	NM	State prison	358
Westside Police Area Command Station	TX	City complex	532
Whitman County Correctional Facility	WA	County complex	566
Wildwood Correctional Center	AK	State prison	74
Woodbury Law Enforcement Center	IA	County complex	246
Wyoming County Jail	PA	County jail	446
Yellowstone County Detention Facility	MT	County complex	326
Young Adult Correctional Facility	UT	State prison	538
Youth Diagnostic and Development Center	NM	Youth detention facility	360
Youth Diagnostic and Development Center—Phase III	NM	Youth detention facility	362
Yuba County Jail	CA	County jail	156
Yukon-Kuskokwim Correctional Center	AK	State prison	76

# **Section IV**Facility profiles

### **Federal Correctional Institution**

Jurisdiction official: J. Michael Quinlan, Director, Bureau of Prisons

Contact: Warden D.J. Southerland, Federal Correctional Institution, Talladega, AL 35160, 205–362–0410

Architect: Charles H. McCauley Associates, Inc., 1400 South 20th Street, P.O. Box 335, Birmingham, AL 35201, 205–933–7100

Construction manager: Lasker Goldman Corporation, 470 Park Avenue South, New York, NY 10016, 212–481–3409

Groundbreaking: September 1977 Finish date: September 1979 Construction time: 24 months Design capacity: 324
Total cost: \$10,069,300
Total annual operating costs:

\$6,500,000

Category: New, independent facility

Facility type: Federal prison

Building configuration: Campus style

### Costs

Total: \$10,069,300 Building only: \$10,069,050 Housing area: \$6,002,840 Housing per inmate: \$18,527 Housing per cell: \$18,527 Total per inmate: \$31,078 Total per GSF: \$38.73

Total annual operating costs: \$6,500,000

### **Dimensions**

Gross square feet/corrections: 260,000 Gross square feet/other: 0 Gross square feet/total: 260,000 Housing area square feet: 155,000 Gross square feet per inmate: 802 Size of cells: 106 square feet (single) Net/gross square feet: Unknown

# Construction type

Structural: Steel frame Exterior walls: CMU block Interior walls: CMU block

Exterior surface/facade: Natural wall,

no coating or treatment

### **Security**

Perimeter: Double fence; patrols Inmate security level: Maximum: 0 (use, 5%) Medium: 75% (use, 90%) Minimum: 25% (use, 5%)

# Inmate design capacity

Single occupancy: 324 Double occupancy: 0

Dorms: 0

Special housing: 0 General population: 324

Total: 324

### **Inmate cells**

Doors/material: Steel Doors/type: Swinging Doors/locking: Manual locking

Floor surface: Vinyl tile

Intercom: One-way to common areas

HVAC: Air conditioning Plumbing: China Furniture: Wood; steel

Fire protection: Sprinklers for common

areas

### **Current staff**

Full-time equivalent:
Administration: 28
Security: 100

Programs/treatment: 39 Maintenance: 46

Total: 213

Current inmate/staff ratio: 4.13:1

### **Inmate housing areas**

Design: Module/pod Cells per unit: 54 Inmates per unit: 54

Management type: Direct supervision

October 1985 population: 879

Facility commitment: Federal prisoners Means to handle crowding: Bunk beds in

cell

### **Construction process**

Finance method: Federal funds

Contract method: Construction manage-

ment fast track

Use of inmate labor: None Use of prefabrication: None

### Architect's reported analyses

Factors affecting construction costs:
Positive: Phased construction, fast track

construction management Negative: Government procedures, regulations, "red tape"; complex


systems

Factors affecting time schedule:

Positive: Phased construction, fast track construction management; advanced order of materials and hardware; coordination of design between parties

electronic, mechanical, and electrical

Negative: Slow responses and delivery from vendors, suppliers; government "red tape"; complex electronic, mechanical, and electrical systems



# Jefferson County Jail

Jurisdiction official: A. Melvin Bailey, Sheriff

Contact: Deputy Sheriff Glenn Anderson, Jefferson County Jail, 809 21 Street North, Birmingham, AL 35263, 205-325-5936 Architect: Giattina Fisher & Company Architects, Inc., 2031 11th Avenue South, Birmingham, AL 35255, 205-933-9060

Construction manager: None

Groundbreaking: January 1982

Finish date: July 1984

Construction time: 31 months

Design capacity: 623 **Total cost:** \$18,200,000

Total annual operating costs:

\$4,480,409

Category: New, independent facility

Facility type: County jail Building configuration: High rise

**Inmate housing areas** 

Design: Module/pod

Inmates per unit: 12

Cells per unit: 12

patrols

### **Costs**

Total: \$18,200,000 Building only: N/A

Housing area: \$14,700,000 Housing per inmate: \$25,699 Housing per cell: \$28,053 Total per inmate: \$29,213 Total per GSF: \$80.83

Total annual operating costs: \$4,480,409

Perimeter: Building exterior; alarm/

### **Dimensions**

Gross square feet/corrections: 225,173 Gross square feet/other: 0

Gross square feet/total: 225,173 Housing area square feet: 181,580 Gross square feet per inmate: 361 Size of cells: 70 square feet (single)

Net/gross square feet: N/A

### **Construction type**

Structural: Cast-in-place concrete frame, flat plate

Exterior walls: CMU block; brick Interior walls: Cast-in-place concrete;

CMU block

Exterior surface/facade: Brick

Inmate design capacity

Single occupancy: 500

Double occupancy: 0

Special housing: 51

General population: 572

Dorms: 72

Total: 623

# **Construction process**

and State prisoners

October 1985 population: 312

Finance method: Local funds;

G.O. Bond issue

Contract method: Conventional; three

Management type: Remote surveillance;

Facility commitment: Local jail inmates

Means to handle crowding: None needed

bid packages

Use of inmate labor: None

Use of prefabrication: Limited; casework,

detention furnishings

### **Inmate cells**

Medium: 0

Security

Doors/material: Steel Doors/type: Swinging

detection systems

Inmate security level:

Maximum: 96%

Minimum: 4%

Doors/locking: Remote unlocking only Floor surface: Vinyl tile; carpet in control rooms and administrative areas Intercom: Two-way to cells and common areas; direct to secure stations

HVAC: Air cond.; heating/air circ.; cent. heat. plant with boilers, fans, chillers, cool. towers; pip. to heat. coils Plumbing: Stainless combination unit Furniture: Steel; stainless steel Fire protection: Smoke det. for com. areas; sprinklers for cells and com.

areas; man. alarm stations; fire pump;

emer. gen.; comp. cont. for HVAC

**Current staff** 

Full-time equivalent: Administration: 10 Security: 104

Programs/treatment: 7 (+ 4 not in

budget)

Maintenance: 0 (+ 6 not in budget) Total: 121 (+ 10 not in budget) Current inmate/staff ratio: 2.58:1

### Architect's reported analyses

Factors affecting construction costs: Positive: Simple construction methods, repetitiveness of design; good competition, favorable market: highrise design with stacking cells and utilities

Negative: Difficult site conditions; complex electronic, mechanical, and

electrical systems


Factors affecting time schedule:

Positive: Phased construction; coordination of design, team/contractor/owner;

all parties local

Negative: Slow responses and delivery from vendors, suppliers; weather

problems





# West Jefferson Correctional Facility

Jurisdiction official: Morris L. Thigpen, Commissioner, Department of Corrections

Contact: John E. Nagle, Warden, West Jefferson Correctional Facility, 100 Warrier Lane, Bessemer, AL 35023, 205-436-3681 Joint venture architects: Tiller/Butner/Rosa Architects, 416 South Perry Street, Montgomery, AL 36104, 205-834-6170

Wittenberg, Delony & Davidson, Inc., 840 Savers Federal Building, Little Rock, AR 72201, 501-376-6681

Construction manager: Brice Building Company/Champion Construction Company, 2721 2nd Avenue North, Birmingham,

AL 35201, 205-252-9911

**Groundbreaking:** December 1981

Finish date: March 1984 Construction time: 28 months Design capacity: 994 Total cost: \$23,420,685 Total annual operating costs:

\$13,111,599

Category: New, independent facility

Facility type: State prison

Building configuration: Wings connect-

ing housing pods

### **Costs**

Total: \$23,420,685

Building only: \$20,120,685 Housing area: \$13,321,500 Housing per inmate: \$13,876,562 Housing per cell: \$22,276,755

Total per inmate: \$23,562 Total per GSF: \$74.23

Total annual operating costs: \$13,111,599

### **Dimensions**

Gross square feet/corrections: 315,522

Gross square feet/other: 0 Gross square feet/total: 315,522 Housing area square feet: 220,900 Gross square feet per inmate: 191 Size of cells: 70 square feet (single)

Net/gross square feet: N/A

### **Inmate housing areas**

Design: Module/pod Cells per unit: 96

Inmates per unit: 96 or 192

Management type: Remote surveillance

July 1985 population: 1,352

Facility commitment: State prisoners Means to handle crowding: Bunk beds

in cell

### Security

Perimeter: Double fence; alarm/ detection systems, razor wire on and between fences; towers; patrols

Inmate security level:
Maximum: 25%
Medium: 50%
Minimum: 25%

# **Construction type**

Structural: Load bearing precast panels (floors); load bearing concrete block

Exterior walls: CMU block Interior walls: CMU block

Exterior surface/facade: CMU block only

### **Construction process**

Finance method: State funds

Contract method: Conventional, two

separate contracts
Use of inmate labor: None

Use of prefabrication: Moderate, preengineered metal roof and frame,

precast panels

### **Inmate cells**

Doors/material: Steel

Doors/type: Swinging; sliding

Doors/locking: Motor driven and remote

locking; remote locking only Floor surface: Sealed concrete Intercom: Two-way to common areas HVAC: Heating/air circulation only;

gas-fired boiler Plumbing: Stainless Furniture: Steel; concrete

Fire protection: Smoke detectors and sprinklers for cells and common areas;

manual alarm stations

### Inmate design capacity

Single occupancy: 192 Double occupancy: 768

Dorms: 0

Special housing: 34 General population: 960

Total: 994

# Architects' reported analyses

Factors affecting construction costs:
Positive: Phased construction; less
expensive materials and hardware
Negative: Difficult site conditions—
abandoned coal mine

Factors affecting time schedule:
Positive: Simple construction methods,
repetitiveness of design; phased
construction, coordination of design
between parties

Negative: Site preparation lengthy


### **Current staff**

Full-time equivalent: Administration: 42 Security: 243

Programs/treatment: 26 Maintenance: 10

Total: 321

Current inmate/staff ratio: 3.09:1



TYPICAL 96 BED HOUSING UNIT

# **Cook Inlet Pre-Trial Facility**

Jurisdiction official: Susan Humphrey-Barnett, Commissioner, Department of Corrections

Contact: Superintendent Charles Moses, Cook Inlet Pre-Trial Facility, P.O. Box 103155, 1300 East 4th Avenue, Anchorage,

AK 99510, 907-258-7267

Architects: Hellmuth, Obata & Kassabaum, Inc., One Lombard Street, San Francisco, CA 94111, 415-627-1600

CCC Architects Alaska, 413 West Seventh, Suite 100, Anchorage, AK 99501, 907-272-3567

Construction manager: None

**Groundbreaking:** September 1979

Finish date: June 1983

Construction time: 45 months

**Design capacity: 228** Total cost: \$21,000,000 **Total annual operating costs:** 

\$8,505,683

Category: New, independent facility Facility type: State detention facility **Building configuration:** Integrated

structure: clusters

### **Costs**

Total: \$21,000,000 Building only: \$20,000,000 Housing area: \$9,800,000 Housing per inmate: \$45,370 Housing per cell: \$45,370 Total per inmate: \$92,105 Total per GSF: \$235.05

Total annual operating costs: \$8,505,683

### **Dimensions**

Gross square feet/corrections: 89,341 Gross square feet/other: 0 Gross square feet/total: 89,341 Housing area square feet: 59,000 Gross square feet per inmate: 392 Size of cells: 70 square feet (single)

Net/gross square feet: 66%

### **Inmate housing areas**

Design: Module/pod Cells per unit: 12 to 24 Inmates per unit: 12 to 48

Management type: Direct supervision October 1985 population: 398 Facility commitment: State prisoners Means to handle crowding: Holding cells

in intake; transfer offenders

# Security

Perimeter: Building exterior; double fence; razor wire on fence

Inmate security level: Maximum: 15% Medium: 65% Minimum: 20%

## **Construction type**

Structural: Steel frame; CIP concrete frame; precast conc. frame (col. and

beam)

Exterior walls: Precast panels

Interior walls: Precast panels; CMU block

with solid grout

Exterior surface/facade: Unknown

### Construction process

Finance method: State funds Contract method: Conventional Use of inmate labor: None

Use of prefabrication: Moderate, tilt-up

walls

### **Inmate cells**

Doors/material: Steel Doors/type: Swinging

Doors/locking: Remote locking

Floor surface: Dexotex

Intercom: Two-way to dayroom HVAC: Heating/air circulation only

Plumbing: Stainless

Furniture: Precast concrete

Fire protection: Smoke detectors and

sprinklers for cells

### Inmate design capacity

Single occupancy: 216 Double occupancy: 0

Dorms: 0

Special housing: 12 General population: 216

Total: 228

Factors affecting construction costs: Positive: Use of tilt-up construction Negative: Alaskan prices; weather

Architects' reported analyses

problems

Factors affecting time schedule:

Positive: Tilt-up system Negative: Weather problems


### **Current staff**

Full-time equivalent: Administration: 14 Security: 95

Programs/treatment: 6 Maintenance: 12

Total: 127


Current inmate/staff ratio: 3.13:1



#### **First Level**

- 1 Sally Port 2 Magistrate 3 Booking Area 4 Superintendent 5 Central Control
- 6 Interview
- 7 Waiting 8 Reception
- 9 Administration 10 Laundry
- 11 Staff Dining 12 Kitchen

- 13 Gymnasium 14 Storage 15 Maintenance
- 16 Receiving 17 Outdoor Exercise
- 18 Dayroom
- 19 Typical Cell 20 Counseling



#### **Second Level**

- 1 Visiting 2 Mechanical 3 Library

- **4** Classroom **5** Gymnasium Below **6** Typical Cell
- 7 Outdoor Exercise 8 Dayroom Below 9 Control Room

# **Cook Inlet Pre-Trial Facility, Phase II (Expansion)**

Jurisdiction official: Susan Humphrey-Barnett, Commissioner, Department of Corrections

Contact: Superintendent Charles Moses, Cook Inlet Pre-Trial Facility, P.O. Box 103155, 1300 East 4th Avenue, Anchorage,

AK 99510, 907-258-7267

Architect: CCC Architects Alaska, 431 West 7th Avenue, Suite 100, Anchorage, AK 99501, 907-272-3567

Construction manager: None

Groundbreaking: March 1984 Finish date: March 1985

Construction time: 12 months

Design capacity: 36 **Total cost:** \$2,020,000

Total annual operating costs: \$8,097,400

Gross square feet/corrections: 7,766

Gross square feet/other: 0

Net/gross square feet: 84%

Gross square feet/total: 7,766

Housing area square feet: 7,766

Gross square feet per inmate: 216

Size of cells: 86.3 square feet (single)

(entire facility)

**Dimensions** 

Category: Expansion; phased project

(past) Facility type: State pre-trial facility Building configuration: Integrated

Management type: Intermittent and

September 1986 population: 36

remote surveillance; direct supervision

Facility commitment: Pre-trial detainees

Means to handle crowding: Use of intake

**Inmate housing areas** 

Design: Module/pod

Inmates per unit: 36

Cells per unit: 36

cells

structure

Costs

Total: \$2,020,000

Building only: \$1,970,000 Housing area: \$1,970,000 Housing per inmate: \$54,722 Housing per cell: \$54,722 Total per inmate: \$56,111

Total annual operating costs: \$8,097,400

(entire facility)

Security

Total per GSF: \$260.11

**Construction type** 

Perimeter: Single fence; alarm/detection systems; video camera surveillance

Inmate security level: Maximum: 100% Medium: 0 Minimum: 0

Structural: Load bearing precast panels;

steel frame

Exterior walls: Precast panels; metal siding Interior walls: Precast panels; CMU block

Exterior surface/facade: Paint

**Construction process** 

Finance method: State funds Contract method: Conventional Use of inmate labor: None Use of prefabrication: Limited

**Inmate cells** 

Doors/material: Steel

Doors/type: Swinging; sliding

Doors/locking: Motor driven and remote

locking; manual locking

Floor surface: Carpet, epoxy coating;

vinyl tile

Intercom: One-way to common areas HVAC: Air conditioning; gas heat Plumbing: Stainless combination unit

Furniture: Steel; concrete

Fire protection: Smoke detectors and sprinklers for cells and common areas Inmate design capacity Single occupancy: 36

Double occupancy: 0

Dorms: 0

Special housing: 0 General population: 36

Total: 36

**Current staff** 

Full-time equivalent: Administration: 9 Security: 95

> Programs/treatment: 10 Maintenance: 12

Total: 126 (entire facility)

Current inmate/staff ratio: N/A

Architect's reported analyses

Factors affecting construction costs: Positive: Use of precast standardized

structural components

Negative: Attachment to existing facility


systems

Factors affecting time schedule:

Positive: Coordination of design between

parties; good administration

Negative: Slow responses and delivery from vendors, suppliers; long lead time for procuring locking mechanisms



# Fairbanks Correctional Center (Remodel/Expansion)

Jurisdiction official: Susan Humphrey-Barnett, Commissioner, Department of Corrections

Contact: Superintendent Gail Frank, Fairbanks Correctional Center, P.O. Box 317, Wilbur and Egan Streets, Fairbanks, AK 99707,

907-452-3125

Architect: Harold Wirum & Associates, 500 L Street, Suite 500, Anchorage, AK 99501-5996, 907-276-3400

Construction manager: None

**Groundbreaking:** May 1982 Finish date: June 1983

**Construction time:** 13 months

Design capacity: 72 **Total cost:** \$7,914,000

Total annual operating costs: \$1,070,400

(entire facility)

Category: Remodeling/renovation

project; expansion Facility type: State prison

Building configuration: Integrated

structure

#### Costs

Total: \$7,914,000 Building only: Unknown Housing area: Unknown Housing per inmate: Unknown Housing per cell: Unknown Total per inmate: \$109,917 Total per GSF: \$210.21

Total annual operating costs: \$1,070,400

(entire facility)

# **Dimensions**

Gross square feet/corrections: 37,648 Gross square feet/other: 0 Gross square feet/total: 37,648 Housing area square feet: 20,685 Gross square feet per inmate: 523 Size of cells: 76 square feet (single) Net/gross square feet: Unknown

Structural: Load bearing precast panels Exterior walls: Precast panels

Exterior surface/facade: Cement plaster

# Design: Linear, outside

**Inmate housing areas** 

Cells per unit: 24 Inmates per unit: 24

Management type: Intermittent surveil-

lance

September 1986 population: 100 Facility commitment: State prisoners Means to handle crowding: Second bunk

permanently attached to wall

**Construction process** 

Finance method: State funds

#### **Security**

Perimeter: Double fence; razor wire on

fences

Inmate security level: Maximum: 0 Medium: 100% Minimum: 0

# **Construction type**

Interior walls: Precast panels; CMU block

Contract method: Conventional Use of inmate labor: None Use of prefabrication: Limited; precast

concrete panels

#### Inmate cells

Doors/material: Steel Doors/type: Swinging

Doors/locking: Manual locking Floor surface: Carpet; sheet vinyl Intercom: One-way to common areas HVAC: Heating/air circulation; oil fired

boilers

Plumbing: Stainless combination unit

Furniture: Steel

Fire protection: Smoke detectors for cells and common areas; manual alarm

stations

# Inmate design capacity

Single occupancy: 72 Double occupancy: 0

Dorms: 0

Special housing: 0 General population: 72

Total: 72

### Current staff

Full-time equivalent: Administration: 0 Security: 10

Programs/treatment: 0 Maintenance: 0

Total: 10 (addition only) Current inmate/staff ratio: 10.0:1

#### **Architect's reported analyses**


Factors affecting construction costs:

Positive: Simple construction methods, repetitiveness of design

Negative: High labor costs Factors affecting time schedule:

Positive: Simple construction methods,

repetitiveness of design Negative: Weather problems



# **Hiland Mountain Correctional Center (Addition)**

Jurisdiction official: Susan Humphrey-Barnett, Commissioner, Department of Corrections

Contact: Superintendent Frank Sauser, Hiland Mountain Correctional Center, P.O. Box 600, Eagle River, AK 99577, 907-694-9511

Architect: Harold Wirum & Associates, 500 L Street, Suite 500, Anchorage, AK 99501-5996, 907-276-3400

Construction manager: None

Groundbreaking: July 1981 Finish date: January 1983 Construction time: 18 months **Design capacity:** 160 **Total cost:** \$3,782,900

**Total annual operating costs:** \$437,400

Gross square feet/corrections: 19,330

(addition only)

**Dimensions** 

Category: New, ancillary building

Facility type: State prison

**Inmate housing areas** 

Design: Linear, outside

Cells per unit: 40

bunk beds

Inmates per unit: 80

Building configuration: Wheel, spoke or

Management type: Remote surveillance

Means to handle crowding: Removable

Facility commitment: State prisoners

radial

#### Costs

Total: \$3,782,900

Building only: \$3,189,900 Housing area: \$3,189,900 Housing per inmate: \$19,937 Housing per cell: \$39,874 Total per inmate: \$23,643 Total per GSF: \$195.70

Total annual operating costs: \$437,400

(addition only)

Security

# Construction type

Perimeter: Double fence; alarm/detection

system; razor wire on fences

Inmate security level:
Maximum: 0
Medium: 0
Minimum: 100%

Size of cells: 80 square feet (double) Net/gross square feet: 91%

Gross square feet/other: 0

Gross square feet/total: 19,330

Housing area square feet: 19,330

Gross square feet per inmate: 121

Structural: Steel frame

Exterior walls: CMU block; wood siding

Interior walls: CMU block

Exterior surface/facade: Wood siding

**Construction process** 

February 1987 population: 100

Finance method: State funds Contract method: Conventional Use of inmate labor: None Use of prefabrication: None

#### **Inmate cells**

Doors/material: Wooden Doors/type: Swinging

Doors/locking: Manual locking

Floor surface: Carpet

Intercom: One-way to common areas

HVAC: Heating/air circulation

Plumbing: China Furniture: Wood

Fire protection: Smoke detectors for cells and common areas; manual alarm

stations

# Inmate design capacity

Single occupancy: 0 Double occupancy: 160

Dorms: 0

Special housing: 0 General population: 160

Total: 160

# **Current staff**

Full-time equivalent: Administration: 1 Security: 10

Programs/treatment: 0

Maintenance:

Total: 11 (addition only)
Current inmate/staff ratio: 9.09:1

#### Architect's reported analyses

Factors affecting construction costs: Positive: Simple construction methods, repetitiveness of design; less expensive materials and hardware

Negative: High labor costs


Factors affecting time schedule:

Positive: Simple construction methods,

repetitiveness of design

Negative: Weather problems; winter

construction



# **Mat-su Pre-Trial Facility**

Jurisdiction official: Susan Humphrey-Barnett, Commissioner, Department of Corrections

Contact: Superintendent Michael W. Dindinger, Mat-su Pre-Trial Facility, 339 East Dogwood, Palmer, AK 99645, 907–745–0944

Architect: McCool-McDonald of Alaska, Inc., 901 West 29th Avenue, Anchorage, AK 99503, 907-563-8474

Construction manager: None

**Groundbreaking:** May 1985 **Finish date:** July 1986

**Construction time:** 14 months

**Design capacity:** 56 **Total cost:** \$2,200,000

Total annual operating costs: Unknown

Category: New, independent facility

Facility type: State prison

Building configuration: Integrated

structure

#### Costs

Total: \$2,200,000 Building only: Unknown Housing area: Unknown Housing per inmate: Unknown Housing per cell: Unknown Total per inmate: \$39,286

Total per GSF: \$100.56

Total annual operating costs: Unknown

#### Dimensions

Gross square feet/corrections: 21,878 Gross square feet/other: 0 Gross square feet/total: 21,878 Housing area square feet: 8,750 Gross square feet per inmate: 391 Size of cells: 88 square feet (gen. double;

spec. single)

Net/gross square feet: Unknown

#### **Inmate housing areas**

Design: Module/pod Cells per unit: 32 Inmates per unit: 56

Management type: Remote surveillance

October 1987 population: 81

Facility commitment: State prisoners Means to handle crowding: Beds in

dayroom (weekends)

# Security

Perimeter: Single fence; razor wire on

fence

Inmate security level:
Maximum: 14%
Medium: 86%
Minimum: 0

# **Construction type**

Structural: Load-bearing precast panels;

steel frame

Exterior walls: Precast panels

Interior walls: Precast panels; CMU block Exterior surface/facade: Textured concrete

# **Construction process**

Finance method: G.O. Bonds Contract method: Conventional Use of inmate labor: None

Use of prefabrication: Moderate; precast

components

#### **Inmate cells**

Doors/material: Steel Doors/type: Swinging

Doors/locking: Manual locking Floor surface: Sealed concrete Intercom: Two-way to cells

HVAC: Heating/air circulation; gas heat

Plumbing: China Furniture: Steel

Fire protection: Sprinklers for cells and

common areas

# Inmate design capacity

Single occupancy: 0 Double occupancy: 48

Dorms: 0

Special housing: 8 General population: 48

Total: 56

#### **Current staff**

Full-time equivalent: Administration: 6 Security: 24

Programs/treatment: 3 Maintenance: 3

Total: 36

Current inmate/staff ratio: 2.25:1

#### Architect's reported analyses

Factors affecting construction costs: Positive: Prefabricated components, factory assembly; less expensive

materials and hardware

Negative: Complex electronic, mechanical, and electrical systems

Factors affecting time schedule:

Positive: Use of prefabricated compo-

nents, factory assembly

Negative: Complex electronic, mechani-

cal, and electrical systems

Alaska
Palmer

(No floorplan available at time of publication)

# **Meadow Creek Correctional Center (Addition)**

Jurisdiction official: Susan Humphrey-Barnett, Commissioner, Department of Corrections

Contact: Superintendent Frank Sauser, Meadow Creek Correctional Center, P.O. Box 600, Eagle River, AK 99687, 907-694-9511

Architect: Harold Wirum & Associates, 500 L Street, Suite 500, Anchorage, AK 99501-5996, 907-276-3400

Construction manager: None

Groundbreaking: October 1980

Finish date: July 1981 Construction time: 9 months Design capacity: 30 **Total cost:** \$2,833,428

Total annual operating costs: N/A

(addition)

Category: New, ancillary building Facility type: State prison (women's

facility)

**Building configuration:** Clusters

#### Costs

Total: \$2,833,428

Building only: \$2,670,928 Housing area: \$640,000 Housing per inmate: \$22,857 Housing per cell: \$22,857 Total per inmate: \$94,448 Total per GSF: \$89.16

Total annual operating costs: N/A

(addition)

#### **Security**

Perimeter: Building exterior; single fence; alarm/detection system; camera

surveillance Inmate security level: Maximum: 0 Medium: 7%

Minimum: 93%

# **Inmate cells**

Doors/material: Steel Doors/type: Swinging

Doors/locking: Manual locking

Floor surface: Carpet

Intercom: One-way to cells; two-way to

common areas

HVAC: Heating/air circulation; gas heat

Plumbing: China Furniture: Steel; wood

Fire protection: Smoke detectors and sprinklers for cells and common areas;

manual alarm stations

#### **Dimensions**

Gross square feet/corrections: 31,780

Gross square feet/other: 0 Gross square feet/total: 31,780 Housing area square feet: 7,167 Gross square feet per inmate: 1,059 Size of cells: 80 square feet (single) Net/gross square feet: Unknown

# **Construction type**

Structural: Steel frame; CMU bearing walls

Exterior walls: CMU block Interior walls: CMU block

Exterior surface/facade: Wood siding

# Inmate design capacity

Single occupancy: 28 Double occupancy: 0

Dorms: 0

Special housing: 2 General population: 28

Total: 30

#### **Current staff**

Full-time equivalent: Administration: 4 Security: 14

> Programs/treatment: 2 Maintenance: 1

Total: 21 (addition only) Current inmate/staff ratio: 1.05:1

#### **Inmate housing areas**

Design: Linear, outside Cells per unit: 15 Inmates per unit: 20

Management type: Intermittent surveil-

lance

September 1986 population: 22 Facility commitment: Female State

prisoners

Means to handle crowding: Bunk beds in

rooms

#### **Construction process**

Finance method: State funds Contract method: Conventional Use of inmate labor: None Use of prefabrication: None

# Architect's reported analyses

Factors affecting construction costs: Positive: Simple construction methods, repetitiveness of design; less expensive


materials and hardware Negative: High labor costs

Factors affecting time schedule: Positive: Simple construction methods,

repetitiveness of design

Negative: Weather problems; winter

construction



# Palmer Correctional Center Medium Security Facility

Jurisdiction official: Susan Humphrey-Barnett, Commissioner, Department of Corrections

Contact: Superintendent Joe Pendergrass, Palmer Correctional Center Medium Security Facility, P.O. Box 919, Mile 58 Glenn

Highway, Palmer, AK 99645, 907-745-5054

Architect: CCC Architects Alaska, 431 West 7th Avenue, Suite 100, Anchorage, AK 99501, 907-272-3567

Construction manager: None

**Groundbreaking:** July 1981 Finish date: July 1982

Construction time: 12 months

Design capacity: 104 **Total cost:** \$2,350,000

Total annual operating costs: Unknown

Category: New, independent facility

Facility type: State prison **Building configuration:** Clusters

#### Costs

**Security** 

Total: \$2,350,000 Building only: \$2,150,000 Housing area: \$1,000,000 Housing per inmate: \$10,000

Housing per cell: \$10,000 Total per inmate: \$22,596 Total per GSF: \$64.90

Perimeter: Single fence

Inmate security level:

Maximum: 3%

Medium: 97%

Minimum: 0

Inmate cells

Doors/material: Wooden

Doors/locking: Unknown

Floor surface: Carpet; vinyl tile Intercom: One-way to common areas

HVAC: Heating/air circulation; oil heat

Furniture: Steel; wood; vinyl/plastic

Fire protection: Smoke detectors and

sprinklers for cells and common areas

Doors/type: Swinging

Plumbing: China

Total annual operating costs: Unknown

#### **Dimensions**

Gross square feet/corrections: 36,211 Gross square feet/other: 0

Gross square feet/total: 36,211 Housing area square feet: 15,705 Gross square feet per inmate: 348 Size of cells: 71 square feet (gen. single);

85 (spec. single) Net/gross square feet: 85%

# **Construction** type

Structural: Wood frame Exterior walls: Wood siding

Interior walls: Wood studs, gypsum board

over plywood

Exterior surface/facade: Wood siding

# Inmate design capacity

Single occupancy: 100

Special housing: 4

Total: 104

Double occupancy: 0

Dorms: 0

General population: 100

#### Current staff

Full-time equivalent: Administration: 2 Security: 31

Programs/treatment: 6 Maintenance: 5

Total: 44

#### **Inmate housing areas**

Design: Module/pod Cells per unit: 20 Inmates per unit: 20

Management type: Office in each pod, inmates circulate during day July 1986 population: 125

Facility commitment: State prisoners Means to handle crowding: Expansion

underway

#### **Construction process**

Finance method: State funds

Contract method: Turn-key design and

build

Use of inmate labor: Limited; construction of cell furnishings and landscaping

Use of prefabrication: None

#### **Architect's reported analyses**

Factors affecting construction costs: Positive: Simple construction methods, repetitiveness of design; good competition, favorable market; less expensive materials and hardware; design-build contracting

Negative: None


Factors affecting time schedule:

Positive: Simple construction methods, repetitiveness of design; coordination of design between parties; design-build

contract

Negative: Weather problems

# Current inmate/staff ratio: 2.84:1



# **Wildwood Correctional Center (Remodel)**

Jurisdiction official: Susan Humphrey-Barnett, Commissioner, Department of Corrections

Contact: Superintendent Russell Moody, Wildwood Correctional Center, Building #10, Chugach Avenue, Kenai, AK 99611,

907-283-7296

Architect: Carmen Vincent Gintoli, 130 Trading Bay Road, Kenai, AK 99611, 907-283-7732

Construction manager: None

Groundbreaking: April 1984 Finish date: April 1985

Construction time: 12 months

**Design capacity:** 200 **Total cost:** \$1,100,000

Total annual operating costs: \$6,553,800

Category: Remodeling/renovation

project

Facility type: State prison

Building configuration: Integrated

structure

#### **Costs**

Total: \$1,100,000

Building only: \$1,100,000 Housing area: Unknown Housing per inmate: Unknown Housing per cell: Unknown

Total per inmate: N/A (remodel)

Total per GSF: \$32.35

Total annual operating costs: \$6,553,800

#### **Dimensions**

Gross square feet/corrections: 34,000

Gross square feet/other: 0 Gross square feet/total: 34,000 Housing area square feet: Unknown Gross square feet per inmate: 170 Size of cells: 175 square feet (gen. double);

90 (spec. single); 145 (spec. double) Net/gross square feet: Unknown

#### **Inmate housing areas**

Design: Linear, outside Cells per unit: Unknown Inmates per unit: Unknown

Management type: Intermittent surveil-

lance; video surveillance May 1987 population: 300

Facility commitment: State prisoners Means to handle crowding: Bunk beds in

cell

#### **Security**

Perimeter: Double fence; alarm/detection systems; razor wire on fences; patrols

Inmate security level:
Maximum: 5%

Medium: 95% Minimum: 0

# **Construction type**

Structural: Cast-in-place concrete frame

Exterior walls: CMU block Interior walls: CMU block Exterior surface/facade: Paint

# **Construction process**

Finance method: State funds Contract method: Conventional

Use of inmate labor: Limited; painting, vinyl tile, concrete cutting and coring,

and new wood doors
Use of prefabrication: None

#### **Inmate cells**

Doors/material: Solid; wooden

Doors/type: Swinging

Doors/locking: Manual locking Floor surface: Carpet; vinyl tile

Intercom: None

HVAC: Steam heat; gas heat

Plumbing: China Furniture: Unknown

Fire protection: Sprinklers for cells and

common areas

# Inmate design capacity

Single occupancy: 0
Double occupancy: 190

Dorms: 0

Special housing: 10 General population: 190

Total: 200

Architect's reported analyses

Factors affecting construction costs: Positive: Good competition, favorable

market

Negative: Slow construction, lengthy

building time

Factors affecting time schedule:

Positive: None Negative: None


# Current staff

Full-time equivalent: Administration: 9 Security: 64

Programs/treatment: 16

Maintenance: 7 Total: 96

Current inmate/staff ratio: 3.13:1



# Yukon-Kuskokwim Correctional Center

Jurisdiction official: Susan Humphrey-Barnett, Commissioner, Department of Corrections

Contact: Superintendent James F. Symbol, Yukon-Kuskokwim Correctional Center, Pouch 400, Bethel, AK 99559, 907-543-5245

Architect: Harold Wirum & Associates, 500 L Street, Suite 500, Anchorage, AK 99501-5996, 907-276-3400

Construction manager: None

Groundbreaking: July 1983 Finish date: September 1984

Construction time: 14 months

Design capacity: 98 Total cost: \$7,150,000

Total annual operating costs: \$3,273,300

Category: New, independent facility

Facility type: State prison

**Inmate housing areas** 

**Building configuration:** Integrated

Design: Linear, outside and inside

Management type: Intermittent surveil-

Facility commitment: State prisoners

Means to handle crowding: Bunk beds in

structure

Cells per unit: 7

lance

cell

Inmates per unit: 14

#### Costs

Total: \$7,150,000 Building only: \$6,650,000

Housing area: Unknown Housing per inmate: Unknown Housing per cell: Unknown Total per inmate: \$72,959

Total per GSF: \$271.55

Total annual operating costs: \$3,273,300

#### **Dimensions**

Gross square feet/corrections: 26,330 Gross square feet/other: 0 Gross square feet/total: 26,330 Housing area square feet: 17,700 Gross square feet per inmate: 269

Size of cells: 72 square feet (gen. single); 79 (gen. double); 59 (spec. single);

78 (spec. double) Net/gross square feet: 93%

# Construction type

Structural: Steel frame

Exterior walls: Steel plate on int. of 6" steel studs w/2" insulated metal Interior walls: Solid cement plaster; metal stud w/½" plywood insulated metal Exterior surface/facade: Prefinished metal

panels

**Construction process** 

April 1987 population: 90

Finance method: State funds Contract method: Conventional Use of inmate labor: None

Use of prefabrication: Limited; metal

panels and steel plate

Security

Perimeter: Building exterior; single fence Inmate security level:

Maximum: 6% Medium: 11% Minimum: 83%

#### **Inmate cells**

Doors/material: Wooden Doors/type: Swinging

Doors/locking: Manual locking

Floor surface: Vinyl tile

Intercom: Two-way to cells and common

areas

HVAC: Heating/air circulation; energy recycle unit; waste heat from elec. gen. plant w/backup oil fired boiler

Plumbing: China Furniture: Steel

Fire protection: Smoke detectors and sprinklers for cells and common areas

# Inmate design capacity

Single occupancy: 5 Double occupancy: 86

Dorms: 0

Special housing: 7 General population: 91

Total: 98

#### **Current staff**

Full-time equivalent: Administration: 3 Security: 27

Programs/treatment: 5 Maintenance: 3

Total: 38

Current inmate/staff ratio: 2.37:1


# Architect's reported analyses

Factors affecting construction costs: Positive: Simple const. methods; phased construction, fast track CM; less expensive materials and hardware Negative: High labor costs; difficult site conditions, very poor soil; rural location, no highway access to Bethel

Factors affecting time schedule:

Positive: Repetitiveness of design; phased construction, fast track CM; advanced order of materials and hardware Negative: Weather problems; winter

construction



# Arizona State Prison—Florence (Addition—East Unit)

Jurisdiction official: Samuel A. Lewis, Director, Department of Corrections

Contact: Deputy Warden A. Grijalva, Arizona State Prison, P.O. Box 629, Florence, AZ 85232, 602-868-4011

Architect: Varney, Sexton, Lunsford, Aye, Associates—Architects, Inc., 2001 East Campbell Avenue, Suite 200, Phoenix, AZ 85016,

602-954-9131

Construction manager: None

**Groundbreaking:** January 1984

Finish date: June 1985

Construction time: 17 months

Design capacity: 540 **Total cost:** \$4,700,000

Total annual operating costs: N/A

(addition)

Category: New, ancillary building

Facility type: State prison

**Building configuration:** Campus style

#### Costs

Total: \$4,700,000

Building only: \$2,218,630 Housing area: \$2,009,088

Housing per inmate: \$3,805 Housing per cell: \$41,856 (dorm)

Total per inmate: \$8,704 Total per GSF: \$42.55

Total annual operating costs: N/A

(addition)

# Security

Perimeter: Double fence; alarm/ detection system; razor wire on

fence; patrols Inmate security level: Maximum: 0

Medium: 98% (+ 2% hard medium)

Minimum: 0

#### Inmate cells

Doors/material: Wooden; steel

Doors/type: Swinging Doors/locking: Unlocked Floor surface: Sealed concrete Intercom: One-way to common areas

HVAC: Evaporative cooling; heating/air circulation only; individual gas-fired

heating units Plumbing: China Furniture: Steel

Fire protection: Smoke detectors for cells

#### **Dimensions**

Gross square feet/corrections: 110,450

Gross square feet/other: 0 Gross square feet/total: 110,450 Housing area square feet: 46,080 Gross square feet per inmate: 205 Size of cells: 680 square feet per

quonset hut

Net/gross square feet: N/A

# **Construction type**

Structural: Steel frame

Exterior walls: CMU block; corrugated

metal

Interior walls: CMU block; gyp board Exterior surface/facade: Stucco; paint

### **Inmate design capacity**

Single occupancy: 0 Double occupancy: 0

Dorms: 528

Special housing: 12 General population: 528

Total: 540

#### **Current staff**

Full-time equivalent: Administration: 6 Security: 141

> Programs/treatment: 6 Maintenance: 1

Total: 154 (addition only) Current inmate/staff ratio: 3.66:1

## **Inmate housing areas**

Design: Dormitory-style quonset huts

Cells per unit: N/A Inmates per unit: 11

Management type: Intermittent

surveillance

October 1985 population: 563 Facility commitment: State prisoners Means to handle crowding: Beds in

day spaces

## **Construction process**

Finance method: State funds Contract method: Construction management fast track; owner built

(inmate labor)

Use of inmate labor: Extensive; 95% of

construction

Use of prefabrication: Extensive; huts and preengineered metal buildings


### Architect's reported analyses

Factors affecting construction costs: Positive: Use of prefabricated components; simple construction methods; less expensive materials and hardware; limited need of contract work

Negative: Slow inmate labor; government procedures, regulations, "red tape"; complex electronic, mechanical, and electrical systems

Factors affecting time schedule: Positive: Use of prefabricated components; simple construction methods; coordination of design

Negative: Labor problems; government 'red tape"; complex electronic, mechanical, and electrical systems



# Arizona State Prison-Perryville

Jurisdiction official: Samuel A. Lewis, Director, Department of Corrections

Contact: Warden William Rhode, Arizona State Prison—Perryville, P.O. Box 3000, Goodyear, AZ 85338, 602–935–9371

Architect: Varney, Sexton, Lunsford, Aye/Gruzen Associated Architects, 2001 East Campbell Avenue, Suite 200, Phoenix, AZ 85016,

602-954-9131

Construction manager: Kitchell, CEM, Inc., 1006 South 24th Street, Phoenix, AZ 85034, 602-275-7541

**Groundbreaking:** November 1979

Finish date: April 1983
Construction time: 41 months

Design capacity: 1,200 Total cost: \$42,600,000

Total annual operating costs:

\$17,058,600

Category: New, ind. fac.; expansion; phased project (past); temp. housing

Facility type: State prison

Building configuration: Campus style

#### **Costs**

Total: \$42,600,000

Building only: \$41,000,000 Housing area: \$17,200,000 Housing per inmate: \$14,333 Housing per cell: \$14,333

Total per inmate: N/A Total per GSF: \$118.33

Total annual operating costs: \$17,058,600

#### **Dimensions**

Gross square feet/other: 0

Gross square feet/other: 0 Gross square feet/total: 360,000 Housing area square feet: 177,800 Gross square feet per inmate: 300 Size of cells: 80 square feet (single)

Net/gross square feet: 90%

# **Construction type**

Structural: Load bearing precast panels; steel frame; cast-in-place concrete frame

irame

Exterior walls: Precast panels; cast-inplace concrete; CMU block (court walls

of housing)

Interior walls: Precast panels; cast-inplace concrete; CMU block

Exterior surface/facade: Stucco; paint;

textured concrete

# Security

Perimeter: Single fence; alarm/ detection system; patrols Inmate security level: Maximum: 0

Medium: 83.3% Minimum: 16.7%

#### **Inmate cells**

Doors/material: Steel Doors/type: Swinging

Doors/locking: Remote locking only
Floor surface: Sealed concrete
Intercom: One-way to common areas
HVAC: Cooling by eval coolers; electric
duct heaters; rooftop package of

heating and cooling units Plumbing: China

Furniture: Steel Fire protection: Smoke detectors for cells

#### Inmate design capacity

Single occupancy: 1,200 Double occupancy: 0

Dorms: 0

Special housing: 0

General population: 1,200

Total: 1,200

#### **Current staff**

Full-time equivalent: Administration: 83 Security: 361

Programs/treatment: 96

Maintenance: 9 Total: 549

Current inmate/staff ratio: 2.55:1

#### **Inmate housing areas**

Design: Linear, outside Cells per unit: 96 Inmates per unit: 96

Management type: Direct supervision October 1985 population: 1,400 Facility commitment: State prisoners Means to handle crowding: Second bunk

permanently attached to wall

# **Construction process**

Finance method: State funds Contract method: Construction management fast track

Use of inmate labor: Limited; concrete flatwork; landscaping; fence; painting; furniture

Use of prefabrication: Moderate; tilt-up concrete; inmate room furniture


#### Architect's reported analyses

Factors affecting construction costs:
Positive: Use of prefabricated components;
simple construction methods; phased
construction; good competition; less
expensive materials and hardware;
inmate labor; local climate

Negative: Government regulations, "red tape"; complex electronic, mechanical, and electrical systems

Factors affecting time schedule:
Positive: Use of prefabricated components;
simple construction methods; phased
construction; advanced order of
materials and hardware; coordination
of design; advance site work
Negative: Government regulations,

"red tape"



# **Cochise County Jail**

Jurisdiction official: Jim V. Judd, Sheriff

Contact: Commander Paul Larimer, Cochise County Jail, Post Office Drawer F, Bisbee, AZ 85603, 602-432-2267

Architect: Lescher & Mahoney, Inc., 1130 East Missouri, Suite 850, Phoenix, AZ 85014, 602-264-6803

Construction manager: Reese-Carr, 4350 East Camelback, 160-C Camelsquare, Phoenix, AZ 85018, 602-952-8171

Groundbreaking: November 1983

Finish date: June 1985

**Construction time:** 19 months

**Design capacity:** 162 **Total cost:** \$4,248,400

Total annual operating costs: \$847,531

Category: New, independent facility

Facility type: County jail

**Inmate housing areas** 

Design: Module/pod

surveillance

Cells per unit: 8 to 16

Inmates per unit: 8 to 16

Management type: Intermittent

October 1985 population: 150

Means to handle crowding: N/A

Facility commitment: Local jail inmates

**Building configuration:** Integrated

structure

#### **Costs**

Total: \$4,248,400

Building only: \$3,855,400 Housing area: \$3,600,000 Housing per inmate: \$22,500 Housing per cell: \$22,500

Total per inmate: \$26,225 Total per GSF: \$89.59

Inmate security level:

Medium: 100%

Maximum: 0

Minimum: 0

Total annual operating costs: \$847,531

Perimeter: Alarm/detection system

#### **Dimensions**

Gross square feet/corrections: 47,420

Gross square feet/other: 0 Gross square feet/total: 47,420 Housing area square feet: 42,000 Gross square feet per inmate: 293 Size of cells: 80 square feet (single)

Net/gross square feet: 89%

# **Construction type**

Structural: Load bearing CMU Exterior walls: CMU block; precast

concrete roof

Interior walls: CIP concrete; CMU block; reinf. mas. walls; conc. mez. slabs;

floor slabs

Exterior surface/facade: Brick; textured

concrete

# Construction process

Finance method: G.O. Bonds Contract method: Conventional Use of inmate labor: None

Use of prefabrication: Limited, precast

concrete tees at roof

#### **Inmate cells**

Security

Doors/material: Steel Doors/type: Swinging

Doors/locking: Manual and remote

locking

Floor surface: Vinyl composition tile Intercom: Two-way between sallyport

and control room

HVAC: Air conditioning; solar; conv./elect. heating plant

Plumbing: China Furniture: Steel

Fire protection: Smoke detectors for

cells and common areas

#### **Inmate design capacity**

Single occupancy: 160 Double occupancy: 0

Dorms: 0

Special housing: 2 General population: 160

Total: 162

# Architect's reported analyses

Factors affecting construction costs: Positive: Good competition, favorable market; quality of bidding documents

Negative: None

Factors affecting time schedule:

Positive: Local bond issue; condition of

existing county jail

Negative: Financial condition of the

low bidder


#### **Current staff**

Full-time equivalent: Administration: 7 Security: 23

Programs/treatment: 1 Maintenance: 7

Total: 38

Current inmate/staff ratio: 3.95:1



#### **Federal Correctional Institution**

Jurisdiction official: J. Michael Quinlan, Director, Bureau of Prisons

Contact: Warden Peter M. Carlson, Federal Correctional Institution, P.O. Box 1680, Black Canyon Stage I, Phoenix, AZ 85029,

602-256-0924

Architect: Lescher & Mahoney, Inc., 1130 East Missouri, Suite 850, Phoenix, AZ 85014, 602–264–6803

Construction manager: None

**Groundbreaking:** November 1983

Finish date: June 1985

Construction time: 19 months

Design capacity: 575 **Total cost:** \$21,035,950

**Total annual operating costs:** 

\$6,877,000

Category: New, independent facility

Facility type: Federal prison Building configuration: Campus style

Costs

Total: \$21,035,950

Building only: \$16,059,500 Housing area: \$6,581,000 Housing per inmate: \$11,566 Housing per cell: \$11,566 Total per inmate: \$36,584

Total per GSF: \$68.05

Total annual operating costs: \$6,877,000

**Dimensions** 

Gross square feet/corrections: 309,126

Gross square feet/other: 0 Gross square feet/total: 309,126 Housing area square feet: 127,272 Gross square feet per inmate: 538 Size of cells: 81 square feet (single)

Net/gross square feet: 84%

Construction type

Structural: Load bearing masonry; precast

Exterior walls: Brick/block Interior walls: Brick/block

Exterior surface/facade: Brick; textured

concrete

**Security** 

Perimeter: Double fence; razor wire on and between fences; alarm/detection

system

Inmate security level: Maximum: 0 Medium: 100% Minimum: 0

**Inmate cells** 

Doors/material: Wooden; steel

Doors/type: Swinging

Doors/locking: Remote locking; manual

locking

Floor surface: Carpet; vinyl composition

tile

Intercom: Two-way between sallyport and

control room

HVAC: Air conditioning; solar; conventional heating plant

Plumbing: China

Furniture: Wood; vinyl/plastic

Fire protection: Smoke detectors for cells

roof system and floor planks

Inmate design capacity

Single occupancy: 569 Double occupancy: 0

Dorms: 0

Special housing: 6 General population: 569

Total: 575

**Current staff** 

Full-time equivalent: Administration: 31 Security: 100

Programs/treatment: 68

Maintenance: 14 Total: 213

Current inmate/staff ratio: 1.26:1

**Inmate housing areas** 

Design: Module/pod

Cells per unit: 132 module/66 pod Inmates per unit: 132 module/66 pod Management type: Direct supervision

October 1985 population: 268

Facility commitment: Federal prisoners Means to handling crowding: Bunk beds

in cell

**Construction process** 

Finance method: Federal funds Contract method: 7 separate phased

packages

Use of inmate labor: None

Use of prefabrication: Limited; precast

concrete roof tees

Architect's reported analyses

Factors affecting construction costs: Positive: Good competition, favorable


market; positive bidding climate; repetition of building types and construction systems; excellent weather

conditions Negative: None

Factors affecting time schedule:

Positive: Coordination of design between parties; architect's ability to maintain schedule through 7 fast-tracked bid packages; excellent weather conditions

Negative: None



#### **Federal Correctional Institution**

Jurisdiction official: J. Michael Quinlan, Director, Bureau of Prisons

Contact: Warden William A. Perrill, Federal Correctional Institution, 8901 South Wilmot Road, Tucson, AZ 85706, 602–294–4404

Architect: Federal Bureau of Prisons, 320 First Street NW., Washington, DC 20534, 202-272-6522

Construction manager: None

Groundbreaking: June 1980 Finish date: February 1982 Construction time: 20 months **Design capacity:** 190 **Total cost:** \$6,286,707

**Total annual operating costs:** 

\$3,824,900

Category: New, independent facility

Facility type: Federal prison
Building configuration: Campus style

#### Costs

Total: \$6,286,707

Building only: \$5,132,174 Housing area: \$2,375,000 Housing per inmate: \$13,268 Housing per cell: \$12,633 Total per inmate: \$33,088 Total per GSF: \$98.72

Total annual operating costs: \$3,824,900

#### **Dimensions**

Gross square feet/corrections: 63,685

Gross square feet/other: 0 Gross square feet/total: 63,685 Housing area square feet: 43,302 Gross square feet per inmate: 335 Size of cells: 70 square feet

(single)

Net/gross square feet: 69%

### Inmate housing areas

Design: Module/pod Cells per unit: 94 Inmates per unit: 89

Management type: Direct supervision

October 1985 population: 380

Facility commitment: Federal prisoners Means to handle crowding: Bunk beds in

cell

#### Security

Perimeter: Double fence, alarm/detection system; razor wire on and between

fences; patrols
Inmate security level:
Maximum: Varies
Medium: Varies
Minimum: Varies

# **Construction type**

Structural: Load bearing precast panels; steel frame; load bearing block Exterior walls: Precast panels; CIP

concrete; CMU block

Interior walls: Precast panels; CIP

concrete; CMU block Exterior surface/facade: Stucco

# **Construction process**

Finance method: Federal funds Contract method: Conventional Use of inmate labor: None Use of prefabrication: Limited

#### **Inmate cells**

Doors/material: Solid; wooden

Doors/type: Swinging

Doors/locking: Manual locking

Floor surface: Vinyl tile

Intercom: Two-way to common areas HVAC: Air conditioning; forced air

packaged heating unit Plumbing: China Furniture: Wood

Fire protection: Smoke detectors for cells and common areas; manual alarm stations; automatic alarm to detectors

# Inmate design capacity

Single occupancy: 179 Double occupancy: 0

Dorms: 0

Special housing: 11 General population: 179

Total: 190

# **Current staff**

Full-time equivalent: Administration: 23 Security: 51

Programs/treatment: 25 Maintenance: 14

Total: 113

Current inmate/staff ratio: 3.36:1

#### Architect's reported analyses

Factors affecting construction costs:
Positive: Use of prefabricated components;
simple construction methods; phased
construction; good competition; less
expensive materials and hardware;
ideal site conditions


Negative: Most of the space was high cost (housing, food preparation, etc.)

Factors affecting time schedule:

Positive: Use of prefabricated components; simple construction methods; phased construction; good bidding climate; coordination between owner and contractor

Negative: Slow responses from vendors, suppliers (long lead times for security

hardware, etc.)



# **Pima County Adult Detention Center**

Jurisdiction official: Clarence Dupnik, Sheriff

Contact: Major Dennis Douglas, Pima County Adult Detention Center, 1270 West Silverlake Road, P.O. Box 910, Tucson,

AZ 85702, 602-882-2848

Architect: Architecture One, Ltd., 6303 East Tanque Verde, S-200, Tucson, AZ 85715, 602–722–0400 Construction manager: Kitchell, CEM, Inc., 1006 South 24th Street, Phoenix, AZ 85034, 602–275–7541

**Groundbreaking:** July 1981 **Finish date:** July 1984

Construction time: 37 months

Design capacity: 499 Total cost: \$14,800,000 Total annual operating costs:

\$10,250,000

Category: New, independent facility

Facility type: County jail

Building configuration: High rise

#### Costs

Total: \$14,800,000

Building only: \$14,100,000 Housing area: \$13,200,000 Housing per inmate: \$28,205 Housing per cell: \$28,205 Total per inmate: \$29,659 Total per GSF: \$105.71

Total annual operating costs: \$10,250,000

#### **Dimensions**

Gross square feet/corrections: 140,000 Gross square feet/other: 0

Gross square feet/total: 140,000 Housing area square feet: 76,999 Gross square feet per inmate: 281 Size of cells: 71 square feet (single)

Net/gross square feet: 80%

# **Construction type**

Structural: Cast-in-place concrete frame Exterior walls: Cast-in-place concrete;

CMU block

Interior walls: Cast-in-place concrete;

CMU block

Exterior surface/facade: Stucco; paint

# Security

Perimeter: Building exterior; double fence; razor wire on and between

fences

Inmate security level:
Maximum: 15%
Medium: 85%
Minimum: 0

#### **Inmate cells**

Doors/material: Steel Doors/type: Swinging

Doors/locking: Remote locking
Floor surface: Carpet; sealed concrete
Intercom: Two-way to common areas
HVAC: Evaporative cooling; boiler
Plumbing: Stainless combination unit

Furniture: Steel; vinyl/plastic Fire protection: Smoke detectors for cells

and common areas; sprinklers for common areas; manual alarm stations

# Inmate design capacity

Single occupancy: 468 Double occupancy: 0

Dorms: 0

Special housing: 31 General population: 468

Total: 499

#### **Current staff**

Full-time equivalent: Administration: 53 Security: 240

Programs/treatment: 36 Maintenance: 13

Total: 342

Current inmate/staff ratio: 1.11:1

#### **Inmate housing areas**

Design: Module/pod Cells per unit: 36 Inmates per unit: 36

Management type: Direct supervision

October 1985 population: 380

Facility commitment: Local jail inmates Means to handle crowding: Beds in dayroom; second bunk can be attached

to wall

# **Construction process**


Finance method: G.O. Bonds Contract method: Conventional Use of inmate labor: None Use of prefabrication: None

# Architect's reported analyses

Factors affecting construction costs: Positive: Repetitiveness of design; good competition, favorable market; use of cast-in-place concrete

Negative: Government procedures, regulations, "red tape"; complex security electronics systems

Factors affecting time schedule:
Positive: Repetitiveness of design; owner and architect had onsite representation
Negative: Use of cast-in-place concrete; special design of cell light fixtures; government procedures, regulations, "red tape"; complex security electronics systems



# **Pima County Adult Detention Center (Addition)**

Jurisdiction official: Clarence Dupnik, Sheriff

Contact: Major Dennis Douglas, Pima County Adult Detention Center, 1270 West Silverlake Road, P.O. Box 910, Tucson,

AZ 85702, 602-882-2848

Architect: Architecture One, Ltd., 6303 East Tanque Verde, S-200, Tucson, AZ 85715, 602–722–0400

Construction manager: Reese-Carr, 4350 East Camelback, 160 C Camel Square, Phoenix, AZ 85018, 602–952–8171

**Groundbreaking:** July 1984 Finish date: August 1986 Construction time: 25 months

Design capacity: 282 Total cost: \$8,400,000 Total annual operating costs: \$4,200,615 (addition only)

Category: New, ancillary building Facility type: County jail Building configuration: Wheel

#### Costs

Total: \$8,400,000

Building only: \$7,900,000 Housing area: \$7,000,000 Housing per inmate: \$26,415 Housing per cell: \$55,118 Total per inmate: \$29,787 Total per GSF: \$102.43

Total annual operating costs: \$4,200,615

(addition only)

#### Security

Perimeter: Building exterior only

Inmate security level: Maximum: 0 Medium: 45% Minimum: 55%

**Dimensions** 

Gross square feet/corrections: 82,000

Gross square feet/other: 0 Gross square feet/total: 82,000 Housing area square feet: 33,273 Gross square feet per inmate: 291 Size of cells: 71 square feet (single)

Net/gross square feet: 83%

## **Construction type**

Structural: Cast-in-place concrete frame Exterior walls: Cast-in-place concrete;

CMU block

Interior walls: Cast-in-place concrete;

CMU block

Exterior surface/facade: Stucco; paint

## Inmate design capacity

Single occupancy: 121 Double occupancy: 0

Dorms: 144

Special housing: 17 General population: 265

Total: 282

#### Inmate cells

Doors/material: Steel Doors/type: Swinging

Doors/locking: Remote locking Floor surface: Carpet; sealed concrete Intercom: Two-way to cells and common

areas

HVAC: Evaporative cooling; boiler

Plumbing: China

Furniture: Steel; vinyl/plastic Fire protection: Smoke detectors for cells and common areas; sprinklers for common areas; manual alarm stations

#### **Current staff**

Full-time equivalent: Administration: 5 Security: 56

Programs/treatment: 13

Maintenance: 3

Total: 77 (addition only) Current inmate/staff ratio: N/A

## **Inmate housing areas**

Design: Module/pod Cells per unit: 48 Inmates per unit: 48

Management type: Direct supervision

October 1985 population: N/A

Facility commitment: Local jail inmates Means to handle crowding: Beds in

dayroom

#### **Construction process**

Finance method: G.O. Bonds Contract method: Conventional Use of inmate labor: None Use of prefabrication: None

#### Architect's reported analyses


Factors affecting construction costs: Positive: Repetitiveness of design; less expensive materials and hardware; use

of cast-in-place concrete

Negative: Slow construction, lengthy building time; compact site; government procedures, regulations, "red

tape"

Factors affecting time schedule: Positive: Repetitiveness of design Negative: Labor problems; complex electronic, mechanical, and electrical systems



# **Pinal Mountain Juvenile Institution**

Jurisdiction official: Carol Moore, Assistant Director, Juvenile and Community Services

Contact: Superintendent Ben Meyers, Pinal Mountain Juvenile Institution, P.O. Box 2799, Globe, AZ 85501, 602–425–7174

Architect: DLR Group/Lescher and Mahoney, 1130 East Missouri, Suite 850, Phoenix, AZ 85014, 602-264-6803

Construction manager: None

Groundbreaking: August 1986 Finish date: November 1987 Construction time: 15 months

**Design capacity:** 144 **Total cost:** \$3,215,320

Total annual operating costs: Unknown

Category: New, independent facility Facility type: Juvenile correctional

facility

Building configuration: Campus style

#### Costs

Total: \$3,215,320 Building only: \$2,629,592 Housing area: \$1,492,304 Housing per inmate: \$10,363 Housing per cell: \$33,916 Total per inmate: \$22,326 Total per GSF: \$88.18

Total annual operating costs: Unknown

#### **Dimensions**

Gross square feet/corrections: 36,464 Gross square feet/other: 0 Gross square feet/total: 36,464 Housing area square feet: 16,100 Gross square feet per inmate: 224 Size of cells: 80 square feet (double); 650

(dorms)

Net/gross square feet: 85%

# **Inmate housing areas**

Design: Linear, outside Cells per unit: 20 Inmates per unit: 36

Management type: Remote surveillance

December 1987 population: 0

Facility commitment: Juvenile offenders Means to handle crowding: Unknown

## Security

Perimeter: Single fence Inmate security level: Maximum: 0 Medium: 0 Minimum: 100%

# **Construction type**

Structural: Masonry bearing Exterior walls: CMU block

Interior walls: CMU block; wood frame Exterior surface/facade: Textured concrete;

colored concrete

# **Construction process**

Finance method: State funds Contract method: Conventional

Use of inmate labor: Limited; landscaping/

fencing

Use of prefabrication: Moderate; precast

concrete roof system

#### **Inmate cells**

Doors/material: Solid; wooden Doors/type: Swinging Doors/locking: No locks Floor surface: Sealed concrete Intercom: Unknown

HVAC: Heating/air circulation; gas heat

Plumbing: China Furniture: Unknown

Fire protection: Sprinklers for cells and

common areas

# Inmate design capacity

Single occupancy: 0 Double occupancy: 80

Dorms: 64 Special housing: 0 General population: 144

Total: 144

# Architect's reported analyses

Factors affecting construction costs: Positive: Simple construction methods, repetitiveness of design; good competition, favorable market; less expensive materials and hardware

Negative: None

Factors affecting time schedule:

Positive: Simple construction methods,

repetitiveness of design

Negative: None


#### **Current staff**

Full-time equivalent:
Administration: 14
Security: 49

Programs/treatment: 29 Maintenance: 10

Total: 102

Current inmate/staff ratio: N/A



# Sacaton Juvenile Rehabilitation Center (Addition)

Jurisdiction official: Henry L. Spomer, Agency Special Officer, Bureau of Indian Affairs

Contact: Captain James Burgess, Sacaton Juvenile Rehabilitation Center, P.O. Box 568, Usis #7 & Canal, Sacaton, AZ 85247,

602-562-3361

Architect: Franz Zwolensky Associates, Architecture/Planning, 3150 North 24th Street, Suite 205-A, Phoenix, AZ 85016,

602-224-9738

Construction manager: None

Groundbreaking: July 1984 Finish date: April 1985 Construction time: 9 months **Design capacity:** 40 **Total cost:** \$1,268,093

Total annual operating costs: \$576,921

(addition only)

Category: New, ancillary building
Facility type: Bureau of Indian Affairs
juvenile rehabilitation center
Building configuration: Integrated

structure

#### **Costs**

Total: \$1,268,093 Building only: \$1,177,951

Housing area: Unknown Housing per inmate: Unknown Housing per cell: Unknown Total per inmate: \$31,702 Total per GSF: \$162.58

Total annual operating costs: \$576,921

(addition only)

#### Security

Perimeter: Building exterior only; single fence with razor wire; patrols; camera

surveillance
Inmate security level:
Maximum: 0
Medium: 30%
Minimum: 70%

#### **Inmate cells**

Doors/material: Steel Doors/type: Sliding

Doors/locking: Motor driven and remote

locking; manual locking

Floor surface: Sealed concrete; padding in

isolation

Intercom: Two-way to cells; one-way to

common areas

HVAC: Heating/air circulation; gas heat Plumbing: Stainless combination unit

Furniture: Steel

Fire protection: Smoke detectors and sprinklers for cells and common areas;

manual alarm stations

#### **Dimensions**

Gross square feet/corrections: 7,800 Gross square feet/other: 0

Gross square feet/other: 0
Gross square feet/total: 7,800
Housing area square feet: 5,230
Gross square feet per inmate: 195
Size of cells: 90 square feet (double);
84 (spec. single); 204 (spec. dorms)

Net/gross square feet: 74%

## **Construction type**

Structural: Steel frame; load bearing CMU

waiis

Exterior walls: CMU block Interior walls: CMU block

Exterior surface/facade: Stucco; split face

CMU block

# Inmate design capacity

Single occupancy: 0 Double occupancy: 4

Dorms: 20

Special housing: 16 General population: 24

Total: 40

#### **Current staff**

Full-time equivalent: Administration: 6

Security: 14

Programs/treatment: 4
Maintenance: 0

Total: 24 (addition only)
Current inmate/staff ratio: 0.67:1

#### **Inmate housing areas**

Design: Linear, outside; linear, inside

Cells per unit: Unknown Inmates per unit: Unknown

Management type: Intermittent surveil-

lance; remote surveillance
June 1987 population: 16
Facility commitment: Juveniles
Means to handle crowding: Unknown

## **Construction process**

Finance method: Federal funds Contract method: Conventional Use of inmate labor: None Use of prefabrication: None

### Architect's reported analyses

Factors affecting construction costs:
Positive: Simple construction methods,


repetitiveness of design

Negative: Government procedures, regulations, and red tape

Factors affecting time schedule:

Positive: Simple construction methods, repetitiveness of design; advanced order of materials and hardware; coordination of design, construction/owner

Negative: Government procedures, regulations, and red tape



# **Clark County Detention Facility (Expansion)**

Jurisdiction official: James A. "Al" Harris, Sheriff

Contact: Sheriff James A. "Al" Harris, Clark County Detention Facility, Courthouse Square, Arkadelphia, AR 71923, 501–246–2222

Architect: Burt Taggart & Associates/Architects, 4500 Burrow Drive, North Little Rock, AR 72116, 501–758–7443

Construction manager: None

Groundbreaking: October 1984

Finish date: May 1986

Construction time: 19 months

Design capacity: 32 **Total cost:** \$1,943,469

Total annual operating costs: \$192,652

(expansion only)

Category: Expansion project

Facility type: Complex: county jail, law enforcement, courts, county emergency

Building configuration: Integ. structure

Costs

Total: \$1,943,469

Building only: \$1,929,969

Housing area: \$964,125 Housing per inmate: \$40,172 Housing per cell: \$41,918

Total per inmate: N/A (complex)

Total per GSF: \$116.40

Total annual operating costs: \$192,652

(expansion only)

**Security** 

Perimeter: Building exterior; alarm/ detection systems; video camera

surveillance

Inmate security level:

Maximum: 100% Medium: 0

Minimum: 0

**Inmate cells** 

Doors/material: Steel Doors/type: Swinging

Doors/locking: Remote locking Floor surface: Epoxy coating; sealed

concrete

Intercom: Two-way to cells and common

HVAC: Air conditioning; heating/air

circulation; gas heat Plumbing: Stainless steel

Furniture: Steel

Fire protection: Smoke detectors and sprinklers for cells and common areas;

manual alarm stations

**Dimensions** 

Gross square feet/corrections: 7,713

Gross square feet/other: 8,983 Gross square feet/total: 16,696 Housing area square feet: 7,713 Gross square feet per inmate: 241 Size of cells: 74 square feet (single)

Net/gross square feet: 90%

**Construction type** 

Structural: Steel frame; cast-in-place concrete frame; reinforced CMU load

bearing walls

Exterior walls: Cast-in-place concrete;

CMU block; brick

Interior walls: Precast panels; cast-in-place

concrete; CMU block; brick

Exterior surface/facade: Brick; textured

concrete

Inmate design capacity

Single occupancy: 22 Double occupancy: 2

Dorms: 0

Special housing: 8 General population: 24

Total: 32

**Current staff** 

Full-time equivalent: Administration: 1

Security: 7

Programs/treatment: N/A

Maintenance: 1

Total: 9 (expansion only)

Current inmate/staff ratio: 2.22:1

**Inmate housing areas** 

Design: Module/pod Cells per unit: 23

Inmates per unit: 24

Management type: Remote surveillance

June 1986 population: 20

Facility commitment: Local jail inmates;

State prisoners

Means to handle crowding: None

**Construction process** 

Finance method: Special election; 2-year

county sales tax increase Contract method: Conventional

Use of inmate labor: None Use of prefabrication: Moderate; panels

for roof structure and ceilings

Architect's reported analyses

Factors affecting construction costs: Positive: Prefabricated components,

factory assembly; good competition,

favorable market


Negative: Slow construction, lengthy building time; complex electronic, mechanical, and electrical systems

Factors affecting time schedule:

Positive: Use of prefabricated components, factory assembly; simple construction methods, repetitiveness of design; coordination of design between

Negative: Slow responses and delivery from vendors, suppliers; weather

problems



## **Cummins Unit—Medium Security (Remodel/Expansion)**

Jurisdiction official: A.L. Lockhart, Director, Department of Correction

Contact: Warden W.H. Sargent, Cummins Unit, Arkansas Department of Corrections, P.O. Box 500, Grady, AR 71644,

501-479-3311

**Architect:** Wittenberg, Delony & Davidson, Inc., 840 Savets Federal Building, Little Rock, AR 72201, 501–376–6681 **Construction manager:** Con-Ark Construction Company, 610 Garland Street, Little Rock, AR 72201, 501–376–1371

Groundbreaking: December 1977

Finish date: April 1979

Construction time: 17 months

**Design capacity:** 184 **Total cost:** \$2,174,184

Total annual operating costs: \$600,586

(expansion only)

Category: Remodeling/renovation proj-

ect; expansion project

Facility type: State prison

Building configuration: Telephone pole

connecting housing pods

#### **Costs**

Total: \$2,174,184 Building only: N/A Housing area: N/A Housing per inmate: N/A Housing per cell: N/A Total per inmate: \$11,816

Total annual operating costs: \$600,586

(expansion only)

Total per GSF: \$56.21

## **Dimensions**

Gross square feet/corrections: 38,680 Gross square feet/other: 0 Gross square feet/total: 38,680

Housing area square feet: N/A Gross square feet per inmate: 210 Size of cells: 70 square feet (single)

Net/gross square feet: N/A

#### **Inmate housing areas**

Design: Module/pod Cells per unit: 92 Inmates per unit: 92

Management type: Remote surveillance

October 1985 population: 368
Facility commitment: State prisoners
Means to handle crowding: Second bunk

permanently attached to wall

## Security

Perimeter: Double fence Inmate security level: Maximum: 0 Medium: 100% Minimum: 0

### **Construction type**

Structural: Load bearing precast panels Exterior walls: Precast panels Interior walls: Precast panels Exterior surface/facade: Textured

concrete

#### **Construction process**

Finance method: State funds Contract method: Conventional Use of inmate labor: None

Use of prefabrication: Moderate, precast

concrete wall panels

#### **Inmate cells**

Doors/material: Steel Doors/type: Swinging

Doors/locking: Manual locking Floor surface: Sealed concrete Intercom: Two-way to common areas

HVAC: Air conditioning Plumbing: Stainless Furniture: Steel

Fire protection: Smoke detectors for cells and common areas; manual alarm

stations

#### Inmate design capacity

Single occupancy: 184 Double occupancy: 0

Dorms: 0

Special housing: 0 General population: 184

Total: 184

#### Architect's reported analyses

Factors affecting construction costs: Positive: Use of prefabricated

components, factory assembly; simple construction methods, repetitiveness of

design; less expensive materials and hardware

Negative: Building within existing prison

compound

Factors affecting time schedule: Positive: Use of prefabricated

components, factory assembly; simple

construction methods


Negative: None

#### **Current staff**

Full-time equivalent: Administration: 3 Security: 42

Programs/treatment: 6
Maintenance: 3

Total: 54 (addition only)
Current inmate/staff ratio: 6.81:1



TYPICAL 108 BED HOUSING UNIT

## **Garland County Detention Facility**

Jurisdiction official: Clay White, Sheriff

Contact: Sheriff Clay White, Garland County Detention Facility, 503 Ouachita Avenue, Hot Springs, AR 71901, 501-321-2683

Architect: Burt Taggart & Associates/Architects, 4500 Burrow Drive, North Little Rock, AR 72116, 501–758–7443

Construction manager: None

Groundbreaking: June 1984 Finish date: January 1986 Construction time: 19 months

**Design capacity:** 96 **Total cost:** \$3,757,412

Total annual operating costs: \$409,910

Category: New, independent facility

Facility type: County jail Building configuration: Clusters

#### Costs

Total: \$3,757,412

Building only: \$3,577,708 Housing area: \$2,983,608 Housing per inmate: \$37,295 Housing per cell: \$37,295 Total per inmate: \$39,140 Total per GSF: \$91.55

Total annual operating costs: \$409,910

#### **Dimensions**

Gross square feet/corrections: 41,041 Gross square feet/other: 0 Gross square feet/total: 41,041 Housing area square feet: 26,172 Gross square feet per inmate: 273 Size of cells: 82 square feet (single)

Net/gross square feet: 90%

### Inmate housing areas

Design: Linear, outside Cells per unit: 11 Inmates per unit: 11

Management type: Remote surveillance

June 1986 population: 72

Facility commitment: Local jail inmates Means to handle crowding: Unknown

## **Security**

Perimeter: Building exterior; video camera surveillance; razor wire at

exercise yard
Inmate security level:
Maximum: 100%
Medium: 0
Minimum: 0

## **Construction type**

Structural: Cast-in-place concrete frame; steel framing; CMU block

Exterior walls: Cast-in-place concrete; brick; architectural precast

Interior walls: Precast panels; cast-in-place

concrete; CMU block

Inmate design capacity

Single occupancy: 80 Double occupancy: 0

Special housing: 16

General population: 80

Exterior surface/facade: Brick; textured

concrete

Dorms: 0

Total: 96

## **Construction process**

Finance method: Local funds Contract method: Conventional Use of inmate labor: None

Use of prefabrication: Extensive; concrete

floor and ceiling slabs

#### **Inmate cells**

Doors/material: Solid Doors/type: Swinging

Doors/locking: Remote locking Floor surface: Carpet; sealed concrete;

vinyl tile

Intercom: Two-way to cells and common

areas

HVAC: Heating/air circulation; gas heat Plumbing: Stainless combination unit Furniture: Steel; wood; vinyl/plastic Fire protection: Smoke detectors and sprinklers for cells and common areas; manual alarm stations

## **Current staff**

Full-time equivalent: Administration: 1 Security: 19

> Programs/treatment: 0 Maintenance: 1

Total: 21

Current inmate/staff ratio: 3.43:1


## Architect's reported analyses

Factors affecting construction costs:
Positive: Prefabricated components,
factory assembly; simple construction
methods, repetitiveness of design; good
competition, favorable market
Negative: Attachment to existing systems

Factors affecting time schedule:
Positive: Use of prefabricated components, factory assembly; simple construction methods, repetitiveness of design

Negative: Weather problems; complex electronic, mechanical, and electrical

systems



## Maximum Security Unit, Tucker Unit

Jurisdiction official: A.L. Lockhart, Director, Department of Corrections

Contact: Warden Larry Norris, Maximum Security Unit, General Delivery, Tucker, AR 72168, 501–541–0040

Architect: Wittenberg, Delony & Davidson, Inc., 840 Savers Federal Building, Little Rock, AR 72201, 501-376-6681

Construction manager: None

Groundbreaking: December 1981 Finish date: February 1986 Construction time: 50 months Design capacity: 492 Total cost: \$10,694,000 Total annual operating costs: \$4,034,006

Category: New, independent facility Facility type: State prison Building configuration: Ladder, telephone pole

#### Costs

Total: \$10,694,000 Building only: N/A Housing area: \$4,800,000 Housing per inmate: \$11,111

Housing per inmate: \$11,111 Total per inmate: \$21,736 Total per GSF: \$64.11

Total annual operating costs: \$4,034,006

#### **Dimensions**

Gross square feet/corrections: 166,816 Gross square feet/other: 0 Gross square feet/total: 166,816 Housing area square feet: 96,044 Gross square feet per inmate: 339 Size of cells: 70 square feet (single)

Net/gross square feet: N/A

## Inmate housing areas

Design: Module/pod Cells per unit: 54 Inmates per unit: 54

Management type: Remote surveillance October 1985 population: 300

Facility commitment: State prisoners Means to handle crowding: None

#### **Security**

Perimeter: Double fence; razor wire on

fence; towers; patrols Inmate security level: Maximum: 100% Medium: 0 Minimum: 0

## **Construction type**

Structural: Load bearing masonry and precast concrete floor panels

Exterior walls: Brick

Interior walls: Precast panels; CMU block

Exterior surface/facade: Brick

## **Construction process**

Finance method: State funds

Contract method: Conventional; owner

build/inmate labor

Use of inmate labor: Extensive for

additional areas

Use of prefabrication: Limited

#### **Inmate cells**

Doors/material: Steel Doors/type: Sliding

Doors/locking: Motor driven and remote

locking

Floor surface: Sealed concrete Intercom: Two-way to common areas HVAC: Air conditioning; gas-fired boiler Plumbing: Stainless combination unit

Furniture: Steel

Fire protection: Smoke detectors for cells and common areas; manual alarm

stations

#### **Inmate design capacity**

Single occupancy: 432 Double occupancy: 0

Dorms: 0

Special housing: 60 General population: 432

Total: 492

#### Architect's reported analyses

Factors affecting construction costs: Positive: Use of inmate labor; ownerconstructed exterior utilities

Negative: None

Factors affecting time schedule: Positive: Phased construction


Negative: None

#### **Current staff**

Full-time equivalent: Administration: 26 Security: 107

Programs/treatment: 9 Maintenance: 7 Total: 149

Current inmate/staff ratio: 2.01:1



TYPICAL 108 BED HOUSING UNIT

## Saline County Detention Facility (New and Remodel)

Jurisdiction official: James Steed, Sheriff

Contact: Albert Wyllia, Jail Administrator, Saline County Detention Facility, Saline County Courthouse, Benton, AR 72015,

501-778-3611

Architect: Burt Taggart & Associates/Architects, 4500 Burrow Drive, North Little Rock, AR 72116, 501-758-7443

Construction manager: None

Groundbreaking: March 1982 Finish date: September 1983 Construction time: 18 months

Design capacity: 27 **Total cost:** \$856,713

**Dimensions** 

**Total annual operating costs:** \$137,459

Category: New, independent facility added to courthouse, with remodel of

old jail into county offices Facility type: County jail

Building configuration: Integrated

structure

#### Costs

Total: \$856,713 Building only: \$833,420 Housing area: \$552,200 Housing per inmate: \$42,477 Housing per cell: \$42,477

Total per inmate: N/A (complex)

Perimeter: Building exterior only

Total per GSF: \$93.91

Inmate security level:

Maximum: 0

Minimum: 0

Medium: 100%

Total annual operating costs: \$137,459

### Construction type

Structural: Steel frame, cast-in-place concrete frame, reinforced CMU load bearing walls

CMU block; granite

concrete; CMU block

granite veneer

#### **Inmate cells**

Security

Doors/material: Steel Doors/type: Swinging

Doors/locking: Remote locking Floor surface: Epoxy coating; sealed

concrete

Intercom: Two-way to cells and common

HVAC: Air conditioning; heating/air

circulation; gas heat Plumbing: Stainless steel

Furniture: Steel

Fire protection: Smoke detectors and sprinklers for common areas and cells;

manual alarm stations

Gross square feet/other: 1,392 Gross square feet/total: 9,123 Housing area square feet: 4,605 Gross square feet per inmate: 286 Size of cells: 74 square feet (single) Net/gross square feet: 91%

Gross square feet/corrections: 7,731

Exterior walls: Cast-in-place concrete;

Interior walls: Precast panels; cast-in-place

Exterior surface/facade: Earth berm and

#### Inmate design capacity

Single occupancy: 13 Double occupancy: 0

Dorms: 0

Special housing: 14 General population: 13

Total: 27

#### Current staff

Full-time equivalent: Administration: 1 Security: 4

> Programs/treatment: 0 Maintenance: 0

Total: 5

Current inmate/staff ratio: 3.60:1

## **Inmate housing areas**

Design: Module/pod Cells per unit: Unknown Inmates per unit: Unknown Management type: Intermittent

surveillance

June 1986 population: 18

Facility commitment: Local jail inmates;

State prisoners

Means to handle crowding: Neighboring jails

### **Construction process**

Finance method: Special election; local funds; 2-year county sales tax increase Contract method: Conventional Use of inmate labor: None Use of prefabrication: Limited; roof slabs

## **Architect's reported analyses**

Factors affecting construction costs: Positive: Prefabricated components, factory assembly; good competition,


favorable market

Negative: Difficult site conditions; complex electronic, mechanical, and

electrical systems

Factors affecting time schedule: Positive: Use of prefabricated components, factory assembly; simple construction methods, repetitiveness of design; coordination of design between parties

Negative: Weather problems



## Alameda County North County Jail

Jurisdiction official: Charles C. Plummer, Sheriff

Contact: Morris L. Hickerson, Facility Manager, Alameda County North County Jail, 550 6th Street, Oakland, CA 94607,

415-268-7763

Architect: Hellmuth, Obata & Kassabaum, Inc., One Lombard Street, San Francisco, CA 94111, 415-627-1600

Construction manager: None

**Groundbreaking:** May 1978 **Finish date:** July 1984

Construction time: 74 months

Design capacity: 596 Total cost: \$23,000,000 Total annual operating costs:

\$10,637,099

Category: New, independent facility

Facility type: County jail

Building configuration: Integrated

structure; high rise; clusters

#### Costs

Total: \$23,000,000

Building only: \$22,000,000 Housing area: \$15,000,000 Housing per inmate: \$26,042 Housing per cell: \$26,042 Total per inmate: \$38,591 Total per GSF: \$110.58

Total annual operating costs: \$10,637,099

Perimeter: Building exterior only

#### **Dimensions**

Gross square feet/corrections: 208,000

Gross square feet/other: 0 Gross square feet/total: 208,000 Housing area square feet: 144,000 Gross square feet per inmate: 349 Size of cells: 71 square feet (single) Net/gross square feet: Unknown

### **Construction type**

Structural: Cast-in-place concrete frame Exterior walls: Cast-in-place concrete

Interior walls: Gunite

Exterior surface/facade: Unknown

#### **Inmate housing areas**

Design: Module/pod Cells per unit: 48 Inmates per unit: 48

Management type: Remote surveillance

October 1985 population: 576

Facility commitment: Local jail inmates;

State prisoners

**Construction process** 

Use of inmate labor: None

Use of prefabrication: None

Finance method: Local funds

Contract method: Conventional

Means to handle crowding: Bunk beds in cell; second bunk attached to wall

## Inmate design capacity

Single occupancy: 576 Double occupancy: 0

Dorms: 0

Special housing: 20 General population: 576

Total: 596

## Architect's reported analyses

Factors affecting construction costs: Positive: Efficiency of area/bed plan; extensive value engineering

Negative: Slow construction, lengthy

building time

Factors affecting time schedule:

Positive: None

Negative: Performance of contractors

#### **Inmate cells**

**Security** 

Doors/material: Steel Doors/type: Swinging

Inmate security level:

Medium: 67%

Maximum: 16.5%

Minimum: 16.5%

Doors/locking: Remote locking only Floor surface: Sealed concrete

Intercom: One-way to cells; two-way to

common areas

HVAC: Heating/air circulation only

Plumbing: Stainless steel Furniture: Concrete

Fire protection: Smoke detectors for cells


#### **Current staff**


Full-time equivalent: Administration: 70 Security: 158

Programs/treatment: 22 Maintenance: 20

Total: 270

Current inmate/staff ratio: 2.13:1





#### **Typical Housing Level**

- 1 Cell 2 Dayroom 3 Counselor 4 Sally Port 5 Medical

- Multi-purpose
- 7 Exercise/Dining

#### **Typical Mezzanine Level**

- 1 Cell 2 Dayroom Below 3 Control 4 Sally Port Below

- Visiting

#### Section

- 1 Support 2 Courtroom 3 Jury Assembly 4 Municipal Offices 5 Traffic Court 6 Security Courts 7 Outdoor Exercise 8 Housing Level 9 Administration 9 Administration10 Intake Processing 11 Kitchen

#### California Correctional Institution

Jurisdiction official: James Rowland, Director, Department of Corrections

Contact: Superintendent B.J. Bunnell, California Correctional Institution, P.O. Box 1031, Tehachapi, CA 93561, 805-822-4402

Architect: VBN/Gruzen, 251 Post Street, San Francisco, CA 94108, 415–956–5515

Construction manager: Heery/VCM, 660 J Street, Sacramento, CA 95812, 916-448-8474

**Groundbreaking:** May 1982 Finish date: March 1986 Construction time: 46 months

Design capacity: 1,000 **Total cost:** \$71,108,726 **Total annual operating costs:** 

\$30,250,000

Category: New, independent facility

Facility type: State prison

**Building configuration:** Courtyard

#### Costs

Total: \$71,108,726

Building only: \$59,058,062 Housing area: \$39,093,518 Housing per inmate: \$39,094 Housing per cell: \$39,094 Total per inmate: \$71,109 Total per GSF: \$150.65

Total annual operating costs: \$30,250,000

#### **Dimensions**

Gross square feet/corrections: 472,000

Gross square feet/other: 0 Gross square feet/total: 472,000 Housing area square feet: 322,840 Gross square feet per inmate: 472 Size of cells: 86 square feet (single)

Net/gross square feet: 65%

# **Inmate housing areas**

Design: Module/pod Cells per unit: 62 and 64 Inmates per unit: 62 and 64

Management type: Remote surveillance March 1986 population: 1,000 Facility commitment: State prisoners Means to handle crowding: None

### Security

Perimeter: Double fence; alarm/detection

systems; towers Inmate security level: Maximum: 100% Medium: 0 Minimum: 0

## Construction type

Structural: Steel frame; cast-in-place

concrete frame

Exterior walls: Precast panels; cast-inplace concrete; CMU block

Interior walls: Cast-in-place; CMU block Exterior surface/facade: Paint; exterior

insulated finish system

# **Construction process**

Finance method: State funds Contract method: Conventional; construction management Use of inmate labor: None

Use of prefabrication: Precast concrete

exterior panels

#### **Inmate cells**

Doors/material: Steel Doors/type: Sliding

Doors/locking: Motor driven and remote

locking

Floor surface: Sealed concrete Intercom: Two-way to common areas HVAC: Heating/air circulation only; economizer energy cycle; central heating plant; steam and hot water

boiler

Plumbing: Stainless Furniture: Steel; concrete

Fire protection: Smoke detectors for cells and common areas; sprinklers for

common areas

#### Inmate design capacity

Single occupancy: 1,000 Double occupancy: 0

General population: 1,000

Total: 1,000

Dorms: 0 Special housing: 0

## **Current staff**

Full-time equivalent: Administration: 87 Security: 496

Programs/treatment: 73 Maintenance: 38 Total: 694

Current inmate/staff ratio: 1.44:1


#### Architect's reported analyses

Factors affecting construction costs: Positive: Simple construction methods, repetitiveness of design; good competition, favorable market Negative: Slow construction, lengthy

building time; difficult site conditions; government procedures, regulations, "red tape"; complex electronic, mechanical, and electrical systems Factors affecting time schedule:

Positive: None

Negative: Slow responses and delivery from vendors, suppliers; government procedures, regulations, "red tape"; complex electronic, mechanical, and electrical systems; remote location of site



## California Medical Facility—South

Jurisdiction official: James Rowland, Director, Department of Corrections

Contact: Superintendent Eddie Yost, California Medical Facility-South, P.O. Box 2000, Vacaville, CA 95696–4000, 707–448–6841

Architect: Giffels/Del Campo & Maru, 45 Lansing Street, San Francisco, CA 94105, 415-777-4025

Construction manager: O'Brien Kreitzberg Associates, P.O. Box 1088, Vacaville, CA 95696, 707-448-4168

Groundbreaking: January 1984 Finish date: August 1986 Construction time: 31 months

Design capacity: 2,404 Total cost: \$111,000,000 Total annual operating costs: \$39,973,996 Category: New, independent facility Facility type: State prison Building configuration: Campus style

#### **Costs**

Total: \$111,000,000 Building only: \$85,000,000 Housing area: \$43,000,000 Housing per inmate: \$17,887 Housing per cell: \$31,341 Total per inmate: \$46,173 Total per GSF: \$101.46

Total annual operating costs: \$39,973,996

#### **Dimensions**

Gross square feet/corrections: 1,094,000 Gross square feet/other: 0

Gross square feet/total: 1,094,000
Housing area square feet: 423,000
Gross square feet per inmate: 455

Size of cells: 60 square feet (single); 305

(dorms)

Net/gross square feet: Unknown

## **Inmate housing areas**

Design: Module/pod Cells per unit: 100 Inmates per unit: 100

Management type: Remote surveillance;

intermittent in dorms

December 1986 population: 3,719 Facility commitment: State prisoners Means to handle crowding: Additional

beds in dorms

#### Security

Perimeter: Double fence; microwave detection system; towers
Inmate security level:
Maximum: 0
Medium: 50%
Minimum: 50%

#### **Inmate cells**

Doors/material: Steel Doors/type: Sliding

Doors/locking: Remote locking

Floor surface: Linoleum; epoxy coating

Intercom: Unknown HVAC: Unknown Plumbing: China Furniture: Steel

Fire protection: Smoke detectors for cells

#### **Construction type**

Structural: Precast concrete; steel roof

frame

Exterior walls: Precast concrete Interior walls: Precast concrete Exterior surface/facade: Concrete

#### Inmate design capacity

Single occupancy: 1,200 Double occupancy: 0 Dorms: 1,204 Special housing: 0 General population: 2,404

Total: 2,404

#### **Current staff**

Full-time equivalent:
Administration: 184
Security: 689
Programs/treatment: 46
Maintenance: 112

Total: 1.031

Current inmate/staff ratio: 3.61:1

#### **Construction process**

Finance method: State funds

Contract method: Construction manage-

ment fast track

Use of inmate labor: Limited; landscap-

ing, irrigation, and painting

Use of prefabrication: Extensive; precast elements made, transported, and

erected by contractors

## Architect's reported analyses

Factors affecting construction costs: Positive: Quick decisionmaking; constant evaluation of cost estimates for a tightly

programmed facility

Negative: Fast schedule; multiple bid


packages

Factors affecting time schedule:
Positive: Advanced order of materials and

hardware; coordination of design between parties; willingness of entire team to work before contractual agreements were finalized; responsiveness of client

Negative: Portions of program required greater scrutiny partly due to cost

implications



## California State Prison—Sacramento County/Folsom

Jurisdiction official: James Rowland, Director, Department of Corrections

Contact: Warden R.G. Borg, California State Prison, P.O. Box 29, Represa, CA 95671, 916–985–8610 Architects: Dreyfuss and Blackford, 3540 Folsom Boulevard, Sacramento, CA 95814, 916–453–1231

Henningson, Durham, & Richardson, Inc., 12700 Hillcrest, Suite 125, Dallas, TX 75230, 214-980-0001

Construction manager: Heery/Vanir CM, 660 J Street, Sacramento CA 95814, 916-448-8474

Groundbreaking: November 1984 Finish date: October 1986 Construction time: 23 months Design capacity: 3,264 Total cost: \$125,962,000 Total annual operating costs: \$24,300,000 Category: New, independent facility Facility type: State prison

**Building configuration:** Courtyard

#### **Costs**

Total: \$125,962,000 Building only: \$111,740,515 Housing area: \$79,568,000 Housing per inmate: \$24,377 Housing per cell: \$51,268 Total per inmate: \$38,591 Total per GSF: \$100.88

Total annual operating costs: \$24,300,000

#### **Dimensions**

Gross square feet/corrections: 1,248,651 Gross square feet/other: 0 Gross square feet/total: 1,248,651 Housing area square feet: 512,036 Gross square feet per inmate: 383

Size of cells: 80 square feet (gen. double); 1,058 (dorms)

Net/gross square feet: Unknown

## **Inmate housing areas**

Design: Module/pod Cells per unit: 128 Inmates per unit: 256

Management type: Remote surveillance

May 1987 population: 2,656

Facility commitment: State prisoners Means to handle crowding: Second bunk

permanently attached to wall

## Security

Perimeter: Double fence; alarm/detection systems; razor wire on and between fences; towers; patrols

Inmate security level:

Maximum: 89%

Medium: 0

Minimum: 11%

## **Construction type**

Structural: Load-bearing precast panels; steel frame

Exterior walls: Precast panels; cast-in-

place concrete

Interior walls: Precast panels; cast-in-place

concrete; CMU block

Exterior surface/facade: Natural wall

#### **Construction process**

Finance method: G.O. Bonds

Contract method: Construction manage-

ment fast track

Use of inmate labor: None

Use of prefabrication: Limited; metal buildings for some functions

#### **Inmate cells**

Doors/material: Steel Doors/type: Sliding

Doors/locking: Motor driven and remote

locking

Floor surface: Sealed concrete Intercom: Two-way to common areas HVAC: Heating/air circulation; steam

neat

Plumbing: Stainless combination unit

Furniture: Steel

Fire protection: Smoke detectors for common areas; sprinklers for cells and common areas; manual alarm stations

#### Inmate design capacity

Single occupancy: 0 Double occupancy: 3,072

Dorms: 192 Special housing: 0 General population: 3,264

Total: 3,264

## **Current staff**

Full-time equivalent: Administration: 177 Security: 811

Programs/treatment: 66 Maintenance: 73

Total: 1,127

Current inmate/staff ratio: 2.36:1


#### Architects' reported analyses

Factors affecting construction costs: Positive: Repetitiveness of design; good competition, favorable market; less expensive materials and hardware; use of prefabrication;

Negative: Difficult site conditions; complex electronic and mechanical

systems

Factors affecting time schedule:
Positive: Simple construction methods;
phased construction, fast track CM;
advanced order of materials and
hardware; coordination of design
Negative: Labor problems; weather
problems; government red tape; complex electronic and mechanical systems



## **Contra Costa County Detention Facility**

Jurisdiction official: Richard Rainey, Sheriff

Contact: Larry Ard, Chief Deputy, Contra Costa County Detention Facility, 1000 Ward Street, Martinez, CA 94553, 415-646-4497 Architect: Kaplan/McLaughlin/Diaz, 222 Vallejo Street, San Francisco, CA 94111, 415-398-5191

Construction manager: Turner Construction Company, 353 Sacramento Street, San Francisco, CA 94111, 415-391-1310

Groundbreaking: September 1977 Finish date: December 1980 Construction time: 39 months

Design capacity: 386 Total cost: \$24,705,000 **Total annual operating costs:** 

\$8,736,000

Category: New, independent facility Facility type: Complex: county jail,

courts

Building configuration: Integrated structure; courtyard; clusters

#### Costs

Total: \$24,705,000 Building only: \$19,428,000 Housing area: Unknown Housing per inmate: Unknown Housing per cell: Unknown

Total per inmate: N/A (complex) Total per GSF: \$136.31

Total annual operating costs: \$8,736,000

## **Dimensions**

Gross square feet/corrections: 170,790 Gross square feet/other: 10,450 Gross square feet/total: 181,240 Housing area square feet: 77,410 Gross square feet per inmate: 442 Size of cells: 70 square feet (single) Net/gross square feet: 62%

# Design: Module/pod

Cells per unit: 46 Inmates per unit: 46 Management type: Direct supervision

October 1985 population: 573

**Inmate housing areas** 

Facility commitment: Local jail inmates,

State prisoners

Means to handle crowding: Mattresses on floor; beds in dayroom; second bunk

attached to wall

#### Security

Perimeter: Building exterior only

Inmate security level: Maximum: 32% Medium: 68% Minimum: 0

### **Construction type**

Structural: Steel frame

Exterior walls: Precast panels; CIP concrete; CMU block; architectural

precast

Interior walls: Precast panels; CIP

concrete: CMU block

Exterior surface/facade: Textured concrete

## **Construction process**

Finance method: Revenue sharing 75%;

property tax override 25%

Contract method: Construction manage-

ment fast track

Use of inmate labor: None

Use of prefabrication: Limited; precast

concrete wall panels

#### **Inmate cells**

Doors/material: Solid; metal-baffled

Doors/type: Swinging

Doors/locking: Remote locking with

manual override Floor surface: Carpet

Intercom: Two-way to common areas

(discipline housing) HVAC: Air conditioning Plumbing: China

Furniture: Wood Fire protection: Smoke detectors and sprinklers for cells and common areas

#### Inmate design capacity

Single occupancy: 305 Double occupancy: 0

Dorms: 0

Special housing: 81 General population: 305

Total: 386

#### **Current staff**

Full-time equivalent: Administration: 42 Security: 97

> Programs/treatment: 35 Maintenance: 10

Total: 184

Current inmate/staff ratio: 3.11:1

#### Architect's reported analyses

Factors affecting construction costs: Positive: Less expensive materials and

hardware

Negative: Slow construction, lengthy building time; high labor costs; complex

electronic, mechanical, and


electrical systems

Factors affecting time schedule: Positive: Use of prefabricated components,

factory assembly

Negative: Labor problems; complex electronic, mechanical, and electrical systems; building too complex for

fast track construction



## Elmwood—Barracks 24 (Addition)

Jurisdiction official: Robert E. Winter, Sheriff

Contact: Captain Dean Madeira, Facility Commander, Elmwood—Barracks 24, 701 South Abel Street, Milpitas, CA 95035,

408-299-2280

Architect: Bodrell Joer' dan Smith Partnership, Suite 350, 900 Veterans Boulevard, Redwood City, CA 94063, 415-369-3322

Construction manager: Morrison-Knudsen Company, 180 Howard Street, San Francisco, CA 94105, 415–442–7711

**Groundbreaking:** April 1985 **Finish date:** August 1985

**Design capacity:** 196 **Total cost:** \$3,158,000

Facility type: County jail

Category: New, ancillary building

Construction time: 4 months

**Total annual operating costs:** \$226,500

**Building configuration:** Integrated

(addition only)

structure

#### Costs

Total: \$3,158,000

Building only: \$2,850,000 Housing area: \$2,850,000 Housing per inmate: \$14,541 Housing per cell: \$356,250 Total per inmate: \$16,112

Total annual operating costs: \$226,500

(addition only)

Total per GSF: \$135.76

#### **Dimensions**

Gross square feet/corrections: 23,262

Gross square feet/other: 0 Gross square feet/total: 23,262 Housing area square feet: 23,262 Gross square feet per inmate: 119 Size of cells: 82 square feet (single)

Net/gross square feet: 98%

## **Inmate housing areas**

Design: Dormitory style Cells per unit: 1 Inmates per unit: 48

Management type: Remote surveillance

June 1986 population: 192

Facility commitment: Local jail inmates Means to handle crowding: None

#### **Security**

Perimeter: Single fence with razor wire; alarm/detection systems; camera

surveillance

Inmate security level:
Maximum: 0
Medium: 100%
Minimum: 0

## **Construction type**

Structural: Load bearing precast panels;

steel frame

Exterior walls: Precast panels

Interior walls: Cast-in-place concrete;

CMU block

Exterior surface/facade: Paint

## **Construction process**

Finance method: G.O. Bonds

Contract method: Turn-key design and

build

Use of inmate labor: None Use of prefabrication: Moderate

#### **Inmate cells**

Doors/material: Steel Doors/type: Sliding

Doors/locking: Motor driven and remote

locking

Floor surface: Sealed concrete

Intercom: Two-way to cells and common

areas

HVAC: Air conditioning; gas heat Plumbing: Stainless combination unit

Furniture: Steel

Fire protection: Smoke detectors for cells and common areas; manual alarm

stations

#### Inmate design capacity

Single occupancy: 4 Double occupancy: 0

Dorms: 192 Special housing: 0

General population: 196

Total: 196

#### **Current staff**

Full-time equivalent: Administration: N/A

Security: 5

Programs/treatment: N/A
Maintenance: N/A
Total: 5 (addition only)
Current inmate/staff ratio: 38.4:1

#### Architect's reported analyses

Factors affecting construction costs: Positive: Simple construction methods, repetitiveness of design; phased construction, fast track construction


management Negative: None

Factors affecting time schedule:

Positive: Coordination of design between parties; design/build contract with county for quick delivery time schedule

 $Negative: Weather \, problems, \, 4 \, weeks \, of \,$ 

rain



## **Foothill Communities Law & Justice Center**

Jurisdiction official: Harry Mays, County Attorney's Office

Contact: Richard Saenz, Director, Probation Department, Foothill Communities Law & Justice Center, 8303 Haven Avenue Rancho,

Cucamonga, CA 91730, 714-945-4000

Architect: HMC Architects, Inc., 500 East "E" Street, Ontario, CA 91764, 714-983-9623 Construction manager: M & E/CM, 8202 Aspen, Cucamonga, CA 91730, 714-945-4393

**Groundbreaking:** May 1983 Finish date: December 1986 Construction time: 41 months Design capacity: 94 **Total cost:** \$33,000,000

Total annual operating costs: Unknown

Category: New, independent facility Facility type: Complex: court, holding

facility

**Building configuration:** Integrated

structure

#### Costs

Total: \$33,000,000 Building only: \$32,500,000 Housing area: Unknown

Housing per inmate: Unknown Housing per cell: Unknown

Total per inmate: N/A (complex)

Total per GSF: \$118.00

Total annual operating costs: Unknown

#### **Dimensions**

Gross square feet/corrections: 14,157 Gross square feet/other: 265,515 Gross square feet/total: 279,672 Housing area square feet: 14,157 Gross square feet per inmate: 151 Size of cells: 72 square feet (single); 112

(double); 1,120 (dorms) Net/gross square feet: 86%

## **Inmate housing areas**

Design: Linear, inside Cells per unit: Unknown Inmates per unit: Unknown Management type: Intermittent

surveillance

Current population: Unknown

Facility commitment: Local iail inmates Means to handle crowding: Unknown

### Security

Perimeter: Building exterior only

Inmate security level: Maximum: 12% Medium: 60% Minimum: 28%

## Construction type

Structural: Steel frame; isolation

foundation

Exterior walls: Precast panels (GFRC)

Interior walls: CMU block

Exterior surface/facade: Textured concrete

(GFRC)

## **Construction process**

Finance method: G.O. Bonds

Contract method: Construction manage-

ment fast track

Use of inmate labor: None Use of prefabrication: Limited

#### **Inmate cells**

Doors/material: Steel

Doors/type: Swinging; sliding Doors/locking: Motor driven and

remote locking

Floor surface: Urethane coating Intercom: One-way to cells HVAC: Air conditioning; gas heat Plumbing: Stainless combination unit

Furniture: Concrete

Fire protection: Smoke detectors for common areas; sprinklers for cells

## Inmate design capacity

Single occupancy: 26 Double occupancy: 4

Dorms: 64 Special housing: 0 General population: 94

Total: 94

## **Current staff**

Full-time equivalent: Administration: Unknown

Security: Unknown Programs/treatment: Unknown

Maintenance: Unknown Total: Unknown

Current inmate/staff ratio: Unknown

#### Architect's reported analyses

Factors affecting construction costs: Positive: Good competition, favorable

market


Negative: Complex electronic, mechanical, and electrical systems; fast track construction management

Factors affecting time schedule:

Positive: Advanced order of materials and

hardware

Negative: Complex electronic, mechanical, and electrical systems



**BASEMENT FLOOR PLAN** 

## **Kings County Branch Jail**

Jurisdiction official: Tom Clark, Sheriff

Contact: Captain Bob Begley, Kings County Branch Jail, 690 East Drive, Hanford, CA 93230, 209-584-1431

Architect: Patrick Sullivan Associates, 542 High Street, Palo Alto, CA 94301, 415-327-2490

Construction manager: None

Groundbreaking: March 1985 Finish date: December 1985 Construction time: 9 months **Design capacity:** 128 **Total cost:** \$2,850,000

Total annual operating costs: \$1,080,347

Category: New, independent facility

Facility type: County jail

Building configuration: Integrated

structure

#### Costs

Total: \$2,850,000

Building only: \$2,400,000 Housing area: \$1,000,000 Housing per inmate: \$7,812 Housing per cell: \$125,000 Total per inmate: \$22,266 Total per GSF: \$109.62

Total annual operating costs: \$1,080,347

#### **Dimensions**

Gross square feet/corrections: 26,000

Gross square feet/other: 0 Gross square feet/total: 26,000 Housing area square feet: 13,500 Gross square feet per inate: 203 Size of dorms: 1,344 square feet

Net/gross square feet: 92%

## Inmate housing areas

Design: Dormitory style Cells per unit: 2 Inmates per unit: 32

Management type: Intermittent surveil-

lance

June 1986 population: 58

Facility commitment: Local jail inmates

(sentenced only)

Means to handle crowding: Unknown

## **Security**

Perimeter: Single fence Inmate security level: Maximum: 0

Medium: 0 Minimum: 100%

## **Construction type**

Structural: Tilt-up panels

Exterior walls: Tilt-up concrete panels Interior walls: Wood frame with gypsum Exterior surface/facade: Stucco; textured

concrete

### **Construction process**

Finance method: Local and State funds Contract method: Conventional

Use of inmate labor: None

Use of prefabrication: Moderate; tilt-up

wall panels

#### **Inmate cells**

Doors/material: Steel Doors/type: Swinging

Doors/locking: Remote and manual

locking

Floor surface: Vinyl tile

Intercom: Two-way to common areas and

dorms

HVAC: Air conditioning; hot water from

central plant Plumbing: China

Furniture: Wood; vinyl/plastic
Fire protection: Smoke detectors and
sprinklers for cells and common areas

#### Inmate design capacity

Single occupancy: 0 Double occupancy: 0

Dorms: 128 Special housing: 0 General population: 128

Total: 128

#### **Current staff**

Full-time equivalent: Administration: 1 Security: 19

Programs/treatment: 0 Maintenance: 4

Total: 24

Current inmate/staff ratio: 2.42:1

## Architect's reported analyses


Factors affecting construction costs: Positive: Simple construction methods, repetitiveness of design; good competition, favorable market; less expensive materials and hardware

Negative: None

Factors affecting time schedule: Positive: Use of prefabricated components; simple construction methods,

repetitiveness of design

Negative: None



## **Lacy Security Facility (Addition)**

Jurisdiction official: Brad Gates, Sheriff

Contact: Sheriff Brad Gates, Orange County, Box 449, Santa Ana, CA 92702, 714-647-1805

Architect: Ralph Allen and Partners, 520 North Main Street, Suite 200, Santa Ana, CA 92701, 714–547–7059 Construction manager: Kitchell CEM, Inc., 501 J Street, Suite 630, Sacramento, CA 95814, 916–442–3779

Groundbreaking: August 1985 Finish date: March 1986 Construction time: 7 months Design capacity: 180
Total cost: \$2,350,000
Total annual operating costs: \$1,195,815 (addition only)

Category: New, ancillary building

Facility type: County jail

**Building configuration:** Integrated

structure

#### **Costs**

Total: \$2,350,000

Building only: \$2,150,000 Housing area: \$2,350,000 Housing per inmate: \$13,056 Housing per cell: \$73,437 (dorm)

Total per inmate: \$13,056 Total per GSF: \$72.24

Total annual operating costs: \$1,195,815

(addition only)

#### Security

Perimeter: Building exterior; single fence; alarm/detection system; razor

wire on fence Inmate security level: Maximum: 0 Medium: Use, 100%

Minimum: Design, 100%

#### **Inmate cells**

Doors/material: None (open dorms)

Doors/type: N/A
Doors/locking: N/A

Floor surface: Sealed concrete; epoxy

coating; carpet Intercom: None

HVAC: Air conditioning; heating

Plumbing: Stainless steel

Furniture: Steel

Fire protection: Smoke detectors and sprinklers for cells and common areas;

manual alarm stations

#### **Dimensions**

Gross square feet/corrections: 32,529

Gross square feet/other: 0 Gross square feet/total: 32,529 Housing area square feet: 32,529 Gross square feet per inmate: 181 Size of cells: 465 and 315 square feet

(dorms)

Net/gross square feet: Unknown

## **Construction type**

Structural: Steel frame; tilt-up concrete

panels

Exterior walls: Tilt-up concrete panels

Interior walls: CMU block
Exterior surface/facade: Textured

concrete

#### Inmate design capacity

Single occupancy: 0 Double occupancy: 0

Dorms: 180 Special housing: 0 General population: 180

Total: 180

#### **Current staff**

Full-time equivalent: Administration: N/A

Security: 10

Programs/treatment: 1 Maintenance: N/A Total: 11 (addition only) Current inmate/staff ratio: 16.36:1

#### **Inmate housing areas**

Design: Module/pod Cells per unit: 32 dorms Inmates per unit: 32

Management type: Remote surveillance;

patrols

October 1985 population: 180

Facility commitment: Local jail inmates Means to handle crowding: Bunk beds in

cell; beds in dayroom

### **Construction process**

Finance method: Local funds Contract method: Conventional; construction management Use of inmate labor: None

Use of prefabrication: Yes, extensive;

tilt-up concrete panels


#### Architect's reported analyses

Factors affecting construction costs: Positive: Use of prefabricated components

Negative: None

Factors affecting time schedule:
Positive: Use of prefabricated components; advanced order of materials and hardware; coordination of design

between parties Negative: None



## **Nevada County Detention Center (Remodel)**

Jurisdiction official: William L. Heafey, Sheriff

Contact: Sergeant Bob Hammill, Facility Manager, Nevada County Detention Center, 10433 Willow Valley Road,

Nevada City, CA 95959, 916-265-9061

Architect: Patrick Sullivan Associates, 542 High Street, Palo Alto, CA 94301, 415–327–2490

Construction manager: None

Groundbreaking: March 1985 Finish date: November 1985 Construction time: 8 months Design capacity: 48 Total cost: \$221,416

Total annual operating costs:

\$387,000

Category: Remodel/renovation

Facility type: Restitution center of main

iail

Building configuration: Integrated

structure

**Costs** 

Total: \$221,416

Building only: Unknown Housing area: \$64,210 Housing per inmate: \$1,338 Housing per cell: \$3,777

Total per inmate: N/A (remodel)

Total per GSF: \$20.83

Total annual operating costs: \$387,000

**Dimensions** 

Gross square feet/corrections: 10,632

Gross square feet/other: 0 Gross square feet/total: 10,632 Housing area square feet: 3,115 Gross square feet per inmate: 221

Size of cells: Unknown

Net/gross square feet: Unknown

**Inmate housing areas** 

Design: Linear, outside Cells per unit: N/A Inmates per unit: N/A

Management type: Intermittent

surveillance

October 1985 population: 30 Facility commitment: Unknown Means to handle crowding: N/A

Security

Perimeter: Existing; new metal frame

and security mesh Inmate security level: Maximum: 0 Medium: 0 Minimum: 100% **Construction type** 

Structural: Wood frame Exterior walls: Poured in place concrete

(existing)

Interior walls: Wood frame and plaster

Exterior surface/facade: Plaster

**Construction process** 

Finance method: Local funds; State funds Contract method: Conventional Use of inmate labor: Yes, painting Use of prefabrication: None

**Inmate cells** 

Doors/material: Hollow metal

Doors/type: Swinging

Doors/locking: Manual and remote

locking

Floor surface: Linoleum; carpet

Intercom: Monitor HVAC: No alteration Plumbing: Stainless steel Furniture: Steel; wood

Fire protection: Station fire alarm

Inmate design capacity

Single occupancy: 2 Double occupancy: 14 Dorms: 32

Special housing: 0
General population: 48

Total: 48

Architect's reported analyses

Factors affecting construction costs:
Positive: Lightweight and common building materials; no phasing required around existing occupancy Negative: Unknown condition of existing

building

Factors affecting time schedule:

Positive: Onsite supervision by county

inspector Negative: None


**Current staff** 

Full-time equivalent: Administration: 2 Security: 13

Programs/treatment: 0
Maintenance: 1

Total: 16

Current inmate/staff ratio: 1.87:1



## Orange County Sheriff's Intake Release Center (Addition/Remodel/Expansion)

Jurisdiction official: Brad Gates, Sheriff-Coroner

Contact: Captain George King, Orange County Sheriff's Intake Release Center, 550 North Flower Street, Santa Ana, CA 92702.

714-834-2037

Architects: Hellmuth, Obata & Kassabaum, Inc., 1999 Bundy Drive, Suite 250, Los Angeles, CA 90025, 213-207-8400

Ficker & Ruffing, 610 Newport Center Drive, Suite 630, Newport Beach, CA 92660, 714-644-1581

Construction manager: Kitchell CEM, Inc., 1040 West Santa Ana Boulevard, Santa Ana, CA 92703, 714-836-7408

**Groundbreaking:** July 1985 Finish date: January 1988 Construction time: 29 months

Design capacity: 1,139 **Total cost:** \$43,500,000 Total annual operating costs: \$24,982,702 (entire facility)

Category: New, ancillary building: remodeling/renovation project; expan-

sion project

Facility type: County jail

Building configuration: Integ. structure

## Costs

Total: \$43,500,000 Building only: \$41,500,000 Housing area: \$27,500,000 Housing per inmate: \$71,615 Housing per cell: \$71,615

Total per inmate: N/A (remodel) Total per GSF: \$171.26

Total annual operating costs: \$24,982,702

(entire facility)

# Security

Perimeter: Building exterior only

Inmate security level: Maximum: 20% Medium: 80% Minimum: 0

**Inmate cells** 

areas

Doors/material: Steel

Doors/type: Swinging

Doors/locking: Remote locking

HVAC: Heating/air circulation

Plumbing: Stainless steel

Furniture: Steel; concrete

common areas

Floor surface: Sealed concrete; vinyl tile

Intercom: Two-way to cells and common

Fire protection: Smoke detectors for cells

and common areas; sprinklers for

#### **Dimensions**

Gross square feet/corrections: 254,000 Gross square feet/other: 0 Gross square feet/total: 254,000 Housing area square feet: 167,500 Gross square feet per inmate: 223 Size of cells: 81 square feet (single) Net/gross square feet: Unknown

## **Construction type**

Structural: Steel frame

Exterior walls: CMU block; architectural

precast

Exterior surface/facade: Textured concrete;

Interior walls: CMU block

colored concrete

#### Inmate design capacity

Single occupancy: 384 Double occupancy: 0

Special housing: 755

Total: 1,139

Dorms: 0

General population: 384

#### **Current staff**

Full-time equivalent: Administration: 56 Security: 189 Programs/treatment: 41

Maintenance: 33 Total: 319

Current inmate/staff ratio: 1.2:1

## **Inmate housing areas**

Design: Module/pod Cells per unit: 96 Inmates per unit: 96

Management type: Remote surveillance

January 1988 population: 384

Facility commitment: Local jail inmates Means to handle crowding: Second bunk

permanently attached to wall

## **Construction process**

Finance method: Local funds; State funds Contract method: Conventional; construc-

tion management

Use of inmate labor: Limited; some inmate furnishings from State Prison

Industries

Use of prefabrication: Limited; exterior

facing

## Architect's reported analyses

Factors affecting construction costs: Positive: Simple const. methods; "spartan" approach to materials/finishes/ furnishings; low-rise const.; experienced and savvy county staff


Negative: High labor costs; government red tape; very high security design; design for future jail population growth

Factors affecting time schedule:

Positive: Repetitiveness of design; phased const., CM; advanced order of materials; coordination of design; court pressures

Negative: Slow responses and delivery

from vendors, suppliers



## **Placer County Jail (Addition)**

Jurisdiction official: Donald J. Nunes, Sheriff/Coroner/Marshal

Contact: Captain Marvin Jacinto, Placer County Jail, DeWitt Center, P.O. Box 6990, Auburn, CA 95603, 916-823-4561

Architects: The Ehrenkrantz Group, 855 Front Street, San Francisco, CA 94111, 415-956-4394

Crippen, Lichau, Minta, 1115 High Street, Auburn, CA 95603, 916-885-7178

Construction manager: None

**Groundbreaking:** November 1983

Finish date: April 1985 Construction time: 17 months Design capacity: 212 **Total cost:** \$4,886,000

Total annual operating costs: \$2,305,029

(addition only)

**Dimensions** 

Category: New, ancillary building; phased project (future); temporary

facility/housing

mod. units

Cells per unit: 12

Inmates per unit: 24

remote surveillance

June 1986 population: 115

Facility type: Complex: county jail,

arraignment court

**Inmate housing areas** 

Building configuration: Integ. structure

Design: Module/pod; linear, outside for

Facility commitment: Local jail inmates Means to handle crowding: Mattresses on

Management type: Intermittent and

#### Costs

Total: \$4,886,000

Building only: \$4,635,000 Housing area: Unknown Housing per inmate: Unknown

Housing per cell: Unknown Total per inmate: N/A (complex)

Total per GSF: \$125.60

Total annual operating costs: \$2,305,029

(addition only)

#### **Security**

Perimeter: Building exterior; razor wire on double fences for exercise yard;

video camera surveillance Inmate security level:

Maximum: 21% Medium: 79% Minimum: 0

# **Construction type**

Structural: Load bearing precast panels and

CMU tilt-up; steel frame

Exterior walls: Precast panels; architectural

precast; tilt-up

Interior walls: Precast panels; CMU block;

steel stud/gypsum board

Exterior surface/facade: Brick; stucco;

paint

#### Gross square feet/corrections: 34,700

Gross square feet/other: 4,200 Gross square feet/total: 38,900 Housing area square feet: 16,364 Gross square feet per inmate: 164 Size of cells: 77 square feet (double)

Net/gross square feet: 63%

## floor **Construction process**

Finance method: Local and State funds

Contract method: Conventional Use of inmate labor: None Use of prefabrication: Limited

#### **Inmate cells**

Doors/material: Steel Doors/type: Swinging

Doors/locking: Motor driven and remote

locking; manual locking

Floor surface: Sealed concrete; vinyl tile Intercom: One-way to common areas HVAC: Air conditioning; gas heat Plumbing: China; stainless combination

unit

Furniture: Steel; vinyl/plastic

Fire protection: Smoke detectors for cells and common areas; sprinklers for common areas; manual alarm stations

#### Inmate design capacity

Single occupancy: 4 Double occupancy: 144

Dorms: 0

Special housing: 64 General population: 148

Total: 212

#### Current staff

Full-time equivalent: Administration: 10 Security: 45

Programs/treatment: N/A Maintenance: N/A Total: 55 (addition only) Current inmate/staff ratio: 2.09:1

#### Architects' reported analyses

Factors affecting construction costs: Positive: Simple construction methods, repetitiveness of design; tilt-up concrete wall panels; good competition,


favorable market

Negative: Difficult site conditions

Factors affecting time schedule: Postive: Simple construction methods, repetitiveness of design; tilt-up concrete wall panels; coordination of

design between parties

Negative: None



## Plumas County Sheriff's Department & Detention Facility (Remodel)

Jurisdiction official: William R. MacKenzie, Sheriff/Coroner

Contact: Sergeant Leonard Gardner, Plumas County Sheriff's Department, P.O. Box 1106, 50 Abernathy Lane, Quincy, CA 95971,

916-283-0400

Architect: Patrick Sullivan Associates, 542 High Street, Palo Alto, CA 94301, 415-327-2490

Construction manager: None

Groundbreaking: October 1984 Finish date: December 1985 Construction time: 14 months **Design capacity:** 35 **Total cost:** \$1,221,227

Total annual operating costs: \$232,600

Category: Remodel/renovation Facility type: County jail

**Inmate housing areas** 

Management type: Intermittent

October 1985 population: 25

Design: Linear, outside

Cells per unit: 10

surveillance

Inmates per unit: 10

Building configuration: Integrated

structure

#### Costs

Total: \$1,221,227 Building only: Unknown Housing area: \$635,000 Housing per inmate: \$19,844 Housing per cell: \$39,687

Total per inmate: N/A (remodel)

Total per GSF: \$124.55

Total annual operating costs: \$232,600

## Security

Perimeter: Concrete block; single fence

Inmate security level:
Maximum: Varies
Medium: Varies
Minimum: Varies

# **Dimensions**

Gross square feet/corrections: 9,805 Gross square feet/other: 0 Gross square feet/total: 9,805 Housing area square feet: 5,132 Gross square feet per inmate: 280 Size of cells: 108 square feet (single) Net/gross square feet: Unknown

#### **Construction type**

Structural: Concrete slab, metal deck (dorms), metal deck with concrete (single)

Exterior walls: Concrete block masonry

with exterior insulation

Interior walls: Concrete block masonry

walls

Exterior surface/facade: Stucco

# Construction process

mattress on floor

Finance method: Local funds; State funds Contract method: Conventional Use of inmate labor: None Use of prefabrication: None

Facility commitment: Local jail inmates

Means to handle crowding: Second

#### **Inmate cells**

Doors/material: Hollow metal

Doors/type: Swinging

Doors/locking: Manual and remote

locking

Floor surface: Sealed concrete Intercom: Two-way monitor

HVAC: Air conditioning; boiler heating

Plumbing: Stainless steel

Furniture: Steel

Fire protection: Smoke detectors and

sprinklers for cells

### Inmate design capacity

Single occupancy: 12 Double occupancy: 0

Dorms: 20 Special housing: 3 General population: 32

Total: 35

#### **Current staff**

Full-time equivalent: Administration: 1 Security: 7

Programs/treatment: 1 Maintenance: County

Total: 9

Current inmate/staff ratio: 2.78:1

## Architect's reported analyses

Factors affecting construction costs:
Positive: Repetitiveness of design and fixtures; use of lighter construction and hardware in medium security areas
Negative: Remodel of existing facility;


phasing to allow continued operation; security and surveillance equipment;

few bidders

Factors affecting time schedule:

Positive: None

Negative: Phasing; weather problems



## **Pre-Trial Detention Facility**

Jurisdiction official: John V. Gillespie, Sheriff

Contact: Commander William A. Wade, Ventura County Sheriff's Department, 800 South Victoria Avenue, Ventura, CA 93009. 805-654-2305

Architect: John Carl Warnecke & Associates/Daniel L. Dworsky FAIA & Associates, 2029 Century Park East, Suite 350, Los Angeles, CA 90067, 213-552-0822

Construction manager: Turner Construction Company, 445 South Figueroa, Los Angeles, CA 90017, 213-683-1430

**Groundbreaking:** December 1977 Finish date: February 1981

Construction time: 38 months

Design capacity: 434 Total cost: \$32,000,000 Total annual operating costs:

\$9,400,000

Category: New independent facility Facility type: Complex: county jail, law

enforcement, other

Building configuration: Integrated

structure

#### Costs

Total: \$32,000,000

Building only: \$22,000,000 Housing area: \$13,000,000 Housing per inmate: \$32,500 Housing per cell: \$32,500

Total per inmate: N/A (complex)

Total per GSF: \$94.12

Total annual operating costs: \$9,400,000

#### **Dimensions**

Gross square feet/corrections: 220,000 Gross square feet/other: 120,000 Gross square feet/total: 340,000 Housing area square feet: 120,000 Gross square feet per inmate: 507 Size of cells: 75 square feet (single)

Net/gross square feet: 71%

### **Inmate housing areas**

Design: Module/pod Cells per unit: 48 Inmates per unit: 48

Management type: Remote surveillance

October 1985 population: 766

Facility commitment: Local jail inmates Means to handle crowding: Second bunk

permanently attached to wall

## **Security**

Perimeter: Building exterior only

Inmate security level: Maximum: 100% Medium: 0 Minimum: 0

## **Construction type**

Structural: Steel frame

Exterior walls: Precast panels; architectural precast Interior walls: CMU block

Exterior surface/facade: Colored concrete

## **Construction process**

Finance method: Local funds Contract method: Construction management fast track Use of inmate labor: None

Use of prefabrication: Limited; precast

exterior walls

#### **Inmate cells**

Doors/material: Steel Doors/type: Sliding

Doors/locking: Remote unlocking;

manual relocking

Floor surface: Sealed concrete

Intercom: Two-way to cells and common

areas

HVAC: Air conditioning; gas-fired

hot water boiler

Plumbing: Stainless combination unit

Furniture: Concrete

Fire protection: Smoke detectors for cells; sprinklers for cells and common

areas; manual alarm stations

#### Inmate design capacity

Single occupancy: 400 Double occupancy: 0

Dorms: 0

Special housing: 34 General population: 400

Total: 434

#### **Current staff**

Full-time equivalent: Administration: 36 Security: 131

> Programs/treatment: 22 Maintenance: 26

Total: 215

Current inmate/staff ratio: 3.56:1

## **Architect's reported analyses**

Factors affecting construction costs: Positive: Phased construction, fast track construction management; conventional design; repetitiveness of design


Negative: Lack of bidding competition; difficult site conditions; busy construction market; large project

for locale

Factors affecting time schedule:

Positive: Phased construction, fast track

construction management Negative: Complex electronic, mechanical, and electrical systems



# Richard J. Donovan Correctional Facility at Rock Mountain

Jurisdiction official: James Rowland, Director, Department of Corrections

Contact: Superintendent John Ratelle, Richard J. Donovan Correctional Facility at Rock Mountain, 480 Alta Road, San Diego,

CA 92179, 619-690-6500

Architect: Hope Consulting Group, 401 West A Street, Suite 500, San Diego, CA 92112–4171, 619–233–5251 Construction manager: Heery/Vanir CM, 660 J Street, Suite 285, Sacramento, CA 95814, 916–448–8474

Groundbreaking: May 1985 Finish date: September 1987 Construction time: 28 months Design capacity: 2,200 Total cost: \$155,450,204 Total annual operating costs:

\$30,781,132

Category: New, independent facility

Facility type: State prison

Building configuration: Courtyard;

clusters; campus style

### Costs

Total: \$155,450,204 Building only: Unknown Housing area: \$45,038,000 Housing per inmate: \$20,547 Housing per cell: \$22,340 Total per inmate: \$70,659 Total per GSF: \$131.85

Total annual operating costs: \$30,781,132

### **Dimensions**

Gross square feet/corrections: 1,179,015 Gross square feet/other: 0 Gross square feet/total: 1,179,015 Housing area square feet: 532,348 Gross square feet per inmate: 536

Size of cells: 60 square feet (single); 1,058 (dorms)

Net/gross square feet: Unknown

# **Inmate housing areas**

Design: Module/pod Cells per unit: 100 Inmates per unit: 100

Management type: Remote surveillance October 1987 population: 2,038 Facility commitment: State prisoners Means to handle crowding: Second bunk

permanently attached to wall

# Security

Perimeter: Double fence; razor wire on

fences; towers
Inmate security level:
Maximum: 0
Medium: 90%
Minimum: 10%

### **Construction type**

Structural: Load-bearing precast panels;

steel frame

Exterior walls: Precast panels Interior walls: CMU block

Exterior surface/facade: Natural wall

# **Construction process**

Finance method: G.O. Bonds

Contract method: Construction manage-

ment fast track

Use of inmate labor: None

Use of prefabrication: Moderate; precast components and metal buildings for

some support functions

### **Inmate cells**

Doors/material: Steel Doors/type: Sliding

Doors/locking: Remote locking Floor surface: Sealed concrete Intercom: Two-way to common areas HVAC: Heating/air circulation; hot water

from co-gen. plant

Plumbing: Stainless combination unit

Furniture: Steel

Fire protection: Smoke detectors for common areas; manual alarm stations

# Inmate design capacity

Single occupancy: 2,000 Double occupancy: 0 Dorms: 192 Special housing: 8 General population: 2,192

Total: 2,200

### **Current staff**

Full-time equivalent:
Administration: 98
Security: 506

Programs/treatment: 55 Maintenance: 45

Total: 704

Current inmate/staff ratio: 2.89:1


# Architect's reported analyses

Factors affecting construction costs:
Positive: Simple construction methods;
good competition, favorable market;
less expensive materials and hardware;
use of prefabricated buildings
Negative: Difficult site conditions:

Negative: Difficult site conditions; government procedures, regulations, and red tape; remote location of site

Factors affecting time schedule:
Positive: Repetitiveness of design; phased construction, fast track CM; advanced order of materials and hardware; coordination of design between parties; use of program manager

Negative: Weather problems; government procedures, regulations, and red tape



# San Joaquin County Honor Farm Women's Minimum Security Facility (Expansion)

Jurisdiction official: John Zunino, Sheriff/Coroner

Contact: Richard A. Sealy, Custody Administrator, San Joaquin County Honor Farm Women's Minimum Security Facility, G Barracks, 999 West Mathews Road, French Camp, CA 95231, 209–982–5151

Architect: The Design Partnership, Architects Planners, 375 Fremont Street, Suite 200, San Francisco, CA 94105, 415–777–3737

Construction manager: None

Groundbreaking: September 1985

Finish date: June 1986 Construction time: 9 months **Design capacity:** 40 **Total cost:** \$616,000

Total annual operating costs: N/A

Gross square feet/corrections: 5,769

Housing area square feet: 5,769

Gross square feet per inmate: 144

Size of cells: 400 square feet (dorm)

Gross square feet/other: 0 Gross square feet/total: 5,769

Net/gross square feet: 79%

(expansion)

Dimensions

Category: Expansion project

**Inmate housing areas** 

August 1986 population: 40

cell; beds in dayroom

**Construction process** 

Finance method: Local funds

Use of prefabrication: None

Contract method: Conventional

Facility type: County jail (women's

facility)

space

Cells per unit: 5

Inmates per unit: 40

Building configuration: Integrated

structure; addition to one building

Design: Dorms with adjacent dayroom

Management type: Direct supervision

Facility commitment: Local jail inmates

Means to handle crowding: Bunk beds in

Use of inmate labor: Limited; demolition

### **Costs**

Total: \$616,000

Building only: Unknown Housing area: Unknown Housing per inmate: Unknown Housing per cell: Unknown

Total per inmate: \$15,400 Total per GSF: \$106.78

Total annual operating costs: N/A

(expansion)

# **Construction type**

Structural: CMU block Exterior walls: CMU block Interior walls: Dry wall

Exterior surface/facade: Split faced block,

natural finish

# Security

Perimeter: Building exterior; single

fence

Inmate security level:
Maximum: 0
Medium: 0
Minimum: 100%

### Inmate design capacity

Single occupancy: 0 Double occupancy: 0

Dorms: 40 Special housing: 0 General population: 40

Total: 40

### Architect's reported analyses

Factors affecting construction costs:

Positive: None Negative: None

Factors affecting time schedule:

Positive: None Negative: None

# **Inmate cells**

Doors/material: Wooden; steel

Doors/type: Swinging

Doors/locking: Manual locking Floor surface: Carpet; vinyl tile Intercom: None (portable radio to

complex)

HVAC: Air conditioning; gas heat

Plumbing: China Furniture: Wood

Fire protection: Smoke detectors and sprinklers for common areas; manual


alarm stations

### **Current staff**

Full-time equivalent: Administration: N/A

Security: 5

Programs/treatment: N/A
Maintenance: N/A
Total: 5 (expansion only)
Current inmate/staff ratio: 8.00:1



# Santa Barbara County Main Jail (Expansion)

Jurisdiction official: John W. Carpenter, Sheriff

Contact: Captain John DaFoe, Jail Commander, Santa Barbara County Main Jail, 4436 Calle Real, Santa Barbara, CA 93110,

805-681-4100

Architects: Patrick Sullivan Associates, 110 North Harvard, Claremont, CA 91711, 714-624-4051

Patrick Sullivan Associates, 542 High Street, Palo Alto, CA 94301, 415-327-2490

Construction manager: None

Groundbreaking: December 1985

Finish date: June 1987

Construction time: 18 months

**Design capacity: 68 Total cost:** \$3,450,700

Total annual operating costs: N/A

(expansion)

Category: Expansion project Facility type: County jail

Building configuration: Integrated

structure

Costs

Total: \$3,450,700

Building only: \$3,450,700

Housing area: \$2,844,930 Housing per inmate: \$59,269 Housing per cell: \$88,904

Total per inmate: \$50,746 Total per GSF: \$139.53

Total annual operating costs: N/A

Perimeter: Building exterior only

(expansion)

Inmate security level:

Maximum: 25%

Medium: 75%

Minimum: 0

**Security** 

**Dimensions** 

Gross square feet/corrections: 24,730

Gross square feet/other: 0 Gross square feet/total: 24,730 Housing area square feet: 15,378 Gross square feet per inmate: 364 Size of cells: 76 square feet (gen. single);

110 (gen. double and spec. single)

Net/gross square feet: 80%

Construction type

Structural: Floors and roof—concrete

waffle slab

Exterior walls: CMU block Interior walls: CMU block

Exterior surface/facade: Plaster over

CMU: stucco

**Inmate cells** 

locking

Doors/material: Steel

Doors/type: Swinging

combination unit

sprinklers for cells

Furniture: Steel

Floor surface: Sealed concrete

HVAC: Air conditioning; gas heat

Plumbing: Stainless steel; stainless

Fire protection: Smoke detectors and

Intercom: Two-way to cells

Doors/locking: Motor driven and remote

**Inmate design capacity** 

Double occupancy: 32

Dorms: 0

Special housing: 20

Total: 68

Single occupancy: 16

General population: 48

**Current staff** 

Full-time equivalent: Administration: 0 Security: 10

Programs/treatment: 0

Maintenance: 0

Total: 10 (expansion only) Current inmate/staff ratio: 12.0:1 **Inmate housing areas** 

Design: Module/pod Cells per unit: 8 Inmates per unit: 12

Management type: Intermittent

surveillance

November 1987 population: 120

Facility commitment: Local jail inmates Means to handle crowding: Bunk beds in

cell

**Construction process** 

Finance method: State funds Contract method: Conventional Use of inmate labor: None

Use of prefabrication: Limited; prefab wall unit with cell door and steel

plumbing chase

Architects' reported analyses

Factors affecting construction costs: Positive: Good competition, favorable

market

Negative: Slow construction, lengthy building time; hillside location; existing

jail structures


Factors affecting time schedule:

Positive: Simple construction methods, factory assembly; advanced order of materials and hardware; coordination of

design between parties

Negative: Slow responses and delivery

from vendors, suppliers



# Santa Cruz County Jail (Phase I)

Jurisdiction official: Alfred F. Noren, Sheriff

Contact: Brad Arbsland, Jail Commander, Santa Cruz County Jail, 259 Water Street, Santa Cruz, CA 95060, 408-425-2666

Architect: Kaplan/McLaughlin/Diaz, 222 Vallejo Street, San Francisco, CA 94111, 415-398-5191

Construction manager: None

**Groundbreaking:** February 1979

Finish date: May 1981

Construction time: 27 months

**Design capacity: 96** Total cost: \$8,400,000

Total annual operating costs:

\$3,799,332

Category: New, independent facility

Facility type: County jail

Building configuration: Integrated

structure; clusters

### **Costs**

Total: \$8,400,000

Building only: \$6,200,000 Housing area: Unknown Housing per inmate: Unknown Housing per cell: Unknown Total per inmate: \$87,500

Total per GSF: \$178.72

Total annual operating costs: \$3,799,332

### **Dimensions**

Gross square feet/corrections: 47,000

Gross square feet/other: 0 Gross square feet/total: 47,000 Housing area square feet: 12,682 Gross square feet per inmate: 490 Size of cells: 74 square feet (single)

Net/gross square feet: Unknown

# Design: Module/pod

Cells per unit: 42 and 50 Inmates per unit: 46

**Inmate housing areas** 

Management type: Remote surveillance

October 1985 population: 150

Facility commitment: Local jail inmates;

State prisoners

Means to handle crowding: Mattresses

on floor; beds in dayroom

# **Security**

Perimeter: Building exterior; alarm/detection system Inmate security level: Maximum: 100%

Medium: 0 Minimum: 0

# Construction type

Structural: Cast-in-place concrete frame Exterior walls: Cast-in-place concrete Interior walls: Cast-in-place concrete Exterior surface/facade: Stucco; paint

# **Construction process**

Finance method: Revenue sharing;

other Federal funds

Contract method: Conventional Use of inmate labor: None Use of prefabrication: None

### **Inmate cells**

Doors/material: Steel Doors/type: Swinging

Doors/locking: Remote locking only Floor surface: Sealed concrete Intercom: Two-way to cells HVAC: Air conditioning Plumbing: Stainless Furniture: Steel

Fire protection: Smoke detectors for cells, common areas, and ducts; manual alarm stations; smoke evacuation

# Inmate design capacity

Single occupancy: 92 Double occupancy: 0

Dorms: 0

Special housing: 4 General population: 92

Total: 96

# Architect's reported analyses

Factors affecting construction costs: Positive: Simple construction methods Negative: Slow construction, lengthy building time; difficult site conditions; complex electronic, mechanical, and electrical systems

Factors affecting time schedule: Positive: Simple construction methods Negative: Complex electronic, mechanical, and electrical systems


**Current staff** 

Full-time equivalent: Administration: 9 Security: 66

Programs/treatment: 20

Maintenance: 4 Total: 99

Current inmate/staff ratio: 1.52:1



# **Sequoia Field Detention Facility**

Jurisdiction official: Bob Wiley, Sheriff/Coroner

Contact: Captain Mitch Vidak, Sequoia Field Detention Facility, 36712 Road 112, Visalia, CA 93291, 209-733-6233

Architect: Hope Consulting Group, 562 Mission Street, San Francisco, CA 94105, 415-434-0381

Construction manager: Kitchell CEM, Inc., 1707 East Highland Avenue, Suite 280, Phoenix, AZ 85016, 602-266-1970

Groundbreaking: November 1985

Finish date: April 1987

**Construction time:** 17 months

Design capacity: 436

Total cost: \$21,300,000

Total annual operating costs: Unknown

Category: New, independent facility

Facility type: County jail

**Building configuration:** Clusters

### Costs

Total: \$21,300,000

Building only: \$20,000,000 Housing area: \$11,000,000 Housing per inmate: \$28,646 Housing per cell: \$61,919 Total per inmate: \$48,853 Total per GSF: \$161.72

Total annual operating costs: Unknown

### **Dimensions**

Gross square feet/corrections: 130,000

Gross square feet/other: 0 Gross square feet/total: 130,000 Housing area square feet: 87,224 Gross square feet per inmate: 298 Size of cells: 70 square feet (gen. single)

Net/gross square feet: Unknown

### **Inmate housing areas**

Design: Module/pod Cells per unit: 96 Inmates per unit: 96

Management type: Remote surveillance September 1987 population: 360 Facility commitment: Local jail inmates Means to handle crowding: Unknown

### **Security**

Perimeter: Single fence; razor wire on fence; video camera surveillance

Inmate security level: Maximum: 13% Medium: 75% Minimum: 12%

# **Construction type**

Structural: Steel frame; load-bearing

masonry

Exterior walls: CMU block

Interior walls: Precast panels; cast-in-place

concrete; CMU block

Exterior surface/facade: Natural wall

### **Construction process**

Finance method: Certificates of Participation; State funds

Contract method: Construction manage-

ment fast track

Use of inmate labor: None

Use of prefabrication: Limited; concrete floor planks in mezzanine and housing;

concrete window frames

### **Inmate cells**

Doors/material: Steel Doors/type: Sliding

Doors/locking: Manual locking Floor surface: Sealed concrete

Intercom: Two-way to cells and common

areas

HVAC: Air conditioning; hydronic heat (hot water from cogeneration facility)

Plumbing: Stainless combination unit

Furniture: Steel

Fire protection: Smoke detectors and sprinklers for cells and common areas

### **Inmate design capacity**

Single occupancy: 336 Double occupancy: 0

Dorms: 48

Special housing: 52 General population: 384

Total: 436

# Architect's reported analyses

Factors affecting construction costs: Positive: Simple construction methods, repetitiveness of design; phased con-

struction; fast track CM

Negative: Complex electronic, mechanical, and electrical systems

Factors affecting time schedule:

Positive: Simple construction methods, repetitiveness of design; phased construction, fast track CM; coordination of design between parties

Negative: Slow responses and delivery from suppliers; complex electronic,


mechanical, and electrical systems

# **Current staff**

Full-time equivalent: Administration: 2 Security: 63

> Programs/treatment: 7 Maintenance: 5 Total: 77

Current inmate/staff ratio: 4.68:1



# **Shasta County Justice Center**

Jurisdiction official: Phil D. Eoff, Sheriff

Contact: Captain Gene Toten, Jail Commander, Shasta County Justice Center, West and Placer Streets, Redding, CA 96001,

916-225-5651

Architects: Hellmuth, Obata & Kassabaum, Inc., One Lombard Street, San Francisco, CA 94111, 415-627-1600

WKSD Architects, 225 Locust, Suite 3, Redding, CA 96001, 916-246-1900

Construction manager: M. Hill Company, 1525 Court Street, Redding, CA 96001, 916-441-3955

**Groundbreaking:** November 1982

Finish date: June 1984

Construction time: 19 months

Design capacity: 250 **Total cost:** \$14,500,000

Total annual operating costs:

\$4,753,529

Category: New, independent facility Facility type: Complex, county jail,

courts

**Building configuration:** Integrated

structure, high rise

Costs

Total: \$14,500,000

Building only: \$14,000,000 Housing area: \$9,500,000 Housing per inmate: \$39,583 Housing per cell: \$39,583

Total per inmate: \$58,000 Total per GSF: \$207.14

Total annual operating costs: \$4,753,529

Security

Perimeter: Building exterior only

Inmate security level: Maximum: 16% Medium: 68% Minimum: 16%

Inmate cells

Doors/material: Wooden Doors/type: Swinging

Doors/locking: Remote locking only

Floor surface: Sealed concrete

Intercom: One-way to cells; two-way to

common areas

HVAC: Heating/air circulation only

Plumbing: Stainless Furniture: Concrete

Fire protection: Smoke detectors for cells

**Dimensions** 

Gross square feet/corrections: 70,000

Gross square feet/other: 0 Gross square feet/total: 70,000 Housing area square feet: Unknown Gross square feet per inmate: 280 Size of cells: 70 square feet (single)

Net/gross square feet: 96%

**Construction type** 

Structural: Steel frame; poured-in-place

concrete lower 2 levels

Exterior walls: Steel studs with heavy duty thermal insulation

Interior walls: CMU block with pneumatic

placed concrete surfaces

Exterior surface/facade: Stucco over steel

studs

**Inmate design capacity** 

Single occupancy: 240 Double occupancy: 0

Dorms: 0

Special housing: 10 General population: 240

Total: 250

**Current staff** 

Full-time equivalent: Administration: 19

Security: 48

Programs/treatment: 19 Maintenance: 10

Total: 96

Current inmate/staff ratio: 2.89:1

**Inmate housing areas** 

Design: Module/pod Cells per unit: 80 Inmates per unit: 80

Management type: Intermittent surveil-

lance; patrols

October 1985 population: 277

Facility commitment: Local jail inmates Means to handle crowding: Second bunk

permanently attached to wall

Construction process

Finance method: Local funds; State funds

Contract method: Construction management fast track Use of inmate labor: None Use of prefabrication: None

Architects' reported analyses


Factors affecting construction costs:

Positive: Simple construction methods, repetitiveness of design; good competition, favorable market Negative: High labor costs; difficult

site conditions; inflation

Factors affecting time schedule: Positive: Simple construction methods, repetitiveness of design; phased construction, fast track construction management; advanced order of

materials and hardware Negative: Weather problems




### **Ground Level**

- 1 Mechanical 2 Vehicular Sally Port 3 Offices
- 4 Public Lobby
- 5 Central Control

- 5 Central Control
  6 Visiting
  7 Cell
  8 Interview
  9 Medical
  10 Holding Room
  11 Services


- 12 Booking 13 Special Segregation



### **Level Two**

- 1 Jury Deliberation 2 Holding Cell 3 Sally Port 4 Court Room 5 Judge's Chamber
- 6 Courts Administration

- 7 Cell
  8 Dayroom
  9 Outdoor Exercise
  10 Multi-Purpose Room



### **Typical Mezzanine Level Two**

- 1 Corridor to Courts
  2 Cell
  3 Dayroom Below
  4 Visiting
  5 Control Room
  6 Electrical/Communication Equipment
  7 Outdoor Everging Release
- 7 Outdoor Exercise Below

# Sonoma North County Detention Facility (Addition/Remodel)

Jurisdiction official: Dick Mickaelsen, Sheriff-Coroner

Contact: John DeWitt, Correctional Lieutenant, Sonoma North County Detention Facility, 2254 Airport Boulevard, Santa Rosa,

CA 95401, 707-542-3375

Architect: The Ehrenkrantz Group, 855 Front Street, San Francisco, CA 94111, 415-956-4394

Construction manager: None

Groundbreaking: March 1985

Finish date: April 1986

Construction time: 13 months

**Design capacity:** 139 **Total cost:** \$5,200,000

Total annual operating costs: \$7,451,624

(entire facility)

Category: New, ancillary building; remodel/renovation; phased project

(future)

Facility type: County jail

Building configuration: Campus style

### **Costs**

Total: \$5,200,000

Building only: Unknown

Housing area: Unknown

Housing per inmate: Unknown

Housing per cell: Unknown
Total per inmate: N/A (remodel)

Total per GSF: \$181.74

Total annual operating costs: \$7,451,624

(entire facility)

# **Security**

Perimeter: Double fence; razor wire on

fences; video camera surveillance; roving officer

Inmate security level: Maximum: 13%

Maximum: 13% Medium: 25% Minimum: 62%

### **Inmate cells**

Doors/material: Solid; wooden

Doors/type: Swinging

Doors/locking: Remote locking; manual

locking

Floors: Carpet; sealed concrete; vinyl tile Intercom: Two-way to cells; one-way to

common areas

HVAC: Air conditioning; gas heat

Plumbing: China

Furniture: Steel; wood; vinyl/plastic;

concrete

Fire protection: Smoke detectors and sprinklers for cells and common areas;

manual alarm stations

### **Dimensions**

Gross square feet/corrections: 28,612

Gross square feet/other: 0 Gross square feet/total: 28,612 Housing area square feet: 12,350

Gross square feet per inmate: 206 Size of cells: 100 square feet (double);

60 (spec. single)

Net/gross square feet: 66%

# Construction type

Structural: Wood frame/steel columns Exterior walls: CMU block; wood stud/

stucco/wood siding

Interior walls: CMU block; wood stud/

GWB

Exterior surface/facade: Stucco; paint;

wood siding

### Inmate design capacity

Single occupancy: 0 Double occupancy: 16

Dorms: 112

Special housing: 11 General population: 128

Total: 139

### **Current staff**

Full-time equivalent: Administration: 2

Security: 18

Programs/treatment: 1 Maintenance: 1

Total: 22 (entire facility)

Total: 22 (entire facility)

Current inmate/staff ratio: 7.91:1

# **Inmate housing areas**

Design: Module/pod Cells per unit: Unknown

Inmates per unit: Unknown Management type: Direct supervision

February 1987 population: 174

Facility commitment: Local jail inmates Means to handle crowding: Beds in

dayroom

### **Construction process**

Finance method: Certificates of Participa-

tion; local funds; State funds

Contract method: Phased (2 bid packages)

Use of inmate labor: None Use of prefabrication: None

# Architect's reported analyses

Factors affecting construction costs:

Positive: Simple construction methods, repetitiveness of design; phased construction, fast track CM; less expensive materials and hardware

Negative: Complex electronic, mechanical, and electrical systems


- car, and electrical systems

Factors affecting time schedule: Positive: Simple construction methods, repetitiveness of design; phased construction, fast track CM

Negative: Complex electronic, mechanical, and electrical systems—minor

delay

HOUSING FLOOR PLAN
1 ENTRANCE
2 OFFICER'S STATION
3 DAYROOM
4 HALL
5 TV ARC
6 BATHROOM
7 DORWITCRY
8 HOCP BATHROOM
9 STORAGE
10 OFFICER'S ROOM



# Stanislaus County Jail (Remodel/Expansion)

Jurisdiction official: Jim Trevena, Sheriff

Contact: Captain Rod Wells, Stanislaus County Jail, 1100 H Street, Modesto, CA 95354, 209-571-6456

Architect: Crosby, Thornton, Marshall, Booker, Lawlor, Architects, 2105 Lancey Drive, Suite 7, Modesto, CA 95355, 209-575-1384

Construction manager: None

**Groundbreaking:** April 1985 Finish date: February 1986 Construction time: 10 months **Design capacity:** 40 **Total cost:** \$791,000

**Total annual operating costs:** 

N/A (expansion)

Category: Remodeling/renovation project to expand jail capacity

Facility type: Complex: county jail, law

enforcement, courts

Building configuration: Integrated

structure

### Costs

Total: \$791,000

Building only: N/A (remodel)

Housing area: Unknown Housing per inmate: Unknown Housing per cell: Unknown

Total per inmate: N/A (complex)

Total per GSF: \$48.55

Total annual operating costs: N/A

(expansion)

# Security

Perimeter: Building exterior; double

fence/exercise yard Inmate security level: Maximum: 20% Medium: 60% Minimum: 20%

### **Inmate cells**

Doors/material: Unknown Doors/type: Sliding Doors/locking: Unknown

Floor surface: Sealed concrete; vinyl tile Intercom: One-way to cells and common

HVAC: Air conditioning; vari-cool unit Plumbing: Stainless combination unit

Furniture: Steel

Fire protection: Smoke detectors for

cells and common areas

### **Dimensions**

Gross square feet/corrections: 8,040 Gross square feet/other: 8,252 Gross square feet/total: 16,292 Housing area square feet: 2,544

Gross square feet per inmate: 201 Size of cells: 55 square feet per bed

(dorms)

Net/gross square feet: 90%

# Construction type

Structural: Cast-in-place concrete frame Exterior walls: Cast-in-place concrete Interior walls: Cast-in-place concrete

Exterior surface/facade: Paint

### **Inmate design capacity**

Single occupancy: 0 Double occupancy: 0

Dorms: 40 Special housing: 0

General population: 40

Total: 40

### **Current staff**

Full-time equivalent: Administration: N/A

Security: 5

Programs/treatment: N/A Maintenance: N/A Total: 5 (expansion only)

Current inmate/staff ratio: 8:1

# **Inmate housing areas**

Design: Linear, inside; dormitories

Cells per unit: N/A Inmates per unit: N/A

Management type: Intermittent

surveillance

October 1985 population: 40

Facility commitment: Local jail inmates Means to handle crowding: Mattresses on floor; second bunk attached to wall

# **Construction process**

Finance method: Revenue sharing;

State funds

Contract method: Conventional Use of inmate labor: Limited Use of prefabrication: None

### Architect's reported analyses

Factors affecting construction costs: Positive: Remodel of existing facility Negative: Slow construction; high labor costs; government procedures, regulations, "red tape"; complex electronic, mechanical, and electrical systems

Factors affecting time schedule:

Positive: None

Negative: Slow responses and delivery from vendors, suppliers; government procedures, regulations, "red tape"



(No floorplan available at time of publication)

# Sunnyvale Public Safety Building and Temporary Holding Facility

Jurisdiction official: Ralph Hern, Commander, Support Services Division

Contact: Regan Williams, Sunnyvale Public Safety Building, 700 All America Way, Sunnyvale, CA 94086, 408-730-7163 Architect: The Ehrenkrantz Group, 855 Front Street, San Francisco, CA 94111, 415-956-4394

Construction manager: Architectural Inspection Service, 2335 Thompson Court, Mountain View, CA 94043, 415–968–7904

**Groundbreaking:** August 1983 Finish date: April 1985

Construction time: 20 months

Design capacity: 20 **Total cost:** \$6,100,000

Total annual operating costs:

\$13,058,406

Category: New, independent facility Facility type: Complex: city jail, law enforcement, city emergency

operations

Building configuration: Integ. structure

### Costs

Total: \$6,100,000

Building only: \$4,000,000 Housing area: \$238,500 Housing per inmate: \$11,925 Housing per cell: \$39,750

Total per inmate: N/A (complex)

Total per GSF: \$152.88

Total annual operating costs: \$13,058,406

### **Dimensions**

Gross square feet/corrections: 2,380 Gross square feet/other: 37,520 Gross square feet/total: 39,900 Housing area square feet: 849 Gross square feet per inmate: 119 Size of cells: 136 square feet (single)

Net/gross square feet: 80%

### **Inmate housing areas**

Design: Linear, interior Cells per unit: 5 Inmates per unit: 9

Management type: Intermittent surveillance; remote surveillance

December 1986 population: 13

Facility commitment: Local jail inmates Means to handle crowding: Unknown

# Security

Perimeter: Building exterior; video

camera surveillance Inmate security level: Maximum: 100% Medium: 0 Minimum: 0

# **Construction type**

Structural: Steel frame Exterior walls: Brick

Interior walls: CMU block; glazed Exterior surface/facade: Brick

# **Construction process**

Finance method: Local funds Contract method: Conventional Use of inmate labor: None Use of prefabrication: None

### Inmate cells

Doors/material: Steel Doors/type: Sliding

Doors/locking: Motor driven and remote

locking; manual locking Floor surface: Quarry tile

Intercom: One-way to cells and common

areas

HVAC: Air conditioning Plumbing: Stainless steel Furniture: Concrete

Fire protection: Smoke detectors and sprinklers for cells and common areas

### Inmate design capacity

Single occupancy: 4 Double occupancy: 0

Dorms: 16 Special housing: 0 General population: 20

Total: 20

### **Current staff**

Full-time equivalent:

Administration: Unknown

Security: Unknown

Programs/treatment: Unknown

Maintenance: Unknown

Total: Unknown

Current inmate/staff ratio: Unknown

### Architect's reported analyses

Factors affecting construction costs: Positive: Good competition, favorable

Negative: Complex electronic, mechani-


cal, and electrical systems

Factors affecting time schedule:

Positive: Simple construction methods, repetitiveness of design; coordination

of design between parties

Negative: Complex electronic, mechanical, and electrical systems



# **Torrance Police Department**

Jurisdiction official: Donald E. Nash, Chief of Police

Contact: Captain Bruce J. Randall, Services Bureau Commander, Torrance Police Department, 3300 Civic Center Drive,

Torrance, CA 90503, 213-618-5702

Architect: H. Wendell Mounce AIA & Associates, 3436 North Verdugo Road, Glendale, CA 91208, 213-245-1044

Construction manager: None

Groundbreaking: April 1980 Finish date: March 1982 Construction time: 23 months **Design capacity: 58 Total cost:** \$7,188,000

Total annual operating costs: \$509,800

Category: New, independent facility Facility type: Complex: city jail; law

enforcement

Building configuration: Integrated

structure

Costs

Total: \$7,188,000

Building only: \$6,500,000 Housing area: \$845,000 Housing per inmate: \$18,778 Housing per cell: \$52,813

Total per inmate: N/A (complex)

Total per GSF: \$97.80

Total annual operating costs: \$509,800

**Dimensions** 

Gross square feet/corrections: 8,640 Gross square feet/other: 64,860 Gross square feet/total: 73,500 Housing area square feet: 8,640 Gross square feet per inmate: 149 Size of cells: 56 square feet (single)

Net/gross square feet: 74%

**Inmate housing areas** 

Design: Module/pod Cells per unit: 22 Inmates per unit: 58

Management type: Remote surveillance

May 1986 population: 30

Facility commitment: Local jail inmates Means to handle crowding: None

Security

Perimeter: Building exterior; alarm/ detection systems; video camera

surveillance Inmate security level: Maximum: 0 Medium: 100% Minimum: 0

**Construction type** 

Structural: Steel frame; CMU block Exterior walls: CMU block; metal studs Interior walls: CMU block; metal studs Exterior surface/facade: Brick; stucco;

paint

**Construction process** 

Finance method: Shared cost from

multiple jurisdictions Contract method: Conventional

Use of inmate labor: None Use of prefabrication: Limited

**Inmate cells** 

Doors/material: Steel Doors/type: Sliding

Doors/locking: Remote and manual

locking

Floor surface: Sealed concrete; vinyl tile Intercom: One-way to cells and common

HVAC: Air conditioning; gas heat

Plumbing: Stainless steel

Furniture: Steel

Fire protection: Smoke detectors and

sprinklers for cells

Inmate design capacity

Single occupancy: 7 Double occupancy: 0

Dorms: 38

Special housing: 13 General population: 45

Total: 58

Architect's reported analyses

Factors affecting construction costs: Positive: Prefabricated components, factory assembly; concrete block construction; good competition,

favorable market

Negative: Government procedures, regulations, and red tape; complex electronic, mechanical, and electrical

systems

Factors affecting time schedule:

Positive: Coordination of design between

Negative: Government procedures, regulations, and red tape; complex electronic, mechanical, and electrical

systems

### **Current staff**


Full-time equivalent: Administration: 2

Security: 18

Programs/treatment: 0

Maintenance: 1 Total: 21

Current inmate/staff ratio: 1.43:1



# **Tuolumne County Jail (Remodel/Expansion)**

Jurisdiction official: Robert T. Coane, Sheriff/Coroner

Contact: James N. Childers, Jail Commander, Tuolumne County Jail, 28 North Lower Sunset Drive, Sonora, CA 95370,

209-533-5844

Architect: Patrick Sullivan Associates, 542 High Street, Palo Alto, CA 94301, 415-327-2490

Construction manager: None

Groundbreaking: April 1985 Finish date: May 1986 Construction time: 13 months

**Design capacity:** 21 **Total cost:** \$920,700

**Total annual operating costs:** \$463,325

(entire facility)

Category: Remodel/renovation project;

expansion project
Facility type: County jail

**Inmate housing areas** 

**Building configuration:** Integrated

Design: Tier design; linear, inside

October 1985 population: 70 (entire

Facility commitment: Local jail inmates Means to handle crowding: Mattresses

Management type: Intermittent

on floor; bunk beds in cell

Finance method: Local funds; State

Contract method: Conventional

**Construction process** 

Use of inmate labor: None

Use of prefabrication: None

structure

Cells per unit: 20

surveillance

facility)

funds

Inmates per unit: 20

### **Costs**

Total: \$920,700

Building only: N/A (remodel) Housing area: \$607,662 Housing per inmate: \$30,383 Housing per cell: \$30,383

Total per inmate: N/A (remodel)

Total per GSF: \$102.12

Total annual operating costs: \$463,325

(entire facility)

# **Security**

Perimeter: Building exterior only

Inmate security level:
Maximum: 70%
Medium: 20%
Minimum: 10%

### **Dimensions**

Gross square feet/corrections: 9,016

Gross square feet/other: 0 Gross square feet/total: 9,016 Housing area square feet: 5,990 Gross square feet per inmate: 429 Size of cells: 105 square feet (single) Net/gross square feet: Unknown

### **Construction type**

Structural: CMU with concrete deck Exterior walls: CMU block

Interior walls: CMU block Exterior surface/facade: Stucco

# Inmate design capacity

Single occupancy: 20 Double occupancy: 0

Double occupancy: 0
Dorms: 0
Special housing: 1
General population: 20

Total: 21

### Architect's reported analyses

Factors affecting construction costs:

Positive: None Negative: None

Factors affecting time schedule:

Positive: None Negative: None

### **Inmate cells**

Doors/material: Steel
Doors/type: Sliding
Doors/locking: Manual
Floor surface: Sealed concrete
Intercom: Two-way to cells and

common areas

HVAC: Air conditioning; forced air

heat

Plumbing: Stainless steel

Furniture: Steel

Fire protection: Smoke detectors and


sprinklers for cells

### **Current staff**

Full-time equivalent: Administration: 1 Security: 15

> Programs/treatment: 1 Maintenance: 2

Total: 19 (entire facility)
Current inmate/staff ratio: 3.68:1



# **Yuba County Jail (Remodel)**

Jurisdiction official: Robert R. Day, Sheriff

Contact: Captain Gary M. Finch, Jail Commander, Yuba County Jail, 215 Fifth Street, Marysville, CA 95901, 916-741-6331

Architect: Patrick Sullivan Associates, 542 High Street, Palo Alto, CA 94301, 415–327–2490

Construction manager: None

**Groundbreaking:** June 1985 Finish date: July 1986

Construction time: 13 months

Design capacity: 134 **Total cost:** \$500,000

Total annual operating costs:

\$620,370

Category: Remodel/renovation Facility type: County jail

Building configuration: Integrated

structure

#### Costs

Total: \$500,000

Building only: Unknown Housing area: Unknown Housing per inmate: Unknown Housing per cell: Unknown

Total per inmate: N/A (remodel)

Total per GSF: \$25.98

Perimeter: No alteration

Inmate security level:

Maximum: 50%

Medium: 50%

Minimum: 0

Total annual operating costs: \$620,370

### **Dimensions**

Gross square feet/corrections: 19,248

Gross square feet/other: 0 Gross square feet/total: 19,248 Housing area square feet: 6,235 Gross square feet per inmate: 144 Size of cells: 56 square feet (single) Net/gross square feet: Unknown

Structural: Concrete

ceilings

Interior walls: Steel bar cell walls; Gunite

Exterior surface/facade: Gunite walls

### **Inmate cells**

Security

Doors/material: Hollow metal and

open bar

Doors/type: Swinging

Doors/locking: Manual and remote

locking

Floor surface: Sealed concrete

Intercom: None **HVAC:** None

Plumbing: Stainless steel

Furniture: Steel

Fire protection: No alteration

(no sprinklers)

# **Construction type**

Exterior walls: Concrete floors and

walls

### Inmate design capacity

Single occupancy: 24 Double occupancy: 4

Dorms: 104 Special housing: 2 General population: 132

Total: 134

### Current staff

Full-time equivalent: Administration: 2 Security: 20

> Programs/treatment: 2 Maintenance: 3

Total: 27

Current inmate/staff ratio: 4.63:1

### **Inmate housing areas**

Design: Linear, inside Cells per unit: N/A Inmates per unit: 20

Management type: Intermittent

surveillance

October 1985 population: 125

Facility commitment: Local jail inmates Means to handle crowding: Mattresses on

floor

### **Construction process**

Finance method: Local funds; State funds Contract method: Conventional Use of inmate labor: Yes, painting Use of prefabrication: None

### Architect's reported analyses

Factors affecting construction costs: Positive: Good competition, favorable market; county's efforts to circulate bid

documents

Negative: Difficult security conditions


during remodeling

Factors affecting time schedule:

Positive: None

Negative: Working within existing building; security hollow metal and

locks



# Adams County Detention Facility

Jurisdiction official: Edward J. Camp, Sheriff

Contact: Deputy Chief Penny Collins, Adams County Detention Facility, 150 N. 19th Street, Brighton, CO 80601, 303-654-1850

Architect: Justice Systems, Inc., 348 Peachtree Street NE., Atlanta, GA 30308, 404-577-3184

Construction manager: Morrison-Knudsen Company, Inc., P.O. Box 7808, Boise, ID 83729, 208-386-5000

Groundbreaking: February 1984

Finish date: May 1985

Construction time: 15 months

Design capacity: 485 **Total cost:** \$15,382,660 Total annual operating costs:

\$3,371,143

Category: New, independent facility

Facility type: County jail **Building configuration:** Wings

connecting housing pods

### Costs

Total: \$15,382,660

Building only: \$14,100,000 Housing area: \$10,800,000 Housing per inmate: \$22,500 Housing per cell: \$22,500 Total per inmate: \$31,717 Total per GSF: \$67.43

Total annual operating costs: \$3,371,143

### **Dimensions**

Gross square feet/corrections: 228,140

Gross square feet/other: 0 Gross square feet/total: 228,140 Housing area square feet: 171,332 Gross square feet per inmate: 470 Size of cells: 83 square feet (single)

Net/gross square feet: 77%

# **Inmate housing areas**

Design: Module/pod Cells per unit: 48 Inmates per unit: 48

Management type: Remote surveillance

October 1985 population: 264 Facility commitment: Local inmates;

State prisoners

Means to handle crowding: N/A

# Security

Perimeter: Double fence; razor wire

on fence

Inmate security level: Maximum: 40% Medium: 60% Minimum: 0

### **Construction type**

Structural: Steel frame Exterior walls: CMU block Interior walls: Precast panels;

cast-in-place concrete; CMU block Exterior surface/facade: Stucco; paint

# **Construction process**

Finance method: G.O. Bonds Contract method: Construction management fast track Use of inmate labor: None Use of prefabrication: Limited

### **Inmate cells**

Doors/material: Solid steel

Doors/type: Sliding (max.); swinging

Doors/locking: Remote locking only (max.); motor driven and remote

locking (med.)

Floor surface: Sealed concrete

Intercom: Two-way to common areas

**HVAC:** Air conditioning

Plumbing: Stainless (max.); china (med.)

Furniture: Steel

Fire protection: Smoke detectors and sprinklers for cells and common areas

### Inmate design capacity

Single occupancy: 480 Double occupancy: 0

Dorms: 0

Special housing: 5 General population: 480

Total: 485

### **Current staff**

Full-time equivalent:

Administration: 19 Security: 113 Programs/treatment: 3

Maintenance: 5 Total: 140 (not incl. contract food,

medical)

Current inmate/staff ratio: 1.89:1

# Architect's reported analyses

Factors affecting construction costs: Positive: Simple construction methods, repetitiveness and cost-consciousness of design; phased construction, fast track construction management; clear plans and specs

Negative: High labor costs; difficult site conditions (expansive clay)

Factors affecting time schedule: Positive: Simple construction methods, repetitiveness of design; phased construction; advanced order of materials and hardware; coordination of design between parties

Negative: Weather problems

(No floorplan available at time of publication)

# Alamosa County Law Enforcement Center

Jurisdiction official: James P. Drury, Sheriff

Contact: Captain Glenn Biggs, Jail Administrator, Alamosa County Law Enforcement Center, 1315 17th Street, Alamosa, CO 81101,

303-589-5787

Architect: E. George Wynn—Architect, 52499 County Road "T", Saguache, CO 81149, 303-655-2247

Construction manager: None

**Groundbreaking:** May 1985 Finish date: July 1986

Construction time: 14 months

Design capacity: 51 **Total cost:** \$1,993,693

**Total annual operating costs:** \$379,526

Category: New, independent facility Facility type: Complex: county jail; law enforcement; Immigration & Naturalization Service

Building configuration: Integrated structure; wheel, spoke or radial

### Costs

Total: \$1,993,693

Building only: \$1,893,693 Housing area: \$1,270,290 Housing per inmate: \$31,757 Housing per cell: \$52,929

Total per inmate: N/A (complex)

Total per GSF: \$80.77

Total annual operating costs: \$379,526

### **Dimensions**

Gross square feet/corrections: 12,098 Gross square feet/other: 12,587 Gross square feet/total: 24,685 Housing area square feet: 12,098 Gross square feet per inmate: 237

Size of cells: 70 square feet (single); 104 (double); 236 (4-man)

Net/gross square feet: 94%

# Construction type

block

Exterior walls: CMU block

Interior walls: Cast-in-place concrete; CMU block; steel stud and drywall Exterior surface/facade: Stucco; paint: natural wall; fluted CMU block

# **Security**

Perimeter: Building exterior; video camera surveillance; razor wire between double fences around

courtyard

Inmate security level: Maximum: 35% Medium: 32% Minimum: 33%

### **Inmate cells**

Doors/material: Steel Doors/type: Swinging

Doors/locking: Solenaid driven and remote locking; manual locking Floor surface: Concrete sealed with paint Intercom: Two-way to cells and common

HVAC: Heating/air circulation; gas heat; passive solar heat; evaporative

cooling

Plumbing: China; stainless combination

unit

Furniture: Steel

Fire protection: Smoke detectors for cells and common areas; manual alarm

stations

Structural: Steel frame; load bearing CMU

### **Inmate design capacity**

Single occupancy: 14 Double occupancy: 14

Dorms: 12

Special housing: 11 General population: 40

Total: 51

### Current staff

Full-time equivalent: Administration: 1 Security: 13

Programs/treatment: 0 Maintenance: 0

Total: 14

Current inmate/staff ratio: 1.00:1

### **Inmate housing areas**

Design: Module/pod Cells per unit: 25 Inmates per unit: 44

Management type: Remote surveillance; "roving" officer in direct supervision

September 1986 population: 14

Facility commitment: Local jail inmates;

State prisoners

Means to handle crowding: Other facilities

# **Construction process**

Finance method: G.O. Bonds; special

election; local funds

Contract method: Conventional; cost plus

contract with upset price Use of inmate labor: None Use of prefabrication: None

### Architect's reported analyses

Factors affecting construction costs: Positive: Simple construction methods; continuous and extensive participation


by design architect

Negative: Exorbitant costs of specialized "detention" equipment (i.e., window frames, fixtures, furnishings, fittings)

Factors affecting time schedule: Positive: Simple construction methods; advanced order of materials and hardware; coordination of design between parties; extensive supervision by design architect; excellent scheduling by general contractor

Negative: Slow responses and delivery

from vendors, suppliers



# **Arkansas Valley Correctional Facility**

Jurisdiction official: Walter Kautzky, Executive Director, Department of Corrections

Contact: Superintendent Jim Brittain, Arkansas Valley Correctional Facility, Box 1000, Crowley, CO 81034, 303–267–3520 Architects: RNL Design, Seventeenth Street Plaza, Suite 1700, 1225 Seventeenth Street, Denver, CO 80202, 303–295–1717

H. Holding and Associates, 216 East Monument, Colorado Springs, CO 80903, 303-475-1270

Construction manager: G.E. Johnson Construction Company, P.O. Box 2139, 310 South 14th Street, Colorado Springs, CO 80901,

303-473-5321

**Groundbreaking:** December 1985 **Finish date:** December 1987

Construction time: 24 months

**Design capacity:** 742 **Total cost:** \$32,800,000

Total annual operating costs: \$9,878,725

Category: New, independent facility

Facility type: State prison

Building configuration: Campus style

### **Costs**

Total: \$32,800,000

Building only: \$30,070,000 Housing area: \$16,679,000 Housing per inmate: \$22,974 Housing per cell: \$22,974 Total per inmate: \$44,205 Total per GSF: \$100.07

Total annual operating costs: \$9,878,725

# **Dimensions**

Gross square feet/corrections: 327,771

Gross square feet/other: 0 Gross square feet/total: 327,771 Housing area square feet: 175,932 Gross square feet per inmate: 442 Size of cells: 72 square feet (gen. single);

80 (spec. single)

Net/gross square feet: Unknown

### **Inmate housing areas**

Design: Module/pod Cells per unit: 40 Inmates per unit: 40

Management type: Remote surveillance

April 1988 population: 782

Facility commitment: State prisoners Means to handle crowding: Double

bunking

### **Security**

Perimeter: Double fence; alarm/detection systems; razor wire on and between

fences; towers; patrols; camera

surveillance

Inmate security level:
Maximum: 2%
Medium: 98%
Minimum: 0

# **Construction type**

Structural: Load-bearing precast panels;

precast concrete frame

Exterior walls: Precast panels; architectural

precast

Interior walls: Precast panels; CMU block Exterior surface/facade: Etched precast

# **Construction process**

Finance method: State funds

Contract method: Construction manage-

ment fast track

Use of inmate labor: None

Use of prefabrication: Extensive; cell units and precast structural area panels

### **Inmate cells**

Doors/material: Steel Doors/type: Swinging

Doors/locking: Manual locking

Floor surface: Sealed concrete; colored

concrete

Intercom: One-way to common areas HVAC: Air conditioning; hot water

heating Plumbing: China Furniture: Concrete

Fire protection: Smoke detectors and sprinklers for cells and common areas; electric control at control stations with

time delays

# Inmate design capacity

Single occupancy: 726 Double occupancy: 0

Dorms: 0

Special housing: 16 General population: 726

Total: 742

### **Current staff**

Full-time equivalent:
Administration: 129

Security: 64

Programs/treatment: 59 Maintenance: 34

Total: 286

Current inmate/staff ratio: 2.73:1


# Architects' reported analyses

Factors affecting construction costs:
Positive: Prefab. components, factory
assembly; simple const. methods; good
coordination by team members

Negative: Lengthy building time; difficult site conditions, poor soil; lack of skilled labor; security equipment contractors overbooked—inflated bids received

Factors affecting time schedule:
Positive: Prefab. components, factory
assembly; phased construction, fast
track CM; cooperation and coordination
by entire team

Negative: Labor problems, strike; poor cooperation from utilities subcontractor



# **Delta County Criminal Justice Facility (Addition)**

Jurisdiction official: Richard A. Miklich, Sheriff

Contact: Sheriff Richard A. Miklich, Delta County Criminal Justice Facility, Delta County Courthouse, 555 Palmer, Delta,

CO81416, 303-874-9734

Architect: Dana Larson Roubal & Associates, 225 North 5th Street, Suite 115, Grand Junction, CO 81501, 303-243-6166

Construction manager: None

Groundbreaking: November 1984

Finish date: January 1986 Construction time: 14 months **Design capacity:** 47 **Total cost:** \$3,400,000

**Total annual operating costs:** 

\$102,689 (addition only)

Category: New, ancillary building Facility type: Complex: county jail, court Building configuration: Integrated

structure

Costs

Total: \$3,400,000

Building only: \$3,258,000 Housing area: \$884,000 Housing per inmate: \$20,091 Housing per cell: \$23,263

Total per inmate: N/A (complex)

Total per GSF: \$99.98

Total annual operating costs: \$102,689

(addition only)

Security

Perimeter: Building exterior only

Inmate security level:
Maximum: 0
Medium: 100%
Minimum: 0

**Inmate cells** 

Doors/material: Wooden
Doors/type: Swinging
Doors/locking: Remote locking
Floor surface: Sealed concrete
Intercom: Two-way to common areas
HVAC: Hydronic heating/cooling system;

heat pumps

Plumbing: Stainless steel

Furniture: Steel

Fire protection: Sprinklers and smoke detectors to cells and common areas

**Dimensions** 

Gross square feet/corrections: 17,783 Gross square feet/other: 16,223 Gross square feet/total: 34,006 Housing area square feet: 8,765 Gross square feet per inmate: 378 Size of cells: 70 square feet (single)

Net/gross square feet: 84%

**Construction type** 

Structural: Concrete frame

Exterior walls: Reinforced concrete block

Interior walls: Concrete block Exterior surface/facade: Brick

Inmate design capacity

Single occupancy: 36 Double occupancy: 0

Dorms: 8

Special housing: 3 General population: 44

Total: 47

**Current staff** 

Full-time equivalent: Administration: 5

Security: 9 Programs/treatment: 1

Maintenance: 4
Total: 19 (entire facility)

Current inmate/staff ratio: .84:1

**Inmate housing areas** 

Design: Module/pod Cells per unit: 8 Inmates per unit: 8

Management type: Intermittent

surveillance

October 1986 population: 16

Means to handle crowding: Bunk beds in cell; second bunk permanently attached

to wall

**Construction process** 

Finance method: Special election; local

funds

Contract method: Conventional Use of inmate labor: None Use of prefabrication: None

Architect's reported analyses

Factors affecting construction costs: Positive: Use of traditional building

materials

Negative: Porous site condition; remote

location

Factors affecting time schedule: Positive: Use of traditional building materials; moderate winter

Negative: None

(No floorplan available at time of publication)

# **Garfield County Jail (Expansion)**

Jurisdiction official: Verne Soucie, Sheriff

Contact: Undersheriff D. Schnider, Garfield County Jail, P.O. Box 249, Glenwood Springs, CO 81601, 303–945–0453 Architect/Builder: MDF Detention/Corrections Facilities, Inc., P.O. Box 979, Fort Collins, CO 80522, 303–223–7052

Construction manager: None

Groundbreaking: June 1982 Finish date: October 1982 Construction time: 4 months

**Design capacity:** 16 **Total cost:** \$293,000

Total annual operating costs: N/A

(expansion)

Category: Expansion project Facility type: County jail

**Building configuration:** Integrated

structure

### Costs

Total: \$293,000

Building only: \$256,000 Housing area: Unknown Housing per inmate: Unknown Housing per cell: Unknown Total per inmate: \$18,312 Total per GSF: \$108.52

Total annual operating costs: N/A

(expansion)

### Security

Perimeter: Building exterior only

Inmate security level:
Maximum: 0
Medium: 100%
Minimum: 0

### **Inmate cells**

Doors/material: Steel Doors/type: Swinging

Doors/locking: Remote locking; manual

locking

Floor surface: Epoxy coating

Intercom: Two-way to cells and common

areas

HVAC: Air conditioning Plumbing: Stainless steel

Furniture: Steel

Fire protection: Smoke detectors for cells

and common areas

### **Dimensions**

Gross square feet/corrections: 2,700

Gross square feet/other: 0 Gross square feet/total: 2,700 Housing area square feet: 1,600 Gross square feet per inmate: 169 Size of cells: 160 square feet (dorms)

Net/gross square feet: 93%

# **Construction type**

Structural: Steel frame Exterior walls: Steel panels Interior walls: Steel panels

Exterior surface/facade: Steel panels

### **Inmate design capacity**

Single occupancy: 0 Double occupancy: 4

Dorms: 12 Special housing: 0 General population: 16

Total: 16

### **Current staff**

Full-time equivalent: Administration: N/A

Security: 5

Programs/treatment: N/A Maintenance: N/A Total: 5 (expansion only) Current inmate/staff ratio: 5:1

### **Inmate housing areas**

Design: Linear, outside Cells per unit: 4 Inmates per unit: 16

Management type: Intermittent

surveillance

October 1985 population: 25

Facility commitment: Local jail inmates;

sentenced State prisoners

Means to handle crowding: Bunk beds

in cell

### **Construction process**

Finance method: Local funds

Contract method: Turn-key design and

build

Use of inmate labor: None
Use of prefabrication: Extensive,
relocatable steel modules

# **Architect's reported analyses**

Factors affecting construction costs:
Positive: Use of prefabricated components,
factory assembly; simple construction
methods, repetitiveness of design;
phased construction, fast track
construction management
Negative: Difficult site conditions

Factors affecting time schedule:
Positive: Use of prefabricated components,
factory assembly; simple construction
methods, repetitiveness of design;
coordination of design between parties
Negative: Slow responses and delivery

from vendors, suppliers



(No floorplan available at time of publication)

Jurisdiction official: Robert C. Braudis, Sheriff

Contact: Jeanne Lederer, Jail Administrator, Pitkin County Jail, 506 East Main Street, Aspen, CO 81611, 303-925-3232

Architect: Caudill Gustafson & Associates Architects, P.C., P.O. Box FF, Aspen, CO 81612, 303-925-3383

Construction manager: Newstrom-Davis, 2000 West 8th Avenue, Denver, CO 80204, 303–623–3171

Groundbreaking: October 1982 Finish date: September 1983 Construction time: 11 months **Design capacity:** 25 **Total cost:** \$1,685,950

**Total annual operating costs:** \$700,000

Category: New, ancillary building; phased project (future)

Facility type: Complex: county jail, law

enforcement admin., shell **Building configuration:** Integrated

structure

### **Costs**

Total: \$1,685,950 Building only: \$1,665,950 Housing area: \$818,650 Housing per inmate: \$51,166 Housing per cell: \$51,166

Total per inmate: N/A (complex)
Total per GSF: N/A (phased project)
Total annual operating costs: \$700,000

# Security

Perimeter: Building exterior only

Inmate security level:
Maximum: 25%
Medium: 50%
Minimum: 25%

### **Inmate cells**

Doors/material: Wooden; steel

Doors/type: Swinging

Doors/locking: Remote locking only Floor surface: Carpet; vinyl tile; synthetic

gym floor

Intercom: One-way to cells; call button

only

HVAC: Heating/air circulation; passive hybrid solar system; hot air/gas heating

Plumbing: Stainless steel; china; enameled steel

steer

Furniture: Wood; concrete (max.)
Fire protection: Smoke detectors for cells
and common areas; sprinklers for

common areas

### **Dimensions**

Gross square feet/corrections: 10,478 Gross square feet/other: 5,948 Gross square feet/total: 16,426 Housing area square feet: 7,976 Gross square feet per inmate: 419 Size of cells: 80 square feet (single)

Net/gross square feet: 83%

# **Construction type**

Structural: Steel frame

Exterior walls: CMU block; brick Interior walls: CMU block

Interior walls: CMU block Exterior surface/facade: Brick

### Inmate design capacity

Single occupancy: 16 Double occupancy: 0

Dorms: 0

Special housing: 9
General population: 16

Total: 25

### **Current staff**

Full-time equivalent: Administration: 1 Security: 8

Programs/treatment: Contracted and

volunteers

Maintenance: Contracted

Total: 9

Current inmate/staff ratio: 2.2:1

### **Inmate housing areas**

Design: Module/pod Cells per unit: 2 to 6 Inmates per unit: 2 to 6

Management type: Direct supervision

October 1985 population: 20

Facility commitment: Local jail inmates Means to handle crowding: Beds in

dayroom

### **Construction process**

Finance method: G.O. Bonds; special

election

Contract method: CM fast track; stipulated sum after subcontracts awarded

Use of inmate labor: None Use of prefabrication: Limited

### Architect's reported analyses

Factors affecting construction costs:
Positive: Use of prefabricated components,
factory assembly; use of many
nonsecurity components
Negative: Difficult site conditions

Negative: Difficult site conditions (prominent site); complex electronic control system; weather problems


(early winter)

Factors affecting time schedule:

Positive: None

Negative: Slow responses and delivery from vendors, suppliers; user changes

during construction



169

# **Summit County Justice Center**

Jurisdiction official: Delbert Ewoldt, Sheriff

Contact: Sheriff Delbert Ewoldt, Summit County Justice Center, 501 North Park, Breckenridge, CO 80424, 303–453–2232 Architect: Peter Witter, Architects, 154 Dillon Mall, Dillon Center Building, P.O. Box 238, Dillon, CO 80435, 303–468–2277 Construction manager: None

Groundbreaking: July 1985 Finish date: December 1986 Construction time: 17 months

**Design capacity:** 46 **Total cost:** \$6,300,000

**Total annual operating costs:** \$475,975

Category: New, independent facility Facility type: Complex: county jail, law enforcement, courts, coroner,

probation

Building configuration: Integ. structure

#### **Costs**

Total: \$6,300,000 Building only: \$4,200,000 Housing area: Unknown Housing per inmate: Unknown Housing per cell: Unknown

Total per inmate: N/A (complex) Total per GSF: \$136.96

Total annual operating costs: \$475,975

#### **Dimensions**

Gross square feet/corrections: 18,400 Gross square feet/other: 27,600 Gross square feet/total: 46,000 Housing area square feet: 18,400 Gross square feet per inmate: 400 Size of cells: 77 square feet (single);

558 (dorm)

Net/gross square feet: 94%

### **Construction type**

Structural: Steel frame; CMU block

bearing walls

Exterior walls: Brick; architectural precast; load bearing masonry; insulated double

Interior walls: CMU block; brick; combination of masonry bearing, steel frame, and poured-in-place concrete

Exterior surface/facade: Brick; stucco;

colored concrete lintels

### Security

Perimeter: Building exterior; alarm/ detection systems; camera

surveillance Inmate security level:

Maximum: 17% Medium: 23% Minimum: 51% Other: 9%

#### **Inmate cells**

Doors/material: Steel Doors/type: Sliding

Doors/locking: Motor driven and remote

locking

Floor surface: Epoxy coating; sealed

concrete

Intercom: Two-way to cells HVAC: Air conditioning; gas heat Plumbing: Stainless steel; china

Furniture: Steel

Fire protection: Smoke detectors for common areas; sprinklers for cells;

manual alarm stations

### Inmate design capacity

Single occupancy: 32 Double occupancy: 0

Dorms: 9

Special housing: 5 General population: 41

Total: 46

#### **Current staff**

Total: 15

Full-time equivalent: Administration: 1 Security: 14

Programs/treatment: 0 Maintenance: 0

Current inmate/staff ratio: 2.87:1

## **Inmate housing areas**

Design: Module/pod Cells per unit: 8 Inmates per unit: 8

Management type: Remote surveillance

December 1986 population: 43

Facility commitment: Local jail inmates Means to handle crowding: Will attach second bunk permanently; 20 bed

expansion

# **Construction process**

Finance method: Certificates of

**Participation** 

Contract method: Negotiated G.M.P. fast

track

Use of inmate labor: None Use of prefabrication: None


#### Architect's reported analyses

Factors affecting construction costs:
Positive: Tight budget; favorable bond
market; popular layout efficiencies
Negative: Exterior aesthetics; masonry
construction; design for retrofit detention hollow metal due to long lead
times; life safety considerations

Factors affecting time schedule: Positive: Separations allowed individual areas to be completed and occupied (e.g., law enforcement, courts, and jail)

Negative: Government procedures, regulations, and red tape; approval

process



# **Bridgeport Correctional Center: Modular Units (Addition)**

Jurisdiction official: Raymond M. Lopes, Commissioner, Department of Correction

Contact: Warden Michael A. Chernovetz, Bridgeport Correctional Center, 1106 North Avenue, Bridgeport, CT 06604, 203-579-6131 Modular manufacturer: Arthur Industries, Inc., P.O. Box 74, South Main Street, Terryville, CT 06786, 203-582-6552 Construction manager: Arthur Industries, Inc., P.O. Box 74, South Main Street, Terryville, CT 06786, 203-582-6552

Groundbreaking: January 1986

Finish date: July 1986 Construction time: 6 months Design capacity: 100 **Total cost:** \$1,326,316

Total annual operating costs: \$745,000

(addition only)

Category: New, ancillary building; temporary facility/housing Facility type: State prison

**Building configuration:** Integrated

Design: Open dormitory with exterior

Management type: Remote surveillance

Facility commitment: State prisoners

Means to handle crowding: Unknown

**Inmate housing areas** 

structure

windows

Cells per unit: 0

Inmates per unit: 50

#### Costs

Total: \$1,326,316

Building only: \$1,138,830 Housing area: \$1,138,830 Housing per inmate: \$11,388 Housing per cell: \$569,415 Total per inmate: \$13,263

Total per GSF: \$76.53 Total annual operating costs: \$745,000

Perimeter: Single fence; razor wire

(addition only)

Inmate security level:

Minimum: 100%

Maximum: 0 Medium: 0

**Security** 

on fence

Gross square feet/corrections: 17,330

Size of cells: 6,400 square feet (dorms)

Net/gross square feet: 97%

# **Construction type**

Structural: Wood construction, wood

trusses

Exterior walls: Wood framed Interior walls: Wood framed Exterior surface/facade: Masonite

# Inmate design capacity

Single occupancy: 0 Double occupancy: 0

Dorms: 100 Special housing: 0 General population: 100

Total: 100

#### **Inmate cells**

Doors/material: Steel Doors/type: Swinging

Doors/locking: Manual locking

Floor surface: Vinyl tile

Intercom: One-way to common areas

HVAC: Air conditioning

Plumbing: China Furniture: None

Fire protection: Smoke detectors and sprinklers for cells and common areas

#### **Current staff**

Full-time equivalent: Administration: 2 Security: 17

Programs/treatment: 1 Maintenance: 1

Total: 21 (addition only) Current inmate/staff ratio: 4.95:1

# Architect's reported analyses

Factors affecting construction costs: Positive: Prefabricated components, factory assembly; simple construction methods, repetitiveness of design; phased construction, fast track CM

Negative: Difficult site conditions; government procedures, regulations,

and red tape

Factors affecting time schedule: Positive: Use of prefabricated components, factory assembly; simple construction methods; phased construction,

fast track CM

Negative: Government procedures, regulations, and red tape

#### **Dimensions**

Gross square feet/other: 0 Gross square feet/total: 17,330 Housing area square feet: 17,330 Gross square feet per inmate: 173

# **Construction process**

August 1986 population: 104

Finance method: State funds

Contract method: Turn-key design and

build

Use of inmate labor: None

Use of prefabrication: Extensive; modular

units

(No floorplan available at time of publication)

# J. Bernard Gates Correctional Unit (Addition)

Jurisdiction official: Raymond M. Lopes, Commissioner, Department of Correction

Contact: Warden Dennis T. Guay, J. Bernard Gates Correctional Unit, 131 North Bridebrook Road, Niantic, CT 06357, 203-739-3973 Modular manufacturer: Arthur Industries, Inc., P.O. Box 74, South Main Street, Terryville, CT 06786, 203-582-6552 Construction manager: Arthur Industries, Inc., P.O. Box 74, South Main Street, Terryville, CT 06786, 203-582-6552

**Groundbreaking:** January 1986

Finish date: July 1986 Construction time: 6 months Design capacity: 104 **Total cost:** \$1,272,546

Total annual operating costs: N/A

(addition)

Category: New, ancillary building; temporary facility/housing

Facility type: State jail

**Building configuration:** Integrated

structure

#### Costs

Total: \$1,272,546

Building only: \$1,009,660 Housing area: \$1,009,660 Housing per inmate: \$9,708 Housing per cell: \$504,830 Total per inmate: \$12,236 Total per GSF: \$73.43

Total annual operating costs: N/A

(addition)

#### **Security**

Perimeter: Single fence; razor wire on

fence

Inmate security level: Maximum: 0 Medium: 0 Minimum: 100%

#### Inmate cells

Doors/material: Steel Doors/type: Swinging

Doors/locking: Manual locking Floor surface: Vinyl tile

Intercom: One-way to common areas **HVAC**: Air conditioning

Plumbing: China Furniture: Unknown

Fire protection: Smoke detectors and sprinklers for cells and common areas

#### **Dimensions**

Gross square feet/corrections: 17,330

Gross square feet/other: 0 Gross square feet/total: 17,330 Housing area square feet: 17,330 Gross square feet per inmate: 167 Size of cells: 6,400 square feet (dorms)

Net/gross square feet: 97%

#### Construction type

Structural: Wood construction/wood

trusses

Exterior walls: Wood framed Interior walls: Wood framed Exterior surface/facade: Masonite

#### **Inmate design capacity**

Single occupancy: 0 Double occupancy: 0

Dorms: 104 Special housing: 0 General population: 104

Total: 104

#### **Current staff**

Full-time equivalent: Administration: 2 Security: 22

Programs/treatment: 4

Maintenance: 1

Total: 29 (entire facility) Current inmate/staff ratio: 3.59:1

# **Inmate housing areas**

Design: Open dorm with exterior windows

Cells per unit: 1 Inmates per unit: 52

Management type: Remote surveillance November 1986 population: 104 Facility commitment: State prisoners Means to handle crowding: Unknown

# **Construction process**

Finance method: State funds

Contract method: Turn-key design and

build

Use of inmate labor: None

Use of prefabrication: Extensive; modular


units

#### Architect's reported analyses

Factors affecting construction costs: Positive: Prefabricated components, factory assembly; simple construction methods, repetitiveness of design; phased construction, fast track CM Negative: Difficult site conditions: government procedures, regulations, and red tape

Factors affecting time schedule: Positive: Use of prefabricated components, factory assembly; simple construction methods, repetitiveness of design; phased construction, fast track

Negative: Government red tape



# **Delaware Correctional Center (Maximum Security) (Addition)**

Jurisdiction official: Robert Watson, Commissioner, Department of Correction

Contact: Warden Walter Redman, Delaware Correctional Center, Smyrna, DE 19977, 302-653-9261 Architect: Weymouth Architects, A.I.A., 901 Washington Street, Wilmington, DE 19801, 302-658-8760

Construction manager: None

**Groundbreaking:** April 1979 Finish date: August 1981 Construction time: 28 months Design capacity: 64 **Total cost:** \$5,100,000 Total annual operating costs: \$1,134,797 (addition only)

Category: New, ancillary building

Facility type: State prison

**Building configuration:** Integrated

structure

#### Costs

Total: \$5,100,000 Building only: \$3,225,000 Housing area: Unknown Housing per inmate: Unknown Housing per cell: Unknown Total per inmate: \$79,687 Total per GSF: \$221.74

Total annual operating costs: \$1,134,797

(addition only)

#### Security

Perimeter: Double fence; razor wire on fence; K-9 and armed vehicle patrols Inmate security level:

Maximum: 100% Medium: 0 Minimum: 0

**Dimensions** 

Gross square feet/corrections: 23,000 Gross square feet/other: 0 Gross square feet/total: 23,000 Housing area square feet: 18,400 Gross square feet per inmate: 359 Size of cells: 73 square feet (single)

Net/gross square feet: 86%

# Construction type

Structural: Load bearing precast panels Exterior walls: Precast panels; CMU block Interior walls: Precast panels; CMU block Exterior surface/facade: Aggregate epoxy and rigid insulated facing

#### Inmate design capacity

Single occupancy: 64 Double occupancy: 0

Dorms: 0

Special housing: 0 General population: 64

Total: 64

#### **Inmate cells**

Doors/material: Steel Doors/type: Sliding Doors/locking: Motor driven and remote

locking

Floor surface: Epoxy coating; sealed concrete

Intercom: Two-way to cell block HVAC: Air conditioning; solar; heat recovery unit; steam heating plant

Plumbing: Stainless steel

Furniture: Steel

Fire protection: Smoke detectors and sprinklers for cells; remote alarms to guards with emergency water

disconnects

#### **Current staff**

Full-time equivalent: Administration: 6 Security: 38

Programs/treatment: 1 Maintenance: 5

Total: 50 (addition only) Current inmate/staff ratio: 1.28:1

### **Inmate housing areas**

Design: Module/pod; modules (triangulated) with "dog bone"

interconnect

Cells per unit: 10 to 12 Inmates per unit: 10 to 12

Management type: Remote surveillance

October 1985 population: 64

Facility commitment: State prisoners Means to handle crowding: None

# **Construction process**

Finance method: G.O. Bonds; State funds Contract method: Conventional

Use of inmate labor: None

Use of prefabrication: Extensive; precast concrete; precut structural steel inserts

# Architect's reported analyses

Factors affecting construction costs: Positive: Use of prefabricated components,

factory assembly


Negative: Slow construction, lengthy building time—elaborative angles; difficult site conditions (high water table); complex mechanical system; low bid system

Factors affecting time schedule:

Positive: Use of prefabricated components, factory assembly; repetitiveness of design; advanced order of materials; coordination between parties

Negative: Slow delivery of detention hardware; labor problems; complex mechanical system (detention

hardware)



# Alachua County Corrections Facility (Expansion/Remodel)

Jurisdiction official: Tom L. Allison, Acting Director

Contact: Tom L. Allison, Acting Director, Alachua County Corrections Facility, 3333 Northeast 39th Avenue, Gainesville,

FL 32609, 904-377-1040

Architect: Flad & Associates, 3300 Southwest Archer Road, Gainesville, FL 32608, 904–377–6884

Construction manager: None

Groundbreaking: February 1983

Finish date: June 1985

Construction time: 29 months

Design capacity: 292 Total cost: \$2,800,000

**Total annual operating costs:** 

\$4,643,382

Category: Remodeling/renovation; expansion; temporary housing Facility type: County jail; drug

rehabilitation

**Building configuration:** Courtyard

Costs

Total: \$2,800,000

Building only: \$2,600,000

Housing area: Unknown Housing per inmate: Unknown

Housing per cell: Unknown

Total per inmate: N/A (remodel)

Total per GSF: \$112.00

Total annual operating costs: \$4,643,382

Security

Perimeter: Building exterior; patrols

Inmate security level: Maximum: 10%

Medium: 70% Minimum: 20%

**Inmate cells** 

Doors/material: Steel Doors/type: Swinging

Doors/locking: Remote locking; manual

locking

Floor surface: Linoleum; carpet dayroom

and corridors

Intercom: Two-way from wing to central

control

HVAC: Central air conditioning; zone

electric

Plumbing: Stainless Furniture: Wood

Fire protection: Smoke detectors and sprinklers for cells and common areas;

manual alarm stations

**Dimensions** 

Gross square feet/corrections: 25,000

Gross square feet/other: 0 Gross square feet/total: 25,000 Housing area square feet: 20,000 Gross square feet per inmate: 86

Size of cells: 63 square feet (single) Net/gross square feet: 92%

**Construction type** 

Structural: Cast-in-place concrete frame

Exterior walls: CMU block Interior walls: CMU block Exterior surface/facade: Stucco

Inmate design capacity

Single occupancy: 190 Double occupancy: 0

Dorms: 90

Special housing: 12 General population: 280

Total: 292

**Current staff** 

Full-time equivalent: Administration: 28

Security: 106

Programs/treatment: 23

Maintenance: 5 Total: 162

Current inmate/staff ratio: 1.54:1

**Inmate housing areas** 

Design: Module/pod Cells per unit: 16

Inmates per unit: 16

Management type: Direct supervision

October 1985 population: 249

Facility commitment: Local jail inmates Means to handle crowding: Mattresses

on floor; beds in dayroom

**Construction process** 

Finance method: Local funds Contract method: Conventional Use of inmate labor: None Use of prefabrication: None

Architect's reported analyses

Factors affecting construction costs: Positive: Simple construction methods,

repetitiveness of design; less expensive materials and hardware; good competition, favorable market

Negative: Complex electronic, mechanical, and electrical systems


Factors affecting time schedule:

Positive: Simple construction methods, repetitiveness of design; coordination

of design between parties Negative: Complex electronic,

mechanical, and electrical systems;

multiple agency reviews



# **Federal Correctional Institution (Addition)**

Jurisdiction official: J. Michael Ouinlan, Director, Bureau of Prisons

Contact: Warden R.E. Honsted, Federal Correctional Institution, Capital Circle East, Tallahassee, FL 32317, 904-878-2173

Architect: Jim Roberson & Associates, Inc., 2551 Blairstone Pines Drive, Tallahassee, FL 32301, 904-878-7891

Construction manager: None

Groundbreaking: March 1984 Finish date: December 1985 Construction time: 21 months

Design capacity: 98
Total cost: \$1,738,932

Total annual operating costs:

N/A (addition)

Category: New, ancillary building Facility type: Federal prison Building configuration: Integrated

structure

#### **Costs**

Total: \$1,738,932

Building only: \$1,710,932 Housing area: \$1,707,932 Housing per inmate: \$17,428 Housing per cell: \$17,428 Total per inmate: \$17,744 Total per GSF: \$67.04

Total annual operating costs: N/A

(addition)

#### **Security**

Perimeter: Double fence; alarm/detection systems; razor wire on and between

fences; patrols Inmate security level: Maximum: 0 Medium: 100% Minimum: 0

#### **Inmate cells**

Doors/material: Solid; wooden

Doors/type: Swinging

Doors/locking: Manual locking Floor surface: Vinyl composition tile

Intercom: None

HVAC: Heating/air circulation only; gas

heating plant Plumbing: China Furniture: Steel; wood

Fire protection: Smoke detectors and sprinklers for cells and common areas:

manual alarm stations

#### **Dimensions**

Gross square feet/corrections: 25,938

Gross square feet/other: 0 Gross square feet/total: 25,938 Housing area square feet: 25,722 Gross square feet per inmate: 265 Size of cells: 70 square feet (single)

Net/gross square feet: 81%

### Construction type

Structural: Load bearing CMU and steel

roof trusses

Exterior walls: CMU block; brick Interior walls: CMU block Exterior surface/facade: Brick; architectural concrete trim

#### **Inmate design capacity**

Single occupancy: 98 Double occupancy: 0

Dorms: 0

Special housing: 0 General population: 98

Total: 98

#### Current staff

Full-time equivalent: Administration: 1 Security: 2

Programs/treatment: 6
Maintenance: N/A
Total: 9 (addition only)
Current inmate/staff ratio: 21.1:1

#### **Inmate housing areas**

Design: Module/pod Cells per unit: 49 Inmates per unit: 49

Management type: Direct supervision

October 1985 population: 190

Facility commitment: Federal prisoners Means to handle crowding: Second bunk

on wall

# **Construction process**

Finance method: Federal funds Contract method: Conventional Use of inmate labor: None Use of prefabrication: None

## Architect's reported analyses

Factors affecting construction costs:
Positive: Simple construction methods,
repetitiveness of design; good competition, favorable market; less expensive
materials and hardware

Negative: Government procedures,

regulations, "red tape"


Factors affecting time schedule:

Positive: Simple construction methods,

repetitiveness of design

Negative: Slow responses and delivery from vendors, suppliers; weather problems; government procedures,

regulations, "red tape"



# **Leon County Jail (Expansion)**

Jurisdiction official: Eddie Boone, Sheriff

Contact: Captain Howard H. Schleich, Jail Director, Leon County Jail, 2825 Municipal Way, Tallahassee, FL 32301, 904–576–3121 Architect: Barrett, Daffin and Carlan, Inc., P.O. Drawer 12339, 3100 Capital Circle N.E., Tallahassee, FL 32317, 904–386–1141

Construction manager: None

Groundbreaking: October 1984 Finish date: December 1985 Construction time: 14 months **Design capacity:** 100 **Total cost:** \$710,255

Total annual operating costs: N/A

(expansion)

Category: Expansion project Facility type: County jail

Inmate housing areas

Design: Dormitories

Inmates per unit: 50

Cells per unit: 1

open dorm

Building configuration: Campus style

Management type: Remote surveillance

Facility commitment: Local jail inmates

Means to handle crowding: Single beds in

September 1986 population: 100

#### **Costs**

Total: \$710,255

Building only: \$710,255 Housing area: \$710,255 Housing per inmate: \$7,103 Housing per cell: \$355,128 Total per inmate: \$7,103 Total per GSF: \$72.47

Total annual operating costs: N/A

Perimeter: Single fence; razor wire on

(expansion)

# Construction type

Structural: Steel frame; precast concrete

frame

Exterior walls: Cast-in-place concrete;

brick

Interior walls: CMU block

Exterior surface/facade: Brick; stucco;

paint

#### fence; video camera surveillance Inmate security level:

**Security** 

Maximum: 0 Medium: 100% Minimum: 0

#### **Inmate cells**

Doors/material: Steel Doors/type: Swinging

Doors/locking: Remote locking; manual

locking

Floor surface: Linoleum

Intercom: One-way to common areas HVAC: Air conditioning; heating/air

circulation

Plumbing: Stainless steel; china

Furniture: Steel

Fire protection: Smoke detectors and sprinklers for common areas; manual

alarm stations

# **Dimensions**

Gross square feet/corrections: 9,800

Gross square feet/other: 0 Gross square feet/total: 9,800 Housing area square feet: 9,800 Gross square feet per inmate: 98 Size of cells: 2,880 square feet (dorms)

Net/gross square feet: 89%

## **Construction process**

Finance method: G.O. Bonds; shared cost from multiple jurisdictions

Contract method: Conventional Use of inmate labor: None

Use of prefabrication: Moderate; precast roof panels—designed for facility

furnishings

# Inmate design capacity

Single occupancy: 0 Double occupancy: 0

Dorms: 100 Special housing: 0 General population: 100

Total: 100

#### **Current staff**

Full-time equivalent: Administration: 0

Security: 3

Programs/treatment: 0 Maintenance: 0

Total: 3 (expansion only)
Current inmate/staff ratio: 33.33:1

# Architect's reported analyses

Factors affecting construction costs:

Positive: Prefabricated components, factory assembly; simple construction methods, repetitiveness of design; good

competition, favorable market Negative: Slow construction

Factors affecting time schedule:
Positive: Use of prefabricated components, factory assembly; simple construction methods, repetitiveness of design; coordination of design between

parties
Negative: Slow responses and delivery
from vendors; weather problems

182

(No floorplan available at time of publication)

# **Leon County Justice Complex (Addition)**

Jurisdiction official: Eddie Boone, Sheriff

Contact: Major Ron Dyke, Leon County Justice Complex, 301 South Monroe Street, Tallahassee, FL 32301, 904–222–4740 Architect: Barrett Daffin and Carlan, Inc., P.O. Drawer 12339, 3100 Capital Circle, Tallahassee, FL 32317, 904–386–1141 Construction manager: Gilbane Building Company, 6200 Courtney Campbell Causeway, Suite 490, Tampa, FL 33607, 813–875–4033

**Groundbreaking:** October 1985 **Finish date:** December 1987 **Construction time:** 26 months

Design capacity: 51
Total cost: \$32,000,000

Total annual operating costs: N/A

(addition)

Category: New, ancillary building Facility type: Complex: holding areas,

law enforcement, courts

**Building configuration:** Integrated

structure; high rise

#### Costs

Total: \$32,000,000 Building only: Unknown Housing area: \$396,360 Housing per inmate: \$11,010 Housing per cell: \$39,636

Total per inmate: N/A (complex)

Total per GSF: \$114.39

Total annual operating costs: N/A

(addition)

#### **Security**

Perimeter: Building exterior; video

camera surveillance Inmate security level: Maximum: 80% Medium: 20% Minimum: 0

#### **Inmate cells**

Doors/material: Steel Doors/type: Sliding

Doors/locking: Manual locking Floor surface: Sealed concrete Intercom: One-way to common areas HVAC: Air conditioning; heating/air

circulation

Plumbing: Stainless steel

Furniture: Steel

Fire protection: Smoke detectors and cells and common areas; sprinklers for cells

# **Dimensions**

Gross square feet/corrections: 5,000 Gross square feet/other: 274,750 Gross square feet/total: 279,750 Housing area square feet: 3,670 Gross square feet per inmate: 98 Size of cells: Unknown

Net/gross square feet: 80%

# **Construction type**

Structural: Cast-in-place concrete frame Exterior walls: Architectural precast;

granite and limestone Interior walls: CMU block

Exterior surface/facade: Natural wall

## Inmate design capacity

Single occupancy: 1 Double occupancy: 10

Dorms: 25

Special housing: 15 General population: 36

Total: 51

#### **Current staff**

Full-time equivalent: Administration: N/A Security: N/A

Programs/treatment: N/A Maintenance: N/A

Total: N/A

Current inmate/staff ratio: N/A (addition)

#### **Inmate housing areas**

Design: Linear, inside; cells arranged around internal vertical circulation core

Cells per unit: 19 Inmates per unit: 51

Management type: Remote surveillance

November 1987 population: N/A

Facility commitment: Local jail inmates Means to handle crowding: Bunk beds in

cells

#### **Construction process**

Finance method: G.O. Bonds; local

funds; State funds

Contract method: Construction manage-

ment fast track

Use of inmate labor: None

Use of prefabrication: Limited; architec-

tural precast

#### Architect's reported analyses

Factors affecting construction costs:
Positive: Phased construction, fast track
construction management; good competition, favorable market

Negative: High labor and materials costs; difficult site conditions; government procedures, regulations and red tape

Factors affecting time schedule:

Positive: Phased construction, fast track construction management; advanced order of materials and hardware; coordination of design between parties

Negative: None

(No floorplan available at time of publication)

# **Marion County Detention Center**

Jurisdiction official: Don R. Moreland, Sheriff

Contact: Captain John Pauls, Marion County Detention Center, 700 Northwest 30th Avenue, Ocala, FL 32675, 904-351-8077

Architect: Justice Systems, Inc., 348 Peachtree Street Northeast, Atlanta, GA 30308, 404-577-3184

Construction manager: Rosser White Hobbs Davidson McClellan & Kelly, Inc., 524 West Peachtree Street NW., Atlanta,

GA 30308, 404-876-3800

Groundbreaking: February 1983

Finish date: May 1985

Construction time: 27 months

Design capacity: 390 **Total cost:** \$8,648,000

Total annual operating costs:

\$3,917,824

Category: New, independent facility

Facility type: County jail

Building configuration: Wings connect-

ing housing pods

#### Costs

Total: \$8,648,000

Building only: \$8,200,000 Housing area: \$6,500,000

Housing per inmate: \$16,667 Housing per cell: \$16,667 Total per inmate: \$22,174

Total per GSF: \$45.75

Total annual operating costs: \$3,917,824

#### **Dimensions**

Gross square feet/corrections: 189,033

Gross square feet/other: 0 Gross square feet/total: 189,033 Housing area square feet: 137,066 Gross square feet per inmate: 485 Size of cells: 83 square feet (single)

Net/gross square feet: 77%

#### **Inmate housing areas**

Design: Module/pod Cells per unit: 96 Inmates per unit: 96

Management type: Remote surveillance

October 1985 population: 279

Facility commitment: Local jail inmates

and State prisoners

Means to handle crowding: Bunk beds in cell; beds in dayroom; mobile home;

National Guard Armory

# Security

Perimeter: Building exterior;

single fence Inmate security level: Maximum: 25% Medium: 75% Minimum: 0

# Construction type

Structural: Steel frame Exterior walls: CMU block Interior walls: Precast panels; cast-in-place concrete

Exterior surface/facade: CMU block

#### **Construction process**

Finance method: G.O. Bonds Contract method: Conventional Use of inmate labor: None Use of prefabrication: Limited

#### **Inmate cells**

Doors/material: Solid steel

Doors/type: Sliding (max.); swinging

(med.)

Doors/locking: Remote locking only (max.); motor driven and remote

locking (med.)

Floor surface: Sealed concrete

Intercom: Two-way to common areas

**HVAC**: Air conditioning Plumbing: Stainless; china

Furniture: Steel

Fire protection: Smoke detectors and sprinklers for cells and common areas

## Inmate design capacity

Single occupancy: 384 Double occupancy: 0

Dorms: 0

Special housing: 6 General population: 384

Total: 390

#### Current staff

Full-time equivalent: Administration: 15 Security: 72

Programs/treatment: 5

Maintenance: 7 Total: 99

Current inmate/staff ratio: 2.82:1

#### Architect's reported analyses

Factors affecting construction costs: Positive: Simple construction methods, repetitiveness of design; good competition, favorable market Negative: Slow construction, lengthy building time; government procedures, regulations, "red tape"

Factors affecting time schedule: Positive: Simple construction methods, repetitiveness of design; coordination of design between parties

Negative: Labor problems; weather problems; government procedures,

regulations, "red tape"



(No floorplan available at time of publication)

## **Martin Correctional Institution**

Jurisdiction official: Richard L. Dugger, Secretary, Department of Corrections

Contact: Superintendent David E. Watson, Martin Correctional Institution, 1150 Southwest Allapattah Road, Indiantown, FL 33456, 305-597-3705

Architect: Schweizer, Inc., 55 East Jackson Street, Orlando, FL 32801, 305-425-0922

Construction manager: Percon Constructors, 217 North Westmont Drive, Suite 3019, Altamonte Spring, FL 32714, 305-682-3030

Groundbreaking: August 1983 Finish date: November 1985 **Construction time:** 27 months

Design capacity: 929 Total cost: \$25,000,000

Total annual operating costs: \$6,625,073

Category: New, independent facility

Facility type: State prison

Building configuration: Campus style

#### **Costs**

Total: \$25,000,000 Building only: \$22,000,000 Housing area: Unknown Housing per inmate: Unknown Housing per cell: Unknown

Total per inmate: \$26,911 Total per GSF: \$109.75

Total annual operating costs: \$6,625,073

#### **Dimensions**

Gross square feet/corrections: 227,790

Gross square feet/other: 0 Gross square feet/total: 227,790 Housing area square feet: 120,000 Gross square feet per inmate: 245 Size of cells: 64 square feet (single)

Net/gross square feet: 88%

**Inmate housing areas** 

Design: Module/pod Cells per unit: 112 Inmates per unit: 150

Management type: Remote surveillance

June 1986 population: 1,069

Facility commitment: Local jail inmates;

State prisoners

Means to handle crowding: Bunk beds in cell; second bunk permanently attached

to wall

## Security

Perimeter: Razor wire on and between double fence; alarm/detection systems;

patrols

Inmate security level: Maximum: 17% Medium: 83% Minimum: 0

# **Construction type**

Structural: Steel frame; precast concrete

frame

Exterior walls: CMU block Interior walls: CMU block Exterior surface/facade: Stucco

#### **Construction process**

Finance method: State funds

Contract method: Construction manage-

ment fast track

Use of inmate labor: None Use of prefabrication: None

#### **Inmate cells**

Doors/material: Steel Doors/type: Swinging Doors/locking: Unknown Floor surface: Sealed concrete Intercom: Two-way to common areas HVAC: Heating/air circulation

Plumbing: China Furniture: Steel

Fire protection: Smoke detectors for cells; sprinklers for cells and common areas;

manual alarm stations

# **Inmate design capacity**

Single occupancy: 448 Double occupancy: 448

Dorms: 0

Special housing: 33 General population: 896

Total: 929

# Architect's reported analyses

Factors affecting construction costs: Positive: Simple construction methods,

repetitiveness of design

Negative: Complex electronic, mechanical, and electrical systems

Factors affecting time schedule:

Positive: Advanced order of materials and

hardware

Negative: Complex electronic, mechani-


cal, and electrical systems

#### **Current staff**

Full-time equivalent: Administration: 81 Security: 167

Programs/treatment: 17 Maintenance: 19 Total: 284

Current inmate/staff ratio: 3.76:1



# Pinellas County Jail—Medium Security Facility (Addition)

Jurisdiction official: Gerard Coleman, Sheriff

Contact: Charles Felton, Director, Detention and Correction, Pinellas County Detention Complex, Building C,

14400 49th Street North, Clearwater, FL 33520, 813-535-6415

Architect: Watson and Company, 3010 Azeele Street, Tampa, FL 33679, 813–876–2411

Construction manager: Peter Brown Company, 1475 Belcher Road South, Clearwater, FL 33518, 813-531-1466

Groundbreaking: May 1984 Finish date: March 1985 Construction time: 10 months **Design capacity:** 194 **Total cost:** \$2,976,221

Total annual operating costs: N/A

(addition)

Category: New, ancillary building

Facility type: County jail

Building configuration: Integrated

structure

#### Costs

Total: \$2,976,221

Building only: \$2,787,600

Housing area: N/A Housing per inmate: N/A Housing per cell: N/A Total per inmate: \$15,341 Total per GSF: \$99.26

Total annual operating costs: N/A

(addition)

#### **Security**

Perimeter: Double fence; razor wire on

fence; towers; patrols Inmate security level: Maximum: 0 Medium: 100% Minimum: 0

# **Dimensions**

Gross square feet/corrections: 29,985

Gross square feet/other: 0 Gross square feet/total: 29,985 Housing area square feet: 24,382 Gross square feet per inmate: 155 Size of cells: 92 square feet (double)

Net/gross square feet: 68%

#### **Inmate housing areas**

Design: Module/pod Cells per unit: 48 Inmates per unit: 96

Management type: Remote surveillance

October 1985 population: 194

Facility commitment: Local jail inmates Means to handle crowding: Beds in

dayroom

# **Construction type**

Structural: Cast-in-place concrete frame;

precast concrete cells

Exterior walls: Precast cells; cast-in-place

concrete; CMU block

Interior walls: Precast cells; cast-in-place

concrete; CMU block

Exterior surface/facade: Stucco; paint

### **Construction process**

Finance method: Ad valorem funds,

budget allocation

Contract method: Conventional Use of inmate labor: None Use of prefabrication: Extensive

#### **Inmate cells**

Doors/material: Steel Doors/type: Sliding

Doors/locking: Motor driven and remote

locking

Floor surface: Sealed concrete

Intercom: Two-way to cells and common

areas

HVAC: Air conditioning; electric heating

plant

Plumbing: Stainless combination unit

Furniture: Steel

Fire protection: Smoke detectors and sprinklers for cells and common areas;

manual alarm stations

#### Inmate design capacity

Single occupancy: 0 Double occupancy: 192

Dorms: 0

Special housing: 2 General population: 192

Total: 194

#### **Current staff**

Full-time equivalent: Administration: N/A

Security: 35

Programs/treatment: 2
Maintenance: N/A
Total: 37 (addition only)
Current inmate/staff ratio: 5.24:1

## Architect's reported analyses


Factors affecting construction costs:
Positive: Use of prefab. components,
simple construction methods, repetitiveness of design, phased construction,
fast track CM

Negative: Difficult site conditions; government procedures, "red tape"

Factors affecting time schedule:
Positive: Use of prefab. components,
factory assembly; simple construction
methods, repetitiveness of design;
coordination of design between parties

Negative: Government "red tape"; complex electronic, mechanical, and electrical

systems



# Santa Rosa County Jail (Remodel/Expansion)

Jurisdiction official: William Carroll, Chairman, Board of County Commissioners

Contact: Lt. Pamela Biggs, Jail Administrator, Santa Rosa County Jail, 217 Willing Street, P.O. Box 7129, Milton, FL 32572,

904-623-3691

Architect: PH & J Architects, Inc., 777 South Lawrence Street, Montgomery, AL 36104, 205-265-8781

Construction manager: None

Groundbreaking: May 1982 Finish date: March 1984 Construction time: 22 months **Design capacity:** 126 **Total cost:** \$3,665,127

Total annual operating costs: \$1,262,024

Category: Remodeling/renovation proj-

ect; expansion project

Facility type: Complex: county jail, law

enforcement

Building configuration: Integ. structure

#### Costs

Total: \$3,665,127

Building only: \$3,546,180 Housing area: \$2,716,374 Housing per inmate: \$24,253 Housing per cell: \$33,535

Total per inmate: N/A (complex)

Total per GSF: \$88.43

Total annual operating costs: \$1,262,024

#### **Dimensions**

Gross square feet/corrections: 31,766 Gross square feet/other: 9,679 Gross square feet/total: 41,445 Housing area square feet: 24,065 Gross square feet per inmate: 252 Size of cells: 75 square feet (single);

97 (double); 1,280 (dorm) Net/gross square feet: 97%

### **Inmate housing areas**

Design: Module/pod Cells per unit: 64 Inmates per unit: 64

Management type: Remote surveillance

July 1986 population: 102

Facility commitment: Local jail inmates Means to handle crowding: Unknown

# Security

Perimeter: Building exterior only

Inmate security level:
Maximum: 57%
Medium: 29%
Minimum: 14%

# **Construction type**

Structural: Cast-in-place concrete frame Exterior walls: Cast-in-place concrete;

architectural precast

Interior walls: Cast-in-place concrete;

CMU block

Exterior surface/facade: Paint

# **Construction process**

Finance method: Local funds Contract method: Conventional Use of inmate labor: None Use of prefabrication: Limited

#### **Inmate cells**

Doors/material: Steel

Doors/type: Swinging; sliding

Doors/locking: Motor driven and remote

locking

Floor surface: Urethane coating Intercom: Two-way to common areas HVAC: Air conditioning; steam heat Plumbing: Stainless combination unit

Furniture: Steel

Fire protection: Smoke detectors for cells and common areas; manual alarm stations; standpipe system with pump

#### Inmate design capacity

Single occupancy: 64 Double occupancy: 32

Dorms: 16

Special housing: 14 General population: 112

Total: 126

#### **Current staff**

Full-time equivalent: Administration: 3 Security: 42

Programs/treatment: 5 Maintenance: 3

Total: 53


Current inmate/staff ratio: 1.92:1

#### Architect's reported analyses

Factors affecting construction costs:
Positive: Prefabricated components,
factory assembly; simple construction
methods, repetitiveness of design
Negative: Lengthy building time, construction phased to allow occupancy;
difficult site, building elevated above
flood plane; complex electronic,
mechanical, and electrical systems

Factors affecting time schedule:
Positive: Use of prefab. components,
factory assembly; simple construction
methods, repetitiveness of design
Negative: Slow responses and delivery

from vendors, suppliers



# **Seminole County Correctional Facility (Addition/Remodel)**

Jurisdiction official: John E. Polk, Sheriff

Contact: Captain Jay Leman, Seminole County Correctional Facility, 211 Bush Boulevard, Sanford, FL 32773, 305-323-6512

Architect: Prime Design, Inc., 3010 Azeele Street, Tampa, FL 33609, 813–876–2411

Construction manager: None

Groundbreaking: August 1985 Finish date: October 1987 Construction time: 26 months **Design capacity:** 739 **Total cost:** \$12,059,000

Total annual operating costs: Unknown

Category: New, ancillary building; remodeling/renovation project Facility type: County jail

Building configuration: Clusters

#### Costs

Total: \$12,059,000

Building only: \$11,481,000 Housing area: \$5,325,000 Housing per inmate: \$7,924 Housing per cell: \$14,315

Total per inmate: N/A (remodel)

Total per GSF: \$65.90

Total annual operating costs: Unknown

# **Security**

Perimeter: Single fence; video camera

surveillance
Inmate security level:
Maximum: 10%
Medium: 76%
Minimum: 14%

### **Inmate cells**

Doors/material: Steel Doors/type: Sliding

Doors/locking: Remote locking Floor surface: Sealed concrete

Intercom: Two-way to cells and common

areas

HVAC: Air conditioning; gas-fired hot

water boilers

Plumbing: Stainless steel

Furniture: Steel

Fire protection: Smoke detectors and

sprinklers for cells

#### **Dimensions**

Gross square feet/corrections: 182,980

Gross square feet/other: 0 Gross square feet/total: 182,980 Housing area square feet: 103,850 Gross square feet per inmate: 248 Size of cells: 70 square feet (gen. single); 90 (gen. double); 1,280 (gen. dorm)

Net/gross square feet: 72%

# Construction type

Structural: Load-bearing precast panels; precast concrete frame

Exterior walls: Concrete filled concrete

block; precast cells

Interior walls: Precast panels; concrete block perimeter walls; prestressed plank

roof and support floors

Exterior surface/facade: Stucco; paint;

textured concrete

#### Inmate design capacity

Single occupancy: 128 Double occupancy: 480

Dorms: 64

Special housing: 67 General population: 672 Total: 739 (entire facility)

#### **Current staff**

Full-time equivalent:

Administration: Unknown Security: Unknown

Programs/treatment: Unknown Maintenance: Unknown

Total: Unknown

Current inmate/staff ratio: Unknown

#### **Inmate housing areas**

Design: Module/pod Cells per unit: 48 Inmates per unit: 96

Management type: Intermittent surv. (remodel); remote surv. (addition)
December 1987 population: 411 (addition)
Facility commitment: Local jail inmates;
State and Federal prisoners on contract
Means to handle crowding: Renovation of

existing facility

#### **Construction process**

Finance method: Special election Contract method: Conventional Use of inmate labor: None

Use of prefabrication: Extensive; prefabri-

cated concrete cells

#### Architect's reported analyses

Factors affecting construction costs: Positive: Load-bearing precast concrete cell units stacked two high and support-

ing the roof planks

Negative: Extensive renovation of existing


structures

Factors affecting time schedule:

Positive: Precast concrete cells within the five similar housing modules

Negative: Necessity of phasing project

with jail in operation



# **South Florida Reception Center**

Jurisdiction official: Richard L. Dugger, Secretary, Department of Corrections

Contact: James E. Curington, Jr., Superintendent II, South Florida Reception Center, 14000 Northwest 41st Street, Miami.

FL 33178, 305-592-9567

Architect: Spillis Candela & Partners, Inc., 800 Douglas Entrance, Coral Gables, FL 33134, 305-447-3539

Consulting engineers: Rosser White Hobbs Davidson McClellan & Kelly, Inc., 524 West Peachtree Street, Atlanta, GA 30308.

404-876-3800

Construction manager: None

**Groundbreaking:** April 1983 Finish date: March 1986

Construction time: 35 months

**Design capacity:** 624 **Total cost:** \$23,142,326

Total annual operating costs: \$6,879,328

Category: New, independent facility

Facility type: State prison **Building configuration:** Clusters

#### Costs

Total: \$23,142,326

Building only: \$21,105,198 Housing area: \$13,214,792 Housing per inmate: \$22,942 Housing per cell: \$22,942

Total per inmate: \$37,087 Total per GSF: \$89.88

Total annual operating costs: \$6,879,328

Perimeter: Double fence; alarm/detection

patrols; camera surveillance

systems; razor wire on fences; towers;

#### **Dimensions**

Gross square feet/corrections: 257,476

Gross square feet/other: 0 Gross square feet/total: 257,476 Housing area square feet: 161,156 Gross square feet per inmate: 413 Size of cells: 80 square feet (gen. single);

96 (spec. single) Net/gross square feet: 66%

# **Construction type**

Exterior walls: Cast-in-place concrete;

CMU block

Exterior surface/facade: Stucco; paint

# Minimum: 0 Inmate cells

Security

Doors/material: Steel

Inmate security level:

Maximum: 10%

Medium: 90%

Doors/type: Swinging; sliding

Doors/locking: Motor driven and remote

locking; remote locking Floor surface: Sealed concrete

Intercom: One-way to cells; two-way to

common areas

HVAC: Heating/air circulation; energy

recycle unit; electric heat

Plumbing: Stainless steel; china; stainless

combination unit Furniture: Steel

Fire protection: Smoke detectors for cells and common areas; manual alarm

stations

Structural: Cast-in-place concrete frame

Interior walls: Cast-in-place concrete;

CMU block

#### Inmate design capacity

Single occupancy: 576 Double occupancy: 0

Dorms: 0

Special housing: 48 General population: 576

Total: 624

#### **Current staff**

Full-time equivalent: Administration: 48

Security: 200 Programs/treatment: 58

Maintenance: 20 Total: 326

Current inmate/staff ratio: 3.06:1

#### **Inmate housing areas**

Design: Module/pod Cells per unit: 48; 64 Inmates per unit: 48; 64

Management type: Remote surveillance

April 1987 population: 996

Facility commitment: Local jail inmates;

State prisoners

Means to handle crowding: Unknown

# **Construction process**

Finance method: State funds Contract method: Conventional Use of inmate labor: Moderate Use of prefabrication: None

#### Architect's reported analyses


Factors affecting construction costs: Positive: Simple construction methods, repetitiveness of design; good competition, favorable market; less expensive materials and hardware Negative: Slow construction, lengthy building time; difficult site conditions

Factors affecting time schedule:

Positive: Simple construction methods, repetitiveness of design; coordination of design between parties

Negative: Slow responses and delivery from vendors, suppliers; slow perform-

ance of general contractor



# **Union Correctional Institution (Addition)**

Jurisdiction official: Richard L. Dugger, Secretary, Department of Corrections

Contact: Superintendent W.M. Ellis, Union Correctional Institution, P.O. Box 221, Raiford, FL 32083, 904-431-1212

Architect: Hansen Lind Meyer P.C., 455 South Orange Avenue, Orlando, FL 32801, 305–422–7061

Construction manager: Federal Construction Company, 255 South Orange Avenue, Orlando, FL 32801, 305-843-5241

Groundbreaking: September 1984

Finish date: June 1985 Construction time: 8 months **Design capacity:** 336 **Total cost:** \$5,773,179

Total annual operating costs: N/A

(addition)

Category: New, ancillary building

Facility type: State prison
Building configuration: Wheel

#### **Costs**

Total: \$5,773,179

Building only: \$5,522,000 Housing area: \$5,522,000 Housing per inmate: \$16,435 Housing per cell: \$16,435 Total per inmate: \$17,182 Total per GSF: \$100.37

Total annual operating costs:

N/A (addition)

#### Security

Perimeter: Triple fence; alarm/ detection systems; razor wire on and between fences; towers; patrols

Inmate security level: Maximum: 100% Medium: 0 Minimum: 0

# **Dimensions**

Gross square feet/corrections: 57,520 Gross square feet/other: 0 Gross square feet/total: 57,520 Housing area square feet: N/A

Gross square feet per inmate: 171 Size of cells: 67.5 square feet (single)

Net/gross square feet: N/A

### **Construction type**

Structural: Precast concrete frame;

precast cells

Exterior walls: CMU block; precast cells Interior walls: Cast-in-place concrete; precast cells and floor planks Exterior surface/facade: Stucco; paint; exterior insulation system at core

# Inmate design capacity

Single occupancy: 336 Double occupancy: 0

Dorms: 0

Special housing: 0 General population: 336

Total: 336

#### **Inmate cells**

Doors/material: Steel Doors/type: Sliding

Doors/locking: Motor driven and

remote locking

Floor surface: Sealed concrete Intercom: Two-way to cells

HVAC: Heating/air circulation only;

boiler, steam coils Plumbing: Stainless Furniture: Steel

Fire protection: Smoke detectors for common areas and cell sprinklers; sprinklers for cells and common areas

# **Current staff**

Full-time equivalent: Administration: N/A

Security: 38

Programs/treatment: N/A Maintenance: N/A Total: 38 (addition only) Current inmate/staff ratio: 8.84:1

# **Inmate housing areas**

Design: Linear, outside Cells per unit: 168 Inmates per unit: 168

Management type: Remote surveillance

October 1985 population: 336
Facility commitment: State prisoners
Means to handle crowding: No crowding

permitted

### **Construction process**

Finance method: State funds Contract method: Construction management fast track

Use of inmate labor: Moderate use of


general unskilled labor

Use of prefabrication: Extensive use for cells, support area floors and roof

# Architect's reported analyses

Factors affecting construction costs:
Positive: Precast cells; phased construction, fast track construction
management (long lead items)
Negative: High water table; rural location
(lack of experienced labor)

Factors affecting time schedule:
Positive: Precast cells; precast repetition,
simple plan; multiple bid groups;
advanced order of security elements;
coordination of design between parties
Negative: Labor problems (rural area)



# **Clarke County Correctional Institution**

Jurisdiction official: David C. Evans, Commissioner, Department of Corrections

Contact: Warden Ed Greenway, Clarke County Correctional Institution, 2325 County Farm Road, Athens, GA 30601, 404-354-2901

Architect: Bryant Architect, Ltd., P.O. Box 99, 120 Avondale Road, Suite B-2, Avondale, GA 30002, 404-296-2533

Construction manager: None

Groundbreaking: July 1985 Finish date: December 1986

**Construction time:** 17 months

Design capacity: 132 **Total cost:** \$900,000

Total annual operating costs: \$870,000

Category: New, independent facility

Facility type: County jail **Building configuration:** Clusters

#### Costs

Total: \$900,000

Building only: \$885,000 Housing area: \$870,000 Housing per inmate: \$8,700 Housing per cell: \$435,000 Total per inmate: \$6,818 Total per GSF: \$45.00

Total annual operating costs: \$870,000

#### Dimensions

Gross square feet/corrections: 20,000 Gross square feet/other: 0

Gross square feet/total: 20,000 Housing area square feet: 15,000 Gross square feet per inmate: 152 Size of cells: 90 square feet (spec. single); 150 (spec. double); 4,000 (gen. dorms)

Net/gross square feet: 85%

#### **Inmate housing areas**

Design: Pod type noncontact dormitory

Cells per unit: Unknown Inmates per unit: 50

Management type: Remote surveillance

November 1987 population: 105

Facility commitment: Local jail inmates;

State prisoners

Means to handle crowding: Unknown

# Security

Perimeter: Single fence; video camera

surveillance Inmate security level: Maximum: 0 Medium: 100% Minimum: 0

# Construction type

Structural: Steel frame; CMU Exterior walls: Precast panels; CMU block; precast panels for roof decks

Interior walls: CMU block

Exterior surface/facade: Treated CMU

# **Construction process**

Finance method: Local funds; State funds Contract method: Materials only contract Use of inmate labor: Extensive; all phases except roof and HVAC installation Use of prefabrication: Limited; prestressed 4" x 6" hollow core slabs

#### Inmate cells

Doors/material: Steel Doors/type: Swinging

Doors/locking: Remote locking; manual

locking

Floor surface: Epoxy coating; quarry tile

Intercom: One-way to cells

HVAC: Heating/air circulation; gas heat

Plumbing: China Furniture: Steel

Fire protection: Smoke detectors for cells

and common areas

### Inmate design capacity

Single occupancy: 0 Double occupancy: 0

Dorms: 100 Special housing: 32 General population: 100

Total: 132

# Architect's reported analyses

Factors affecting construction costs: Positive: 100% use of inmate labor Negative: Slow construction, lengthy building time; inmate labor slowed process; could not obtain favorable material costs

Factors affecting time schedule:

Positive: None

Negative: Inmate labor


#### **Current staff**

Full-time equivalent: Administration: 0 Security: 25

Programs/treatment: 0 Maintenance: 0

Total: 25

Current inmate/staff ratio: 4.2:1



# **Dooly County Jail (Expansion)**

Jurisdiction official: L. Van Peavy, Sheriff

Contact: Sheriff L. Van Peavy, Dooly County Jail, P.O. Box 315, Vienna, GA 31092, 912-268-4128 Architect: M.G. Turner and Associates, 513 East 10th Street, Rome, GA 30161, 404-232-4456

Original design and precast by: Design Concrete, Inc., P.O. Box 2828, Rome, GA 30164, 404-295-7676

Construction manager: Grover Tuten, Route #1, Box 185, Harlem, GA 30814, 404-556-9885

**Groundbreaking:** June 1985 Finish date: October 1985 **Construction time:** 4 months

Design capacity: 11 **Total cost:** \$78,000

Total annual operating costs: N/A

(expansion)

Category: Expansion project Facility type: County jail

Building configuration: Integrated

structure

#### **Costs**

Total: \$78,000

Building only: \$75,000 Housing area: \$78,000 Housing per inmate: \$7,091 Housing per cell: \$14,187 Total per inmate: \$7,091 Total per GSF: \$71.89

Total annual operating costs: N/A

(expansion)

# Security

Perimeter: Double fence Inmate security level: Maximum: 0

Minimum: 10%

Medium: 90%

#### Inmate cells

Doors/material: Steel Doors/type: Swinging

Doors/locking: Manual locking Floor surface: Sealed concrete Intercom: Two-way to cells

HVAC: Air conditioning; heating/air

circulation

Plumbing: Stainless steel

Furniture: Steel

Fire protection: Smoke detectors for cells; wired to master panel and automatic

alarm

#### **Dimensions**

Gross square feet/corrections: 1,085 Gross square feet/other: 0

Gross square feet/total: 1,085 Housing area square feet: 1,085 Gross square feet per inmate: 99 Size of cells: 140 square feet (double)

Net/gross square feet: 82%

# **Construction type**

Structural: Load bearing precast panels Exterior walls: Precast panels (insulated)

Interior walls: Precast panels

Exterior surface/facade: Paint; textured

concrete

#### Inmate design capacity

Single occupancy: 1 Double occupancy: 10

Dorms: 0

Special housing: 0 General population: 11

Total: 11

#### **Current staff**

Full-time equivalent: Administration: N/A Security: N/A

Programs/treatment: N/A Maintenance: N/A

Total: N/A (no extra staff added) Current inmate/staff ratio: Unknown

### **Inmate housing areas**

Design: Linear, outside; linear, inside

Cells per unit: 6 Inmates per unit: 11

Management type: Intermittent surv.

October 1985 population: 10

Facility commitment: Local jail inmates

and State prisoners

Means to handle crowding: Bunk beds in cell; second bunk permanently attached

to wall

#### **Construction process**

Finance method: Local funds: State funds Contract method: Subcontract in phases Use of inmate labor: Moderate; inmate labor used for site work, floor slab, plumbing

Use of prefabrication: Extensive; precast loadbearing walls, roof panels

#### **Architect's reported analyses**

Factors affecting construction costs: Positive: Use of prefabricated components, factory assembly; simple construction methods, repetitiveness of design

Negative: Government procedures, regulations, "red tape"; complex electronic, mechanical, and

electrical systems


Factors affecting time schedule:

Positive: Use of prefabricated components, factory assembly; simple construction methods, coordination of design between parties

Negative: Government procedures,

regulations, "red tape"; complex electronic, mechanical, and

electrical systems



# Richmond County Law Enforcement and Justice Center

Jurisdiction official: Charles B. Webster, Sheriff

Contact: Charles A. Toole, Sr., Chief Jailer, Richmond County Law Enforcement and Justice Center, 401 Walton Way,

Augusta, GA 30901, 404-821-1005

Architect: Hellmuth, Obata & Kassabaum, Inc., 100 North Broadway, St. Louis, MO 63102, 314-421-2000

Construction manager: Mellon-Stuart Company, 540 Douglas Avenue, Altamonte Springs, FL 32701, 305–862–4400

**Groundbreaking:** November 1982

Finish date: October 1985 Construction time: 35 months **Design capacity: 240** 

**Total cost:** \$15,743,000 (excl. site work)

Total annual operating costs:

\$1,200,000

Category: New, independent facility Facility type: Complex: county jail, courts, law enforcement, other Building configuration: High rise

Costs

Total: \$15,743,000 (excl. site work)

Building only: \$15,743,000 Housing area: Unknown Housing per inmate: Unknown

Housing per cell: Unknown Total per inmate: N/A (complex)

Total per GSF: \$166.78

Total annual operating costs: \$1,200,000

**Dimensions** 

Gross square feet/corrections: Unknown

Gross square feet/other: Unknown Gross square feet/total: 94,392 Housing area square feet: 68,210 Gross square feet per inmate: 393 Size of cells: 74 square feet (single)

Net/gross square feet: 80%

Exterior walls: Stucco

Interior walls: CMU block partitions; concrete frame, floor, and roof

Perimeter: Single fence; perimeter

Security

alarm/detection systems Inmate security level: Maximum: 10% Medium: 90% Minimum: 0

**Inmate cells** 

Doors/material: Wooden Doors/type: Swinging

Doors/locking: Remote locking only Floor surface: Sealed concrete Intercom: One-way to common areas

**HVAC**: Air conditioning Plumbing: Stainless steel; china

Furniture: Steel

Fire protection: Sprinklers for cells

**Construction type** 

Structural: Cast-in-place concrete frame

Exterior surface/facade: Stucco

Inmate design capacity

Single occupancy: 240 Double occupancy: 0

Dorms: 0

Special housing: 0 General population: 240

Total: 240

**Current staff** 

Full-time equivalent: Administration: 8

Security: 44

Programs/treatment: 4 Maintenance: 5

Total: 61

Current inmate/staff ratio: 2.38:1

Inmate housing areas

Design: Module/pod Cells per unit: 24 Inmates per unit: 24

Management type: Remote surveillance

October 1985 population: 145

Facility commitment: Local jail inmates Means to handle crowding: Bunk beds in

**Construction process** 

Finance method: G.O. Bonds

Contract method: Construction manage-

ment fast track

Use of inmate labor: None Use of prefabrication: None

Architect's reported analyses

Factors affecting construction costs:

Positive: Choice of exterior wall system;

good bidding climate


Negative: None

Factors affecting time schedule:

Positive: None

Negative: Indecision on city vs. county

participation



# **Level Three Mezzanine**

- 1 Outdoor Exercise Below2 Typical Cell3 Dayroom Below4 Mechanical

#### **Maui Community Correctional Center (Addition)**

Jurisdiction official: Theodore Sakai, Administrator, Corrections Division

Contact: Kazumi Kobayashi, Administrator, Maui Community Correctional Center, 600 Waiale Drive, Wailuku, HI 96793,

808-244-5505

Architect: Omni Signal, Inc., P.O. Box 801, Capitola, CA 95010, 408-688-0412

Construction manager: None

**Groundbreaking:** March 1984 **Finish date:** May 1984

Construction time: 2 months

**Design capacity:** 83 **Total cost:** \$170,000

Total annual operating costs: \$261,025

(addition only)

Category: New, ancillary building Facility type: County jail; city jail; State

prison

Building configuration: Campus style

#### Costs

Total: \$170,000

Building only: \$150,000 Housing area: \$150,000 Housing per inmate: \$1,852

Housing per cell: \$6,818 Total per inmate: \$2,048 Total per GSF: \$37.78

Total annual operating costs: \$261,025

(addition only)

#### **Security**

Perimeter: Single fence; razor wire on

fence; patrols
Inmate security level:
Maximum: 0
Medium: 100%
Minimum: 0

#### **Inmate cells**

Doors/material: Solid; wooden

Doors/type: Swinging Doors/locking: Unknown Floor surface: Linoleum

Intercom: None HVAC: None needed Plumbing: China Furniture: Wood

Fire protection: Smoke detectors and

sprinklers for cells

#### **Dimensions**

Gross square feet/corrections: 4,500

Gross square feet/other: 0 Gross square feet/total: 4,500 Housing area square feet: 4,500 Gross square feet per inmate: 54

Size of cells: Unknown

Net/gross square feet: Unknown

#### **Construction type**

Structural: Solid log walls Exterior walls: Solid log

Interior walls: Solid log

Exterior surface/facade: Solid cedar logs

#### Inmate design capacity

Single occupancy: 1 Double occupancy: 40

Dorms: 40

Special housing: 2 General population: 81

Total: 83

#### **Current staff**

Full-time equivalent: Administration: 6

Security: 32 Programs/treatment: 3

Maintenance: 4

Total: 45 (entire facility)
Current inmate/staff ratio: 1.84:1

#### **Inmate housing areas**

Design: Dormitory style Cells per unit: Unknown Inmates per unit: 40

Management type: Direct supervision

October 1985 population: 83

Facility commitment: Local jail inmates;

State prisoners

Means to handle crowding: Bunk beds in cell; beds in dayroom; second bunk permanently attached to wall

#### **Construction process**

Finance method: State funds Contract method: Unknown

Use of inmate labor: Extensive; facility

built with inmate labor

Use of prefabrication: Building preengineered and pre-cut but assembled

onsite


#### Architect's reported analyses

Factors affecting construction costs: Positive: Onsite assembly of prefab. components; simple construction methods; less expensive materials and hardware; inmate labor Negative: Government procedures,

Negative: Government procedures, regulations, and red tape

Factors affecting time schedule:
Positive: Onsite assembly of prefab.
components; simple construction
methods, repetitiveness of design;
coordination of design between parties;
inmate labor

Negative: Government procedures, regulations, and red tape



#### **Centralia Correctional Center (Addition)**

Jurisdiction official: Michael P. Lane, Director, Department of Corrections

Contact: Warden Ronald J. Haws, Centralia Correctional Center, P.O. Box 1266, Shattuc Road, Centralia, IL 62801, 618-533-4111

Architect: Turner-Witt Associates, Inc., 970 East Court Street, Kankakee, IL 60901, 815-933-5529

Construction manager: None

Groundbreaking: October 1979 Finish date: October 1981 Construction time: 24 months **Design capacity:** 800 **Total cost:** \$15,000,000

Total annual operating costs: \$1,389,500

(addition only)

Category: New, ancillary building Facility type: State prison

Building configuration: Wheel, spoke or

radial (modified)

#### **Costs**

Total: \$15,000,000

Building only: \$15,000,000 Housing area: \$15,000,000 Housing per inmate: \$20,000 Housing per cell: \$20,000 Total per inmate: \$18,750 Total per GSF: \$94.33

Total annual operating costs: \$1,389,500

(addition only)

#### **Security**

Perimeter: Double fence; razor wire on

and between fences; towers

Inmate security level:
Maximum: 4%
Medium: 96%
Minimum: 0

#### **Dimensions**

Gross square feet/corrections: 159,020

Gross square feet/other: 0 Gross square feet/total: 159,020 Housing area square feet: 159,020 Gross square feet per inmate: 199 Size of cells: 80 square feet (single) Net/gross square feet: Unknown

#### **Construction type**

Structural: Masonry bearing with roof rafters; 5/8" GWB finish ceiling and

fiberglass

Exterior walls: CMU block; redwood siding over insulation secured to CMU

Interior walls: CMU block

Exterior surface/facade: Diagonal redwood

siding

#### Inmate design capacity

Single occupancy: 750 Double occupancy: 0

Dorms: 0

Special housing: 50 General population: 750

Total: 800

#### **Inmate cells**

Doors/material: Steel

Doors/type: Swinging; sliding

Doors/locking: Remote locking; manual

locking

Floor surface: Vinyl tile

Intercom: One-way to cells and common

areas

HVAC: Air conditioning; heating/air circulation; gas heat; hot water heating and tempered air handling equipment for makeup air

Plumbing: China Furniture: Vinyl/plastic

Fire protection: Smoke detectors for common areas; manual alarm stations

## Current staff

Full-time equivalent:
Administration: 11
Security: 27

Programs/treatment: 4 Maintenance: 6

Total: 48

Current inmate/staff ratio: 19.96:1

## **Inmate housing areas**

Design: Linear, outside Cells per unit: 50 Inmates per unit: 50

Management type: Remote surveillance

June 1986 population: 958

Facility commitment: State prisoners Means to handle crowding: Bunk beds

### **Construction process**

Finance method: G.O. Bonds; State funds Contract method: Conventional Use of inmate labor: None Use of prefabrication: None

#### Architect's reported analyses

Factors affecting construction costs:
Positive: Simple construction methods,
repetitiveness of design; less expensive
materials and hardware; builder's
hardware used in medium security;
excellent contracts and good construction documents

Negative: High labor costs Factors affecting time schedule:

Positive: Simple construction methods,

repetitiveness of design Negative: Labor problems

Illin	ois
Can	tralia

### Cook County Medical and Psychiatric Facility—RTU Building (Addition)

Jurisdiction official: James O'Grady, Sheriff

Contact: Tom Moynahan, Executive Director, Cook County Medical and Psychiatric Facility—RTU Building, 2700 South California

Avenue, Chicago, IL 60608, 312-890-6876

Architect: Michael R. Eiben AIA, 79 West Monroe Street, Chicago, IL 60603, 312-782-9562

Construction manager: None

**Groundbreaking:** June 1984

Finish date: May 1985

**Construction time:** 11 months

**Design capacity:** 524 **Total cost:** \$5,900,000

Total annual operating costs: N/A

(addition)

Category: New, ancillary building
Facility type: County jail, medical and
psychiatric treatment facility
Building configuration: Integrated

structure; ladder, telephone pole

Costs

Total: \$5,900,000

Building only: \$4,450,000 Housing area: \$3,200,000 Housing per inmate: \$6,107 Housing per cell: \$152,381 Total per inmate: \$11,260

Total per GSF: \$75.64

Total annual operating costs: N/A

(addition)

**Security** 

Perimeter: Double fence; razor wire on and between fences; towers; patrols

Inmate security level:

Maximum: 0 Medium: 1% Minimum: 99%

**Inmate cells** 

Doors/material: Steel Doors/type: Swinging

Doors/locking: Manual locking

Floor surface: Epoxy coating; vinyl tile;

rubber tile

Intercom: Two-way to all areas HVAC: Air conditioning; steam heat

Plumbing: Stainless steel Furniture: Steel; vinyl/plastic

Fire protection: Smoke detectors and sprinklers for cells and common areas;

manual alarm stations

**Dimensions** 

Gross square feet/corrections: 78,000

Gross square feet/other: 0 Gross square feet/total: 78,000 Housing area square feet: 54,600 Gross square feet per inmate: 149 Size of cells: 90 square feet (single);

3,000 (dorm)

Net/gross square feet: 96%

Design: Dorms off linear support core

**Inmate housing areas** 

Cells per unit: 1 Inmates per unit: 30

Management type: Direct supervision

March 1987 population: 456

Facility commitment: Local jail inmates;

State prisoners

Means to handle crowding: Unknown

**Construction type** 

Structural: Steel frame Exterior walls: Brick

Interior walls: CMU block; metal panels

Exterior surface/facade: Brick

Inmate design capacity

Single occupancy: 4 Double occupancy: 0 Dorms: 520

Special housing: 0 General population: 524

Total: 524

**Current staff** 

Full-time equivalent: Administration: 1 Security: 175

Programs/treatment: 41

Maintenance: 1 Total: 218

Current inmate/staff ratio: 2.09:1

Finance method: G.O. Bonds

**Construction process** 

Contract method: Conventional Use of inmate labor: None

Use of prefabrication: Interior wall panels

Architect's reported analyses

Factors affecting construction costs:
Positive: Simple const. methods; favorable market; less expensive materials


and hardware; dorm design

Negative: High labor costs; difficult site conditions; government procedures, regulations; complex electronic and electrical systems; local building codes

Factors affecting time schedule: Positive: Use of prefab. components, factory assembly; simple const. methods; \$2000 per day penalty for

contractor delay

Negative: Government procedures, regulations; complex electronic and electrical systems; local building codes



#### **Danville Correctional Center**

Jurisdiction official: Michael P. Lane, Director, Department of Corrections

Contact: John Russian, Chief Engineer, Danville Correctional Center, Route 136 East, Danville, IL 61832, 217-446-0441

Architect: Salogga, Bradley, Likins, Dillow, 100 Merchant Street, Decatur, IL 62523, 217–429–5105

Construction manager: None

Groundbreaking: July 1983 Finish date: September 1985 Construction time: 26 months

Design capacity: 941 Total cost: \$33,120,000 Total annual operating costs:

\$9,363,200

Category: New, independent facility

Facility type: State prison

Building configuration: Campus style

#### **Costs**

Total: \$33,120,000

Building only: \$29,975,000 Housing area: \$15,450,000 Housing per inmate: \$16,685 Housing per cell: \$16,685 Total per inmate: \$35,197 Total per GSF: \$90.85

Total annual operating costs: \$9,363,200

#### **Dimensions**

Gross square feet/corrections: 364,575

Gross square feet/other: 0 Gross square feet/total: 364,575 Housing area square feet: 163,400 Gross square feet per inmate: 387 Size of cells: 70 square feet (single)

Net/gross square feet: 92%

#### **Inmate housing areas**

Design: Module/pod Cells per unit: 54 Inmates per unit: 54

Management type: Remote surveillance

March 1986 population: 866

Facility commitment: State prisoners Means to handle crowding: Mattresses on floor; beds in dayroom; bunks in gym

#### **Security**

Perimeter: Double fence; alarm/detection systems; razor wire on and between

fences; towers Inmate security level: Maximum: 0 Medium: 100% Minimum: 0

#### **Construction type**

Structural: Load bearing precast panels; steel frame

Exterior walls: CMU block, textured face

Interior walls: CMU block

Exterior surface/facade: Stain and sealer

#### **Construction process**

Finance method: G.O. Bonds; State funds Contract method: Conventional Use of inmate labor: None

Use of prefabrication: Moderate; precast concrete floor and ceiling unit;

preengineered frame

#### **Inmate cells**

Doors/material: Steel Doors/type: Swinging

Doors/locking: Remote and manual

locking

Floor surface: Vinyl tile

Intercom: Call button from cell to control

room

HVAC: Heating/air circulation only

Plumbing: Stainless steel

Furniture: Wood

Fire protection: Smoke detectors for

common areas

#### Inmate design capacity

Single occupancy: 926 Double occupancy: 0

Dorms: 0

Special housing: 15 General population: 926

Total: 941

# Architect's reported analyses

Factors affecting construction costs: Positive: Simple construction methods, repetitiveness of design; good competition, favorable market

Negative: None

Factors affecting time schedule:
Positive: Simple construction methods,
repetitiveness of design; phased
construction, fast track construction
management

Negative: Weather problems


#### **Current staff**

Full-time equivalent: Administration: 43 Security: 200

Programs/treatment: 23 Maintenance: 22

Total: 288

Current inmate/staff ratio: 3.0:1



#### **Dixon Correctional Center (Addition)**

Jurisdiction official: Michael P. Lane, Director, Department of Corrections

Contact: Warden Richard Gramley, Dixon Correctional Center, 2600 North Brinton Avenue, P.O. Box 768, Dixon, IL 61021,

815-288-5561

Architect: Turner-Witt Associates, Inc., 970 East Court Street, Kankakee, IL 60901, 815-933-5529

Construction manager: None

Groundbreaking: August 1983 Finish date: December 1984 Construction time: 16 months Design capacity: 50 Total cost: \$1,152,303 Total annual operating costs:

\$15,247,100 (entire facility)

Category: New, ancillary building

Facility type: State prison

**Building configuration:** Campus style

#### **Costs**

Total: \$1,152,303

Building only: \$1,152,303 Housing area: \$1,152,303 Housing per inmate: N/A Housing per cell: N/A Total per inmate: \$23,046 Total per GSF: \$118.43

Total annual operating costs: \$15,247,100

(entire facility)

#### **Security**

Perimeter: Double fence; alarm/detection systems; razor wire on and between fences; towers; patrols; camera

surveillance

Inmate security level:
Maximum: 100%
Medium: 0
Minimum: 0

#### **Inmate cells**

Doors/material: Steel

Doors/type: Swinging; sliding

Doors/locking: Motor driven and remote

locking; remote locking Floor surface: Vinyl tile

Intercom: One-way to cells and common

areas

HVAC: Air conditioning; heating/air circulation; steam heat; steam to hot water and makeup tempered air han-

dling units

Plumbing: Stainless combination unit

Furniture: Steel

Fire protection: Smoke detectors for cells and common areas; manual alarm

stations

#### **Dimensions**

Gross square feet/corrections: 9,730

Gross square feet/other: 0
Gross square feet/total: 9,730
Housing area square feet: 9,730
Gross square feet per inmate: 195
Size of cells: 85 square feet (spec. single)

Net/gross square feet: Unknown

#### **Construction type**

Structural: Masonry bearing
Exterior walls: CMU block; brick
Interior walls: CMU block

Exterior surface/facade: Brick

#### Inmate design capacity

Single occupancy: 0 Double occupancy: 0

Dorms: 0

Special housing: 50 General population: 0

Total: 50

#### Current staff

Full-time equivalent: Administration: 34 Security: 361

Programs/treatment: 36 Maintenance: 30

Total: 461 (entire facility)
Current inmate/staff ratio: 1.92:1

#### **Inmate housing areas**

Design: Linear, outside Cells per unit: 50 Inmates per unit: 50

Management type: Remote surveillance April 1987 population: 885 (entire

facility)

Facility commitment: State prisoners Means to handle crowding: Bunk beds

#### **Construction process**

Finance method: G.O. Bonds; State funds Contract method: Conventional Use of inmate labor: None Use of prefabrication: None

#### Architect's reported analyses

Factors affecting construction costs: Positive: Good competition, favorable market; less expensive materials and hardware


Negative: Slow construction, lengthy building time; high labor costs

Factors affecting time schedule:

Positive: Simple construction methods, repetitiveness of design; advanced order of materials and hardware; coordination of design between parties

Negative: Slow responses and delivery from vendors, suppliers; labor problems (strike); weather problems (extremely

cold early)



### **Douglas County Jail**

Jurisdiction official: Charles "Chub" Conner, Sheriff

Contact: Sheriff Charles "Chub" Conner, Douglas County Jail, P.O. Box 401, Route 36 and Washington Street, Tuscola, IL 61953,

217-253-3511

Architect: Polson Architects, Suite 220, 2701 Rockcreek Parkway North, Kansas City, MO 64117, 816-474-9909

Construction manager: None

**Groundbreaking:** April 1984

Finish date: May 1986

**Construction time:** 13 months

**Design capacity:** 20 **Total cost:** \$2,100,000

Total annual operating costs: \$128,000

Category: New, independent facility Facility type: Complex: county jail, law

enforcement, courts

Building configuration: Integrated

structure

#### **Costs**

Total: \$2,100,000

Building only: \$2,050,000

Housing area: Unknown Housing per inmate: Unknown Housing per cell: Unknown

Total per inmate: N/A (complex)

Perimeter: Building exterior only

Total per GSF: \$150.49

Total annual operating costs: \$128,000

# Dimensions

Gross square feet/corrections: 7,825 Gross square feet/other: 6,129

Gross square feet/total: 13,954 Housing area square feet: 6,455

Gross square feet per inmate: 391 Size of cells: 70 square feet (single)

Net/gross square feet: 69%

#### **Construction type**

Structural: Wood frame; load-bearing

masonry

Exterior walls: Brick; limestone skirt; tile

roof

Interior walls: Precast panels; CMU block;

gypsum board on metal studs

Exterior surface/facade: Brick; limestone

skirt; tile roof

#### **Inmate cells**

Medium: 0

Minimum: 0

Security

Doors/material: Steel

Inmate security level:

Maximum: 100%

Doors/type: Sliding

Doors/locking: Manual locking; motor

driven and remote locking
Floor surface: Sealed concrete
Intercom: Two-way to cells
HVAC: Air conditioning; gas heat

Plumbing: Stainless steel

Furniture: Steel

Fire protection: Smoke detectors for cells and common areas; sprinklers for common areas; manual alarm stations

#### Inmate design capacity

Single occupancy: 18 Double occupancy: 0

Dorms: 0

Special housing: 2 General population: 18

Total: 20

#### **Current staff**

Full-time equivalent: Administration: 2

Security: 4

Programs/treatment: 2 Maintenance: 3

Total: 11

Current inmate/staff ratio: 1.45:1

#### **Inmate housing areas**

Design: Linear, inside; direct light into

cells

Cells per unit: 20 Inmates per unit: 20

Management type: Intermittent

surveillance

October 1987 population: 16

Facility commitment: Local jail inmates Means to handle crowding: Bunk beds in

exercise room

#### **Construction process**

Finance method: Revenue sharing; local

funds

Contract method: Conventional Use of inmate labor: None

Use of prefabrication: Limited; prefabricated wood roof trusses, precast

concrete planks

#### Architect's reported analyses

Factors affecting construction costs: Positive: Good competition, favorable

market; design effort

Negative: Complex electronic, mechani-

cal, and electrical systems


Factors affecting time schedule:

Positive: Simple construction methods,

repetitiveness of design

Negative: Slow responses and delivery from vendors, suppliers; labor problems

(strike); five prime contracts



### **DuPage County Jail and Sheriff's Department**

Jurisdiction official: Richard P. Doria, Sheriff

Contact: Sheriff Richard P. Doria, DuPage County Jail and Sheriff's Department, 501 North County Farm Road, Wheaton, IL

60187, 312-682-7256

Architect: Patrick + Associates, Inc., 199 South Fifth Street, Columbus, OH 43215, 614–228–3233

Construction manager: None

**Groundbreaking:** May 1981 Finish date: March 1983 Construction time: 22 months Design capacity: 354 **Total cost:** \$14,059,500

Total annual operating costs: N/A

(complex)

Category: New, independent facility Facility type: Complex: county jail, law

enforcement

**Building configuration:** Integrated

structure

#### Costs

Total: \$14,059,500

Building only: \$13,459,500 Housing area: \$8,015,606 Housing per inmate: \$25,366 Housing per cell: \$40,688

Total per inmate: N/A (complex)

Total per GSF: \$92.10

Total annual operating costs: N/A

(complex)

#### Security

Perimeter: Single fence; video camera

surveillance Inmate security level: Maximum: 50%

Medium: 50% Minimum: 0

#### **Inmate cells**

Doors/material: Steel

Doors/type: Sliding, swinging

Doors/locking: Motor driven and remote locking; remote locking only Floor surface: Sealed concrete Intercom: One way to common areas HVAC: Heating/air circulation only Plumbing: Stainless combination unit

Furniture: Steel

Fire protection: Smoke detectors and sprinklers for common areas

#### **Dimensions**

Gross square feet/corrections: 121,318 Gross square feet/other: 31,337 Gross square feet/total: 152,655 Housing area square feet: 37,569 Gross square feet per inmate: 343 Size of cells: 60 square feet (single)

Net/gross square feet: 65%

#### **Construction type**

Structural: Cast-in-place concrete frame Exterior walls: Cast-in-place concrete;

brick

Interior walls: Cast-in-place concrete;

CMU block

Exterior surface/facade: Brick

#### Inmate design capacity

Single occupancy: 194 Double occupancy: 0

Dorms: 122

Special housing: 38 General population: 316

Total: 354

#### **Current staff**

Full-time equivalent: Administration: 7 Security: 76

> Programs/treatment: 6 Maintenance: 5

Total: 94

Current inmate/staff ratio: 3.03:1

#### **Inmate housing areas**

Design: Linear, outside Cells per unit: 8 to 10 Inmates per unit: 8 to 20

Management type: Intermittent and

remote surveillance

October 1985 population: 285

Facility commitment: Local jail inmates Means to handle crowding: Bunk beds

in cell; mattresses on floor

#### **Construction process**

Finance method: G.O. Bonds; State funds Contract method: Conventional Use of inmate labor: None Use of prefabrication: Detention

equipment items

#### Architect's reported analyses


Factors affecting construction costs: Positive: Use of prefabricated components; repetitiveness of design in housing areas; favorable market; less expensive materials and hardware

Negative: High security level construction; cast-in-place concrete frame

Factors affecting time schedule: Positive: Use of prefab.; repetitiveness of

housing areas; advanced order of materials and hardware; coordination of design between parties

Negative: Slow responses from vendors; labor and weather problems; government "red tape"; complex electronic, mechanical, and electrical systems; CIP concrete



### **Dwight Correctional Center (1979 Addition)**

Jurisdiction official: Michael P. Lane, Director, Department of Corrections

Contact: Warden Jane Huch, Dwight Correctional Center, P.O. Box 5001, Dwight, IL 60420-5001, 815-584-2806

Architect: Turner-Witt Associates, Inc., 970 East Court Street, Kankakee, IL 60901, 815-933-5529

Construction manager: None

**Groundbreaking:** April 1978 Finish date: May 1979

Construction time: 13 months

Design capacity: 100 **Total cost:** \$1,241,079

Total annual operating costs: \$1,176,700

(addition only)

**Dimensions** 

Category: New, ancillary building Facility type: State prison (women's

**Building configuration:** Wheel, spoke or

radial (modified)

#### Costs

Total: \$1,241,079

Building only: \$1,107,194 Housing area: \$1,107,194 Housing per inmate: \$22,144 Housing per cell: \$22,144 Total per inmate: \$12,411 Total per GSF: \$71.92

Total annual operating costs: \$1,176,700

Perimeter: Single fence; double fence;

razor wire on and between fences

(addition only)

Inmate security level:

Maximum: 50% Medium: 50% Minimum: 0

Security

Gross square feet/corrections: 17,256

Gross square feet/other: 0 Gross square feet/total: 17,256 Housing area square feet: 17,256 Gross square feet per inmate: 173 Size of cells: 72 square feet (single) Net/gross square feet: Unknown

#### **Construction type**

Structural: Masonry bearing with wood

Interior walls: CMU block Exterior surface/facade: Brick

#### **Inmate cells**

Doors/material: Steel Doors/type: Swinging

Doors/locking: Remote locking Floor surface: Carpet; vinyl tile

Intercom: Two-way to cells; one-way to

common areas

HVAC: Air conditioning; heating/air circulation; gas heat; hot water heating with gas fuel tempered air handling for

makeup air

Plumbing: China; stainless combination

unit

Furniture: Steel; wood; vinyl/plastic Fire protection: Smoke detectors for cells and common areas; manual alarm

stations

rafters and 11/2" gypsum plaster ceiling Exterior walls: CMU block; brick

#### Inmate design capacity

Single occupancy: 50 Double occupancy: 0

Dorms: 0

Special housing: 50 General population: 50

Total: 100

#### **Current staff**

Full-time equivalent:

Administration: Unknown

Security: Unknown

Programs/treatment: Unknown Maintenance: Unknown

Total: Unknown

Current inmate/staff ratio: Unknown

#### **Inmate housing areas**

Design: Linear, outside Cells per unit: 50 Inmates per unit: 50

Management type: Remote surveillance

April 1987 population: 100

Facility commitment: Female State

prisoners

Means to handle crowding: Bunk beds

#### **Construction process**

Finance method: G.O. Bonds; State funds Contract method: Conventional

Use of inmate labor: None Use of prefabrication: None

#### Architect's reported analyses

Factors affecting construction costs: Positive: Simple construction methods, repetitiveness of design; good competition, favorable market; less expensive

materials and hardware

Negative: None

Factors affecting time schedule:

Positive: Simple construction methods,

repetitiveness of design

Negative: None

Dwight

### **Dwight Correctional Center (1984 Addition)**

Jurisdiction official: Michael P. Lane, Director, Department of Corrections

Contact: Warden Jane Huch, Dwight Correctional Center, P.O. Box 5001, Dwight, IL 60420-5001, 815-584-2806

Architect: Turner-Witt Associates, Inc., 970 East Court Street, Kankakee, IL 60901, 815-933-5529

Construction manager: None

**Groundbreaking:** March 1984 **Finish date:** December 1984

Construction time: 9 months

**Design capacity:** 96 **Total cost:** \$3,120,935

Total annual operating costs: \$1,366,800

(addition only)

Category: New, ancillary building Facility type: State prison (women's

facility)

Building configuration: Wheel, spoke or

radial (modified)

#### Costs

Total: \$3,120,935

Building only: \$2,817,325 Housing area: \$2,817,325 Housing per inmate: \$56,347 Housing per cell: \$56,347 Total per inmate: \$32,510 Total per GSF: \$143.24

Total annual operating costs: \$1,366,800

(addition only)

#### **Security**

Perimeter: Single fence; double fence; razor wire on and between fences

Inmate security level:
Maximum: 51%
Medium: 49%
Minimum: 0

### Inmate cells

Doors/material: Steel Doors/type: Swinging

Doors/locking: Remote locking

Floor surface: Carpet; vinyl tile; terrazzo Intercom: Two-way to cells; one-way to

common areas

HVAC: Air conditioning; heating/air circulation; hot water heating with gas fuel tempered air handling for makeup

air

Plumbing: China; stainless combination

unit

Furniture: Steel; wood; vinyl/plastic Fire protection: Smoke detectors for cells and common areas; manual alarm

stations

#### **Dimensions**

Gross square feet/corrections: 21,788

Gross square feet/other: 0 Gross square feet/total: 21,788 Housing area square feet: 21,788 Gross square feet per inmate: 227 Size of cells: 63.5 (gen. single);

85.3 (spec. single)

Net/gross square feet: Unknown

#### **Construction type**

Structural: Masonry bearing with wood rafters and 1½" gypsum plaster ceiling

Exterior walls: CMU block; brick Interior walls: CMU block Exterior surface/facade: Brick

#### Inmate design capacity

Single occupancy: 50 Double occupancy: 0

Dorms: 0

Special housing: 46 General population: 50

Total: 96

#### **Current staff**

Full-time equivalent:

Administration: Unknown

Security: Unknown

Programs/treatment: Unknown Maintenance: Unknown

Total: Unknown

Current inmate/staff ratio: Unknown

#### **Inmate housing areas**

Design: Linear, outside Cells per unit: Unknown Inmates per unit: 50

Management type: Remote surveillance

April 1987 population: 96

Facility commitment: Female State

prisoners

Means to handle crowding: Bunk beds

#### **Construction process**

Finance method: G.O. Bonds; State funds

Contract method: Conventional Use of inmate labor: None

Use of prefabrication: Limited; precut


roof system

#### Architect's reported analyses

Factors affecting construction costs:
Positive: Prefabricated components;
reduced construction time in field;
simple construction methods; favorable
market; less expensive materials and
hardware; well qualified and organized
contractor; quality of construction
documents

Negative: None

Factors affecting time schedule:
Positive: Simple construction methods;
coordination of design; contractor
incentives and organized contractors
Negative: Early spring rains caused initial
delay (contractor caught up later)



#### **East Moline Correctional Center (Addition)**

Jurisdiction official: Michael P. Lane, Director, Department of Corrections

Contact: Warden Odie Washington, East Moline Correctional Center, 100 Hillcrest Road, East Moline, IL 61244, 309-755-4511

Architect: Turner-Witt Associates, Inc., 970 East Court Street, Kankakee, IL 60901, 815-933-5529

Construction manager: None

**Groundbreaking:** October 1982

Finish date: May 1984

Construction time: 19 months

Design capacity: 200 **Total cost:** \$4,225,999

Total annual operating costs: \$3,135,000

(addition only)

Category: New, ancillary building

Facility type: State prison Building configuration: High rise;

wheel, spoke or radial (modified)

#### **Costs**

Total: \$4,225,999

Building only: \$4,225,999 Housing area: \$4,225,999 Housing per inmate: \$21,130 Housing per cell: \$21,130

Total per inmate: \$21,130 Total per GSF: \$83.29

Total annual operating costs: \$3,135,000

(addition only)

#### Security

Perimeter: Single fence; razor wire on

fence

Inmate security level: Maximum: 3% Medium: 0 Minimum: 97%

**Inmate cells** 

davrooms

Plumbing: China

stations

areas

Doors/material: Steel

Doors/type: Swinging

Doors/locking: Remote locking

circulation; steam heat

Furniture: Vinyl/plastic

Floor surface: Vinyl tile; terrazzo in

HVAC: Air conditioning; heating/air

Fire protection: Smoke detectors for cells

and common areas; manual alarm

Intercom: One-way to cells and common

# **Dimensions**

Gross square feet/corrections: 50,736

Gross square feet/other: 0 Gross square feet/total: 50,736 Housing area square feet: 50,736 Gross square feet per inmate: 254 Size of cells: 80 square feet (single) Net/gross square feet: Unknown

# Construction type

Structural: Masonry bearing precast

concrete floor slabs

Exterior walls: CMU block; brick Interior walls: CMU block Exterior surface/facade: Brick

#### **Inmate design capacity**

Single occupancy: 200

Special housing: 0

Total: 200

Double occupancy: 0

Dorms: 0

General population: 200

#### **Current staff**

Full-time equivalent: Administration: 27 Security: 214

Programs/treatment: 20

Maintenance: 46

Total: 307 (entire facility)

Current inmate/staff ratio: Unknown

#### **Inmate housing areas**

Design: Module/pod (modified) Cells per unit: Unknown Inmates per unit: Unknown

Management type: Remote surveillance

April 1987 population: 200

Facility commitment: State prisoners Means to handle crowding: Added beds

#### **Construction process**

Finance method: G.O. Bonds; State funds

Contract method: Conventional Use of inmate labor: None

Use of prefabrication: Moderate; precast structural concrete floor deck

#### Architect's reported analyses

Factors affecting construction costs: Positive: Prefabricated components, factory assembly; simple construction methods, repetitiveness of design; good competition, favorable market Negative: High labor costs; difficult site


conditions

Factors affecting time schedule: Positive: Simple construction methods, repetitiveness of design; coordination of design between parties

Negative: Slow responses and delivery from vendors suppliers; finish roofing

material supplier

# NIJ/National Directory of Corrections Construction



#### **Graham Correctional Center (Addition)**

Jurisdiction official: Michael P. Lane, Director, Department of Corrections

Contact: Warden Alethea T. Camp, Graham Correctional Center, P.O. Box 499, Hillsboro, IL 62049, 217-532-6961

Architect: Turner-Witt Associates, Inc., 970 East Court Street, Kankakee, IL 60901, 815-933-5529

Construction manager: None

**Groundbreaking:** October 1979 Finish date: October 1981 Construction time: 24 months

Design capacity: 786 **Total cost:** \$15,000,000

Total annual operating costs: \$1,388,200

(addition only)

Category: New, ancillary building Facility type: State prison

Building configuration: Wheel, spoke or

radial (modified)

#### Costs

Total: \$15,000,000

Building only: \$15,000,000 Housing area: \$15,000,000 Housing per inmate: \$20,000 Housing per cell: \$20,000 Total per inmate: \$19,084 Total per GSF: \$94.33

Total annual operating costs: \$1,388,200

(addition only)

#### Security

Perimeter: Double fence; razor wire on and between fences; towers

Inmate security level: Maximum: 4% Medium: 96%

# **Inmate cells**

Minimum: 0

Doors/material: Steel

Doors/type: Swinging; sliding

Doors/locking: Remote locking; manual

locking

Floor surface: Vinyl tile

Intercom: One-way to cells and common

HVAC: Air conditioning; heating/air circulation; gas heat; hot water heating and tempered air handling equipment for makeup air

Plumbing: China Furniture: Vinyl/plastic

Fire protection: Smoke detectors for common areas; manual alarm stations

#### **Dimensions**

Gross square feet/corrections: 159,020

Gross square feet/other: 0 Gross square feet/total: 159,020 Housing area square feet: Unknown Gross square feet per inmate: 202 Size of cells: 80 square feet (single) Net/gross square feet: Unknown

#### Construction type

Structural: Masonry bearing with roof rafters; 5/8" GWB finish ceiling and

fiberglass

Exterior walls: CMU block; redwood siding over insulation secured to CMU

Interior walls: CMU block

Exterior surface/facade: Diagonal redwood

siding

#### Inmate design capacity

Single occupancy: 750 Double occupancy: 0

Dorms: 0

Special housing: 36 General population: 750

Total: 786

#### **Current staff**

Full-time equivalent: Administration: 34 Security: 361

Programs/treatment: 30 Maintenance: 36

Total: 461

Current inmate/staff ratio: 2.20:1

#### **Inmate housing areas**

Design: Linear, outside Cells per unit: 50 Inmates per unit: 50

Management type: Remote surveillance

April 1987 population: 1,015

Facility commitment: State prisoners Means to handle crowding: Bunk beds

#### **Construction process**

Finance method: State funds Contract method: Conventional Use of inmate labor: None Use of prefabrication: None

#### Architect's reported analyses

Factors affecting construction costs: Positive: Simple construction methods, repetitiveness of design; less expensive materials and hardware; builder's hardware used for medium security; good competition, favorable market Negative: High labor costs; large number

of contracts

Factors affecting time schedule:

Positive: Simple construction methods,

repetitiveness of design Negative: Labor problems



### Illinois Youth Center—Kankakee (Dining Facility) (Addition)

Jurisdiction official: Michael P. Lane, Director, Department of Corrections

Contact: Superintendent Dennis R. Cooper, Illinois Youth Center—Kankakee, RR1 Box 190, Manteno, IL 60950, 815-476-5201

Architect: Turner-Witt Associates, Inc., 970 East Court Street, Kankakee, IL 60901, 815-933-5529

Construction manager: None

**Groundbreaking:** October 1980

Finish date: April 1981 Construction time: 6 months **Design capacity:** N/A **Total cost:** \$426,906

Total annual operating costs: \$1,475,100

(entire facility)

Category: New, ancillary building Facility type: Juvenile correctional facility (dining room/kitchen)

Building configuration: Wheel, spoke or

radial (modified)

Costs

Total: \$426,906

**Building only: \$426,906** 

Housing area: N/A Housing per inmate: N/A Housing per cell: N/A

Total per inmate: N/A Total per GSF: \$90.31

Total annual operating costs: \$1,475,000

(entire facility)

Security

Perimeter: Building exterior only

Inmate security level:
Maximum: 4%
Medium: 0
Minimum: 96%

Inmate cells (No inmate cells)

Doors/material: N/A Doors/type: N/A Doors/locking: N/A Floor surface: N/A Intercom: N/A HVAC: N/A Plumbing: N/A Furniture: N/A

Fire protection: N/A

**Dimensions** 

Gross square feet/corrections: 4,727 Gross square feet/other: 0 Gross square feet/total: 4,727

Housing area square feet: N/A Gross square feet per inmate: N/A

Size of cells: N/A

Net/gross square feet: 82%

**Construction type** 

Structural: Unknown

Exterior walls: CMU block; brick Interior walls: CMU block Exterior surface/facade: Brick

Inmate design capacity

Single occupancy: N/A Double occupancy: N/A

Dorms: N/A

Special housing: N/A
General population: N/A
Total: N/A (support services)

Current staff

Full-time equivalent: Administration: 12 Security: 21

Programs/treatment: 6
Maintenance: 4

Total: 43

Current inmate/staff ratio: N/A

**Inmate housing areas** 

Design: N/A
Cells per unit: N/A
Inmates per unit: N/A
Management type: N/A
Current population: N/A

Facility commitment: Juveniles Means to handle crowding: N/A

**Construction process** 

Finance method: G.O. Bonds; State funds

Contract method: Conventional Use of inmate labor: None Use of prefabrication: None

Architect's reported analyses

Factors affecting construction costs: Positive: Simple construction methods, repetitiveness of design; less expensive

materials and hardware

Negative: None

Factors affecting time schedule: Positive: Simple construction methods, repetitiveness of design; coordination

of design between parties

Negative: None

Illin	ois
Mor	stano

### Illinois Youth Center—Kankakee (Housing Unit) (Addition)

Jurisdiction official: Michael P. Lane, Director, Department of Corrections

Contact: Superintendent Dennis R. Cooper, Illinois Youth Center—Kankakee, RR1 Box 190, Manteno, IL 60950, 815-476-5201

Architect: Turner-Witt Associates, Inc., 970 East Court Street, Kankakee, IL 60901, 815–933–5529

Construction manager: None

Groundbreaking: October 1979 Finish date: November 1980 Construction time: 13 months **Design capacity:** 50 **Total cost:** \$905,313

Total annual operating costs: \$1,475,100

(entire facility)

Category: New, ancillary building Facility type: Juvenile correctional

**Inmate housing areas** 

Inmates per unit: Unknown

Facility commitment: Juveniles

cell; mattresses on floor

**Construction process** 

Use of inmate labor: None

Use of prefabrication: None

Contract method: Conventional

May 1987 population: 60

Design: Linear, outside

Cells per unit: 50

facility

Building configuration: Wheel, spoke or

Management type: Remote surveillance

Means to handle crowding: Bunk beds in

Finance method: G.O. Bonds; State funds

radial

#### Costs

Total: \$905,313 Building only: \$905,313 Housing area: \$905,313 Housing per inmate: \$18,106 Housing per cell: \$18,106

Total per inmate: \$18,106 Total per GSF: \$95.43

Total annual operating costs: \$1,475,100

(entire facility)

#### Security

Perimeter: Building exterior only

Inmate security level:
Maximum: 4%
Medium: 0
Minimum: 96%

#### **Dimensions**

Gross square feet/corrections: 9,487 Gross square feet/other: 0 Gross square feet/total: 9,487 Housing area square feet: 9,487 Gross square feet per inmate: 190 Size of cells: 70 square feet (single) Net/gross square feet: 37%

#### **Construction type**

Structural: Load-bearing wood rafters with GWB ceilings and fiberglass shingle Exterior walls: CMU block; brick

Interior walls: CMU block

Exterior surface/facade: Brick; combination brick and redwood siding

#### Inmate design capacity

Single occupancy: 50 Double occupancy: 0

Dorms: 0

Special housing: 0 General population: 50

Total: 50

# Architect's reported analyses

Factors affecting construction costs:
Positive: Simple construction methods,
repetitiveness of design; less
expensive materials and hardware

Negative: None

Factors affecting time schedule: Positive: Simple construction methods, repetitiveness of design; coordination

of design between parties

Negative: None

#### **Inmate cells**

Doors/material: Steel Doors/type: Swinging

Doors/locking: Remote locking; manual

locking

Floor surface: Unknown

Intercom: One-way to cells and common

areas

HVAC: Air conditioning; heating/air circulation; hot water heater with air handling units for tempered makeup

air; gas heat

Plumbing: Stainless combination unit

Furniture: Vinyl/plastic

Fire protection: Smoke detectors for cells

and common areas

#### **Current staff**

Full-time equivalent: Administration: 12 Security: 21

Programs/treatment: 4 Maintenance: 6

Total: 43

Current inmate/staff ratio: 1.4:1

### **Peoria County Adult Detention and Work Release Facility**

Jurisdiction official: George P. Shadid, Sheriff

Contact: John Maher, Jail Superintendent, Peoria County Adult Detention and Work Release Facility, 301 North Maxwell Road,

Peoria, IL 61604, 309-697-8515

Architects: LZT Associates, Inc., 124 S.W. Adams, Suite 450, Peoria, IL 61602, 309-673-3100

John Hackler and Company, Architects, 504 Fayette Street, Peoria, IL 61603, 309-676-6159

Construction manager: None

**Groundbreaking:** April 1983 **Finish date:** June 1985

Construction time: 26 months

**Design capacity:** 345 **Total cost:** \$12,500,000

Total annual operating costs: \$2,000,000

Category: New, independent facility Facility type: Complex: county jail, law

enforcement

Building configuration: Integrated

structure

Costs

Total: \$12,500,000

Building only: \$11,200,000

Housing area: Unknown

Housing per inmate: Unknown

Housing per cell: Unknown

Total per inmate: N/A (complex)

Total per GSF: \$97.66

Total annual operating costs: \$2,000,000

Security

Perimeter: Double fence; razor wire on

fences; video camera surveillance Inmate security level:

Maximum: 71%
Medium: 0
Minimum: 29%

**Inmate cells** 

Doors/material: Steel Doors/type: Swinging

Doors/locking: Remote locking Floor surface: Sealed concrete; vinyl tile,

carpet

Intercom: Two-way to common areas HVAC: Heating/air circulation; tempered air; sealed energy efficient boiler Plumbing: Stainless steel; stainless

combination unit Furniture: Stainless steel

Fire protection: Smoke detectors for cells

and common areas

**Dimensions** 

Gross square feet/corrections: 117,300 Gross square feet/other: 10,700 Gross square feet/total: 128,000 Housing area square feet: 48,800 Gross square feet per inmate: 340 Size of cells: 62 square feet (gen. single);

80 (spec. single)

Net/gross square feet: 69%

**Construction type** 

Structural: Steel frame; cast-in-place concrete frame; precast concrete frame;

double tees

Exterior walls: CMU block; brick Interior walls: CMU block; brick Exterior surface/facade: Brick; natural

wall

Inmate design capacity

Single occupancy: 222 Double occupancy: 0

Dorms: 0

Special housing: 123 General population: 222

Total: 345

**Current staff** 

Full-time equivalent:

Administration: Unknown Security: Unknown

Programs/treatment: Unknown

Maintenance: Unknown

Total: Unknown

Current inmate/staff ratio: Unknown

**Inmate housing areas** 

Design: Module/pod Cells per unit: Unknown Inmates per unit: Unknown

Management type: Remote surveillance

November 1987 population: 185

Facility commitment: Local jail inmates; State prisoners; Federal prisoners Means to handle crowding: Unknown

**Construction process** 

Finance method: Lease revenue bonds

Contract method: Conventional Use of inmate labor: None Use of prefabrication: None

Architects' reported analyses

Factors affecting construction costs: Positive: Simple construction methods;

good competition, favorable market Negative: Complex electronic and


mechanical systems

Factors affecting time schedule:

Positive: Repetitiveness of design; coordination of design between parties; excellent cooperation, specific scheduling, defined decision dates; good prep-

aration and public education

Negative: None



### **Rock Island County Jail**

Jurisdiction official: Gordon Powell, Sheriff

Contact: Lieutenant G. Jungwirth, Rock Island County Jail, P.O. Box 306, Rock Island, IL 61201, 309-794-1230

Architect: Phillips Swager Associates, 3622 North Knoxville Avenue, Peoria, IL 61603, 309-688-9511

Construction manager: None

**Groundbreaking:** July 1983 Finish date: August 1985 Construction time: 25 months Design capacity: 200 **Total cost:** \$7,566,000

Total annual operating costs: Unknown

Category: New, independent facility Facility type: Complex: county jail,

sheriff admin., court

**Inmate housing areas** 

October 1985 population: 145

**Construction process** 

Finance method: G.O. Bonds

Use of inmate labor: None

Use of prefabrication: None

Contract method: Conventional

Design: Module/pod

Inmates per unit: 16

Cells per unit: 16

Building configuration: Integrated

Management type: Remote surveillance

Facility commitment: Local jail inmates

Means to handle crowding: Unknown

structure

#### **Costs**

Total: \$7,566,000

Building only: \$7,450,000 Housing area: \$4,171,000 Housing per inmate: \$23,172 Housing per cell: \$29,793

Total per inmate: N/A (complex)

Perimeter: Building exterior only

Total per GSF: \$98.51

Inmate security level:

Maximum: 22%

Medium: 31%

**Inmate cells** 

Doors/material: Solid

Doors/type: Swinging

Floor surface: Terrazzo

Furniture: Steel; concrete

Minimum: 18% Other: 29%

Security

Total annual operating costs: Unknown

#### **Dimensions**

Gross square feet/corrections: 43,000 Gross square feet/other: 33,804 Gross square feet/total: 76,804 Housing area square feet: Unknown Gross square feet per inmate: 215 Size of cells: 70 square feet (single) Net/gross square feet: 56%

#### Construction type

Structural: Cast-in-place concrete frame Exterior walls: CMU block; architectural

Interior walls: Cast-in-place concrete;

CMU block: terrazzo

Exterior surface/facade: Textured concrete

block

precast

#### Inmate design capacity

Single occupancy: 128 Double occupancy: 0

Special housing: 20

Total: 200

Dorms: 44 Other: 8

General population: 180

#### **Current staff**

Full-time equivalent: Administration: 2 Security: 35

Programs/treatment: Volunteers

Maintenance: 8 Total: 45

Current inmate/staff ratio: 3.22:1

Factors affecting construction costs: Positive: Repetitiveness of cell block

Architect's reported analyses

design; CMU throughout; good

competition

Negative: Security glazing

Factors affecting time schedule: Positive: Simple construction methods,

repetitiveness of design; coordination of design between parties

Negative: Elevator—security

# sprinklers for common areas


Fire protection: Smoke detectors for cells;

Doors/locking: Remote locking only

Intercom: Two-way to cells and common

areas; one-way to common areas HVAC: Air conditioning; hot water heating

Plumbing: Stainless combination unit



#### **Shawnee Correctional Center (Addition)**

Jurisdiction official: Michael P. Lane, Director, Department of Corrections

Contact: Warden James H. Thieret, Shawnee Correctional Center, P.O. Box 400, Vienna, IL 62995, 618-658-8331

Architect: Phillips Swager Associates, 3622 North Knoxville Avenue, Peoria, IL 61603, 309-688-9511

Construction manager: None

**Groundbreaking:** November 1982 Finish date: February 1985 Construction time: 28 months

Design capacity: 926 **Total cost:** \$32,400,000 **Total annual operating costs:** \$14,796,200 (addition only)

Category: New, ancillary building Facility type: State prison; State vehicle

maintenance

**Inmate housing areas** 

October 1985 population: 901

Means to handle crowding: N/A

Design: Linear, outside

Cells per unit: 224

Inmates per unit: 224

Building configuration: Campus style

Management type: Remote surveillance

Facility commitment: State prisoners

#### Costs

Total: \$32,400,000 (inc. veh. main. area) Building only: \$27,000,000

Housing area: \$15,020,348 Housing per inmate: \$16,764 Housing per cell: \$16,764 Total per inmate: \$34,989 Total per GSF: \$88.35

Total annual operating costs: \$14,796,200

(addition only)

#### Security

Perimeter: Double fence; razor wire on and between fences; towers; patrols

Inmate security level: Maximum: 3% Medium: 97% Minimum: 0

#### **Dimensions**

Gross square feet/corrections: 359,723 Gross square feet/other: 7,000 Gross square feet/total: 366,723 Housing area square feet: 165,645 Gross square feet per inmate: 388 Size of cells: 71 square feet (single);

80 square feet (special) Net/gross square feet: 70%

#### Construction type

Structural: Steel frame

Exterior walls: Brick; metal panel above 8 foot brick wainscot Interior walls: CMU block

Exterior surface/facade: Brick; 8 foot brick wainscot and metal panel above

# Inmate design capacity

Single occupancy: 896 Double occupancy: 0

Special housing: 30 General population: 896

Dorms: 0

Total: 926

#### Current staff

Full-time equivalent: Administration: 55 Security: 351

Programs/treatment: 33 Maintenance: 34

Total: 473 (addition only) Current inmate/staff ratio: 1.90:1 Finance method: G.O. Bonds Contract method: Conventional Use of inmate labor: None Use of prefabrication: None

**Construction process** 

## Architect's reported analyses

Factors affecting construction costs: Positive: Simple construction methods: good competition, favorable market; less expensive materials and hardware Negative: Difficult site conditions

Factors affecting time schedule: Positive: Simple construction methods, repetitiveness of design; preengineered construction on support buildings Negative: Weather problems; vendor/ supplier problems

#### **Inmate cells**

Doors/material: Solid; hollow metal

Doors/type: Swinging

Doors/locking: Remote locking only

Floor surface: Sealed concrete Intercom: Two-way to common areas HVAC: Heating/air circulation only;


steam heating plant

Plumbing: Stainless combination unit

Furniture: Steel

Fire protection: Smoke detectors for cells and common areas; manual alarm

stations



### **Sheridan Correctional Center (Kitchen/Dining Facility) (Addition)**

Jurisdiction official: Michael P. Lane, Director, Department of Corrections

Contact: Warden George Welborn, Sheridan Correctional Center, Box 38, Sheridan, IL 60551, 815-496-2311

Architect: Turner-Witt Associates, Inc., 970 East Court Street, Kankakee, IL 60901, 815-933-5529

Construction manager: None

**Groundbreaking:** May 1982 Finish date: May 1983

Construction time: 12 months

Design capacity: N/A **Total cost:** \$2,088,303

Total annual operating costs: N/A

(addition)

Category: New, ancillary building Facility type: State prison (kitchen/dining

Building configuration: Unknown

#### Costs

Total: \$2,088,303 Building only: Unknown Housing area: N/A

Housing per inmate: N/A Housing per cell: N/A Total per inmate: N/A Total per GSF: \$109.08

Total annual operating costs: N/A

(addition)

#### **Security**

Perimeter: Double fence; alarm/detection systems; razor wire on and between

fences; towers Inmate security level: Maximum: 0 Medium: 100% Minimum: 0

#### **Inmate cells** (No inmate cells)

Doors/material: Steel Doors/type: Swinging Doors/locking: N/A Floor surface: Terrazzo

Intercom: N/A

HVAC: Heating/air circulation; hot water heating and air handling equipment Plumbing: Stainless steel; china Furniture: Food service and equipment Fire protection: Smoke detectors for common areas; manual alarm stations

#### **Dimensions**

Gross square feet/corrections: 19,144 Gross square feet/other: 0

Gross square feet/total: 19,144 Housing area square feet: N/A Gross square feet per inmate: N/A

Size of cells: N/A

Net/gross square feet: 82%

#### Construction type

Structural: Masonry bearing with heavy timber

Exterior walls: Brick; cedar siding Interior walls: CMU block; structural

glazed tile

Exterior surface/facade: Brick

#### Inmate design capacity

Single occupancy: N/A Double occupancy: N/A

Dorms: N/A

Special housing: N/A General population: N/A

Total: N/A

#### **Current staff**

Full-time equivalent:

Administration: Unknown

Security: Unknown

Programs/treatment: Unknown Maintenance: Unknown

Total: Unknown

Current inmate/staff ratio: Unknown

#### **Inmate housing areas**

Design: N/A Cells per unit: N/A Inmates per unit: N/A Management type: Unknown Current population: N/A

Facility commitment: State prisoners Means to handle crowding: Unknown

#### **Construction process**

Finance method: G.O. Bonds Contract method: Conventional Use of inmate labor: None

Use of prefabrication: Moderate; roof

construction


#### Architect's reported analyses

Factors affecting construction costs: Positive: Prefabricated components, factory assembly; good competition, favorable market; less expensive materials and hardware

Negative: None

Factors affecting time schedule: Positive: Use of prefabricated components, factory assembly; simple construction methods, repetitiveness of design; coordination of design between

parties Negative: None



# Sheridan Correctional Center (Medical/Security Services) (Addition/Remodel/Expansion)

Jurisdiction official: Michael P. Lane, Director, Department of Corrections

Contact: Warden George Welborn, Sheridan Correctional Center, Box 38, Sheridan, IL 60551, 815-496-2311

Architect: Turner-Witt Associates, Inc., 970 East Court Street, Kankakee, IL 60901, 815–933–5529

Construction manager: None

**Groundbreaking:** December 1982

Finish date: February 1984 Construction time: 14 months **Design capacity:** 10 **Total cost:** \$2,812,065

Total annual operating costs: N/A

(addition)

**Category:** New, ancillary building; remodel/renovation project; expansion

Facility type: State prison

Building configuration: Existing build-

ings and additions

**Costs** 

Total: \$2,812,065 Building only: Unknown

Housing area: Unknown

Housing per inmate: Unknown Housing per cell: Unknown

Total per inmate: N/A (remodel)

Total per GSF: \$100.18

Total annual operating costs: N/A

(addition)

Security

Perimeter: Double fence; alarm/detection systems; razor wire on and between

fences; towers
Inmate security level:
Maximum: 0
Modium: 100%

Medium: 100% Minimum: 0

**Inmate cells** 

Doors/material: Steel Doors/type: Swinging

Doors/locking: Remote locking

Floor surface: Carpet; sealed concrete;

vinyl tile

Intercom: Unknown

HVAC: Air conditioning; gas heat; hot water heat and tempered air handling

units

Plumbing: China Furniture: Vinyl/plastic

Fire protection: Smoke detectors for common areas; manual alarm stations

**Dimensions** 

Gross square feet/corrections: 28,070

Gross square feet/other: 0 Gross square feet/total: 28,070 Housing area square feet: Unknown Gross square feet per inmate: 2,807 Size of cells: 100 square feet (single); 158

(double)

Net/gross square feet: 82%

**Construction type** 

Structural: Steel frame Exterior walls: Brick Interior walls: CMU block Exterior surface/facade: Brick

Inmate design capacity

Single occupancy: 0 Double occupancy: 0

Dorms: 0

Special housing: 10 General population: 0

Total: 10

**Current staff** 

Full-time equivalent:

Administration: Unknown

Security: Unknown

Programs/treatment: Unknown

Maintenance: Unknown

Total: Unknown

Current inmate/staff ratio: Unknown

**Inmate housing areas** 

Design: Module/pod Cells per unit: Unknown Inmates per unit: Unknown

Management type: Remote surveillance

Current population: Unknown

Facility commitment: State prisoners Means to handle crowding: Unknown

**Construction process** 

Finance method: G.O. Bonds; State funds

Contract method: Conventional Use of inmate labor: None Use of prefabrication: None

Architect's reported analyses

Factors affecting construction costs: Positive: Simple construction methods repetitiveness of design; good competition, favorable market; less expensive

materials and hardware

Negative: None

Factors affecting time schedule: Positive: Simple construction methods,

repetitiveness of design; coordination

of design between parties

Negative: None

(No floorplan available at time of publication)

# Marion County Jail (Addition/Remodel)

Jurisdiction official: Joseph G. McAtee, Sheriff

Contact: Deputy Chief Jerry T. Cooper, Marion County Jail, 40 South Alabama Street, Indianapolis, IN 46204, 317-633-5181

Architect: McGuire & Shook Architects, 7440 North Shadeland Avenue, Indianapolis, IN 46250, 317–842–0000

Criminal justice consultants: Phillips Swager Associates, 3622 North Knoxville Avenue, Peoria, IL 61603, 309-688-9511

Construction manager: None

**Groundbreaking:** January 1983 Finish date: December 1985 Construction time: 36 months

Design capacity: 337 **Total cost:** \$18,000,000 Total annual operating costs: \$24,500,000 (entire facility)

Category: New, ancil. building; remodel Facility type: Complex: county jail, law enforcement, crime lab

Building configuration: High rise in

radial formation

Costs

Total: \$18,000,000

Building only: \$17,700,000 Housing area: \$12,240,000 Housing per inmate: \$18,092 Housing per cell: \$18,092

Total per inmate: N/A (complex)

Total per GSF: \$112.50

Total annual operating costs: \$24,500,000

(entire facility)

Security

Perimeter: Alarm detection systems; video camera surveillance

Inmate security level: Maximum: 0 Medium: 100% Minimum: 0

**Dimensions** 

Structural: Cast-in-place concrete frame

Gross square feet/corrections: 115,000

Gross square feet/other: 45,000

Gross square feet/total: 160,000

Gross square feet per inmate: 341

Size of cells: 77 square feet (single)

Housing area square feet: N/A

Net/gross square feet: 60%

Exterior walls: Brick Interior walls: CMU block Exterior surface/facade: Brick

**Inmate cells** 

Doors/material: Steel Doors/type: Swinging

Doors/locking: Remote locking only

Floor surface: Terrazzo

Intercom: Two-way to common areas

HVAC: Air conditioning

Plumbing: Stainless combination unit

Furniture: Steel

Fire protection: Smoke detectors and sprinklers for common areas Construction type

Inmate design capacity

Single occupancy: 325 Double occupancy: 0

Dorms: 0

Special housing: 12 General population: 325

Total: 337

**Current staff** 

Full-time equivalent: Administration: N/A

Security: 27

Programs/treatment: N/A

Maintenance: 10

Total: 37 (addition only) Current inmate/staff ratio: 8.0:1 **Inmate housing areas** 

Design: Module/pod Cells per unit: 16, 20, 26 Inmates per unit: 16, 20, 26

Management type: Remote surveillance

July 1987 population: 296

Facility commitment: Local jail inmates

Means to handle crowding: N/A

**Construction process** 

Finance method: G.O. Bonds Contract method: Conventional Use of inmate labor: None Use of prefabrication: None

Architect's reported analyses

Factors affecting construction costs: Positive: Simple construction methods, repetitiveness of design; good competition, favorable market


Negative: None

Factors affecting time schedule:

Positive: Simple construction methods,

repetitiveness of design

Negative: None



Jurisdiction official: Bob E. Rice, Sheriff

Contact: Floyd Jones, Chief Jailer, Polk County Jail, 110 6th Avenue, Des Moines, IA 50309, 515-286-3804 Architect: FEH Associates, Inc., 1115 Midland Financial Building, Des Moines, IA 50309, 515-283-2479

Construction manager: None

**Groundbreaking:** April 1981 Finish date: December 1983 Construction time: 32 months Design capacity: 210 Total cost: \$8,900,000

Total annual operating costs: \$2,276,016

Category: New, independent facility

Facility type: County jail

Building configuration: High rise in

radial formation

#### Costs

Total: \$8,900,000 Building only: \$8,900,000 Housing area: \$3,240,000 Housing per inmate: \$16,364

Housing per cell: \$16,364 Total per inmate: \$42,381 Total per GSF: \$82.41

Total annual operating costs: \$2,276,016

# **Dimensions**

Gross square feet/corrections: 108,000 Gross square feet/other: 0

Gross square feet/total: 108,000 Housing area square feet: 40,515 Gross square feet per inmate: 514 Size of cells: 74.39 square feet (single)

Net/gross square feet: 94%

# **Construction type**

Structural: Cast-in-place concrete frame Exterior walls: CMU block; brick

Interior walls: CMU block Exterior surface/facade: Brick

### Security

Perimeter: Building exterior; single fence; alarm/detection systems

Doors/material: Solid steel; wooden

locking; remote locking only

Doors/locking: Motor driven and remote

Intercom: Two-way to cells and common

HVAC: Heating/air circulation only; gas-fired boilers supply hot water to

Doors/type: Sliding; swinging

Floor surface: Sealed concrete

Inmate security level: Maximum: 83% Medium: 0 Minimum: 17%

**Inmate cells** 

areas

# Inmate design capacity

Single occupancy: 180 Double occupancy: 0

Dorms: 0 Other: 18

Special housing: 12 General population: 198

Total: 210

## **Current staff**

Full-time equivalent: Administration: 13

Security: 53

Programs/treatment: Contractual

Maintenance: 4 Total: 70

Current inmate/staff ratio: 1.9:1

# **Inmate housing areas**

Design: Linear/outside; 5 floors have guard station, dayrooms, and 3 wings

Cells per unit: 36 Inmates per unit: 36

Management type: Intermittent

surveillance

October 1985 population: 133

Facility commitment: Local jail inmates Means to handle crowding: Use holding

cells

# **Construction process**

Finance method: G.O. Bonds Contract method: Conventional Use of inmate labor: None

Use of prefabrication: Moderate; ducts include lighting, door operators, and

sprinkler piping

# Architect's reported analyses

Factors affecting construction costs: Positive: Simple construction methods, repetitiveness of design; good competition, favorable market

Negative: None

Factors affecting time schedule:

Positive: Simple construction methods,

repetitiveness of design

Negative: Slow responses and delivery from vendors, suppliers; complex electronic, mechanical, and electrical

systems


heating coils


Furniture: Steel

Plumbing: Stainless

Fire protection: Sprinklers for cells and common areas; manual alarm stations;

duct smoke detectors





# Woodbury Law Enforcement Center

Jurisdiction official: Russell H. White, Jr., Sheriff

Contact: Lieutenant Lynette M. Hertz, Jail Commander, Woodbury Law Enforcement Center, 7th & Douglas, Sioux City,

IA 51101, 712-279-6040

Architect: Dana Larson Roubal & Associates, 400 Essex Court, Omaha, NE 68114, 402-393-4100

Construction manager: None

**Groundbreaking:** January 1986 Finish date: September 1987 Construction time: 20 months

**Design capacity: 108 Total cost:** \$7,112,760

**Total annual operating costs:** \$840,601

Category: New, independent facility Facility type: Complex: county jail, law

enforcement, courts, Sheriff's

Department

Building configuration: Integ. structure

#### **Costs**

Total: \$7,112,760

Building only: \$6,612,670 Housing area: \$3,300,000 Housing per inmate: \$50,000 Housing per cell: \$50,000

Total per inmate: N/A (complex)

Total per GSF: \$82.63

Total annual operating costs: \$840,601

## **Dimensions**

Gross square feet/corrections: 34,988 Gross square feet/other: 51,094 Gross square feet/total: 86,082 Housing area square feet: 25,500 Gross square feet per inmate: 324 Size of cells: 70 square feet (single)

Net/gross square feet: 73%

# **Inmate housing areas**

Design: Linear, outside Cells per unit: 4 to 22 Inmates per unit: 4 to 22

Management type: Remote surveillance

October 1987 population: 68

Facility commitment: Local jail inmates Means to handle crowding: Beds in

dayrooms

# Security

Perimeter: Building exterior only

Inmate security level: Maximum: 11% Medium: 89% Minimum: 0

# **Construction type**

Structural: Cast-in-place concrete frame Exterior walls: Cast-in-place concrete;

CMU block; brick

Interior walls: Cast-in-place concrete;

CMU block

Exterior surface/facade: Brick; textured

concrete

# **Construction process**

Finance method: Lease Purchase Bonds Contract method: Separate contracts

Use of inmate labor: None Use of prefabrication: None

### **Inmate cells**

Doors/material: Steel Doors/type: Swinging

Doors/locking: Remote locking Floor surface: Carpet; sealed concrete;

vinyl tile

Intercom: Two-way to common areas;

two-way radio

HVAC: Air conditioning; gas heat Plumbing: Stainless combination unit

Furniture: Steel; wood

Fire protection: Smoke detectors and sprinklers for cells and common areas

# Inmate design capacity

Single occupancy: 66 Double occupancy: 0

Dorms: 0

Special housing: 42

Total: 108

General population: 66

#### **Current staff**

Full-time equivalent: Administration: 8 Security: 33

Programs/treatment: 1 Maintenance: 0

Total: 42

Current inmate/staff ratio: 1.62:1

### Architect's reported analyses

Factors affecting construction costs: Positive: Simple construction methods,

repetitiveness of design Negative: High labor costs

Factors affecting time schedule:

Positive: Coordination of design between

Negative: Weather problems

(No floorplan available at time of publication)

# Johnson County Juvenile Hall

Jurisdiction official: Herbert Walton, Judge

Contact: Jerry Jacobson, Director, Johnson County Juvenile Hall, 915 West Spruce, Olathe, KS 66061, 913-764-7411

Architect: Abend Singleton Associates, 20 West Ninth Street, Kansas City, MO 64105, 816-221-5011

Construction manager: None

**Groundbreaking:** May 1978 **Finish date:** May 1980

Construction time: 24 months

**Design capacity:** 34 **Total cost:** \$1,700,000

**Total annual operating costs:** \$697,594

Category: New, independent facility Facility type: Juvenile detention facility Building configuration: Clusters

#### Costs

Total: \$1,700,000 Building only: Unknown Housing area: \$554,200 Housing per inmate: \$16,300 Housing per cell: \$16,300 Total per inmate: \$50,000

Total per GSF: \$68.55

Total annual operating costs: \$697,594

# **Security**

Perimeter: Single fence at exercise yard;

alarm/detection system
Inmate security level:
Maximum: Design, 100%
Medium: Use, varies
Minimum: Use, varies

### **Inmate cells**

Doors/material: Steel Doors/type: Swinging

Doors/locking: Remote locking Floor surface: Sealed concrete

Intercom: Two-way to cells and common

areas

HVAC: Air conditioning; rooftop heating

unit

Plumbing: Stainless steel

Furniture: Steel

Fire protection: Smoke detectors for cells and common areas; sprinklers

### **Dimensions**

Gross square feet/corrections: 24,800

Gross square feet/other: 0 Gross square feet/total: 24,800 Housing area square feet: 6,990 Gross square feet per inmate: 729 Size of cells: 56 square feet (single) Net/gross square feet: Unknown

**Construction type** 

Structural: Concrete block Exterior walls: Brick and block Interior walls: Painted masonry; brick in

privileged area

Exterior surface/facade: Brick and glazed

block

### Inmate design capacity

Single occupancy: 30 Double occupancy: 0

Dorms: 0 Other: 4

Special housing: 0 General population: 34

Total: 34

### **Current staff**

Full-time equivalent: Administration: 2 Security: 21

Programs/treatment: 3 Maintenance: 4

Total: 30

Current inmate/staff ratio: .60:1

### **Inmate housing areas**

Design: Module/pod Cells per unit: 7 and 8 Inmates per unit: 7 and 8

Management type: Remote surveillance

October 1985 population: 18

Facility commitment: Juvenile detainees Means to handle crowding: None

# **Construction process**

Finance method: G.O. Bonds Contract method: Conventional Use of inmate labor: None Use of prefabrication: None

### Architect's reported analyses

Factors affecting construction costs: Positive: Simple construction methods, repetitiveness of design; good competition, favorable market; less expensive


materials and hardware

Negative: None

Factors affecting time schedule:

Positive: None

Negative: Local decisionmaking process



# **Kansas State Penitentiary (Phase One) (Addition)**

Jurisdiction official: Richard A. Mills, Secretary, Department of Corrections

Contact: Herb Maschner, Director, Kansas State Penitentiary, Medium Security Facility, P.O. Box 2, Lansing, KS 66043,

913-727-3235

Architect: Horst-Terrill-Karst, Architects, P.A., 2900 MacVicar Avenue, Topeka, KS 66611, 913-266-5373

Construction manager: None

Groundbreaking: September 1982

Finish date: July 1985

Construction time: 35 months

**Design capacity:** 288 **Total cost:** \$10,700,000

Total annual operating costs: N/A

(addition)

Category: New, ancillary building; phased project (future)

Facility type: State prison

**Building configuration:** Courtyard:

clusters

#### **Costs**

Total: \$10,700,000 Building only: \$7,850,000 Housing area: \$5,200,000 Housing per inmate: \$18,056 Housing per cell: \$18,056 Total per inmate: \$37,153 Total per GSF: \$70.26

Total annual operating costs: N/A

(addition)

# **Security**

Perimeter: Double fence; alarm detection systems; razor wire on fence; towers;

patrols

Inmate security level:
Maximum: 0
Medium: 100%
Minimum: 0

#### **Inmate cells**

Doors/material: Solid; steel Doors/type: Swinging

Doors/locking: Manual locking cells; electric/mechanical all ext. doors Floor surface: Epoxy coating; sealed

concrete

Intercom: Two-way to common areas; security communications intercom HVAC: Heating/air circulation only;

central boilers Plumbing: China

Furniture: Wood; vinyl/plastic

Fire protection: Smoke detectors for cells and common areas; sprinklers for

common areas

#### **Dimensions**

Gross square feet/corrections: 152,300

Gross square feet/other: 0 Gross square feet/total: 152,300 Housing area square feet: 76,150 Gross square feet per inmate: 529 Size of cells: 60 square feet (single)

Net/gross square feet: 76%

# **Construction type**

Structural: Cast-in-place concrete frame;

bearing walls

Exterior walls: Precast panels; CIP concrete; CMU block; architectural

precasi

Interior walls: CIP concrete; CMU block Exterior surface/facade: Stucco; paint

### Inmate design capacity

Single occupancy: 288 Double occupancy: 0

Dorms: 0

Special housing: 0 General population: 288

Total: 288

#### **Current staff**

Full-time equivalent: Administration: 14 Security: 76

Programs/treatment: 8
Maintenance: N/A

Total: 98 (addition only)
Current inmate/staff ratio: 2.17:1

# **Inmate housing areas**

Design: Module/pod Cells per unit: 12 Inmates per unit: 96

Management type: Remote surveillance

October 1985 population: 213
Facility commitment: Sentenced State

prisoners

Means to handle crowding: Bunk beds in

cell

# **Construction process**

Finance method: Revenue sharing;

State funds

Contract method: Conventional Use of inmate labor: Extensive Use of prefabrication: Limited

### Architect's reported analyses


Factors affecting construction costs: Positive: Good competition, favorable market; less expensive materials and hardware

Negative: Slow construction, lengthy building time; government procedures, regulations, "red tape"; complex electronic, mechanical, and electrical systems

Factors affecting time schedule:

Positive: None

Negative: Government procedures, regulations, "red tape"; complex electronic, mechanical, and electrical systems; four contractor defaults



# **Shawnee County Department of Corrections**

Jurisdiction official: Earl Hindman, Director, Department of Corrections

Contact: Earl Hindman, Director, Shawnee County Department of Corrections, 501 East 8th Street, Topeka, KS 66607, 913-291-4073 Architect: Slemmons Associates Architects, P.A., Suite 1515, One Townsite Plaza, Topeka, KS 66603, 913-235-9244

Construction manager: None

**Groundbreaking:** August 1985 Finish date: September 1987 Construction time: 25 months

Design capacity: 190 Total cost: \$14,407,900

Total annual operating costs: Unknown

Category: New, independent facility Facility type: Complex: county jail, city jail, work release center, admin. offices **Building configuration:** Integrated

structure

#### Costs

Total: \$14,407,900

Building only: \$14,322,365 Housing area: \$10,806,000 Housing per inmate: \$77,186 Housing per cell: \$77,186 Total per inmate: \$75,831 Total per GSF: \$115.48

Total annual operating costs: Unknown

Perimeter: Single fence; alarm/detection

systems; video camera surveillance

#### **Dimensions**

Gross square feet/corrections: 124,765

Gross square feet/other: 0 Gross square feet/total: 124,765 Housing area square feet: 84,000 Gross square feet per inmate: 657 Size of cells: 70 square feet (single); 180

(spec. dorms)

Net/gross square feet: 84%

# Construction type

Structural: Steel frame; cast-in-place

concrete frame

Exterior walls: Cast-in-place concrete,

CMU block

Interior walls: Cast-in-place concrete; CMU block; steel cell ceilings Exterior surface/facade: Brick; paint;

painted concrete; stone

# **Inmate cells**

Other: 5%

Medium: 0

Inmate security level:

Maximum: 74%

Minimum: 21%

**Security** 

Doors/material: Solid; wooden Doors/type: Swinging Doors/locking: Unknown Floor surface: Sealed concrete Intercom: Two-way to cells

HVAC: Air conditioning; gas boilers;

centrifugal chiller

Plumbing: Stainless combination unit Furniture: Steel; particle board with

laminate; steel mesh

Fire protection: Smoke detectors and sprinklers for cells and common areas; manual alarm stations; smoke evacua-

tion system

# Inmate design capacity

Single occupancy: 140 Double occupancy: 0

Dorms: 0

Special housing: 50 General population: 140

Total: 190

#### **Current staff**

Full-time equivalent: Administration: 8 Security: 33

Programs/treatment: 0 Maintenance: 1

Total: 42

Current inmate/staff ratio: 3.29:1

### **Inmate housing areas**

Design: Module/pod Cells per unit: 20 Inmates per unit: 20

Management type: Direct supervision November 1987 population: 138 Facility commitment: Local jail inmates;

State prisoners

Means to handle crowding: Unknown

# **Construction process**

Finance method: G.O. Bonds; local funds Contract method: Conventional Use of inmate labor: None Use of prefabrication: None

### Architect's reported analyses

Factors affecting construction costs: Positive: Simple construction methods,


repetitiveness of design

Negative: Government procedures, regulations, and red tape; complex electronic and mechanical systems; expensive security components and cell plumbing

Factors affecting time schedule: Positive: Simple construction methods,

repetitiveness of design; good weather Negative: Slow responses and delivery from vendors, suppliers; government procedures, regulations, and red tape; complex electronic, mechanical, and

electrical systems



# **Federal Correctional Institution (Addition)**

Jurisdiction official: J. Michael Quinlan, Director, Bureau of Prisons

Contact: Warden Bill R. Story, Federal Correctional Institution, P.O. Box 888, Ashland, KY 41101, 606–928–6414 Architect: Design Group Inc., Architects/Planners, 1080 Kingsmill Parkway, Columbus, OH 43229, 614–888–6390

Construction manager: None

Groundbreaking: December 1983 Finish date: November 1985 Construction time: 23 months **Design capacity:** 100 **Total cost:** \$1,753,000

Total annual operating costs: \$418,310

(addition only)

Category: New, ancillary building Facility type: Federal prison Building configuration: Integrated

structure

#### Costs

Total: \$1,753,000

Building only: \$1,703,000 Housing area: \$1,703,000 Housing per inmate: \$17,030 Housing per cell: \$17,030 Total per inmate: \$17,530 Total per GSF: \$80.44

Total annual operating costs: \$418,310

(addition only)

### Security

Perimeter: Single fence; triple fence; razor wire on and between fences; patrols

Inmate security level:
Maximum: 0
Medium: 100%
Minimum: 0

#### **Inmate cells**

Doors/material: Steel Doors/type: Swinging

Doors/locking: Manual locking Floor surface: Epoxy coating; sealed

concrete

Intercom: Unknown

HVAC: Air conditioning; heating/air circulation; gas heat; 2 boilers; low pressure forced draft burner; 3 air

handlers Plumbing: China Furniture: Unknown

Fire protection: Smoke detectors and sprinklers for cells and common areas; manual alarm stations; duct mounted

heat detectors

#### **Dimensions**

Gross square feet/corrections: 21,792

Gross square feet/other: 0 Gross square feet/total: 21,792 Housing area square feet: 21,792 Gross square feet per inmate: 218 Size of cells: 68 square feet (single)

Net/gross square feet: 75%

# **Construction type**

Structural: Load-bearing CMU, flexicore

floor slabs

Exterior walls: Precast panels; CMU

block; brick

Interior walls: Precast panels; CMU block

Exterior surface/facade: Brick

### Inmate design capacity

Single occupancy: 100 Double occupancy: 0

Dorms: 0

Special housing: 0 General population: 100

Total: 100

#### **Current staff**

Full-time equivalent: Administration: 3 Security: 5

Security. 5

Programs/treatment: 4 Maintenance: 0

Total: 12 (addition only)
Current inmate/staff ratio: 16.08:1

### **Inmate housing areas**

Design: Module/pod; cells on outside

walls (direct light) Cells per unit: 100 Inmates per unit: 100

Management type: Remote surveillance

March 1987 population: 193

Facility commitment: Federal prisoners Means to handle crowding: Bunk beds in

cell

### **Construction process**

Finance method: Federal funds Contract method: Conventional Use of inmate labor: Limited; painting

Use of prefabrication: None

### Architect's reported analyses

Factors affecting construction costs:
Positive: Simple con. methods, repetitiveness of design; masonry bearing walls; flexicore deck and roof slab; design of open day spaces—no suspended ceiling required except offices and under 2nd floor walkways

Negative: Difficult site conditions


Factors affecting time schedule:

Positive: Simple con. methods, repetitiveness of design; advanced order of

materials and hardware

Negative: Labor problems; default of initial masonry contractor; controlled

access into site



# **Knox County Jail**

Jurisdiction official: Wilbur Bingham, Sheriff

Contact: Ned Stewart, Jailer, Knox County Jail, Barbourville, KY 40906, 606-546-6215

Architect: Chrisman, Miller, Woodford, Inc., 326 South Broadway, Lexington, KY 40508, 606-254-6623

Construction manager: None

**Groundbreaking:** January 1984 Finish date: November 1984 Construction time: 10 months

**Design capacity: 37 Total cost:** \$666,000

**Total annual operating costs:** \$284,115

Category: New, independent facility

Facility type: County jail

**Building configuration:** Integrated

structure

### **Costs**

Total: \$666,000

**Building only: \$573,097** Housing area: Unknown Housing per inmate: Unknown Housing per cell: Unknown Total per inmate: \$18,000 Total per GSF: \$91.23

Total annual operating costs: \$284,115

# **Dimensions**

Gross square feet/corrections: 7,300 Gross square feet/other: 0 Gross square feet/total: 7,300 Housing area square feet: 2,190 Gross square feet per inmate: 197 Size of cells: 70 square feet (single)

Net/gross square feet: 90%

# Inmate housing areas

Design: Linear, outside Cells per unit: 2 to 4 Inmates per unit: 12

Management type: Intermittent

surveillance

October 1985 population: 45

Facility commitment: Local jail inmates

and State prisoners

Means to handle crowding: Mattresses

on floor

# Security

Perimeter: Building exterior only

Inmate security level: Maximum: 40% Medium: 20% Minimum: 40%

# **Construction type**

Structural: Load bearing masonry Exterior walls: CMU block Interior walls: CMU block

Inmate design capacity

Exterior surface/facade: Stucco; textured

concrete block

Single occupancy: 0

Special housing: 7

Dorms: 12

Total: 37

Double occupancy: 18

General population: 30

# **Construction process**

Finance method: Local funds; State funds Contract method: Conventional Use of inmate labor: None Use of prefabrication: None

# **Inmate cells**

Doors/material: Steel Doors/type: Swinging

Doors/locking: Remote locking only Floor surface: Sealed concrete; vinyl tile Intercom: Two-way to cells and common areas

HVAC: Air conditioning; gas rooftop

heating unit

Plumbing: Stainless combination unit

Furniture: Steel

Fire protection: Smoke detectors for cells and common areas; manual alarm stations; fire emergency auto release (FEAR) for electric locks

**Current staff** 

Full-time equivalent: Administration: 2 Security: 7

> Programs/treatment: 1 Maintenance: 1

Total: 11

Current inmate/staff ratio: 4.09:1

# **Architect's reported analyses**

Factors affecting construction costs: Positive: Conventional construction materials and systems; good competition, favorable market Negative: Delivery of materials and

hardware

Factors affecting time schedule: Positive: Simple construction methods,

repetitiveness of design

Negative: Slow responses and delivery from security equipment suppliers;

weather problems

Laundry Kitchen Storage Outdoor Exercise Control Room Sallyport Booking Detox Search/Shower Holding Medical Exam Multipurpose Dayroom Lobby Visitation 2 Bed Cel 1.2... 8... 10... 111... 2 21 21 22 14

# **Dixon Correctional Institute (Remodel)**

Jurisdiction official: C. Paul Phelps, Secretary, Department of Public Safety and Corrections

Contact: Warden Burl Cain, Dixon Correctional Institute, Highway 68, P.O. Box 788, Jackson, LA 70748, 504-634-2691

Architect: Newman and Grace Architects, Inc., 2532 Toulon Drive, Baton Rouge, LA 70816, 504-292-1210

Construction manager: None

Groundbreaking: November 1983

Finish date: January 1985

Construction time: 14 months

**Design capacity:** 100 **Total cost:** \$1,135,427

Total annual operating costs: \$1,475,400

Category: Remodeling/renovation

project

Facility type: State prison

Building configuration: Campus style

#### Costs

Total: \$1,135,427

Building only: \$1,135,427 Housing area: \$1,135,427 Housing per inmate: \$11,354

Housing per cell: \$22,263 Total per inmate: \$11,354 Total per GSF: \$66.95

Total annual operating costs: \$1,475,400

### **Dimensions**

Gross square feet/corrections: 16,960

Gross square feet/other: 0 Gross square feet/total: 16,960 Housing area square feet: 16,960 Gross square feet per inmate: 170 Size of cells: 65 square feet (single);

3,240 (dorms)

Net/gross square feet: Unknown

### **Inmate housing areas**

Design: Linear, inside Cells per unit: 50 Inmates per unit: 50

Management type: Intermittent

surveillance

January 1987 population: 100

Facility commitment: State prisoners Means to handle crowding: Unknown

# Security

Perimeter: Single fence; razor wire on

fence; patrols
Inmate security level:
Maximum: 50%
Medium: 0
Minimum: 50%

# **Construction type**

Structural: Steel frame Exterior walls: Brick Interior walls: CMU block Exterior surface/facade: Brick

# **Construction process**

Finance method: G.O. Bonds Contract method: Conventional Use of inmate labor: Limited; demolition

work prior to construction Use of prefabrication: None

#### **Inmate cells**

Doors/material: Steel Doors/type: Swinging

Doors/locking: Remote locking Floor surface: Sealed concrete Intercom: Two-way to common areas

HVAC: Heating/air circulation; gas heat Plumbing: Stainless combination unit

Furniture: Steel; concrete

Fire protection: Smoke detectors and sprinklers for cells and common areas;

automatic fire alarm

# Inmate design capacity

Single occupancy: 50 Double occupancy: 0

Dorms: 50
Special housing: 0
General population: 100

Total: 100

### Architect's reported analyses

Factors affecting construction costs: Positive: Simple construction methods,

repetitiveness of design

Negative: None

Factors affecting time schedule: Positive: Simple construction methods,

repetitiveness of design

Negative: Inmates did some of the

demolition


#### **Current staff**

Full-time equivalent: Administration: 4 Security: 24

Programs/treatment: 0
Maintenance: 0

Total: 28

Current inmate/staff ratio: 3.57:1



### **Federal Detention Center**

Jurisdiction official: J. Michael Quinlan, Director, Bureau of Prisons

Contact: Warden J.R. Johnson, Federal Detention Center, P.O. Box 5050, East Whatley Road, Oakdale, LA 71463,

318-335-4070

Architect: Barron, Heinberg & Brocato, P.O. Box 1952, 1015 Wisteria Street, Alexandria, LA 71301, 318-443-7291

Construction manager: Jose Barron, Jr., P.O. Box 930, Oakdale, LA 71463-0930, 318-335-4070

Groundbreaking: July 1984 Finish date: March 1986 Construction time: 20 months Design capacity: 907
Total cost: \$16,823,295
Total annual operating costs:

\$10,400,000

Category: New, independent facility
Facility type: Complex: Federal detention
center, law enforcement, courts
Building configuration: Campus style

#### Costs

Total: \$16,823,295

Building only: \$13,132,275 Housing area: \$6,966,178 Housing per inmate: \$7,723 Housing per cell: \$24,272

Total per inmate: N/A (complex)

Total per GSF: \$73.81

Total annual operating costs: \$10,400,000

# Security

Perimeter: Single fence; alarm/ detection systems; patrols Inmate security level: Maximum: None

Medium: 16% Minimum: 84%

#### **Inmate cells**

Doors/material: Wooden (single);

no doors (dorms)
Doors/type: Swinging
Doors/locking: Manual
Floor surface: Sealed concrete

Intercom: One-way to common areas HVAC: Air conditioning; boiler,

natural gas fired

Plumbing: China; combination unit

in special cells Furniture: Wood

Fire protection: Smoke detectors for common areas; sprinklers for cells and common areas; manual alarm stations

#### **Dimensions**

Gross square feet/corrections: 183,381 Gross square feet/other: 44,540 Gross square feet/total: 227,921 Housing area square feet: 126,186

Gross square feet per inmate: 202 Size of cells: 95 square feet (single);

190 square feet (dorm) Net/gross square feet: 95%

# **Construction type**

Structural: Cast-in-place concrete frame;

preengin. metal; comb. wall

bearing/steel frame

Exterior walls: Precast panels;

cast-in-place concrete; CMU block;

metal roof, windows

Interior walls: Cast-in-place concrete;

CMU block

Exterior surface/facade: Painted block;

preengin. metal/prefinished

# Inmate design capacity

Single occupancy: 82 Double occupancy: 0

Dorms: 820 Special housing: 5 General population: 902

Total: 907

#### **Current staff**

Full-time equivalent: Administration: 45

Security: 98

Programs/treatment: 48

Maintenance: 25

Total: 216

Current inmate/staff ratio: N/A

# Inmate housing areas

Design: Module/pod

Cells per unit: 1 wing 82; 5 wings 41

Inmates per unit: 82; 164

Management type: Direct supervision

October 1985 population: N/A

Facility commitment: Federal prisoners Means to handle crowding: None needed

# **Construction process**

Finance method: Federal funds

Contract method: Conventional; general

contract (lump sum)
Use of inmate labor: None

Use of prefabrication: Limited; precast


concrete wall panels

### Architect's reported analyses

Factors affecting construction costs:
Positive: Good competition, favorable
market; less expensive materials and
hardware; simple construction
methods, repetitiveness of design
Negative: Difficult site conditions

Factors affecting time schedule:
Positive: Simple construction methods,
repetitiveness of design; coordination
of design between parties; efficient
contractor

Negative: Labor problems; weather problems/initial poor drainage



# Feliciana Forensic Facility (Addition)

Jurisdiction official: Sandra L. Robinson, M.D., M.P.H., Department of Health and Human Resources

Contact: Murry Henderson, Administrator, Feliciana Forensic Facility, P.O. Box 888, Jackson, LA 70748, 504-634-2651 Architect: Lasseigne & Legett, AIA, Architects, Inc., 554 Colonial Drive, Baton Rouge, LA 70806, 504-926-1432

Construction manager: None

**Groundbreaking:** April 1982 Finish date: May 1984

Construction time: 24 months

Design capacity: 75 **Total cost:** \$3,647,164

Total annual operating costs: N/A

(addition)

Category: New, ancillary building Facility type: Complex: State prison,

courts, forensic hospital

**Inmate housing areas** 

October 1985 population: 72

Building configuration: Integrated

Design: Linear, outside; module/pod

Management type: Remote surveillance

Facility commitment: State prisoners

Means to handle crowding: None

structure

Cells per unit: 19

Inmates per unit: 19

#### **Costs**

Total: \$3,647,164

Building only: \$3,600,000 Housing area: \$2,637,582 Housing per inmate: \$35,168 Housing per cell: \$35,168

Total per inmate: N/A (complex)

Total per GSF: \$126.54

Total annual operating costs: N/A

(addition)

# **Security**

Perimeter: Double fence; towers; patrols

Inmate security level: Maximum: 75% Medium: 0 Minimum: 25%

# **Dimensions**

Gross square feet/corrections: 23,696 Gross square feet/other: 5,126 Gross square feet/total: 28,822 Housing area square feet: 21,696 Gross square feet per inmate: 316 Size of cells: 80 square feet (single)

Net/gross square feet: 96%

# Construction type

Structural: Load bearing precast cell modules

Exterior walls: Brick; architectural

precast

Interior walls: Precast cell modules; CIP concrete; CMU block; brick Exterior surface/facade: Brick

# **Construction process**

Finance method: G.O. Bonds Contract method: Conventional Use of inmate labor: None

Use of prefabrication: Extensive, precast

cell units

#### **Inmate cells**

Doors/material: Steel Doors/type: Swinging

Doors/locking: Remote locking only

Floor surface: Linoleum

Intercom: Two-way to common areas HVAC: Air conditioning; boiler

Plumbing: Stainless steel

Furniture: Steel

Fire protection: Sprinklers for cells and

common areas

# Inmate design capacity

Single occupancy: 75 Double occupancy: 0

Dorms: 0

Special housing: 0 General population: 75

Total: 75

# **Current staff**

Full-time equivalent: Administration: 17 Security: 50

Programs/treatment: 10 Maintenance: 16

Total: 93 (addition only) Current inmate/staff ratio: .77:1

# Architect's reported analyses

Factors affecting construction costs: Positive: Use of prefabricated components, factory assembly; simple construction methods, repetitiveness of design Negative: High labor costs; complex


electronic, mechanical, and electrical systems


Factors affecting time schedule:

Positive: Use of prefabricated components, factory assembly; simple construction methods, repetitiveness of design, advanced order of materials and hardware; coordination of design between parties

Negative: Weather problems; complex electronic, mechanical, and electrical

systems





# **Hunt Correctional Center (Addition)**

Jurisdiction official: C. Paul Phelps, Secretary, Department of Public Safety and Corrections

Contact: John P. Whitley, Corrections Warden III, Hunt Correctional Center, P.O. Box 174, St. Gabriel, LA 70776, 504–642–3306

Architect: Alpha Three, 253 St. Joseph Street, P.O. Box 843, Baton Rouge, LA 70821, 504-383-7565

Construction manager: None

Groundbreaking: September 1984 Finish date: November 1985 Construction time: 14 months

Design capacity: 744 **Total cost:** \$6,571,257

Total annual operating costs: \$3,800,000

(addition only)

Category: New, ancillary building

Facility type: State prison

Building configuration: Ladder, telephone pole; covered walkways to

connect buildings

#### Costs

Total: \$6,571,257

Building only: \$6,414,358 Housing area: \$6,414,358 Housing per inmate: \$8,621 Housing per cell: \$19,797 Total per inmate: \$8,832 Total per GSF: \$89.40

Total annual operating costs: \$3,800,000

(addition only)

# **Security**

Perimeter: Single fence; double fence; alarm/detection systems; razor wire on and between fences; towers; patrols

Inmate security level: Maximum: 100% Medium: 0 Minimum: 0

**Inmate cells** 

Doors/material: Steel Doors/type: Sliding

Doors/locking: Motor driven and remote

locking

Floor surface: Sealed concrete Intercom: Two-way to common areas HVAC: Air conditioning; heating/air circulation; solar heat; hot water to air handlers

Plumbing: Stainless steel; stainless

combination unit Furniture: Steel; concrete

Fire protection: Smoke detectors for cells and common areas; automatic alarm

### **Dimensions**

Gross square feet/corrections: 73,505

Gross square feet/other: 0 Gross square feet/total: 73,505 Housing area square feet: 73,505 Gross square feet per inmate: 99 Size of cells: 66 square feet (double); 1,244

(dorm)

Net/gross square feet: 85%

# Construction type

Structural: Load bearing masonry Exterior walls: CMU block; precast panel

roof

Interior walls: CMU block Exterior surface/facade: Paint

# Inmate design capacity

Single occupancy: 0 Double occupancy: 640

Dorms: 104 Special housing: 0 General population: 744

Total: 744

#### **Current staff**

Full-time equivalent: Administration: 10 Security: 160

Programs/treatment: 8 Maintenance: N/A Total: 178 (addition only) Current inmate/staff ratio: 4.17:1

# **Inmate housing areas**

Design: Linear, inside Cells per unit: 64 Inmates per unit: 128

Management type: Intermittent surveil-

lance

July 1986 population: 743

Facility commitment: State prisoners Means to handle crowding: Unknown

# **Construction process**

Finance method: G.O. Bonds Contract method: Conventional Use of inmate labor: None Use of prefabrication: None

# Architect's reported analyses


Factors affecting construction costs: Positive: Simple construction method,

repetitiveness of design

Negative: None

Factors affecting time schedule: Positive: Simple construction methods, repetitiveness of design; experience in design and construction of this type of

facility Negative: None



# **Louisiana Correctional Institute for Women (Addition)**

Jurisdiction official: C. Paul Phelps, Secretary, Department of Public Safety and Corrections

Contact: Warden Johnnie W. Jones, Louisiana Correctional Institute for Women, Highway 74, P.O. Box 26, St. Gabriel, LA 70776,

504-342-6297

Architect: Newman and Grace Architects, Inc., 2532 Toulon Drive, Baton Rouge, LA 70816, 504-292-1210

Construction manager: None

Groundbreaking: November 1979 Finish date: December 1980 **Construction time:** 13 months

**Design capacity: 100 Total cost:** \$1,373,421

Total annual operating costs: N/A

(addition)

Category: New, ancillary building Facility type: State prison (women's

facility)

Building configuration: Integrated

structure

### **Costs**

Total: \$1,373,421

Building only: \$1,360,521 Housing area: \$1,360,521 Housing per inmate: \$16,197 Housing per cell: \$32,393 Total per inmate: \$13,605

Total per GSF: \$74.61

Total annual operating costs: N/A

(addition)

### Security

Perimeter: Single fence; patrols; double

"V" barbed wire top Inmate security level: Maximum: 16% Medium: 0 Minimum: 84%

# **Inmate cells**

Doors/material: Unknown Doors/type: Swinging

Doors/locking: Manual locking; remote

locking

Floor surface: Vinyl tile

Intercom: Two-way to common areas HVAC: Air conditioning; gas heat Plumbing: China (min.); stainless steel

(max.)

Furniture: Steel; wood; vinyl/plastic Fire protection: Smoke detectors for cells and common areas; automatic fire

alarms

### **Dimensions**

Gross square feet/corrections: 18,407

Gross square feet/other: 0 Gross square feet/total: 18,407 Housing area square feet: 18,407 Gross square feet per inmate: 184 Size of cells: 145 square feet (double);

63 (spec. single)

Net/gross square feet: Unknown

# Construction type

Structural: Steel frame

Exterior walls: Brick; 6" steel stud cavity

Interior walls: CMU block; plaster

partitions

Exterior surface/facade: Brick

### Inmate design capacity

Single occupancy: 0 Double occupancy: 84

Dorms: 0

Special housing: 16 General population: 84

Total: 100

#### **Current staff**

Full-time equivalent: Administration: 8 Security: 137

Programs/treatment: 17

Maintenance: 11

Total: 173 (entire facility) Current inmate/staff ratio: 2.25:1

# **Inmate housing areas**

Design: Linear, outside Cells per unit: 58 Inmates per unit: 100

Management type: Combination of intermittent and remote surveillance July 1986 population: 389 (entire facility) Facility commitment: State prisoners Means to handle crowding: Unknown

# **Construction process**

Finance method: G.O. Bonds Contract method: Conventional Use of inmate labor: None Use of prefabrication: None

### Architect's reported analyses

Factors affecting construction costs: Positive: Simple construction methods,

repetitiveness of design


Negative: None

Factors affecting time schedule:

Positive: Simple construction methods,

repetitiveness of design

Negative: None



# **Washington Correctional Institute**

Jurisdiction official: C. Paul Phelps, Secretary, Department of Public Safety and Corrections

Contact: Warden J.F. Donnelly, Jr., Washington Correctional Institute, Route 2, Box 5, Highway 21, Angie, LA 70426,

504-986-3182

Architect: Cimini Meric Burns Counce, 615 Barrone Street, Suite 200, New Orleans, LA 70113, 504-588-9488

Construction manager: None

Groundbreaking: December 1980

Finish date: July 1983

Construction time: 31 months

**Design capacity:** 1,182 **Total cost:** \$27,316,900

Total annual operating costs: \$9,824,653

Category: New, independent facility

Facility type: State prison

**Inmate housing areas** 

Design: Linear, interior

Cells per unit: 1 (dorm)

May 1986 population: 1,120

Inmates per unit: 80

Building configuration: Campus style

Management type: Remote surveillance

Facility commitment: State prisoners

Means to handle crowding: None

### Costs

Total: \$27,316,900

Building only: \$20,816,000 Housing area: \$9,100,000 Housing per inmate: \$7,765 Housing per cell: \$137,879 Total per inmate: \$23,111 Total per GSF: \$121.64

Total annual operating costs: \$9,824,653

### **Dimensions**

Gross square feet/corrections: 224,569

Gross square feet/other: 0 Gross square feet/total: 224,569 Housing area square feet: 113,235 Gross square feet per inmate: 190 Size of cells: 56 square feet (single); 6,800

square feet (dorm) Net/gross square feet: 89%

# Construction type

Structural: Cast-in-place concrete frame Exterior walls: Cast-in-place concrete;

brick

Interior walls: Cast-in-place concrete;

CMU block

Exterior surface/facade: Brick

# **Construction process**

Finance method: G.O. Bonds Contract method: Conventional Use of inmate labor: None Use of prefabrication: None

# Security

Perimeter: Double fence; razor wire on and between fences; towers

Inmate security level:
Maximum: 5%
Medium: 95%
Minimum: 0

### **Inmate cells**

Doors/material: Steel Doors/type: Sliding

Doors/locking: Motor driven and remote

locking

Floor surface: Sealed concrete

Intercom: None

HVAC: Heating/air circulation; gas heat

Plumbing: Stainless steel

Furniture: Steel

Fire protection: Smoke detectors for cells and common areas; manual alarm

stations

### Inmate design capacity

Single occupancy: 52 Double occupancy: 0 Dorms: 1,120 Special housing: 10 General population: 1,172

Total: 1,182

### **Current staff**

Full-time equivalent: Administration: 34 Security: 372

Programs/treatment: 31 Maintenance: 8

Total: 445

Current inmate/staff ratio: 2.52:1

# Architect's reported analyses

Factors affecting construction costs: Positive: Simple construction methods,

repetitiveness of design

Negative: Difficult site conditions

Factors affecting time schedule: Positive: Simple construction methods,

repetitiveness of design Negative: Weather problems

Louisian	a
Ang	ie

(No floorplan available at time of publication)

# Franklin County Detention/Law Enforcement Facility

Jurisdiction official: Ronald A. Durrell, Sheriff

Contact: Sheriff Ronald A. Durrell, Franklin County Detention/Law Enforcement Facility, Farmington, ME 04938, 207-778-2680

Architect: Alexander/Truex/de Groot, 209 Battery Street, Burlington, VT 05401, 802-658-2775

Construction manager: None

Groundbreaking: May 1982 Finish date: April 1983 Construction time: 11 months **Design capacity:** 24 **Total cost:** \$1,302,000

**Total annual operating costs:** \$417,188

Category: New, independent facility Facility type: Complex: county jail, law

enforcement

Building configuration: Integrated

structure

#### **Costs**

Total: \$1,302,000

Building only: \$1,186,000 Housing area: Unknown Housing per inmate: Unknown Housing per cell: Unknown

Total per inmate: N/A (complex)

Total per GSF: \$61.50

Total annual operating costs: \$417,188

# **Security**

Perimeter: Building exterior only;

razor wire on fence Inmate security level: Maximum: 12% Medium: 45%

Minimum: 33% (plus 10% holding

and detox)

### **Inmate cells**

Doors/material: Steel Doors/type: Swinging

Doors/locking: Remote and manual

locking

Floor surface: Epoxy coating

Intercom: Two-way to cells and common

areas

HVAC: Air conditioning-control room; heating/air circulation; heat recovering wheel; oil-fired boiler Plumbing: Stainless combination unit

Furniture: Steel

Fire protection: Smoke detectors for cells and common areas; air pacs in central control; fire mains and hoses

#### **Dimensions**

Gross square feet/corrections: 15,170 Gross square feet/other: 6,000 Gross square feet/total: 21,170 Housing area square feet: 7,500 Gross square feet per inmate: 632 Size of cells: Max. sec. 80 square feet;

med. sec. 66.5 square feet Net/gross square feet: 67%

# **Construction type**

Structural: Cast-in-place concrete

bearing walls Exterior walls: Brick

Interior walls: CMU block in attic spaces;

cast-in-place concrete Exterior surface/facade: Brick

### Inmate design capacity

Single occupancy: 13 Double occupancy: 0

Dorms: 8

Special housing: 3 General population: 21

Total: 24

### **Current staff**

Full-time equivalent: Administration: 2 Security: 12

> Programs/treatment: 0 Maintenance: Contractual

Total: 14

Current inmate/staff ratio: 1.21:1

# Inmate housing areas

Design: Module/pod; combined use cells

Cells per unit: 13 Inmates per unit: 13

Management type: Direct supervision

October 1985 population: 17

Facility commitment: Local jail inmates

and State prisoners

Means to handle crowding: Weekend use

of multipurpose room; beds in

dayroom

### **Construction process**

Finance method: G.O. Bonds Contract method: Conventional Use of inmate labor: None Use of prefabrication: None

# Architect's reported analyses


Factors affecting construction costs:
Positive: Simple construction methods,
repetitiveness of design; early ordering
of long lead time components
Negative: Complex electronic,
mechanical, and electrical systems;

mechanical, and electrical systems; government procedures, regulations, "red tape"

Factors affecting time schedule: Positive: Advanced order of materials and hardware; simple construction

methods, repetitiveness of design Negative: Slow responses and delivery

from vendors, suppliers



# **Baltimore City Correctional Center**

Jurisdiction official: Arnold J. Hopkins, Commissioner, Department of Public Safety and Correctional Services, Division of Correction

Contact: George Redd, Unit Manager, Baltimore City Correctional Center, 901 Greenmount Avenue, Baltimore, MD 21202,

301-234-1400

Architect: Nelson Salabes, Suite 208, 1045 Taylor Avenue, Baltimore, MD 21204, 301-828-6636

Construction manager: Heery Program Management, Inc., 7133 Rutherford Road, Baltimore, MD 21207-2784, 301-944-3700

**Groundbreaking:** May 1982 **Finish date:** July 1984

Construction time: 26 months

**Total annual operating costs:** \$3,758,432

**Design capacity: 384** 

**Total cost:** \$7,918,000

Category: New, independent facility

Facility type: State prison

Building configuration: Integrated

structure; wheel

#### **Costs**

Total: \$7,918,000

Building only: \$7,104,348 Housing area: \$4,750,800 Housing per inmate: \$12,372 Housing per cell: \$18,558 Total per inmate: \$20,620 Total per GSF: \$108.47

Total annual operating costs: \$3,758,432

### **Dimensions**

Gross square feet/corrections: 73,000

Gross square feet/other: 0 Gross square feet/total: 73,000 Housing area square feet: 55,700 Gross square feet per inmate: 190

Size of cells: Unknown Net/gross square feet: N/A

# **Construction type**

Structural: Steel frame; CIP concrete frame; load bearing masonry walls Exterior walls: Cast-in-place concrete;

CMU block; brick

Interior walls: Precast panels; cast-inplace concrete, CMU block

Exterior surface/facade: Brick; textured

concrete

# Security

Perimeter: Building exterior; razor

wire on fences
Inmate security level:
Maximum: 0
Medium: 0
Minimum: 100%

# Inmate design capacity

Single occupancy: 128 Double occupancy: 256

Dorms: 0

Special housing: 0 General population: 384

Total: 384

### **Inmate cells**

Doors/material: Steel Doors/type: Swinging

Doors/locking: Manual locking Floor surface: Sealed concrete

Intercom: None

HVAC: Heating/air circulation only

Plumbing: Stainless Furniture: Steel

Fire protection: Sprinklers for common

areas

### **Current staff**

Full-time equivalent: Administration: 22

Security: 74

Programs/treatment: 3 Maintenance: 7 Total: 106

Current inmate/staff ratio: 3.37:1

# **Inmate housing areas**

Design: Linear, outside Cells per unit: 128 Inmates per unit: 192

Management type: Intermittent

surveillance

October 1985 population: 357
Facility commitment: State prisoners
Means to handle crowding: Second bunk

permanently attached to wall


# **Construction process**

Finance method: G.O. Bonds Contract method: Construction management fast track Use of inmate labor: None Use of prefabrication: Limited

# Architect's reported analyses

Factors affecting construction costs:
Positive: Simple construction methods;
phased construction, fast track
construction management; good
competition, favorable market
Negative: Slow construction, lengthy
building time

Factors affecting time schedule:
Positive: Use of prefabricated
components, factory assembly; simple
construction methods, repetitiveness
of design; phased construction, fast
track construction management
Negative: Slow responses and delivery
from vendors, suppliers; labor problems



# **Baltimore City Jail (Addition)**

Jurisdiction official: Clarence "Du" Burns, Mayor

Contact: Warden Paul Davis, Baltimore City Jail, 401 East Eager Street, Baltimore, MD 21202, 301–396–5219 Architect: The Leon Bridges Company, 123 Market Place, Ninth Floor, Baltimore, MD 21202, 301–625–2555

Construction manager: None

**Groundbreaking:** August 1984

Finish date: May 1985 Construction time: 9 months **Design capacity:** 50 **Total cost:** \$655,000

Total annual operating costs: N/A

Gross square feet/corrections: 7,000

Gross square feet/other: 0

Net/gross square feet: 93%

Gross square feet/total: 7,000

Housing area square feet: 3,120

Gross square feet per inmate: 140

(addition)

**Dimensions** 

Category: New, ancillary building

Facility type: City jail

**Building configuration:** Integrated

structure

#### Costs

Total: \$655,000

Building only: \$650,000 Housing area: \$500,000 Housing per inmate: \$10,000 Housing per cell: N/A Total per inmate: \$13,100

Total per GSF: \$93.57

Total annual operating costs: N/A

(addition)

# Construction type

Structural: Concrete and CMU pilasters with steel beam and interior st. col.

Exterior walls: CMU block; architectural

Size of cells: N/A

precast roof

Interior walls: CMU block Exterior surface/facade: Paint

# Security

Perimeter: Single fence; alarm/detection system; razor wire on fence

Inmate security level:
Maximum: 0
Medium: 10%
Minimum: 90%

#### **Inmate cells**

Doors/material: Steel Doors/type: Swinging

Doors/locking: Remote locking Floor surface: Linoleum; sealed concrete

Intercom: One-way to common areas

HVAC: Heat pump Plumbing: Stainless Furniture: Steel

Fire protection: Smoke detectors for common areas; manual alarm stations

# Inmate design capacity

Single occupancy: 0
Double occupancy: 0

Dorms: 50 Special housing: 0 General population: 50

Total: 50

### **Current staff**

Full-time equivalent: Administration: N/A

Security: 10

Programs/treatment: N/A Maintenance: N/A Total: 10 (addition only) Current inmate/staff ratio: 5:1

# **Inmate housing areas**

Design: Open dormitory Cells per unit: N/A Inmates per unit: 25

Management type: Remote surveillance;

direct supervision

October 1985 population: 50

Facility commitment: Local jail inmates

Means to handle crowding: New

construction

# **Construction process**

Finance method: Federal funding Contract method: Turn-key design and

build

Use of inmate labor: None Use of prefabrication: Limited

### Architect's reported analyses

Factors affecting construction costs: Positive: Simple construction methods, repetitiveness of design; good

competition, favorable market; simple


building design

Negative: Difficult site conditions; detention grade doors, fixtures

Factors affecting time schedule: Positive: Fast track proposal;

coordination of design between parties Negative: Slow responses and delivery from vendors, suppliers; weather

problems



# **Eastern Correctional Institution**

Jurisdiction official: Arnold J. Hopkins, Commissioner, Division of Correction

Contact: Warden Wayne B. Winebrenner, Eastern Correctional Institution, Route 1, Box 500, Westover, MD 21871, 301-651-9000

Architects: Dewberry & Davis, 8401 Arlington Boulevard, Fairfax, VA 22031, 703–849–0430 Phillips Swager Associates, 3622 North Knoxville, Peoria, IL 61603, 309–688–9511

Construction manager: Heery Program Management, Inc., 7133 Rutherford Road, Baltimore, MD 21207, 301-944-3700

**Groundbreaking:** May 1984 **Finish date:** July 1987

Construction time: 38 months

Design capacity: 1,440 Total cost: \$77,600,000 Total annual operating costs:

\$20,850,146

Category: New, independent facility

Facility type: State prison

Building configuration: Campus style;

wheel, spoke or radial

### Costs

Total: \$77,600,000

Building only: \$68,200,000 Housing area: \$30,000,000 Housing per inmate: \$26,042 Housing per cell: \$26,042

Total per inmate: \$53,889 Total per GSF: \$121.25

Total annual operating costs: \$20,850,146

# **Dimensions**

Gross square feet/corrections: 640,000

Gross square feet/other: 0 Gross square feet/total: 640,000 Housing area square feet: 336,570 Gross square feet per inmate: 444 Size of cells: 70 square feet (gen. single);

82 (spec. single) Net/gross square feet: 60%

# Inmate housing areas

Design: Spoke Cells per unit: 192 Inmates per unit: 192

Management type: Remote surveillance

October 1987 population: 468 Facility commitment: State prisoners Means to handle crowding: Double-

celling

# **Security**

Perimeter: Double fence; alarm/detection systems; razor wire on and between fences; towers; patrols; camera surveillance

Inmate security level:
Maximum: 0
Medium: 100%
Minimum: 0

# **Construction type**

Structural: Load-bearing precast panels; steel frame

Exterior walls: Precast panels; brick Interior walls: Precast panels; CMU block Exterior surface/facade: Brick; natural

wall

### **Construction process**

Finance method: State funds Contract method: Conventional Use of inmate labor: None

Use of prefabrication: Moderate; precast

concrete panels

#### **Inmate cells**

Doors/material: Steel Doors/type: Sliding

Doors/locking: Remote locking Floor surface: Carpet; sealed concrete;

vinvl tile

Intercom: Two-way to common areas HVAC: Heating/air circulation; steam

heat

Plumbing: Stainless combination unit

Furniture: Steel

Fire protection: Smoke detectors for cells; sprinklers for cells and common areas;

manual alarm stations

# Inmate design capacity

Single occupancy: 1,152 Double occupancy: 0

Dorms: 0

Special housing: 288 General population: 1,152

Total: 1,440

# Architects' reported analyses

Factors affecting construction costs: Positive: Simple construction methods,

repetitiveness of design

Negative: Difficult site conditions; government procedures, regulations,

and red tape

Factors affecting time schedule:

Positive: Phased construction; advanced order of materials and hardware Negative: Slow responses and delivery


from vendors, suppliers

### **Current staff**

Full-time equivalent: Administration: 170 Security: 513

Programs/treatment: 34 Maintenance: 25

Total: 742 Current inmate/staff ratio: .63:1



# Montgomery County Detention Center (Remodel/Expansion)

Jurisdiction official: Calvin Lightfoot, Director, Department of Correction and Rehabilitation

Contact: John E. Wright, Director, Montgomery County Detention Center, 1307 Seven Locks Road, Rockville, MD 20854,

301-424-0940

Architect: Hellmuth, Obata and Kassabaum, Inc., 1110 Vermont Avenue NW., Suite 330, Washington, DC 20005, 202-457-9400

Construction manager: None

Groundbreaking: February 1984 Finish date: September 1986 Construction time: 32 months **Design capacity:** 131 **Total cost:** \$6,200,000

**Total annual operating costs:** \$981,710

(expansion only)

Category: Remodeling/renovation project; expansion project

Facility type: Complex: county jail,

courts

Building configuration: Integ. structure

#### Costs

Total: \$6,200,000
Building only: Unknown
Housing area: Unknown
Housing per inmate: Unknown
Housing per cell: Unknown
Total per inmate: N/A (remodel)
Total per GSF: \$134.73

Total annual operating costs: \$981,710

(expansion only)

#### **Dimensions**

Gross square feet/corrections: 44,819 Gross square feet/other: 1,200 Gross square feet/total: 46,019 Housing area square feet: 38,915 Gross square feet per inmate: 351

Size of cells: Unknown Net/gross square feet: 55%

# **Inmate housing areas**

Design: Module/pod Cells per unit: 16 Inmates per unit: 16

Management type: Remote surveillance

May 1987 population: 181

Facility commitment: Local jail inmates;

State prisoners

Means to handle crowding: Bunk beds in

cell; mattresses on floor

#### **Security**

Perimeter: Building exterior; single

fence

Inmate security level:
Maximum: 100%
Medium: 0
Minimum: 0

# **Construction type**

Structural: Cast-in-place concrete frame Exterior walls: Precast panels; reinforced

block

Interior walls: Cast-in-place concrete Exterior surface/facade: Textured colored precast

#### **Construction process**

Finance method: Local funds; State funds Contract method: Conventional Use of inmate labor: None Use of prefabrication: None

#### **Inmate cells**

Doors/material: Steel Doors/type: Swinging

Doors/locking: Remote locking; manual

locking

Floor surface: Sealed concrete

Intercom: Two-way to cells and common

areas

HVAC: Air conditioning; oil-fired heating Plumbing: Stainless combination unit

Furniture: Steel

Fire protection: Smoke detectors and sprinklers for cells and common areas

#### **Inmate design capacity**

Single occupancy: 131 Double occupancy: 0

Dorms: 0

Special housing: 0 General population: 131

Total: 131

# **Current staff**

Full-time equivalent: Administration: 0 Security: 10

Programs/treatment: 0 Maintenance: 0

Total: 10 (expansion only)
Current inmate/staff ratio: 18.1:1


#### Architect's reported analyses

Factors affecting construction costs:

Positive: None Negative: None

Factors affecting time schedule:

Positive: None Negative: None



# **Prince George's County Correctional Center**

Jurisdiction official: Parris N. Glendening, County Executive

Contact: Samuel F. Saxton, Director, Prince George's County Correctional Center, 13400 Dille Drive, Upper Marlboro, MD 20772,

301-952-7015

Architects: Maguire Group Architects, 5203 Leesburg Pike, Suite 200, Falls Church, VA 22401, 703-998-0100

Greenhorne & O'Mara, 9001 Edmonston Road, Greenbelt, MD 20770, 301-982-2800

Construction manager: Morrison-Knudsen/Parametric Co., P.O. Box 549, 14524 Elm Street, 3rd Floor, Upper Marlboro,

MD 20772, 301–627–6730

Groundbreaking: October 1985 Finish date: February 1987 Construction time: 16 months

Design capacity: 596 Total cost: \$43,000,000 Total annual operating costs:

\$11,679,000

Category: New, independent facility

Facility type: County jail

**Building configuration:** Integrated

structure

#### Costs

Total: \$43,000,000 Building only: Unknown Housing area: Unknown Housing per inmate: Unknown Housing per cell: Unknown Total per inmate: \$72,148 Total per GSF: \$165.38

Total annual operating costs: \$11,679,000

#### **Dimensions**

Gross square feet/corrections: 260,000 Gross square feet/other: 0 Gross square feet/total: 260,000 Housing area square feet: 143,430 Gross square feet per inmate: 436 Size of cells: 70 square feet (single); 2,400

(spec. dorms)

Net/gross square feet: Unknown

#### **Inmate housing areas**

Design: Module/pod Cells per unit: 48 Inmates per unit: 48

Management type: Direct supervision

June 1987 population: 711

Facility commitment: Local jail inmates Means to handle crowding: Second bunk

permanently attached to wall

# Security

Perimeter: Double fence; alarm/detection systems; razor wire on and between

fences; patrols Inmate security level: Maximum: 16% Medium: 60% Minimum: 8% Other: 16%

#### **Construction type**

Structural: Cast-in-place concrete frame Exterior walls: CMU block; brick Interior walls: Cast-in-place concrete;

CMU block

Exterior surface/facade: Brick

# Construction process

Finance method: G.O. Bonds; State funds Contract method: Construction manage-

ment fast track

Use of inmate labor: None Use of prefabrication: None

#### **Inmate cells**

Doors/material: Solid; wooden

Doors/type: Swinging

Doors/locking: Remote locking; manual

locking

Floor surface: Sealed concrete Intercom: Two-way to common areas HVAC: Air conditioning; hot water,

methane gas Plumbing: China Furniture: Steel

Fire protection: Sprinklers for cells and

common areas

# Inmate design capacity

Single occupancy: 432 Double occupancy: 0

Dorms: 0

Special housing: 164 General population: 432

Total: 596

# Architects' reported analyses

Factors affecting construction costs: Positive: Simple construction methods,

repetitiveness of design

Negative: None

Factors affecting time schedule:

Positive: Phased construction, fast track construction management; site package

issued early

Negative: Weather problems


#### **Current staff**

Full-time equivalent: Administration: 57 Security: 187

Programs/treatment: 36 Maintenance: 13

Total: 293

Current inmate/staff ratio: 2.43:1



# **Somerset County Detention Center**

Jurisdiction official: Charles Massey, County Administrator

Contact: Warden Keith W. Roper, Somerset County Detention Center, Route 1, Box 425, Westover, MD 21871, 301-651-9223

Architects: Dewberry & Davis, 8401 Arlington Boulevard, Fairfax, VA 22031, 703-849-0430

Phillips Swager Associates, 3622 North Knoxville Avenue, Peoria, IL 61603, 309-688-9511

Construction manager: Heery Program Management, Inc., One Rutherford Plaza, Baltimore, MD 21207, 301-944-3700

Groundbreaking: March 1985

Finish date: July 1987

Construction time: 28 months

Design capacity: 51 **Total cost:** \$2,810,000

Total annual operating costs: Unknown

Category: New, independent facility

Facility type: County jail

**Inmate housing areas** 

Inmates per unit: Unknown

October 1987 population: 27

Management type: Remote surveillance

Facility commitment: Local jail inmates

Means to handle crowding: Unknown

Design: Module/pod Cells per unit: Unknown

**Building configuration:** Integrated

structure

#### Costs

Total: \$2,810,000

Building only: \$2,663,000 Housing area: \$1,095,900

Housing per inmate: \$21,918 Housing per cell: \$21,918

Total per inmate: \$55,098 Total per GSF: \$134.49

Total annual operating costs: Unknown

#### **Dimensions**

Gross square feet/corrections: 20,894

Gross square feet/other: 0 Gross square feet/total: 20,894 Housing area square feet: 6,400 Gross square feet per inmate: 410 Size of cells: 70 square feet (single)

Net/gross square feet: 56%

# **Construction type**

Structural: Load-bearing precast panels;

precast concrete frame; masonry

construction

Exterior walls: Brick; block cavity wall Interior walls: Brick; block-bearing walls with precast plank floors and roofs

Exterior surface/facade: Split face concrete

block

Security

Perimeter: Building exterior only

Inmate security level: Maximum: 8% Medium: 39% Minimum: 31% Other: 22%

#### **Inmate cells**

Doors/material: Steel Doors/type: Swinging

Doors/locking: Remote locking Floor surface: Sealed concrete

Intercom: Two-way to cells and common

areas

HVAC: Variable air volume Plumbing: Stainless steel

Furniture: Steel

Fire protection: Smoke detectors and

sprinklers for cells

# **Inmate design capacity**

Single occupancy: 50 Double occupancy: 0

Dorms: 0

Special housing: 1 General population: 50

Total: 51

#### **Current staff**

Full-time equivalent: Administration: 3 Security: 11

Programs/treatment: 0 Maintenance: 0

Total: 14

Current inmate/staff ratio: 1.93:1

# **Construction process**

Finance method: G.O. Bonds

Contract method: Construction manage-

ment fast track

Use of inmate labor: None

Use of prefabrication: Moderate: precast concrete panels, plank floors, and roof

#### Architects' reported analyses


Factors affecting construction costs: Positive: Bid and built simultaneously with Eastern Correctional Institution using same materials and systems

Negative: None

Factors affecting time schedule:

Positive: Time was saved because of the joint projects, Somerset County Detention Center and Eastern Correctional

Institution Negative: None



# **Washington County Detention Center**

Jurisdiction official: Charles Mades, Sheriff

Contact: Lieutenant Wayne McAllister, Warden, Washington County Detention Center, 500 Western Maryland Parkway, Hagerstown,

MD 21740, 301-791-3300

Architect: Hellmuth, Obata & Kassabaum, Inc., One Lombard Street, San Francisco, CA 94111, 415-627-1600

Construction manager: None

Groundbreaking: August 1982 Finish date: February 1984 Construction time: 18 months Design capacity: 152 Total cost: \$5,869,700

Total annual operating costs:

\$1,088,334

Category: New independent facility

Facility type: County jail

Building configuration: Integrated

structure

#### **Costs**

Total: \$5,869,700

Building only: \$5,369,700 Housing area: \$3,758,790 Housing per inmate: \$25,397 Housing per cell: \$28,262

Total per inmate: \$38,616 Total per GSF: \$104.88

Total annual operating costs: \$1,088,334

# **Dimensions**

Gross square feet/corrections: 55,965

Gross square feet/other: 0 Gross square feet/total: 55,965 Housing area square feet: 27,982 Gross square feet per inmate: 368 Size of cells: 70 square feet (single)

Net/gross square feet: 72%

# **Inmate housing areas**

Design: Module/pod Cells per unit: 36 Inmates per unit: 36

Management type: Remote surveillance

October 1985 population: 142

Facility commitment: Local jail inmates Means to handle crowding: Second bunk

permanently attached to wall

# Security

Perimeter: Double fence; razor wire on

fence

Inmate security level:
Maximum: 80%
Medium: 0
Minimum: 20%

# **Construction type**

Structural: Unknown

Exterior walls: CMU block; brick Interior walls: Cast-in-place concrete;

CMU block

Exterior surface/facade: Unknown

# **Construction process**

Finance method: Local funds; State funds Contract method: Conventional Use of inmate labor: None Use of prefabrication: None

#### **Inmate cells**

Doors/material: Steel Doors/type: Swinging

Doors/locking: Remote locking only Floor surface: Sealed concrete Intercom: Two-way to common areas HVAC: Heating/air circulation only

Plumbing: Stainless Furniture: Steel

Fire protection: Smoke detectors and

sprinklers for cells

# Inmate design capacity

Single occupancy: 128 Double occupancy: 0 Dorms: 20 Special housing: 4 General population: 148

Total: 152

# Architect's reported analyses

Factors affecting construction costs: Positive: Detention specialities

Negative: None

Factors affecting time schedule: Positive: Structure independent of

masonry

Negative: Slow response and delivery of


hardware


#### Current staff

Full-time equivalent: Administration: 4 Security: 45

Programs/treatment: 4 Maintenance: 3 Total: 56

Current inmate/staff ratio: 2.54:1





#### **Second Floor**

- 1 Housing Mezzanine 2 Segregated Mezzanine 3 Female Mezzanine
- 4 Future Expansion
- 5 Mechanical Room
- 6 Upper Gymnasium 7 Work Release

# **Longwood Treatment Center (Remodel)**

Jurisdiction official: Michael V. Fair, Commissioner, Department of Correction

Contact: Superintendent David MacDonald, Longwood Treatment Center, P.O. Box 1706, 125 South Huntington Avenue, Jamaica Plain, MA 02130, 617-727-0280

State architect: Facilities Planning and Maintenance, Department of Correction, 100 Cambridge Street, Boston, MA 02202, 617-727-3300

Construction manager: Hancock Property Management, Inc. (owner of facility), 275 Hancock Street, Quincy, MA 02171, 617-770-2836

**Groundbreaking:** N/A (remodel) Finish date: August 1984 Construction time: Unknown

Design capacity: 125

Total cost: \$1,250,000 (incl. building

purchase)

**Total annual operating costs:** \$2,344,538

Category: Building purchase; remodel-

ing/renovation project

Facility type: Treatment facility for

alcoholic offenders

Building configuration: Two connected

buildings

#### Costs

Total: \$1,250,000 (incl. building purchase)

Building only: \$1,250,000 Housing area: Unknown Housing per inmate: Unknown Housing per cell: Unknown

Total per inmate: N/A (remodel) Total per GSF: Unknown

Total annual operating costs: \$2,344,538

#### **Dimensions**

Gross square feet/corrections: 38,918 Gross square feet/other: 0

Gross square feet/total: 38,918 Housing area square feet: 19,000 Gross square feet per inmate: 311

Size of cells: Varies

Net/gross square feet: Unknown

#### **Inmate housing areas**

Design: Semi-private rooms for 1 to 6

inmates

Cells per unit: Unknown Inmates per unit: Unknown

Management type: Direct supervision

August 1986 population: 125

Facility commitment: Local jail inmates;

State prisoners

Means to handle crowding: No crowding

permitted

#### Security

Perimeter: Building exterior; building exit

alarm

Inmate security level: Maximum: 0 Medium: 0 Minimum: 100%

#### **Construction type**

Structural: Wood and concrete floors; steel

frame

Exterior walls: Brick

Interior walls: Masonry and plaster Exterior surface/facade: Brick

#### **Construction process**

Finance method: Privately purchased, renovated, and leased to State Contract method: Purchased and reno-

vated by private company Use of inmate labor: None Use of prefabrication: None

#### Inmate cells

Doors/material: Wooden Doors/type: Swinging

Doors/locking: Manual locking Floor surface: Linoleum; carpet; sealed

concrete; vinyl tile

Intercom: One-way to common areas HVAC: Air conditioning; heating/air circulation; gas heat; oil burners Plumbing: Stainless steel; china Furniture: Steel: wood; vinyl/plastic Fire protection: Smoke detectors and sprinklers for common areas; manual alarm stations; sprinklers for rooms

#### **Inmate design capacity**

Single occupancy: 1 Double occupancy: 34

Dorms: 90 Special housing: 0 General population: 125

Total: 125

#### **Current staff**

Full-time equivalent: Administration: 10 Security: 23

Programs/treatment: 11

Maintenance: 2 Total: 46

Current inmate/staff ratio: 2.72:1


# Architect's reported analyses


Factors affecting construction costs: Positive: Good competition, favorable market; less expensive materials and hardware

Negative: Slow construction, lengthy building time; difficult site conditions; government procedures, regulations, and red tape

Factors affecting time schedule: Positive: Simple construction methods Negative: Slow responses and delivery from vendors, suppliers; labor problems; government procedures, regulations, and red tape

# EXISTING 2nd FLOOR







# Massachusetts Correctional Institution Norfolk (Visitors' **Center Addition**)

Jurisdiction official: Michael V. Fair, Commissioner, Department of Correction

Contact: Superintendent Norman J. Butler, Massachusetts Correctional Institution Norfolk, P.O. Box 43, Norfolk, MA 02056,

617-668-0800

Architect: Donham & Sweeney, Architects, 103 Broad Street, Boston, MA 02110, 617-423-4280

Construction manager: None

Groundbreaking: October 1984

Finish date: May 1986 **Construction time:** 19 months Design capacity: N/A **Total cost:** \$898,000

Total annual operating costs: \$109,000

(addition only)

Category: New, ancillary building Facility type: State prison visitors

center

**Building configuration:** Integrated structure; wheel, spoke or radial

#### Costs

Total: \$898,000

Building only: \$830,000 Housing area: Unknown Housing per inmate: Unknown Housing per cell: Unknown

Total per inmate: N/A Total per GSF: \$84.41

Total annual operating costs: \$109,000

(addition only)

#### **Dimensions**

Gross square feet/corrections: 10,638

Gross square feet/other: 0 Gross square feet/total: 10,638 Housing area square feet: N/A Gross square feet per inmate: N/A

Size of cells: N/A

Net/gross square feet: Unknown

# **Inmate housing areas**

Design: N/A Cells per unit: N/A Inmates per unit: N/A Management type: N/A

October 1985 population: N/A

Facility commitment: Local jail inmates;

State prisoners

Means to handle crowding: N/A

#### Security

Perimeter: Single fence; towers; wall

Inmate security level: Maximum: 0 Medium: 100% Minimum: 0

# Construction type

Structural: Laminated wood columns,

beams, and trusses Exterior walls: Brick Interior walls: CMU block Exterior surface/facade: Brick

#### **Construction process**

Finance method: State funds Contract method: Conventional Use of inmate labor: None Use of prefabrication: None

#### **Inmate cells (rooms)**

Doors/material: Steel Doors/type: Swinging

Doors/locking: Manual locking

Floor surface: Vinyl tile

Intercom: None

HVAC: Heating/air circulation; steam heat; steam from existing plant used to

heat water

Plumbing: Stainless steel; china Fire protection: Smoke detectors

# Inmate design capacity

Single occupancy: N/A Double occupancy: N/A

Dorms: N/A

Special housing: N/A General population: N/A Total: N/A (no inmates)

#### **Architect's reported analyses**

Factors affecting construction costs: Positive: Simple construction methods,

repetitiveness of design

Negative: Slow construction, lengthy

building time

Factors affecting time schedule:


Positive: None Negative: None

#### **Current staff**

Full-time equivalent: Administration: 0

Security: 2 Programs/treatment: 0 Maintenance: 0

Total: 2 (addition only) Current inmate/staff ratio: N/A



# Correction Camp Cusino

Jurisdiction official: Robert Brown, Jr., Director, Department of Corrections

Contact: S. George Field, Camp Supervisor-Deputy Warden, Correction Camp Cusino, Box 88, Shingleton, MI 49884-0088,

906-452-6248

Architect: Blomquist/Nelson & Associates, 116 East Ludington Street, Iron Mountain, MI 49801, 906-774-7000

Construction manager: None

Groundbreaking: April 1986 Finish date: December 1986

Construction time: 8 months

Design capacity: 160 Total cost: \$3,800,000

Total annual operating costs: Unknown

Category: New, independent facility; phased project (future)

Facility type: State prison

**Building configuration:** Integrated

structure

#### Costs

Total: \$3,800,000

Building only: \$3,500,000 Housing area: \$3,200,000 Housing per inmate: \$20,000 Housing per cell: \$20,000 Total per inmate: \$23,750 Total per GSF: \$59.38

Total annual operating costs: Unknown

#### **Dimensions**

Gross square feet/corrections: 64,000

Gross square feet/other: 0 Gross square feet/total: 64,000 Housing area square feet: 46,000 Gross square feet per inmate: 400 Size of cells: 80 square feet (single)

Net/gross square feet: 91%

#### **Inmate housing areas**

Design: Module/pod Cells per unit: 20 Inmates per unit: 20

Management type: Intermittent

surveillance

October 1987 population: 252 Facility commitment: State prisoners Means to handle crowding: Beds in dayroom; bunk beds in visiting room

# Security

Perimeter: Single fence Inmate security level: Maximum: 0 Medium: 0

Minimum: 100%

#### **Construction type**

Structural: Load-bearing CMU with

hollow core slabs Exterior walls: CMU block Interior walls: CMU block

Exterior surface/facade: Paint; waterproof

coating

# Construction process

Finance method: State funds Contract method: Conventional Use of inmate labor: None

Use of prefabrication: Limited; precast

structure

#### **Inmate cells**

Doors/material: Steel Doors/type: Swinging

Doors/locking: Manual locking Floor surface: Carpet; vinyl tile Intercom: Two-way to common areas HVAC: Heating/air circulation; woodfired boilers for heating and hot water

Plumbing: China Furniture: Steel

Fire protection: Manual alarm stations; smoke detectors for common areas and storage; sprinklers for some storage

#### **Inmate design capacity**

Single occupancy: 160 Double occupancy: 0

Dorms: 0

Special housing: 0 General population: 160

Total: 160

#### Current staff

Full-time equivalent: Administration: 16 Security: 22

> Programs/treatment: 1 Maintenance: 2

Total: 41

Current inmate/staff ratio: 6.15:1

# Architect's reported analyses

Factors affecting construction costs: Positive: Simple construction methods, repetitiveness of design; less expensive materials and hardware, low security

Negative: None

Factors affecting time schedule: Positive: Good contractor

Negative: Government procedures,

regulations, and red tape

# **Grand Traverse County Correctional Facility (Remodel/Expansion)**

Jurisdiction official: Jack J. Canfield, Sheriff

Contact: Joseph D. Smith, Corrections Administrator, Grand Traverse County Correctional Facility, 320 Washington Street, Traverse

City, MI 49684, 616-922-4500

Architects: GBKB Associates, Hannah Lay Building, 109 East Front Street, Suite 303, Traverse City, MI 49684, 616-946-7116

Durrant Group, 2445 Darwin Road, Madison, WI 53704, 608-241-3340

Construction manager: None

Groundbreaking: January 1985

Finish date: May 1986 Construction time: 16 months Design capacity: 126 Total cost: \$3,199,852

Total annual operating costs: \$1,009,680

Category: Remodeling/renovation proj-

ect; expansion

Facility type: Complex: county and city

jails, law enforcement

Building configuration: Ladder,

telephone pole

#### **Costs**

Total: \$3,199,852 Building only: Unknown

Housing area: \$1,788,570 Housing per inmate: \$17,034 Housing per cell: \$55,893

Total per inmate: N/A (complex)

Total per GSF: \$55.01

Total annual operating costs: \$1,009,680

#### **Dimensions**

Gross square feet/corrections: 24,041 Gross square feet/other: 34,123 Gross square feet/total: 58,164 Housing area square feet: 21,042 Gross square feet per inmate: 191

Size of cells: 78 square feet (double) Net/gross square feet: 89%

# Design: Linear, outside and interior; module/pod

**Inmate housing areas** 

Cells per unit: 8

Cells per unit: 8 Inmates per unit: 16

Management type: Intermittent and

remote surveillance

September 1986 population: 108 Facility commitment: Local jail inmates;

State and Federal prisoners

Means to handle crowding: Bunk beds in

cell; mattresses on floor

#### **Security**

Perimeter: Single fence Inmate security level: Maximum: 4% Medium: 80%

Minimum: 16%

# Construction type

Structural: Precast plank-wall bearing Exterior walls: CMU block; limestone

facing

Interior walls: CMU block; metal stud and

gypsum board

Exterior surface/facade: Limestone

# **Construction process**

Finance method: Federal and local funds; shared cost from multiple jurisdictions

Contract method: Conventional Use of inmate labor: None Use of prefabrication: Limited

#### **Inmate cells**

Doors/material: Steel Doors/type: Swinging

Doors/locking: Motor driven and remote

locking; manual locking
Floor surface: Sealed concrete
Intercom: Two-way to cells
HVAC: Air conditioning; gas heat
Plumbing: Stainless combination unit

Furniture: Steel

Fire protection: Smoke detectors and sprinklers for cells and common areas

# Inmate design capacity

Single occupancy: 5 Double occupancy: 32

Dorms: 68

Special housing: 21 General population: 105

Total: 126

#### **Current staff**

Full-time equivalent: Administration: 2 Security: 16

Programs/treatment: 4 Maintenance: 3

Total: 25

Current inmate/staff ratio: 4.32:1

#### Architects' reported analyses

Factors affecting construction costs: Positive: Good competition, favorable

market


Negative: Slow construction, lengthy building time; government procedures, regulations, and red tape; subcontractor's bankruptcy—new subcontractor increased cost

Factors affecting time schedule:

Positive: Simple construction methods,

repetitiveness of design

Negative: Slow responses and delivery from vendors, suppliers; weather problems; government red tape; complex electronic, mechanical, and electrical systems; approval of new subcontractor



# Macomb County Jail (Remodel/Expansion)

Jurisdiction official: William Hackel, Sheriff

Contact: Donald Amboyer, Jail Administrator, Macomb County Jail, 43565 Elizabeth Road, Mt. Clemens, MI 48043, 313–469–5024

Architect: Hellmuth, Obata and Kassabaum, Inc., 100 North Broadway, St. Louis, MO 63102, 314-421-2000

Construction manager: None

Groundbreaking: October 1984

Finish date: June 1987

Construction time: 32 months

**Design capacity:** 463 **Total cost:** \$27,000,000

Total annual operating costs: N/A

(expansion)

Category: Remodeling/renovation project; expansion project
Facility type: County jail

Building configuration: High rise

**Inmate housing areas** 

Cells per unit: Unknown

Inmates per unit: Unknown

November 1987 population: 900

State prisoners on contract

Means to handle crowding: Double bunking; renovation of old section

Management type: Remote surveillance

Facility commitment: Local jail inmates;

Design: Module/pod

**Costs** 

Total: \$27,000,000 Building only: Unknown

Housing area: Unknown

Housing per inmate: Unknown Housing per cell: Unknown

Total per inmate: N/A (remodel)

Total per GSF: \$133.64

Total annual operating costs: N/A

(expansion)

**Security** 

Perimeter: Video camera surveillance

Inmate security level:
Maximum: 25%
Medium: 50%
Minimum: 25%

Dimensions

Gross square feet/corrections: 202,042

Gross square feet/other: 0 Gross square feet/total: 202,042 Housing area square feet: 167,938 Gross square feet per inmate: 436

Size of cells: Unknown

Net/gross square feet: Unknown

**Construction type** 

Structural: Clay security facing tile Exterior walls: Cast-in-place concrete Interior walls: Cast-in-place concrete

Exterior surface/facade: Brick

Inmate design capacity

Single occupancy: 324

Double occupancy: 0

Special housing: 35

General population: 428

Dorms: 104

Total: 463

**Construction process** 

Finance method: Local funds Contract method: Conventional Use of inmate labor: None Use of prefabrication: None

**Inmate cells** 

Doors/material: Steel Doors/type: Swinging

Doors/locking: Remote locking; manual

locking

Floor surface: Carpet; epoxy coating;

sealed concrete

Intercom: Two-way to cells and common

areas

HVAC: Air conditioning; gas-fired boilers

Plumbing: Stainless steel

Furniture: Steel; vinyl/plastic

Fire protection: Smoke detectors and sprinklers for cells and common areas

Current staff

Full-time equivalent:

Administration: Unknown

Security: Unknown

Programs/treatment: Unknown

Maintenance: Unknown

Total: Unknown

Current inmate/staff ratio: Unknown

Architect's reported analyses

Factors affecting construction costs: Positive: Simple construction methods,

repetitiveness of design

Negative: None

Factors affecting time schedule:

Positive: Simple construction methods,

repetitiveness of design

Negative: Weather problems, construction

started in late fall

(No floorplan available at time of publication)

# **State Prison of Southern Michigan (Hospital Addition)**

Jurisdiction official: Robert Brown, Jr., Director, Department of Corrections

Contact: Larry N. Coe, Physical Plant Superintendent, State Prison of Southern Michigan, 4000 Cooper Street, Jackson, MI 49201,

517-788-7560

Architect: Louis G. Redstone Associates, Inc., 28425 West Eight Mile Road, Livonia, MI 48152, 313-476-6620

Construction manager: None

Groundbreaking: December 1983 Finish date: February 1986 Construction time: 26 months Design capacity: 94
Total cost: \$9,717,255
Total annual operating costs: \$12,000,000 (hospital)

Category: New, ancillary building Facility type: State prison hospital Building configuration: Integrated

structure

Costs

Total: \$9,717,255 Building only: \$8,479,255 Housing area: N/A (hospital) Housing per inmate: N/A Housing per cell: N/A

Total per inmate: N/A (addition)

Total per GSF: \$95.83

Total annual operating costs: \$12,000,000

(hospital)

**Security** 

Perimeter: Building exterior; double fence; alarm/detection systems; razor

wire on fence Inmate security level: Maximum: 80% Medium: 20% Minimum: 0

**Inmate cells** 

Doors/material: Steel Doors/type: Swinging

Doors/locking: Remote locking; manual

locking

Floor surface: Sheet vinyl

Intercom: Staff to staff only; patients

have call button

HVAC: Air conditioning; steam from

central heating plant Plumbing: Stainless; china

Furniture: Steel

Fire protection: Smoke detectors for common areas; sprinklers throughout

**Dimensions** 

Gross square feet/corrections: 101,400

Gross square feet/other: 0 Gross square feet/total: 101,400 Housing area square feet: N/A (hospital) Gross square feet per inmate: 1,079

Size of cells: N/A (hospital) Net/gross square feet: 54%

**Construction type** 

Structural: Cast-in-place concrete frame

Exterior walls: Brick

Interior walls: CMU block; plaster on lath

Exterior surface/facade: Brick

Inmate design capacity

Single occupancy: 0 Double occupancy: 0

Dorms: 0

Special housing: 94 General population: 0

Total: 94

Current staff

Full-time equivalent:
Administration: 12
Security: 50

Programs/treatment: 292

Maintenance: 4 Total: 358 (hospital)

Current inmate/staff ratio: .26:1

Inmate housing areas

Design: Linear, outside Cells per unit: N/A Inmates per unit: 94

Management type: Intermittent

surveillance

October 1985 population: 94

Facility commitment: State prison patients

Means to handle crowding: N/A

**Construction process** 

Finance method: State funds Contract method: Conventional Use of inmate labor: None

Use of prefabrication: Limited; brick soffit

panels

Architect's reported analyses

Factors affecting construction costs:
Positive: Good competition, favorable
market; no major security provisions

necessary


Negative: Government procedures, regulations, "red tape"; complex remote locking, mechanical, and electrical

systems

Factors affecting time schedule: Positive: Simple construction methods, repetitiveness of design; coordination

of design between parties

Negative: Slow responses and delivery from vendors, suppliers; government procedures, regulations, "red tape"



# **Hennepin County Juvenile Detention Center**

Jurisdiction official: Mike Cunniff, Associate County Administrator, Bureau of Community Corrections

Contact: Superintendent Arthur J. Cavara, Hennepin County Juvenile Detention Center, 510 Park Avenue, Minneapolis, MN 55415,

612-348-3894

Architect: Ellerbe Associates, Inc., One Appletree Square, Minneapolis, MN 55420, 612-853-2000

Construction manager: None

**Groundbreaking:** June 1982 Finish date: June 1984 Construction time: 24 months **Design capacity: 87 Total cost:** \$13,000,000

**Total annual operating costs:** \$3,001,716

Category: New, independent facility Facility type: County juvenile detention

Building configuration: Integrated

structure; courtyard

Costs

Total: \$13,000,000

Building only: \$12,500,000 Housing area: \$6,000,000 Housing per inmate: \$68,966 Housing per cell: \$68,966 Total per inmate: \$149,425

Total per GSF: \$101.56

Total annual operating costs: \$3,001,716

Structural: Cast-in-place concrete frame: grout filled concrete block and rebar

grout filled cores

Exterior surface/facade: Brick; colored

**Security** 

Perimeter: Single fence; video camera surveillance

Inmate security level: Maximum: 5% Medium: 95% Minimum: 0

Inmate cells

Doors/material: Steel Doors/type: Swinging

Doors/locking: Motor driven and remote

locking; manual locking

Floor surface: Epoxy coating; carpet Intercom: Two-way to cells and common

HVAC: Air conditioning; steam heat

Plumbing: Stainless Furniture: Concrete

Fire protection: Smoke detectors and sprinklers for cells and common areas **Dimensions** 

Gross square feet/corrections: 128,000

Gross square feet/other: 0 Gross square feet/total: 128,000 Housing area square feet: 60,000 Gross square feet per inmate: 1,471 Size of cells: 75.5 square feet (single)

Net/gross square feet: 75%

Construction type

Exterior walls: Brick; cast-in-place con-

crete; CMU block

Interior walls: Cast-in-place concrete; CMU block; brick; concrete block with

concrete

**Inmate design capacity** 

Single occupancy: 87 Double occupancy: 0

Dorms: 0

Special housing: 0 General population: 87

Total: 87

**Current staff** 

Full-time equivalent: Administration: 7 Security: 64

> Programs/treatment: 2 Maintenance: 0

Total: 73

Current inmate/staff ratio: 0.88:1

**Inmate housing areas** 

Design: Module/pod Cells per unit: 12 Inmates per unit: 12

Management type: Intermittent surveil-

lance; direct supervision March 1987 population: 64 Facility commitment: Juveniles Means to handle crowding: Release of

residents; restrict admissions

**Construction process** 

Finance method: Local funds Contract method: Conventional Use of inmate labor: None Use of prefabrication: None

Architect's reported analyses

Factors affecting construction costs: Positive: Healthy bidding climate

Negative: None

Factors affecting time schedule:

Positive: None Negative: None (No floorplan available at time of publication)

# **Minnesota Supervised Living Facility (Addition)**

Jurisdiction official: Orville B. Pung, Commissioner, Department of Corrections

Contact: William Pederson, Chief Executive Officer, Minnesota Supervised Living Facility, 100 Freeman Drive, St. Peter, MN

56082, 507-931-7100

Architect: Hammel Green & Abrahamson, Inc., 1201 Harmon Place, Minneapolis, MN 55403, 612-332-3944

Construction manager: None

Groundbreaking: October 1979

Finish date: June 1981

Construction time: 21 months

Design capacity: 164
Total cost: \$8,389,800

**Total annual operating costs:** 

N/A (addition)

**Category:** New, ancillary building **Facility type:** State prison for criminally

insane

Building configuration: Integrated

structure with courtyard

#### **Costs**

Total: \$8,389,800

Building only: \$7,189,800

Housing area: \$5,578,846 Housing per inmate: \$34,017

Housing per cell: \$46,106

Total per inmate: \$51,157

Total per GSF: \$68.80

Total annual operating costs: N/A

(addition)

# **Security**

Perimeter: Building exterior; razor wire on and between fences; wire netting over interior courtyards; double fence

around recreation area Inmate security level: Maximum: 60%

Medium: 40% Minimum: 0

#### Inmate cells

Doors/material: Steel Doors/type: Swinging

Doors/locking: Remote locking

Floor surface: Carpet or epoxy coating Intercom: Two-way to common areas

HVAC: Air conditioning; steam boiler heating plant pumps hot water to building fan coils, radiation,

convectors, and heating coils

Plumbing: Stainless combination unit Furniture: Steel; wood; vinyl/plastic;

concrete

Fire protection: Smoke detectors for

common areas

#### **Dimensions**

Gross square feet/corrections: 121,939

Gross square feet/other: 0 Gross square feet/total: 121,939 Housing area square feet: 81,574 Gross square feet per inmate: 744

Size of cells: 91 square feet (single); 134 (double); 331 (4-bed) Net/gross square feet: 84%

# **Construction type**

Structural: Steel frame; CIP concrete

frame

Exterior walls: Precast panels/decking; CIP concrete; CMU block; brick Interior walls: CIP concrete; CMU block

Exterior surface/facade: Brick

#### Inmate design capacity

Single occupancy: 86 Double occupancy: 62

Dorms: 0 Other: 16

Special housing: 0 General population: 164

Total: 164

#### **Current staff**

Full-time equivalent:

Administration: Unknown

Security: Unknown

Programs/treatment: Unknown

Maintenance: Unknown

Total: 160 to 170 (addition only) Current inmate/staff ratio: Approx. 1:1

#### **Inmate housing areas**

Design: Linear, outside, inside Cells per unit: 16 to 24

Inmates per unit: 16 to 32

Management type: Direct supervision;

remote surveillance

October 1985 population: Approx. 165 Facility commitment: State prisoners;

local jail inmates

Means to handle crowding: Unknown

# **Construction process**

Finance method: State funds Contract method: Conventional Use of inmate labor: None Use of prefabrication: Limited

#### Architect's reported analyses


Factors affecting construction costs:
Positive: Simple construction methods,

repetitiveness of design; good competition, favorable market

Negative: Difficult site conditions

Factors affecting time schedule:
Positive: Simple construction methods,
repetitiveness of design; advanced
order of materials and hardware;
coordination of design between parties
Negative: Government procedures,

regulations, "red tape"



# **Jackson County Adult Detention Center**

Jurisdiction official: D.B. Pope, Sheriff

Contact: Fearon Jenne III, Director, Adult Detention Center, 1719 Kenneth Avenue, Pascagoula, MS 39567, 601–769–3052

Architect: Slaughter & Allred, P.A., A.I.A., P.O. Box 447, 3690 14th Street, Pascagoula, MS 39567, 601-762-1975

Construction manager: None

**Groundbreaking:** January 1978

Finish date: May 1979

**Construction time:** 16 months

**Design capacity:** 99 **Total cost:** \$1,362,291

**Total annual operating costs:** 

\$1,028,776

Category: New, independent facility

Facility type: County jail

Building configuration: Integrated

structure

#### Costs

Total: \$1,362,291

Building only: \$1,287,137 Housing area: \$994,544 Housing per inmate: \$12,589 Housing per cell: \$12,589 Total per inmate: \$13,761 Total per GSF: \$61.70

Total annual operating costs: \$1,028,776

#### **Dimensions**

Gross square feet/corrections: 22,078

Gross square feet/other: 0 Gross square feet/total: 22,078 Housing area square feet: 16,818 Gross square feet per inmate: 223 Size of cells: 80 square feet (single)

Net/gross square feet: N/A

# Inmate housing areas

Design: Module/pod Cells per unit: 18 Inmates per unit: 18

Management type: Intermittent surv. October 1985 population: 105

Facility commitment: Local jail inmates

and State prisoners

Means to handle crowding: Mattresses on floor; second bunk permanently

attached to wall

# Security

Perimeter: Single fence; razor wire

on fence

Inmate security level: Maximum: 8%

Medium: 68%

Minimum: 20% (+ 4% safety cells)

# **Construction type**

Structural: Load bearing precast panels

Exterior walls: Precast panels Interior walls: Precast panels; CMU block

Exterior surface/facade: Textureflex coating on concrete panels

# **Construction process**

Finance method: Federal and local funds

Contract method: Conventional Use of inmate labor: None Use of prefabrication: Limited

#### **Inmate cells**

Doors/material: Steel Doors/type: Swinging

Doors/locking: Remote locking only Floor surface: Sealed concrete Intercom: One-way to common areas

HVAC: Air conditioning

Plumbing: Stainless combination unit

Furniture: Steel

Fire protection: Smoke detectors for common areas; manual alarm stations; exhaust fans interlocked with

smoke detectors in ducts

## Inmate design capacity

Single occupancy: 79 Double occupancy: 0

Dorms: 0

Special housing: 20 General population: 79

Total: 99

#### **Current staff**

Full-time equivalent: Administration: 6 Security: 22

Programs/treatment: 2 Maintenance: 6

Total: 36

Current inmate/staff ratio: 2.92:1

#### Architect's reported analyses

Factors affecting construction costs:
Positive: Precast concrete wall and roof panels; good competition, favorable

market


Negative: Complex electronic, mechanical, and electrical systems

Factors affecting time schedule:

Positive: Precast concrete wall and roof panels; simple construction methods, repetitiveness of design; coordination

of design between parties Negative: Weather problems; security

glass problems



# Mississippi State Penitentiary—Unit 29

Jurisdiction official: Gene A. Scroggy, Commissioner, Department of Corrections

Contact: Deputy Warden Dwight Presley, Mississippi State Penitentiary—Unit 29, Parchman, MS 38738, 601-745-6611 Architect: The Design Collective, P.A., P.O. Box 22678, 777 North State Street, Jackson, MS 39205, 601–969–7113

Construction manager: None

Groundbreaking: June 1979 Finish date: September 1981 Construction time: 28 months Design capacity: 1,576 Total cost: \$18,706,145 Total annual operating costs:

\$6,200,000

Category: New, independent facility

Facility type: State prison

Building configuration: Campus style

#### **Costs**

Total: \$18,706,145 Building only: \$14,924,901 Housing area: \$12,178,475 Housing per inmate: \$7,727 Housing per cell: \$23,153 Total per inmate: \$11,869

Total per GSF: \$86.43

Total annual operating costs: \$6,200,000

## **Dimensions**

Gross square feet/corrections: 216,426 Gross square feet/other: 0 Gross square feet/total: 216,426

Housing area square feet: 175,950 Gross square feet per inmate: 137 Size of cells: 70 square feet (single)

Net/gross square feet: 92%

# **Security**

Perimeter: Double fence; alarm/detection systems; razor wire on fence; towers;

patrols

Inmate security level: Maximum: 0 Medium: 33.5% Minimum: 66.5%

# Construction type

Structural: Load bearing precast panels; precast concrete frame

Exterior walls: Precast panels; architectural precast

Interior walls: Precast panels; CMU block

Exterior surface/facade: Textured

concrete

#### Inmate design capacity

Single occupancy: 176 Double occupancy: 0 Dorms: 1,400 Special housing: 0 General population: 1,576

#### **Inmate cells**

Doors/material: Solid steel Doors/type: Swinging

Doors/locking: Motor driven and remote

locking

Floor surface: Sealed concrete; tile Intercom: Two-way to cells

HVAC: Heating/air circulation only

Plumbing: Stainless Furniture: Steel

Fire protection: Smoke detectors for cells

and common areas

Total: 1,576

#### **Current staff**

Full-time equivalent: Administration: 4 Security: 221

Programs/treatment: 56

Maintenance: 2 Total: 283

Current inmate/staff ratio: 5.14:1

#### **Inmate housing areas**

Design: Module/pod Cells per unit: 12

Inmates per unit: 44 (single cell bldgs.);

64 (dorm bldgs.)

Management type: Remote surveillance October 1985 population: 1,456 Facility commitment: State prisoners;

local jail inmates

Means to handle crowding: N/A

# **Construction process**

Finance method: Shared cost from

multiple jurisdictions

Contract method: Conventional Use of inmate labor: None


Use of prefabrication: Extensive, elements made at plant and shipped to job site

# Architect's reported analyses

Factors affecting construction costs: Positive: Use of prefabricated components, factory assembly; simple construction methods, repetitiveness of design; phased construction, fast track construction management Negative: Difficult site conditions (landfill required)

Factors affecting time schedule: Positive: Use of prefabricated components, factory assembly; simple construction methods, repetitiveness of design Negative: Weather problems; difficult

site conditions



# Tunica County Jail and Sheriff's Department

Jurisdiction official: Hugh M. Monteith, Jr., Sheriff

Contact: Sheriff Hugh M. Monteith, Jr., Tunica County Jail and Sheriff's Department, South Court Street, P.O. Box 25,

Tunica, MS 38676, 601-363-1411

Architect: Pritchard & Nickles, Engineers/Planners, P.O. Box 727, 245 First South Street East, Tunica, MS 38676, 601–363–1811 Construction manager: Pritchard & Nickles, P.O. Box 727, 245 First South Street East, Tunica, MS 38676, 601-363-1811

**Groundbreaking:** October 1978 Finish date: August 1980

Construction time: 22 months

**Design capacity: 33 Total cost:** \$816.893

Total annual operating costs: \$115,500

Category: New, independent facility Facility type: Complex: county jail, law

enforcement

Building configuration: Integrated

structure

**Costs** 

Total: \$816.893

Building only: \$789,984 Housing area: \$469,768 Housing per inmate: \$15,659 Housing per cell: \$16,199

Total per inmate: N/A (complex)

Total per GSF: \$71.83

Total annual operating costs: \$115,500

**Dimensions** 

Gross square feet/corrections: 9,345 Gross square feet/other: 0 Gross square feet/total: 11,373 Housing area square feet: 7,227 Gross square feet per inmate: 283 Size of cells: 71 square feet (gen. single); 146 (double); 67 (spec. single)

Net/gross square feet: 75%

**Inmate housing areas** 

Design: Linear, inside Cells per unit: 32 Inmates per unit: 33

Management type: Intermittent surveil-

September 1986 population: 38

Facility commitment: Local jail inmates;

State prisoners

Means to handle crowding: Bunk beds in

cell; beds in dayroom

**Security** 

Perimeter: Building exterior; single fence;

patrols

Inmate security level: Maximum: 5% Medium 95% Minimum: 0

**Construction type** 

Structural: Load bearing CMU

Exterior walls: CMU block; brick; architec-

tural precast

Interior walls: Precast panels; CMU block Exterior surface/facade: Brick; textured

concrete

**Construction process** 

Finance method: G.O. Bonds; Federal

funds

Contract method: Conventional Use of inmate labor: None

Use of prefabrication: Moderate; precast floor slabs and exterior stone fascia

Architect's reported analyses

Inmate cells

Doors/material: Steel Doors/type: Sliding

Doors/locking: Motor driven and remote

locking

Floor surface: Sealed concrete

Intercom: None

HVAC: Air conditioning; gas heat Plumbing: China; stainless combination

unit

Furniture: Steel

Fire protection: Smoke detectors for cells and common areas; manual alarm stations: thermal detectors

Inmate design capacity

Single occupancy: 28 Double occupancy: 2

Dorms: 0

Special housing: 3 General population: 30

Total: 33

Factors affecting construction costs:

Positive: Prefabricated components, factory assembly; simple construction methods, repetitiveness of design

Negative: None

Factors affecting time schedule:

Positive: Use of prefabricated components, factory assembly; simple construction methods, repetitiveness of design; coordination of design between

parties

Negative: Weather problems; government procedures, regulations, and red tape


**Current staff** 

Full-time equivalent: Administration: 4 Security: 3

> Programs/treatment: 0 Maintenance: 1

Total: 8

Current inmate/staff ratio: 4.75:1



# **Clay County Detention Center**

Jurisdiction official: Jack Corum, Sheriff

Contact: Captain Mary Richardson, Jail Administrator, Clay County Detention Center, 14 South Water Street, Liberty, MO 64068,

816-792-7625

Architect: Abend Singleton Associates, 20 West Ninth, Kansas City, MO 64105, 816–221–5011 Construction manager: Cecil Lovett, 27 South Leonard, Liberty, MO 64068, 816–781–4189

Groundbreaking: December 1982 Finish date: February 1985 Construction time: 26 months

Design capacity: 161 **Total cost:** \$6,230,000 Total annual operating costs: \$1,464,949

Justice Complex)

Category: New, independent facility Facility type: County jail (as part of

**Building configuration:** Clusters

# **Costs**

Total: \$6,230,000 Building only: Unknown Housing area: Unknown Housing per inmate: Unknown Housing per cell: Unknown Total per inmate: \$38,696 Total per GSF: \$102.98

Total annual operating costs: \$1,464,949

# **Dimensions**

Gross square feet/corrections: 60,500 Gross square feet/other: 0 Gross square feet/total: 60,500 Housing area square feet: 34,600 Gross square feet per inmate: 376 Size of cells: 70 square feet (single);

90 square feet (double) Net/gross square feet: Unknown

# **Inmate housing areas**

Design: Module/pod Cells per unit: 10 to 20 Inmates per unit: 10 to 20

Management type: Remote surveillance

October 1985 population: 131

Facility commitment: Local jail inmates Means to handle crowding: Second bunk

permanently attached to wall

# Security

Perimeter: Building exterior only Inmate security level:

Maximum: 15% (design: 100%)

Medium: 20% Minimum: 65%

# **Construction type**

Structural: Masonry Exterior walls: Masonry Interior walls: Masonry

Exterior surface/facade: Masonry

#### **Construction process**

Finance method: G.O. Bonds Contract method: Conventional Use of inmate labor: None Use of prefabrication: None

#### **Inmate cells**

Doors/material: Steel Doors/type: Swinging

Doors/locking: Remote locking Floor surface: Sealed concrete

Intercom: Two-way to cells and common

areas

HVAC: Air conditioning; heating includes computerized energy management

system

Plumbing: Stainless steel

Furniture: Steel

Fire protection: Smoke detectors for cells

#### **Inmate design capacity**

Single occupancy: 100 Double occupancy: 32

Dorms: 0 Other: 20

Special housing: 9 General population: 152

Total: 161

# Architect's reported analyses

Factors affecting construction costs: Positive: Good competition, favorable market; less expensive materials and hardware

Negative: Slow construction, lengthy building time; difficult site conditions

Factors affecting time schedule:

Positive: None Negative: None


#### **Current staff**

Full-time equivalent: Administration: 5 Security: 38

> Programs/treatment: 3 Maintenance: 5

Total: 51

Current inmate/staff ratio: 2.57:1



# Farmington Correctional Center (Addition/Remodel)

Jurisdiction official: Dick D. Moore, Director, Department of Corrections and Human Resources

Contact: Superintendent Denis Dowd, Farmington Correctional Center, 1012 West Columbia, Farmington, MO 63640, 314-756-8001

Architect: Jones Mayer Architecture, Inc., 2190 South Mason Road, St. Louis, MO 63131, 314–965–3400 Construction manager: Hercules Construction Company, 8820 Delmar, St. Louis, MO 63124, 314–991–3730

Groundbreaking: April 1985 Finish date: January 1987 Construction time: 21 months

**Design capacity:** 1,100 **Total cost:** \$37,000,000

Total annual operating costs: N/A

(addition)

Category: New, ancillary building; remodeling/renovation project
Facility type: State prison

**Building configuration:** Campus style

#### **Costs**

Total: \$37,000,000 Building only: Unknown Housing area: \$16,368,524 Housing per inmate: \$18,707 Housing per cell: \$18,707

Total per inmate: N/A (remodel)

Total per GSF: \$78.44

Total annual operating costs: N/A

(addition)

# **Security**

Perimeter: Double fence; alarm/detection systems; razor wire on fences; patrols;

video camera surveillance

Inmate security level:
Maximum: 0
Medium: 100%
Minimum: 0

#### Inmate cells

Doors/material: Steel Doors/type: Swinging

Doors/locking: Remote locking Floor surface: Sealed concrete

Intercom: One-way to cells and common

areas

HVAC: Heating/air circulation; steam

heat

Plumbing: China Furniture: Steel

Fire protection: Smoke detectors for cells;

sprinklers for common areas

#### **Dimensions**

Gross square feet/corrections: 471,720 Gross square feet/other: 0

Gross square feet/total: 471,720 Housing area square feet: 203,976 Gross square feet per inmate: 429 Size of cells: 82 square feet (single) Net/gross square feet: Unknown

#### **Construction type**

Structural: Load-bearing masonry Exterior walls: CMU block; brick

Interior walls: Precast panels; cast-in-place

concrete; CMU block Exterior surface/facade: Brick

#### Inmate design capacity

Single occupancy: 875 Double occupancy: 0

Dorms: 0

Special housing: 225 General population: 875

Total: 1,100

#### Current staff

Full-time equivalent: Administration: 17 Security: 334

Programs/treatment: 24 Maintenance: 37

Total: 412

Current inmate/staff ratio: 3.55:1

#### **Inmate housing areas**

Design: Module/pod Cells per unit: 100 Inmates per unit: 100

Management type: Remote surveillance October 1987 population: 1,464 Facility commitment: State prisoners Means to handle crowding: Second bunk

permanently attached to wall

# **Construction process**

Finance method: State funds

Contract method: Construction manage-

ment fast track

Use of inmate labor: None Use of prefabrication: None

# Architect's reported analyses

Factors affecting construction costs:
Positive: Simple construction methods;
phased construction, fast track CM;
good competition, favorable market
Negative: Difficult site conditions;
government procedures, regulations

and red tape

Factors affecting time schedule: Positive: Repetitiveness of design; phased

construction, fast track CM Negative: Weather problems; government procedures, regulations, and red tape (No floorplan available at time of publication)

# Fulton Reception and Diagnostic Center, Phase I

Jurisdiction official: Ernest L. Cowles, Director, Division of Classification and Treatment

Contact: Superintendent Ronald L. Smith, Fulton Reception and Diagnostic Center, P.O. Box 581, Fulton, MO 65251-0581,

314-642-1707

Architect: The Hoffmann Partnership, 710 North Second Street, Suite 500 South, St. Louis, MO 63102, 314-621-6600

Construction manager: CRS Constructors, Inc., Route 1, Box 241A, Fulton, MO 65251, 314-642-0311

Groundbreaking: June 1985 Finish date: January 1987 Construction time: 19 months

Design capacity: 264 Total cost: \$16,800,000

Total annual operating costs: \$4,108,489

Category: New, independent facility Facility type: State prison—diagnostic

and reception center

Building configuration: Clusters; cam-

pus style

#### **Costs**

Total: \$16,800,000

Building only: \$13,050,000 Housing area: \$6,300,000 Housing per inmate: \$24,609 Housing per cell: \$24,609 Total per inmate: \$63,636

Total per GSF: \$106.93

Total annual operating costs: \$4,108,489

#### **Dimensions**

Gross square feet/corrections: 157,107

Gross square feet/other: 0 Gross square feet/total: 157,107 Housing area square feet: 76,000 Gross square feet per inmate: 595 Size of cells: 83 square feet (gen. single);

145 (spec. single)

Net/gross square feet: Unknown

# Construction type

Structural: Steel frame; load bearing

masonry walls Exterior walls: Brick Interior walls: CMU block Exterior surface/facade: Brick

#### **Security**

Perimeter: Double fence; alarm/detection system; razor wire on fences; towers;

patrols; camera surveillance

Inmate security level:
Maximum: 100%
Medium: 0
Minimum: 0

# Inmate design capacity

Single occupancy: 256 Double occupancy: 0

Dorms: 0

Special housing: 8 General population: 256

Total: 264

#### **Inmate cells**

Doors/material: Steel

Doors/type: Swinging; sliding

Doors/locking: Motor driven and remote

locking; manual locking
Floor surface: Sealed concrete
Intercom: Two-way to common areas
HVAC: Circulating hot water; ventilation

in cells and dayrooms Plumbing: Stainless steel Furniture: Steel; wood

Fire protection: Smoke detectors and sprinklers for common areas; return air ducts from cells have smoke detectors

#### **Current staff**

Full-time equivalent:
Administration: 53
Security: 101

Security: 101
Programs/treatment: 42

Maintenance: 17
Total: 213

Current inmate/staff ratio: 1.85:1

# **Inmate housing areas**

Design: Module/pod Cells per unit: 64 Inmates per unit: 64

Management type: Remote surveillance November 1987 population: 391 Facility commitment: State prisoners Means to handle crowding: Double bunking; Phase II under construction

#### **Construction process**

Finance method: State funds; State bond

issue

Contract method: Conventional Use of inmate labor: None Use of prefabrication: None


## **Architect's reported analyses**

Factors affecting construction costs:
Positive: Simple construction methods,
repetitiveness of design; good
competition, favorable market
Negative: Difficult site conditions;
complex electronic, mechanical, and
electrical systems

Factors affecting time schedule: Positive: Simple construction methods, repetitiveness of design; coordination of design between parties; good material supply response

Negative: Weather problems; complex electronic, mechanical, and electrical

systems



# **Jackson County Detention Center**

Jurisdiction official: Charles Megerman, Director

Contact: Charles Megerman, Director, Jackson County Detention Center, 1300 Cherry Street, Kansas City, MO 64106, 816–881–4233 Architect: Patrick + Associates, Inc., 199 South Fifth Street, Columbus, OH 43215, 614–228–3233 Construction manager: Concordia, Crown Center, Suite 120, 244 Pershing Road, Kansas City, MO 61408, 816–842–9015

Groundbreaking: May 1981 Finish date: November 1983 Construction time: 30 months

Design capacity: 520
Total cost: \$27,201,575
Total annual operating costs:
\$5,500,000 (excl. utilities and maintenance)

Building configuration: Integrated

Cells per unit: 16

on floor

Inmates per unit: 16

remote surveillance

August 1987 population: 632

courts

structure; high rise

**Inmate housing areas** 

Category: New, independent facility

Facility type: Complex: county jail and

Design: Module/pod (direct natural light)

Facility commitment: Local jail inmates

Means to handle crowding: Mattresses

Management type: Intermittent and

#### **Costs**

Total: \$27,201,575

Building only: \$27,044,575 Housing area: \$13,847,297 Housing per inmate: \$33,287 Housing per cell: \$33,287

Total per inmate: N/A (complex)

Total per GSF: \$137.88

Total annual operating costs: \$5,500,000 (excl. utilities and maintenance)

# Security

Perimeter: Video camera surveillance

Inmate security level:
Maximum: 100%
Medium: 0
Minimum: 0

# **Dimensions**

Gross square feet/corrections: 197,280 Gross square feet/other: 105,311 Gross square feet/total: 302,591 Housing area square feet: 160,735 Gross square feet per inmate: 379 Size of cells: 70.5 square feet (single) Net/gross square feet: 66%

# Construction type

Structural: Cast-in-place concrete frame Exterior walls: Cast-in-place concrete; CMU block; brick

CIVIO DIOCK, DIICK

Interior walls: CMU block; cast-in-place

concrete

Exterior surface/facade: Brick

# **Construction process**

Finance method: G.O. Bonds Contract method: Conventional Use of inmate labor: None Use of prefabrication: Limited

# **Inmate cells**

Doors/material: Steel Doors/type: Sliding

Doors/locking: Motor driven and remote

locking; manual locking Floor surface: Sealed concrete

Intercom: One way to cells and common

areas

HVAC: Heating/air circulation only; gas

heat

Plumbing: Stainless steel; stainless

combination unit Furniture: Steel

Fire protection: Smoke detectors and sprinklers for common areas; manual

alarm stations

# Inmate design capacity

Single occupancy: 416 Double occupancy: 0

Dorms: 0

Special housing: 104 General population: 416

Total: 520

#### **Current staff**

Full-time equivalent:
Administration: 16

Security: 175

Programs/treatment: 22 Maintenance: 28


Total: 241

Current inmate/staff ratio: 2.62:1

# Architect's reported analyses

Factors affecting construction costs:
Positive: Use of prefabricated components;
repetitiveness of design; good competition; less expensive materials
Negative: High security level construction;
cast-in-place concrete frame

Factors affecting time schedule:
Positive: Use of prefabricated components;
simple construction methods; advanced
order of materials and hardware;
coordination of design; good contractor
Negative: Slow responses from vendors;
labor and weather problems; government "red tape"; complex electronic,
mechanical, and electrical systems;
12-story building



# Missouri Eastern Correctional Center

Jurisdiction official: Dick D. Moore, Director, Department of Corrections and Human Resources

Contact: Myrna E. Trickey, Superintendent, Missouri Eastern Correctional Center, Pacific, MO 63069, 314–257–3322

Architect: Hellmuth, Obata & Kassabaum, Inc., 100 North Broadway, St. Louis, MO 63102, 314–421–2000

Construction manager: McBro Planning & Development, 1341 North Rock Hill Road, St. Louis, MO 63126, 314–968–0825

**Groundbreaking:** December 1978

Finish date: August 1981 Construction time: 32 months Design capacity: 560 Total cost: \$20,509,000 Total annual operating costs:

\$7,571,666

Category: New, independent facility

Facility type: State prison

**Building configuration:** Campus style

#### **Costs**

Total: \$20,509,000 Building only: Unknown Housing area: Unknown Housing per inmate: Unknown Housing per cell: Unknown Total per inmate: \$36,623 Total per GSF: \$79.70

Total annual operating costs: \$7,571,666

#### **Dimensions**

Gross square feet/corrections: 257,330 Gross square feet/other: 0 Gross square feet/total: 257,330 Housing area square feet: 106,000 Gross square feet per inmate: 460 Size of cells: 75 square feet (single) Net/gross square feet: Unknown

# **Construction type**

Structural: CIP concrete frame (housing); steel frame (ancillary buildings) Exterior walls: Brick; metal panels

Interior walls: CMU block

Exterior surface/facade: Brick; painted

metal panels

# **Security**

Perimeter: Double fence; razor wire on

fence; towers
Inmate security level:
Maximum: 0
Medium: 100%
Minimum: 0

#### Inmate cells

Doors/material: Steel Doors/type: Swinging

Doors/locking: Remote locking only Floor surface: Sealed concrete

Intercom: One-way to cells and common

areas

HVAC: Heating/air circulation only Plumbing: Stainless steel; china

Furniture: Steel

Fire protection: Smoke detectors for cells

# Inmate design capacity

Single occupancy: 512 Double occupancy: 0

Dorms: 0

Special housing: 48 General population: 512

Total: 560

#### **Current staff**

Full-time equivalent: Administration: 17 Security: 143

Programs/treatment: 34 Maintenance: 26

Total: 220

Current inmate/staff ratio: 4.67:1

# **Inmate housing areas**

Design: Module/pod Cells per unit: 32 Inmates per unit: 32

Management type: Remote surveillance October 1985 population: 1,028 Facility commitment: State prisoners Means to handle crowding: Double bunking all available space;

mattresses on floor

# **Construction process**

Finance method: State funds

Contract method: Construction manage-

ment fast track

Use of inmate labor: None Use of prefabrication: None

### Architect's reported analyses

Factors affecting construction costs: Positive: Campus plan and repetitive,

prototypical housing units

Negative: Difficult site conditions (had to


provide own water system)

Factors affecting time schedule:

Positive: Phased construction, fast track

construction management

Negative: None



# **Chouteau County Law Enforcement Facility**

Jurisdiction official: Paul F. Williams, Sheriff

Contact: Sheriff Paul F. Williams, Chouteau County Law Enforcement Facility, 1215 Washington, Fort Benton, MT 59442,

406-622-5451

Architect: Page-Werner & Partners, 300 4th Street North, P.O. Box 3005, Great Falls, MT 59403, 406-727-4405

Construction manager: None

**Groundbreaking:** May 1985 **Finish date:** February 1986 **Construction time:** 9 months

**Design capacity:** 35 **Total cost:** \$1,415,500

**Total annual operating costs:** \$108,800

Category: New, independent facility Facility type: Complex: county jail, law enf., courts, Health & Human Services

Admin. office

Building configuration: Integ. structure

#### **Costs**

Total: \$1,415,500

Building only: \$1,385,500 Housing area: \$803,172 Housing per inmate: \$25,099 Housing per cell: \$50,198

Total per inmate: N/A (complex)

Total per GSF: \$80.62

Total annual operating costs: \$108,800

# **Dimensions**

Gross square feet/corrections: 7,147 Gross square feet/other: 10,411 Gross square feet/total: 17,558 Housing area square feet: 7,147 Gross square feet per inmate: 204 Size of cells: 83 square feet (double)

Net/gross square feet: 74%

# **Inmate housing areas**

Design: Module/pod Cells per unit: 4 Inmates per unit: 8

Management type: Remote surveillance;

direct, one-way observation January 1987 population: 7

Facility commitment: Local jail inmates Means to handle crowding: Unknown

# **Security**

Perimeter: Building exterior only

Inmate security level:
Maximum: 25%
Medium: 25%
Minimum: 25%
Other: 25%

# **Construction type**

Structural: Steel frame Exterior walls: CMU block

Interior walls: Cast-in-place concrete; CMU block; steel stud framing Exterior surface/facade: Textured concrete block (colored) with metal fascia

# **Construction process**

Finance method: G.O. Bonds; local funds Contract method: Conventional Use of inmate labor: None Use of prefabrication: None

#### **Inmate cells**

Doors/material: Steel

Doors/type: Swinging; sliding Doors/locking: Motor driven and remote

locking; remote locking
Intercom: Two-way to cells
HVAC: Air conditioning; gas heat
Plumbing: Stainless combination unit

Furniture: Steel; wood

Fire protection: Smoke detectors and sprinklers for cells and common areas

# Inmate design capacity

Single occupancy: 0 Double occupancy: 32

Dorms: 0

Special housing: 3 General population: 32

Total: 35

# **Current staff**

Full-time equivalent: Administration: 0 Security: 9

Programs/treatment: 0

Maintenance: 1 Total: 10

Current inmate/staff ratio: .70:1

# Architect's reported analyses

Factors affecting construction costs:
Positive: Simple construction methods,
repetitiveness of design; good
competition, favorable market; less
expensive materials and hardware
Negative: Complex electronic, mechani-


cal, and electrical systems
Factors affecting time schedule:

Positive: Simple construction methods,

repetitiveness of design

Negative: Complex electronic, mechani-

cal, and electrical systems



# **Jefferson County Criminal Justice Center (Addition)**

Jurisdiction official: Douglas Schmitz, Chairman, Board of County Commissioners

Contact: Sheriff Tom Dawson, Jefferson County Criminal Justice Center, Courthouse Square, Boulder, MT 59632, 406–225–3323

Architect: Schutz Foss Architects, 208 North 29th Street, Suite 201, Billings, MT 59101, 406–252–9218

Construction manager: None

Groundbreaking: May 1985 Finish date: April 1986 Construction time: 11 months **Design capacity:** 14 **Total cost:** \$1,200,000

Total annual operating costs: \$43,500

(addition only)

Category: New, ancillary building Facility type: Complex: county jail, law

enforcement, courts

Building configuration: Integrated

structure

#### Costs

Total: \$1,200,000

Building only: \$1,179,433 Housing area: \$505,050 Housing per inmate: \$45,914 Housing per cell: \$56,117

Total per inmate: N/A (complex)

Total per GSF: \$92.01

Total annual operating costs: \$43,500

(addition only)

#### **Security**

Perimeter: Building exterior; video

camera surveillance Inmate security level: Maximum: 0 Medium: 70% Minimum: 30%

#### **Inmate cells**

Doors/material: Steel Doors/type: Swinging Doors/locking: Unknown Floor surface: Sealed concrete

Intercom: Two-way to cells and common

areas

HVAC: Heating/air circulation Plumbing: Stainless steel

Furniture: Steel

Fire protection: Smoke detectors and sprinklers for cells and common areas

#### **Dimensions**

Gross square feet/corrections: 4,550 Gross square feet/other: 8,492 Gross square feet/total: 13,042 Housing area square feet: 4,550 Gross square feet per inmate: 325 Size of cells: 75 square feet (single);

285 (gen. dorm); 140 (spec. double)

Net/gross square feet: 85%

# **Construction type**

Structural: Load bearing CMU walls and

steel frame

Exterior walls: CMU block; brick Interior walls: CMU block Exterior surface/facade: Brick

#### **Inmate design capacity**

Single occupancy: 8 Double occupancy: 0

Dorms: 3

Special housing: 3 General population: 11

Total: 14

### **Current staff**

Full-time equivalent: Administration: 1 Security: 2

Programs/treatment: 0 Maintenance: 0

Total: 3 (addition only)
Current inmate/staff ratio: 1.67:1

# **Inmate housing areas**

Design: Linear, outside Cells per unit: 3 Inmates per unit: 3

Management type: Intermittent surveil-

lance; direct supervision October 1986 population: 5

Facility commitment: Local jail inmates;

State prisoners

Means to handle crowding: Unknown

# **Construction process**

Finance method: G.O. Bonds Contract method: Conventional Use of inmate labor: None Use of prefabrication: None

# Architect's reported analyses


Factors affecting construction costs: Positive: Simple construction methods, repetitiveness of design; good competition, favorable market; less expensive materials and hardware

Negative: Complex electronic, mechanical, and electrical systems

Factors affecting time schedule:

Positive: Simple construction methods, repetitiveness of design; coordination of design between parties; good plans and well-managed construction team Negative: Slow responses and delivery

from vendors, suppliers



# Lewis and Clark County Criminal Justice Facility

Jurisdiction official: Charles M. O'Reilly, Sheriff

Contact: Captain Robert Bourassa, Lewis and Clark County Criminal Justice Facility, 221 Breckenridge, Helena, MT 59601,

406-443-1010

Architects: Davidson/Kuhr Architects PC, Post Office Box 3064, Great Falls, MT 59403, 406-761-2277

The NBBJ Group, 111 South Jackson Street, Seattle, WA 98104, 206-223-5555

Construction manager: None

**Groundbreaking:** June 1983 **Finish date:** October 1985

**Construction time:** 28 months

**Design capacity:** 48 **Total cost:** \$3,310,700

**Total annual operating costs:** \$258,229

Category: New, independent facility Facility type: Complex: county jail, law

Management type: Remote surveillance

Facility commitment: Local jail inmates;

enforcement

**Building configuration:** Integrated

**Inmate housing areas** 

October 1985 population: 34

Means to handle crowding: N/A

Design: Module/pod

State prisoners

Cells per unit: 6 Inmates per unit: 6

structure

**Costs** 

Total: \$3,310,700

Building only: \$3,130,200 Housing area: Unknown Housing per inmate: Unknown Housing per cell: Unknown

Total per inmate: N/A (complex)

Perimeter: Building exterior only

Total per GSF: \$77.40

Inmate security level:

Maximum: 17%

Medium: 58%

Minimum: 25%

Total annual operating costs: \$258,229

Dimensions

Gross square feet/corrections: 22,275 Gross square feet/other: 20,495 Gross square feet/total: 42,770 Housing area square feet: 15,640 Gross square feet per inmate: 464 Size of cells: 72 square feet (single)

Net/gross square feet: 83%

**Construction type** 

Structural: Cast-in-place concrete frame Exterior walls: 4" brick/3" rigid insul./6"

**RCMU** 

Interior walls: Precast panels; CIP concrete; CMU block; 5/8" GBDW

over metal studs

Exterior surface/facade: Brick

**Construction process** 

Finance method: G.O. Bonds; local funds Contract method: Conventional Use of inmate labor: None

Use of prefabrication: Limited; selected floor slabs; core slabs; steel roof

framing

**Inmate cells** 

Security

Doors/material: Steel Doors/type: Swinging

Doors/locking: Motor driven and remote

locking; remote locking Floor surface: Epoxy coating

Intercom: Two-way to cells and common

areas

HVAC: Air conditioning; exhaust air heat reclaim; hot water boiler, heat pumps Plumbing: Stainless combination unit

(penal type)
Furniture: Steel

Fire protection: Smoke detectors and sprinklers for cells and common areas

Inmate design capacity

Single occupancy: 36 Double occupancy: 2

Dorms: 10

Special housing: 0 General population: 48

Total: 48

**Current staff** 

Full-time equivalent: Administration: 1 Security: 10

Programs/treatment: 0 Maintenance: 1

Total: 12

Current inmate/staff ratio: 2.83:1

Architects' reported analyses

Factors affecting construction costs:
Positive: Repetitiveness of design; good competition, favorable market; good

soil conditions


Negative: Slow construction; restricted site size; complex electronic, mechanical, and electrical systems; jail on top floor; complex building shape

Factors affecting time schedule:

Positive: Simple construction methods, single construction contract; use of

prefab. components

Negative: Slow responses and delivery from vendors; labor problems; weather problems; complex electronic, mechanical, and electrical systems; jail on top floor; restricted site size



# Pondera County Jail (Remodel/Expansion)

Jurisdiction official: Leon D. Simpson, Sheriff

Contact: Robert L. Stocker, Jail Administrator, Pondera County Jail, 20 4th Avenue South, Conrad, MT 59425, 406–278–7681

Architect: Page-Werner, P.C., P.O. Box 3005, Great Falls, MT 59403, 406-727-4405

Construction manager: Page-Werner, P.C., P.O. Box 3005, Great Falls, MT 59403, 406-727-4405

Groundbreaking: March 1986 Finish date: December 1986 Construction time: 9 months

**Design capacity:** 8 **Total cost:** \$1,235,740

Total annual operating costs: N/A

(expansion)

Category: Remodeling/renovation proj-

ect; expansion project Facility type: Complex: county jail, law

enforcement, courts

Building configuration: Integ. structure

#### Costs

Total: \$1,235,740 Building only: Unknown Housing area: \$340,000 Housing per inmate: \$48,571 Housing per cell: \$68,000

Total per inmate: N/A (complex)

Total per GSF: \$256.17

Total annual operating costs: N/A

(expansion)

Perimeter: Video camera surveillance

Maximum: 20% Medium: 80% Minimum: 0

#### **Dimensions**

Gross square feet/corrections: 2,622 Gross square feet/other: 2,202 Gross square feet/total: 4,824 Housing area square feet: 2,622 Gross square feet per inmate: 328 Size of cells: 83 square feet (gen. single);

165 (double)

Net/gross square feet: 84%

# **Inmate housing areas**

Design: Module/pod; single quadrant configuration

Cells per unit: 5 Inmates per unit: 7

Management type: Remote surveillance

December 1987 population: 2

Facility commitment: Local jail inmates;

State prisoners

Means to handle crowding: Second bunk

# Security

Inmate security level:

# **Construction type**

Structural: Steel frame; cast-in-place

concrete frame

Exterior walls: Brick; architectural precast Interior walls: CMU block; brick Exterior surface/facade: Brick; colored

concrete

# **Construction process**

Finance method: Revenue sharing:

Federal funds

Contract method: Conventional Use of inmate labor: None

Use of prefabrication: Limited; architec-

tural precast

#### **Inmate cells**

Doors/material: Steel Doors/type: Sliding

Doors/locking: Motor driven and remote

locking

Floor surface: Epoxy coating

Intercom: Two-way to cells and common

HVAC: Air conditioning; gas-fired steam

boiler

Plumbing: Stainless steel

Furniture: Steel

Fire protection: Sprinklers for cells and

common areas

# Inmate design capacity

Single occupancy: 3 Double occupancy: 4

Dorms: 0

Special housing: 1 General population: 7

Total: 8

# Architect's reported analyses

Factors affecting construction costs: Positive: Good competition, favorable

market

Negative: Lengthy building time, courthouse and sheriff's office operational during construction; intricate masonry work to conform to original courthouse detailing; complex electronic and mechanical systems

Factors affecting time schedule:

Positive: Coordination of design between

parties

Negative: Slow delivery from suppliers;

material delivery problems


#### **Current staff**

Full-time equivalent: Administration: 4 Security: 11

Programs/treatment: 0 Maintenance: 2

Total: 17

Current inmate/staff ratio: .12:1



# **Yellowstone County Detention Facility**

Jurisdiction official: Mike Schafer, Sheriff

Contact: Lt. Rickard A. Ross, Commander, Yellowstone County Detention Facility, 3165 King Avenue, East Billings, MT 59101,

406-256-6884

Architects: Dana Larson Roubal & Associates/DLR Group, 2929 Third Avenue North, First Federal Building, Suite 206, Billings, MT 59101, 406–245–6201

Lescher and Mahoney/DLR Group, 1130 East Missouri, Suite 850, Phoenix, AZ 85014, 602-264-6803

Miller Levine Architects, P.C., 3111 1st Avenue North, Billings, MT 59101, 406-245-0947

Construction manager: None

Groundbreaking: October 1985

Finish date: June 1987

Construction time: 20 months

**Design capacity:** 174 **Total cost:** \$7,607,597

**Total annual operating costs:** \$1,550,567

Category: New, independent facility Facility type: Complex: county jail,

courts

Building configuration: Integrated

structure

**Costs** 

Total: \$7,607,597

Building only: \$7,146,058 Housing area: \$4,706,693 Housing per inmate: \$37,355 Housing per cell: \$37,355

Total per inmate: N/A (complex)

Total per GSF: \$102.32

Total annual operating costs: \$1,550,567

**Dimensions** 

Gross square feet/corrections: 72,755 Gross square feet/other: 1,598 Gross square feet/total: 74,353 Housing area square feet: 48,972 Gross square feet per inmate: 418

Size of cells: 70 square feet (single)

Net/gross square feet: 85%

Inmates per unit: 44
Management type: I

Management type: Direct supervision

October 1987 population: 84

**Inmate housing areas** 

Design: Module/pod Cells per unit: 44

Facility commitment: Local jail inmates Means to handle crowding: Not necessary—court-ordered cap on population

**Security** 

Perimeter: Video camera surveillance;

chain link fence Inmate security level: Maximum: 28% Medium: 72% Minimum: 0 **Construction type** 

Structural: CMU walls; poured-in-place concrete floors; precast concrete tees/

hollowcore roof

Exterior walls: CMU block Interior walls: CMU block Exterior surface/facade: Brick **Construction process** 

Finance method: G.O. Bonds Contract method: Conventional Use of inmate labor: None

Use of prefabrication: Moderate; precast concrete roof, hollowcore slabs-short,

double tees-long

**Inmate cells** 

Doors/material: Steel

Doors/type: Swinging; sliding

Doors/locking: Remote locking; manual

locking

Floor surface: Carpet; vinyl tile
Intercom: Two-way to common areas and

Intercom: Two-way to common areas and

dayrooms

HVAC: Air conditioning; gas heat Plumbing: Stainless steel; china Furniture: Steel; wood; vinyl/plastic Fire protection: Smoke detectors and sprinklers for cells and common areas Inmate design capacity

Single occupancy: 126 Double occupancy: 0

Dorms: 0

Special housing: 48 General population: 126

Total: 174

Current staff

Full-time equivalent: Administration: 3 Security: 32

Programs/treatment: 3 Maintenance: 4

Total: 42

Current inmate/staff ratio: 2:1

Architects' reported analyses

Factors affecting construction costs: Positive: Quality of bidding documents;


favorable bidding climate

Negative: None

Factors affecting time schedule:
Positive: Overcrowding of existing jail;
need to have construction underway
before onset of winter; mild winter
facilitated contractor's schedule

Negative: Government procedures and regulations; passing of bond issue (funding) failed first attempt, delaying

project 6 months



# **Dodge County Judicial Center**

Jurisdiction official: Dan Weddle, Sheriff

Contact: William Steyer, Jail Administrator, Dodge County Judicial Center, 4th and Broad Street, Fremont, NE 68025, 402-721-1962

Architect: Dana Larson Roubal and Associates, 400 Essex Court Omaha, NE 68114, 402-393-4100

Construction manager: None

Groundbreaking: June 1985 Finish date: November 1986 Construction time: 17 months

**Design capacity:** 43 **Total cost:** \$3,259,060

Total annual operating costs: Unknown

Category: New, independent facility Facility type: Complex: county jail,

courts

Building configuration: Integrated

structure

#### Costs

Total: \$3,259,060

Building only: \$3,124,060 Housing area: \$1,250,000 Housing per inmate: \$41,667 Housing per cell: \$41,667

Total per inmate: N/A (complex)

Total per GSF: \$93.28

Total annual operating costs: Unknown

# **Dimensions**

Gross square feet/corrections: 22,688 Gross square feet/other: 18,562 Gross square feet/total: 41,250 Housing area square feet: 9,625 Gross square feet per inmate: 528 Size of cells: 70 square feet (single)

Net/gross square feet: 69%

# Inmate housing areas

Design: Module/pod Cells per unit: 2 to 8 Inmates per unit: 2 to 8

Management type: Intermittent

surveillance

December 1987 population: 32

Facility commitment: Local jail inmates Means to handle crowding: Unknown

# **Security**

Perimeter: Building exterior only

Inmate security level:
Maximum: 12%
Medium: 88%
Minimum: 0

# **Construction type**

Structural: Cast-in-place concrete frame Exterior walls: Brick; architectural precast Interior walls: Cast-in-place concrete;

CMU block

Exterior surface/facade: Brick

#### **Construction process**

Finance method: Lease purchase bonds Contract method: Separate contracts

Use of inmate labor: None Use of prefabrication: None

# **Inmate cells**

Doors/material: Steel Doors/type: Swinging

Doors/locking: Remote locking Floor surface: Carpet; sealed concrete;

vinyl tile

Intercom: Two-way to common areas;

two-way radios

HVAC: Air conditioning; gas heat

Plumbing: China Furniture: Steel; wood

Fire protection: Smoke detectors and sprinklers for cells and common areas

#### Inmate design capacity

Single occupancy: 30 Double occupancy: 0

Dorms: 0

Special housing: 13 General population: 30

Total: 43

# **Current staff**

Full-time equivalent: Administration: 2 Security: 18

Programs/treatment: 1 Maintenance: 1

Total: 22

Current inmate/staff ratio: 1.45:1

# Architect's reported analyses

Factors affecting construction costs: Positive: Good competition, favorable

market


Negative: Difficult site conditions

Factors affecting time schedule: Positive: Coordination of design between

parties

Negative: Slow responses and delivery

from vendors, suppliers



# **Douglas County Correctional Center**

Jurisdiction official: Michael Kelly, County Commissioner

Contact: Joseph Vitek, Director, Douglas County Correctional Center, 710 South 17 Street, Omaha, NE 68102, 402-444-7400 Architect: Dana Larson Roubal/Lescher & Mahoney, Inc., 1130 East Missouri, Suite 850, Phoenix, AZ 85014, 602-264-6803

Construction manager: None

**Groundbreaking:** January 1977

Finish date: July 1979

Construction time: 31 months

**Design capacity:** 204 **Total cost:** \$4,636,423

Total annual operating costs:

\$4,000,000

Category: New, independent facility

Facility type: County jail

Building configuration: Integrated

structure

#### **Costs**

Total: \$4,636,423

Building only: \$4,200,000 Housing area: Unknown Housing per inmate: Unknown Housing per cell: Unknown Total per inmate: \$22,728 Total per GSF: \$54.55

Total annual operating costs: \$4,000,000

Perimeter: Building exterior only

# **Dimensions**

Gross square feet/corrections: 84,995

Gross square feet/other: 0 Gross square feet/total: 84,995 Housing area square feet: 60,000 Gross square feet per inmate: 417 Size of cells: 70 square feet (single) Net/gross square feet: Unknown

# Construction type

Structural: Poured-in-place concrete;

load bearing masonry

Exterior walls: Cast-in-place concrete;

brick

Interior walls: Cast-in-place concrete;

brick

Exterior surface/facade: Textured

concrete

# Inmate cells

**Security** 

Doors/material: Wooden; steel

Doors/type: Swinging

Inmate security level:

Medium: 100%

Maximum: 0

Minimum: 0

Doors/locking: Remote locking; manual

locking

Floor surface: Carpet; vinyl composition

tile

Intercom: Dayrooms and control rooms HVAC: Heating/air circulation only;

solar heating Plumbing: China

Furniture: Wood; vinyl/plastic

Fire protection: Smoke detectors for cells,

corridors, and dayrooms

# Inmate design capacity

Single occupancy: 202 Double occupancy: 0

Dorms: 0

Special housing: 2 General population: 202

Total: 204

#### **Current staff**

Full-time equivalent: Administration: 15 Security: 100

Programs/treatment: 15 Maintenance: 30

Total: 160

Current inmate/staff ratio: 1.87:1

# **Inmate housing areas**

Design: Module/pod Cells per unit: 16 to 20 Inmates per unit: 16 to 20

Management type: Direct supervision

October 1985 population: 300

Facility commitment: Local jail inmates;

felony pretrial detainees
Means to handle crowding: None

# **Construction process**

Finance method: Local funds; Federal

funds

Contract method: Conventional Use of inmate labor: None

Use of prefabrication: Limited; precast

concrete tees for roof

# Architect's reported analyses

Factors affecting construction costs:

Positive: None


Negative: Hardware costs (security); lack

of program definition

Factors affecting time schedule:

Positive: Good client

Negative: Court mandate to complete



# **Nebraska State Penitentiary (Addition)**

Jurisdiction official: Frank O. Gunter, Director, Department of Correctional Services

Contact: Warden Gary Grammer, Nebraska State Penitentiary, P.O. Box 2500, Station B, Lincoln, NE 68502, 402-471-3161

Architects: Leo A. Daly, 8600 Indian Hills Drive, Omaha, NE 68114, 402–391–8111

Curtis and Davis, Architects and Planners, Inc., 512 South Peters Street, New Orleans, LA 70130, 504-522-3656

Construction manager: None

Groundbreaking: April 1979 Finish date: August 1982 Construction time: 40 months **Design capacity:** 320 **Total cost:** \$14,500,000

Total annual operating costs: \$9,149,393

(addition only)

Category: New, ancillary building

Facility type: State prison

Building configuration: Campus style

# Costs

Total: \$14,500,000

Building only: \$11,850,000 Housing area: \$4,921,000 Housing per inmate: \$20,504 Housing per cell: \$20,504 Total per inmate: \$45,313 Total per GSF: \$105.24

Total annual operating costs: \$9,149,393

(addition only)

# **Security**

Perimeter: Double fence; alarm/detection systems; razor wire on and between

fences; towers; patrols Inmate security level: Maximum: 100% Medium: 0 Minimum: 0

# **Inmate cells**

Doors/material: Steel Doors/type: Swinging

Doors/locking: Remote locking; manual

locking

Floor surface: Carpet; vinyl tile Intercom: Two-way to common areas HVAC: Air conditioning; steam heat Plumbing: Stainless combination unit

Furniture: Steel; wood

Fire protection: Smoke detectors for common areas; manual alarm stations

#### **Dimensions**

Gross square feet/corrections: 137,776

Gross square feet/other: 0 Gross square feet/total: 137,776 Housing area square feet: 66,732 Gross square feet per inmate: 431 Size of cells: 74 square feet (single)

Net/gross square feet: 62%

# Construction type

Structural: Cast-in-place concrete frame; load bearing CMU block walls

Exterior walls: Brick

Interior walls: Cast-in-place concrete;

CMU block

Exterior surface/facade: Brick

#### Inmate design capacity

Single occupancy: 240 Double occupancy: 0

Dorms: 0

Special housing: 80 General population: 240

Total: 320

#### **Current staff**

Full-time equivalent: Administration: 46 Security: 223

Programs/treatment: 34 Maintenance: 48

Total: 351

Current inmate/staff ratio: 1.95:1

# Inmate housing areas

Design: Linear 'X' with dining at center

Cells per unit: 80 Inmates per unit: 80

Management type: Remote surveillance September 1986 population: 684 Facility commitment: State prisoners Means to handle crowding: Bunk beds in

cell

# **Construction process**

Finance method: State funds Contract method: Conventional Use of inmate labor: None Use of prefabrication: None

# Architect's reported analyses

Factors affecting construction costs: Positive: Simple const. methods, repetitiveness of design; CMU walls; poured-in-place concrete; good competition;

utility plant


Negative: Difficult site conditions; complex electronic and mechanical

systems

Factors affecting time schedule:
Positive: Simple const. methods, repetitiveness of design; CMU walls; poured-in-place concrete; coordination of design; single construction contract
Negative: Slow delivery from vendors;

weather problems; complex electronic

and mechanical systems



# **Clark County Detention Center**

Jurisdiction official: John T. Moran, Sheriff

Contact: Gordon Yach, Director, Clark County Detention Center, 330 South Casino Center Boulevard, Las Vegas, NV 89101,

702-383-7650

Architect: Hellmuth, Obata & Kassabaum, Inc., One Lombard Street, San Francisco, CA 94111, 415-627-1600

Construction manager: None

Groundbreaking: June 1981 Finish date: June 1984

Construction time: 36 months

Design capacity: 850 Total cost: \$43,500,000 Total annual operating costs:

\$17,586,658

Category: New, independent facility

Facility type: County jail

**Inmate housing areas** 

Design: Modular

Cells per unit: 48-49

Inmates per unit: 48-49

remote surveillance

State prisoners

October 1985 population: 915

**Building configuration:** Integrated structure; high rise; clusters

Management type: Direct supervision;

Facility commitment: Local jail inmates;

Means to handle crowding: Bunk beds in

#### **Costs**

Total: \$43,500,000 Building only: \$43,000,000 Housing area: \$28,140,000 Housing per inmate: \$35,175 Housing per cell: \$35,175

Total per inmate: \$51,176 Total per GSF: \$124.29

Total annual operating costs: \$17,586,658

Perimeter: Building exterior only

Inmate security level:

Maximum: 12%

Medium: 63%

Minimum: 25%

# **Dimensions**

Gross square feet/corrections: 350,000

Gross square feet/other: 0 Gross square feet/total: 350,000 Housing area square feet: 234,500 Gross square feet per inmate: 412 Size of cells: 71 square feet (single)

Net/gross square feet: 70%

# **Construction type**

Structural: Cast-in-place concrete

frame

Exterior walls: Prefab. panels using tile surface, metal frame, batt

insulation, plaster

Interior walls: Cast-in-place concrete;

CMU block

Exterior surface/facade: Tile

# **Construction process**

dayrooms of intake

Finance method: Local funds Contract method: Construction management fast track Use of inmate labor: None Use of prefabrication: Limited;

exterior wall

#### **Inmate cells**

Security

Doors/material: Wooden Doors/type: Swinging

Doors/locking: Remote locking only Floor surface: Carpet; epoxy coating;

sealed concrete; vinyl tile

Intercom: Two-way to cells; one-way to common areas

HVAC: Air conditioning Plumbing: Stainless

Furniture: Wood; vinyl/plastic

Fire protection: Smoke detectors for cells and common areas; sprinklers for

common areas

# Inmate design capacity

Single occupancy: 800 Double occupancy: 0

Dorms: 0

Special housing: 50 General population: 800

**Total: 850** 

#### **Current staff**

Full-time equivalent: Administration: 154 Security: 289

Programs/treatment: 28 Maintenance: 34

Total: 505

Current inmate/staff ratio: 1.81:1

# Architect's reported analyses

Factors affecting construction costs: Positive: Good competition, favorable market; direct supervision; extensive


value engineering

Negative: Complex electronic, mechancal, and electrical systems; use of four

bid packages


Factors affecting time schedule:
Positive: Phased construction, fast track
construction management; tight
contract with general contractor that
specified schedule

Negative: Use of four bid packages



- **Mezzanine Level**
- 1 Sally Port 2 Secure Elevator 3 Visiting

- 4 Meeting Room 5 Control Below 6 Outdoor Exercise
- **7** Showers **8** Typical Cell



# **Main Level**

- 1 Sally Port 2 Secure Elevator 3 Multi-purpose 4 Sick Call

- **5** Storage **6** Commissary **7** Dayroom **8** Typical Cell

- 9 Food Service 10 Outdoor Exercise Above 11 Course "
- 12 Counseling

# **Camden County Correctional Facility**

Jurisdiction official: William J. Simon, Sheriff

Contact: Warden William C. Strang, Jr., Camden County Correctional Facility, 310 Federal Street, Camden, NJ 08101, 609–757–6657 Architect: Sullivan Associates, Architects & Planners, 2314 Market Street, 2nd Floor, Philadelphia, PA 19103, 215–567–7300 Construction manager: The Lisiewski Group, 19 West Cuthbert Boulevard, Collingswood, NJ 08108, 609–854–7500

Groundbreaking: October 1983 Finish date: September 1987 Construction time: 47 months **Design capacity:** 499 **Total cost:** \$28,300,000

Total annual operating costs: Unknown

Category: New, independent facility

Facility type: County jail

Building configuration: High rise

# Costs

Total: \$28,300,000

Building only: \$27,720,000 Housing area: \$12,700,000 Housing per inmate: \$29,195 Housing per cell: \$29,195 Total per inmate: \$56,713

Total per GSF: \$115.98
Total annual operating costs: Unknown

# **Dimensions**

Gross square feet/corrections: 244,000

Gross square feet/other: 0 Gross square feet/total: 244,000 Housing area square feet: 91,500 Gross square feet per inmate: 489 Size of cells: 70 square feet (single)

Net/gross square feet: 57%

# **Inmate housing areas**

Design: Module/pod Cells per unit: 14 to 38 Inmates per unit: 14 to 38

Management type: Remote surveillance December 1987 population: 0 (electrical

problems prevent opening)

Facility commitment: Local jail inmates;

State prisoners

Means to handle crowding: Unknown

# **Security**

Perimeter: Building exterior only

Inmate security level:
Maximum: 20%
Medium: 80%
Minimum: 0

# **Construction type**

Structural: Precast concrete frame Exterior walls: CMU block; brick Interior walls: CMU block Exterior surface/facade: Brick

# **Construction process**

Finance method: G.O. Bonds; State funds Contract method: Conventional

Use of inmate labor: None

Use of prefabrication: Moderate; precast

concrete frame

#### **Inmate cells**

Doors/material: Steel Doors/type: Swinging

Doors/locking: Remote locking

Floor surface: Dexotex (rubber composite

flooring)

Intercom: Two-way to common areas HVAC: Air conditioning; solar heat; gas

heat

Plumbing: Stainless combination unit

Furniture: Steel

Fire protection: Smoke detectors and sprinklers for cells and common areas

# Inmate design capacity

Single occupancy: 435 Double occupancy: 0

Dorms: 0

Special housing: 64 General population: 435

Total: 499

# **Current staff**

Full-time equivalent:

Administration: Unknown

Security: Unknown

Programs/treatment: Unknown

Maintenance: Unknown

Total: Unknown

Current inmate/staff ratio: Unknown

#### Architect's reported analyses

Factors affecting construction costs: Positive: Simple construction methods,

repetitiveness of design

Negative: Slow construction, lengthy building time; BOCP code for life safety was problematic in correctional

facility

Factors affecting time schedule:

Positive: None

Negative: Slow responses and delivery from vendors, suppliers; electrical engineer unable to meet deadlines for installation and debugging of system (No floorplan available at time of publication)

# Gerald L. Gormley Justice Facility

Jurisdiction official: Richard E. Squires, County Executive

Contact: Joseph D. Wagner, Division Director, Gerald L. Gormley Justice Facility, 2200 Atlantic Avenue, Mays Landing, NJ 08330,

609-641-0111

Architect: Sullivan Associates, Architects & Planners, 2314 Market Street, Philadelphia, PA 19103, 215-567-7300

Construction manager: Day and Zimmerman, 2200 Atlantic Avenue, 24 East Main Street, Mays Landing, NJ 08330, 609-625-0044

**Groundbreaking:** July 1982 Finish date: June 1984

Construction time: 23 months

**Design capacity: 368 Total cost:** \$13,744,500

Total annual operating costs: Unknown

Category: New, independent facility Facility type: Complex: county jail,

**Building configuration:** Courtyard

# Costs

Total: \$13,744,500

Building only: \$12,878,500 Housing area: \$6,200,000 Housing per inmate: \$24,219 Housing per cell: \$24,219

Total per inmate: N/A (complex)

Total per GSF: \$127.97

Total annual operating costs: Unknown

#### **Dimensions**

Gross square feet/corrections: 105,000 Gross square feet/other: 2,400 Gross square feet/total: 107,400 Housing area square feet: 57,000 Gross square feet per inmate: 285

Size of cells: 70 square feet (single) Net/gross square feet: 70%

# **Inmate housing areas**

Design: Module/pod Cells per unit: 32 Inmates per unit: 32

Management type: Remote surveillance

October 1986 population: 518

Facility commitment: Local jail inmates;

State prisoners

Means to handle crowding: Beds in dayroom; second bunk permanently

attached to wall

# Security

Perimeter: Double fence; alarm/detection

systems; razor wire on fences

Inmate security level: Maximum: 22% Medium: 54% Minimum: 24%

# **Construction type**

Structural: Cast-in-place concrete frame Exterior walls: CMU block; brick

Interior walls: CMU block Exterior surface/facade: Brick

# **Construction process**

Finance method: Local funds; State funds Contract method: Construction manage-

ment fast track

Use of inmate labor: None Use of prefabrication: None

# Inmate cells

Doors/material: Steel Doors/type: Swinging

Doors/locking: Remote locking

Floor surface: Metallic cement coating Intercom: Two-way to common areas HVAC: Air conditioning; other energy recycle unit; waste-to-energy facility onsite

Plumbing: Stainless combination unit

Furniture: Steel

Fire protection: Smoke detectors and sprinklers for cells and common areas

# Inmate design capacity

Single occupancy: 256 Double occupancy: 0

Dorms: 0

Special housing: 112 General population: 256

Total: 368

# Architect's reported analyses

Factors affecting construction costs: Positive: Phased construction, fast track construction management; good competition, favorable market; less expensive materials and hardware

Negative: None

Factors affecting time schedule:

Positive: Simple construction methods, repetitiveness of design; phased construction, fast track construction

management

Negative: Slow responses and delivery

from vendors, suppliers

#### **Current staff**


Full-time equivalent: Administration: 25

Security: 110

Programs/treatment: 16 Maintenance: 0

Total: 151

Current inmate/staff ratio: 3.43:1



# **Middlesex County Correctional Facility**

Jurisdiction official: Anthony Pellicane, Director, Corrections and Youth Services

Contact: Warden Rudolph Johnson, Middlesex County Correctional Facility, P.O. Box 226, New Brunswick, NJ 08903,

201-297-3636

**Architect:** The Grad Partnership, Gateway One, Newark, NJ 07102, 201–621–1700

Construction manager: None

Groundbreaking: December 1981

Finish date: July 1984

Construction time: 30 months

Design capacity: 330 Total cost: \$18,000,000

**Total annual operating costs:** 

\$10,007,500

Category: New, independent facility

Facility type: County jail

Building configuration: Integrated

structure; courtyard

#### **Costs**

Total: \$18,000,000

Building only: \$17,738,000

Housing area: Unknown

Housing per inmate: Unknown Housing per cell: Unknown

Total per inmate: \$54,545 Total per GSF: \$123.69

Total annual operating costs: \$10,007,500

#### **Dimensions**

Gross square feet/corrections: 145,521

Gross square feet/other: 0 Gross square feet/total: 145,521 Housing area square feet: 58,695 Gross square feet per inmate: 441

Size of cells: Unknown Net/gross square feet: 61%

# **Inmate housing areas**

Design: Module/pod Cells per unit: 24 Inmates per unit: 24

Management type: Remote surveillance

November 1987 population: 505

Facility commitment: Local jail inmates Means to handle crowding: Bunk beds in

cell; use of old building

# Security

Perimeter: Double fence; alarm/detection

systems; razor wire on fences

Inmate security level:
Maximum: 15%
Medium: 85%
Minimum: 0

# **Construction type**

Structural: Steel frame Exterior walls: Dryvit

Interior walls: Poured-in-place concrete Exterior surface/facade: Finished system

### **Construction process**

Finance method: G.O. Bonds; State funds

Contract method: Conventional Use of inmate labor: None Use of prefabrication: None

#### **Inmate cells**

Doors/material: Steel

Doors/type: Swinging; sliding

Doors/locking: Motor driven and remote

locking

Floor surface: Carpet; sealed concrete;

vinyl tile

Intercom: One-way to common areas HVAC: Air conditioning; gas/oil option

boiler

Plumbing: Stainless steel; china Furniture: Steel; vinyl/plastic Fire protection: Smoke detectors a

Fire protection: Smoke detectors and sprinklers for cells and common areas

# Inmate design capacity

Single occupancy: 300 Double occupancy: 0

Dorms: 0

Special housing: 30 General population: 300

Total: 330

#### **Current staff**

Full-time equivalent: Administration: 35 Security: 174

Programs/treatment: 22 Maintenance: 15

Total: 246

Current inmate/staff ratio: 2.30:1

#### Architect's reported analyses


Factors affecting construction costs:

Positive: Rural open site

Negative: None

Factors affecting time schedule:

Positive: None Negative: None



# **Ocean County Justice Complex**

Jurisdiction official: Benjamin H. Mabie, County Administrator

Contact: Warden Theodore J. Hutler, Ocean County Justice Complex, 101 Hooper Avenue, CN 2191, Toms River, NJ 08754,

201-929-2043

Architects: The Grad Partnership, Gateway One, Newark, NJ 07102, 201-621-1700

Henningson, Durham, & Richardson, Inc., 12700 Hillcrest, Suite 125, Dallas, TX 75230, 214-980-0001

Construction manager: None

Groundbreaking: March 1982 Finish date: November 1985 Construction time: 44 months Design capacity: 209 Total cost: \$20,000,000 Total annual operating costs:

\$3,658,500

Category: New, independent facility Facility type: Complex: county jail,

courts

**Building configuration:** Integrated

structure

**Costs** 

Total: \$20,000,000

Building only: \$18,600,000 Housing area: \$6,357,000 Housing per inmate: \$33,109 Housing per cell: \$33,109

Total per inmate: N/A (complex)
Total per GSF: Unknown

Total annual operating costs: \$3,658,500

**Dimensions** 

Gross square feet/corrections: 60,548 Gross square feet/other: Unknown Gross square feet/total: Unknown Housing area square feet: 34,182 Gross square feet per inmate: 290

Size of cells: 72 square feet (single) Net/gross square feet: 73% **Inmate housing areas** 

Design: Module/pod Cells per unit: 64 Inmates per unit: 64

Management type: Remote surveillance

May 1987 population: 214

Facility commitment: Local jail inmates Means to handle crowding: 96 bed annex

Security

Perimeter: Building exterior only

Inmate security level:
Maximum: 20%
Medium: 80%
Minimum: 0

**Construction type** 

Structural: Steel frame

Exterior walls: Brick; AWP panels

Interior walls: CMU block

Exterior surface/facade: Brick; glass

**Construction process** 

Finance method: G.O. Bonds; State funds

Contract method: Conventional Use of inmate labor: None Use of prefabrication: None

**Inmate cells** 

Doors/material: Steel

Doors/type: Swinging; sliding

Doors/locking: Motor driven and remote

locking; remote locking

Floor surface: Epoxy coating; sealed

concrete

Intercom: One-way to common areas; two-way to common areas HVAC: Air conditioning; gas heat Plumbing: Stainless combination unit

Furniture: Steel

Fire protection: Smoke detectors for common areas; sprinklers for cells and common areas; manual alarm stations Inmate design capacity

Single occupancy: 192 Double occupancy: 0

Dorms: 0

Special housing: 17 General population: 192

Total: 209

Architects' reported analyses

Factors affecting construction costs: Positive: Good competition, favorable market; less expensive materials and

hardware

Negative: Steel reinforcement and concrete filled partitions; slow construction, lengthy building time; complex electronic, mechanical, and electrical systems

Factors affecting time schedule:

Positive: Simple construction methods,

repetitiveness of design Negative: Labor problems


#### **Current staff**

Full-time equivalent: Administration: 9 Security: 94

Programs/treatment: 11 Maintenance: 10

Total: 124

Current inmate/staff ratio: 1.73:1



# Southern State Correctional Facility: Modular Units (Phase I and II)

Jurisdiction official: William H. Fauver, Commissioner, Department of Corrections

Contact: Superintendent Robert Edmiston, Southern State Correctional Facility, Route #47, Delmont, NJ 08314, 609-785-1300 Architect: CUH2A Architects, Engineers, Planners, 600 Alexander Road, CN 5240, Princeton, NJ 08540, 609-452-1212 Modular manufacturer: Arthur Industries, Inc., P.O. Box 74, South Main Street, Terryville, CT 06786, 203-582-6552 Construction manager: Shoemaker Construction Company, 245 South 24th Street, Philadelphia, PA 19103, 215-732-2000

**Groundbreaking:** December 1982

Finish date: January 1984

**Construction time:** 6 months (Phase I);

5 months (Phase II)

Design capacity: 1,106 Total cost: \$24,300,000 **Total annual operating costs:** 

\$25,265,000 (entire facility)

Category: New, independent facility

Facility type: State prison

Building configuration: Campus style

#### Costs

Total: \$24,300,000 Building only: Unknown Housing area: \$10,672,284 Housing per inmate: \$10,846 Housing per cell: \$296,452 Total per inmate: \$24,107

Total annual operating costs: \$25,265,000

(entire facility)

Total per GSF: \$107.72

#### Security

Perimeter: Double fence; razor wire on

fences; towers; patrols Inmate security level: Maximum: 2% Medium: 83% Minimum: 15%

#### **Inmate cells**

Doors/material: Steel

Doors/type: Swinging; sliding

Doors/locking: Motor driven and remote

locking; manual locking

Floor surface: Epoxy coating; vinyl tile Intercom: One-way to common areas,

cells, and dorms

HVAC: Air conditioning; electric heat

pump

Plumbing: China; stainless combination

unit

Furniture: Steel

Fire protection: Smoke detectors and sprinklers for cells and common areas;

manual alarm stations

#### **Dimensions**

Gross square feet/corrections: 225,580 Gross square feet/other: 0 Gross square feet/total: 225,580

Housing area square feet: Unknown Gross square feet per inmate: 224

Size of cells: Unknown Net/gross square feet: 92%

# **Construction type**

Structural: Steel frame; wood trusses; steel members

Exterior walls: Steel panels, masonite siding over study, metal panels over steel

substructure

Interior walls: CMU block; fiberglass panels over gypsum board; steel panels Exterior surface/facade: Natural wall

# Inmate design capacity

Single occupancy: 0 Double occupancy: 0

Dorms: 984

Special housing: 24 General population: 984

Total: 1.008

#### **Current staff**

Full-time equivalent: Administration: 61 Security: 464

Programs/treatment: 71 Maintenance: 44

Total: 640 (entire facility)

Current inmate/staff ratio: Unknown

# **Inmate housing areas**

Design: Dormitory style housing

Cells per unit: 0 Inmates per unit: 80

Management type: Intermittent surveillance (segregation); direct supervision

Current population: Unknown Facility commitment: State prisoners Means to handle crowding: Bunk beds in

wing

#### **Construction process**

Finance method: G.O. Bonds

Contract method: Conventional (Phase I);

CM fast track (Phase II) Use of inmate labor: None

Use of prefabrication: Extensive; modules for all housing and some program/ support; pre-engineered buildings for

some program/support

# Architect's reported analyses

Factors affecting construction costs: Positive: Prefabricated components, factory assembly; simple construction methods; phased construction; fast track CM; good competition, favorable market; less expensive materials and hardware

Negative: Difficult site conditions

Factors affecting time schedule: Positive: Use of prefabricated components, factory assembly; repetitiveness of design; phased construction, fast track CM; coordination of design

between parties Negative: Slow responses and delivery

from vendors, suppliers; bad weather

**DETENTION UNIT** Holding Area #**!!!!** TYPICAL HOUSING COMPLEX TYPICAL MODULE Day Room Pantry Control Inmate Sleeping Spaces

# Trenton State Prison (Addition/Remodel)

Jurisdiction official: William H. Fauver, Commissioner, Department of Corrections

Contact: Howard L. Beyer, Administrator, Trenton State Prison, Third Street, Trenton, NJ 08611, 609-292-9700

Architect: The Grad Partnership, Gateway One, Newark, NJ 07102, 201-621-1700

Construction manager: None

Groundbreaking: September 1979 Finish date: October 1982

Construction time: 37 months

Design capacity: 837 **Total cost:** \$65,000,000 **Total annual operating costs:** 

\$44,580,000 (entire facility)

Category: New, ancillary building;

remodel/renovation Facility type: State prison

Building configuration: Integ. structure;

Management type: Remote surveillance

Facility commitment: State prisoners

Means to handle crowding: Bunk beds in

high rise; courtyard

Design: Module/pod Cells per unit: 48

Inmates per unit: 48

cell

**Inmate housing areas** 

May 1987 population: 768

**Construction process** 

Use of inmate labor: None

Use of prefabrication: None

Finance method: G.O. Bonds Contract method: Conventional

Costs

Total: \$65,000,000 Building only: \$42,149,106

Housing area: Unknown Housing per inmate: Unknown Housing per cell: Unknown

Total per inmate: N/A (remodel)

Total per GSF: \$180.80

Total annual operating costs: \$44,580,000

Perimeter: Building exterior; alarm/detec-

(entire facility)

tion systems

Inmate security level:

Maximum: 100% Medium: 0 Minimum: 0

Security

Structural: Steel frame

Interior walls: Cast-in-place concrete; brick

Exterior surface/facade: Brick

**Dimensions** 

Gross square feet/corrections: 359,518

Gross square feet/other: 0 Gross square feet/total: 359,518 Housing area square feet: 222,970 Gross square feet per inmate: 430

Size of cells: Unknown Net/gross square feet: 76.5%

Construction type

Exterior walls: Cast-in-place concrete;

Inmate design capacity

Single occupancy: 837 Double occupancy: 0

Dorms: 0

Special housing: 0 General population: 837

Total: 837

Architect's reported analyses

Factors affecting construction costs:

Positive: None Negative: None

Factors affecting time schedule: Positive: None Negative: None

Doors/type: Sliding Doors/locking: Motor driven and remote

locking

**Inmate cells** 

Doors/material: Steel

Floor surface: Sealed concrete; epoxy

coating

Intercom: Two-way to common areas

**HVAC**: Climate control Plumbing: Stainless steel

Furniture: Steel

Fire protection: Smoke detectors and sprinklers for common areas

Current staff

Full-time equivalent: Administration: 111 Security: 821

Programs/treatment: 116

Maintenance: 68

Total: 1,116 (entire facility) Current inmate/staff ratio: 2.03:1

NIJ/National Directory of Corrections Construction

(No floorplan available at time of publication)

# **Warren County Correctional Center**

Jurisdiction official: Robert Sharr, Warden

Contact: Warden Robert Sharr, Warren County Correctional Center, Belvidere, NJ 07823, 201–475–8200 Architect: L. Robert Kimball & Associates, 615 West Highland Avenue, Ebensburg, PA 15931, 814–472–7700

Construction manager: None

Groundbreaking: April 1984 Finish date: February 1986 Construction time: 22 months Design capacity: 76 Total cost: \$5,408,522

Total annual operating costs:

\$1,578,000

Category: New, independent facility

Facility type: County jail

Building configuration: Integrated

structure

#### **Costs**

Total: \$5,408,522

Building only: \$5,172,289 Housing area: Unknown Housing per inmate: Unknown Housing per cell: Unknown Total per inmate: \$71,165 Total per GSF: \$109.48

Total annual operating costs: \$1,578,000

#### **Dimensions**

Gross square feet/corrections: 49,400

Gross square feet/other: 0 Gross square feet/total: 49,400 Housing area square feet: 15,300 Gross square feet per inmate: 650 Size of cells: 60 to 80 square feet (single)

Net/gross square feet: N/A

# **Inmate housing areas**

Design: Module/pod Cells per unit: 4 to 12 Inmates per unit: 4 to 12

Management type: Remote surveillance

October 1985 population: 56

Facility commitment: Local jail inmates Means to handle crowding: Mattresses

on floor

# **Security**

Perimeter: Building exterior only

Inmate security level:
Maximum: 20%
Medium: 60%
Minimum: 20%

# **Construction type**

Structural: Steel frame Exterior walls: Brick Interior walls: CMU block Exterior surface/facade: Brick

# **Construction process**

Finance method: G.O. Bonds Contract method: Conventional Use of inmate labor: None Use of prefabrication: None

#### **Inmate cells**

Doors/material: Steel Doors/type: Sliding

Doors/locking: Motor driven and

remote locking

Floor surface: Sealed concrete

Intercom: Two-way to cells and common

areas

HVAC: Air conditioning; steam heating

plant

Plumbing: Stainless Furniture: Steel

Fire protection: Smoke detectors and sprinklers for cells and common areas; manual alarm stations; smoke ejectors

# Inmate design capacity

Single occupancy: 69 Double occupancy: 0

Dorms: 0

Special housing: 7 General population: 69

Total: 76

# Architect's reported analyses

Factors affecting construction costs: Positive: Simple construction methods, repetitiveness of design; competitive

bidding climate

Negative: High labor costs; only one

prison equipment bidder

Factors affecting time schedule: Positive: Simple construction methods, repetitiveness of design; coordination

of design between parties

Negative: Labor, weather, and contractor

problems


#### **Current staff**

Full-time equivalent: Administration: 4 Security: 55

Programs/treatment: 1 Maintenance: 4

Total: 64

Current inmate/staff ratio: .87:1



# **Bernalillo County Detention Center (South Tower)**

Jurisdiction official: Michael F. Hanrahan, Director

Contact: Michael F. Hanrahan, Director, Bernalillo County Detention Center, 415 Roma Street NW., Albuquerque, NM 87102,

505-764-3590

Architect: Hellmuth, Obata & Kassabaum, Inc., One Lombard Street, San Francisco, CA 94111, 415-627-1600

Construction manager: None

**Groundbreaking:** July 1977 Finish date: November 1979 Construction time: 28 months Design capacity: 300 **Total cost:** \$7,000,000

**Dimensions** 

Total annual operating costs: N/A

Gross square feet/corrections: 107,000

(addition added later)

Gross square feet/other: 0

Net/gross square feet: 65%

Gross square feet/total: 107,000

Housing area square feet: 71,690

Gross square feet per inmate: 357

Size of cells: 71 square feet (single)

Category: New, independent facility

Facility type: County jail

**Building configuration:** Integrated structure; high rise; clusters

Costs

Total: \$7,000,000

Building only: \$6,800,000 Housing area: \$4,690,000 Housing per inmate: \$16,285 Housing per cell: \$16,285 Total per inmate: \$23,333 Total per GSF: \$65.42

Total annual operating costs: N/A

(addition added later)

Construction type

Structural: Steel frame Exterior walls: Precast panels

Interior walls: Cast-in-place concrete Exterior surface/facade: Metal with

fiberglass insulation

Security

Perimeter: Building exterior only

Inmate security level:

Maximum: 100% (design) Medium: 100% (use)

Minimum: 0

**Inmate cells** 

areas

Doors/material: Steel

Doors/type: Swinging

Plumbing: Stainless

and common areas

Furniture: Steel

Doors/locking: Remote locking only

HVAC: Heating/air circulation only

Intercom: One-way to cells and common

Fire protection: Smoke detectors for cells

Floor surface: Sealed concrete

Inmate design capacity

Single occupancy: 288 Double occupancy: 0

Special housing: 12 General population: 288

Total: 300

Dorms: 0

Security: N/A

Programs/treatment: N/A

Total: N/A (addition added later)

Inmate housing areas

Design: Module/pod Cells per unit: 48 Inmates per unit: 48

Management type: Remote surveillance;

patrols

October 1985 population: 288

Facility commitment: Local jail inmates;

State prisoners

Means to handle crowding: Bunk beds

in cell; mattresses on floor

**Construction process** 

Finance method: G.O. Bonds Contract method: Conventional Use of inmate labor: None

Use of prefabrication: Moderate; exterior

walls

Architect's reported analyses

Factors affecting construction costs: Positive: Good bidding climate; low

area/bed cost Negative: None

Factors affecting time schedule:

Positive: None

Negative: Contractor problems

# **Current staff**

Full-time equivalent: Administration: N/A

Maintenance: N/A

Current inmate/staff ratio: N/A

# **Central New Mexico Correctional Facility**

Jurisdiction official: O.L. McCotter, Secretary, Corrections Department

Contact: Warden Dareld Kerby, Central New Mexico Correctional Facility, P.O. Drawer 1328, Los Lunas, NM 87031, 505-865-2300 Architect: W.C. Kruger & Associates, Architects-Planners, Inc., P.O. Box 1084, Albuquerque, NM 87103, 505-842-8663

Construction manager: None

**Groundbreaking:** December 1980 Finish date: October 1982 **Construction time:** 21 months

**Design capacity:** 486 **Total cost:** \$18,975,756 **Total annual operating costs:** 

\$8,800,000

Category: New, independent facility

Facility type: State prison **Building configuration:** Clusters:

campus style

#### Costs

Total: \$18,975,756 Building only: Unknown Housing area: Unknown Housing per inmate: Unknown Housing per cell: Unknown Total per inmate: \$39,045 Total per GSF: \$110.80

Total annual operating costs: \$8,800,000

## **Dimensions**

Gross square feet/corrections: 171,267 Gross square feet/other: 0 Gross square feet/total: 171,267 Housing area square feet: 70,550 Gross square feet per inmate: 352 Size of cells: 63 square feet (single) Net/gross square feet: Unknown

# **Construction type**

Structural: 2-story precast concrete, exterior walls and roof

Exterior walls: Precast load bearing concrete

Interior walls: Load bearing CMU interior

partitions

Exterior surface/facade: Natural wall,

no coating or treatment

# **Security**

Perimeter: Double fence with razor wire; alarm/detection system; tower Inmate security level:

Maximum: 0 Medium: 100% Minimum: 0

#### **Inmate cells**

Doors/material: Steel Doors/type: Swinging

Doors/locking: Remote locking Floor surface: Sealed concrete

Intercom: Two-way control to common areas; pager to common areas HVAC: Heating/air circulation only

Plumbing: Stainless steel Furniture: Wood; concrete

Fire protection: Smoke detectors and sprinklers for cells and common areas

## Inmate design capacity

Single occupancy: 486 Double occupancy: 0

Dorms: 0

Special housing: 0 General population: 486

Total: 486

#### **Current staff**

Full-time equivalent: Administration: 22 Security: 202

Programs/treatment: 31 Maintenance: 18

Total: 273

Current inmate/staff ratio: 1.76:1

## **Inmate housing areas**

Design: Module/pod Cells per unit: 48 Inmates per unit: 48

Management type: Remote surveillance

October 1985 population: 480 Facility commitment: State prisoners Means to handle crowding: Bunks on floor

in common areas

### **Construction process**

Finance method: State funds Contract method: Conventional Use of inmate labor: None

Use of prefabrication: Extensive; precast concrete walls and roof system

# Architect's reported analyses

Factors affecting construction costs: Positive: Use of prefabricated components Negative: Complex electronic, mechanical, and electrical systems

Factors affecting time schedule: Positive: Use of prefabricated components Negative: Complex electronic,

mechanical, and electrical systems

# Penitentiary of New Mexico

Jurisdiction official: O.L. McCotter, Secretary, Corrections Department

Contact: Efren Montoya, Admin. Assistant, Penitentiary of New Mexico, P.O. Box 1059, Santa Fe, NM 87504-1059, 505-471-7300

Joint venture architects: The Gruzen Partnership, 251 Post Street, San Francisco, CA 94108, 415-956-5515

Hutchinson, Brown & Partners, 215 Gold SW., Albuquerque, NM 87102, 505-842-5630

Construction manager: None

Groundbreaking: June 1982 Finish date: March 1985 Construction time: 33 months Design capacity: 576
Total cost: \$32,525,610
Total annual operating costs: \$3,700,000

Category: New, independent facility Facility type: State prison Building configuration: Clusters

#### **Costs**

Total: \$32,525,610

Building only: \$29,085,682

Housing area: \$27,192,158 (incl. special

housing)

Housing per inmate: \$47,209 Housing per cell: \$47,209 Total per inmate: \$56,468 Total per GSF: \$114.01

Total annual operating costs: \$3,700,000

# **Security**

Perimeter: Double fence; alarm/detection

systems; patrols Inmate security level: Maximum: 50% Medium: 50% Minimum: 0

#### **Inmate cells**

Doors/material: Steel

Doors/type: Swinging; sliding

Doors/locking: Motor driven and remote

locking

Floor surface: Sealed concrete

Intercom: Two-way to cells and common

areas

HVAC: Evaporative cooling; central heating plant—boiler unit

Plumbing: Stainless steel Furniture: Steel; concrete

Fire protection: Smoke detectors for cells and common areas; sprinklers for

common areas

#### **Dimensions**

Gross square feet/corrections: 285,272

Gross square feet/other: 0 Gross square feet/total: 285,272 Housing area square feet: 188,820 Gross square feet per inmate: 495 Size of cells: 80 square feet (single)

Net/gross square feet: 72%

## **Construction type**

Structural: Load bearing precast panels; cast-in-place and precast concrete frame Exterior walls: Precast panels; cast-in-

place concrete

Interior walls: Precast panels; cast-inplace concrete; CMU block Exterior surface/facade: Paint

## Inmate design capacity

Single occupancy: 384 Double occupancy: 0

Dorms: 0

Special housing: 192 General population: 384

Total: 576

# **Current staff**

Full-time equivalent: Administration: 5 Security: 97

Programs/treatment: 18

Maintenance: 3 Total: 123

Current inmate/staff ratio: 1.31:1

# **Inmate housing areas**

Design: Module/pod Cells per unit: 48 Inmates per unit: 48

Management type: Remote surveillance

October 1985 population: 161 Facility commitment: State prisoners Means to handle crowding: N/A

# **Construction process**

Finance method: State funds

Contract method: Construction manage-

ment fast track

Use of inmate labor: Limited; contractors

trained inmates

Use of prefabrication: Limited; precast


panels

# Architects' reported analyses

Factors affecting construction costs:
Positive: Simple construction methods,
repetitiveness of design; good
competition, favorable market; less
expensive materials and hardware
Negative: Government "red tape"; complex
electronic, mechanical, and electrical
systems; multiple-bid contracts

Factors affecting time schedule:
Positive: Repetitiveness of design;
coordination of design between parties
Negative: Slow responses from vendors;
weather problems; complex electronic,
mechanical, and electrical systems;

multiple-bid contracts



# **Southern New Mexico Correctional Facility**

Jurisdiction official: O.L. McCotter, Secretary, Corrections Department

Contact: Warden Eloy Mondragon, Southern New Mexico Correctional Facility, P.O. Box 639, Las Cruces, NM 88004,

505-523-3200

Architect: W.C. Kruger & Associates, Architects-Planners, Inc., P.O. Box 1084, Albuquerque, NM 87103, 505-842-8663 Construction manager: Morrison-Knudsen Company, Inc., Two Morrison Knudsen Plaza, Boise, ID 83729, 208-386-6162

Groundbreaking: December 1982

Finish date: July 1985

**Construction time:** 31 months

**Design capacity:** 480 **Total cost:** \$25,289,795

Total annual operating costs:

\$8,862,986 (excluding medical)

Category: New, independent facility

Facility type: State prison

**Inmate housing areas** 

Design: Module/pod

Inmates per unit: 48

roving foot patrols

October 1985 population: 480

Cells per unit: 48

dayroom

Building configuration: Clusters;

campus style

#### **Costs**

Total: \$25,289,795

Building only: \$24,689,795

Housing area: Unknown

Housing per inmate: Unknown Housing per cell: Unknown

Total per inmate: \$52,687 Total per GSF: \$109.01

Total annual operating costs: \$8,862,986

(excluding medical)

#### Security

Perimeter: Double fence with razor wire; alarm/detection system; tower

Inmate security level:

Maximum: 0 Medium: 100% Minimum: 0

# **Dimensions**

Gross square feet/corrections: 231,994

Gross square feet/other: 0

Gross square feet/total: 231,994 Housing area square feet: 125,000 Gross square feet per inmate: 483 Size of cells: 80 square feet (single) Net/gross square feet: Unknown

# **Construction type**

Structural: Cast-in-place concrete

Exterior walls: Precast roof and exterior walls; precast concrete panels

Interior walls: Load bearing CMU interior

walls

Exterior surface/facade: Natural wall,

no coating or treatment

# **Construction process**

Finance method: State funds

Contract method: Construction manage-

Management type: Remote surveillance;

Facility commitment: State prisoners

Means to handle crowding: Beds in

ment fast track

Use of inmate labor: None
Use of prefabrication: Extensive;
precast concrete walls and roof system

# **Inmate cells**

Doors/material: Steel Doors/type: Swinging

Doors/locking: Remote electronic locking

with key override

Floor surface: Sealed concrete
Intercom: Two-way to common areas
HVAC: Heating/air circulation only
Plumbing: Stainless steel; china
Furniture: Wood; concrete

Fire protection: Smoke detectors and sprinklers for cells and common areas

# Inmate design capacity

Single occupancy: 480 Double occupancy: 0

Dorms: 0

Special housing: 0 General population: 480

Total: 480

## **Current staff**

Full-time equivalent: Administration: 16 Security: 199

Programs/treatment: 38

Maintenance: 11

Total: 264 (excludes medical, mental health, corr. indus., food service)
Current inmate/staff ratio: 1.82:1

# Architect's reported analyses

Factors affecting construction costs:
Positive: Use of prefabricated components;
simple construction methods; fast track
construction; good bidding market
Negative: State requirement of hiring

outside construction manager; high labor costs; government "red tape"

Factors affecting time schedule:
Positive: Use of prefab. components;
simple con. methods; fast track con.;
advanced order of materials and hardware; coordination of design

Negative: 15 bid packages; slow delivery from suppliers; complex electronic, mechanical, and electrical systems

# **Western New Mexico Correctional Facility**

Jurisdiction official: O.L. McCotter, Secretary, Corrections Department

Contact: Warden Tom Newton, Western New Mexico Correctional Facility, P.O. Drawer 250, Lobo Canyon Road, Grants, NM 87020, 505–287–7961

NM 8/020, 505-28/-/961

Architect: W.C. Kruger & Associates, Architects-Planners, Inc., First Interstate Bank Building, Suite 1100, 4th and Gold Southwest,

P.O. Box 1084, Albuquerque, NM 87103, 505-842-8663

Construction manager: None

Groundbreaking: March 1983 Finish date: September 1984 Construction time: 18 months Design capacity: 258
Total cost: \$15,404,215
Total annual operating costs: \$5,721,400

Category: New, independent facility Facility type: State prison Building configuration: Clusters;

campus style

#### Costs

Total: \$15,404,215 Building only: \$14,967,728 Housing area: Unknown Housing per inmate: Unknown Housing per cell: Unknown Total per inmate: \$59,706 Total per GSF: \$116.34

Total annual operating costs: \$5,721,400

#### **Dimensions**

Gross square feet/corrections: 132,409 Gross square feet/other: 0 Gross square feet/total: 132,409 Housing area square feet: 57,842 Gross square feet per inmate: 513 Size of cells: 63 square feet (single) Net/gross square feet: Unknown

# **Construction type**

Structural: Load bearing precast panels; load bearing CMU

Exterior walls: Precast panels Interior walls: CMU block

Exterior surface/facade: Colored and

textured concrete

# Security Struct loa

Perimeter: Building exterior; double fence with razor wire; detection system; towers; patrols

Inmate security level:
Maximum: 30%
Medium: 40%
Minimum: 30%

Doors/material: Steel Doors/type: Swinging

Doors/locking: Manual and remote

locking

**Inmate cells** 

Floor surface: Sealed concrete

Intercom: Two-way to cells and common

areas: all call

HVAC: Air conditioning; heating/air circulation; heat pumps; fan coil units;

central boiler plant

Plumbing: Stainless steel; china; cast

iron rough plumbing Furniture: Wood; concrete

Fire protection: Smoke detectors for common areas; sprinklers throughout

facility

# Inmate design capacity

Single occupancy: 232 Double occupancy: 0

Dorms: 0 Other: 11

Special housing: 15 General population: 243

Total: 258

#### **Current staff**

Full-time equivalent: Administration: 42 Security: 117

Programs/treatment: 22 Maintenance: 10

Total: 191

Current inmate/staff ratio: 1.31:1

#### **Inmate housing areas**

Design: Module/pod Cells per unit: 24, 32, 48 Inmates per unit: 24, 32, 48

Management type: Remote surveillance

October 1985 population: 251 Facility commitment: State prisoners

Means to handle crowding: Beds in dayroom and hallways

# **Construction process**

Finance method: State funds Contract method: Conventional Use of inmate labor: None

Use of prefabrication: Extensive; precast

walls and roof system

# Architect's reported analyses

Factors affecting construction costs:
Positive: Use of prefab. components;
simple con. methods; fast track con.;
good bidding market; good contractors
and inspector

Negative: High labor costs; government "red tape"; remote location

Factors affecting time schedule: Positive: Use of prefab. components; simple con. methods: fast track con

simple con. methods; fast track con.; adv. order of materials and hardware; coordination of design; gen. contr. in

charge of purchasing

Negative: Some slow delivery from vendors, suppliers; government "red tape"; complex electronic, mechanical, and electrical systems

# Youth Diagnostic and Development Center

Jurisdiction official: Lloyd W. Mixdorf, Director, Juvenile Facilities and Programs Division

Contact: Superintendent Celedonio Vigil, Youth Diagnostic and Development Center, 4000 Edith Boulevard, Albuquerque,

NM 87107, 505-841-2400

Architect: Fernandez, Lujan, Beltran, Inc., 8009 Marble Northeast, Albuquerque, NM 87110, 505-262-2391

Construction manager: None

**Groundbreaking:** April 1982 **Finish date:** April 1983

Construction time: 12 months

Design capacity: 100 Total cost: \$1,800,000 Total annual operating costs:

\$2,728,000

Category: New, independent facility Facility type: State youth detention

facility

Building configuration: Campus style

#### **Costs**

Total: \$1,800,000 Building only: \$1,300,000 Housing area: Unknown Housing per inmate: Unknown

Housing per cell: Unknown Total per inmate: \$18,000 Total per GSF: \$75.00

Total annual operating costs: \$2,728,000

#### **Dimensions**

Gross square feet/corrections: 24,000

Gross square feet/other: 0 Gross square feet/total: 24,000 Housing area square feet: 12,000 Gross square feet per inmate: 240 Size of cells: 75 square feet (per inmate)

Net/gross square feet: 81%

# **Inmate housing areas**

Design: Module/pod Cells per unit: 20 Inmates per unit: 20–25

Management type: Direct supervision October 1985 population: 148 Facility commitment: Juveniles Means to handle crowding: Bunk beds

in cell; mattresses on floor

# Security

Perimeter: Single fence; alarm/detection

system

Inmate security level:
Maximum: 0
Medium: 0
Minimum: 100%

# **Construction type**

Structural: Steel frame; load bearing

masonry walls

Exterior walls: CMU block Interior walls: CMU block Exterior surface/facade: Stucco

# **Construction process**

Finance method: State funds Contract method: Conventional Use of inmate labor: None Use of prefabrication: None

#### **Inmate cells**

Doors/material: Wooden; steel

Doors/type: Swinging

Doors/locking: Manual locking

Floor surface: Linoleum; carpet; sealed

concrete; ceramic tile

Intercom: One-way to cells; two-way to

common areas

HVAC: Air conditioning; solar; gas-fired

heating plant/forced air Plumbing: Stainless Furniture: Wood

Fire protection: Sprinklers for cells and common areas; manual alarm stations

# Inmate design capacity

Single occupancy: 0
Double occupancy: 0

Dorms: 100 Special housing: 0 General population: 100

Total: 100

# Current staff

Full-time equivalent: Administration: 22 Security: 44

Programs/treatment: 32 Maintenance: 10

**Total: 108** 

Current inmate/staff ratio: 1.37:1

#### Architect's reported analyses

Factors affecting construction costs: Positive: Simple construction methods, repetitiveness of design; good competition, favorable market; durability of materials


Negative: Government "red tape"; complex electronic, mechanical, and electrical systems; vandal/tamper resistance requirements

Factors affecting time schedule:

Positive: Simple construction methods, repetitiveness of design; coordination

of design between parties

Negative: Weather problems; government procedures, regulations, "red tape"; complex electronic, mechanical, and electrical systems (solar units)



# Youth Diagnostic and Development Center—Phase III (Addition/Expansion)

Jurisdiction official: Lloyd W. Mixdorf, Director, Juvenile Facilities and Programs Division

Contact: Superintendent Caledonio Vigil, Youth Diagnostic and Development Center, 4000 Edith Boulevard, Albuquerque,

NM 87107, 505–841–2400

Architect: Van H. Gilbert Architect, 319 Central Avenue NW., Suite 201, Albuquerque, NM 87102, 505-247-9955

Construction manager: None

Groundbreaking: September 1983

Finish date: March 1985 Construction time: 18 months **Design capacity:** 7 **Total cost:** \$2,551,601

Total annual operating costs: \$2,653,800

(entire facility)

Category: New, ancillary building;

expansion project

Facility type: State youth detention

facility support service

Building configuration: Courtyard;

clusters

#### Costs

Total: \$2,551,601

Building only: \$2,321,360

Housing area: N/A Housing per inmate: N/A Housing per cell: N/A Total per inmate: N/A Total per GSF: \$108.27

Total annual operating costs: \$2,653,800

(entire facility)

### **Security**

Perimeter: Building exterior; single

fence

Inmate security level:
Maximum: 100% (design)
Medium: 100% (use)

Minimum: 0

# **Dimensions**

Gross square feet/corrections: 23,568

Gross square feet/other: 0 Gross square feet/total: 23,568 Housing area square feet: N/A Gross square feet per inmate: 3,367 Size of cells: 72 square feet (spec. single)

Net/gross square feet: 80%

# **Construction type**

Structural: Steel frame

Exterior walls: Architectural precast; steel stud with exterior insulating finish

system

Interior walls: Steel stud drywall; CMU at

special housing

Exterior surface/facade: Exterior insulating

finishing system

# Inmate design capacity

Single occupancy: 0
Double occupancy: 0

Dorms: 0

Special housing: 7 General population: 0

Total: 7

# Inmate cells (No general population cells)

Doors/material: N/A Doors/type: N/A Doors/locking: N/A Floor surface: N/A Intercom: N/A HVAC: N/A Plumbing: N/A Furniture: N/A Fire protection: N/A

# **Current staff**

Full-time equivalent: Administration: 24 Security: 48

Security: 46

Programs/treatment: 28 Maintenance: 9

Total: 109 (entire facility)
Current inmate/staff ratio: 1.24:1

## **Inmate housing areas**

Design: N/A
Cells per unit: N/A
Inmates per unit: N/A

Management type: Direct supervision October 1986 population: 135 (entire

facility)

Facility commitment: Juveniles

Means to handle crowding: Mattresses on

floor

# **Construction process**

Finance method: G.O. Bonds Contract method: Conventional Use of inmate labor: None

Use of prefabrication: Limited; architectural precast and some stud wall framing prefabricated offsite

# Architect's reported analyses

Factors affecting construction costs: Positive: Good competition, favorable

market

Negative: Government procedures, regulations, and red tape


Factors affecting time schedule:

Positive: Simple construction methods,

repetitiveness of design

Negative: Slow responses and delivery

from vendors, suppliers



# **Brooklyn Correctional Facility (Remodel)**

Jurisdiction official: Richard J. Koehler, Commissioner, New York City Department of Corrections

Contact: Warden Marvin Fischer, Brooklyn Correctional Facility, 136 Flushing Avenue, Brooklyn, NY 11205, 718-802-3301 Architect: The Office of David Elliott Leibowitz, P.C., 70 West 40th Street, New York, NY 10018, 212-354-8100 Construction manager: A. J. Contracting Co., 470 Park Avenue South, New York, NY 10016, 212-889-9100

**Groundbreaking:** February 1984

Finish date: June 1986 Construction time: 28 months Design capacity: 810 **Total cost:** \$34,000,000

Total annual operating costs: Unknown

Category: Remodel/renovation project

Facility type: City jail

Building configuration: High rise; ladder, telephone pole; 5 stories,

6 wings per floor

#### Costs

Total: \$34,000,000 Building only: \$34,000,000 Housing area: \$14,000,000 Housing per inmate: \$17,284 Housing per cell: \$518,519

Total per inmate: \$41,975 Total per GSF: \$95.77

Total annual operating costs: Unknown

# **Dimensions**

Gross square feet/corrections: 355,000

Gross square feet/other: 0 Gross square feet/total: 355,000 Housing area square feet: 180,000 Gross square feet per inmate: 438 Size of cells: 2,059 square feet (dorm)

Net/gross square feet: 80%

### Construction type

Structural: Cast-in-place concrete frame Exterior walls: Cast-in-place concrete;

CMU block; brick; steel plate and insulated cementitious panels Interior walls: Cast-in-place concrete;

CMU block; gypsum board and steel sheet

Exterior surface/facade: Brick; paint; painted concrete and transite panels and

steel plate

# Security

Perimeter: Single fence; razor wire on fence; patrols; guard booths

Inmate security level: Maximum: 0 Medium: 100% Minimum: 0

#### Inmate design capacity **Inmate cells**

Doors/material: Steel Doors/type: Swinging

Doors/locking: Manual locking Floor surface: Vinyl tile

Intercom: One-way to common areas and

dorms

HVAC: Steam heat; ventilation by

operable windows Plumbing: China Furniture: Steel

Fire protection: Smoke detectors for cells and common areas; manual alarm stations; sprinklers in corridors

Single occupancy: 0 Double occupancy: 0

Dorms: 810 Special housing: 0 General population: 810

Total: 810

# **Current staff**

Full-time equivalent: Administration: 39 Security: 366

> Programs/treatment: 10 Maintenance: 18

Total: 433

Current inmate/staff ratio: 1.30:1

# **Inmate housing areas**

Design: Ladder, telephone pole; dormi-

tory style housing Cells per unit: 1 Inmates per unit: 30

Management type: Remote surveillance

July 1986 population: 561

Facility commitment: Local jail inmates;

State prisoners

Means to handle crowding: Unknown

# **Construction process**

Finance method: Local funds

Contract method: Construction manage-

ment fast track

Use of inmate labor: None Use of prefabrication: None

# Architect's reported analyses

Factors affecting construction costs: Positive: Fast track construction manage-

ment

Negative: Difficult site conditions; staged


occupancy of prison caused

escalation of costs as security require-

ments increased

Factors affecting time schedule:

Positive: Phased construction, fast track construction management; advanced order of materials and hardware; coordination of design between parties Negative: Phased occupancy of prison



# Elmira Correctional & Reception Center Food Service & Dining Facility (Remodel)

Jurisdiction official: Thomas A. Coughlin III, Commissioner, Department of Correctional Services

Contact: Superintendent Ronald E. Miles, Elmira Correctional & Reception Center, Corner of Bancroft & Davis Streets,

P.O. Box 500, Elmira, NY 14902, 607-734-3901

Architect: Quinlivan Pierik & Krause, Architects/Engineers, 101 East Water Street, P.O. Box 29, Syracuse, NY 13201-0029,

315-472-7806

Construction manager: None

**Groundbreaking:** August 1978 **Finish date:** December 1978 **Construction time:** 4 months

**Design capacity:** N/A **Total cost:** \$1,817,000

Total annual operating costs: \$1,290,000

Category: Remodeling/renovation project; phased project (past)

Facility type: State prison food service

and dining facility

**Building configuration:** Unknown

# **Costs**

Total: \$1,817,000

Building only: \$1,817,000

Housing area: N/A (no housing) Housing per inmate: N/A Housing per cell: N/A

Total per inmate: N/A (remodel)

Total per GSF: \$38.85

Total annual operating costs: \$1,290,000

#### **Dimensions**

Gross square feet/corrections: 46,768

Gross square feet/other: 0 Gross square feet/total: 46,768 Housing area square feet: 0 Gross square feet per inmate: N/A

Size of cells: None

Net/gross square feet: 84%

## **Inmate housing areas**

Design: N/A
Cells per unit: N/A
Inmates per unit: N/A
Management type: Unknown
Current population: N/A

Facility commitment: State prisoners Means to handle crowding: N/A

# **Security**

Perimeter: Building exterior; single

fence

Inmate security level:
Maximum: 100%
Medium: 0
Minimum: 0

# **Construction type**

Structural: Existing steel and concrete

Exterior walls: Brick

Interior walls: CMU block; brick Exterior surface/facade: Brick

## **Construction process**

Finance method: State funds Contract method: Conventional Use of inmate labor: None Use of prefabrication: None

# **Inmate cells (no cells)**

Doors/material: N/A Doors/type: N/A Doors/locking: N/A Floor surface: N/A Intercom: N/A HVAC: N/A Plumbing: N/A Furniture: N/A Fire protection: N/A

# Inmate design capacity

Single occupancy: N/A Double occupancy: N/A

Dorms: N/A

Special housing: N/A General population: N/A

Total: N/A

# Architect's reported analyses

Factors affecting construction costs: Positive: Good competition, favorable

market

Negative: Construction in occupied building; security procedures for

contractor workforce

Factors affecting time schedule:

Positive: Coordination between institution

and contractor

Negative: Building in use during

construction

#### Current staff

Full-time equivalent:

Administration: Unknown Security: Unknown

Programs/treatment: Unknown

Maintenance: Unknown

Total: Unknown

Current inmate/staff ratio: Unknown

# **Erie County Correctional Facility**

Jurisdiction official: Dennis Gorski, County Executive

Contact: Superintendent Frederick Netzel, Department of Corrections, Box X, Alden, NY 14004, 716–937–9101 Architect: Milstein, Wittek & Associates, Architects, P.C., 300 Delaware Avenue, Buffalo, NY 14202, 716-856-8320 Construction manager: John W. Cowper Company, 4246 Ridge Lea Road, Amherst, NY 14226, 716-837-8410

Groundbreaking: April 1984 Finish date: February 1986 Construction time: 22 months Design capacity: 402 **Total cost:** \$23,451,711 **Total annual operating costs:** \$4,987,265

Facility type: County jail

Building configuration: Integrated

Category: New, independent facility

structure; clusters

#### Costs

Total: \$23,451,711 Building only: \$21,919,871 Housing area: \$12,249,902 Housing per inmate: \$32,068 Housing per cell: \$32,068 Total per inmate: \$58,338 Total per GSF: \$112.60

Total annual operating costs: \$4,987,265

#### **Dimensions**

Gross square feet/corrections: 208,280 Gross square feet/other: 0 Gross square feet/total: 208,280 Housing area square feet: 97,371 Gross square feet per inmate: 518 Size of cells: 76 square feet (single)

Net/gross square feet: 72%

# **Inmate housing areas**

Design: Module/pod Cells per unit: 12, 24, 48 Inmates per unit: 48 (half pod)

Management type: Remote surveillance (max.); direct supervision (med.)

May 1986 population: 467

Facility commitment: Local jail inmates Means to handle crowding: None

# Security

Perimeter: Building exterior; single and double fences with razor wire; alarm detection system; patrols Inmate security level:

Maximum: 14.3% Medium: 85.7% Minimum: 0

# **Construction type**

Structural: Steel frame; cast-in-place

concrete frame

Exterior walls: CMU block; brick Interior walls: Cast-in-place concrete;

CMU block

Exterior surface/facade: Brick

# **Construction process**

Finance method: State funds

Contract method: Construction manage-

ment fast track

Use of inmate labor: None Use of prefabrication: None

#### **Inmate cells**

Doors/material: Steel Doors/type: Swinging

Doors/locking: Remote locking; manual

locking

Floor surface: Epoxy coating Intercom: Two-way to cells HVAC: Air conditioning; hot water heating/air circulation

Plumbing: Stainless combination unit;

china

Furniture: Steel

Fire protection: Smoke detectors and sprinklers for cells and common areas;

manual alarm stations

# Inmate design capacity

Single occupancy: 382 Double occupancy: 0

Dorms: 0

Special housing: 20 General population: 382

Total: 402

#### **Current staff**

Full-time equivalent: Administration: 25 Security: 134

> Programs/treatment: 19 Maintenance: 5

Total: 183


Current inmate/staff ratio: 2.55:1

# Architect's reported analyses

Factors affecting construction costs: Positive: Simple construction methods: phased construction, fast track construction management; less expensive materials and hardware Negative: Weather problems

Factors affecting time schedule: Positive: Simple construction methods; phased construction, fast track construction management; coordination of design between parties

Negative: Weather problems



# **Erie County Holding Center (Remodel/Expansion)**

Jurisdiction official: Thomas F. Higgins, Sheriff

Contact: Superintendent Raul Russi, Erie County Holding Center, 40 Delaware, Buffalo, NY 14202, 716-846-7636

Architects: Cannon Design, 2170 White Haven Boulevard, Grand Island, NY 14072, 716-745-3688

The Ehrenkrantz Group, 19 West 44th Street, New York, NY 10036-4072, 212-730-1950

Construction manager: Siegfried Construction, 1 Town Center, Audubon-Amherst, Buffalo, NY 14228, 716-689-8500

Groundbreaking: March 1984 Finish date: September 1986 Construction time: 30 months

Design capacity: 516 Total cost: \$20,000,000

Total annual operating costs: N/A

(expansion)

Category: Remodeling/renovation proj-

ect; expansion project Facility type: County jail

Building configuration: Integrated

Management type: Direct supervision

Facility commitment: Local jail inmates

Means to handle crowding: Unknown

November 1987 population: 532

structure; high rise

Design: Module/pod

Inmates per unit: 48

Cells per unit: 48

**Inmate housing areas** 

## Costs

Total: \$20,000,000

Building only: \$19,850,000

Housing area: Unknown Housing per inmate: Unknown Housing per cell: Unknown Total per inmate: N/A (remodel)

Total per GSF: \$142.86

Total annual operating costs: N/A

(expansion)

#### Security

Perimeter: Video camera surveillance

Inmate security level: Maximum: 0 Medium: 100% Minimum: 0

# **Dimensions**

Gross square feet/corrections: 140,000

Gross square feet/other: 0 Gross square feet/total: 140,000 Housing area square feet: 62,294 Gross square feet per inmate: 271 Size of cells: 70 square feet (gen. single);

80 square feet (spec. single) Net/gross square feet: 63%

# Construction type

Structural: Cast-in-place concrete frame Exterior walls: Architectural precast Interior walls: Cast-in-place concrete; CMU block; gypsum board; security

plaster

Exterior surface/facade: Architectural

precast panels

# **Construction process**

Finance method: Local funds; State funds Contract method: Construction manage-

ment fast track

Use of inmate labor: None

Use of prefabrication: Moderate; exterior

wall panels

#### **Inmate cells**

Doors/material: Steel Doors/type: Swinging

Doors/locking: Remote locking Floor surface: Sealed concrete

Intercom: One-way to cells; PA system throughout facility; intercom for door

operation

HVAC: Air conditioning; gas heat

Plumbing: China

Furniture: Steel; wood; vinyl/plastic Fire protection: Smoke detectors and sprinklers for cells and common areas; manual alarm stations; preaction system with abort function

# Inmate design capacity

Single occupancy: 468 Double occupancy: 0

Dorms: 0

Special housing: 48 General population: 468

Total: 516

#### Current staff

Full-time equivalent:

Administration: Unknown

Security: Unknown

Programs/treatment: Unknown

Maintenance: Unknown

Total: Unknown

Current inmate/staff ratio: Unknown


# Architects' reported analyses

Factors affecting construction costs: Positive: Prefab. components, factory assembly; phased const., fast track CM; favorable market; less expensive materials; new generation jail

Negative: Difficult site conditions; complex electronic and mechanical systems

Factors affecting time schedule: Positive: Prefab. components, factory assembly; phased const., fast track CM; coordination of design between parties

Negative: Difficulty in getting security systems subcontractor to deliver materials per specs and on time



# **Federal Correctional Institution**

Jurisdiction official: J. Michael Ouinlan, Director, Bureau of Prisons

Contact: Warden Jesse R. James, Federal Correctional Institution, Otisville, NY 10963, 914-386-5855 Architect: Davis Brody and Associates, 100 East 42nd Street, New York, NY 10017, 212-599-7272

Construction manager: Lasker Goldman Corporation, 470 Park Avenue South, New York, NY 10016, 212-481-3409

Groundbreaking: October 1976 Finish date: October 1980 **Construction time:** 48 months

Design capacity: 500 **Total cost:** \$16,861,964 Total annual operating costs:

\$7,712,800

Category: New, independent facility

Facility type: Federal prison

Building configuration: Campus style

#### Costs

Total: \$16,861,964 Building only: \$14,315,000

Housing area: Unknown Housing per inmate: Unknown Housing per cell: Unknown Total per inmate: \$33,724 Total per GSF: \$63.58

Total annual operating costs: \$7,712,800

# **Dimensions**

Gross square feet/corrections: 265,195

Gross square feet/other: 0 Gross square feet/total: 265,195 Housing area square feet: 94,104 Gross square feet per inmate: 530 Size of cells: 84 square feet (single)

Net/gross square feet: 74%

# **Construction type**

Structural: Concrete columns/block Exterior walls: Masonry walls reinforced with steel rods and concrete grout

Interior walls: CMU block

Exterior surface/facade: Natural wall,

no coating or treatment

# Security

Perimeter: Double fence; razor wire on fence; alarm/detection system; patrols Inmate security level:

Maximum: 0 Medium: 100% Minimum: 0

#### **Inmate cells**

Doors/material: Steel Doors/type: Swinging

Doors/locking: Manual locking Floor surface: Vinyl tile

Intercom: None

HVAC: Heating/air circulation only

Plumbing: China Furniture: Wood

Fire protection: Smoke detectors in ducts

# Inmate design capacity

Single occupancy: 390 Double occupancy: 0

Dorms: 0

Special housing: 110 General population: 390

Total: 500

#### **Current staff**

Full-time equivalent: Administration: 44 Security: 100

> Programs/treatment: 70 Maintenance: 32

Total: 246

Current inmate/staff ratio: 3.12:1

## **Inmate housing areas**

Design: Module/pod Cells per unit: 65 Inmates per unit: 65-130

Management type: Direct supervision;

TV surveillance

September 1987 population: 767

Facility commitment: Federal prisoners Means to handle crowding: Bunk beds

in cell

# Construction process

Finance method: Federal funds

Contract method: Construction manage-

ment fast track

Use of inmate labor: Limited; interior painting; floor tile; concrete walks;

finished site work Use of prefabrication: None


# Architect's reported analyses

Factors affecting construction costs:

Positive: Unknown Negative: Unknown

Factors affecting time schedule:

Positive: Unknown Negative: Unknown



# **Federal Correctional Institution**

Jurisdiction official: J. Michael Quinlan, Director, Bureau of Prisons

Contact: Warden John T. Hadden, Federal Correctional Institution, Ray Brook, NY 12977-0300, 518-891-5400 Architect: The Robinson Green Beretta Corporation, 2 John Street, Providence, RI 02906, 401-272-1730 Construction manager: Gilbane Building Company, 90 Calverley Street, Providence, RI 01940, 401-456-5800

Groundbreaking: May 1977 Finish date: December 1980 Construction time: 43 months

Design capacity: 534 Total cost: \$21,424,630

Total annual operating costs:

\$8,000,000

Category: New, independent facility

Facility type: Federal prison

Building configuration: Campus style

#### **Costs**

Total: \$21,424,630

Building only: \$21,270,040 Housing area: Unknown Housing per inmate: Unknown Housing per cell: Unknown Total per inmate: \$40,121 Total per GSF: \$76.16

Total annual operating costs: \$8,000,000

#### **Dimensions**

Gross square feet/corrections: 281,310

Gross square feet/other: 0 Gross square feet/total: 281,310 Housing area square feet: 144,000 Gross square feet per inmate: 527 Size of cells: 91 square feet (single)

Net/gross square feet: N/A

# Inmate housing areas

Design: Module/pod Cells per unit: 102 Inmates per unit: 102

Management type: Direct supervision

October 1985 population: 797

Facility commitment: Federal prisoners Means to handle crowding: Bunk beds in

cell

# **Security**

Perimeter: Double fence; alarm/detection systems; razor wire on fences; razor

wire between fences; patrols

Inmate security level:
Maximum: 4.5%
Medium: 95.5%
Minimum: 0

# **Construction type**

Structural: Cast-in-place concrete frame

Exterior walls: Brick Interior walls: CMU block Exterior surface/facade: Brick

# **Construction process**

Finance method: Federal funds
Contract method: Construction management fast track; sealed bidding
Use of inmate labor: None
Use of prefabrication: None

# **Inmate cells**

Doors/material: Steel Doors/type: Swinging

Doors/locking: Manual locking Floor surface: Vinyl tile; carpet

Intercom: Unknown

HVAC: Heating/air circulation only

Plumbing: China Furniture: Wood

Fire protection: Smoke detectors for cells

# Inmate design capacity

Single occupancy: 510 Double occupancy: 0

Dorms: 0

Special housing: 24 General population: 510

Total: 534

# Architect's reported analyses

Factors affecting construction costs:
Positive: Simple construction methods,

repetitiveness of design

Negative: Difficult site conditions; remote location, limited labor pool

Factors affecting time schedule:

Positive: Phased construction, fast track construction management; advanced order of materials and hardware; coordination of design between parties

Negative: Weather problems


#### **Current staff**

Full-time equivalent: Administration: 29 Security: 91

Programs/treatment: 24 Maintenance: 13

Total: 157

Current inmate/staff ratio: 5.08:1



# **Kirby Forensic Psychiatric Center (Remodel)**

Jurisdiction official: Richard C. Surles, Commissioner, New York State Office of Mental Health

Contact: Stuart Linder, Director, Admin. Services, Kirby Forensic Psychiatric Center, Wards Island, New York, NY 10035,

212-427-9003

Architect: Rose, Beaton + Rose, 81 Main Street, White Plains, NY 10601, 914-682-4850

Construction manager: Facilities Development Corporation, 44 Holland Avenue, Albany, NY 12208, 518-474-2121

Groundbreaking: July 1982 Finish date: December 1984 Construction time: 29 months Design capacity: 356 Total cost: \$4,328,172 Total annual operating costs:

\$8,770,000

Category: Remodel, renovation of

psychiatric hospital

Facility type: State forensic treatment

center

Building configuration: High rise

#### Costs

Total: \$4,328,172 Building only: \$3,447,610 Housing area: Unknown Housing per inmate: Unknown Housing per cell: Unknown Total per inmate: N/A (remodel) Total per GSF: N/A (remodel)

Total annual operating costs: \$8,770,000

#### **Dimensions**

Gross square feet/corrections: 252,835 Gross square feet/other: 0 Gross square feet/total: 252,835 Housing area square feet: 184,860 Gross square feet per inmate: 710 Size of cells: N/A (hospital) Net/gross square feet: 59%

# **Construction type**

Structural: Fireproofed steel frame Exterior walls: Brick facing with terra cotta block backup

Interior walls: Cast-in-place concrete floors; terra cotta block partitions Exterior surface/facade: Brick

## Security

Perimeter: Double fence; sensor and razor wire on fence; microwave detection

Inmate security level:
Maximum: 100%
Medium: 0
Minimum: 0

# Inmate design capacity

Single occupancy: 13 Double occupancy: 78

Dorms: 234 Special housing: 31 General population: 325

Total: 356

#### **Inmate cells**

Doors/material: Steel Doors/type: Swinging

Doors/locking: Manual locking

Floor surface: Linoleum; existing terrazzo

Intercom: None

HVAC: Heating/air circulation only;

steam heating plant Plumbing: China Furniture: Wood

Fire protection: Smoke detectors in

corridors

#### **Current staff**

Full-time equivalent: Administration: 58 Security: 160

Programs/treatment: 70 Maintenance: 40

Total: 328

Current inmate/staff ratio: .46:1

# Inmate housing areas

Design: Dormitory style Cells per unit: N/A Inmates per unit: 25

Management type: Direct supervision October 1985 population: 150 Facility commitment: State prisoners Means to handle crowding: Additional

beds in dormitory area

## **Construction process**

Finance method: State funds

Contract method: Conventional; six prime

contractors

Use of inmate labor: None Use of prefabrication: None

# Architect's reported analyses

Factors affecting construction costs: Positive: Building had been a psychiatric hospital, well built and adaptable

to design criteria

Negative: Poor heating system could not be rehabilitated

Factors affecting time schedule:

Positive: Structural modifications were

minimal

Negative: Contractor problems

New	York
N	lew Vork

# Masten Park Secure Center (Remodel/Expansion)

Jurisdiction official: Leonard G. Dunston, Director, New York State Executive Department Division for Youth

Contact: Ruth M. Noriega, Director, Masten Park Secure Center, 485 Best Street, Buffalo, NY 14208, 716-881-7577 Architect: Milstein, Wittek & Associates, Architects, P.C., 300 Delaware Avenue, Buffalo, NY 14202, 716-856-8320

Construction manager: None

**Groundbreaking:** September 1980

Finish date: June 1983

Construction time: 33 months

**Design capacity:** 68 **Total cost: \$2.630.695** 

Total annual operating costs: N/A

(expansion)

Category: Remodeling/renovation

project; expansion

Facility type: State secure center for

youth

Building configuration: Campus style

#### Costs

Total: \$2,630,695

Building only: \$2,480,000 Housing area: \$929,120 Housing per inmate: \$15,485 Housing per cell: \$15,485

Total per inmate: N/A (remodel)

Total per GSF: \$48.90

Total annual operating costs: N/A

(expansion)

# Security

Perimeter: Single fence; razor wire on fence; video camera surveillance

Inmate security level: Maximum: 100% Medium: 0 Minimum: 0

Inmate cells

Doors/material: Steel

Doors/type: Swinging

Floor surface: Vinyl tile

steam heating plant

Plumbing: Stainless steel

dry sprinkler in attic

Furniture: Steel; wood

Doors/locking: Manual locking

Intercom: Two-way to common areas

HVAC: Heating/air circulation only;

Fire protection: Smoke detectors for

cells and common areas: manual

alarm stations; standpipe system;

#### **Dimensions**

Gross square feet/corrections: 53,799

Gross square feet/other: 0 Gross square feet/total: 53,799 Housing area square feet: 20,156 Gross square feet per inmate: 791 Size of cells: 93 square feet (single)

Net/gross square feet: 83%

# **Construction type**

Structural: Steel frame; load-bearing

masonry

Exterior walls: Brick; stone

Interior walls: CMU block; reinforced

veneer plaster system

Exterior surface/facade: Brick; stone

# Inmate design capacity

Dorms: 0

Special housing: 8 General population: 60

Total: 68

Single occupancy: 60 Double occupancy: 0

#### **Current staff**

Full-time equivalent:

Administration: Unknown

Security: Unknown

Programs/treatment: Unknown Maintenance: Unknown Total: 147 (entire facility) Current inmate/staff ratio: .68:1

(entire facility)

# **Inmate housing areas**

Design: Module/pod Cells per unit: 16 Inmates per unit: 16

Management type: Direct supervision October 1985 population: 100 (entire

facility)

Facility commitment: Adjudicated youths,

13 to 21 years of age

Means to handle crowding: None

# **Construction process**

Finance method: State funds Contract method: Conventional Use of inmate labor: None Use of prefabrication: None

# Architect's reported analyses

Factors affecting construction costs: Positive: Simple construction methods: good competition, favorable markets; less expensive materials

and hardware

Negative: Slow construction; government procedures, regulations, "red tape"; complex electronic, mechanical, and electrical systems


Factors affecting time schedule:

Positive: Coordination of design between

parties

Negative: Slow responses and delivery from vendors, suppliers; government procedures, regulations, "red tape"; complex electronic, mechanical, and electrical systems

378



Jurisdiction official: Richard J. Koehler, Commissioner, New York City Department of Corrections

Contact: Warden Otis Bantum, North Facility, 1600 Hazen Street, East Elmhurst, New York, NY 11370, 718–956–2400 Architect: Gonchor & Sput Architects & Planners, 192 Lexington Avenue, New York, NY 10016, 212–685–2883 Construction manager: Morrison-Knudsen Company, 800 Second Avenue, 5th Floor, New York, NY 10017, 718–274–3856

**Groundbreaking:** March 1984

Finish date: April 1985 Construction time: 13 months **Design capacity:** 800 **Total cost:** \$38,840,000

Total annual operating costs: Unknown

Category: New, independent facility

Facility type: City jail

Building configuration: Telephone pole

with courtyard

#### **Costs**

Total: \$38,840,000

Building only: \$32,310,000 Housing area: \$17,500,000 Housing per inmate: \$21,875 Housing per cell: \$1,093,750 Total per inmate: \$48,550 Total per GSF: \$164.96

Total annual operating costs: Unknown

# **Dimensions**

Gross square feet/corrections: 235,450

Gross square feet/other: 0 Gross square feet/total: 235,450 Housing area square feet: 124,500 Gross square feet per inmate: 294 Size of cells: 3,485 square feet (dorms)

Net/gross square feet: 71%

# **Inmate housing areas**

Design: Ladder Cells per unit: 1

Inmates per unit: 57 to 87

Management type: Remote surveillance

January 1987 population: 1,324

Facility commitment: Local jail inmates Means to handle crowding: Bunk beds in

dormitory

# Security

Perimeter: Double fence; alarm/detection systems; razor wire on fences

Inmate security level:
Maximum: 0
Medium: 0
Minimum: 100%

# **Construction type**

Structural: Steel frame

Exterior walls: Cast-in-place concrete; pre-engineered metal building Interior walls: CMU block

Exterior surface/facade: Metal panels

# **Construction process**

Finance method: Local funds

Contract method: Construction manage-

ment fast track

Use of inmate labor: None Use of prefabrication: None

#### **Inmate cells**

Doors/material: Steel Doors/type: Swinging Doors/locking: Unknown Floor surface: Vinyl tile Intercom: Two-way to cells

HVAC: Steam heat; heating/air circulation

Plumbing: China Furniture: Steel; wood

Fire protection: Smoke detectors for cells and common areas; manual alarm stations; sprinklers for corridors and

storage areas

# Inmate design capacity

Single occupancy: 0 Double occupancy: 0 Dorms: 800 Special housing: 0 General population: 800

Total: 800

# **Current staff**

Full-time equivalent: Administration: 28 Security: 610

Programs/treatment: 90 Maintenance: 16

Total: 744

Current inmate/staff ratio: 1.78:1

#### Architect's reported analyses

Factors affecting construction costs:
Positive: Phased construction, fast track
CM; good competition, favorable

market

Negative: Difficult site conditions; complex electronic, mechanical, and electrical systems


Factors affecting time schedule:

Positive: Phased construction, fast track CM; advanced order of materials and hardware

hardware

Negative: Labor problems; complex electronic, mechanical, and electrical

systems



# **Rikers Island: Modular Units (Addition)**

Jurisdiction official: Richard J. Koehler, Commissioner, New York City Department of Corrections

Contact: Leonard Venachanos, Rikers Island, Hazen Street, East Elmhurst, NY 11370, 718-374-7934 Modular manufacturer: Arthur Industries, Inc., P.O. Box 74, Terryville, CT 06786, 203-582-6552

Construction manager: None

**Groundbreaking:** March 1985

Finish date: July 1985

**Construction time:** 4 months

Design capacity: 1,900

**Total cost:** \$32,609,440

Total annual operating costs: Unknown

Category: New, ancillary building

Facility type: City jail

**Building configuration:** Clusters

#### Costs

Total: \$32,609,440

Building only: \$32,609,440 Housing area: \$22,800,000 Housing per inmate: \$12,000 Housing per cell: \$1,200,000 Total per inmate: \$17,163 Total per GSF: \$133.45

Total annual operating costs: Unknown

## **Dimensions**

Gross square feet/corrections: 244,360

Gross square feet/other: 0 Gross square feet/total: 244,360 Housing area square feet: 178,080 Gross square feet per inmate: 129

Size of cells: Unknown Net/gross square feet: 85%

## **Inmate housing areas**

Design: Dormitory style Cells per unit: 1 Inmates per unit: 100

Management type: Remote surveillance

July 1986 population: 1,900

Facility commitment: Local jail inmates Means to handle crowding: New modular

construction

# Security

Perimeter: Double fence; razor wire on

fences; patrols Inmate security level: Maximum: 0 Medium: 100% Minimum: 0

## Construction type

Structural: Wood trusses Exterior walls: Wood framed Interior walls: Wood framed

Exterior surface/facade: Aluminum siding

### **Construction process**

Finance method: Local funds; capital budget for New York City Contract method: Conventional Use of inmate labor: None

Use of prefabrication: Extensive; all

modular construction

#### Inmate cells

Doors/material: Steel Doors/type: Swinging

Doors/locking: Remote locking Floor surface: Epoxy coating; vinyl tile Intercom: One-way to common areas HVAC: Air conditioning; electric heat

pump

Plumbing: China

Fire protection: Smoke detectors for

common areas

# Inmate design capacity

Single occupancy: 0 Double occupancy: 0 Dorms: 1,900 Special housing: 0 General population: 1,900

Total: 1,900

#### **Current staff**

Full-time equivalent: Administration: N/A

Security: 76


Programs/treatment: N/A Maintenance: N/A Total: 76 (addition only) Current inmate/staff ratio: 25.00:1

# Architect's reported analyses

Factors affecting construction costs: Positive: Prefabricated components, factory assembly; simple construction methods, repetitiveness of design; phased construction, fast track CM Negative: High labor costs; government procedures, regulations, and red tape

Factors affecting time schedule: Positive: Use of prefabricated components, factory assembly; simple construction methods, repetitiveness of design; phased construction, fast track CM

Negative: Slow responses and delivery from vendors, suppliers; labor problems



# **Craven County Law Enforcement Center**

Jurisdiction official: Pete Bland, Sheriff

Contact: Captain Ed Weigl, Jail Administrator, Craven County Law Enforcement Center, New Bern, NC 28560, 919-636-6619

Architect: J.N. Pease Associates, P.O. Box 18725, Charlotte, NC 28218, 704–376–6423

Construction manager: None

**Groundbreaking:** February 1982

Finish date: March 1984 Construction time: 24 months **Total cost:** \$3,500,000

**Design capacity: 78** 

Total annual operating costs: \$581,205

Category: New independent facility Facility type: Complex: county jail, law

Management type: Remote surveillance

Facility commitment: Local jail inmates

Means to handle crowding: Bunk beds

enforcement

Building configuration: Integrated

**Inmate housing areas** 

October 1985 population: 50

and State prisoners

Design: Module/pod

Inmates per unit: 24

Cells per unit: 24

structure

Costs

Total: \$3,500,000

Building only: \$3,200,000 Housing area: \$1,600,000 Housing per inmate: \$20,513 Housing per cell: \$20,513

Total per inmate: N/A (complex)

Perimeter: Building exterior only

Total per GSF: \$87.50

Inmate security level:

Maximum: 100%

Total annual operating costs: \$581,205

**Dimensions** 

Gross square feet/corrections: 20,000 Gross square feet/other: 20,000

Gross square feet/total: 40,000 Housing area square feet: N/A Gross square feet per inmate: 513

Size of cells: 72 square feet (single)

Net/gross square feet: 75%

**Construction type** 

Structural: Cast-in-place concrete frame Exterior walls: CMU block; brick

Interior walls: CMU block (reinforced);

steel plate

Exterior surface/facade: Brick

**Construction process** 

Finance method: Revenue sharing Contract method: Conventional Use of inmate labor: None Use of prefabrication: None

Inmate cells

Medium: 0 Minimum: 0

Security

Doors/material: Steel Doors/type: Sliding

Doors/locking: Motor driven and

remote locking

Floor surface: Sealed concrete Intercom: Two-way to common areas HVAC: Air conditioning; central heating

plant/boiler

Plumbing: Stainless combination unit

Furniture: Steel

Fire protection: Smoke detectors and sprinklers for cells and common areas

Inmate design capacity

Single occupancy: 78 Double occupancy: 0

Dorms: 0

Special housing: 0 General population: 78

Total: 78

**Current staff** 

Full-time equivalent: Administration: 2 Security: 18

Programs/treatment: 0

Maintenance: 4 Total: 24

Current inmate/staff ratio: 2.08:1

Architect's reported analyses


Factors affecting construction costs:
Positive: Simple construction methods,
repetitiveness of design; good
competition, favorable market
Negative: Difficult site conditions;
complex electronic, mechanical, and

electrical systems

Factors affecting time schedule: Positive: Simple construction methods, repetitiveness of design; coordination

of design between parties

Negative: Complex electronic, mechanical, and electrical systems



### **Eastern Correctional Center**

Jurisdiction official: Aaron J. Johnson, Secretary, Department of Correction

Contact: Superintendent David W. Chester, Eastern Correctional Center, P.O. Box 215, Maury, NC 28554, 919-747-8101 Architect: Grier-Fripp Associates, Inc., Suite 300, P.O. Box 11207, 4108 Park Road, Charlotte, NC 28220, 704-527-2514

Construction manager: None

**Groundbreaking:** December 1980 Finish date: February 1983 Construction time: 26 months

**Design capacity:** 488 **Total cost:** \$16,582,143 Total annual operating costs: \$7,155,702

Category: New, independent facility Facility type: State prison **Building configuration:** Clusters

#### Costs

Total: \$16,582,143 Building only: \$15,567,015 Housing area: \$11,997,088 Housing per inmate: \$24,994 Housing per cell: \$24,994 Total per inmate: \$33,980 Total per GSF: \$83.99

Total annual operating costs: \$7,155,702

### Security

Perimeter: Double fence; razor wire on fence; towers Inmate security level: Maximum: 20% Medium: 80% Minimum: 0

### **Inmate cells**

Doors/material: Steel Doors/type: Swinging; sliding Doors/locking: Motor driven and remote locking; remote locking only Floor surface: Sealed concrete Intercom: Two-way to common areas HVAC: Air conditioning; wood chip boiler—hot water to air handling units Plumbing: Stainless combination unit; china (med.) Furniture: Steel Fire protection: Smoke detectors for

common areas; manual alarm stations

### **Dimensions**

Gross square feet/corrections: 197,441 Gross square feet/other: 0 Gross square feet/total: 197,441 Housing area square feet: 137,804 Gross square feet per inmate: 405 Size of cells: 66 square feet (single) Net/gross square feet: 90%

### Construction type

Structural: Cast-in-place concrete frame Exterior walls: Insulated precast panels (interior wall surface) Interior walls: Precast panels (interior wall surface); cast-in-place concrete; CMU block

Exterior surface/facade: Natural wall. no coating or treatment; textured

concrete

### **Inmate design capacity**

Single occupancy: 480 Double occupancy: 0 Dorms: 0

Special housing: 8 General population: 480

Total: 488

### **Current staff**

Full-time equivalent: Administration: 33 Security: 182 Programs/treatment: 38

Maintenance: 19 Total: 272

Current inmate/staff ratio: 1.65:1

#### **Inmate housing areas**

Design: Linear, outside; module/pod Cells per unit: 24 and 32 Inmates per unit: 100

Management type: Remote surveillance;

direct supervision

October 1985 population: 448 Facility commitment: State prisoners Means to handle crowding: Beds in

dayroom

### Construction process


Finance method: State funds Contract method: Conventional Use of inmate labor: None Use of prefabrication: Limited

### Architect's reported analyses

Factors affecting construction costs: Positive: Use of prefabricated components, factory assembly; simple construction methods, repetitiveness of design; good competition, favorable market; design innovations Negative: Difficult site conditions

Factors affecting time schedule: Positive: Use of prefabricated components, factory assembly; simple construction methods, repetitiveness of design; design innovations

Negative: None



### North Carolina Central Prison (Addition)

Jurisdiction official: Aaron J. Johnson, Secretary, Department of Correction

Contact: Warden Nathan A. Rice, North Carolina Central Prison, 1300 Western Boulevard, Raleigh, NC 27606, 919-834-0130 Architects: J.N. Pease Associates, P.O. Box 18725, Charlotte, NC 28218, 704-376-6423

Hellmuth, Obata & Kassabaum, Inc., 100 North Broadway, St. Louis, MO 63102, 314-421-2000

Construction manager: Metric Constructors, Inc., 6135 Park Road, Two South Executive Park, Charlotte, NC 28210, 704-554-1415

Groundbreaking: November 1978

Finish date: April 1982 Construction time: 41 months **Design capacity: 588** Total cost: \$35,000,000

Total annual operating costs: N/A

(addition)

**Dimensions** 

Category: New, ancillary building

Facility type: State prison **Building configuration:** Wings connecting housing pods

#### Costs

Total: \$35,000,000

Building only: \$33,500,000 Housing area: \$19,950,000 Housing per inmate: \$33,929 Housing per cell: \$33,929 Total per inmate: \$59,524 Total per GSF: \$92.11

Total annual operating costs: N/A

(addition)

### Security

Perimeter: Double fence; razor wire on

fence; towers Inmate security level: Maximum: 75% Medium: 25% Minimum: 0

Gross square feet/total: 380,000 Housing area square feet: 210,000 Gross square feet per inmate: 646 Size of cells: 72 square feet (single)

Gross square feet/corrections: 380,000

Net/gross square feet: 76%

Gross square feet/other: 0

### **Construction type**

Structural: Cast-in-place concrete frame

Exterior walls: Precast panels

Interior walls: Precast panels; cast-inplace concrete; CMU block Exterior surface/facade: Textured

concrete

### **Inmate design capacity**

Single occupancy: 588 Double occupancy: 0

Dorms: 0

Special housing: 0 General population: 588

Total: 588

#### **Inmate cells**

Doors/material: Steel Doors/type: Sliding

Doors/locking: Motor driven and remote

locking

Floor surface: Sealed concrete Intercom: Two-way to common areas HVAC: Air conditioning; central heating plant/boiler

Plumbing: Stainless combination unit

Furniture: Steel

Fire protection: Smoke detectors for cells and common areas; central fire alarm

# Current staff

Full-time equivalent: Administration: N/A Security: N/A

Programs/treatment: N/A Maintenance: N/A Total: N/A (addition) Current inmate/staff ratio: N/A

#### **Inmate housing areas**

Design: Module/pod Cells per unit: 16 Inmates per unit: 16

Management type: Remote surveillance;

direct supervision

October 1985 population: 831 Facility commitment: State prisoners Means to handle crowding: Bunk beds

in cells

### **Construction process**

Finance method: State funds Contract method: Conventional Use of inmate labor: None

Use of prefabrication: Extensive; exterior walls and structural frame inside


perimeter

#### Architects' reported analyses

Factors affecting construction costs: Positive: Use of prefabricated components, factory assembly; simple construction methods, repetitiveness of design Negative: Slow construction, difficult site conditions; complex electronic, mechanical, and electrical systems

Factors affecting time schedule: Positive: Use of prefab. components, factory assembly; simple con. methods, repetitiveness of design; coordination of design between parties

Negative: Slow responses and delivery from vendors; complex electronic, mechanical, and electrical systems



### **Southern Correctional Center**

Jurisdiction official: Aaron J. Johnson, Secretary, Department of Correction

Contact: Superintendent Michael Bumgarner, Southern Correctional Center, P.O. Box 786, Troy, NC 27371, 919-572-3784 Architect: Grier-Fripp Associates, Inc., Suite 300, P.O. Box 11207, 4108 Park Road, Charlotte, NC 28220, 704-527-2514 Construction manager: None

Groundbreaking: December 1980

Finish date: March 1983 Construction time: 27 months Design capacity: 488 **Total cost:** \$15,799,176 Total annual operating costs:

\$6,952,667

Category: New, independent facility

Facility type: State prison **Building configuration:** Clusters

#### Costs

Security

fence; towers

Inmate security level:

Maximum: 20%

Medium: 80%

Minimum: 0

Total: \$15,799,176

Building only: \$14,627,223 Housing area: \$11,382,647 Housing per inmate: \$23,714 Housing per cell: \$23,714 Total per inmate: \$32,375 Total per GSF: \$80.02

Total annual operating costs: \$6,952,667

Perimeter: Double fence; razor wire on

#### **Dimensions**

Gross square feet/corrections: 197,441 Gross square feet/other: 0 Gross square feet/total: 197,441 Housing area square feet: 137,804 Gross square feet per inmate: 405 Size of cells: 66 square feet (single)

Exterior walls: Insulated precast panels

block

Exterior surface/facade: Natural wall, no coating or treatment; textured concrete

# Construction type

Net/gross square feet: 90%

Structural: Cast-in-place concrete frame (interior wall surface)

Interior walls: Precast panels (interior wall surface); cast-in-place concrete, CMU

#### **Inmate cells**

Doors/material: Steel

Doors/type: Swinging; sliding

Doors/locking: Motor driven and remote locking; remote locking only Floor surface: Sealed concrete Intercom: Two-way to common areas HVAC: Air conditioning; wood chip

boiler—hot water to air handling units Plumbing: Stainless combination unit

(max.); china (med.)

Furniture: Steel

Fire protection: Smoke detectors for common areas; manual alarm stations

#### Inmate design capacity

Single occupancy: 480 Double occupancy: 0

Dorms: 0

Special housing: 8 General population: 480

Total: 488

#### **Current staff**

Full-time equivalent: Administration: 31 Security: 183

Programs/treatment: 42

Maintenance: 17 Total: 273

Current inmate/staff ratio: 1.82:1

#### **Inmate housing areas**

Design: Linear, outside; module/pod

Cells per unit: 24 and 32 Inmates per unit: 100

Management type: Remote surveillance;

direct supervision

October 1985 population: 498 Facility commitment: State prisoners Means to handle crowding: Beds in

dayroom

### **Construction process**


Finance method: State funds Contract method: Conventional Use of inmate labor: None Use of prefabrication: Limited

### Architect's reported analyses

Factors affecting construction costs: Positive: Use of prefabricated components, factory assembly; simple construction methods, repetitiveness of design; good competition, favorable market; design innovations Negative: Difficult site conditions

Factors affecting time schedule: Positive: Use of prefabricated components, factory assembly; simple construction methods, repetitiveness of design; design innovations

Negative: Weather problems



### **Ashtabula County Justice Center**

Jurisdiction official: William K. Johnston, Sheriff

**Contact:** Lieutenant Thomas Bishop, Ashtabula County Justice Center, 25 West Jefferson Street, Jefferson, OH 44047, 216–576–0055 **Architect:** Robert P. Madison International, 2930 Euclid Avenue, Cleveland, OH 44115, 216–861–8195

Construction manager: Ruhlin Construction Company, 200 North Cleveland-Massillon Road, Akron, OH 44313, 216–666–7505

**Groundbreaking:** November 1977

Finish date: January 1979 Construction time: 14 months **Design capacity:** 74 **Total cost:** \$4,100,000

Total annual operating costs: Unknown

Category: New, independent facility Facility type: Complex: county jail,

courts

Building configuration: Integrated

structure

#### Costs

Total: \$4,100,000

Building only: \$4,000,000

Housing area: Unknown Housing per inmate: Unknown Housing per cell: Unknown

Total per inmate: N/A (complex)

Perimeter: Building exterior only

Total per GSF: \$65.97

Inmate security level:

Maximum: 39%

Medium: 11%

Total annual operating costs: Unknown

Minimum: 39% (+ 11% work release)

#### **Dimensions**

Gross square feet/corrections: 56,750 Gross square feet/other: 5,400

Gross square feet/total: 62,150 Housing area square feet: 11,704 Gross square feet per inmate: 767

Size of cells: 70 square feet (single) Net/gross square feet: 85%

# **Construction type**

Structural: Cast-in-place concrete

frame; post tensioned

Exterior walls: CMU block; brick Interior walls: CMU block Exterior surface/facade: Brick

### Inmate design capacity

Single occupancy: 74 Double occupancy: 0

Dorms: 0

Special housing: 0 General population: 74

Total: 74

#### **Inmate cells**

Security

Doors/material: Steel Doors/type: Swinging

Doors/locking: Manual locking Floor surface: Sealed concrete Intercom: One-way to cells; two-way

to common areas

HVAC: Air conditioning; fired boilers

Plumbing: Stainless steel

Furniture: Steel

Fire protection: Smoke detectors for

common areas

### **Current staff**

Full-time equivalent: Administration: 4 Security: 15

> Programs/treatment: 2 Maintenance: 2

Total: 23

Current inmate/staff ratio: 2.35.1

#### **Inmate housing areas**

Design: Module/pod Cells per unit: 8 Inmates per unit: 8

Management type: Intermittent surveillance; remote surveillance

October 1985 population: 54

Facility commitment: Local jail inmates Means to handle crowding: Plans to

expand

### **Construction process**

Finance method: Revenue sharing; other Federal funds; local funds Contract method: Construction man-

agement fast track Use of inmate labor: None Use of prefabrication: None

### Architect's reported analyses

Factors affecting construction costs:
Positive: Phased construction, fast
track construction management
Negative: Complex electronic, mechanical, and electrical systems

Factors affecting time schedule:
Positive: Phased construction, fast track construction management

Negative: Slow responses and delivery

from vendors, suppliers

Ashtabula County

(No floorplan available at time of publication)

### **Clermont County Jail**

Jurisdiction official: John Van Camp, Sheriff

Contact: Sheriff John Van Camp, Clermont County Jail, 4200 Filager Road, Betavia, OH 45103, 513-732-9300

Architect: Steinkamp & Nordloh, 102 Wooster Pike, Milford, OH 45150, 513-831-4955

Construction manager: None

Groundbreaking: August 1984 Finish date: February 1986 Construction time: 18 months **Design capacity:** 133 **Total cost:** \$5,980,000

Total annual operating costs: \$1,891,000

Category: New, independent facility

Facility type: County jail Building configuration: Integrated

**Inmate housing areas** 

Design: Module/pod

Inmates per unit: 48

State prisoners

officer in day rooms

March 1987 population: 137

Cells per unit: 48

structure

#### Costs

Total: \$5,980,000

Building only: \$5,830,000 Housing area: \$2,500,000 Housing per inmate: \$19,531 Housing per cell: \$19,531 Total per inmate: \$44,962 Total per GSF: \$94.92

Total annual operating costs: \$1,891,000

#### **Dimensions**

Gross square feet/corrections: 63,000

Gross square feet/other: 0 Gross square feet/total: 63,000 Housing area square feet: 21,120 Gross square feet per inmate: 474 Size of cells: 82 square feet (single)

Net/gross square feet: 67%

### **Construction type**

Structural: Load bearing masonry; precast

concrete roof Exterior walls: Brick

Interior walls: Precast panels; CMU block;

brick; bearing wall Exterior surface/facade: Brick

**Construction process** 

Finance method: Local funds; State funds Contract method: Conventional

Management type: Remote surveillance;

officer stations view all cells; roving

Facility commitment: Local jail inmates;

Means to handle crowding: Unknown

Use of inmate labor: None

Use of prefabrication: Limited; precast

concrete roof

### Security

Perimeter: Building exterior; single fence; razor wire on fence; video camera

surveillance Inmate security level: Maximum: 20% Medium: 80% Minimum: 0

#### **Inmate cells**

Doors/material: Steel Doors/type: Sliding

Doors/locking: Motor driven and remote

locking

Floor surface: Sealed concrete; vinyl tile;

sealed concrete Plumbing: Stainless steel

HVAC: Air conditioning; Gas heat Floors: Sealed concrete; vinyl tile;

ceramic tile

Intercom: Two-way system throughout

building Furniture: Steel

Fire protection: Sprinkler system through-

out building

#### Inmate design capacity

Single occupancy: 128 Double occupancy: 0

Dorms: 0

Special housing: 5 General population: 128

Total: 133

#### **Current staff**

Full-time equivalent: Administration: 2 Security: 72

Programs/treatment: 1 Maintenance: 6

Total: 81

Current inmate/staff ratio: 1.69:1

### Architect's reported analyses

Factors affecting construction costs:
Positive: Simple construction methods,
repetitiveness and simplicity of design;
concise bidding documents; excellent
contractors


Negative: None

Factors affecting time schedule:

Positive: Simple construction methods, repetitiveness of design; coordination

of design between parties

Negative: None



### **Hamilton County Justice Complex**

Jurisdiction official: Simon L. Leis, Jr., Sheriff

Contact: William R. Barnett, Director of Corrections, Hamilton County Sheriff's Office, 1000 Sycamore Street, Room 120, Cincinnati,

OH 45202, 513-763-5153

Associated architects: Glaser & Myers, Inc., Champlin/Haupt, Inc., 2753 Erie Avenue, Cincinnati, OH 45208, 513-891-9111

Consulting architect: The Gruzen Partnership, 1700 Broadway, New York, NY 10019, 212-840-3940

Construction manager: None

**Groundbreaking:** June 1982 **Finish date:** May 1985

**Construction time:** 36 months

**Design capacity:** 848 **Total cost:** \$50,000,000

Total annual operating costs: Unknown

Category: New, independent facility Facility type: Complex: county jail,

courts

Building configuration: High rise

#### **Costs**

Total: \$50,000,000

Building only: \$49,750,000 Housing area: \$33,000,000 Housing per inmate: \$42,526 Housing per cell: \$42,526

Total per inmate: N/A (complex)

Total per GSF: \$112.36

Total annual operating costs: Unknown

#### **Dimensions**

Gross square feet/corrections: 420,000 Gross square feet/other: 25,600 Gross square feet/total: 445,000 Housing area square feet: 294,000

Gross square feet per inmate: 495 Size of cells: 80 square feet (single)

Net/gross square feet: 80%

# Inmate housing areas

Design: Module/pod Cells per unit: 56 Inmates per unit: 56

Management type: Remote surveillance

October 1985 population: 748

Facility commitment: Local jail inmates Means to handle crowding: Beds in

dayroom

#### Security

Perimeter: Building exterior only

Inmate security level:
Maximum: 14%
Medium: 86%
Minimum: 0

# **Construction type**

Structural: Cast-in-place concrete frame

Exterior walls: Brick

Interior walls: Cast-in-place concrete;

CMU block

Exterior surface/facade: Brick

#### **Construction process**

Finance method: G.O. Bonds; local funds Contract method: Conventional

Use of inmate labor: None Use of prefabrication: None

### **Inmate cells**

Doors/material: Solid Doors/type: Swinging

Doors/locking: Remote locking only Floor surface: Epoxy coating

Intercom: Two-way to cells and common

areas

HVAC: Air conditioning; central air

handling units Plumbing: Stainless Furniture: Steel

Fire protection: Smoke detectors and sprinklers for cells and common areas;

manual alarm stations

### Inmate design capacity

Single occupancy: 776 Double occupancy: 0

Dorms: 0

Special housing: 72 General population: 776

Total: 848

Full-time equivalent: Administration: 9 Security: 268

Programs/treatment: 44 Maintenance: 5

Total: 326

**Current staff** 

Current inmate/staff ratio: 2.29:1

### Architects' reported analyses

Factors affecting construction costs:
Positive: Good competition, favorable
market; simple construction methods,

repetitiveness of design

Negative: Complex electronic, mechanical, and electrical systems; slow construction, lengthy building time


Factors affecting time schedule:

Positive: Coordination of design between parties; simple construction methods,

repetitiveness of design

Negative: Complex electronic, mechan-

ical, and electrical systems



## **Logan County Jail and Office Complex**

Jurisdiction official: Michael E. Henry, Sheriff

Contact: Lt. R. A. Bair, Jail Administrator, Logan County Jail and Office Complex, 104 South Madriver Street, Bellefontaine,

OH 43311, 513-592-5731

Architect: Patrick + Associates, 65 East State Street, Suite 500, Columbus, OH 43215-4213, 614-228-3233

Construction manager: None

**Groundbreaking:** February 1982

Finish date: April 1983 Construction time: 14 months Design capacity: 27
Total cost: \$2.835.248

Total annual operating costs: \$570,000

Category: New, independent facility
Facility type: Complex: county jail, law
enforcement, courts, county offices
Building configuration: Integrated

structure; courtyard

#### **Costs**

Total: \$2,835,248

Building only: \$2,800,000 Housing area: \$545,625 Housing per inmate: \$22,734 Housing per cell: \$22,734

Total per inmate: N/A (complex)

Total per GSF: \$76

Total annual operating costs: \$570,000

#### **Dimensions**

Gross square feet/corrections: 13,288 Gross square feet/other: 24,229 Gross square feet/total: 37,517 Housing area square feet: 13,288 Gross square feet per inmate: 492 Size of cells: 70 square feet (gen. single);

120 (spec. single) Net/gross square feet: 69%

# Security

Perimeter: Patrols; video camera surveillance Inmate security level:

Maximum: 0 Medium: 100% Minimum: 0

## Construction type

Structural: Cast-in-place concrete frame Exterior walls: Precast panels; cast-in-place concrete; CMU block; brick

Interior walls: CMU block

Exterior surface/facade: Brick; reinforced

concrete block backup

#### Inmate cells

Doors/material: Steel Doors/type: Sliding

Doors/locking: Motor driven and remote

locking; manual locking Floor surface: Sealed concrete

Intercom: Two-way to cells and common

areas

HVAC: Heating/air circulation; gas heat Plumbing: Stainless combination unit

Furniture: Steel

Fire protection: Smoke detectors and sprinklers for common areas

### Inmate design capacity

Single occupancy: 24 Double occupancy: 0

Dorms: 0

Special housing: 3 General population: 24

Total: 27

#### Current staff

Full-time equivalent: Administration: 2 Security: 16

> Programs/treatment: 2 Maintenance: 4

Total: 24

Current inmate/staff ratio: .88:1

### **Inmate housing areas**

Design: Linear, outside Cells per unit: 8 Inmates per unit: 8

Management type: Intermittent surveillance; remote surveillance

October 1987 population: 21

Facility commitment: Local jail inmates;

State prisoners

Means to handle crowding: Portable cots

### **Construction process**

Finance method: Local funds Contract method: Conventional Use of inmate labor: None Use of prefabrication: Moderate


### Architect's reported analyses

Factors affecting construction costs: Positive: Simple construction methods, repetitiveness of design; prefabricated components, factory assembly; favorable market

Negative: High labor cost; difficult site conditions; facility not primarily designed for corrections operation

Factors affecting time schedule:
Positive: Advanced order of materials and hardware; coordination of design between parties; use of prefab. components; simple construction methods

Negative: Weather problems



### **Madison Correctional Institution**

Jurisdiction official: Richard P. Seiter, Director, Department of Rehabilitation and Correction

Contact: Superintendent George D. Alexander, Madison Correctional Institution, 1581 State Route 56, P.O. Box 740, London,

OH 43140-0740, 614-852-9650

**Architect:** Patrick + Associates, Inc., 199 South Fifth Street, Columbus, OH 43215, 614–228–3233 **Construction manager:** Turner/Smoot, 65 East State Street, Columbus, OH 43215, 614–225–2900

**Groundbreaking:** May 1985 **Finish date:** November 1987 **Construction time:** 30 months

**Design capacity:** 1,034 **Total cost:** \$42,000,000

**Total annual operating costs:** \$9,970,333

Category: New, independent facility

Facility type: State prison

Building configuration: Campus style

#### **Costs**

Total: \$42,000,000 Building only: \$38,000,000 Housing area: \$26,048,905 Housing per inmate: \$26,049 Housing per cell: \$50,094

Total per inmate: \$40,619 Total per GSF: \$93.33

Total annual operating costs: \$9,970,333

#### **Dimensions**

Gross square feet/corrections: 450,000

Gross square feet/other: 0 Gross square feet/total: 450,000 Housing area square feet: 292,685 Gross square feet per inmate: 435

Size of cells: 70 square feet (single); 2,400

(dorms)

Net/gross square feet: 76%

#### **Inmate housing areas**

Design: Module/pod Cells per unit: Unknown Inmates per unit: Unknown

Management type: Remote surveillance;

direct supervision

December 1987 population: 810 Facility commitment: State prisoners Means to handle crowding: Double bunk

cells and dorms

#### Security

Perimeter: Double fence; alarm/detection systems; razor wire on and between fences; video camera surveillance;

mobile guard Inmate security level: Maximum: 0 Medium: 52% Minimum: 48%

### **Construction type**

Structural: Steel frame

Exterior walls: Cast-in-place concrete;

CMU block; brick

Interior walls: Cast-in-place concrete;

CMU block; brick

Exterior surface/facade: Brick; stucco

## **Construction process**

Finance method: State funds

Contract method: Construction manage-

ment fast track

Use of inmate labor: None Use of prefabrication: Limited

#### **Inmate cells**

Doors/material: Steel Doors/type: Sliding

Doors/locking: Motor driven and remote

locking

Floor surface: Sealed concrete; vinyl tile;

quarry tile Intercom: None

HVAC: Heating/air circulation; gas heat

Plumbing: Stainless steel; china

Furniture: Steel

Fire protection: Smoke detectors and sprinklers for common areas; manual

alarm stations

# Inmate design capacity

Single occupancy: 504 Double occupancy: 0

Dorms: 496 Special housing: 34 General population: 1,000

Total: 1,034

#### Current staff

Full-time equivalent: Administration: 99 Security: 165

Programs/treatment: 41 Maintenance: 33 Total: 338

Current inmate/staff ratio: 2.4:1


### Architect's reported analyses

Factors affecting construction costs:
Positive: Simple const. methods; favorable market; bulk purchase of materials and hardware; prefab. components
Negative: Slow const.; high labor costs; government red tape; phased const.

Factors affecting time schedule:
Positive: Prefab. components; repetitiveness of design; fast track CM; advanced order of materials; coordination of design between parties

Negative: Slow delivery from suppliers; labor problems; weather problems;

government regulations



### **Ohio Reformatory for Women (Addition)**

Jurisdiction official: Richard P. Seiter, Director, Department of Rehabilitation and Correction

Contact: Superintendent Dorothy M. Arn, Ohio Reformatory for Women, 1479 Collins Avenue, Marysville, OH 43040, 513-642-1065

Architect: Moody/Nolan Ltd., 1780 East Broad Street, Columbus, OH 43203, 614-253-2623

Construction manager: None

Groundbreaking: November 1984 Finish date: November 1986 **Construction time:** 24 months

Design capacity: 402 **Total cost:** \$5,650,000

Total annual operating costs: N/A

(addition)

Category: New, ancillary building Facility type: State prison (women's

facility)

**Building configuration:** Integrated

structure; courtyard

#### Costs

Total: \$5,650,000

Building only: \$5,450,000 Housing area: \$5,105,000 Housing per inmate: \$14,181 Housing per cell: \$28,361 Total per inmate: \$14,055 Total per GSF: \$97.14

Total annual operating costs: N/A

(addition)

**Dimensions** 

Gross square feet/corrections: 58,165 Gross square feet/other: 0 Gross square feet/total: 58,165 Housing area square feet: 54,485 Gross square feet per inmate: 145 Size of cells: 82 square feet (spec. single);

76 (gen. double) Net/gross square feet: 88%

### **Inmate housing areas**

Design: Module/pod Cells per unit: 60 Inmates per unit: 120

Management type: Direct supervision

May 1987 population: 329

Facility commitment: State prisoners;

local jail inmates

Means to handle crowding: Unknown

### **Security**

Perimeter: Single fence; patrols

Inmate security level: Maximum: 20% Medium 80% Minimum: 0

### **Construction type**

Structural: Precast concrete frame Exterior walls: Brick: stone Interior walls: CMU block

Exterior surface/facade: Brick; stone

### **Construction process**

Finance method: State funds; local funds Contract method: Conventional

Use of inmate labor: None

Use of prefabrication: Limited; precast concrete columns and beams

#### **Inmate cells**

Doors/material: Solid; wooden; steel

Doors/type: Swinging Doors/locking: Unknown Floor surface: Sealed concrete

Intercom: None

HVAC: Heating/air circulation Plumbing: Stainless steel; china

Furniture: Steel

Fire protection: Smoke detectors for cells and common areas; sprinklers for

common areas

### Inmate design capacity

Single occupancy: 0 Double occupancy: 360

Dorms: 0

Special housing: 42 General population: 360

Total: 402

#### Architect's reported analyses

Factors affecting construction costs: Positive: Simple construction methods, repetitiveness of design; good competition, favorable market Negative: High labor costs

Factors affecting time schedule: Positive: Use of prefabricated components, factory assembly; simple construction methods, repetitiveness of


design


Negative: Weather problems

#### Current staff

Full-time equivalent: Administration: 4 Security: 29

Programs/treatment: 3 Maintenance: N/A Total: 36 (addition only) Current inmate/staff ratio: 9.14:1





## **Ottawa County Detention Facility**

Jurisdiction official: John Crosser, Sheriff

Contact: Martin Gosses, Jail Administrator, Ottawa County Detention Facility, Port Clinton, OH 43452, 419-734-4404

Architect: Geary, Moore and Ahrens, Inc., 672 East Royalton Road, Cleveland, OH 44147, 216-526-0672

Construction manager: None

**Groundbreaking:** August 1979

Finish date: April 1981 Construction time: 20 months **Design capacity:** 41 **Total cost:** \$2,671,461

Total annual operating costs: \$500,000

Gross square feet/corrections: 22,080

Gross square feet/other: 9,300

Gross square feet/total: 31,380

Net/gross square feet: 78%

Housing area square feet: 9,444

Gross square feet per inmate: 539

Size of cells: 80 square feet (single)

(excl. utilities)

**Dimensions** 

Category: New, independent facility;

phased project (future)

Facility type: Complex: county jail, law

enforcement, courts

Building configuration: Integrated

structure

#### Costs

Total: \$2,671,461

Building only: \$2,671,461 Housing area: Unknown Housing per inmate: Unknown Housing per cell: Unknown

Total per inmate: N/A (complex)

Total per GSF: \$85.13

Total annual operating costs: \$500,000

(excl. utilities)

### Construction type

Structural: Cast-in-place concrete frame

Exterior walls: Sandstone

Interior walls: Cast-in-place concrete; CMU block; hollow metal partitions Exterior surface/facade: Sandstone

#### **Security**

Perimeter: Building exterior only

Inmate security level:
Maximum: 10%
Medium: 80%
Minimum: 10%

### Inmate design capacity

Single occupancy: 28 Double occupancy: 0

Dorms: 8

Special housing: 5 General population: 36

Total: 41

#### Single occ

Doors/material: Aluminum and glass

Doors/type: Sliding

**Inmate cells** 

Doors/locking: Remote locking only Floor surface: Concrete with integral

color hardener

Intercom: Two-way to cells and

common areas

HVAC: Air conditioning; gas boiler Plumbing: Stainless combination unit

Furniture: Steel

Fire protection: Smoke detectors for common areas; sprinklers for cells and common areas; manual alarm stations

#### **Current staff**

Full-time equivalent: Administration: 1

Security: 14

Programs/treatment: 0 Maintenance: 3 Total: 18

Current inmate/staff ratio: 2.28:1

### **Inmate housing areas**

Design: Module/pod Cells per unit: 16 Inmates per unit: 16

Management type: Remote surveillance

October 1985 population: 41

Facility commitment: Local jail inmates

Means to handle crowding: None

# **Construction process**

Finance method: Local funds Contract method: Conventional Use of inmate labor: None Use of prefabrication: None

### Architect's reported analyses

Factors affecting construction costs: Positive: Good competition, favorable

market


Negative: Complex electronic, mechanical, and electrical systems; expensive materials to match existing courthouse

Factors affecting time schedule: Positive: Good architectural trades

contractor

Negative: Complex electronic, mechanical, and electrical systems; use of five

prime contractors



### **Ross Correctional Institution\***

Jurisdiction official: Richard P. Seiter, Director, Department of Rehabilitation and Correction

Contact: Superintendent Gary Mohr, Ross Correctional Institution, 16149 State Route 104, Chillicothe, OH 45601, 614–774–4182

Architect: Voinovich Sgro Architects, 2450 Prospect Avenue, Cleveland, OH 44115, 216-621-9200

Construction manager: None

**Groundbreaking:** September 1985

Finish date: May 1987

**Construction time:** 21 months

**Design capacity:** 1,274 **Total cost:** \$53,012,000

**Total annual operating costs:** 

\$23,178,800

Category: New, independent facility

Facility type: State prison

Building configuration: Campus style

#### **Costs**

Total: \$53,012,000

Building only: \$45,000,000 Housing area: Unknown Housing per inmate: Unknown Housing per cell: Unknown Total per inmate: \$41,611

Total per GSF: \$96.90

Total annual operating costs: \$23,178,800

#### Dimensions

Gross square feet/corrections: 547,096

Gross square feet/other: 0 Gross square feet/total: 547,096 Housing area square feet: 276,600 Gross square feet per inmate: 429 Size of cells: 70 square feet (single)

Net/gross square feet: 70%

### **Inmate housing areas**

Design: Housing unit in two triangular

shapes—outside cells Cells per unit: 128 Inmates per unit: 128

Management type: Direct supervision;

unit management

October 1987 population: 1,235 Facility commitment: State prisoners Means to handle crowding: Bunk beds in

cell

### **Security**

Perimeter: Double fence; alarm/ detection system; razor wire on fences;

patrols; camera surveillance

Inmate security level:
Maximum: 2.5%
Medium: 77.5%
Minimum: 20%

### Construction type

Structural: Load-bearing precast panels; precast concrete frame Exterior walls: Precast panels

Interior walls: Precast panels; CMU block Exterior surface/facade: Natural wall

### **Construction process**

Finance method: State funds Contract method: Conventional Use of inmate labor: None

Use of prefabrication: Moderate; precast

components

#### **Inmate cells**

Doors/material: Steel Doors/type: Sliding

Doors/locking: Motor driven and remote

locking; manual locking

Floor surface: Sealed concrete; carpet;

vinyl tile

Intercom: Two-way to cells; one-way to

common areas

HVAC: Heating/air circulation; hot water

heater

Plumbing: China; stainless; stainless

combination unit Furniture: Vinyl/plastic

Fire protection: Smoke detectors for cells and common areas; sprinklers for

common areas

### Inmate design capacity

Single occupancy: 1,024 Double occupancy: 0

Dorms: 250 Special housing: 0

General population: 1,274

Total: 1,274

#### **Current staff**

Full-time equivalent: Administration: 82 Security: 143

Programs/treatment: 63 Maintenance: 35

Total: 323

Current inmate/staff ratio: 3.82:1

#### Architect's reported analyses


Factors affecting construction costs: Positive: Precast modular construction

Negative: None

Factors affecting time schedule:
Positive: Precast modular construction
Negative: Government procedures,
regulations, and red tape—paperwork

with State officials

<sup>\*</sup> A detailed case study of this institution has been published by NIJ, entitled *Building on Experience*, NCJ 103869.



### **Wayne County Justice Center**

Jurisdiction official: Loran D. Alexander, Sheriff

Contact: Captain Gene Rhodes, Wayne County Justice Center, Wooster, OH 44691, 216–264–2288 Architect: Robert P. Madison International, 2930 Euclid Avenue, Cleveland, OH 44115, 216–861–8195

Construction manager: None

Groundbreaking: November 1977 Finish date: November 1978 Construction time: 12 months **Design capacity:** 78 **Total cost:** \$3,000,000

**Total annual operating costs:** \$924,565

Category: New, independent facility Facility type: Complex: county jail, law

enforcement

Building configuration: Integrated

structure

#### Costs

Total: \$3,000,000

Building only: \$2,950,000

Housing area: Unknown
Housing per inmate: Unknown
Housing per cell: Unknown

Total per inmate: N/A (complex)

Total per GSF: \$56.60

Total annual operating costs: \$924,565

#### **Dimensions**

Gross square feet/corrections: 40,000 Gross square feet/other: 13,000 Gross square feet/total: 53,000 Housing area square feet: 11,928 Gross square feet per inmate: 513 Size of cells: 70 square feet (single)

Net/gross square feet: 85%

# Inmate housing areas

Design: Module/pod Cells per unit: 7 to 12 Inmates per unit: 7 to 12

Management type: Intermittent surveil-

lance; remote surveillance October 1985 population: 97

Facility commitment: Local jail inmates Means to handle crowding: Extra cot

in cell

#### Security

Perimeter: Building exterior only

Inmate security level:
Maximum: 16%
Medium: 41%

Minimum: 22% (+ 21% work release and holding)

### **Construction type**

Structural: Steel frame

Exterior walls: CMU block; brick Interior walls: CMU block Exterior surface/facade: Brick

#### **Construction process**

Finance method: Revenue sharing; other

Federal funds

Contract method: Conventional Use of inmate labor: None Use of prefabrication: None

### **Inmate cells**

Doors/material: Steel Doors/type: Swinging

Doors/locking: Remote locking only

Floor surface: Epoxy coating Intercom: One-way to cells; two-way to

common areas

HVAC: Air conditioning; fired boilers

Plumbing: Stainless Furniture: Steel

Fire protection: Smoke detectors for

common areas

#### Inmate design capacity

Single occupancy: 72 Double occupancy: 0

Dorms: 0 Other: 6

Special housing: 0 General population: 78

Total: 78

### Architect's reported analyses

Factors affecting construction costs: Positive: Simple construction methods;

repetitiveness of design

Negative: Complex electronic, mechan-

ical, and electrical systems

Factors affecting time schedule:

Positive: Simple construction methods, repetitiveness of design; coordination

of design between parties

Negative: Slow responses and delivery

from vendors, suppliers


# **Current staff**

Full-time equivalent: Administration: 2 Security: 22

Programs/treatment: 5 Maintenance: 1

Total: 30

Current inmate/staff ratio: 2.60:1



### **Cleveland County Detention Center**

Jurisdiction official: John J. Walsh, Jr., Sheriff

Contact: Kenneth K. Zane, Jail Administrator, Cleveland County Detention Center, 203 South Jones, Norman, OK 73069,

405-321-8600

Architect: Rees Associates, Inc., 4200 Perimeter Center Drive, Suite 245, Oklahoma City, OK 73112, 405–946–9800

Construction manager: None

**Groundbreaking:** March 1983

Finish date: May 1984

Construction time: 14 months

Design capacity: 134 **Total cost:** \$3,632,000

Total annual operating costs: \$1,409,000

Category: New, independent facility Facility type: Complex: county jail, law

enforcement

Building configuration: Integrated

structure

#### **Costs**

Total: \$3,632,000

Building only: \$3,512,000 Housing area: Unknown Housing per inmate: Unknown Housing per cell: Unknown

Total per inmate: N/A (complex)

Total per GSF: \$88.10

Total annual operating costs: \$1,409,000

### **Dimensions**

Gross square feet/corrections: 38,642 Gross square feet/other: 2,582 Gross square feet/total: 41,224 Housing area square feet: 24,750 Gross square feet per inmate: 288 Size of cells: 95 square feet (double);

77 (spec. single)

Net/gross square feet: 83%

**Inmate housing areas** 

Design: Module/pod Cells per unit: 8 Inmates per unit: 16

Management type: Remote surveillance September 1987 population: 97

Facility commitment: Local jail inmates; U.S. Marshal's transients; FBOP

prisoners\*

Means to handle crowding: Mattresses on

floor

### Security

Perimeter: Building exterior only

Inmate security level: Maximum: 100% Medium: 0 Minimum: 0

### **Construction type**

Structural: Cast-in-place concrete frame Exterior walls: Cast-in-place concrete

Interior walls: CMU block

Exterior surface/facade: Colored concrete;

split face CMU

### **Construction process**

Finance method: G.O. Bonds; revenue

sharing; local funds

Contract method: Conventional Use of inmate labor: None Use of prefabrication: None

#### **Inmate cells**

Doors/material: Steel Doors/type: Swinging

Doors/locking: Remote locking; manual

locking

Floor surface: Sealed concrete

Intercom: Two-way to cells; one-way to

common areas

HVAC: Air conditioning; gas heat; operable windows for outside air Plumbing: Stainless combination unit

Furniture: Steel

Fire protection: Smoke detectors for cells and common areas; sprinklers for

common areas

### Inmate design capacity

Single occupancy: 0 Double occupancy: 108

Dorms: 0

Special housing: 26 General population: 108

Total: 134

## **Current staff**

Full-time equivalent: Administration: 6 Security: 22

> Programs/treatment: 0 Maintenance: 2 Total: 30

Current inmate/staff ratio: 3.23:1


#### Architect's reported analyses

Factors affecting construction costs: Positive: Simple construction methods, repetitiveness of design; good competition, favorable market; less expensive materials and hardware Negative: Difficult site conditions

Factors affecting time schedule: Positive: Simple construction methods, repetitiveness of design; advanced order of materials and hardware: coordination of design between parties Negative: Slow delivery of windows and

security locks

<sup>\*</sup>Juveniles are detained for no more than 6 hours.



### **Kay County Detention Facility**

Jurisdiction official: Richard D. Stickney, Sheriff

Contact: Nathan R. McCoy, Jail Administrator, Kay County Detention Facility, 110 South Maple, Newkirk, OK 74647, 405–362–2517

Architect: Rees Associates, Inc., 4200 Perimeter Center Drive, Suite 245, Oklahoma City, OK 73112, 405-946-9800

Construction manager: None

Groundbreaking: November 1983

Finish date: July 1985

Construction time: 20 months

Design capacity: 80 **Total cost:** \$3,133,072

**Total annual operating costs:** \$550,857

Category: New, independent facility Facility type: Complex: county jail; law

enforcement

**Building configuration:** Integrated

structure

Costs

Total: \$3,133,072

Building only: \$2,960,372

Housing area: Unknown Housing per inmate: Unknown Housing per cell: Unknown

Total per inmate: N/A (complex)

Total per GSF: \$108.88

Total annual operating costs: \$550,857

**Dimensions** 

Gross square feet/corrections: 25,798

Gross square feet/other: 2,977 Gross square feet/total: 28,775 Housing area square feet: 17,139

Gross square feet per inmate: 322 Size of cells: 95 square feet (gen. double);

73 (spec. single); 77 (spec. double)

Net/gross square feet: 91%

**Inmate housing areas** 

Design: Module/pod Cells per unit: 4 to 8 Inmates per unit: 4 to 16

Management type: Remote surveillance

October 1987 population: 39

Facility commitment: Local jail inmates Means to handle crowding: Unknown

Security

Perimeter: Video camera surveillance

Inmate security level: Maximum: 100% Medium: 0

Minimum: 0

Construction type

Structural: Steel frame; cast-in-place

concrete frame

Exterior walls: Cast-in-place concrete

Interior walls: CMU block

Exterior surface/facade: Modified Portland

cement coating on concrete

**Construction process** 

Finance method: G.O. Bonds Contract method: Conventional Use of inmate labor: None

Use of prefabrication: Limited; precast, prestressed concrete roof planks

**Inmate cells** 

Doors/material: Steel Doors/type: Sliding

Doors/locking: Motor driven and remote

locking

Floor surface: Sealed concrete

Intercom: Two-way to cells and common

HVAC: Air conditioning; gas heat; hot water heating (gas-fired boiler) Plumbing: Stainless combination unit

Furniture: Steel

Fire protection: Smoke detectors and sprinklers for cells and common areas **Inmate design capacity** 

Single occupancy: 0 Double occupancy: 60

Dorms: 0

Special housing: 20 General population: 60

Total: 80

Architect's reported analyses

Factors affecting construction costs: Positive: Simple construction methods repetitiveness of design; good competition, favorable market; less expensive

materials and hardware

Negative: Difficult site conditions; complex electronic, mechanical, and

electrical systems

Factors affecting time schedule:

Positive: Simple construction methods,

repetitiveness of design

Negative: Slow responses and delivery from vendors, suppliers; weather problems; inexperienced contractor


#### **Current staff**

Full-time equivalent: Administration: 1 Security: 14

> Programs/treatment: 0 Maintenance: 1

Total: 16

Current inmate/staff ratio: 2.44:1



### **Lexington Assessment & Reception Center (Addition)**

Jurisdiction official: Gary Maynard, Director, Department of Corrections

Contact: Warden Peter Douglas, Lexington Assessment & Reception Center, Box 260, Lexington, OK 73051, 405-527-5676

Architect: The Benham Group, Inc., P.O. Box 20400, 9400 Broadway, Oklahoma City, OK 73156, 405-478-5353

Construction manager: None

Groundbreaking: September 1982

Finish date: June 1983 Construction time: 9 months Design capacity: 90 **Total cost:** \$1,819,408

Total annual operating costs: N/A

(addition)

Category: New, ancillary building

Facility type: State prison Building configuration: Integrated

structure

#### Costs

Total: \$1,819,408

Building only: \$1,752,000 Housing area: \$1,489,408 Housing per inmate: \$17,731 Housing per cell: \$17,731 Total per inmate: \$20,216 Total per GSF: \$62.26

Total annual operating costs: N/A

(addition)

### Security

Perimeter: Building exterior only

Inmate security level: Maximum: 0 Medium: 0

Minimum: 94.6% (+ 5.4% holding)

#### **Dimensions**

Gross square feet/corrections: 29,225

Gross square feet/other: 0 Gross square feet/total: 29,225 Housing area square feet: 24,625 Gross square feet per inmate: 325 Size of cells: 63 square feet (single)

Net/gross square feet: 98%

### **Construction type**

Structural: Load bearing precast panels;

double T's

Exterior walls: Precast panels

Interior walls: Precast panels; CMU block Exterior surface/facade: Raked finish,

precast

#### Inmate design capacity

Single occupancy: 84 Double occupancy: 0

Dorms: 0

Special housing: 6 General population: 84

Total: 90

# **Inmate cells**

Doors/material: Steel Doors/type: Swinging

Doors/locking: Manual locking Floor surface: Linoleum; tile

Intercom: One-way to common areas: two-way to counseling rooms HVAC: Heating/air circulation only;

gas U.H.U. Plumbing: China Furniture: Steel

Fire protection: Smoke detectors in common areas, cells, and mechanical ductwork; fire hose cabinets and fire

extinguishers

#### **Current staff**

Full-time equivalent: Administration: N/A

Security: 4

Programs/treatment: 2 Maintenance: 1

Total: 7 (addition only) Current inmate/staff ratio: 21:1

### **Inmate housing areas**

Design: Module/pod Cells per unit: 90 Inmates per unit: 90

Management type: Remote surveillance

October 1985 population: 144 Facility commitment: State prisoners Means to handle crowding: Stacked bunks

### **Construction process**

Finance method: State funds Contract method: Conventional Use of inmate labor: None

Use of prefabrication: Extensive; exterior walls, interior walls, floor and roof

slabs

### Architect's reported analyses


Factors affecting construction costs: Positive: Use of prefabricated components, factory assembly; simple construction methods; less expensive materials and hardware

Negative: None

Factors affecting time schedule: Positive: Use of prefabricated components,

factory assembly; simple construction methods; coordination of design

between parties Negative: None



## Lexington Assessment & Reception Center, Phase I and II

Jurisdiction official: Gary Maynard, Director, Department of Corrections

Contact: Warden Peter Douglas, Lexington Assessment & Reception Center, Box 260, Lexington, OK 73051, 405-527-5676 Architects: W. Gene Williams & Associates, Inc., 4422 F.M. 1960 West, Suite 220, Houston, TX 77068, 713-440-4422

WMFL Architects & Engineers, West 244 Main Avenue, Spokane, WA 99210, 509-838-8681

Construction manager: None

**Groundbreaking:** August 1976 Finish date: January 1978 Construction time: 17 months

Design capacity: 428 **Total cost:** \$14,500,000

Total annual operating costs: \$7,408,984

Category: New, independent facility

Facility type: State prison **Building configuration:** Clusters

#### Costs

Total: \$14,500,000 Building only: \$13,731,639 Housing area: Unknown Housing per inmate: Unknown Housing per cell: Unknown Total per inmate: \$33,879

Total annual operating costs: \$7,408,984

### **Dimensions**

Gross square feet/corrections: 203,786 Gross square feet/other: 0 Gross square feet/total: 203,786 Housing area square feet: 110,376 Gross square feet per inmate: 476 Size of cells: 73 square feet (single) Net/gross square feet: Unknown

### Construction type

Structural: Load bearing precast panels; cast-in-place concrete frame; precast concrete frame

Exterior walls: Precast panels; cast-inplace concrete; architectural precast Interior walls: Precast panels; cast-in-place concrete; CMU block

Exterior surface/facade: Paint; colored

concrete

### Security

Perimeter: Double fence; alarm/detection systems; razor wire on fences; towers; patrols

Inmate security level: Maximum: 100% Medium: 0 Minimum: 0

Total per GSF: \$71.15

#### Inmate cells

Doors/material: Steel Doors/type: Swinging

Doors/locking: Motor driven and remote

Floor surface: Sealed concrete; vinyl tile;

quarry tile

Intercom: Two-way to cells

HVAC: Air conditioning; steam heat

Plumbing: Stainless steel

Furniture: Steel

Fire protection: Portable fire extinguishers

### Inmate design capacity

Single occupancy: 400 Double occupancy: 0

Dorms: 0

Special housing: 28 General population: 400

Total: 428

#### Current staff

Full-time equivalent: Administration: 45 Security: 131

Programs/treatment: 24 Maintenance: 24

Total: 224

Current inmate/staff ratio: 4.12:1

#### **Inmate housing areas**

Design: Module/pod Cells per unit: 80 Inmates per unit: 80

Management type: Remote surveillance September 1986 population: 922 Facility commitment: State prisoners Means to handle crowding: Bunk beds in cell; second bunk permanently attached

to wall

#### Construction process

Finance method: State funds Contract method: Conventional

Use of inmate labor: Limited; construction

of fence

Use of prefabrication: Limited; precast

T-beams


### Architects' reported analyses

Factors affecting construction costs: Positive: Prefabricated components, factory assembly; simple construction methods, repetitiveness of design; phased construction, fast track construction management; good competition, favorable market

Negative: None

Factors affecting time schedule: Positive: Use of prefabricated components, factory assembly; simple construction methods, repetitiveness of design; phased construction, fast track CM; coordination of design between parties; good general contractor

Negative: None



417

### **Mabel Bassett Correctional Center (Addition)**

Jurisdiction official: Gary Maynard, Director, Department of Corrections

Contact: Warden Larry Fields, Mabel Bassett Correctional Center, 3300 Martin Luther King Avenue, Oklahoma City, OK 73136,

405-521-3949

Architect: Rees Associates, Inc., #245, 4200 Perimeter Center Drive, Oklahoma City, OK 73112, 405-946-9800

Construction manager: None

**Groundbreaking:** October 1979

Finish date: April 1981 Construction time: 18 months **Design capacity:** 53 **Total cost:** \$912,809

Total annual operating costs: N/A

(addition)

Category: New, ancillary building

Facility type: State prison

Building configuration: Integrated

structure

#### **Costs**

Total: \$912.809

Building only: \$899,500 Housing area: \$860,000 Housing per inmate: \$28,667 Housing per cell: \$28,667 Total per inmate: \$17,223 Total per GSF: \$74.88

Total annual operating costs: N/A

(addition)

#### Security

Perimeter: Double fence; alarm/ detection system; razor wire on fence

Inmate security level:
Maximum: 20%
Medium: 80%

#### **Dimensions**

Gross square feet/corrections: 12,191

Gross square feet/other: 0 Gross square feet/total: 12,191 Housing area square feet: 11,766 Gross square feet per inmate: 230 Size of cells: 70 square feet (single)

Net/gross square feet: N/A

### **Construction type**

Structural: Steel frame; load bearing CMU walls; cast-in-place concrete

frame

Exterior walls: Cast-in-place concrete; CMU split-face block; block masonry Interior walls: Cast-in-place concrete;

CMU block

Exterior surface/facade: Split-face block

### **Inmate housing areas**

Design: Module/pod Cells per unit: 53 Inmates per unit: 53

Management type: Remote surveillance

October 1985 population: 106
Facility commitment: State prisoners
Means to handle crowding: Bunk beds

in cell

#### **Construction process**

Finance method: State funds Contract method: Conventional Use of inmate labor: None Use of prefabrication: Limited

#### **Inmate cells**

Minimum: 0

Doors/material: Steel Doors/type: Swinging

Doors/locking: Remote locking; manual

locking

Floor surface: Linoleum, sealed concrete Intercom: Two-way to cells and common

areas

HVAC: Air conditioning; rooftop heating plant with boilers and condensing units

Plumbing: Stainless Furniture: Steel

Fire protection: Smoke detectors for cells and common areas; manual alarm

stations

### Inmate design capacity

Single occupancy: 30 Double occupancy: 0

Dorms: 0

Special housing: 23 General population: 30

Total: 53

# Architect's reported analyses

Factors affecting construction costs: Positive: Use of prefabricated masonry units; simple building technique; repetition and simplicity of design; local availability of materials

Negative: None


Factors affecting time schedule:
Positive: Use of prefabricated masonry units; simple construction technique Negative: Weather problems; delivery problems with vendor/supplier

#### **Current staff**

Full-time equivalent: Administration: N/A

Security: 6

Programs/treatment: N/A
Maintenance: N/A
Total: 6 (addition only)
Current inmate/staff ratio: 17.7:1



**Ground Level Floor Plan** 

### Muskogee County/City Detention Facility

Jurisdiction official: Bill Vinzant, Sheriff

Contact: Sheriff Bill Vinzant, Muskogee County/City Detention Facility, 120 South 3rd, Muskogee, OK 74401, 918-687-1275

Architect: Roger Richter/Architect Inc., 608 Manhattan Building, Muskogee, OK 74401, 918-682-3419

Construction manager: None

Groundbreaking: March 1985 Finish date: October 1986 Construction time: 19 months **Design capacity:** 136 **Total cost:** \$4,026,000

Total annual operating costs: Unknown

Category: New, independent facility Facility type: County jail; city jail Building configuration: Integrated

structure

#### **Costs**

Total: \$4,026,000 Building only: \$3,923,000 Housing area: \$2,456,440 Housing per inmate: \$19,652 Housing per cell: \$23,620 Total per inmate: \$29,603 Total per GSF: \$91.04

Total annual operating costs: Unknown

#### **Dimensions**

Gross square feet/corrections: 44,223 Gross square feet/other: 0 Gross square feet/total: 44,223 Housing area square feet: 28,247 Gross square feet per inmate: 325 Size of cells: 70 square feet (single);

90 (double)

Net/gross square feet: 90%

### **Inmate housing areas**

Design: Module/pod Cells per unit: 49 Inmates per unit: 59

Management type: Remote surveillance

Current population: Unknown

Facility commitment: Local jail inmates; State prisoners; Federal prisoners on

contract

Means to handle crowding: Unknown

### **Security**

Perimeter: Single fence; razor wire on fence; video camera surveillance

Inmate security level:
Maximum: 18%
Medium: 82%
Minimum: 0

### **Construction type**

Structural: Cast-in-place concrete frame Exterior walls: Cast-in-place concrete;

CMU block; brick

Interior walls: Cast-in-place concrete;

CMU block

Exterior surface/facade: Brick; colored

concrete

### **Construction process**

Finance method: Special election; 1¢ county sales tax for 20 months Contract method: Conventional Use of inmate labor: None Use of prefabrication: None

### **Inmate cells**

Doors/material: Steel

Doors/type: Swinging; sliding

Doors/locking: Motor driven and remote

locking

Floor surface: Epoxy coating; vinyl tile Intercom: Two-way to cells and common

areas

HVAC: Air conditioning; gas heat Plumbing: Stainless combination unit

Furniture: Steel

Fire protection: Smoke detectors for cells and common areas; sprinklers for common areas; manual alarm stations

#### Inmate design capacity

Single occupancy: 83 Double occupancy: 42

Dorms: 0

Special housing: 11 General population: 125

Total: 136

### **Current staff**

Full-time equivalent:

Administration: Unknown

Security: Unknown

Programs/treatment: Unknown Maintenance: Unknown

Total: Unknown

Current inmate/staff ratio: Unknown

### Architect's reported analyses

Factors affecting construction costs: Positive: Simple construction methods, repetitiveness of design; good competi-


tion, favorable market

Negative: Difficult site conditions; government procedures, regulations, and red tape; complex electronic and

mechanical systems

Factors affecting time schedule:
Positive: Repetitiveness of design; advanced order of materials and hardware; coordination of design between parties
Negative: Government red tape; complex

electronic and mechanical systems



### Oklahoma State Penitentiary (Addition/Remodel)

Jurisdiction official: Gary Maynard, Director, Department of Corrections

Contact: Warden James Saffle, Oklahoma State Penitentiary, P.O. Box 97, McAlester, OK 74501, 918-423-4700

Architect: Bruton, Knowles & Love, Inc., P.O. Box 582528, Tulsa, OK 74158, 918-835-9588

Construction manager: None

Groundbreaking: November 1978 Finish date: November 1984 Construction time: 72 months Design capacity: 500
Total cost: \$17,204,022
Total annual operating costs:
\$10,367,500 (entire facility)

Category: New, ancillary building; remodeling/renovation; expansion Facility type: State prison

Building configuration: Wheel, spoke,

or radial

#### **Costs**

Total: \$17,204,022

Building only: \$15,804,022 Housing area: \$14,500,000 Housing per inmate: \$29,000 Housing per cell: \$29,000

Total per inmate: N/A (addition/remodel)

Perimeter: Double fence; razor wire on

and between fences; towers; patrols

Total per GSF: \$90.17
Total annual operating costs: \$10,367,500 (entire facility)

### **Construction type**

Gross square feet/other: 0
Gross square feet/total: 190,800

Net/gross square feet: 77%

**Dimensions** 

Structural: Load bearing precast panels; cast-in-place concrete frame Exterior walls: Precast panels Interior walls: Precast panels; cast-in-place concrete Exterior surface/facade: Colored concrete

Gross square feet/corrections: 190,800

Housing area square feet: 172,000

Gross square feet per inmate: 382

Size of cells: 98 square feet (single)

### **Inmate design capacity**

Single occupancy: 500 Double occupancy: 0

Dorms: 0

Special housing: 0 General population: 500

Total: 500

### **Inmate cells**

Medium: 0

Minimum: 0

Security

Doors/material: Steel Doors/type: Swinging

Inmate security level:

Maximum: 100%

Doors/locking: Motor driven and remote

locking

Floor surface: Sealed concrete Intercom: Two-way to common areas HVAC: Air conditioning; hot water

boilers

Plumbing: Stainless steel

Furniture: Steel

Fire protection: Smoke detectors for cells

#### **Current staff**

Full-time equivalent: Administration: 7 Security: 278

Programs/treatment: 21 Maintenance: 16

Total: 364 (entire facility)
Current inmate/staff ratio: 1.79:1

### **Inmate housing areas**

Design: Linear, outside Cells per unit: 80 to 112 Inmates per unit: 80 to 112

Management type: Remote surveillance October 1985 population: 650 Facility commitment: State prisoners Means to handle crowding: Bunk beds in cell; second bunk permanently attached

to wall

#### **Construction process**

Finance method: State funds Contract method: Conventional Use of inmate labor: None

Use of prefabrication: Extensive; entire structure was precast concrete with

minor CIP

### Architect's reported analyses

Factors affecting construction costs: Positive: Use of prefabricated components,

factory assembly

Negative: Complex electronic, mechan-

ical, and electrical systems


Factors affecting time schedule:

Positive: Use of prefabricated components,

factory assembly

Negative: Slow responses and delivery

from vendors, suppliers



### **Ouachita Correctional Center (Addition)**

Jurisdiction official: Gary Maynard, Director, Department of Corrections

Contact: Warden Bill Yeager, Ouachita Correctional Center, Route 1, P.O. Box 70, Hodgen, OK 74939, 918-653-7831 Architect: The Benham Group, Inc., P.O. Box 20400, 9400 North Broadway, Oklahoma City, OK 73156, 405-478-5353

Construction manager: None

Groundbreaking: September 1982

Finish date: May 1983 Construction time: 8 months Design capacity: 90 **Total cost:** \$1,426,200

Total annual operating costs:

N/A (addition)

Category: New, ancillary building

Facility type: State prison

Building configuration: Integrated

structure

### Costs

Total: \$1,426,200

Building only: \$1,406,200 Housing area: Unknown Housing per inmate: Unknown Housing per cell: Unknown

Total per inmate: \$15,847 Total per GSF: \$57.92

Total annual operating costs: N/A

(addition)

Perimeter: Building exterior; single fence

Inmate security level: Maximum: 0

Minimum: 94.6% (+ 5.4% holding)

### **Dimensions**

Gross square feet/corrections: 24,625

Gross square feet/other: 0 Gross square feet/total: 24,625 Housing area square feet: 20,033 Gross square feet per inmate: 274 Size of cells: 63 square feet (single)

Net/gross square feet: 98%

#### **Inmate housing areas**

Design: Module/pod Cells per unit: 90 Inmates per unit: 90

Management type: Remote surveillance

October 1985 population: 90

Facility commitment: State prisoners Means to handle crowding: Stacked bunks

in cell

### Security

Medium: 0

### Construction type

Structural: Load bearing precast panels

Exterior walls: Precast panels

Interior walls: Precast panels; CMU block Exterior surface/facade: Raked finish,

precast

### **Construction process**

Finance method: State funds Contract method: Conventional Use of inmate labor: None

Use of prefabrication: Extensive; exterior walls; most interior walls; precast

concrete slabs

#### **Inmate cells**

Doors/material: Steel Doors/type: Swinging

Doors/locking: Manual locking

Floor surface: Linoleum; sealed concrete Intercom: One-way to common areas; two-way to counseling rooms HVAC: Heating/air circulation only;

gas A.H.U. Plumbing: China Furniture: Steel; wood

Fire protection: Smoke detectors in common areas, cells, and mechanical ductwork; fire hose cabinets and

fire extinguishers

#### Inmate design capacity

Single occupancy: 84 Double occupancy: 0

Dorms: 0

Special housing: 6 General population: 84

Total: 90

#### Architect's reported analyses

Factors affecting construction costs: Positive: Use of prefabricated components, factory assembly; simple construction methods; less expensive materials and

hardware Negative: None

Factors affecting time schedule: Positive: Use of prefabricated components,

factory assembly; simple construction methods; coordination of design

between parties

Negative: None


#### **Current staff**

Full-time equivalent: Administration: N/A

Security: N/A

Programs/treatment: N/A Maintenance: N/A

Total: N/A (no extra staff added) Current inmate/staff ratio: Unknown



## **Jackson County Jail**

Jurisdiction official: C.W. Smith, Sheriff

Contact: Gale R. Fulton, Jail Administrator, Jackson County Jail, 787 West 8th Street, Medford, OR 97501, 503-776-7127 Architect: Afseth, Jacobs & Schmitz, Architects, A.I.A., 2950 East Barnett Road, Medford, OR 97504, 503-779-5237

Construction manager: None

**Groundbreaking:** October 1978 Finish date: February 1981 Construction time: 28 months

Design capacity: 183 **Total cost:** \$7,921,838

Total annual operating costs: \$1,984,629

Category: New, independent facility

Facility type: County jail

**Inmate housing areas** 

Design: Linear, outside

Building configuration: Integrated

structure

#### Costs

Total: \$7,921,838 Building only: \$7,589,851 Housing area: Unknown Housing per inmate: Unknown Housing per cell: Unknown Total per inmate: \$43,289

Total per GSF: \$87.42

Total annual operating costs: \$1,984,629

Perimeter: Building exterior only

Inmate security level:

Maximum: 13%

Medium: 55% Minimum: 22%

Holding: 10%

### **Dimensions**

Gross square feet/corrections: 90,621 Gross square feet/other: 0 Gross square feet/total: 90,621 Housing area square feet: 32,301 Gross square feet per inmate: 495 Size of cells: 55 square feet (single) Net/gross square feet: 81%

### **Construction type**

Structural: Cast-in-place concrete frame;

Exterior walls: Cast-in-place concrete;

architectural precast

Interior walls: Cast-in-place concrete;

Exterior surface/facade: Colored concrete

precast core floor

CMU block; steel studs with gypsum

Single occupancy: 112 Double occupancy: 4

Inmate design capacity

Dorms: 0

Special housing: 67 General population: 116

Total: 183

#### **Inmate cells**

Security

Doors/material: Solid; wooden

Doors/type: Swinging Doors/locking: Unknown

Floor surface: Carpet; sealed concrete;

vinyl tile

Intercom: Two-way to cells

HVAC: Air conditioning; gas heat; heat

recovery from housing Plumbing: Stainless steel; china

Furniture: Steel; wood

Fire protection: Smoke detectors for cells

#### **Current staff**

Full-time equivalent: Administration: 11 Security: 41

> Programs/treatment: 2 Maintenance: 3

Total: 57

Current inmate/staff ratio: 3.30:1

Cells per unit: 8 (med.); 16 (max.) Inmates per unit: 8 (med.); 16 (max.) Management type: Remote surveillance April 1986 population: 188

Facility commitment: Local jail inmates Means to handle crowding: Mattresses on

floor

#### **Construction process**

Finance method: Local funds Contract method: Conventional Use of inmate labor: None

Use of prefabrication: Limited; concrete

deck and exterior facade

### Architect's reported analyses


Factors affecting construction costs: Positive: Simple construction methods,

repetitiveness of design

Negative: Slow construction, lengthy building time; high labor costs; complex electronic, mechanical, and electrical systems

Factors affecting time schedule:

Positive: None Negative: None



### Justice Center

Jurisdiction official: Fred B. Pearce, Sheriff

Contact: Captain Joe Golden, Justice Center, 1120 SW. Third, Portland, OR 97204, 503-248-5129

Architect: Zimmer Gunsul Frasca Partnership, Suite 500, 320 SW. Oak, Portland, OR 97204, 503-224-3860

Construction manager: Turner Construction Company, 1201 Pennsylvania Avenue NW., Washington, DC 20004, 202-393-5100

**Groundbreaking:** May 1980 Finish date: November 1983 Construction time: 43 months Design capacity: 430 **Total cost:** \$44,162,400 Total annual operating costs: \$11,477,300

Category: New, independent facility Facility type: Complex: county jail, law enforcement admin., courts, retail Building configuration: High rise

Costs

Total: \$44,162,400 Building only: \$44,112,400 Housing area: \$12,430,573 Housing per inmate: \$32,371 Housing per cell: \$32,371

Total per inmate: N/A (complex)

Total per GSF: \$93.56

Total annual operating costs: \$11,477,300

Security

Perimeter: Building exterior only

Inmate security level: Maximum: 0 Medium: 100% Minimum: 0

**Inmate cells** 

Doors/material: Wooden Doors/type: Swinging

Doors/locking: Remote locking only Floor surface: Sealed concrete Intercom: One-way to cells; two-way

to common areas

HVAC: Air conditioning; heat exchanger (hot water); gas-fired boilers Plumbing: Stainless combination unit

Furniture: Concrete

Fire protection: Smoke detectors and sprinklers for cells and common areas; manual alarm stations; manual override

of cell sprinklers

**Dimensions** 

Gross square feet/corrections: 243,245 Gross square feet/other: 228,793 Gross square feet/total: 472,038 Housing area square feet: 108,792 Gross square feet per inmate: 566 Size of cells: 70 square feet (single)

Net/gross square feet: 57%

**Construction type** 

Structural: Load bearing precast panels; cast-in-place concrete frame Exterior walls: Cast-in-place concrete;

architectural precast Interior walls: Precast panels;

cast-in-place concrete; CMU block Exterior surface/facade: Precast

textured concrete

Inmate design capacity

Single occupancy: 384 Double occupancy: 0

Dorms: 0

Special housing: 46 General population: 384

Total: 430

**Current staff** 

Full-time equivalent: Administration: 27 Security: 193

Programs/treatment: 46

Maintenance: 43

Total: 309 (not incl. food service or

county medical staff)

Current inmate/staff ratio: 1.55:1

**Inmate housing areas** 

Design: Module/pod Cells per unit: 32 Inmates per unit: 32

Management type: Direct supervision

October 1985 population: 480

Facility commitment: Local jail inmates Means to handle crowding: Mattresses

on floor

**Construction process** 

Finance method: Federal and State funds Contract method: Construction

management fast track Use of inmate labor: None

Use of prefabrication: Extensive, precast cell walls and exterior cladding

Architect's reported analyses

Factors affecting construction costs: Positive: Use of prefab.; repetitiveness of design; three bid packages; good competition, favorable market; collaboration in value engineering Negative: Small downtown site, strict


development guidelines; complex electronic monitoring and control system for security

Factors affecting time schedule: Positive: Use of prefab.; repetitiveness of design; three bid packages;


coordination of design between parties; pressure to complete before demolition

of existing jail

Negative: Complex electronics system



FOURTH FLOOR PLAN SPECIAL HOUSING



FIFTH THROUGH EIGHTH FLOOR PLAN TYPICAL HOUSING

## Allegheny County Jail Annex (Remodel/Expansion)

Jurisdiction official: Charles J. Kozakiewicz, Warden

Contact: Warden Charles Kozakiewicz, Allegheny County Jail Annex, 311 Ross Street, Pittsburgh, PA 15219, 412-355-4451

Architect: L. Robert Kimball & Associates, 615 West Highland Avenue, Edensburg, PA 15931, 814-472-7700

Construction manager: Dick Corporation, P.O. Box 10896, Pittsburgh, PA 15236, 412-664-8000

Groundbreaking: October 1984 Finish date: January 1986 Construction time: 15 months

Design capacity: 274 **Total cost:** \$9,678,540

Total annual operating costs: \$3,503,700

(entire facility)

Category: Remodeling/renovation

project; expansion Facility type: County jail

Building configuration: High rise

#### Costs

Total: \$9,678,540

Building only: \$9,554,540 Housing area: \$7,020,000 Housing per inmate: \$25,620 Housing per cell: \$25,620 Total per inmate: \$35,323 Total per GSF: \$113.66

Total annual operating costs: \$3,503,700

(entire facility)

reinforced at security perimeter Exterior walls: Brick; two-inch insulation

in cavity

Interior walls: CMU block

## **Security**

Perimeter: Building exterior only

Inmate security level: Maximum: 0 Medium: 0 Minimum: 100%

#### **Inmate cells**

Doors/material: Steel

Doors/type: Swinging; sliding Doors/locking: Motor driven and remote

locking

Floor surface: Sealed concrete

Intercom: Two-way to cells and common

HVAC: Steam heat Plumbing: Stainless steel

Furniture: Steel

Fire protection: Smoke detectors and sprinklers for cells and common areas; manual alarm stations; smoke ejectors

### **Dimensions**

Gross square feet/corrections: 85,150

Gross square feet/other: 0 Gross square feet/total: 85,150 Housing area square feet: 45,280 Gross square feet per inmate: 311

Size of cells: Unknown Net/gross square feet: 78%

### **Construction type**

Structural: Steel frame; CMU partition

Exterior surface/facade: Brick; dryvit

#### Inmate design capacity

Single occupancy: 274 Double occupancy: 0

Dorms: 0

Special housing: 0 General population: 274

Total: 274

#### **Current staff**

Full-time equivalent: Administration: 13 Security: 113 Programs/treatment: 7 Maintenance: 4

Total: 137 (entire facility) Current inmate/staff ratio: 3.01:1

## **Inmate housing areas**

Design: Module/pod Cells per unit: 50 Inmates per unit: 50

Management type: Direct supervision

May 1987 population: 412

Facility commitment: Local iail inmates Means to handle crowding: Unknown

### **Construction process**

Finance method: G.O. Bonds Contract method: Conventional Use of inmate labor: None Use of prefabrication: None

### Architect's reported analyses

Factors affecting construction costs: Positive: Simple construction methods; good competition; renovation of existing county office building as auxiliary jail


Negative: Difficult site conditions; costly remodel


Factors affecting time schedule:

Positive: Phased construction, fast track CM; coordination of design between

parties

Negative: Slow responses and delivery from vendors, suppliers; conversion/ remodel of office building into jail





TYPICAL UPPER LEVEL CELL FLOOR

### **Blair County Prison (Expansion)**

Jurisdiction official: William Stouffer, County Commissioner

Contact: Warden Garry Sparks, Blair County Prison, Hollidaysburg, PA 16648, 814–695–9731

Architect: L. Robert Kimball & Associates, 615 West Highland Avenue, Ebensburg, PA 15931, 814-472-7700

Construction manager: None

**Groundbreaking:** July 1982 Finish date: September 1984 Construction time: 27 months Design capacity: 141 **Total cost:** \$4,092,581

Total annual operating costs: N/A

(expansion)

Category: Expansion project Facility type: County jail

**Building configuration:** Integrated

structure

#### Costs

Total: \$4,092,581 Building only: \$3,936,257

Housing area: Unknown Housing per inmate: Unknown Housing per cell: Unknown Total per inmate: \$29,025 Total per GSF: \$81.69

Total annual operating costs: N/A

(expansion)

### Security

Perimeter: Building exterior only

Inmate security level: Maximum: 18% Medium: 67% Minimum: 15%

### **Dimensions**

Gross square feet/corrections: 50,100 Gross square feet/other: 0 Gross square feet/total: 50,100

Housing area square feet: 21,950 Gross square feet per inmate: 355 Size of cells: 60 square feet (single);

90 square feet (double) Net/gross square feet: Unknown

### **Construction type**

Structural: Steel frame Exterior walls: Brick Interior walls: CMU block Exterior surface/facade: Brick

#### **Inmate cells**

Doors/material: Steel

Doors/type: Swinging; sliding

Doors/locking: Motor driven and remote

locking

Floor surface: Sealed concrete

Intercom: Two-way to cells and common

HVAC: Air conditioning Plumbing: Stainless; china

Furniture: Steel

Fire protection: Smoke detectors and sprinklers for cells and common areas;

smoke ejectors

## Inmate design capacity

Single occupancy: 14 Double occupancy: 108

Dorms: 8

Special housing: 11 General population: 130

Total: 141

#### **Current staff**

Full-time equivalent: Administration: 4 Security: 42

Programs/treatment: 0 (contractual) Maintenance: 0 (contractual) Total: 46 (expansion only) Current inmate/staff ratio: 3.41:1

#### **Inmate housing areas**

Design: Module/pod (new); linear,

outside (old) Cells per unit: 7 to 15

Inmates per unit: 7 to 38

Management type: Remote surveillance

October 1985 population: 157

Facility commitment: Local jail inmates Means to handle crowding: DUI quarters;

work release unit

### **Construction process**

Finance method: G.O. Bonds Contract method: Conventional Use of inmate labor: None Use of prefabrication: None


#### Architect's reported analyses

Factors affecting construction costs: Positive: Simple construction methods, repetitiveness of design; good competition, favorable market Negative: Difficult site conditions

Factors affecting time schedule: Positive: Simple construction methods, repetitiveness of design; coordination of design between parties

Negative: Slow responses and delivery

from vendors, suppliers



### **Lycoming County Prison**

Jurisdiction official: Charles Brewer, Sheriff

Contact: Warden David Desmond, Lycoming County Prison, 277 West Third Street, Williamsport, PA 17701, 717-326-4623

Architect: L. Robert Kimball & Associates, 615 West Highland Avenue, Ebensburg, PA 15931, 814-472-7700

Construction manager: None

Groundbreaking: September 1983

Finish date: October 1985

Construction time: 26 months

Design capacity: 150 **Total cost:** \$6,579,727

Total annual operating costs:

\$1,480,986

Category: New, independent facility

Facility type: County jail

**Building configuration:** Integrated

structure

**Costs** 

Total: \$6,579,727

Building only: \$6,467,292

Housing area: Unknown Housing per inmate: Unknown Housing per cell: Unknown

Total per inmate: \$43,865 Total per GSF: \$101.13

Total annual operating costs: \$1,480,986

**Dimensions** 

Gross square feet/corrections: 65,060

Gross square feet/other: 0 Gross square feet/total: 65,060 Housing area square feet: 22,965 Gross square feet per inmate: 434

Size of cells: 60 to 80 square feet (single) Net/gross square feet: N/A

**Inmate housing areas** 

Design: Module/pod Cells per unit: 6 to 10 Inmates per unit: 6 to 10

Management type: Remote surveillance;

patrols

October 1985 population: 134

Facility commitment: Local jail inmates Means to handle crowding: Bunk beds in

cell; transfer out

Security

Perimeter: Building exterior only

Inmate security level: Maximum: 20% Medium: 60% Minimum: 20%

Construction type

Structural: Steel frame Exterior walls: Brick Interior walls: CMU block Exterior surface/facade: Brick **Construction process** 

Finance method: G.O. Bonds Contract method: Conventional Use of inmate labor: None Use of prefabrication: None

**Inmate cells** 

Doors/material: Steel Doors/type: Sliding

Doors/locking: Motor driven and remote

locking

Floor surface: Sealed concrete

Intercom: Two-way to cells and common

HVAC: Air conditioning; steam heating

plant

Plumbing: Stainless Furniture: Steel

Fire protection: Smoke detectors for cells and common areas; smoke ejectors

Inmate design capacity

Single occupancy: 142 Double occupancy: 0

Dorms: 0

Special housing: 8 General population: 142

Total: 150

Architect's reported analyses

Factors affecting construction costs: Positive: Simple construction methods, repetitiveness of design; good competition, favorable market Negative: Difficult site conditions (demolition of existing buildings)

Factors affecting time schedule: Positive: Simple construction methods,

repetitiveness of design; coordination of design between parties

Negative: Slow responses and delivery from vendors, suppliers; weather problems due to late contract award


**Current staff** 

Full-time equivalent: Administration: 6 Security: 44

> Programs/treatment: 6 Maintenance: 5

Total: 61

Current inmate/staff ratio: 2.20:1



### Philadelphia Industrial Correctional Center

Jurisdiction official: Edmund H. Lyons, Superintendent of Prisons

Contact: Warden Philip J. Dukes, Philadelphia Industrial Correctional Center, 8301 State Road, Philadelphia, PA 19136,

215-335-7102

Architects: The Ehrenkrantz Group, 19 West 44th Street, New York, NY 10036, 212-730-1950 Jacobs Wyper, 1232 Chancellor Street, Philadelphia, PA 19136, 215-985-0400

Construction manager: Morrison-Knudsen/Parametric Co., P.O. Box 11110, Philadelphia, PA 19136, 215-331-7820

Groundbreaking: May 1984 Finish date: May 1986

Construction time: 24 months

Design capacity: 650 Total cost: \$50,000,000

Total annual operating costs: Unknown

Category: New, independent facility;

phased project (future)

Facility type: County jail; city jail Building configuration: Integrated

structure; clusters

#### Costs

Total: \$50,000,000

Building only: \$47,500,000

Housing area: Unknown Housing per inmate: Unknown Housing per cell: Unknown

Total per inmate: \$76,923 Total per GSF: \$181.82

Total annual operating costs: Unknown

#### **Dimensions**

Gross square feet/corrections: 275,000

Gross square feet/other: 0 Gross square feet/total: 275,000 Housing area square feet: 126,000 Gross square feet per inmate: 423 Size of cells: 70 square feet (single) Net/gross square feet: Unknown

### **Construction type**

Structural: Steel frame

Exterior walls: Cast-in-place concrete;

CMU block; brick

Interior walls: Cast-in-place concrete; CMU block; drywall, security plaster Exterior surface/facade: Brick; split faced

block; marble trim

#### Security

Perimeter: Building exterior; double fence with razor wire; alarm/detection systems; patrols; camera surv.

Inmate security level: Maximum: 62% Medium: 32% Minimum: 0 Other: 6%

#### **Inmate cells**

Doors/material: Steel Doors/type: Swinging

Doors/locking: Remote locking Floor surface: Epoxy coating; sealed

concrete

Intercom: PA monitor in walkways outside cells; one-way to cells

HVAC: Air conditioning

Plumbing: Stainless steel; nonsecurity lavatory built into precast vanity unit,

plastic seat

Furniture: Steel; wood

Fire protection: Smoke detectors and sprinklers for cells and common areas; manual alarm stations; preaction system with abort function

#### Inmate design capacity

Single occupancy: 550 Double occupancy: 0

Dorms: 0

Special housing: 100 General population: 550

Total: 650

#### Current staff

Full-time equivalent: Administration: 22 Security: 202

> Programs/treatment: 10 Maintenance: 26

Total: 260

Current inmate/staff ratio: N/A

**Inmate housing areas** 

Design: Module/pod Cells per unit: 50 Inmates per unit: 50

Management type: Direct supervision

August 1986 population: 235

Facility commitment: Local jail inmates Means to handle crowding: Unknown

### **Construction process**

Finance method: G.O. Bonds; Certificates of Participation; local funds; facility owned by municipal authority and

leased back to city

Contract method: Construction manage-

ment fast track

Use of inmate labor: None Use of prefabrication: None

### Architects' reported analyses

Factors affecting construction costs: Positive: Repetitiveness of design; fast track CM; less expensive materials and hardware; being a "new generation jail"


Negative: High labor costs; difficult site conditions; complex electronic and mechanical systems; 35% minority enterprise requirements on all bids

Factors affecting time schedule: Positive: Simple construction methods; phased construction; cooperation between owner, user, architect, and

construction manager

Negative: Slow delivery from vendors and subcontractor; complex electronic and

mechanical systems



### Schuylkill County Prison (New and Remodel)

Jurisdiction official: John E. Lavelle, Chairman, Prison Board

Contact: Warden David J. Kurtz, Schuylkill County Prison, 2nd and Sanderson Streets, Pottsville, PA 17901, 717-622-5570

Architect: Benatec Associates, P.O. Box 1943, Harrisburg, PA 17105, 717–763–7391

Construction manager: Mellon-Stuart Company, P.O. Box 1161, Pottsville, PA 17901, 717-628-4050

Groundbreaking: June 1984 Finish date: June 1986 Construction time: 24 months

**Design capacity:** 140 **Total cost:** \$5,313,872

**Total annual operating costs:** \$820,375

Category: New, independent facility; remodeling/renovation project

Facility type: County jail

**Building configuration:** Integrated

structure

#### **Costs**

Total: \$5,313,872

Building only: \$5,158,992 Housing area: Unknown Housing per inmate: Unknown Housing per cell: Unknown Total per inmate: \$37,956 Total per GSF: \$91.27

Total annual operating costs: \$820,375

#### **Dimensions**

Gross square feet/corrections: 58,220

Gross square feet/other: 0 Gross square feet/total: 58,220 Housing area square feet: Unknown Gross square feet per inmate: 416 Size of cells: 70 square feet (single)

Net/gross square feet: 61%

### **Inmate housing areas**

Design: Module/pod Cells per unit: 30 Inmates per unit: 30

Management type: Remote surveillance

June 1986 population: 163

Facility commitment: Local jail inmates Means to handle crowding: None

### **Security**

Perimeter: Existing perimeter wall; video

camera surveillance Inmate security level: Maximum: 12% Medium: 73% Minimum: 15%

## **Construction type**

Structural: Steel frame

Exterior walls: CMU block; brick, splitfaced concrete masonry units with iron

spot brick coursing

Interior walls: Precast panels; cast-in-place

concrete; CMU block Exterior surface/facade: Brick

### **Construction process**

Finance method: G.O. Bonds

Contract method: Construction manage-

ment fast track

Use of inmate labor: None Use of prefabrication: None

#### **Inmate cells**

Doors/material: Solid; steel Doors/type: Swinging

Doors/locking: Remote and manual

locking

Floor surface: Sealed concrete
Intercom: Two-way to common areas
HVAC: Heating/air circulation; coal fired
boiler with hot water radiant floor

panels Plumbing: Stainless steel

Furniture: Steel

Fire protection: Smoke detectors for cells and common areas; manual alarm

stations

### Inmate design capacity

Single occupancy: 113 Double occupancy: 0

Dorms: 0

Special housing: 27 General population: 113

Total: 140

### **Current staff**

Full-time equivalent: Administration: 5 Security: 21

Programs/treatment: 4 Maintenance: 2

Total: 32

Current inmate/staff ratio: 5.09:1

#### Architect's reported analyses

Factors affecting construction costs:
Positive: Simple construction methods,
repetitiveness of design; phased
construction, fast track construction
management; good competition,
favorable market


Negative: Difficult site conditions; government procedures, regulations,

and red tape

Factors affecting time schedule:

Positive: Phased construction, fast track

construction management Negative: Weather problems



### **State Correctional Institution at Smithfield**

Jurisdiction official: David S. Owens Jr., Commissioner, Department of Corrections

Contact: Superintendent Margaret Moore, State Correctional Institution at Smithfield, 1120 Pike Street, Huntingdon, PA 11652,

814-963-6520

Architect: Sullivan Associates, Architects & Planners, 2314 Market Street, 2nd Floor, Philadelphia, PA 19103, 215-567-7300

Construction manager: None

Groundbreaking: November 1984 Finish date: December 1987 Construction time: 37 months

Design capacity: 560 Total cost: \$26,665,159 Total annual operating costs: \$11,300,000 (projected)

Gross square feet/corrections: 245,000

Size of cells: 63 square feet (single); 48

Housing area square feet: 110,000

Gross square feet per inmate: 438

Category: New, independent facility

Facility type: State prison

Building configuration: Campus style

### **Costs**

Total: \$26,665,159 Building only: \$23,840,069 Housing area: \$15,624,000 Housing per inmate: \$30,516 Housing per cell: \$30,516 Total per inmate: \$47,616

(projected)

# Net/gross square feet: 73%

(spec. double)

**Dimensions** 

Structural: Steel frame; cast-in-place

precast plank

Exterior walls: CMU block; brick Interior walls: CMU block Exterior surface/facade: Brick

Total per GSF: \$108.84

Total annual operating costs: \$11,300,000

### **Security**

Perimeter: Double fence; razor wire on fences: towers

Inmate security level: Maximum: 10% Medium: 90% Minimum: 0

#### Inmate cells

Doors/material: Steel Doors/type: Swinging

Doors/locking: Remote locking Floor surface: Sealed concrete

Intercom: None

HVAC: Air conditioning; coal furnace

Plumbing: China Furniture: Steel

Fire protection: Smoke detectors for cells

and common areas

# **Construction type**

Gross square feet/other: 0 Gross square feet/total: 245,000

concrete frame; CMU bearing walls and

#### **Inmate design capacity**

Single occupancy: 512 Double occupancy: 0

Dorms: 0

Special housing: 48 General population: 512

Total: 560

#### Current staff

Full-time equivalent: Administration: 82 Security: 216 Programs/treatment: 12

Maintenance: 38

Total: 348

Current inmate/staff ratio: N/A

#### **Inmate housing areas**

Design: Linear, outside Cells per unit: 64 Inmates per unit: 64

Management type: Remote surveillance November 1987 population: N/A Facility commitment: State prisoners Means to handle crowding: Second bunk

permanently attached to wall

### **Construction process**

Finance method: State funds Contract method: Conventional Use of inmate labor: None

Use of prefabrication: Limited; precast concrete plank in approximately 50%

of facility structures

#### Architect's reported analyses

Factors affecting construction costs: Positive: NFPA guidelines for correctional facility life safety codes, appropriate for use and reasonably priced

Negative: None

Factors affecting time schedule:

Positive: None

Negative: Project could have been fast-

tracked

Huntingdon

(No floorplan available at time of publication)

### State Regional Correctional Facility at Mercer (Addition)

Jurisdiction official: David S. Owens, Jr., Commissioner, Department of Corrections

Contact: Superintendent Gilbert A. Walters, State Regional Correctional Facility at Mercer, 801 Butler Pike, Mercer, PA 16136,

412-748-3020

Architect: L.D. Astorino & Associates, Ltd., 227 Fort Pitt Boulevard, Pittsburgh, PA 15222, 412–765–1700

Construction manager: None

Groundbreaking: May 1984 Finish date: March 1986 Construction time: 22 months **Design capacity: 180 Total cost:** \$7,800,000

Gross square feet/other: 0

Net/gross square feet: 91%

Gross square feet/total: 76,200

Housing area square feet: 43,400

Gross square feet per inmate: 423

Size of cells: 70 square feet (single)

Total annual operating costs: N/A

Gross square feet/corrections: 76,200

(expansion)

**Dimensions** 

Category: New ancillary building

Facility type: State prison

Building configuration: Campus style

#### Costs

Total: \$7,800,000

Building only: \$7,200,000 Housing area: \$4,450,000 Housing per inmate: \$29,667 Housing per cell: \$29,667 Total per inmate: \$43,333 Total per GSF: \$102.36

Total annual operating costs: N/A

(expansion)

### Security

Perimeter: Single fence; razor wire on

fence; patrols Inmate security level: Maximum: 6% Medium: 94% Minimum: 0

## Construction type

Structural: Precast concrete frame Exterior walls: Brick

Interior walls: CMU block Exterior surface/facade: Brick

### **Inmate cells**

Doors/material: Steel Doors/type: Sliding

Doors/locking: Motor driven and remote

locking

Floor surface: Sealed concrete

Intercom: One-way to cells and common

HVAC: Air conditioning; electric heat

Plumbing: China Furniture: Steel

Fire protection: Smoke detectors for common areas; manual alarm stations

# Inmate design capacity

Single occupancy: 150 Double occupancy: 0

Dorms: 0

Special housing: 30 General population: 150

Total: 180

#### **Current staff**

Full-time equivalent: Administration: N/A Security: N/A

Programs/treatment: N/A Maintenance: N/A Total: N/A (expansion)

Current inmate/staff ratio: Unknown

#### **Inmate housing areas**

Design: Linear, outside Cells per unit: 30 Inmates per unit: 30

Management type: Intermittent surveil-

November 1986 population: 180 Facility commitment: State prisoners Means to handle crowding: Bunk beds in cell; second bunk permanently attached

to wall

### **Construction process**

Finance method: State funds Contract method: Conventional

Use of inmate labor: Limited; installation

of furniture

Use of prefabrication: None

### Architect's reported analyses


Factors affecting construction costs: Positive: Simple construction methods; phased construction, fast track CM; good competition, favorable market;

efficient design

Negative: Slow construction, lengthy building time; high labor costs; difficult site conditions; government red tape

Factors affecting time schedule: Positive: Repetitiveness of design; advanced order of materials and hardware

Negative: Slow responses and delivery from vendors, suppliers; labor problems; weather problems; government procedures, regulations, and red tape



### Warren County Jail

Jurisdiction official: Donnell Allen, Jr., Sheriff

Contact: Sheriff Donnell Allen, Jr., Warren County Jail, Warren, PA 16365, 814-723-7553

Architect: L. Robert Kimball & Associates, 615 West Highland Avenue, Ebensburg, PA 15931, 814-472-7700

Construction manager: None

**Groundbreaking:** August 1978

Finish date: April 1980

**Construction time:** 20 months

Design capacity: 50 Total cost: \$2,189,614

**Total annual operating costs:** 

\$1,263,592

Category: New, independent facility

Facility type: County jail

Building configuration: Integrated

structure

**Costs** 

Total: \$2,189,614

Building only: \$2,126,369 Housing area: Unknown

Housing per inmate: Unknown Housing per cell: Unknown Total per inmate: \$43,792

Total per GSF: \$95.08

Total annual operating costs: \$1,263,592

**Dimensions** 

Gross square feet/corrections: 23,030

Gross square feet/other: 0 Gross square feet/total: 23,030 Housing area square feet: 7,300 Gross square feet per inmate: 461 Size of cells: 60 square feet (single)

Net/gross square feet: N/A

Inmate housing areas

Design: Module/pod Cells per unit: 3 to 9 Inmates per unit: 6 to 14

Management type: Remote surveillance

September 1987 population: 91

Facility commitment: Local jail inmates Means to handle crowding: Second bunk

permanently attached to wall

**Security** 

Perimeter: Building exterior only

Inmate security level:
Maximum: 15%
Medium: 70%
Minimum: 15%

**Construction type** 

Structural: Steel frame Exterior walls: Brick Interior walls: CMU block Exterior surface/facade: Brick **Construction process** 

Finance method: Revenue sharing Contract method: Conventional Use of inmate labor: None Use of prefabrication: None

**Inmate cells** 

Doors/material: Steel Doors/type: Sliding

Doors/locking: Motor driven and

remote locking

Floor surface: Sealed concrete

Intercom: Two-way to cells and common

areas

HVAC: Air conditioning; steam heating

plant

Plumbing: Stainless Furniture: Steel

Fire protection: Smoke detectors and sprinklers for common areas; manual

alarm stations; smoke ejectors

Inmate design capacity

Single occupancy: 43 Double occupancy: 0

Dorms: 0

Special housing: 7 General population: 43

Total: 50

Architect's reported analyses

Factors affecting construction costs: Positive: Simple construction methods, repetitiveness of design; good competition, favorable market;

site owned by county

Negative: Difficult site conditions

(had to demolish old jail)

Factors affecting time schedule: Positive: Simple construction methods, repetitiveness of design; coordination

of design between parties

Negative: Weather problems; rejected installation of precast concrete

**Current staff** 


Full-time equivalent: Administration: 2

Security: 19

Programs/treatment: 2

Maintenance: 1 Total: 24

Current inmate/staff ratio: 3.79:1



## Wyoming County Jail

Jurisdiction official: Robert Truesdale, Sheriff

Contact: Sheriff Robert Truesdale, Wyoming County Jail, Tunkhannock, PA 18657, 717-836-3200

Architect: L. Robert Kimball & Associates, 615 West Highland Avenue, Ebensburg, PA 15931, 814-472-7700

Construction manager: None

Groundbreaking: October 1984 Finish date: January 1986 Construction time: 16 months

Design capacity: 50 **Total cost: \$2,460,895** 

Total annual operating costs: \$238,000

(projected)

Category: New, independent facility

Facility type: County jail

**Building configuration:** Integrated

structure

#### **Costs**

Total: \$2,460,895 Building only: \$2,404,694 Housing area: Unknown Housing per inmate: Unknown Housing per cell: Unknown Total per inmate: \$49,218 Total per GSF: \$170.90

Total annual operating costs: \$238,000

Perimeter: Building exterior only

(projected)

Security

#### **Dimensions**

Gross square feet/corrections: 14,400 Gross square feet/other: 0 Gross square feet/total: 14,400 Housing area square feet: 6,960 Gross square feet per inmate: 288 Size of cells: 60 to 80 square feet (double) Net/gross square feet: Unknown

### **Construction type**

Structural: Steel frame Exterior walls: Brick Interior walls: CMU block

Exterior surface/facade: Brick

#### **Inmate cells**

Doors/material: Steel Doors/type: Sliding

Inmate security level:

Maximum: 10%

Medium: 70%

Minimum: 20%

Doors/locking: Motor driven and remote

locking

Floor surface: Sealed concrete Intercom: Two-way to cells and common

areas

HVAC: Air conditioning; steam heating

plant

Plumbing: Stainless steel

Furniture: Steel

Fire protection: Smoke detectors and sprinklers for cells and common areas; manual alarm stations; smoke ejectors

## Inmate design capacity

Single occupancy: 0 Double occupancy: 40

Dorms: 8

Special housing: 2 General population: 48

Total: 50

#### **Current staff**

Full-time equivalent: Administration: 2 Security: 16

> Programs/treatment: 0 Maintenance: 5

Total: 23

Current inmate/staff ratio: N/A

## **Inmate housing areas**

Design: Module/pod Cells per unit: 4 to 6 Inmates per unit: 8 to 12

Management type: Remote surveillance

October 1985 population: N/A

Facility commitment: Local jail inmates

Means to handle crowding: None

### **Construction process**

Finance method: G.O. Bonds Contract method: Conventional Use of inmate labor: None Use of prefabrication: None

#### Architect's reported analyses

Factors affecting construction costs: Positive: Simple construction methods,


repetitiveness of design

Negative: High labor costs; difficult site

conditions

Factors affecting time schedule: Positive: Simple construction methods, repetitiveness of design; coordination

of design between parties Negative: Weather problems



### Clemson Police Department (Remodel)

Jurisdiction official: Johnson Link, Chief of Police

Contact: Chief Johnson Link, Clemson Police Department, P.O. Box 1566, Clemson, SC 29633, 803-654-5636

Architect: Louis P. Batson III, Arch. Inc., 110 Williams Street, Greenville, SC 29601, 803-233-2232

Construction manager: None

Groundbreaking: September 1984

Finish date: June 1985 **Construction time:** 9 months Design capacity: 13 Total cost: \$134,000

Total annual operating costs: \$600,000

Category: Remodeling/renovation;

phased project (past)

Facility type: Complex: city jail; law

enforcement

Building configuration: Integrated

structure

#### **Costs**

Total: \$134,000

Building only: N/A (remodel) Housing area: Unknown Housing per inmate: Unknown Housing per cell: Unknown

Total per inmate: N/A (complex)

Total per GSF: \$22.71

Total annual operating costs: \$600,000

### **Dimensions**

Gross square feet/corrections: 1,000 Gross square feet/other: 4,900 Gross square feet/total: 5,900 Gross square feet per inmate: 77

Size of cells: 70 square feet (single) Net/gross square feet: 78%

### **Inmate housing areas**

Design: Linear, outside Cells per unit: 6 Inmates per unit: 12

Management type: Remote surveillance

October 1985 population: 2

Facility commitment: Local jail inmates Means to handle crowding: County jail

### **Security**

Perimeter: Building exterior only

Inmate security level: Maximum: 0 Medium: 100% Minimum: 0

### Construction type

Structural: Steel frame Exterior walls: CMU block Interior walls: CMU block

Exterior surface/facade: Stucco; paint

#### **Construction process**

Finance method: Local funds Contract method: Conventional Use of inmate labor: None Use of prefabrication: None

#### **Inmate cells**

Doors/material: Steel Doors/type: Swinging

Doors/locking: Manual locking Floor surface: Sealed concrete Intercom: One-way to cells

HVAC: Air conditioning; heating/air

circulation; heat pumps Plumbing: Stainless steel

Furniture: Steel

Fire protection: Smoke detectors for cells and common areas; manual alarm

stations

### Inmate design capacity

Single occupancy: 5 Double occupancy: 0

Dorms: 0 Other: 7

Special housing: 1 General population: 12

Total: 13

### Architect's reported analyses

Factors affecting construction costs: Positive: Simple construction methods, repetitiveness of design; good competition, favorable market; cooperation of South Carolina Department of Corrections

Negative: Slow construction, lengthy building time (default of original contractor)

Factors affecting time schedule:

Positive: Simple construction methods, repetitiveness of design; coordination of design between parties

Negative: Slow responses and delivery from vendors, suppliers (due to previous contractor problems)

#### **Current staff**

Full-time equivalent: Administration: 1 Security: 25


> Programs/treatment: 0 Maintenance: 0

Total: 26

Current inmate/staff ratio: .08:1



**LOWER LEVEL PLAN** 



### **Gilliam Psychiatric Center (Addition)**

Jurisdiction official: Parker Evatt, Commissioner, Department of Corrections

Contact: Warden Kenneth D. McKellar, Gilliam Psychiatric Center, 4344 Broad River Road, Columbia, SC 29210, 803-737-8572

Architect: Architects Boudreaux, Ltd., P.O. Box 5695, Columbia, SC 29250, 803-799-0247

Construction manager: None

Groundbreaking: March 1983

Finish date: July 1984

**Construction time:** 18 months

**Design capacity:** 96 **Total cost:** \$1,552,000

Total annual operating costs: N/A

(addition)

Category: New, ancillary building

Facility type: State prison

Building configuration: Campus style

#### **Costs**

Total: \$1,552,000 Building only: Unknown Housing area: Unknown Housing per inmate: Unknown Housing per cell: Unknown Total per inmate: \$16,167 Total per GSF: \$62.58

Total annual operating costs: N/A

(addition)

### **Security**

Perimeter: Double fence; alarm/detection systems; razor wire on fences; patrols;

video camera surveillance

Inmate security level:
Maximum: 0
Medium: 100%
Minimum: 0

#### **Inmate cells**

Doors/material: Solid; steel Doors/type: Swinging

Doors/locking: Remote locking; manual

locking

Floor surface: Vinyl tile

Intercom: Two-way to cells and common

areas

HVAC: Air conditioning; electric heat Plumbing: Stainless combination unit

Furniture: Steel

Fire protection: Smoke detectors and sprinklers for cells and common areas;

manual alarm stations

#### **Dimensions**

Gross square feet/corrections: 24,800

Gross square feet/other: 0 Gross square feet/total: 24,800 Housing area square feet: 20,982 Gross square feet per inmate: 258 Size of cells: 91 square feet (single)

Net/gross square feet: 79%

### **Construction type**

Structural: Steel frame

Exterior walls: Precast panels; brick Interior walls: Cast-in-place concrete;

CMU block

Exterior surface/facade: Brick

#### Inmate design capacity

Single occupancy: 96 Double occupancy: 0

Dorms: 0

Special housing: 0 General population: 96

Total: 96

#### **Current staff**

Full-time equivalent: Administration: 7 Security: 26

Programs/treatment: 47

Maintenance: 0

Total: 80 (entire facility) Current inmate/staff ratio: 1.19:1

#### **Inmate housing areas**

Design: Module/pod Cells per unit: 96 Inmates per unit: 96

Management type: Remote surveillance

September 1986 population: 95

Facility commitment: Local jail inmates;

State prisoners

Means to handle crowding: Unknown

### **Construction process**

Finance method: State funds

Contract method: Owner constructed Use of inmate labor: Extensive; everything

but security systems

Use of prefabrication: Limited; precast

panels

#### Architect's reported analyses

Factors affecting construction costs: Positive: Simple construction methods, repetitiveness of design; inmate labor Negative: Complex electronic, mechani-

cal, and electrical systems


Factors affecting time schedule: Positive: Advanced order of materials

between parties

Negative: Slow responses and delivery from vendors, suppliers; complex electronic, mechanical, and electrical

and hardware; coordination of design

systems



### **Lieber Correctional Institution**

Jurisdiction official: Parker Evatt, Commissioner, Department of Corrections

Contact: Warden P. Douglas Taylor, Lieber Correctional Institution, P.O. Box 205, Ridgeville, SC 29472, 803–875–3332 Architects: McNair, Johnson and Associates, 1529 Washington Street, P.O. Box 84, Columbia, SC 29202, 803–799–5472

Lescher & Mahoney, Inc., 1130 East Missouri, Suite 850, Phoenix, AZ 85014, 602–264–6803

Construction manager: None

Groundbreaking: October 1984

Finish date: July 1986

**Construction time:** 21 months

**Design capacity:** 696 **Total cost:** \$20,571,000

Total annual operating costs: \$5,977,898

Category: New, independent facility

Facility type: State prison

**Inmate housing areas** 

Building configuration: Campus style

#### **Costs**

Total: \$20,571,000

Building only: \$19,104,000 Housing area: \$10,928,000 Housing per inmate: \$15,701 Housing per cell: \$15,701

Total per inmate: \$29,556 Total per GSF: \$77.99

Total annual operating costs: \$5,977,898

### **Dimensions**

Gross square feet/corrections: 263,765

Gross square feet/other: 0 Gross square feet/total: 263,765 Housing area square feet: 168,828 Gross square feet per inmate: 379 Size of cells: 88 square feet (single)

Net/gross square feet: 95%

### Design: Module/pod

Design: Module/pod Cells per unit: 126 Inmates per unit: 126

Management type: Direct supervision; remote surv. for max. security
January 1987 population: 682
Facility commitment: State prisoners
Means to handle crowding: Unknown

### Security

Perimeter: Double fence; alarm/detection systems; razor wire on and between fences; patrols; camera surveillance

Inmate security level:
Maximum: 24%
Medium: 76%
Minimum: 0

### **Construction type**

Structural: Steel frame; bar joists on CMU walls

waiis

Exterior walls: CMU block; brick Interior walls: CMU block Exterior surface/facade: Brick, stucco

# **Construction process**

Finance method: G.O. Bonds; State funds Contract method: Conventional Use of inmate labor: None

Use of prefabrication: Limited; double-tee prestressed members for some building roofs

#### Inmate cells

Doors/material: Steel Doors/type: Swinging

Doors/locking: Remote locking; manual

locking

Floor surface: Sealed concrete; vinyl tile Intercom: One-way to common areas HVAC: Air conditioning; recirculated hot

water/chilled water

Plumbing: Stainless combination unit;

vitreous china Furniture: Steel

Fire protection: Smoke detectors for cells and common areas; sprinklers for cells; manual alarm stations; smoke

evacuation

### Inmate design capacity

Single occupancy: 696 Double occupancy: 0

Dorms: 0

Special housing: 0 General population: 696

Total: 696

## Architects' reported analyses

Factors affecting construction costs:
Positive: Simple construction methods,
repetitiveness of design; less
expensive materials and hardware
Negative: Complex electronic, mechanical, and electrical systems; lack of
skilled journeymen; competition with
other construction

Factors affecting time schedule: Positive: Simple construction methods, repetitiveness of design; coordination

of design between parties

Negative: Slow responses and delivery

from vendors, suppliers


#### **Current staff**

Full-time equivalent: Administration: 74 Security: 303

Programs/treatment: 28 Maintenance: 18

Total: 423

Current inmate/staff ratio: 1.61:1



### Myrtle Beach Law Enforcement Center

Jurisdiction official: J. Stanley Bird, Chief of Police

Contact: William A. Pickering, Detention Lieutenant, Myrtle Beach Law Enforcement Center, 1101 Oak Street, Myrtle Beach,

SC 29577, 803-626-9589

Architect: Timbes/Wilund/Usry/Architects, Inc., 5001 North Kings Highway, Suite 203, Myrtle Beach, SC 29577, 803-449-5204

Construction manager: None

Groundbreaking: May 1981 Finish date: October 1982 Construction time: 17 months **Design capacity:** 112 **Total cost:** \$3,743,625

**Total annual operating costs:** \$588,520

Category: New, independent facility Facility type: Complex: city jail; law enforcement, courts, 48-hour lockup Building configuration: Integrated

structure

Costs

Total: \$3,743,625

Building only: \$3,410,025 Housing area: \$1,400,000 Housing per inmate: \$12,500 Housing per cell: \$45,161 Total per inmate: N/A (complex)

Total per GSF: \$85.86

Total annual operating costs: \$588,520

Security

Perimeter: Building exterior; video

camera surveillance Inmate security level: Maximum: 0 Medium: 100% Minimum: 0

**Inmate cells** 

Doors/material: Steel Doors/type: Swinging

Doors/locking: Remote locking; manual

locking

Floor surface: Epoxy coating

Intercom: None

HVAC: Air conditioning; gas heat Plumbing: Stainless combination unit

Furniture: Steel

Fire protection: Smoke detectors and sprinklers for cells; manual alarm

stations

**Dimensions** 

Gross square feet/corrections: 21,000 Gross square feet/other: 22,600 Gross square feet/total: 43,600 Housing area square feet: 13,200 Gross square feet per inmate: 188 Size of cells: 75 square feet (single)

Net/gross square feet: 67%

Construction type

Structural: Steel frame; cast-in-place

concrete frame Exterior walls: Brick

Interior walls: Cast-in-place concrete;

CMU block; brick

Exterior surface/facade: Brick

Inmate design capacity

Single occupancy: 14 Double occupancy: 0

Dorms: 98

Special housing: 0 General population: 112

Total: 112

**Current staff** 

Full-time equivalent: Administration: 2 Security: 17

Security. 17

Programs/treatment: 0 (outside

contractor)

Maintenance: 0 (outside contractor)

Total: 19

Current inmate/staff ratio: 1.84:1

**Inmate housing areas** 

Design: Linear, outside Cells per unit: 12 to 19 Inmates per unit: 40 to 70

Management type: Intermittent surveillance; direct viewing of circulation

passages

June 1986 population: 35

Facility commitment: Local jail inmates\*
Means to handle crowding: Unknown

**Construction process** 

Finance method: Local funds Contract method: Conventional Use of inmate labor: None Use of prefabrication: None

Architect's reported analyses

Factors affecting construction costs:

Positive: Cooperation of owner/architect/contractor in dealing with negotiated

items

Negative: Complexity of multi-use law enforcement and city government


facility


Factors affecting time schedule:

Positive: Coordination of design between parties; job finished 2-3 months ahead

of schedule Negative: None

<sup>\*</sup>Juveniles are detained for no more than 6 hours.





### **Nashville Community Service Center (Addition)**

Jurisdiction official: Stephen H. Norris, Commissioner, Department of Correction

Contact: Warden Charles R. Bass, Nashville Community Service Center, 7466 Centennial Place Extended, Nashville, TN 37219–5260,

615-385-3810

Architect: Paul M. Johnson—Architect, 4206 Farrar Avenue, Nashville, TN 37215, 615–292–0120

Construction manager: None

Groundbreaking: January 1982 Finish date: December 1983 Construction time: 23 months **Design capacity:** 120 **Total cost:** \$280,000

Total annual operating costs: \$3,618,100

(entire facility)

Category: New, ancillary building

Facility type: State prison

Building configuration: Campus style

#### **Costs**

Total: \$280,000

Building only: \$260,000 Housing area: \$240,000 Housing per inmate: \$2,000 Housing per cell: \$60,000 Total per inmate: \$2,333 Total per GSF: \$17.50

Total annual operating costs: \$3,618,100

(entire facility)

#### Security

Perimeter: Single fence Inmate security level: Maximum: 0 Medium: 0

Minimum: 100%

#### **Inmate cells**

Doors/material: Steel
Doors/type: Swinging
Doors/locking: Unknown
Floor surface: Sealed concrete
Intercom: One-way to common areas
HVAC: Heating/air circulation; gas heat

Plumbing: China Furniture: Steel

Fire protection: Smoke detectors and sprinklers for common areas

#### **Dimensions**

Gross square feet/corrections: 16,000 Gross square feet/other: 0 Gross square feet/total: 16,000 Housing area square feet: 12,800 Gross square feet per inmate: 133 Size of cells: 3,200 square feet (dorm)

Net/gross square feet: 92%

### **Construction type**

Structural: Masonry bearing Exterior walls: Brick Interior walls: CMU block Exterior surface/facade: Brick

#### Inmate design capacity

Single occupancy: 0 Double occupancy: 0 Dorms: 120 Special housing: 0 General population: 120

Total: 120

#### **Current staff**

Full-time equivalent: Administration: 15 Security: 74

Programs/treatment: 16

Maintenance: 7

Total: 112 (entire facility)
Current inmate/staff ratio: 2.68:1

#### **Inmate housing areas**

Design: Dormitory style Cells per unit: 1 Inmates per unit: 30

Management type: Intermittent surveil-

lance

April 1986 population: 120

Facility commitment: State prisoners Means to handle crowding: Unknown

### **Construction process**

Finance method: State funds Contract method: State procurement Use of inmate labor: Extensive Use of prefabrication: Limited; wood

trussed rafters

#### Architect's reported analyses

Factors affecting construction costs: Positive: Simple construction methods, repetitiveness of design; less

expensive materials and hardware; use

of inmate labor Negative: None

Factors affecting time schedule: Positive: Simple construction methods, repetitiveness of design; coordination

of design between parties

Negative: Slow construction, lengthy

building time

### **Shelby County Justice Center**

Jurisdiction official: Jack Owens, Sheriff

Contact: Edward Totten, Chief Jailer, Shelby County Justice Center, 201 Poplar Avenue, Memphis, TN 38103, 901-576-2415 Architect: Mahan and Shappley Architects, Inc., 5575 Poplar Avenue, Suite 603, Memphis, TN 38119, 901-767-9170 Construction manager: Grinder, Taber and Grinder, Inc., 2850 Tarbora Avenue, P.O. Box 14485, Memphis, TN 38114, 901-743-6370

Groundbreaking: July 1977 Finish date: August 1981 Construction time: 49 months Design capacity: 1,224 **Total cost:** \$39,500,000 Total annual operating costs:

\$11,904,022

Category: New, independent facility Facility type: Complex: county and city jail; law enforcement, courts Building configuration: High rise

#### Costs

Total: \$39,500,000 Building only: \$39,140,000

Housing area: \$18,086,650 Housing per inmate: \$14,777 Housing per cell: \$14,777

Total per inmate: N/A (complex)

Total per GSF: \$48.39

Total annual operating costs: \$11,904,022

# **Dimensions**

Gross square feet/corrections: 326,892 Gross square feet/other: 489,448 Gross square feet/total: 816,340 Housing area square feet: 326,892 Gross square feet per inmate: 267 Size of cells: 54 square feet (single)

Net/gross square feet: 83%

# **Inmate housing areas**

Design: Module/pod Cells per unit: 23 Inmates per unit: 23

Management type: Intermittent surveil-

lance; remote surveillance July 1986 population: 1,240

Facility commitment: Local jail inmates Means to handle crowding: Beds in

dayroom

#### Security

Perimeter: Building exterior only

Inmate security level: Maximum: 4% Medium: 96% Minimum: 0

### **Construction type**

Structural: Steel frame; cast-in-place

concrete frame Exterior walls: Brick

Interior walls: Cast-in-place concrete;

CMU block

Exterior surface/facade: Brick

Inmate design capacity

Single occupancy: 1,224

General population: 1,224

Double occupancy: 0

Special housing: 0

Dorms: 0

Total: 1,224

#### **Construction process**

Finance method: G.O. Bonds; local funds Contract method: Construction manage-

ment

Use of inmate labor: None Use of prefabrication: None

#### **Inmate cells**

Doors/material: Solid; wooden and steel

Doors/type: Swinging; sliding

Doors/locking: Motor driven and remote locking; manual locking

Floor surface: Carpet; terrazzo Intercom: Two-way to common areas HVAC: Air conditioning; gas heat Plumbing: Stainless combination unit

Furniture: Steel

Fire protection: Smoke detectors and sprinklers for common areas; manual alarm stations; fully automatic sprinkler

and alarm

### **Current staff**

Full-time equivalent: Administration: 41 Security: 311

Programs/treatment: 0 Maintenance: 25

Total: 377

Current inmate/staff ratio: 3.29:1

### Architect's reported analyses


Factors affecting construction costs: Positive: Simple construction methods, repetitiveness of design; phased construction, fast track CM; good competition, favorable market Negative: Slow construction, lengthy

building time; difficult site conditions; government procedures, regulations,

and red tape.

Factors affecting time schedule: Positive: Simple construction methods, repetitiveness of design; coordination of design between parties

Negative: Slow responses and delivery from vendors, suppliers; weather problems; government red tape



### **Austin County Jail**

Jurisdiction official: Truman A. Maddox, Sheriff

Contact: Sheriff Truman A. Maddox, Austin County Jail, P.O. Box 457, Belleville, TX 77418, 409-865-3112

Architect: Christopher Di Stefano & Associates, Inc., 2500 Citywest Boulevard, #2010, Houston, TX 77042, 713-953-9032

Construction manager: None

Groundbreaking: May 1981 Finish date: December 1981 Construction time: 7 months

**Design capacity:** 52 **Total cost:** \$1,142,520

Total annual operating costs: Unknown

Category: New, independent facility Facility type: Complex: county jail, law

enforcement

**Building configuration:** Integrated

structure

### Costs

Total: \$1,142,520

Building only: \$1,124,520

Housing area: Unknown
Housing per inmate: Unknown
Housing per cell: Unknown
Total per inmate: N/A (complex)

Total per inmate: N/A (complex)

Total per GSF: \$77.72

Total annual operating costs: Unknown

#### **Dimensions**

Gross square feet/corrections: 8,200 Gross square feet/other: 6,500 Gross square feet/total: 14,700 Housing area square feet: 8,200 Gross square feet per inmate: 158 Size of cells: 55.5 square feet (single);

86 (spec. single)

Net/gross square feet: Unknown

### **Inmate housing areas**

Design: Linear, inside Cells per unit: 8 Inmates per unit: 8

Management type: Intermittent

surveillance

September 1987 population: 16

Facility commitment: Local jail inmates Means to handle crowding: Unknown

### **Security**

Perimeter: Building exterior; video

camera surveillance
Inmate security level:
Maximum: 40%
Medium: 60%
Minimum: 0

### **Construction type**

Structural: Steel frame

Exterior walls: Concrete job cast tilt wall

panels

Interior walls: CMU block

Inmate design capacity

Single occupancy: 24

Double occupancy: 0

Special housing: 16

General population: 36

Dorms: 12

Total: 52

Exterior surface/facade: Tilt wall concrete

### **Construction process**

Finance method: G.O. Bonds; local funds Contract method: Conventional Use of inmate labor: None Use of prefabrication: None

#### **Inmate cells**

Doors/material: Steel Doors/type: Sliding

Doors/locking: Motor driven and remote

locking

Floor surface: Sealed concrete

Intercom: Two-way to cells and common

areas

HVAC: Air conditioning; electric heat Plumbing: Stainless combination unit

Furniture: Steel

system

Fire protection: Smoke detectors for cells and common areas; manual alarm stations; automatic smoke removal **Current staff** 

Full-time equivalent: Administration: 1 Security: 5

Programs/treatment: 0 Maintenance: 0

Total: 6

Current inmate/staff ratio: 2.67:1

#### Architect's reported analyses

Factors affecting construction costs: Positive: Simple construction methods,

repetitiveness of design

Negative: Slow construction, lengthy building time; complex electronic, mechanical, and electrical systems


Factors affecting time schedule:

Positive: Simple construction methods,

repetitiveness of design

Negative: Slow responses and delivery

from vendors, suppliers



Jurisdiction official: James A. Lynaugh, Director, Department of Corrections

Contact: Warden Terry L. Terrell, Beto I Unit, P.O. Box 128, Tennessee Colony, TX 75861, 214-928-2417

Architects: Page Southerland Page, 606 West Avenue, Austin, TX 78701, 512-472-6721 Geren and Associates, Littlefield Building, Austin, TX 78701, 512-472-7799

Construction manager: None

**Groundbreaking:** January 1978 Finish date: December 1986 Construction time: 107 months Design capacity: 1,103 **Total cost:** \$31,215,000

Total annual operating costs: \$5,200,159

Category: New, independent facility

Facility type: State prison

Building configuration: Integrated structure; ladder, telephone pole

#### Costs

Total: \$31,215,000 Building only: \$31,215,000 Housing area: \$17,620,314 Housing per inmate: \$4,319

Housing per cell: \$8,637 Total per inmate: \$11,947 Total per GSF: \$38.27

Total annual operating costs: \$5,200,159

Perimeter: Single fence; alarm/detection

systems; razor wire on fence; towers;

#### **Dimensions**

Gross square feet/corrections: 815,628

Gross square feet/other: 0 Gross square feet/total: 815,628 Housing area square feet: 366,937 Gross square feet per inmate: 195 Size of cells: 53 square feet (double)

Net/gross square feet: 94%

### Construction type

Structural: Lead-bearing precast panels; cast-in-place concrete frame; precast concrete frame

Exterior walls: Precast panels; cast-in-

place concrete

Interior walls: Precast panels; cast-in-

place concrete; CMU block

Exterior surface/facade: Textured concrete

# Inmate cells

Medium: 0

Minimum: 0

**Security** 

patrols

Doors/material: Steel Doors/type: Sliding

Inmate security level:

Maximum: 100%

Doors/locking: Motor driven and

remote locking

Floor surface: Sealed concrete; monile

surfacing

Intercom: One-way to common areas HVAC: Heating/air circulation; steam

heat; gas heat

Plumbing: Stainless combination unit

Furniture: Steel

Fire protection: Manual alarm stations;

fire hose cabinets

# Inmate design capacity

Single occupancy: 0 Double occupancy: 4,080

Dorms: 0

Special housing: 108 General population: 4,080

Total: 1,103

#### **Current staff**

Full-time equivalent: Administration: 38 Security: 450

Programs/treatment: 628

Maintenance: 44 Total: 1,160

Current inmate/staff ratio: 2.92:1

### **Inmate housing areas**

Design: Linear, inside Cells per unit: 204 Inmates per unit: 408

Management type: Intermittent

surveillance

September 1987 population: 3,391 Facility commitment: State prisoners Means to handle crowding: Unknown

### **Construction process**


Finance method: State funds Contract method: Conventional Use of inmate labor: 100% Use of prefabrication: Extensive; concrete panel, jail steel, concrete columns, and beams

### Architects' reported analyses

Factors affecting construction costs: Positive: Prefab. components, factory assembly; repetitiveness of design Negative: Slow construction; difficult site conditions; government regulations and red tape; complex electronic and mechanical systems; 100% inmate labor

Factors affecting time schedule: Positive: Prefab. components, factory assembly; simple construction methods; advanced order of materials and hardware

Negative: Slow delivery from vendors; labor problems; 100% inmate labor; weather problems; government red tape



Jurisdiction official: James A. Lynaugh, Director, Department of Corrections

Contact: Warden Michael W. Countz, Beto II Unit, Route 2, Box 250, Palestine, TX 75801, 214-723-5074

Architects: Barnes, Landes, Goodman and Youngblood, 1600 West 38th Street, Suite 100, Austin, TX 78731, 512-451-8281 Dahl-Braden-PTM, Inc., Reverchon Plaza, 3500 Maple Avenue, LB 87, Suite 1100, Dallas, TX 75219, 214-520-0077

Construction manager/General contractor: B.F.W. Construction Company, P.O. Box 628, Temple, TX 76501, 817-778-8941

**Groundbreaking:** May 1981 Finish date: July 1984

Construction time: 38 months

Design capacity: 1,101 **Total cost:** \$13,177,520

Total annual operating costs: Unknown

Category: New, independent facility

Facility type: State prison Building configuration: Integrated

structure; ladder, telephone pole

#### Costs

Total: \$13,177,520

Building only: \$13,177,520 Housing area: \$9,224,264 Housing per inmate: \$8,735 Housing per cell: \$576,517 Total per inmate: \$11,969 Total per GSF: \$93.69

Total annual operating costs: Unknown

Perimeter: Single fence; alarm/detection

systems; razor wire on fence; towers;

#### **Dimensions**

Gross square feet/corrections: 140,650 Gross square feet/other: 0 Gross square feet/total: 140,650 Housing area square feet: 97,800

Gross square feet per inmate: 128 Size of cells: 3,640 square feet (dorms);

64 (spec. single) Net/gross square feet: 90%

panel" type construction

Interior walls: CMU block; jail steel Exterior surface/facade: Metal

#### patrols Inmate security level:

**Security** 

Maximum: 0 Medium: 0 Minimum: 100%

#### **Inmate cells**

Doors/material: Steel Doors/type: Swinging

Doors/locking: Manual locking

Floor surface: Sealed concrete; hard floor

wearing surface material

Intercom: One-way to common areas HVAC: Heating/air circulation; gas heat

Plumbing: China Furniture: Steel

Fire protection: Manual alarm stations;

fire hose reels

### **Construction type**

Structural: Steel frame

Exterior walls: Metal building "sandwich

#### Inmate design capacity

Single occupancy: 0 Double occupancy: 0 Dorms: 1,056 Special housing: 47 General population: 1,056

Total: 1,101

#### **Current staff**

Full-time equivalent: Administration: 10 Security: 199

> Programs/treatment: 40 Maintenance: 13

Total: 262

Current inmate/staff ratio: 3.92:1

### **Inmate housing areas**

Design: Dormitory style

Cells per unit: 1 Inmates per unit: 66

Management type: Intermittent

surveillance

January 1987 population: 1,026 Facility commitment: State prisoners Means to handle crowding: Court order

limits inmate capacity

### **Construction process**

Finance method: State funds

Contract method: Turn-key design and

Use of inmate labor: None

Use of prefabrication: Extensive; prefabri-

cated metal buildings

### Architects' reported analyses

Factors affecting construction costs: Positive: Prefab. components; simple const. methods; phased construction, fast track CM; favorable market; less


expensive materials

Negative: High labor costs; difficult site conditions; government red tape; complex electronic and mechanical


systems

Factors affecting time schedule: Positive: Prefab. components; repetitiveness of design; phased construction; advanced order of materials; coordination of design between parties

Negative: Slow delivery from vendors; weather problems; government red tape



MAIN BUILDING COMPLEX



### **Bexar County Juvenile Center**

Jurisdiction official: Dr. Tom Broussard, Chief Juvenile Probation Officer

Contact: Dr. Tom Broussard, Chief Juvenile Probation Officer, Bexar County Juvenile Center, 600 Mission Road, San Antonio,

TX 78210, 512-531-1060

Architects: Golemon & Rolfe Associates, Inc., 1600 Smith Street, 36th Floor, Houston, TX 77002, 713-655-9988

L. K. Travis & Associates, 1222 Main Street, Suite 407, San Antonio, TX 48212, 512-224-4041

Construction manager: None

**Groundbreaking:** September 1984

Finish date: January 1986 Construction time: 16 months **Design capacity:** 104 **Total cost:** \$5,827,817

**Total annual operating costs:** \$1,924,328

Category: New, independent facility
Facility type: Complex: juvenile detention facility, courts, probation
Building configuration: Integrated

structure; wheel, spoke or radial

**Costs** 

Total: \$5,827,817

Building only: \$5,500,000 Housing area: \$1,665,000 Housing per inmate: \$17,344 Housing per cell: \$17,344

Total per inmate: N/A (complex)

Total per GSF: \$92.58

Total annual operating costs: \$1,924,328

**Dimensions** 

Gross square feet/corrections: 40,515 Gross square feet/other: 22,435 Gross square feet/total: 62,950 Housing area square feet: 17,525 Gross square feet per inmate: 390 Size of cells: 75 square feet (single)

Net/gross square feet: 84%

**Inmate housing areas** 

Design: Module/pod Cells per unit: 12 Inmates per unit: 12

Management type: Remote surveillance;

direct supervision
June 1986 population: 65

Facility commitment: Juvenile detainees Means to handle crowding: Mattresses on

floor

**Security** 

Perimeter: Single fence; video camera

surveillance
Inmate security level:
Maximum: 0
Medium: 100%
Minimum: 0

**Construction type** 

Structural: Steel frame

Exterior walls: CMU block; architectural

precast

Interior walls: CMU block

Exterior surface/facade: Prefinished

concrete masonry units

**Construction process** 

Finance method: G.O. Bonds; Certificates

of Participation

Contract method: Conventional Use of inmate labor: None Use of prefabrication: None

**Inmate cells** 

Doors/material: Solid Doors/type: Swinging

Doors/locking: Remote and manual

locking

Floor surface: Carpet; vinyl tile Intercom: One-way to common areas HVAC: Air conditioning; heating/air

circulation; gas heat
Plumbing: Stainless steel
Furniture: Wood; vinyl/plastic
Fire protection: Smoke detectors and
sprinklers for cells and common areas;

manual alarm stations

Inmate design capacity

Single occupancy: 96 Double occupancy: 0

Dorms: 0

Special housing: 8 General population: 96

Total: 104

Architects' reported analyses

Factors affecting construction costs:

Positive: None

Negative: Complex electronic, mechani-

cal, and electrical systems Factors affecting time schedule:


Positive: None Negative: None

#### **Current staff**

Full-time equivalent:
Administration: 11
Security: 51
Programs/treatment: 0

Maintenance: 3 Total: 65

Current inmate/staff ratio: 1.00:1



### Brazoria County Sheriff's Department Detention Center II

Jurisdiction official: E.J. King, Sheriff

Contact: Captain Richard A. Dix, Brazoria County Sheriff's Department Detention Center II, P.O. Box 1046,

3602 County Road 45, Angleton, TX 77515, 409-849-8263

Architect: Brooks Association for Architecture and Planning, 2200 West Loop South, Suite 895, Houston, TX 77027, 713–871–0667

Construction manager: None

Groundbreaking: November 1983 Finish date: November 1985 Construction time: 24 months **Design capacity:** 252 **Total cost:** \$4,754,221

Total annual operating costs: \$1,253,632

Category: New, independent facility Facility type: County jail

Building configuration: Ladder, tele-

phone pole

#### Costs

Total: \$4,754,221

Building only: \$4,252,477

Housing area: Unknown

Housing per inmate: Unknown

Total per inmate: \$18,866

Total per inmate: \$18,866 Total per GSF: \$105.65

Total annual operating costs: \$1,253,632

# Dimensions

Gross square feet/corrections: 45,000 Gross square feet/other: 0 Gross square feet/total: 45,000 Housing area square feet: 25,000 Gross square feet per inmate: 179 Size of cells: 66 square feet (single) Net/gross square feet: Unknown

### **Construction type**

Structural: Reinforced load-bearing concrete block with steel bar joists and

concrete Exterior walls: Brick

Interior walls: Cast-in-place concrete;

CMU block

Exterior surface/facade: Brick; stucco;

paint

#### Security

Perimeter: Double fence; razor wire

between fences
Inmate security level:
Maximum: 0
Medium: 20%
Minimum: 80%

### **Inmate cells**

Doors/material: Steel Doors/type: Swinging

Doors/locking: Manual locking Floor surface: Sealed concrete; seamless

flooring

Intercom: Two-way to cells and common

areas

HVAC: Air conditioning; gas heat Plumbing: Stainless combination unit

Furniture: Steel

Fire protection: Smoke detectors for cells and common areas; manual alarm stations; smoke evacuation system

#### **Inmate design capacity**

Single occupancy: 12 Double occupancy: 0

Dorms: 240 Special housing: 0 General population: 252

Total: 252

#### **Current staff**

Full-time equivalent: Administration: 4 Security: 34

Programs/treatment: 4 Maintenance: 3

Total: 45

Current inmate/staff ratio: 3.58:1

### **Inmate housing areas**

Design: Linear, outside Cells per unit: 1 Inmates per unit: 24

Management type: Intermittent surveillance; remote surveillance; direct

supervision

June 1986 population: 161

Facility commitment: Local jail inmates Means to handle crowding: Unknown

#### **Construction process**

Finance method: G.O. Bonds Contract method: Conventional Use of inmate labor: None Use of prefabrication: None


### Architect's reported analyses

Factors affecting construction costs:
Positive: Simple construction methods,
repetitiveness of design; good
competition, favorable market; less
expensive materials and hardware
Negative: Government procedures,
regulations, and red tape; complex
electronic, mechanical, and electrical

Factors affecting time schedule: Positive: Simple construction methods, repetitiveness of design

Negative: Slow responses and delivery from vendors, suppliers; labor problems

systems



### **Chambers County Law Enforcement Center**

Jurisdiction official: C.E. "Chuck" Morris, Sheriff

Contact: Captain Jackie O. Wheat, Jail Administrator, Chambers County Law Enforcement Center, P.O. Box 998, 201 North Court,

Anahuac, TX 77514, 409-267-6761

Architect: Christopher Di Stefano & Associcates, Inc., 2500 Citywest Boulevard, #2010, Houston, TX 77042, 713-953-9032

Construction manager: None

**Groundbreaking:** December 1981

Finish date: May 1983

Construction time: 17 months

**Design capacity:** 75 **Total cost:** \$1,956,000

Total annual operating costs: \$1,200,000

Category: New, independent facility Facility type: Complex: county jail, law

enforcement, courts

Building configuration: Integrated

structure

**Costs** 

Total: \$1,956,000

Building only: \$1,932,000 Housing area: Unknown Housing per inmate: Unknown

Housing per cell: Unknown
Total per inmate: N/A (complex)

Total per GSF: \$72.44

Total annual operating costs: \$1,200,000

**Dimensions** 

Gross square feet/corrections: 19,500 Gross square feet/other: 7,500 Gross square feet/total: 27,000 Housing area square feet: 9,100 Gross square feet per inmate: 260 Size of cells: 55 square feet (gen. single);

81 (spec. single)

Net/gross square feet: Unknown

**Inmate housing areas** 

Design: Linear, inside Cells per unit: 8 Inmates per unit: 8

Management type: Intermittent surveil-

lance

September 1986 population: 52

Facility commitment: Local jail inmates Means to handle crowding: Mattresses on

floor

**Security** 

Perimeter: Building exterior; video

camera surveillance Inmate security level: Maximum: 75% Medium: 25% Construction type

Structural: Steel frame

Exterior walls: Architectural precast Interior walls: CMU block; steel in

detention area

Exterior surface/facade: Textured concrete

**Construction process** 

Finance method: G.O. Bonds Contract method: Conventional Use of inmate labor: None Use of prefabrication: None

**Inmate cells** 

Minimum: 0

Doors/material: Steel Doors/type: Sliding

Doors/locking: Motor driven and remote

locking

Floor surface: Sealed concrete

Intercom: Two-way to cells and common

areas

HVAC: Air conditioning; electric heat

Plumbing: Stainless steel

Furniture: Steel

Fire protection: Smoke detectors for cells and common areas; manual alarm stations; automatic smoke removal

system

Inmate design capacity

Single occupancy: 36 Double occupancy: 0

Dorms: 14

Special housing: 25 General population: 50

Total: 75

\_\_\_\_\_

Architect's reported analyses

Factors affecting construction costs: Positive: Simple construction methods, repetitiveness of design; good compe-

tition, favorable market

Negative: Slow construction, lengthy building time; complex electronic, mechanical, and electrical systems

Factors affecting time schedule:

Positive: Simple construction methods,

repetitiveness of design Negative: Labor problems


#### **Current staff**

Full-time equivalent: Administration: 8 Security: 26

Programs/treatment: 0 Maintenance: 1

Total: 35

Current inmate/staff ratio: 1.49:1



Jurisdiction official: James A. Lynaugh, Director, Department of Corrections

Contact: Warden J.E. Alford, Coffield Unit, Route 1, Box 150, Tennessee Colony, TX 75861, 214-928-2211

Architect: George Dahl, Architects & Engineers (no longer in business)

Construction manager/General contractor: Texas Department of Corrections, New Construction Department, P.O. Box 99,

N/C Huntsville, TX 77340, 409-295-6371

**Groundbreaking:** July 1965 **Finish date:** July 1979

Construction time: 168 months

**Design capacity:** 3,783 **Total cost:** \$12,641,281

Total annual operating costs: Unknown

Category: New, independent facility

Facility type: State prison

Building configuration: Wheel, spoke or

radial

#### Costs

Total: \$12,641,281 Building only: Unknown Housing area: \$10,239,438 Housing per inmate: \$3,801 Housing per cell: \$8,670 Total per inmate: \$3,342 Total per GSF: \$18.22

Total annual operating costs: Unknown

#### **Dimensions**

Gross square feet/corrections: 693,642 Gross square feet/other: 0 Gross square feet/total: 693,642 Housing area square feet: 564,879 Gross square feet per inmate: 183

Size of cells: 45 square feet (double); 9,000

(dorms)

Net/gross square feet: Unknown

### **Inmate housing areas**

Design: Linear, inside Cells per unit: 126 Inmates per unit: 252

Management type: Intermittent

surveillance

October 1987 population: 2,832
Facility commitment: State prisoners
Means to handle crowding: Unknown

### **Security**

Perimeter: Double fence; alarm/detection systems; razor wire on fences; towers;

patrols; camera surveillance

Inmate security level:
Maximum: 100%
Medium: 0
Minimum: 0

### **Construction type**

Structural: Cast-in-place concrete frame Exterior walls: Cast-in-place concrete;

brick

Interior walls: Cast-in-place concrete;

CMU block; brick

Exterior surface/facade: Brick

### **Construction process**

Finance method: State funds

Contract method: Conventional; inmate

labor

Use of inmate labor: 100%

Use of prefabrication: Limited; jail steel

#### **Inmate cells**

Doors/material: Steel Doors/type: Swinging

Doors/locking: Motor driven and remote

locking

Floor surface: Carpet; epoxy coating; sealed concrete; vinyl tile

Intercom: One-way to common areas HVAC: Heating/air circulation; steam

heat; gas heat

Plumbing: Stainless combination unit

Furniture: Steel

Fire protection: Manual alarm stations;

fire hose cabinets

#### **Inmate design capacity**

Single occupancy: 0
Double occupancy: 2,354

Dorms: 340

Special housing: 1,089 General population: 2,694

Total: 3,783

### **Current staff**

Full-time equivalent:

Administration: Unknown Security: Unknown

Programs/treatment: Unknown

Maintenance: Unknown Total: Unknown

Current inmate/staff ratio: Unknown

### Architect's reported analyses

Factors affecting construction costs: Positive: Prefab. components, factory assembly; repetitiveness of design;

inmate labor


Negative: Slow construction; difficult site conditions; government red tape; complex electronic and mechanical

systems

Factors affecting time schedule:
Positive: Use of prefab. components,
factory assembly; simple const.
methods; advanced order of materials;
coordination of design between parties

Negative: Slow delivery from vendors; labor problems; weather problems; complex electronic and mechanical

systems; inmate labor



Jurisdiction official: Walter Fellers, Sheriff

Contact: Walter Sumner, Jail Administrator, Comal County Jail, 3005 West San Antonio Street, New Braunfels, TX 78130,

512-625-9141

Architect: Christopher Di Stefano & Associates Inc., 2500 Citywest Boulevard, #2010, Houston, TX 77042, 713–953–9032

Construction manager: None

Groundbreaking: February 1984

Finish date: June 1985 Construction time: 16 months Design capacity: 184 **Total cost:** \$2,727,000

**Total annual operating costs:** \$764,461

Category: New, independent facility Facility type: Complex: county jail, law

enforcement

Building configuration: Integrated

structure

Costs

Total: \$2,727,000

Building only: \$2,706,000 Housing area: Unknown Housing per inmate: Unknown Housing per cell: Unknown

Total per inmate: N/A (complex) Total per GSF: \$68.15

Total annual operating costs: \$764,461

**Dimensions** 

Gross square feet/corrections: 31,912 Gross square feet/other: 8,100 Gross square feet/total: 40,012 Housing area square feet: 23,589 Gross square feet per inmate: 173 Size of cells: 66 square feet (single); 112 (spec. single); 305 (spec. dorms)

Net/gross square feet: Unknown

**Inmate housing areas** 

Design: Linear, inside Cells per unit: 7 Inmates per unit: 7

Management type: Intermittent

surveillance

September 1987 population: 126 Facility commitment: Local jail inmates Means to handle crowding: Unknown

Security

Perimeter: Building exterior; video

camera surveillance Inmate security level: Maximum: 34% Medium: 66% Minimum: 0

**Construction type** 

Structural: Steel frame

Inmate design capacity

Exterior walls: Architectural precast Interior walls: CMU block; steel in

detention area

Single occupancy: 47

Double occupancy: 0

Special housing: 39

General population: 145

Dorms: 96

Total: 184

Exterior surface/facade: Textured concrete

**Construction process** 

Finance method: Local funds; Certificates

of Obligation

Contract method: Conventional Use of inmate labor: None Use of prefabrication: None

**Inmate cells** 

Doors/material: Steel Doors/type: Sliding

Doors/locking: Motor driven and remote

locking

Floor surface: Epoxy coating

Intercom: Two-way to cells and common

HVAC: Air conditioning; electric heat Plumbing: Stainless combination unit

Furniture: Steel

Fire protection: Smoke detectors for cells and common areas; manual alarm stations; automatic smoke removal system

**Current staff** 

Full-time equivalent: Administration: 1 Security: 27

> Programs/treatment: 3 Maintenance: 0

Total: 31

Current inmate/staff ratio: 4.06:1

Architect's reported analyses

Factors affecting construction costs: Positive: Simple construction methods,

repetitiveness of design

Negative: Difficult site conditions; complex electronic, mechanical, and

electrical systems


Factors affecting time schedule:

Positive: Simple construction methods,

repetitiveness of design

Negative: Slow responses and delivery from vendors, suppliers; labor prob-

lems; weather problems



## **Darrington Unit (Addition/Remodel/Expansion)**

Jurisdiction official: James A. Lynaugh, Director, Department of Corrections

Contact: Warden Keith Price, Ph.D., Darrington Unit, Rt. 3, Box 59, Rosharon, TX 77583, 713-595-3465 Architect: W. Gene Williams & Associates, Inc., 3000 South Post Oak—1470, Houston, TX 77056, 713-440-4422

Construction manager: None

**Groundbreaking:** May 1980 Finish date: May 1987 Construction time: 84 months

Design capacity: 1,344 **Total cost:** \$11,030,238

Total annual operating costs: Unknown

Category: New, ancillary building; remodel/renovation; expansion Facility type: State prison

Building configuration: Ladder, tele-

phone pole

#### Costs

Total: \$11,030,238 Building only: Unknown Housing area: Unknown Housing per inmate: Unknown Housing per cell: Unknown Total per inmate: N/A (remodel)

Total per GSF: \$60.39

Total annual operating costs: Unknown

#### **Dimensions**

Gross square feet/corrections: 182,640

Gross square feet/other: 0 Gross square feet/total: 182,640 Housing area square feet: 113,030 Gross square feet per inmate: 136 Size of cells: 55 square feet (double); 2,665

(dorms)

Net/gross square feet: Unknown

#### **Security**

Perimeter: Double fence; alarm/ detection systems; razor wire on fences; towers; patrols; camera surveillance

Inmate security level: Maximum: 100% Medium: 0 Minimum: 0

### Construction type

Structural: Cast-in-place concrete frame Exterior walls: Cast-in-place concrete;

CMU block; brick

Interior walls: Cast-in-place concrete;

CMU block; brick

Exterior surface/facade: Brick; paint

#### **Inmate design capacity**

Single occupancy: 0 Double occupancy: 1,128

Dorms: 152 Special housing: 74 General population: 1,270

Total: 1,344

#### **Inmate cells**

Doors/material: Steel Doors/type: Sliding

Doors/locking: Motor driven and remote

locking

Floor surface: Sealed concrete; vinyl tile Intercom: One-way to common areas HVAC: Heating/air circulation; steam

heat; gas heat

Plumbing: Stainless combination unit

Furniture: Steel

Fire protection: Manual alarm stations;

fire hose cabinets

#### **Current staff**

Full-time equivalent: Administration: 50 Security: 428

Programs/treatment: 80

Maintenance: 45

Total: 603 (entire facility) Current inmate/staff ratio: 2.84:1

**Inmate housing areas** 

Design: Linear, inside Cells per unit: Unknown Inmates per unit: Unknown

Management type: Intermittent surveil-

lance

May 1987 population: 1,710

Facility commitment: State prisoners Means to handle crowding: Second bunk

permanently attached to wall

#### **Construction process**

Finance method: State funds Contract method: Conventional Use of inmate labor: 100%

Use of prefabrication: Limited; jail steel

fronts and doors

### **Architect's reported analyses**

Factors affecting construction costs: Positive: Prefab. components, factory assembly; repetitiveness of design;


inmate labor

Negative: Difficult site conditions; government procedures and red tape; complex electronic and mechanical

systems

Factors affecting time schedule: Positive: Use of prefab. components; simple const. methods; repetitiveness of design; advanced order of materials and hardware

Negative: Slow delivery from suppliers; government red tape; complex electronic and mechanical systems; inmate



### **Diagnostic Unit (Addition)**

Jurisdiction official: James A. Lynaugh, Director, Department of Corrections

Contact: Warden Billy R. Ware, Diagnostic Unit, P.O. Box 100, Huntsville, TX 77340, 409-295-5768 Architect: O'Neill, Conrad, Oppelt & Joneskell, Inc., 100 West Olmos, San Antonio, TX 78212, 512-829-1737 Construction manager: Lebco Construction Company, P.O. Box 771949, Houston, TX 77215, 713–781–9501

Groundbreaking: December 1984 Finish date: February 1986 Construction time: 14 months

**Design capacity: 448 Total cost:** \$7,224,119

Total annual operating costs: N/A

(addition)

Category: New, ancillary building

Facility type: State prison

Building configuration: Ladder, tele-

phone pole

#### Costs

Total: \$7,224,119

Building only: \$7,000,000 Housing area: \$3,500,000 Housing per inmate: \$7,812 Housing per cell: \$7,812 Total per inmate: \$16,125

Total per GSF: \$173.66

Total annual operating costs: N/A

(addition)

#### Security

Perimeter: Double fence; razor wire on

fences

Inmate security level: Maximum: 100% Medium: 0 Minimum: 0

#### **Inmate cells**

Doors/material: Steel Doors/type: Sliding

Doors/locking: Motor driven and remote

locking

Floor surface: Sealed concrete

Intercom: One-way to cells and common

HVAC: Heating/air circulation Plumbing: Stainless combination unit

Furniture: Steel

Intercom: One-way to cells and common

areas

Fire protection: Smoke detectors for common areas; manual alarm stations;

fire hose cabinets

#### **Dimensions**

Gross square feet/corrections: 41,600

Gross square feet/other: 0 Gross square feet/total: 41,600 Housing area square feet: 41,600 Gross square feet per inmate: 93 Size of cells: 72.6 square feet (double)

Net/gross square feet: 73%

### **Construction type**

Structural: Cast-in-place concrete frame

Exterior walls: Brick

Interior walls: Cast-in-place concrete,

precast concrete

Exterior surface/facade: Brick; paint

#### Inmate design capacity

Single occupancy: 0 Double occupancy: 448

Dorms: 0

Special housing: 0 General population: 448

Total: 448

#### Current staff

Full-time equivalent: Administration: 4 Security: 36

> Programs/treatment: 3 Maintenance: 0

Total: 43 (addition only) Current inmate/staff ratio: 9.6:1

### **Inmate housing areas**

Design: Linear, inside Cells per unit: Unknown Inmates per unit: Unknown Management type: Intermittent

surveillance

November 1987 population: 413 Facility commitment: State prisoners Means to handle crowding: Unknown

### **Construction process**

Finance method: State funds Contract method: Conventional Use of inmate labor: None

Use of prefabrication: Limited; jail steel

### Architect's reported analyses

Factors affecting construction costs: Positive: Prefabricated components,

factory assembly

Negative: Government procedures, regulations and red tape

Factors affecting time schedule:

Positive: Use of prefabricated components, factory assembly; advanced order of materials and hardware Negative: Slow responses and delivery

from vendors, suppliers

### Ellis II Unit (Phase I and II)

Jurisdiction official: James A. Lynaugh, Director, Department of Corrections

Contact: Warden Randy McLeod, Ellis II Unit, P.O. Box 6438, Huntsville, TX 77340, 409-291-4200 Architect: Lawrence D. White & Associates, Inc., P.O. Box 17148, Fort Worth, TX 76102, 817-332-7101 Construction manager: 3D International, 2700 South Post Oak Road, Houston, TX 77056, 713-622-5030

Groundbreaking: March 1983 Finish date: December 1984 Construction time: 21 months

Design capacity: 2,358 Total cost: \$43,941,497 Total annual operating costs: \$21,271,082 Category: New, independent facility Facility type: State prison Building configuration: Ladder, telephone pole

#### Costs

Total: \$43,941,497 Building only: \$39,963,266 Housing area: \$15,607,746 Housing per inmate: \$6,882 Housing per cell: \$13,763

Total per inmate: \$18,635 Total per GSF: \$99.65

Total annual operating costs:

\$21,271,082

#### **Security**

Perimeter: Single fence; razor wire on

fence; towers; patrols Inmate security level: Maximum: 100% Medium: 0 Minimum: 0

### **Inmate cells**

Doors/material: Steel Doors/type: Sliding

Doors/locking: Motor driven and remote locking Floor surface: Sealed concrete

Intercom: None

HVAC: Heating/air circulation Plumbing: Stainless combination

unit

Furniture: Steel

Fire protection: Manual alarm

stations

#### **Dimensions**

Gross square feet/corrections: 440,968

Gross square feet/other: 0 Gross square feet/total: 440,968 Housing area square feet: 204,480 Gross square feet per inmate: 187 Size of cells: 60 square feet (double);

78 (spec. single)

Net/gross square feet: Unknown

### **Construction type**

Structural: Unknown

Exterior walls: Architectural precast Interior walls: Precast panels; CMU block; gypsum board on metal studs Exterior surface/facade: Natural wall

#### Inmate design capacity

Single occupancy: 0 Double occupancy: 2,268

Dorms: 0

Special housing: 90 General population: 2,268

Total: 2,358

#### **Current staff**

Full-time equivalent: Administration: 47 Security: 478

Programs/treatment: 167 Maintenance: 12

Total: 704

Current inmate/staff ratio: 2.49:1

#### **Inmate housing areas**

Design: Linear, inside Cells per unit: 126 Inmates per unit: 252

Management type: Intermittent

surveillance

July 1986 population: 1,750

Facility commitment: Local jail inmates;

State prisoners

Means to handle crowding: Unknown

### **Construction process**

Finance method: State funds

Contract method: Conventional; construc-

tion management fast track Use of inmate labor: None

Use of prefabrication: Extensive; precast concrete panels, columns, and beams

## Architect's reported analyses

Factors affecting construction costs:
Positive: Prefabricated components,
factory assembly; simple construction
methods; fast track CM; good competi-

Negative: None

Factors affecting time schedule:
Positive: Use of prefabricated components, factory assembly; repetitiveness of design; phased construction; advanced order of materials and hardware; coordination of design between parties
Negative: Slow responses and delivery

from vendors, suppliers

tion, favorable market

### **Fayette County Detention Center**

Jurisdiction official: V.K. Koopmann, Sheriff

Contact: Sheriff V.K. Koopmann, Fayette County Detention Center, P.O. Box 112, La Grange, TX 78945, 409-968-5856

Architect: Edward Mattingly Associates, Inc., P.O. Box 576, La Grange, TX 78945, 409-968-5163

Construction manager: None

Groundbreaking: July 1984 Finish date: August 1985 Construction time: 13 months Design capacity: 61 Total cost: \$1,455,000

Total annual operating costs: Unknown

Category: New, independent facility Facility type: Complex: county jail, State Department of Public Safety;

Justice of Peace

Building configuration: Integrated

structure

#### **Costs**

Total: \$1,455,000

Building only: \$1,295,000 Housing area: \$700,000 Housing per inmate: \$11,475 Housing per cell: \$25,000

Total per inmate: N/A (complex)

Total per GSF: \$105.34

Total annual operating costs: Unknown

#### Security

Perimeter: Building exterior only

Inmate security level:
Maximum: 40%
Medium: 55%
Minimum: 5%

#### Inmate cells

Doors/material: Steel

Doors/type: Swinging; sliding

Doors/locking: Motor driven and remote

locking

Floor surface: Sealed concrete

Intercom: Two-way to cells and common

areas

HVAC: Air conditioning; small air cooled

split system heat pumps Plumbing: Stainless steel

Furniture: Steel

Fire protection: Smoke detectors for cells and common areas; manual alarm station; positive smoke removal system

#### **Dimensions**

Gross square feet/corrections: 13,812

Gross square feet/other: 0 Gross square feet/total: 13,812 Housing area square feet: 6,724 Gross square feet per inmate: 226 Size of cells: 65 square feet (single);

332 square feet (dorm) Net/gross square feet: 88%

### **Construction type**

Structural: Load bearing CMU Exterior walls: CMU block, fluted and

stucco

Interior walls: CMU block and steel Exterior surface/facade: Stucco; fluted

**CMU** 

### Inmate design capacity

Single occupancy: 18 Double occupancy: 4

Dorms: 8 Other: 16

Special housing: 15 General population: 46

Total: 61

#### **Current staff**

Full-time equivalent:

Administration: 4 Security: 15

Programs/treatment: 2 Maintenance: 0

Total: 21

Current inmate/staff ratio: 1.67:1

### **Inmate housing areas**

Design: Radial Cells per unit: 24 Inmates per unit: 46

Management type: Direct supervision;

remote surveillance October 1985 population: 35

Facility commitment: Local jail inmates; State prisoners; Federal prisoners Means to handle crowding: None

### **Construction process**

Finance method: Certificates of Obligation by county Contract method: Conventional Use of inmate labor: None Use of prefabrication: Limited, prefabricated steel detention

equipment

#### Architect's reported analyses

Factors affecting construction costs:
Positive: Use of prefabricated components
for cell areas; load bearing CMU
firewalls, steel joists, metal deck, B.U.
roof, insulated; good competition;
less expensive materials and hardware;
innovative planning

Negative: Complex electronic, mechanical, and electrical systems, and smoke removal system; strict local codes Factors affecting time schedule:

Positive: Steel modular single cells; simple construction methods; cooperation between county and State officials

Negative: Slow delivery of detention equipment; weather problems

### **Federal Correctional Institution**

Jurisdiction official: J. Michael Quinlan, Director, Bureau of Prisons

Contact: Warden Fred J. Stock, Federal Correctional Institution, Bastrop, TX 78602, 512–321–3903

Architect: CRS Group, 1111 West Loop Street, P.O. Box 22427, Houston, TX 77027, 713–552–2000

Construction manager: Robert E. McGee, Inc., 2608 Inwood Road, Dallas, TX 75235, 214–357–4381

Groundbreaking: September 1976

Finish date: August 1979 Construction time: 35 months **Design capacity:** 501 **Total cost:** \$10,950,000 **Total annual operating costs:** 

\$7,284,000

Category: New, independent facility Facility type: Federal prison

Building configuration: Campus style

#### **Costs**

Total: \$10,950,000

Building only: \$10,550,000 Housing area: Unknown Housing per inmate: Unknown Housing per cell: Unknown Total per inmate: \$21,856

Total per GSF: \$54.49

Total annual operating costs: \$7,284,000

Perimeter: Double fence; alarm/detection

#### **Dimensions**

Gross square feet/corrections: 200,950

Gross square feet/other: 0 Gross square feet/total: 200,950 Housing area square feet: Unknown Gross square feet per inmate: 401

Size of cells: Unknown Net/gross square feet: 74%

## **Construction type**

Structural: Load bearing reinforced masonry; wood trusses; concrete Exterior walls: Load bearing masonry Interior walls: Load bearing masonry Exterior surface/facade: Rough-saw cedar

#### Inmate design capacity

Single occupancy: 460 Double occupancy: 0

Dorms: 0

Special housing: 41 General population: 460

Total: 501

### **Inmate cells**

Security

system

Doors/material: Steel Doors/type: Swinging

Inmate security level:

Maximum: 0

Medium: 100% Minimum: 0

Doors/locking: Manual locking Floor surface: Vinyl tile

Intercom: None

**HVAC**: Air conditioning

Plumbing: China Furniture: Wood

Fire protection: Smoke detectors in

common areas

#### **Current staff**

Full-time equivalent: Administration: 4 Security: 107

Programs/treatment: 10 Maintenance: 19

Total: 140

Current inmate/staff ratio: 4.43:1

#### **Inmate housing areas**

Design: Module/pod Cells per unit: 112 Inmates per unit: 112

Management type: Direct supervision

October 1985 population: 620

Facility commitment: Federal prisoners Means to handle crowding: Bunk beds in

cell

#### **Construction process**

Finance method: Federal funds Contract method: Construction management fast track Use of inmate labor: None Use of prefabrication: None

#### Architect's reported analyses

Factors affecting construction costs:

Positive: Unknown Negative: Unknown

Factors affecting time schedule:

Positive: Unknown

Negative: Demolition of existing structures; site and utility work

### Ferguson Unit (Remodel/Expansion)

Jurisdiction official: James A. Lynaugh, Director, Department of Corrections

Contact: Charles A. Blanchette, Warden-II, Ferguson Unit, Route 2, Box 20, Midway, TX 75852, 409–348–3751 Architect: Lawrence D. White & Associates, Inc., P.O. Box 17148, Fort Worth, TX 76102, 817–877–0685

Construction manager: None

Groundbreaking: May 1981 Finish date: May 1985

Construction time: 48 months

**Design capacity:** 656 **Total cost:** \$32,000,000

Total annual operating costs: N/A

(expansion)

Category: Remodeling/renovation proj-

ect; expansion project Facility type: State prison

Building configuration: Ladder, tele-

phone pole

#### Costs

Total: \$32,000,000

Building only: \$32,000,000 Housing area: \$5,083,677 Housing per inmate: \$8,147 Housing per cell: \$16,294

Total per inmate: N/A (remodel)

Total per GSF: \$63.87

Total annual operating costs: N/A

(expansion)

#### **Security**

Perimeter: Double fence; razor wire on fences; towers; patrols; alarm/detection

systems

Inmate security level:
Maximum: 100%
Medium: 0
Minimum: 0

#### **Inmate cells**

Doors/material: Steel Doors/type: Sliding

Doors/locking: Motor driven and remote

locking

Floor surface: Sealed concrete

Intercom: None

HVAC: Heating/air circulation; other energy recycle unit; four 30,000 gal. water storage tanks, two solar heated Plumbing: Stainless combination unit

Furniture: Steel

Fire protection: Manual alarm stations

#### **Dimensions**

Gross square feet/corrections: 501,000

Gross square feet/other: 0 Gross square feet/total: 501,000 Housing area square feet: 181,871 Gross square feet per inmate: 764 Size of cells: 66.5 (double); 65 (spec.

single)

Net/gross square feet: Unknown

### **Construction type**

Structural: Cast-in-place concrete frame;

precast concrete frame

Exterior walls: CMU block; brick Interior walls: Precast panels; cast-in-place

concrete; CMU block; brick Exterior surface/facade: Brick

#### **Inmate design capacity**

Single occupancy: 0 Double occupancy: 624

Dorms: 0

Special housing: 32 General population: 624

Total: 656

#### **Current staff**

Full-time equivalent: Administration: N/A

Security: 20

Programs/treatment: N/A

Maintenance: N/A

Total: 20 (expansion only) Current inmate/staff ratio: 33:1

#### **Inmate housing areas**

Design: Linear, inside Cells per unit: 78 Inmates per unit: 156

Management type: Intermittent

surveillance

February 1987 population: 656 Facility commitment: State prisoners Means to handle crowding: Unknown

#### **Construction process**

Finance method: State funds

Contract method: Conventional design;

prisoner labor

Use of inmate labor: Extensive; inmates

acted as labor force

Use of prefabrication: Moderate; precast

panels for cells

### Architect's reported analyses

Factors affecting construction costs:
Positive: Prefabricated components,
factory assembly; simple construction
methods, repetitiveness of design;
owner furnished most building materials (i.e. brick, CMU, precast, jail
steel, bunks, toilet units, tables, and
chairs)


Negative: Slow construction due to prisoner labor

Factors affecting time schedule:

Positive: Simple construction methods,

repetitiveness of design

Negative: Slow responses and delivery from vendors, suppliers; labor problems



### Fort Bend County Jail

Jurisdiction official: Gus George, Sheriff

Contact: Captain Tom Sparkman, Fort Bend County Jail, 1410 Ransom Road, Richmond, TX 77469, 713-341-4611

Architect: Christopher Di Stefano & Associates, Inc., 2500 Citywest Boulevard, #2010, Houston, TX 77042, 713-953-9032

Construction manager: None

Groundbreaking: July 1979
Finish date: September 1980
Construction time: 14 months

Design capacity: 166
Total cost: \$3,139,000

Total annual operating costs:

\$1,421,613

Category: New, independent facility Facility type: Complex: county jail, law

enforcement, courts

Building configuration: Integrated

structure

#### Costs

Total: \$3,139,000

Building only: \$3,038,000

Housing area: Unknown
Housing per inmate: Unknown
Housing per cell: Unknown

Total per inmate: N/A (complex)

Total per GSF: \$61.50

Total annual operating costs:

\$1,421,613

#### Security

Perimeter: Building exterior only; video

camera surveillance Inmate security level: Maximum: 33% Medium: 67% Minimum: 0

#### **Inmate cells**

Doors/material: Steel Doors/type: Sliding

Doors/locking: Motor driven and remote

locking

Floor surface: Epoxy coating Intercom: Two-way to cells and common

areas

HVAC: Air conditioning; electric heat Plumbing: Stainless combination unit

Furniture: Steel

Fire protection: Smoke detectors for cells and common areas; manual alarm stations; automatic smoke removal

system

#### **Dimensions**

Gross square feet/corrections: 33,520 Gross square feet/other: 15,000 Gross square feet/total: 48,520 Housing area square feet: 20,848 Gross square feet per inmate: 202 Size of cells: 55 square feet (single);

75 (spec. single)

Net/gross square feet: Unknown

### **Construction type**

Structural: Steel frame

Exterior walls: Architectural precast Interior walls: CMU block; steel in

detention area

Exterior surface/facade: Textured concrete

### Inmate design capacity

Single occupancy: 56 Double occupancy: 0

Dorms: 44

Special housing: 66 General population: 100

Total: 166

#### **Current staff**

Full-time equivalent: Administration: 6 Security: 26

Programs/treatment: 4 Maintenance: 2

Total: 38 Current inmate/staff ratio: 4.13:1 Inmate housing areas

Design: Linear, inside Cells per unit: 16 Inmates per unit: 16

Management type: Intermittent

surveillance

September 1987 population: 157

Facility commitment: Local jail inmates Means to handle crowding: Unknown

### **Construction process**

Finance method: G.O. Bonds Contract method: Conventional Use of inmate labor: None Use of prefabrication: None

### Architect's reported analyses

Factors affecting construction costs:
Positive: Simple construction methods,

repetitiveness of design

Negative: Complex electronic, mechani-

cal, and electrical systems


Factors affecting time schedule:

Positive: Simple construction methods,

repetitiveness of design

Negative: Slow responses and delivery

from vendors, suppliers



### Fort Bend County Jail (Expansion)

Jurisdiction official: Gus George, Sheriff

Contact: Captain Tom Sparkman, Fort Bend County Jail, 1410 Ransom Road, Richmond, TX 77469, 713–341–4611 Architect: Christopher Di Stefano & Associates, Inc., 2500 Citywest Boulevard, #2010, Houston, TX 77042, 713–953–9032

Construction manager: None

Groundbreaking: July 1983 Finish date: August 1984 Construction time: 13 months **Design capacity:** 127 **Total cost:** \$1,140,000

Total annual operating costs: \$1,421,613

(entire facility)

Category: Expansion project Facility type: County jail

Building configuration: Integrated

structure

#### **Costs**

Total: \$1,140,000 Building only: \$1,105,000 Housing area: Unknown Housing per inmate: Unknown Housing per cell: Unknown Total per inmate: \$8,976

Total annual operating costs: \$1,421,613

(entire facility)

Total per GSF: \$68.47

### **Security**

Perimeter: Building exterior; video

camera surveillance Inmate security level: Maximum: 5% Medium: 95% Minimum: 0

#### **Inmate cells**

Doors/material: Steel Doors/type: Sliding

Doors/locking: Motor driven and remote

locking

Floor surface: Epoxy coating

Intercom: Two-way to cells and common

areas

HVAC: Air conditioning; electric heat Plumbing: Stainless combination unit

Furniture: Steel; concrete

Fire protection: Smoke detectors for cells and common areas; manual alarm stations; automatic smoke removal

system

#### **Dimensions**

Gross square feet/corrections: 16,650

Gross square feet/other: 0
Gross square feet/total: 16,650
Housing area square feet: 16,650
Gross square feet per inmate: 131
Size of cells: 75 square feet (spec. single)
Net/gross square feet: Unknown

### **Construction type**

Structural: Steel frame

Exterior walls: Architectural precast Interior walls: CMU block; steel in

detention area

Exterior surface/facade: Textured concrete

#### Inmate design capacity

Single occupancy: 0 Double occupancy: 0

Dorms: 124 Special housing: 3 General population: 124

Total: 127

#### **Current staff**

Full-time equivalent: Administration: 0 Security: 3

Programs/treatment: 0 Maintenance: 0

Total: 3 (expansion only)
Current inmate/staff ratio: 27.33:1

### Inmate housing areas

Design: Linear, inside Cells per unit: Unknown Inmates per unit: Unknown Management type: Intermittent

surveillance

September 1987 population: 82

Facility commitment: Local jail inmates Means to handle crowding: Unknown

### **Construction process**

Finance method: G.O. Bonds Contract method: Conventional Use of inmate labor: None Use of prefabrication: None

### Architect's reported analyses

Factors affecting construction costs: Positive: Simple construction methods,

repetitiveness of design

Negative: Complex electronic, mechanical, and electrical systems

Factors affecting time schedule:

Positive: Simple construction methods,

repetitiveness of design

Negative: Slow responses and delivery

from vendors, suppliers

### **Freeport Police and Courts Building**

Jurisdiction official: Charles G. Bankston, Chief of Police

Contact: Chief Charles G. Bankston, Freeport Police and Courts Building, 430 North Brazosport Boulevard, Freeport, TX 77541,

409-239-1211

Architect: Christopher Di Stefano & Associates, Inc., 2500 Citywest Boulevard, #2010, Houston, TX 77042, 713-953-9032

Construction manager: None

**Groundbreaking:** June 1978 **Finish date:** July 1979

**Construction time:** 13 months

**Design capacity:** 21 **Total cost:** \$710,400

Total annual operating costs: \$71,950

Category: New, independent facility Facility type: Complex: city jail, law

enforcement, courts

Building configuration: Integrated

structure

#### Costs

Total: \$710,400

Building only: \$680,000
Housing area: Unknown
Housing per inmate: Unknown
Housing per cell: Unknown
Total per inmate: N/A (complex)

Total per GSF: \$59.20

Total annual operating costs: \$71,950

#### **Dimensions**

Gross square feet/corrections: 3,300 Gross square feet/other: 8,700 Gross square feet/total: 12,000 Housing area square feet: 1,050 Gross square feet per inmate: 157 Size of cells: 63 square feet (single);

85 (double); 153 (dorm) Net/gross square feet: Unknown

### **Inmate housing areas**

Design: Linear, inside Cells per unit: 6 Inmates per unit: 6

Management type: Intermittent surveil-

lance

September 1986 population: 8

Facility commitment: Local jail inmates Means to handle crowding: Mattresses on

floor

#### Security

Perimeter: Building exterior; video

camera surveillance Inmate security level: Maximum: 100% Medium: 0 Minimum: 0

#### **Construction type**

Structural: Steel frame

Exterior walls: CMU block; brick Interior walls: CMU block Exterior surface/facade: Brick

### **Construction process**

Finance method: G.O. Bonds Contract method: Conventional Use of inmate labor: None Use of prefabrication: None

### **Inmate cells**

Doors/material: Steel Doors/type: Swinging

Doors/locking: Manual locking Floor surface: Sealed concrete

Intercom: None

HVAC: Air conditioning; electric heat Plumbing: Stainless combination unit

Furniture: Steel

Fire protection: Smoke detectors for common areas; manual alarm stations

#### Inmate design capacity

Single occupancy: 2 Double occupancy: 4

Dorms: 8

Special housing: 7 General population: 14

Total: 21

### **Current staff**

Full-time equivalent: Administration: 6

Security: 28

Programs/treatment: 0 Maintenance: 2

Total: 36

Current inmate/staff ratio: 0.22:1

#### Architect's reported analyses

Factors affecting construction costs:
Positive: Simple construction methods,
repetitiveness of design; good
competition, favorable market
Negative: Difficult site conditions
Factors affecting time schedule:

Positive: Simple construction methods,

repetitiveness of design

Negative: None

## Harris County Juvenile Detention Home (Remodel/Expansion)

Jurisdiction official: John A. Cocoros, Chief Probation Officer

Contact: James K. Martins, Director, Harris County Juvenile Detention Home, 3540 West Dallas, Houston TX 77019, 713-521-4232 Architect: Golemon & Rolfe Associates, Inc., 1600 Smith Street, 36th Floor, Houston, TX 77002, 713-655-9988

Construction manager: None

**Groundbreaking:** June 1982 Finish date: May 1985 Construction time: 35 months **Design capacity: 198 Total cost:** \$10,200,000

Total annual operating costs: \$4,110,657

Gross square feet/corrections: 72,600

Gross square feet/other: 37,400

Gross square feet/total: 110,000

Housing area square feet: 72,600

Gross square feet per inmate: 367

Size of cells: 82 square feet (single)

(entire facility)

**Dimensions** 

Category: Remodeling/renovation

project; expansion

Facility type: Complex: county jail, law enforcement, courts, juv. detention Building configuration: Int. structure; high rise; wheel, spoke or radial

#### **Costs**

Total: \$10,200,000 Building only: \$9,900,000 Housing area: \$6,500,000 Housing per inmate: \$32,828 Housing per cell: \$32,828

Total per inmate: N/A (complex)

Total per GSF: \$92.73

Total annual operating costs: \$4,110,657

(entire facility)

## Construction type

Structural: Steel frame; cast-in-place concrete frame

Exterior walls: Brick; preformed metal

Exterior surface/facade: Brick

# Security

Perimeter: Single fence; alarm/detection systems; video camera surveillance

Inmate security level: Maximum: 0 Medium: 100% Minimum: 0

#### **Inmate cells**

Doors/material: Solid; steel Doors/type: Swinging

Doors/locking: Remote locking; manual

locking

Floor surface: Linoleum; carpet; sealed

concrete

Intercom: Two-way to cells and common

areas

HVAC: Air conditioning; heating/air

circulation

Plumbing: Stainless steel

Furniture: Steel; wood; vinyl/plastic Fire protection: Smoke detectors and sprinklers for cells and common areas;

manual alarm stations

Net/gross square feet: 83%

Interior walls: CMU block

## Inmate design capacity

Single occupancy: 198 Double occupancy: 0

Dorms: 0

Special housing: 0 General population: 198

Total: 198

#### **Current staff**

Full-time equivalent: Administration: 18 Security: 68

Total: 115 (entire facility) Current inmate/staff ratio: 0.77:1

Programs/treatment: 19 Maintenance: 10

## **Inmate housing areas**

Design: Linear, outside; module/pod

Cells per unit: 30 Inmates per unit: 30

Management type: Intermittent surveil-

lance; remote surveillance July 1986 population: 88

Facility commitment: Juvenile detainees Means to handle crowding: Mattresses on

floor

## **Construction process**

Finance method: G.O. Bonds Contract method: Conventional Use of inmate labor: None Use of prefabrication: None

## Architect's reported analyses


Factors affecting construction costs: Positive: Simple construction methods, repetitiveness of design; good competition, favorable market Negative: Difficult site conditions: complex electronic and mechanical

Factors affecting time schedule: Positive: Simple construction methods, repetitiveness of design; coordination of design between parties

Negative: Slow responses and delivery from vendors; complex electronic and

mechanical systems

systems



## Hidalgo County Jail (Expansion)

Jurisdiction official: Brigido Marmelejo, Sheriff

Contact: Captain Juan Ramon Perez, Hidalgo County Jail, Courthouse, P.O. Box 359, Edinburg, TX 78539, 512–383–2751 Architect: Christopher Di Stefano & Associates, Inc., 2500 Citywest Boulevard, #2010, Houston, TX 77042, 713–953–9032

Construction manager: None

Groundbreaking: September 1984

Finish date: October 1985 Construction time: 13 months **Design capacity:** 184 **Total cost:** \$853,600

Total annual operating costs: N/A

(expansion)

Category: Expansion project Facility type: County jail

Building configuration: Integrated

structure

#### Costs

Total: \$853,600

Building only: \$849,000 Housing area: \$849,000 Housing per inmate: \$4,614 Housing per cell: \$106,125 Total per inmate: \$4,639 Total per GSF: \$61.94

Total annual operating costs: N/A

(expansion)

#### **Security**

Perimeter: Building exterior; video

camera surveillance Inmate security level: Maximum: 0 Medium: 100% Minimum: 0

#### **Inmate cells**

Doors/material: Steel Doors/type: Sliding

Doors/locking: Motor driven and remote

locking

Floor surface: Epoxy coating

Intercom: Two-way to cells and common

areas

HVAC: Air conditioning; electric heat Plumbing: Stainless combination unit

Furniture: Steel

Fire protection: Smoke detectors for cells and common areas; manual alarm stations; automatic smoke removal

system

### **Dimensions**

Gross square feet/corrections: 13,780

Gross square feet/other: 0 Gross square feet/total: 13,780 Housing area square feet: 13,780 Gross square feet per inmate: 75

Size of cells: Unknown

Net/gross square feet: Unknown

## **Construction type**

Structural: Steel frame Exterior walls: Brick Interior walls: CMU block

Exterior surface/facade: Brick veneer with

concrete block backup

#### **Inmate design capacity**

Single occupancy: 0 Double occupancy: 0

Dorms: 184 Special housing: 0 General population: 184

Total: 184

#### **Current staff**

Full-time equivalent: Administration: 2 Security: 14

Programs/treatment: 1
Maintenance: 5

Total: 22

Current inmate/staff ratio: 12.5:1

### **Inmate housing areas**

Design: Linear, inside Cells per unit: 2 Inmates per unit: 92

Management type: Intermittent

surveillance

September 1987 population: 275 (entire

facility)

Facility commitment: Local jail inmates Means to handle crowding: Unknown

## Construction process

Finance method: G.O. Bonds; Federal

funds; local funds

Contract method: Conventional Use of inmate labor: None Use of prefabrication: None

## Architect's reported analyses

Factors affecting construction costs: Positive: Simple construction methods, repetitiveness of design; good compe-


tition, favorable market

Negative: Difficult site conditions Factors affecting time schedule:

Positive: Simple construction methods,

repetitiveness of design

Negative: None



## **Hunt County Criminal Justice Center**

Jurisdiction official: Bobby Young, Sheriff

Contact: Sheriff Bobby Young, Hunt County Criminal Justice Center, 2700 Johnson Street, Greenville, TX 75401, 214–455–3502 Architect: Hobbs/Wiginton/Fawcett—Architects & Planners, Suite 2, 3511 Cedar Springs, Dallas, TX 75219, 214-855-5155 Construction manager: North Texas Construction Company, 4100 Frisco Road, Sherman, TX 75090, 214-893-4362

**Groundbreaking:** December 1982

Finish date: June 1984 Construction time: 19 months **Design capacity: 109 Total cost:** \$2,845,000 Total annual operating costs:

\$256,200 (jail only)

Category: New, independent facility Facility type: Complex: county jail, law

enforcement, courts

**Building configuration:** Courtyard

## **Costs**

Total: \$2,845,000 Building only: Unknown Housing area: \$2,000,000 Housing per inmate: \$27,027 Housing per cell: \$45,455

Total per inmate: N/A (complex)

Total per GSF: \$86.74

Total annual operating costs: \$256,200

(jail only)

## **Security**

Perimeter: Building exterior only

Inmate security level: Maximum: 30% Medium: 30% Minimum: 40%

## Inmate cells

Doors/material: Steel Doors/type: Sliding

Doors/locking: Remote locking only Floor surface: Sealed concrete Intercom: Two-way to cells **HVAC**: Air conditioning

Plumbing: Stainless combination unit

Furniture: Steel

Fire protection: Smoke detectors for cells

and common areas

### **Dimensions**

Gross square feet/corrections: 23,800 Gross square feet/other: 9,000 Gross square feet/total: 32,800 Housing area square feet: 18,680 Gross square feet per inmate: 218 Size of cells: 72 square feet (single) Net/gross square feet: 85%

## **Construction type**

Structural: Cast-in-place concrete frame

Exterior walls: Brick

Interior walls: Glazed structural tile Exterior surface/facade: Brick

#### Inmate design capacity

Single occupancy: 38 Double occupancy: 0

Dorms: 36

Special housing: 35 General population: 74

Total: 109

#### **Current staff**

Full-time equivalent: Administration: 1 Security: 14 Programs/treatment: 0

Maintenance: 1 Total: 16 (jail only)

Current inmate/staff ratio: 3.81:1

#### **Inmate housing areas**

Design: Courtyard Cells per unit: 8 Inmates per unit: 8

Management type: Remote surveillance

October 1985 population: 61

Facility commitment: Local jail inmates Means to handle crowding: None

necessary

#### **Construction process**

Finance method: G.O. Bonds Contract method: Construction

management

Use of inmate labor: None Use of prefabrication: None

## Architect's reported analyses

Factors affecting construction costs: Positive: Simple construction methods, repetitiveness of design; good competi-

tion, favorable market

Negative: Difficult site conditions; complex electronic, mechanical, and

electrical systems

Factors affecting time schedule:

Positive: None

Negative: Complex electronic,

mechanical, and electrical systems

## Jester Unit Number 3

Jurisdiction official: James A. Lynaugh, Director, Department of Corrections

Contact: Warden Morris M. Jones, Jester Unit Number 3, Route 2, Richmond, TX 77469, 713-491-1110

Architects: Barnes, Landes, Goodman, and Youngblood, 1600 West 38th Street, Suite 100, Austin, TX 78731, 512-451-8281

Dahl-Braden-PTM, Inc., 1800 North Market Street, Dallas, TX 75202, 214-748-1466

Construction manager/General contractor: Texas Department of Corrections, New Construction Department, P.O. Box 99,

N/C Huntsville, TX 77340, 409-295-6371

**Groundbreaking:** August 1981

Finish date: July 1984

Construction time: 35 months

Design capacity: 1,060 **Total cost:** \$14,044,570

Total annual operating costs: Unknown

Category: New, independent facility

Facility type: State prison

Building configuration: Integrated structure; ladder, telephone pole

#### **Costs**

Total: \$14,044,570 Building only: Unknown Housing area: \$9,831,199 Housing per inmate: \$10,327 Housing per cell: \$655,413

Total per inmate: \$13,250 Total per GSF: \$98.49

Total annual operating costs: Unknown

#### **Dimensions**

Gross square feet/corrections: 142,596

Gross square feet/other: 0 Gross square feet/total: 142,596 Housing area square feet: 99,217 Gross square feet per inmate: 135 Size of cells: 64 square feet (spec. single);

3,640 (dorms)

Net/gross square feet: 90%

## **Inmate housing areas**

Design: Dormitory style Cells per unit: Unknown Inmates per unit: 64

Management type: Remote surveillance September 1987 population: 990 Facility commitment: State prisoners Means to handle crowding: Unknown

## Security

Perimeter: Single fence; alarm/detection systems; razor wire on fence; towers;

patrols

Inmate security level: Maximum: 0 Medium: 0 Minimum: 100%

## **Construction type**

Structural: Steel frame

Exterior walls: "Sandwich panel" type

metal buildings

Interior walls: CMU block; jail steel Exterior surface/facade: Metal

## Construction process

Finance method: State funds

Contract method: Turn-key design and

build

Use of inmate labor: None

Use of prefabrication: Extensive; prefabricated metal buildings and jail steel

#### **Inmate cells**

Doors/material: Steel Doors/type: Swinging

Doors/locking: Remote locking Floor surface: Sealed concrete; hard floor

wearing surface material

Intercom: One-way to common areas HVAC: Heating/air circulation; gas heat

Plumbing: China Furniture: Steel

Fire protection: Manual alarm stations;

fire hose reels

### Inmate design capacity

Single occupancy: 0 Double occupancy: 0

Dorms: 952 Special housing: 108 General population: 952

Total: 1,060

#### **Current staff**

Full-time equivalent:

Administration: Unknown

Security: Unknown

Programs/treatment: Unknown Maintenance: Unknown

Total: Unknown

Current inmate/staff ratio: Unknown


## Architects' reported analyses

Factors affecting construction costs: Positive: Prefab. components; simple const. methods; phased const., fast track CM; favorable market; less expensive materials and hardware Negative: High labor costs; difficult site

conditions; government red tape; complex electronic and mechanical systems

Factors affecting time schedule: Positive: Use of prefab. components; repetitiveness of design; phased const., fast track CM; advanced order of materials; coordination of design Negative: Slow delivery from suppliers;

weather problems; government red tape



## **Katy Police Department**

Jurisdiction official: Pat Adams, Chief of Police

Contact: Chief Pat Adams, Katy Police Department, 5456 Franz Road, Katy, TX 77492, 713-391-9221

Architect: Christopher Di Stefano & Associates, Inc., 2500 Citywest Boulevard, #2010, Houston, TX 77042, 713-953-9032

Construction manager: None

Groundbreaking: June 1986 Finish date: April 1985 Construction time: 10 months **Design capacity:** 21 **Total cost:** \$800,000

Total annual operating costs: Unknown

Category: New, independent facility Facility type: Complex: city jail; law

enforcement

**Building configuration:** Integrated

structure

#### **Costs**

Total: \$800,000

Building only: \$751,000 Housing area: Unknown Housing per inmate: Unknown Housing per cell: Unknown

Total per inmate: N/A (complex)

Total per GSF: \$67.80

Total annual operating costs: Unknown

#### **Dimensions**

Gross square feet/corrections: 2,491 Gross square feet/other: 9,309 Gross square feet/total: 11,800 Housing area square feet: 1,728 Gross square feet per inmate: 119 Size of cells: 84 square feet (double); 192

(dorms)

Net/gross square feet: Unknown

## **Inmate housing areas**

Design: Linear, inside Cells per unit: 5 Inmates per unit: 12

Management type: Intermittent

surveillance

Current population: Unknown

Facility commitment: Local jail inmates Means to handle crowding: Unknown

## **Security**

Perimeter: Video camera surveillance

Inmate security level:
Maximum: 100%
Medium: 0
Minimum: 0

## **Construction type**

Structural: Steel frame

Exterior walls: Architectural precast

Interior walls: CMU block

Exterior surface/facade: Textured concrete

## **Construction process**

Finance method: G.O. Bonds; local funds Contract method: Conventional Use of inmate labor: None Use of prefabrication: None

#### **Inmate cells**

Doors/material: Steel Doors/type: Swinging

Doors/locking: Manual locking Floor surface: Epoxy coating

Intercom: Two-way to cells and common

areas

HVAC: Air conditioning; electric heat Plumbing: Stainless combination unit

Furniture: Steel

Fire protection: Smoke detectors for cells and common areas; manual alarm stations; smoke removal system

## Inmate design capacity

Single occupancy: 0 Double occupancy: 8

Dorms: 4

Special housing: 9 General population: 12

Total: 21

## Architect's reported analyses

Factors affecting construction costs:
Positive: Simple construction methods,
repetitiveness of design; good competi-

tion, favorable market Negative: None

ricgative. Indite

Factors affecting time schedule:

Positive: Simple construction methods,

repetitiveness of design

Negative: Slow responses and delivery from vendors, suppliers; labor problems

#### **Current staff**

Full-time equivalent:

Administration: Unknown Security: Unknown

Programs/treatment: Unknown Maintenance: Unknown

Total: Unknown

Current inmate/staff ratio: Unknown

## **Lew Sterrett Justice Center**

Jurisdiction official: Jim Bowles, Sheriff

Contact: Major Bob Knowles, Deputy Detentions Commander, Lew Sterrett Justice Center, 111 Commerce Street, Dallas,

TX 75202, 214-749-6857

Architects: Dahl-Braden-PTM, Inc., 1800 North Market Street, Dallas, TX 75202, 214-720-0077

Justice Center Architects, 1800 North Market Street, Dallas, TX 75202

Construction manager: McKee/Mays, A Joint Venture, 2708 Inwood Road, Dallas, TX 75235, 214-357-4381

**Groundbreaking:** March 1979 Finish date: November 1983 Construction time: 56 months Design capacity: 1,162 **Total cost:** \$52,585,999

**Total annual operating costs:** Unknown

Category: New, independent facility;

phased project (future)

Facility type: County jail; city jail Building configuration: High rise

#### Costs

Total: \$52,585,999 Building only: \$48,538,833 Housing area: \$30,768,404 Housing per inmate: \$27,109 Housing per cell: \$37,522

Total per inmate: \$45,255 Total per GSF: \$111.85

Total annual operating costs: Unknown

#### **Dimensions**

Gross square feet/corrections: 470,165 Gross square feet/other: 0 Gross square feet/total: 470,165 Housing area square feet: 275,135 Gross square feet per inmate: 405 Size of cells: 63 square feet (single)

Net/gross square feet: 85%

## **Inmate housing areas**

Design: Module/pod Cells per unit: Unknown Inmates per unit: Unknown

Management type: Intermittent surveil-

lance; remote surveillance July 1986 population: 856

Facility commitment: Local jail inmates;

State prisoners

Means to handle crowding: Unknown

## Security

Perimeter: Double fence; razor wire on fences; patrols; video camera

surveillance Inmate security level: Maximum: 100% Medium: 0 Minimum: 0

## **Construction type**

Structural: Cast-in-place concrete frame

Exterior walls: Brick

Interior walls: Structural glazed tile Exterior surface/facade: Brick

## **Construction process**

Finance method: Local funds; shared cost

from multiple jurisdictions

Contract method: Construction manage-

ment fast track

Use of inmate labor: None

Use of prefabrication: Limited; jail steel

#### Inmate cells

Doors/material: Steel Doors/type: Sliding

Doors/locking: Motor driven and remote locking; remote locking; manual

locking

Floor surface: Epoxy coating

Intercom: Two-way to cells and common

areas

**HVAC**: Air conditioning

Plumbing: Stainless combination unit Furniture: Steel; structural glazed tile Fire protection: Smoke detectors for cells and common areas; manual alarm stations; smoke evacuation system

## Inmate design capacity

Single occupancy: 800 Double occupancy: 0

Dorms: 335

Special housing: 27 General population: 1,135

Total: 1,162

## **Current staff**

Full-time equivalent: Administration: 19 Security: 464 Programs/treatment: 6

Maintenance: 0 **Total: 489** 

Current inmate/staff ratio: 1.75:1

#### Architects' reported analyses

Factors affecting construction costs: Positive: Phased construction, fast track construction management; good competition, favorable market Negative: Difficult site conditions; complex electronic, mechanical, and electrical systems


Factors affecting time schedule:

Positive: Coordination of design between

parties

Negative: Complex electronic, mechani-

cal, and electrical systems



## Liberty County Jail (Remodel/Expansion)

Jurisdiction official: Sheriff E.W. Applebe, Sheriff

Contact: Captain A. G. Cleaveland, Jail Administrator, Liberty County Jail, 2113 Sam Houston, Liberty, TX 77575, 409–336–8906 Architect: Christopher Di Stefano & Associates, Inc., 2500 Citywest Boulevard, #2010, Houston, TX 77042, 713–953–9032 Construction manager: None

Groundbreaking: March 1984 Finish date: April 1985 Construction time: 13 months Design capacity: 87 Total cost: \$1,610,000

Total annual operating costs: N/A

(expansion)

Category: Remodeling/renovation

project; expansion

Facility type: Complex: county jail, law

enforcement

Building configuration: Integrated

structure

#### **Costs**

Total: \$1,610,000 Building only: \$1,568,000 Housing area: Unknown Housing per inmate: Unknown Housing per cell: Unknown Total per inmate: N/A (complex)

Total per inmate: N/A (complex)
Total per GSF: \$106.48

10tal per GSF: \$100.48

Total annual operating costs: N/A

(expansion)

## **Security**

Perimeter: Building exterior; video camera surveillance

Inmate security level:
Maximum: 40%
Medium: 60%
Minimum: 0

#### Inmate cells

Doors/material: Steel Doors/type: Sliding

Doors/locking: Motor driven and remote

locking

Floor surface: Epoxy coating

Intercom: Two-way to cells and common

areas

HVAC: Air conditioning; electric heating Plumbing: Stainless combination unit

Furniture: Steel

Fire protection: Smoke detectors for cells and common areas; manual alarm stations; automatic smoke removal

system

#### **Dimensions**

Gross square feet/corrections: 12,820 Gross square feet/other: 2,300 Gross square feet/total: 15,120 Housing area square feet: 11,272 Gross square feet per inmate: 147 Size of cells: 55 square feet (gen. single);

63 (spec. single); 252 (dorm) Net/gross square feet: Unknown

## **Construction type**

Structural: Steel frame

Exterior walls: CMU block; brick Interior walls: CMU block; steel in

detention section

Exterior surface/facade: Brick

## Inmate design capacity

Single occupancy: 24 Double occupancy: 0

Dorms: 36

Special housing: 27 General population: 60

Total: 87

#### Current staff

Full-time equivalent: Administration: 1 Security: 11

Programs/treatment: 0

Maintenance: 1

Total: 13 (entire facility)
Current inmate/staff ratio: 6.46:1

### **Inmate housing areas**

Design: Linear, inside Cells per unit: 8 Inmates per unit: 8

Management type: Intermittent surveil-

lance

September 1986 population: 84

Facility commitment: Local jail inmates Means to handle crowding: Unknown

## **Construction process**

Finance method: G.O. Bonds; local funds Contract method: Conventional

Use of inmate labor: None Use of prefabrication: None

## Architect's reported analyses

Factors affecting construction costs: Positive: Simple construction methods,

repetitiveness of design

Negative: Slow construction, lengthy building time; complex electronic, mechanical, and electrical systems

Factors affecting time schedule:

Positive: Simple construction methods,

repetitiveness of design

Negative: Slow responses and delivery from vendors, suppliers; labor problems

## **Missouri City Police Department**

Jurisdiction official: L.C. Guillot, Chief of Police

Contact: Chief L.C. Guillot, Missouri City Police Department, 1522 Texas Parkway, Missouri City, TX 77459, 713-261-4200 Architect: Christopher Di Stefano & Associcates, Inc., 2500 Citywest Boulevard, #2010, Houston, TX 77042, 713-953-9032

Construction manager: None

Groundbreaking: April 1981 Finish date: January 1983 Construction time: 21 months **Design capacity:** 24 **Total cost:** \$835,000

Total annual operating costs: \$1,944,040

Category: New, independent facility Facility type: Complex: city jail, law

enforcement, courts

Building configuration: Integrated

structure

#### Costs

Total: \$835,000 Building only: \$818,000 Housing area: Unknown Housing per inmate: Unknown Housing per cell: Unknown

Total per inmate: N/A (complex)

Total per GSF: \$59.64

Total annual operating costs: \$1,944,040

#### **Dimensions**

Gross square feet/corrections: 3,100 Gross square feet/other: 10,900 Gross square feet/total: 14,000 Housing area square feet: 962 Gross square feet per inmate: 129 Size of cells: 99 square feet (gen. double); 198 (gen. dorm); 247 (spec. dorm) Net/gross square feet: Unknown

## Inmate housing areas

Design: Linear, inside Cells per unit: 5 Inmates per unit: 5

Management type: Intermittent surveillance by law enforcement personnel

October 1986 population: 0

Facility commitment: Local jail inmates
Means to handle crowding: Unknown

## Security

Perimeter: Building exterior; video

camera surveillance Inmate security level: Maximum: 100% Medium: 0 Minimum: 0

## **Construction type**

Structural: Steel frame

Exterior walls: CMU block; brick Interior walls: CMU block; steel in

detention area

Exterior surface/facade: Brick

## **Construction process**

Finance method: G.O. Bonds; local funds Contract method: Conventional Use of inmate labor: None Use of prefabrication: None

#### **Inmate cells**

Doors/material: Steel Doors/type: Swinging

Doors/locking: Manual locking Floor surface: Sealed concrete

Intercom: None

HVAC: Air conditioning; electric heat Plumbing: Stainless combination unit

Furniture: Steel

Fire protection: Smoke detectors for common areas; sprinklers for cells

## Inmate design capacity

Single occupancy: 0 Double occupancy: 8

Dorms: 4

Special housing: 12 General population: 12

Total: 24

Factors affecting construction costs: Positive: Simple construction methods, repetitiveness of design

Architect's reported analyses

Negative: None

Factors affecting time schedule:

Positive: Simple construction methods,

repetitiveness of design Negative: Weather problems

#### **Current staff**

Full-time equivalent: Administration: 16 Security: 30

Programs/treatment: 0 Maintenance: 0

Total: 46

Current inmate/staff ratio: N/A

## **Mountain View Unit (Addition)**

Jurisdiction official: James A. Lynaugh, Director, Department of Corrections

Contact: Warden Catherine Craig, Mountain View Unit, Route 4, Box 800, Gatesville, TX 76528, 817-865-7226

Architects: Gary/Parsons & Associates, P.O. Box 3657, Conroe, TX 77305, 409–273–4279

F.D. Freeman & Associates, 1712 North Frazier, Suite 206, Conroe, TX 77301, 409-760-3666

Construction manager: None

Groundbreaking: June 1984 Finish date: April 1986 Construction time: 22 months **Design capacity:** 96 **Total cost:** \$2,274,755

Total annual operating costs: N/A

(addition)

**Category:** New, ancillary building **Facility type:** State prison (women's

facility)

Building configuration: Campus style

#### **Costs**

Total: \$2,274,755

Building only: \$2,274,755 Housing area: \$1,088,676 Housing per inmate: \$11,340 Housing per cell: \$20,936 Total per inmate: \$23,695 Total per GSF: Unknown

Total annual operating costs: N/A

(addition)

## **Security**

Perimeter: Double fence; alarm/detection systems; razor wire on fences; towers; patrols; camera surveillance

Inmate security level:

Maximum: 100% Medium: 0 Minimum: 0

#### **Inmate cells**

Doors/material: Steel Doors/type: Sliding

Doors/locking: Motor driven and remote

locking

Floor surface: Carpet; epoxy coating;

sealed concrete; vinyl tile

Intercom: One-way to common areas HVAC: Heating/air circulation Plumbing: Stainless combination unit

Furniture: Steel

Fire protection: Manual alarm stations;

fire hose cabinets

#### **Dimensions**

Gross square feet/corrections: Unknown Gross square feet/other: Unknown Gross square feet/total: Unknown Housing area square feet: Unknown Gross square feet per inmate: Unknown Size of cells: 100 square feet (single)

Net/gross square feet: Unknown

## **Construction type**

Structural: Cast-in-place concrete frame Exterior walls: Precast panels; cast-inplace concrete; CMU block; brick Interior walls: Precast panels; cast-in-place

concrete; CMU block; brick Exterior surface/facade: Brick

## Inmate design capacity

Single occupancy: 8 Double occupancy: 88

Dorms: 0

Special housing: 0 General population: 96

Total: 96

#### **Current staff**

Full-time equivalent:
Administration: N/A

Security: 24

Programs/treatment: N/A Maintenance: N/A Total: 24 (addition only) Current inmate/staff ratio: 4.00:1

## **Inmate housing areas**

Design: Linear, outside Cells per unit: 52 Inmates per unit: 96

Management type: Direct supervision

October 1987 population: 96
Facility commitment: Female State prisoners

Means to handle crowding: Unknown

## **Construction process**

Finance method: State funds

Contract method: Conventional; inmate labor—Texas Dept. of Corrections

Use of inmate labor: 100%

Use of prefabrication: Limited; jail steel


## Architects' reported analyses

Factors affecting construction costs:
Positive: Simple construction methods,
repetitiveness of design; inmate labor
Negative: Government procedures,
regulations, and red tape; complex
electronic and mechanical systems

Factors affecting time schedule: Positive: Use of prefabricated components; simple construction methods; advanced order of materials and

hardware
Negative: Slow delivery from suppliers;
labor problems; weather problems;
government procedures, regulations,

and red tape



## **Orange County Jail (Addition)**

Jurisdiction official: James Wade, Sheriff

Contact: Captain Wayne Dial, Orange County Jail, 115 South Border Street, P.O. Box 1461, Orange, TX 77630, 409-883-2612 Architect: Christopher Di Stefano & Associates, Inc., 2500 Citywest Boulevard, #2010, Houston, TX 77042, 713-953-9032

Construction manager: Unknown

Groundbreaking: March 1984

Finish date: May 1985

Construction time: 14 months

Design capacity: 64 **Total cost:** \$1,800,000

Total annual operating costs: N/A

(addition)

Category: New, ancillary building;

phased project (future)

Facility type: Complex: county jail, law

enforcement

Building configuration: Integ. structure

#### **Costs**

Total: \$1,800,000

Building only: \$1,758,000 Housing area: Unknown

Housing per inmate: Unknown Housing per cell: Unknown

Total per inmate: N/A (complex)

Total per GSF: \$59.67

Total annual operating costs: N/A (addi-

tion)

## **Security**

Perimeter: Building exterior only

Inmate security level: Maximum: 34% Medium: 66%

## **Dimensions**

Gross square feet/corrections: 17,160 Gross square feet/other: 13,008 Gross square feet/total: 30,168 Housing area square feet: 16,060 Gross square feet per inmate: 268 Size of cells: 55.5 square feet (single)

Net/gross square feet: Unknown

## **Inmate housing areas**

Design: Linear, inside Cells per unit: 8 Inmates per unit: 8

Management type: Intermittent surveil-

lance

September 1987 population: 55

Facility commitment: Local jail inmates Means to handle crowding: Unknown

Minimum: 0

## **Construction type**

Structural: Steel frame Exterior walls: CMU block Interior walls: CMU block; steel in

Inmate design capacity

Single occupancy: 16

Double occupancy: 0

Special housing: 18

General population: 46

Dorms: 30

Total: 64

detention area

Exterior surface/facade: CMU (textured)

## **Construction process**

Finance method: G.O. Bonds: local funds Contract method: Conventional

Use of inmate labor: None Use of prefabrication: None

## **Inmate cells**

Doors/material: Steel Doors/type: Sliding

Doors/locking: Motor driven and remote

locking

Floor surface: Epoxy coating

Intercom: Two-way to cells and common

HVAC: Air conditioning; electric heat Plumbing: Stainless combination unit

Furniture: Steel

Fire protection: Smoke detectors for cells and common areas; manual alarm stations; automatic smoke removal system

**Current staff** 

Full-time equivalent: Administration: 3 Security: 16

Programs/treatment: 3 Maintenance: 3

Total: 25 (entire facility) Current inmate/staff ratio: 2.2:1

## Architect's reported analyses

Factors affecting construction costs: Positive: Simple construction methods,

repetitiveness of design


Negative: High labor costs; government procedures, regulations, and red tape; complex electronic, mechanical, and

electrical systems

Factors affecting time schedule: Positive: Simple construction methods,

repetitiveness of design

Negative: Slow responses and delivery from vendors, suppliers; labor problems



## Pearland Public Safety Building

Jurisdiction official: Robert Riemenschneider, Chief of Police

Contact: Chief Robert Riemenschneider, Pearland Public Safety Building, 2703 Veterans Drive, Pearland, TX 77584, 713–485–4361 Architect: Christopher Di Stefano & Associates, Inc., 2500 Citywest Boulevard, #2010, Houston, TX 77042, 713-953-9032

Construction manager: None

**Groundbreaking:** July 1985 Finish date: May 1986

**Construction time:** 10 months

**Design capacity: 36 Total cost:** \$1,360,000

Total annual operating costs: Unknown

Category: New, independent facility Facility type: Complex: city jail, law enforcement, courts, E.O.C. **Building configuration:** Integrated

structure

Costs

Total: \$1,360,000

Building only: \$1,309,000 Housing area: Unknown Housing per inmate: Unknown Housing per cell: Unknown

Total per inmate: N/A (complex)

Total per GSF: \$70.28

Total annual operating costs: Unknown

**Dimensions** 

Gross square feet/corrections: 5,215 Gross square feet/other: 14,135 Gross square feet/total: 19,350 Housing area square feet: 3,158 Gross square feet per inmate: 145 Size of cells: 99 square feet (double); 192 (gen. dorms); 312 (spec. dorms)

Net/gross square feet: Unknown

**Inmate housing areas** 

Design: Linear, inside Cells per unit: 3 Inmates per unit: 8

Management type: Intermittent

surveillance

September 1987 population: 2

Facility commitment: Local jail inmates Means to handle crowding: Unknown

Security

Perimeter: Video camera surveillance

Inmate security level: Maximum: 100% Medium: 0 Minimum: 0

**Construction type** 

Structural: Steel frame Exterior walls: CMU block

Interior walls: CMU block: steel in

detention areas

Exterior surface/facade: Textured CMU

**Construction process** 

Finance method: G.O. Bonds Contract method: Conventional Use of inmate labor: None Use of prefabrication: None

**Inmate cells** 

Doors/material: Steel Doors/type: Swinging

Doors/locking: Manual locking Floor surface: Epoxy coating

Intercom: Two-way to cells and common

areas

HVAC: Air conditioning; electric heat Plumbing: Stainless combination unit

Furniture: Steel

Fire protection: Smoke detectors for cells and common areas; manual alarm stations; smoke removal system

**Inmate design capacity** 

Single occupancy: 0 Double occupancy: 10

Dorms: 8

Special housing: 18 General population: 18

Total: 36

Architect's reported analyses

Factors affecting construction costs: Positive: Simple construction methods, repetitiveness of design; good compe-

tition, favorable market

Negative: None

Factors affecting time schedule:

Positive: Simple construction methods, repetitiveness of design; coordination of

design between parties

Negative: None

## **Current staff**

Full-time equivalent:


Administration: Unknown Security: Unknown

Programs/treatment: Unknown

Maintenance: Unknown

Total: Unknown

Current inmate/staff ratio: Unknown



## San Patricio County Sheriff's Department

Jurisdiction official: Wayne Hitt, Sheriff

Contact: Sheriff Wayne Hitt, San Patricio County Sheriff's Department, 300 North Racal, Sinton, TX 78387, 512–364–2251 Architect: Christopher Di Stefano & Associates, Inc., 2500 Citywest Boulevard, #2010, Houston, TX 77042, 713–953–9032

Construction manager: None

Groundbreaking: May 1980 Finish date: April 1982 Construction time: 23 months **Design capacity:** 132 **Total cost:** \$2,229,000

**Total annual operating costs:** \$345,500

Category: New, independent facility Facility type: Complex: county jail, law

enforcement, courts

Building configuration: Integrated

structure

Costs

Total: \$2,229,000

Building only: \$2,165,000 Housing area: Unknown Housing per inmate: Unknown Housing per cell: Unknown

Total per inmate: N/A (complex)

Total per GSF: \$66.29

Total annual operating costs: \$345,500

**Security** 

Perimeter: Building exterior; video

camera surveillance Inmate security level: Maximum: 55% Medium: 45% Minimum: 0

**Inmate cells** 

Doors/material: Steel Doors/type: Sliding

Doors/locking: Motor driven and remote

locking

Floor surface: Sealed concrete

Intercom: Two-way to cells and common

areas

HVAC: Air conditioning; electric heat Plumbing: Stainless combination unit

Furniture: Steel

Fire protection: Smoke detectors for cells and common areas; manual alarm stations; automatic smoke removal

system

**Dimensions** 

Gross square feet/corrections: 24,100 Gross square feet/other: 9,527 Gross square feet/total: 33,627 Housing area square feet: 14,260 Gross square feet per inmate: 183 Size of cells: 56 square feet (gen. single);

91 (spec. single)

Net/gross square feet: Unknown

**Construction type** 

Structural: Steel frame

Exterior walls: Concrete site cast tilt wall

panels

Interior walls: CMU block; steel in

detention area

Exterior surface/facade: Textured concrete

Inmate design capacity

Single occupancy: 46 Double occupancy: 0

Dorms: 30

Special housing: 56 General population: 76

Total: 132

**Current staff** 

Full-time equivalent: Administration: 2 Security: 13

Programs/treatment: 1 Maintenance: 0

Total: 16

Current inmate/staff ratio: 3.38:1

**Inmate housing areas** 

Design: Linear, inside Cells per unit: 8 Inmates per unit: 8

Management type: Intermittent surveil-

lance

September 1986 population: 54

Facility commitment: Local jail inmates Means to handle crowding: Mattresses on

floor

**Construction process** 

Finance method: G.O. Bonds; local funds

Contract method: Conventional Use of inmate labor: None

Use of prefabrication: Limited; tilt-up

construction

Architect's reported analyses

Factors affecting construction costs: Positive: Simple construction methods,

repetitiveness of design

Negative: None

Factors affecting time schedule:

Positive: Simple construction methods,

repetitiveness of design Negative: Labor problems

## **Smith County Jail**

Jurisdiction official: J.B. Smith, Sheriff

Contact: Ron Scott, Jail Administrator, Smith County Jail, Tyler, TX 75701, 214-593-8434 Architect: Page Southerland Page, P.O. Box 2004, Austin, TX 78768, 512-472-6721

Construction manager: None

**Groundbreaking:** November 1983

Finish date: January 1986 Construction time: 26 months Design capacity: 264 **Total cost:** \$8,000,000

Total annual operating costs:

\$1,562,463

Category: New, independent facility

Facility type: County jail

**Building configuration:** Integrated

structure

#### **Costs**

Total: \$8,000,000

Building only: \$7,200,000 Housing area: Unknown Housing per inmate: Unknown Housing per cell: Unknown

Total per inmate: \$30,303 Total per GSF: \$93.79

Total annual operating costs: \$1,562,463

Doors/locking: Motor driven and remote

Floor surface: Sealed concrete; vinyl tile

Plumbing: Stainless combination unit

Fire protection: Smoke detectors for cells

and common areas; sprinklers for

common areas: manual alarm stations

## **Dimensions**

Gross square feet/corrections: 85,300

Gross square feet/other: 0 Gross square feet/total: 85,300 Housing area square feet: 51,400 Gross square feet per inmate: 323 Size of cells: 77 square feet (single);

123 (double); 790 (dorm) Net/gross square feet: Unknown

# **Construction type**

Structural: Cast-in-place concrete frame Exterior walls: Cast-in-place concrete Interior walls: Cast-in-place concrete;

CMU block; brick

Exterior surface/facade: Brick

## **Inmate housing areas**

Design: Module/pod Cells per unit: 132 Inmates per unit: 132

Management type: Remote surveillance

October 1985 population: N/A

Facility commitment: Local jail inmates Means to handle crowding: Cots in dorm

## **Security**

Inmate cells

locking

Furniture: Steel

Doors/material: Steel

Intercom: Two-way to cells

HVAC: Air conditioning; boiler

Doors/type: Sliding

Perimeter: Building exterior Inmate security level: Maximum: 100% Medium: 0 Minimum: 0

Single occupancy: 108 Double occupancy: 60

Special housing: 24 General population: 240

Total: 264

#### Inmate design capacity

Dorms: 72

#### Current staff

Full-time equivalent: Administration: 8 Security: 55

> Programs/treatment: Volunteers Maintenance: County staff

Total: 63

Current inmate/staff ratio: N/A

#### **Construction process**

Finance method: G.O. Bonds Contract method: Conventional Use of inmate labor: None

Use of prefabrication: Limited; detention

equipment

## Architect's reported analyses


Factors affecting construction costs: Positive: Simple construction methods, repetitiveness of design; good competition, favorable market Negative: Slow construction; difficult site conditions; complex electronic, mechanical, and electrical systems

Factors affecting time schedule:

Positive: Simple construction methods,

repetitiveness of design

Negative: Slow responses and delivery from vendors, suppliers; weather problems; complex electronic, mechanical, and electrical systems



Jurisdiction official: Eugenio Falcon, Sheriff

Contact: Ramon Reymundo, Chief Jailer, Starr County Jail, Rio Grande City, TX 78582, 512-487-4552

Architect: Christopher Di Stefano & Associates, Inc., 2500 Citywest Boulevard, #2010, Houston, TX 77042, 713-953-9032

Construction manager: None

Groundbreaking: November 1985

Finish date: October 1986 Construction time: 11 months **Design capacity:** 123 **Total cost:** \$1,413,000

Total annual operating costs: Unknown

Category: New, independent facility

Facility type: County jail

Building configuration: Integrated

structure

#### Costs

Total: \$1,413,000

Building only: \$1,385,000 Housing area: Unknown Housing per inmate: Unknown Housing per cell: Unknown Total per inmate: \$11,488

Total per GSF: \$76.38

Total annual operating costs: Unknown

### **Dimensions**

Gross square feet/corrections: 18,500

Gross square feet/other: 0 Gross square feet/total: 18,500 Housing area square feet: 16,300 Gross square feet per inmate: 150 Size of cells: 75 square feet (gen. single);

200 (spec. dorms)

Net/gross square feet: Unknown

## **Inmate housing areas**

Design: Linear, inside Cells per unit: 1 Inmates per unit: 24

Management type: Remote surveillance

Means to handle crowding: Unknown

September 1987 population: 70 Facility commitment: Local jail inmates

## Security

Perimeter: Building exterior; video

camera surveillance Inmate security level: Maximum: 10% Medium: 90% Minimum: 0

## **Construction type**

Structural: Steel frame Exterior walls: Precast panels Interior walls: CMU block

Exterior surface/facade: Textured concrete

#### **Construction process**

Finance method: Federal funds; local funds; Certificates of Obligation Contract method: Conventional Use of inmate labor: None

Use of prefabrication: Limited; exterior

precast panels

## **Inmate cells**

Doors/material: Steel Doors/type: Sliding

Doors/locking: Motor driven and remote

locking

Floor surface: Epoxy coating

Intercom: Two-way to cells and common

areas

HVAC: Air conditioning; electric heat Plumbing: Stainless combination unit

Furniture: Steel

Fire protection: Smoke detectors for cells and common areas; manual alarm stations; automatic smoke removal

system

## Inmate design capacity

Single occupancy: 13 Double occupancy: 0 Dorms: 104 Special housing: 6 General population: 117

Total: 123

#### **Current staff**

Full-time equivalent: Administration: 1 Security: 17

> Programs/treatment: 1 Maintenance: 2 Total: 21

Current inmate/staff ratio: 3.33:1

## Architect's reported analyses

Factors affecting construction costs: Positive: Simple construction methods, repetitiveness of design; good compe-

tition, favorable market

Negative: Complex electronic, mechanical, and electrical systems

Factors affecting time schedule:

Positive: Simple construction methods,

repetitiveness of design

Negative: None

## TDC Hospital at Galveston

Jurisdiction official: James A. Lynaugh, Director, Department of Corrections

Contact: Warden Frederick Becker, TDC Hospital at Galveston, P.O. Box 48, Substation #1, Galveston, TX 77550, 409–761–2875

Architect: Jesson & Associates, 700 American Bank Tower, Austin, TX 78701, 512–478–7437 Construction manager: University of Texas, 6000 Strand, Galveston, TX 77550, 409–765–1588

Groundbreaking: March 1978 Finish date: June 1985

Construction time: 87 months

Design capacity: 144 **Total cost:** \$38,989,679

Total annual operating costs: \$7,366,500

Category: New, independent facility Facility type: State prison hospital Building configuration: High rise

#### **Costs**

Total: \$38,989,679 Building only: Unknown Housing area: Unknown Housing per inmate: Unknown Housing per cell: Unknown Total per inmate: \$270,762 Total per GSF: \$185.14

Total annual operating costs: \$7,366,500

## Security

Perimeter: Patrols; video camera

surveillance Inmate security level: Maximum: 100% Medium: 0 Minimum: 0

#### **Inmate cells**

Doors/material: Steel Doors/type: Swinging

Doors/locking: Manual locking

Floor surface: Carpet; sealed concrete;

vinyl tile

Intercom: Two-way to common areas HVAC: Air conditioning; steam heat; gas heat

Plumbing: Stainless steel Furniture: Steel; wood

Intercom: Two-way to common areas Fire protection: Smoke detectors and sprinklers for rooms; sprinklers for common areas; manual alarm stations

## **Dimensions**

Gross square feet/corrections: 210,600

Gross square feet/other: 0 Gross square feet/total: 210,600 Housing area square feet: 52,650 Gross square feet per inmate: 1,463 Size of cells: 264 square feet (double) Net/gross square feet: Unknown

## **Construction type**

Structural: Load-bearing precast panels; steel frame; cast-in-place concrete frame Exterior walls: Precast panels; cast-inplace concrete; CMU block; brick Interior walls: Precast panels; cast-in-place concrete; CMU block; brick

Exterior surface/facade: Brick; stucco;

paint; textured concrete

#### Inmate design capacity

Single occupancy: 0 Double occupancy: 144

Dorms: 0

Special housing: 0 General population: 144

Total: 144

#### **Current staff**

Full-time equivalent: Administration: 22 Security: 186

Programs/treatment: 8 Maintenance: 2 Total: 218

Current inmate/staff ratio: 0.50:1

## **Inmate housing areas**

Design: Rooms on outside walls, direct

light to rooms Cells per unit: 12 Inmates per unit: 24

Management type: Intermittent

surveillance

April 1987 population: 110

Facility commitment: State prisoners Means to handle crowding: Unknown

## **Construction process**

Finance method: State funds

Contract method: Coordinated by the

University of Texas Use of inmate labor: None Use of prefabrication: Extensive

## Architect's reported analyses

Factors affecting construction costs: Positive: Prefabricated components,


factory assembly

Negative: Slow construction; high labor cost; difficult site conditions; government procedures and red tape; complex electronic and mechanical systems

Factors affecting time schedule:

Positive: Use of prefabricated components, factory assembly; simple construction methods, repetitiveness of design; phased const., fast track CM

Negative: Slow delivery from suppliers; labor problems; weather problems; government red tape; complex electronic and mechanical systems



## Victoria County Jail

Jurisdiction official: Dalton G. Meyer, Sheriff

Contact: Captain Richard Romano, Victoria County Jail, 101 North Glass, Victoria, TX 77901, 512-575-0651

Architect: Christopher Di Stefano & Associates, Inc., 2500 Citywest Boulevard, #2010, Houston, TX 77042, 713-953-9032

Construction manager: None

Groundbreaking: October 1982 Finish date: October 1984 Construction time: 24 months **Design capacity:** 132 **Total cost:** \$5,465,000

Total annual operating costs: Unknown

Category: New, ancillary building;

phased project (future)

Facility type: Complex: county jail, law

enforcement

Building configuration: Integ. structure

#### **Costs**

Total: \$5,465,000

Building only: \$5,234,250 Housing area: Unknown Housing per inmate: Unknown Housing per cell: Unknown Total per inmate: N/A (complex)

Total per GSF: \$45.90

Total annual operating costs: Unknown

## **Dimensions**

Gross square feet/corrections: 37,590 Gross square feet/other: 81,470 Gross square feet/total: 119,060 Housing area square feet: 34,718 Gross square feet per inmate: 285

Size of cells: 55.5 square feet (gen. single);

63 (spec. single)

Net/gross square feet: Unknown

# Inmate housing areas

Design: Linear, inside Cells per unit: 16 Inmates per unit: 16

Management type: Intermittent

surveillance

September 1987 population: 103

Facility commitment: Local jail inmates Means to handle crowding: Unknown

## Security

Perimeter: Building exterior; video

camera surveillance Inmate security level: Maximum: 66% Medium: 34% Minimum: 0

## **Construction type**

Structural: Steel frame

Exterior walls: CMU block; brick Interior walls: CMU block; steel in

detention areas

Exterior surface/facade: Brick

## **Construction process**

Finance method: Local funds; Certificates of Obligation Contract method: Conventional Use of inmate labor: None Use of prefabrication: None

#### **Inmate cells**

Doors/material: Steel Doors/type: Sliding

Doors/locking: Motor driven and remote

locking

Floor surface: Epoxy coating

Intercom: Two-way to cells and common

areas

HVAC: Air conditioning; electric heat Plumbing: Stainless combination unit

Furniture: Steel

Fire protection: Smoke detectors for cells and common areas; manual alarm stations; automatic smoke removal system

# Inmate design capacity

Single occupancy: 84 Double occupancy: 0

Dorms: 44 Special housing: 4 General population: 128

Total: 132

#### **Current staff**

Full-time equivalent: Administration: 9 Security: 18

Programs/treatment: 1 Maintenance: 2

Total: 30

Current inmate/staff ratio: 3.43:1

## Architect's reported analyses

Factors affecting construction costs: Positive: Simple construction methods,

repetitiveness of design

Negative: Slow construction, lengthy building time; high labor costs; difficult site conditions; complex electronic, mechanical, and electrical systems

Factors affecting time schedule:

Positive: Simple construction methods,

repetitiveness of design Negative: Labor problems

## Wallace Pack Unit I

Jurisdiction official: James A. Lynaugh, Director, Department of Corrections

Contact: Warden Bobby D. Morgan, Wallace Pack Unit I, Route #3, Box 300, Navasota, TX 77868, 409-825-3728

Architects: Barnes, Landes, Goodman and Youngblood, 1600 West 38th Street, Suite 100, Austin, TX 78731, 512-451-8281

Dahl-Braden-PTM, Inc., Reverchon Plaza, 3500 Maple Avenue, LB 87, Suite 1100, Dallas, TX 75219, 214-520-0077

Construction manager/General contractor: B.F.W. Construction Company, P.O. Box 628, Temple, TX 87501, 817-778-8941

Groundbreaking: May 1981 Finish date: July 1986 Construction time: 62 months **Design capacity:** 1,101 **Total cost:** \$14,911,460

Total annual operating costs: Unknown

Category: New, independent facility

Facility type: State prison

**Building configuration:** Integrated structure; ladder, telephone pole

#### **Costs**

Total: \$14,911,460 Building only: \$10,746,707 Housing area: \$7,512,238 Housing per inmate: \$7,168 Housing per cell: \$469,515 Total per inmate: \$13,544 Total per GSF: \$98.43

Total annual operating costs: Unknown

#### **Dimensions**

Gross square feet/corrections: 151,492 Gross square feet/other: 0 Gross square feet/total: 151,492 Housing area square feet: 105,897 Gross square feet per inmate: 138 Size of cells: 3,640 square feet (dorms);

64 (spec. single)
Net/gross square feet: 90%

## **Inmate housing areas**

Design: Dormitory Cells per unit: 1 Inmates per unit: 66

Management type: Remote surveillance September 1987 population: 1,046 Facility commitment: State prisoners Means to handle crowding: Unknown

## Security

Perimeter: Single fence; alarm/detection systems; razor wire on fence; towers;

patrols

Inmate security level:
Maximum: 0
Medium: 0
Minimum: 100%

## **Construction type**

Structural: Steel frame

Exterior walls: "Sandwich panel" type

metal buildings

Interior walls: CMU block; jail steel Exterior surface/facade: Metal buildings

## **Construction process**

Finance method: State funds

Contract method: Turn-key design and

build

Use of inmate labor: Limited; 100 percent inmate labor until 30 percent complete Use of prefabrication: Extensive; prefabri-

cated metal buildings

#### Inmate cells

Doors/material: Steel Doors/type: Swinging Doors/locking: Remote locking

Floor surface: Sealed concrete
Intercom: One-way to common areas
HVAC: Heating/air circulation; gas heat

Plumbing: China Furniture: Steel

Fire protection: Manual alarm stations;

fire hose reels

### Inmate design capacity

Single occupancy: 0 Double occupancy: 0 Dorms: 1,048 Special housing: 53 General population: 1,048

Total: 1,101

#### Current staff

Full-time equivalent: Administration: 24 Security: 175

Programs/treatment: 50 Maintenance: 15

Total: 264

Current inmate/staff ratio: 3.96:1

### Architects' reported analyses

Factors affecting construction costs: Positive: Prefab. components, factory assembly; simple const. methods; fast track CM; favorable market; less expensive materials


Negative: Slow construction; high labor costs; difficult site conditions; government red tape; complex electronic and mechanical systems

Factors affecting time schedule:

Positive: Prefab. components; repetitiveness of design; phased const.; advanced order of materials; coordination of

design between parties

Negative: Slow delivery from vendors; weather problems; government red tape



MAIN BUILDING COMPLEX

SCALE I" = 30' - 0"



	ABBREVIATION	KEY	
ASST	ASSISTANT	LIEUTEN	LIEUTENANT
BBR	BARBER	M	MEN
BKKP.	BOOKEEPING	MECH.	MECHANICAL
COMM.	. COMMISSARY	MED.	MEDICAL
CORR.	CORRIDOR	OFF.	OFFICE
COUN.	COUNSELOR	PKI.	PICKET
GR.	DOCTOR	PRER	PREPARATION
DRS.	DRESS	88.	RESTROOM
EMERG.	EMERGENCY	RM.	ROOM
EXAM.	EXAMINATION	SH.	SHOWER
ISOL .	ISOLATION	STOR.	STORAGE
JAN .	JAMITOR :	TOM.	TOILET
KIT.	KITCHEN	VEG.	VEGETABLE
LAB.	LABORATORY	₩.	WOMEN

## Wallace Pack Unit II

Jurisdiction official: James A. Lynaugh, Director, Department of Corrections

Contact: Warden Kenneth Hughes, Wallace Pack Unit II, Route 1, Box 1000, Navasota, TX 77868, 409-825-7100

Architects: Barnes, Landes, Goodman and Youngblood, 1600 West 38th Street, Suite 100, Austin, TX 78731, 512-451-8281

Dahl-Braden-PTM, Inc., 1800 North Market Street, Dallas, TX 75202, 214-748-1466

**Construction manager/General contractor:** Texas Department of Corrections, New Construction Department, P.O. Box 99, N/C Huntsville, TX 77340, 409-295-6371

**Groundbreaking:** August 1981

Finish date: July 1984

**Construction time:** 35 months

**Design capacity:** 1,364 **Total cost:** \$16,009,587

Total annual operating costs: Unknown

Category: New, independent facility

Facility type: State prison

**Building configuration:** Integrated structure; ladder, telephone pole

#### Costs

Total: \$16,009,587 Building only: Unknown Housing area: \$11,686,989 Housing per inmate: \$8,854 Housing per cell: \$584,349

Total per inmate: \$11,737 Total per GSF: \$95.60

Total annual operating costs: Unknown

#### **Dimensions**

Gross square feet/corrections: 167,470 Gross square feet/other: 0 Gross square feet/total: 167,470 Housing area square feet: 122,070

Gross square feet per inmate: 123 Size of cells: 64 square feet (single); 3,640 (dorms)

Net/gross square feet: 90%

## **Inmate housing areas**

Design: Dormitory style Cells per unit: 1 Inmates per unit: 66

Management type: Remote surveillance September 1987 population: 1,309 Facility commitment: State prisoners Means to handle crowding: Unknown

## Security

Perimeter: Single fence; alarm/detection systems; razor wire on fence; towers;

patrols

Inmate security level:
Maximum: 0
Medium: 0
Minimum: 100%

## **Construction type**

Structural: Steel frame

Exterior walls: "Sandwich panel" type

metal buildings

Interior walls: CMU block; jail steel Exterior surface/facade: Metal

## **Construction process**

Finance method: State funds

Contract method: Turn-key design and

build

Use of inmate labor: None

Use of prefabrication: Extensive; metal

buildings

#### **Inmate cells**

Doors/material: Steel Doors/type: Swinging

Doors/locking: Remote locking

Floor surface: Sealed concrete; hard floor

wearing surface material

Intercom: One-way to common areas HVAC: Heating/air circulation; gas heat

Plumbing: China Furniture: Steel

Fire protection: Manual alarm stations;

fire hose reels

## Inmate design capacity

Single occupancy: 0 Double occupancy: 0 Dorms: 1,320 Special housing: 44 General population: 1,320

Total: 1,364

## Current staff

Full-time equivalent: Administration: 11 Security: 209

Programs/treatment: 54
Maintenance: 10

Total: 284

Current inmate/staff ratio: 4.61:1

## Architects' reported analyses


Factors affecting construction costs:
Positive: Prefab. components, factory
assembly; simple const. methods;
phased const., fast track CM; favorable
market; less expensive materials
Negative: High labor costs; difficult site;
government regulations and red tape;

Factors affecting time schedule:
Positive: Use of prefab. components,
factory assembly; repetitiveness of
design; phased const., fast track CM;
advanced order of materials; coordina-

complex electronic systems

tion of design

Negative: Slow delivery from suppliers; weather problems; government red tape



# **Westside Police Area Command Station**

Jurisdiction official: Lee P. Brown, Chief of Police

Contact: W.T. Higgins, Administrative Captain, Westside Police Area Command Station, 3203 South Dairy Ashford, Houston,

TX 77082, 713-247-5420

Architect: The McGinty Partnership Architects, Inc., 601 Sawyer, Third Floor, Houston, TX 77007, 713-880-2500 Criminal justice consultants: Phillips Swager Associates, 3622 North Knoxville, Peoria, IL 61603, 309-688-9511 Construction manager: Turner Construction Company, 3203 South Dairy, Ashford, Houston, TX 77082, 713-558-9644

**Groundbreaking:** July 1985 **Finish date:** September 1987

Construction time: 26 months

**Design capacity:** 176 **Total cost:** \$17,096,000

**Total annual operating costs:** \$4,912,573

(9 mos. projected)

Category: New, independent facility Facility type: Complex: city jail, law enforcement, courts, vehicle

maintenance

Building configuration: Integ. structure

## **Costs**

Total: \$17,096,000

Building only: \$16,700,000

Housing area: Unknown
Housing per inmate: Unknown
Housing per cell: Unknown

Total per inmate: N/A (complex)

Total per GSF: \$123.88

Total annual operating costs: \$4,912,573

(9 mos. projected)

# Dimensions

Gross square feet/corrections: 37,000 Gross square feet/other: 101,000 Gross square feet/total: 138,000 Housing area square feet: 21,000 Gross square feet per inmate: 210 Size of cells: 84 square feet (single);

163 (dorms)

Net/gross square feet: Unknown

# **Inmate housing areas**

Design: Linear, outside with skylights in

corridors

Cells per unit: 8 to 10 Inmates per unit: 8 to 20

Management type: Remote surveillance

September 1987 population: 0

Facility commitment: Local jail inmates Means to handle crowding: No need

anticipated

# **Security**

Perimeter: Building exterior only

Inmate security level:
Maximum: 95%
Medium: 5%
Minimum: 0

# **Construction type**

Structural: Cast-in-place concrete frame

Exterior walls: CMU block; brick Interior walls: CMU block Exterior surface/facade: Brick

# **Construction process**

Finance method: G.O. Bonds Contract method: Conventional Use of inmate labor: None Use of prefabrication: None

# **Inmate cells**

Doors/material: Steel Doors/type: Sliding

Doors/locking: Motor driven and remote

locking

Floor surface: Sealed concrete

Intercom: Two-way to cells and common

areas

HVAC: Air conditioning; high efficiency chillers; 4-pipe system with boilers for

heating water

Plumbing: Stainless combination unit

Furniture: Steel

Fire protection: Smoke detectors and sprinklers for cells and common areas;

manual alarm stations

### Inmate design capacity

Single occupancy: 38 Double occupancy: 0

Dorms: 60

Special housing: 78 General population: 98

Total: 176

#### **Current staff**

Full-time equivalent: Administration: 23 Security: 92

> Programs/treatment: 8 Maintenance: 12 Total: 135

Current inmate/staff ratio: N/A

### Architect's reported analyses

Factors affecting construction costs:
Positive: Simple construction methods,
repetitiveness of design; good
competition, favorable market
Negative: Complex electronic, mechani-

cal, and electrical systems


Factors affecting time schedule:

Positive: Simple construction methods,

Positive: Simple construction methods, repetitiveness of design; coordination of design between parties

Negative: Complex electronic, mechani-

cal, and electrical systems



# **Orange Street Community Correctional Center**

Jurisdiction official: Gary W. DeLand, Director, Department of Corrections

Contact: Kathy Cochran, Director, Orange Street Community Correctional Center, #80 South Orange Street, Salt Lake City,

UT 84116, 801-533-6360

Architect: Molen, Huss, Money, Fuller Architects, 50 South 600 East, Suite #100, Salt Lake City, UT 84102, 801-532-1603

Construction manager: None

Groundbreaking: March 1985
Finish date: December 1985
Construction time: 9 months

**Design capacity:** 62 **Total cost:** \$740,000

**Total annual operating costs:** \$805,500

Category: New, independent facility Facility type: State-run communitybased correctional facility Building configuration: Integrated

structure

#### Costs

Total: \$740,000 Building only: \$693,000 Housing area: \$550,265 Housing per inmate: \$9,171 Housing per cell: \$18,342

Total per inmate: \$11,935 Total per GSF: \$51.74

Total annual operating costs: \$805,500

# **Dimensions**

Gross square feet/corrections: 14,302 Gross square feet/other: 0 Gross square feet/total: 14,302 Housing area square feet: 11,956 Gross square feet per inmate: 231 Size of cells: 168 square feet (double); 80

(spec. single)

Net/gross square feet: 95%

# Inmates per unit: 60

Cells per unit: 30

Design: Linear, outside

Management type: Intermittent surveillance; limited protection from glass-

housed central station October 1986 population: 59

**Inmate housing areas** 

Facility commitment: Local jail inmates;

State prisoners

Means to handle crowding: Unknown

# Security

Perimeter: Nonsecure facility; visual control only; rooms and hallways not

locked mate se

Inmate security level:
Maximum: 0
Medium: 0
Minimum: 94%
Other: 6%

# **Construction type**

Structural: Load bearing wood frame Exterior walls: 2" x 6" wood stud walls Interior walls: CMU block; metal studs/

drywall

Exterior surface/facade: Brick veneer

# **Construction process**

Finance method: Developer-bank financing; States leases with option to buy Contract method: Turn-key design and

build

Use of inmate labor: None
Use of prefabrication: Limited; roof
trusses and furniture (built in)

#### Inmate cells

Doors/material: Wooden Doors/type: Swinging

Doors/locking: Manual locking Floor surface: Carpet in rooms; epoxy

coating in holding rooms

Intercom: None

HVAC: Air conditioning; gas heat

Plumbing: China

Furniture: Wood; plastic laminate; con-

crete in holding rooms

Fire protection: Smoke detectors and sprinklers for rooms and common areas

# Inmate design capacity

Single occupancy: 0 Double occupancy: 60

Dorms: 0

Special housing: 2 General population: 60

Total: 62

#### **Current staff**

Full-time equivalent: Administration: 5 Security: 15

> Programs/treatment: 0 Maintenance: 0 Total: 20

Current inmate/staff ratio: 2.95:1


### Architect's reported analyses

Factors affecting construction costs:
Positive: Factory assembled prefab. roof
trusses; simple construction methods;
favorable market; private developer,
leased to State; less expensive materials
and hardware; frame structure (very
low security)

Negative: Government procedures, regulations, and red tape

Factors affecting time schedule:
Positive: Use of prefabricated components; repetitiveness of design; advanced order of materials; good working relationship between owner,

contractor, and architect Negative: Government red tape



# **Uintah County Jail**

Jurisdiction official: Drew Christiansen, Sheriff

Contact: Ken Konrad, Jail Commander, Uintah County Jail, 204 East 100 North, Vernal, UT 84078, 801–781–1300 Architect: Molen, Huss, Money, Fuller, Architects, 50 South 600 East, Suite 100, Salt Lake City, UT 84102, 801–532–1603

Construction manager: None

Groundbreaking: March 1984 Finish date: September 1985 Construction time: 18 months **Design capacity:** 68 **Total cost:** \$2,399,689

**Total annual operating costs:** \$440,312

Category: New, independent facility

Facility type: County jail

Building configuration: Integrated

structure

#### **Costs**

Total: \$2,399,689

Building only: \$2,263,374 Housing area: \$2,132,374 Housing per inmate: \$39,488 Housing per cell: \$39,488 Total per inmate: \$35,290 Total per GSF: \$106.33

Total annual operating costs: \$440,312

### **Dimensions**

Gross square feet/corrections: 22,568 Gross square feet/other: 0 Gross square feet/total: 22,568 Housing area square feet: 8,227 Gross square feet per inmate: 332 Size of cells: 70 square feet (single) Net/gross square feet: Unknown

**Construction type** 

Structural: Load bearing CMU walls and cast-in-place concrete floors and roof Exterior walls: Brick; preglazed CMU

block

Interior walls: Cast-in-place concrete;

CMU block

Exterior surface/facade: Brick; preglazed

**CMU** 

# **Security**

Perimeter: Building exterior; video

camera surveillance Inmate security level: Maximum: 14% Medium: 39% Minimum: 29% Other: 18%

### **Inmate cells**

Doors/material: Steel Doors/type: Swinging Doors/locking: Unknown

Floor surface: Epoxy coating; carpet in

dayrooms

Intercom: Two-way to common areas;

one-way from cells

HVAC: Air conditioning; gas heat Plumbing: Stainless combination unit Furniture: Steel; precast concrete bunks

and desks

Fire protection: Smoke detectors for common areas; sprinklers for cells and

common areas

Inmate design capacity

Single occupancy: 54 Double occupancy: 0

Dorms: 0

Special housing: 14 General population: 54

Total: 68

#### **Current staff**

Full-time equivalent: Administration: 2 Security: 12

> Programs/treatment: 0 Maintenance: 2 Total: 16

Current inmate/staff ratio: 1.87:1

# **Inmate housing areas**

Design: Linear, outside Cells per unit: 8 Inmates per unit: 8

Management type: Intermittent surveillance; audio/video surveillance of all dayrooms, corridors, entries, etc.
September 1987 population: 30

Facility commitment: Local jail inmates;

State prisoners

Means to handle crowding: Unknown

# **Construction process**

Finance method: Local funds Contract method: Conventional Use of inmate labor: None

Use of prefabrication: Limited; all bunks

and desks for single cells


# Architect's reported analyses

Factors affecting construction costs: Positive: Simple construction methods;

favorable market

Negative: Slow construction; difficult site conditions; severe winter weather; site was remote—180 miles from nearest location for suppliers and trades

Factors affecting time schedule:
Positive: Repetitiveness of design; coordination of design between parties
Negative: Slow delivery from vendors; site was remote; weather problems, below 0 degrees F.



# Young Adult Correctional Facility

Jurisdiction official: Gary W. DeLand, Director, Department of Corrections

Contact: Warden Jeffrey R. Galli, Young Adult Correctional Facility, 14000 South Frontage Road, Draper, UT 84020, 801-572-5700 Architect: Henningson, Durham & Richardson, Inc., 12700 Hillcrest Road, Suite 125, Dallas, TX 75230, 214–980–0001

Construction manager: None

**Groundbreaking:** July 1983 Finish date: August 1984 Construction time: 13 months Design capacity: 292 **Total cost:** \$12,463,348

Total annual operating costs: \$2,801,135

Category: New, independent facility

Facility type: State prison **Building configuration:** Campus style

#### Costs

Total: \$12,463,348 Building only: \$11,413,934 Housing area: \$5,320,000 Housing per inmate: \$18,472 Housing per cell: \$18,472 Total per inmate: \$42,683 Total per GSF: \$79.56

Total annual operating costs: \$2,801,135

# **Dimensions**

Gross square feet/corrections: 156,660 Gross square feet/other: 0 Gross square feet/total: 156,660 Housing area square feet: 58,608 Gross square feet per inmate: 537 Size of cells: 70 square feet (single); 173

(spec. double)

Net/gross square feet: 72%

# **Inmate housing areas**

Design: Module/pod Cells per unit: 72 Inmates per unit: 72

Management type: Direct supervision

May 1987 population: 508

Facility commitment: State prisoners Means to handle crowding: Second bunk

permanently attached to wall

# **Security**

Perimeter: Double fence; alarm/detection systems; razor wire on and between

fences; patrols Inmate security level: Maximum: 0 Medium: 100% Minimum: 0

# Construction type

Structural: Cast-in-place concrete frame; CMU block

Exterior walls: Precast panels; cast-inplace concrete; brick

Interior walls: Precast panels; CMU block;

Exterior surface/facade: Brick; paint;

textured concrete

# Finance method: State funds

**Construction process** 

Contract method: Conventional Use of inmate labor: None

Use of prefabrication: Limited; precast

panels

# **Inmate cells**

Doors/material: Steel Doors/type: Swinging

Doors/locking: Remote locking; manual

locking

Floor surface: Carpet; epoxy coating;

vinyl tile

Intercom: One-way and two-way to cells;

two-way to common areas

HVAC: Air conditioning; steam heat;

evaporative cooling Plumbing: Vitreous china

Furniture: Steel; wood; vinyl/plastic Fire protection: Smoke detectors and sprinklers for cells and common areas;

manual alarm stations

## Inmate design capacity

Single occupancy: 288 Double occupancy: 0

Dorms: 0

Special housing: 4 General population: 288

Total: 292

#### **Current staff**

Full-time equivalent: Administration: 19 Security: 54

Programs/treatment: 10

Maintenance: 6 Total: 89

Current inmate/staff ratio: 5.71:1

# Architect's reported analyses

Factors affecting construction costs: Positive: Simple construction methods, repetitiveness of design; good competition, favorable market; less expensive


materials and hardware

Negative: Difficult site conditions Factors affecting time schedule:

Positive: Simple construction methods, repetitiveness of design; coordination

of design between parties

Negative: None



# **Northwest State Correctional Facility (Expansion)**

Jurisdiction official: Joseph J. Patrissi, Commissioner of Corrections, Agency of Human Services, Department of Corrections

Contact: Superintendent Heinz Arenz, Northwest State Correctional Facility, P.O. Box 713, St. Albans, VT 05478, 802-524-6771

Architect: Wiemann-Lamphere Architects, Inc., 289 College Street, Burlington, VT 05401, 802–864–0950

Construction manager: None

Groundbreaking: March 1984 Finish date: September 1985 **Construction time:** 18 months

Design capacity: 51 **Total cost:** \$2,506,181

**Total annual operating costs:** \$271,087

(expansion only)

Category: Expansion Facility type: State prison **Building configuration:** Clusters

#### Costs

Total: \$2,506,181 Building only: \$2,490,181 Housing area: \$1,600,000 Housing per inmate: \$35,556 Housing per cell: \$35,556 Total per inmate: \$49,141 Total per GSF: \$125.31

Total annual operating costs: \$271,087

(expansion only)

# Security

Perimeter: Single fence; alarm/detection system; towers; patrols; camera

surveillance Inmate security level: Maximum: 100% Medium: 0 Minimum: 0

### **Inmate cells**

Doors/material: Steel Doors/type: Swinging

Doors/locking: Remote locking Floor surface: Epoxy coating

Intercom: Two-way to common areas HVAC: Heating/air circulation; gas heat Plumbing: Stainless combination unit

Furniture: Steel

Fire protection: Smoke detectors for common areas; manual alarm stations

#### **Dimensions**

Gross square feet/corrections: 20,000

Gross square feet/other: 0 Gross square feet/total: 20,000 Housing area square feet: 13,500 Gross square feet per inmate: 392 Size of cells: 100 square feet (gen. single);

102 (spec. double) Net/gross square feet: 65%

# **Construction type**

Structural: Steel frame Exterior walls: Brick

Interior walls: Cast-in-place concrete Exterior surface/facade: Brick

# Inmate design capacity

Single occupancy: 45 Double occupancy: 0

Dorms: 0

Special housing: 6 General population: 45

Total: 51

#### **Current staff**

Full-time equivalent: Administration: 1 Security: 12

> Programs/treatment: 2 Maintenance: 1

Total: 16 (expansion only) Current inmate/staff ratio: 4.31:1

# **Inmate housing areas**

Design: Module/pod Cells per unit: 15 Inmates per unit: 15

Management type: Remote surveillance

November 1987 population: 51 Facility commitment: Local jail inmates;

State prisoners

Means to handle crowding: None

permitted

# **Construction process**

Finance method: State funds Contract method: Conventional Use of inmate labor: None Use of prefabrication: None

# **Architect's reported analyses**


Factors affecting construction costs: Positive: Simple construction methods, repetitiveness of design; good compe-

tition, favorable market

Negative: Slow concrete work, lengthy building time; site and security problems

Factors affecting time schedule: Positive: Simple construction methods, repetitiveness of design; coordination of design between construction manager and owner

Negative: Slow responses and delivery vendors, suppliers; poor coordination by contractor and lack of understanding of security requirements



# St. Johnsbury Community Correctional Center

Jurisdiction official: Joseph J. Patrissi, Commissioner of Corrections, Agency of Human Services, Department of Corrections

Contact: Superintendent Raymond J. Pilette, St. Johnsbury Community Correctional Center, Route 5 South, RFD #3, St. Johnsbury,

VT 05819, 802-748-8151.

Architect: Alexander/Truex/de Groot, 209 Battery Street, Burlington, VT 05401, 802-658-2775

Construction manager: None

Groundbreaking: November 1979 Finish date: November 1981 Construction time: 24 months **Design capacity:** 96 **Total cost:** \$4,200,000 **Total annual operating costs:** 

\$1,588,173

Category: New, independent facility Facility type: County jail, State prison Building configuration: Integrated

structure

#### **Costs**

Total: \$4,200,000

Building only: \$3,678,250 Housing area: \$3,500,000 Housing per inmate: \$38,043 Housing per cell: \$58,333 Total per inmate: \$43,750 Total per GSF: \$125.07

Total annual operating costs: \$1,588,173

# **Dimensions**

Gross square feet/corrections: 33,580 Gross square feet/other: 0 Gross square feet/total: 33,580 Housing area square feet: 30,800 Gross square feet per inmate: 350

Size of cells: 96 square feet (max. sec.); 80 square feet (med.); 102 square feet

(min.)

Net/gross square feet: 61%

# Security

Perimeter: Building exterior only; fence for exercise yard

Inmate security level:
Maximum: 12%
Medium: 62%
Minimum: 24%
Other: 2%

# **Construction type**

Structural: Cast-in-place load bearing concrete walls, floors, and ceilings Exterior walls: Cast-in-place concrete;

brick

Interior walls: Cast-in-place concrete;

brick

Exterior surface/facade: Brick

# **Inmate cells**

Doors/material: Steel

Doors/type: Swinging; sliding (max.) Doors/locking: Remote locking and

manual

Floor surface: Epoxy coating

Intercom: One-way to cells; two-way

to common areas

HVAC: Heating/air circulation; heat wheel; oil/wood heating plant;

two separate boilers

Plumbing: Stainless combination unit

Furniture: Steel

Fire protection: Smoke detectors for cells and common areas; fire mains and hoses; air pacs and portable extinguishers in control areas

# Inmate design capacity

Single occupancy: 28 Double occupancy: 64

Dorms: 0

Special housing: 4 General population: 92

Total: 96

#### **Current staff**

Full-time equivalent: Administration: 7 Security: 41

Programs/treatment: 15

Maintenance: 7 Total: 70

Current inmate/staff ratio: 1.5:1

# **Inmate housing areas**

Design: Module/pod Cells per unit: 28 Inmates per unit: 40

Management type: Direct supervision

October 1985 population: 105

Facility commitment: State prisoners and

local jail inmates

Means to handle crowding: Mattresses on floor; second bunk attached to wall

# **Construction process**

Finance method: State funds Contract method: Conventional Use of inmate labor: None Use of prefabrication: Moderate; custom designed steel shaftways

# Architect's reported analyses

Factors affecting construction costs: Positive: Good competition, favorable

market; large size


Negative: Long lead time plus slow delivery of security items; complex electronic, mechanical, and electrical systems; government procedures, regulations, "red tape"

Factors affecting time schedule: Positive: Advanced order of materials and hardware; coordination of design between parties

Negative: Slow responses and delivery

from vendors, suppliers





# **Alexandria Detention Center**

Jurisdiction official: James H. Dunning, Sheriff

Contact: Sheriff James H. Dunning, Alexandria Detention Center, 2001 Mill Road, Alexandria, VA 22314, 703-838-4114

Architects: Phillips Swager Associates, 3622 North Knoxville, Peoria, IL 61603, 309–688–9511

VVKR, Inc., 901 Pitt Street, Alexandria, VA 22314, 703-549-9200

Construction manager: None

**Groundbreaking:** February 1984

Finish date: August 1987 Construction time: 42 months **Design capacity:** 346 **Total cost:** \$18,000,000

Total annual operating costs:

\$9,709,532

Category: New, independent facility Facility type: Complex: city jail, law enforcement, court, E.O.C. Building configuration: Integrated

structure; high rise

Costs

Total: \$18,000,000

Building only: \$15,900,000 Housing area: \$13,200,000 Housing per inmate: \$38,150 Housing per cell: \$39,879

Total per inmate: N/A (complex)

Total per GSF: \$84.19

Total annual operating costs: \$9,709,532

**Dimensions** 

Gross square feet/corrections: 143,000 Gross square feet/other: 70,800 Gross square feet/total: 213,800 Housing area square feet: 120,000

Gross square feet per inmate: 413 Size of cells: 70 square feet (single); 1,700

(dorms)

Net/gross square feet: 75%

**Inmate housing areas** 

Design: Module/pod Cells per unit: 48 Inmates per unit: 48

Management type: Remote surveillance;

direct supervision

September 1987 population: 310

Facility commitment: Local jail inmates;

State prisoners

Means to handle crowding: Not necessary

**Security** 

Perimeter: Alarm/detection systems;

video camera surveillance

Inmate security level: Maximum: 10% Medium 67% Minimum: 23% **Construction type** 

Structural: Cast-in-place concrete frame

Exterior walls: Brick

Interior walls: Cast-in-place concrete;

CMU block

Exterior surface/facade: Brick

**Construction process** 

Finance method: G.O. Bonds; Federal

funds

Contract method: Conventional Use of inmate labor: None Use of prefabrication: None

**Inmate cells** 

Doors/material: Unknown Doors/type: Swinging

Doors/locking: Remote locking

Floor surface: Carpet

Intercom: Two-way to cells and common

areas

HVAC: Air conditioning Plumbing: Stainless steel Furniture: Steel; vinyl/plastic

Fire protection: Smoke detectors for cells and common areas; sprinklers for

common areas

Inmate design capacity

Single occupancy: 330 Double occupancy: 0

Dorms: 16 Special housing: 0 General population: 346

Total: 346

Positive: Good competition, favorable

market

Negative: Slow construction, lengthy

**Architect's reported analyses** 

Factors affecting construction costs:

building time

Factors affecting time schedule:

Positive: Coordination of design between

parties

Negative: Slow responses and delivery

from vendors, suppliers


**Current staff** 

Full-time equivalent: Administration: 23 Security: 93

Programs/treatment: 21

Maintenance: 8 Total: 145

Current inmate/staff ratio: 2.14:1





# **Augusta County Jail (Expansion)**

Jurisdiction official: Glenn Lloyd, Sheriff

Contact: Sheriff Glenn Lloyd, Augusta County Jail, P.O. Box 1267, 6 East Johnson Street, Staunton, VA 24401, 703-885-7253

Architect: Sherertz, Franklin, Crawford, Shaffner, 14 West Kirk Avenue, Roanoke, VA 24011, 703-344-6664

Construction manager: None

**Groundbreaking:** July 1980 Finish date: April 1982 Construction time: 21 months Design capacity: 61 **Total cost:** \$2,486,000

Gross square feet/other: 0

Net/gross square feet: 83%

Gross square feet/total: 28,390

Housing area square feet: 12,500

Gross square feet per inmate: 465

Size of cells: 70 square feet (single)

Total annual operating costs: N/A

Gross square feet/corrections: 28,390

(expansion)

**Dimensions** 

Category: Expansion project Facility type: County jail

**Building configuration:** Integrated

structure

#### Costs

Total: \$2,486,000 Building only: \$2,392,600 Housing area: \$1,700,000 Housing per inmate: \$28,333 Housing per cell: \$28,333 Total per inmate: \$40,754

Total per GSF: \$87.57

Total annual operating costs: N/A

(expansion)

# Security

Perimeter: Building exterior only

Inmate security level: Maximum: 100% Medium: 0 Minimum: 0

# **Construction type**

Exterior walls: CMU block; brick Interior walls: Cast-in-place concrete;

CMU block

#### **Inmate housing areas**

Design: Module/pod Cells per unit: 10 Inmates per unit: 10

Management type: Intermittent surveil-

lance

February 1987 population: 90

Facility commitment: Local jail inmates Means to handle crowding: Mattresses on

floor

# **Inmate cells**

Doors/material: Steel Doors/type: Swinging

Doors/locking: Remote locking Floor surface: Sealed concrete Intercom: Two-way to common areas HVAC: Air conditioning; gas heat Plumbing: Stainless combination unit

Furniture: Steel

Fire protection: Smoke detectors for cells and common areas; sprinklers for common areas; manual alarm stations

Structural: Cast-in-place concrete frame

Exterior surface/facade: Brick

# Inmate design capacity

Single occupancy: 60 Double occupancy: 0

Dorms: 0

Special housing: 1 General population: 60

Total: 61

#### **Current staff**

Full-time equivalent: Administration: 2 Security: 22

> Programs/treatment: 1 Maintenance: 2 Total: 27

Current inmate/staff ratio: 3.33:1

# **Construction process**

Finance method: Local funds; State funds; shared cost from multiple jurisdictions Contract method: Conventional

Use of inmate labor: None Use of prefabrication: None

# Architect's reported analyses


Factors affecting construction costs: Positive: Simple construction methods, repetitiveness of design; good competition, favorable market Negative: Difficult site conditions; complex electronic, mechanical, and electrical systems

Factors affecting time schedule: Positive: Simple construction methods,

repetitiveness of design

Negative: Complex electronic, mechanical, and electrical systems; site

conditions



# Fairfax County Adult Detention Center and Pre-Release Center (Expansion)

Jurisdiction official: M. Wayne Huggins, Sheriff

Contact: Major Thomas J. Dever, Correctional Services Division, Fairfax County Adult Detention Center and Pre-Release Center,

10520 Judicial Drive, Fairfax, VA 22030, 703-246-7630

Architect: Henningson, Durham & Richardson, Inc., 12700 Hillcrest, Suite 125, Dallas, TX 75230, 214-980-0001

Construction manager: None

Groundbreaking: October 1985 Finish date: January 1987 Construction time: 15 months **Design capacity:** 300 **Total cost:** \$12,700,000

**Total annual operating costs:** \$1,914,250

(excluding utilities)

Category: Expansion project
Facility type: Complex: county jail,
sheriff's pre-release center
Building configuration: Integrated

structure; high rise

#### **Costs**

Total: \$12,700,000 Building only: Unknown Housing area: Unknown Housing per inmate: Unknown Housing per cell: Unknown Total per inmate: \$42,333 Total per GSF: \$107.63

Total annual operating costs: \$1,914,250

(excluding utilities)

# **Security**

Perimeter: Video camera surveillance

Inmate security level:
Maximum: 33%
Medium: 33%
Minimum: 0
Other: 34%

### Inmate cells

Doors/material: Steel Doors/type: Sliding

Doors/locking: Motor driven and remote

locking

Floor surface: Terrazzo

Intercom: Two-way to common areas

**HVAC**: Air conditioning

Plumbing: Stainless combination unit

Furniture: Concrete

Fire protection: Smoke detectors for cells; sprinklers for common areas

#### **Dimensions**

Gross square feet/corrections: 118,000

Gross square feet/other: 0 Gross square feet/total: 118,000 Housing area square feet: Unknown Gross square feet per inmate: 393 Size of cells: 77 square feet (single) Net/gross square feet: Unknown

# **Construction type**

Structural: Cast-in-place concrete frame Exterior walls: Architectural precast Interior walls: Cast-in-place concrete; CMU block; drywall in work release Exterior surface/facade: Colored concrete

# Inmate design capacity

Single occupancy: 200 Double occupancy: 0

Dorms: 0

Special housing: 100 General population: 200

Total: 300

#### **Current staff**

Full-time equivalent: Administration: 7 Security: 33

Programs/treatment: 16

Maintenance: 3

Total: 59 (expansion only) Current inmate/staff ratio: 3.78:1

# **Inmate housing areas**

Design: Module/pod Cells per unit: 50 Inmates per unit: 50

Management type: Remote surveillance

May 1987 population: 223

Facility commitment: Local jail inmates Means to handle crowding: Unknown

# **Construction process**

Finance method: Local funds Contract method: Conventional Use of inmate labor: None Use of prefabrication: None

# Architect's reported analyses

Factors affecting construction costs: Positive: Good competition, favorable

market

Negative: Slow construction, lengthy

building time


Factors affecting time schedule:

Positive: Coordination of design between

parties

Negative: Slow responses and delivery

from vendors, suppliers



# Pittsylvania County Jail

Jurisdiction official: T.E. McGregor, Sheriff

Contact: T.E. Yeatts, Jail Administrator, Pittsylvania County Jail, P.O. Box 336, Bank Street, Chatham, VA 24531, 804-432-2041

Architect: Sherertz, Franklin, Crawford, Shaffner, 14 West Kirk Avenue, Roanoke, VA 24011, 703-344-6664

Construction manager: None

**Groundbreaking:** March 1980

Finish date: June 1981

**Construction time:** 15 months

**Design capacity:** 39 **Total cost:** \$1,700,000

Total annual operating costs: \$684,463

Category: New, independent facility

Facility type: County jail

**Building configuration:** Integrated

structure

#### **Costs**

Total: \$1,700,000

Building only: \$1,674,400 Housing area: Unknown Housing per inmate: Unknown Housing per cell: Unknown Total per inmate: \$43,590

Total per GSF: \$96.06

Total annual operating costs: \$684,463

# **Dimensions**

Gross square feet/corrections: 17,697

Gross square feet/other: 0 Gross square feet/total: 17,697 Housing area square feet: 8,850 Gross square feet per inmate: 454 Size of cells: 70 square feet (single)

Net/gross square feet: 81%

# Inmate housing areas

Design: Module/pod Cells per unit: 6 Inmates per unit: 6

Management type: Remote surveillance

April 1986 population: 45

Facility commitment: Local jail inmates Means to handle crowding: Mattresses on floor; second bunk permanently

attached to wall

# Security

Perimeter: Building exterior; video

camera surveillance Inmate security level: Maximum: 33% Medium: 33% Minimum: 33%

# Construction type

Structural: Cast-in-place concrete frame Exterior walls: CMU block; brick Interior walls: Cast-in-place concrete;

CMU block

Exterior surface/facade: Brick

# **Construction process**

Finance method: Federal, State, and local

funds

Contract method: Conventional Use of inmate labor: None Use of prefabrication: None

#### **Inmate cells**

Doors/material: Solid Doors/type: Swinging

Doors/locking: Remote locking Floor surface: Sealed concrete Intercom: Two-way to common areas HVAC: Air conditioning; electric heat

pumps

Plumbing: Stainless combination unit

Furniture: Steel

Fire protection: Smoke detectors for cells

and common areas

# Inmate design capacity

Single occupancy: 36 Double occupancy: 0

Dorms: 0 Special housing: 3 General population: 36

Total: 39

# Architect's reported analyses

Factors affecting construction costs: Positive: Simple construction methods,

repetitiveness of design

Negative: Slow construction; difficult site conditions; government red tape; conflict in Federal and State funding

regulations

Factors affecting time schedule:

Positive: Simple construction methods,

repetitiveness of design

Negative: Slow responses and delivery from vendors, suppliers; government red tape; conflict between State and

Federal regulations


#### Current staff

Full-time equivalent: Administration: 3 Security: 19

Programs/treatment: 2 Maintenance: 2

Total: 26

Current inmate/staff ratio: 1.73:1



Jurisdiction official: W. Alvin Hudson, Sheriff

Contact: Sheriff W. Alvin Hudson, Sheriff's Department, 316 Campbell Avenue, Roanoke, VA 24016, 703–981–2721

Architect: Hayes, Seay, Mattern and Mattern, P.O. Box 13446, 1315 Franklin Road SW., Roanoke, VA 24034, 703-343-6971

Construction manager: None

**Groundbreaking:** July 1977 **Finish date:** July 1979

**Construction time:** 24 months

Design capacity: 201 Total cost: \$5,813,110

**Total annual operating costs:** 

\$2,573,363

Category: New, independent facility;

phased project (future)

Facility type: Complex: city jail and

sheriff's office

**Building configuration:** Integrated

structure

#### **Costs**

Total: \$5,813,110

Building only: \$5,471,500 Housing area: \$1,924,934 Housing per inmate: \$11,458 Housing per cell: \$11,458

Total per inmate: N/A (complex)

Total per GSF: \$62.19

Total annual operating costs: \$2,573,363

# **Dimensions**

Gross square feet/corrections: 80,554

(+ 8,110 future) Gross square feet/other: 4,816 Gross square feet/total: 93,480 Housing area square feet: 32,888

Gross square feet per inmate: 401 Size of cells: 63 square feet (single)

Net/gross square feet: 51%

# **Inmate housing areas**

Design: Module/pod

Cells per unit: 20 per pod, 10 per dayroom

Inmates per unit: 20

Management type: Remote surveillance;

TV; and rounds

October 1985 population: 192

Facility commitment: Local jail inmates Means to handle crowding: Second bunk permanently attached to wall; beds in

chapel

# Security

Perimeter: Building exterior only

Inmate security level:
Maximum: 18%
Medium: 40%
Minimum: 42%

# **Construction type**

Structural: Load bearing precast panels

and cast-in-place frame

Exterior walls: Architectural precast Interior walls: Precast panels; cast-in-place concrete; CMU block Exterior surface/facade: Textured

concrete

# **Construction process**

Finance method: Local funds Contract method: Conventional Use of inmate labor: None Use of prefabrication: Extensive

#### **Inmate cells**

Doors/material: Steel

Doors/type: Sliding (max.); swinging

(max. and min.)

Doors/locking: Remote locking (max.);

manual and remote locking

(max. and min.)

Floor surface: Epoxy coating

Intercom: Two-way to common areas HVAC: Air conditioning; electric heating—electric resistance and

electric terminal reheat Plumbing: Stainless Furniture: Steel

Fire protection: Manual alarm stations; smoke detectors in HVAC ducts

# Inmate design capacity

Single occupancy: 168 Double occupancy: 0

Dorms: 0

Special housing: 33 General population: 168

Total: 201

#### **Current staff**

Full-time equivalent: Administration: 12 Security: 57

Programs/treatment: 11

Maintenance: 3 Total: 83

Current inmate/staff ratio: 2.31:1


# Architect's reported analyses

Factors affecting construction costs:
Positive: Use of prefabricated components,
factory assembly; simple construction
methods, repetitiveness of design; good
competition, favorable market; precast
concrete exterior walls

Negative: Shelled space and provisions for future construction

Factors affecting time schedule:
Positive: Use of prefabricated components,
factory assembly; simple construction
methods, repetitiveness of design;
precast concrete exterior walls

Negative: None



# **Benton County Justice Center**

Jurisdiction official: Jim Kennedy, Sheriff

Contact: Bernie Freeman, Jail Administrator, Benton County Justice Center, 7320 West Quinault, Kennewick, WA 99336,

509-735-6555

Architect: Henningson, Durham & Richardson, Inc., 12700 Hillcrest, #125, Dallas, TX 75230, 214–980–0001

Construction manager: None

Groundbreaking: October 1982 Finish date: October 1983 Construction time: 12 months

Design capacity: 103 **Total cost:** \$11,442,995

Total annual operating costs: \$1,230,989

Category: New, independent facility Facility type: Complex: county jail; law

enforcement, courts

**Building configuration:** Integrated

structure

# Costs

Total: \$11.442.995 Building only: \$10,957,995 Housing area: \$4,300,000 Housing per inmate: \$48,864 Housing per cell: \$74,138

Total per inmate: N/A (complex)

Total per GSF: \$118.18

Total annual operating costs: \$1,230,989

# **Dimensions**

Gross square feet/corrections: 29,069 Gross square feet/other: 67,758 Gross square feet/total: 96,827 Housing area square feet: 17,295 Gross square feet per inmate: 282

Size of cells: Unknown Net/gross square feet: 72%

# **Construction type**

Exterior surface/facade: Natural wall

# **Inmate housing areas**

Design: Module/pod Cells per unit: 16 Inmates per unit: 16

Management type: Remote surveillance

March 1987 population: 109

**Construction process** 

Contract method: Conventional

Facility commitment: Local jail inmates Means to handle crowding: Bunk beds; mattresses on floor; beds in dayroom; second bunk permanently attached to

wall

# Security

Structural: Cast-in-place concrete frame Exterior walls: Precast panels

Interior walls: CMU block

Use of inmate labor: None Use of prefabrication: Moderate; precast

Finance method: Local funds; State funds

components

Perimeter: Building exterior only

Inmate security level: Maximum: 0 Medium: 85% Minimum: 15%

Single occupancy: 64 Double occupancy: 0

Special housing: 15 General population: 88

# **Inmate design capacity**

Dorms: 39

Total: 103

#### **Current staff**

Full-time equivalent: Administration: 2 Security: 33

> Programs/treatment: 1 Maintenance: 0 Total: 36

Current inmate/staff ratio: 3.03:1

# Architect's reported analyses

Factors affecting construction costs: Positive: Prefabricated components,

factory assembly Negative: High labor costs Factors affecting time schedule: Positive: Use of prefabricated compo-

nents, factory assembly Negative: Weather problems

# **Inmate cells**

Doors/material: Solid; steel Doors/type: Swinging; sliding Doors/locking: Remote locking Floor surface: Linoleum


Intercom: Two-way to common areas HVAC: Heating/air circulation; steam

Plumbing: Stainless combination unit

Furniture: Vinyl/plastic

Fire protection: Smoke detectors and

sprinklers for cells



# Forks City Jail (Addition)

Jurisdiction official: Kenneth W. Bryson, Chief of Police

Contact: Chief Kenneth W. Bryson, Forks City Jail, Fifth and Division, P.O. Box 28, Forks, WA 98331, 206-374-2223

Architects: Johnston/Hunt & Associates, P.S., 1112 East Front Street, Port Angeles, WA 98362, 206-683-5584

Johnston Associates, 299 Old Blyn Highway, Sequim, WA 98382, 206-683-5584

Construction manager: None

Groundbreaking: July 1982 Finish date: August 1983 Construction time: 13 months **Design capacity:** 14 **Total cost:** \$773,916

**Total annual operating costs:** \$164,500

(addition only)

Category: New, ancillary building
Facility type: Complex: city jail, law
enforcement, courts, City Hall
Building configuration: Wheel, spoke or

radial

Costs

Total: \$773,916

Building only: \$752,916 Housing area: \$526,891 Housing per inmate: \$47,899 Housing per cell: \$47,899

Total per inmate: N/A (complex)

Total per GSF: \$68.84

Total annual operating costs: \$164,500

(addition only)

**Security** 

Perimeter: Single fence Inmate security level: Maximum: 100% Medium: 0

**Inmate cells** 

Minimum: 0

Doors/material: Steel

Doors/type: Swinging; sliding

Doors/locking: Motor driven and remote

locking

Floor surface: Sealed concrete

Intercom: Two-way to cells and common

areas

HVAC: Air conditioning; electric heat

pump

Plumbing: Stainless combination unit

Furniture: Steel

Fire protection: Smoke detectors and sprinklers for cells and common areas; manual alarm stations; sprinklers operated manually for cells, electrically from control room **Dimensions** 

Gross square feet/corrections: 6,200 Gross square feet/other: 5,042 Gross square feet/total: 11,242 Housing area square feet: 4,715 Gross square feet per inmate: 443 Size of cells: 73 square feet (single)

Net/gross square feet: 82%

**Construction type** 

Structural: Load bearing precast panels and

masonry

Exterior walls: Precast panels and

sandwich panels Interior walls: CMU block Exterior surface/facade: Paint

Inmate design capacity

Single occupancy: 11 Double occupancy: 0

Dorms: 0

Special housing: 3 General population: 11

Total: 14

**Current staff** 

Full-time equivalent: Administration: 1 Security: 10

Programs/treatment: N/A

Maintenance: N/A Total: 11 (addition only) Current inmate/staff ratio: 0.36:1 **Inmate housing areas** 

Design: Linear, outside Cells per unit: 8 Inmates per unit: 8

Management type: Remote surveillance

May 1986 population: 4

Facility commitment: Local jail inmates;

State prisoners

Means to handle crowding: Beds in

dayroom

**Construction process** 

Finance method: State funds Contract method: Conventional Use of inmate labor: None

Use of prefabrication: Extensive; concrete

sandwich and plain panels

Architects' reported analyses

reported analyses


Factors affecting construction costs:
Positive: Simple construction methods,
repetitiveness of design; good competition, favorable market; good design
Negative: Slow construction, lengthy
building time; difficult site conditions;

bad weather

Factors affecting time schedule:

Positive: Simple construction methods, repetitiveness of design; ordering materials and hardware 6 months ahead of bidding; coordination of design between parties; architect also project manager

Negative: Extremely rainy; complex electronic, mechanical, and electrical systems



# **Jefferson County Correctional Facility**

Jurisdiction official: L.B. Smith, Sheriff

Contact: Sheriff L.B. Smith, Jefferson County Correctional Facility, 81 Elkins Road, Hadlock, WA 98339, 206-385-3831

Mailing Address: Jefferson County Correctional Facility, P.O. Box 1220, Port Townsend, WA 98339

Architects: Johnston/Hunt & Associates, P.S., 1112 East Front Street, Port Angeles, WA 98362, 206-683-5584

Johnston Associates, 299 Old Blyn Highway, Sequim, WA 98382, 206-683-5584

Construction manager: Johnston/Hunt & Associates, above

Groundbreaking: October 1983

Finish date: July 1985

Construction time: 21 months

**Design capacity: 33 Total cost:** \$2,093,328

Total annual operating costs: \$234,111

Category: New, independent facility Facility type: Complex: county jail, law enforcement, FEMA emergency center Building configuration: Integrated

structure

Costs

Total: \$2,093,328

Building only: \$2,032,950

Housing area: \$1,207,234 Housing per inmate: \$60,362 Housing per cell: \$60,362

Total per inmate: N/A (complex)

Total per GSF: \$116.70

Total annual operating costs: \$234,111

Security

Perimeter: Single fence; video camera

surveillance

Inmate security level:

Maximum: 61% Medium: 39% Minimum: 0

**Inmate cells** 

Doors/material: Steel

Doors/type: Swinging; sliding

Doors/locking: Motor driven and remote

locking

Floor surface: Sealed concrete

Intercom: Two-way to cells and common

HVAC: Heating/air circulation; electric

and heat recovery

Plumbing: Stainless combination unit

Furniture: Steel

Fire protection: Smoke detectors and sprinklers for cells and common areas;

manual alarm stations

**Dimensions** 

Gross square feet/corrections: 11,636

Gross square feet/other: 6,302 Gross square feet/total: 17,938

Housing area square feet: 11,636 Gross square feet per inmate: 353

Size of cells: 73 square feet (single) Net/gross square feet: 84%

**Construction type** 

Structural: Load bearing precast panels;

bearing masonry

Exterior walls: Precast panels and

sandwich panels

Interior walls: Cast-in-place concrete

Exterior surface/facade: Paint

**Inmate design capacity** 

Single occupancy: 20 Double occupancy: 0

Dorms: 0

Special housing: 13 General population: 20

Total: 33

**Current staff** 

Full-time equivalent:

Administration: 1

Security: 6

Programs/treatment: 2

Maintenance: 2

Total: 11

Current inmate/staff ratio: 2.18:1

**Inmate housing areas** 

Design: Linear, outside (high ceilings)

Cells per unit: 6 Inmates per unit: 6

Management type: Intermittent and

remote surveillance May 1986 population: 24

Facility commitment: Local jail inmates;

State prisoners

Means to handle crowding: Removable

second bunks

**Construction process** 

Finance method: G.O. Bonds; Federal,

State, and local funds

Contract method: Conventional: second

contractor takeover Use of inmate labor: None

Use of prefabrication: Extensive;

sandwich and roof panels

Architects' reported analyses

Factors affecting construction costs:

Positive: Prefabricated components,

factory assembly; good competition,


favorable market

Negative: Slow construction, lengthy building time; complex electronic,

mechanical, and electrical systems

Factors affecting time schedule:

Positive: None Negative: None



- 1. Drive thru Salle
- 2. Storage
- 3. Holding
- 4. Receiving
- 5. Strip Search
- 6. Property
- 7. Laundry
- 8. Janitor
- 9. Medical
- 10. Kitchen
- 11. Segregation
- 12. Crisis

- 13. Control
- 14. Cell Block A (Work Release)
- 15. Cell Block B (Work Release)
- 16. Work Release
   (Clothes Change)
- 17. Cell Block C (Women)
- 18. Cell Block D
- 19. Indoor Recreation
- 20. Outdoor Recreation
- 21. Cell Block E

- 22. Cell Block F
- 23. Visitation
- 24. Arraignment
- 25. Interview
- 26. Jail Administrator
- 27. Public Lobby
- 28. Reception
- 29. Sheriff's Department
- 30. Staff Lockers (women)
- 31. Staff Lockers (men)

# **Thurston County Corrections Facility (Remodel/Expansion)**

Jurisdiction official: Dan Montgomery, Sheriff

Contact: James P. Bachmeier, Chief Deputy/Corrections Bureau, Thurston County Corrections Facility, 2000 Lakeridge Drive,

Olympia, WA 98502, 206-786-5505

Architect: The BJSS Group, Architects & Planners, AIA, 320 West Bay Drive, Suite 212, Olympia, WA 98502, 206-943-4650

Construction manager: None

Groundbreaking: September 1983

Finish date: May 1986

**Construction time:** 32 months

**Design capacity:** 158 **Total cost:** \$3,931,394

**Dimensions** 

Total annual operating costs: \$1,240,000

Gross square feet/corrections: 64,066

Gross square feet/other: 22,515 Gross square feet/total: 86,581

Housing area square feet: 22,800

Gross square feet per inmate: 405

Size of dorms: 800 square feet

Net/gross square feet: 80%

Category: Remodeling/renovation proj-

ect; expansion

Facility type: Complex: county jail, law enforcement, courts, county offices

Building configuration: Integ. structure

#### **Costs**

Total: \$3,931,394

Building only: \$3,706,994 Housing area: \$1,240,000 Housing per inmate: \$11,481 Housing per cell: \$16,104

Total per inmate: N/A (complex)

Perimeter: Building exterior; video

Total per GSF: \$45.41

camera surveillance

Inmate security level:

Maximum: 27%

Minimum: 53%

Medium 20%

Total annual operating costs: \$1,240,000

# **Construction type**

Structural: Load bearing precast panels; steel frame

Exterior walls: Precast panels; architectural precast

Interior walls: Precast panels; cast-in-place

concrete; CMU block

Exterior surface/facade: Stucco; paint; wall coating on precast concrete

#### **Inmate cells**

Security

Doors/material: Solid; wooden; steel

Doors/type: Swinging

Doors/locking: Motor driven and remote

locking; manual locking Floor surface: Sealed concrete

Intercom: Two-way to cells and common

areas

HVAC: Air conditioning; electric heat Plumbing: China; stainless combination

unit

Furniture: Steel; wood; vinyl/plastic;

concrete

Fire protection: Smoke detectors for cells; sprinklers for common areas

# Inmate design capacity

Single occupancy: 72 Double occupancy: 0

Dorms: 36

Special housing: 50 General population: 108

Total: 158

#### **Current staff**

Full-time equivalent: Administration: 3

Security: 34

Programs/treatment: 2 Maintenance: 2

Total: 41

Current inmate/staff ratio: 3.54:1

# **Inmate housing areas**

Design: Module/pod Cells per unit: 15 Inmates per unit: 15

Management type: Remote surveillance

June 1986 population: 145

Facility commitment: Local jail inmates Means to handle crowding: None

# **Construction process**

Finance method: State funds Contract method: Conventional Use of inmate labor: None

Use of prefabrication: Extensive; architectural precast concrete wall panels;

concrete plank structure


# Architect's reported analyses

Factors affecting construction costs: Positive: Prefab. components, factory assembly; precast concrete; less expensive materials and hardware; simple construction methods

Negative: Slow construction, lengthy building time; con. phasing to allow occupancy during con.; high labor costs; complex electronic, mech., and

electrical systems

Factors affecting time schedule:
Positive: Use of prefab. components,
factory assembly; simple construction
methods, repetitiveness of design
Negative: Slow responses and delivery
from vendors, suppliers; complex
systems



# **Twin Rivers Corrections Center**

Jurisdiction official: Chase Riveland, Secretary, Department of Corrections

Contact: Superintendent Janet Barbour, Twin Rivers Corrections Center, P.O. Box 888, Monroe, WA 98272, 206–794–2515 Architect: TRA, Architecture Engineering Planning Interiors, 215 Columbia, Seattle, WA 98104–1551, 206–682–1331 Design consultants: Hellmuth, Obata & Kassabaum, Inc., One Lombard Street, San Francisco, CA 94111, 415–627–1600 Construction manager: None

Groundbreaking: May 1981 Finish date: March 1984 Construction time: 34 months

Design capacity: 545 Total cost: \$26,500,000 Total annual operating costs:

\$10,330,237

Category: New, independent facility Facility type: State prison

**Building configuration:** Wheel; campus

#### **Costs**

Total: \$26,500,000

Building only: \$24,763,598 Housing area: \$11,930,274 Housing per inmate: \$23,861 Housing per cell: \$23,861 Total per inmate: \$48,624

Total per GSF: \$104.91 Total annual operating costs: \$10,330,237

# **Dimensions**

Gross square feet/corrections: 252,590 Gross square feet/other: 0

Gross square feet/other: 0 Gross square feet/total: 252,590 Housing area square feet: 109,400 Gross square feet per inmate: 481 Size of cells: 80 square feet (single)

Net/gross square feet: 95%

# **Construction type**

Structural: Cast-in-place concrete frame

Exterior walls: Tilt-up concrete Interior walls: CMU block

Exterior surface/facade: Stucco over metal

lath and insulation

# Security

Perimeter: Double fence; alarm/detection system; razor wire on fence

Inmate security level:
Maximum: 5%
Medium: 95%
Minimum: 0

# Inmate design capacity

Single occupancy: 500 Double occupancy: 0

Dorms: 0 Other: 20

Special housing: 25 General population: 520

Total: 545

## **Inmate cells**

Doors/material: Steel Doors/type: Swinging

Doors/locking: Remote locking only Floor surface: Integral color concrete Intercom: Nurse call feature at cells; two-

way to common areas

HVAC: Heating/air circulation only; limited air-conditioning

Plumbing: Stainless

Furniture: Painted steel—custom

designed

Fire protection: Smoke detectors in duct work; sprinklers in corridors, exit ways

and group areas

# Current staff

Full-time equivalent: Administration: 22.5 Security: 163

Programs/treatment: 39.5

Maintenance: 27 Total: 252

Current inmate/staff ratio: 2.08:1

# **Inmate housing areas**

Design: Linear, outside Cells per unit: 125 Inmates per unit: 125

Management type: Remote surveillance;

patrols

October 1985 population: 524
Facility commitment: State prisoners
Means to handle crowding: Second bunk

permanently attached to wall

# **Construction process**

Finance method: State funds Contract method: Conventional Use of inmate labor: None Use of prefabrication: None

# Architect's reported analyses

Factors affecting construction costs: Positive: Advanced correctional concepts; coordination of value engineering by


architect and owner Negative: None

Factors affecting time schedule:

Positive: None

Negative: Slow responses and delivery from vendors, suppliers; weather

problems



# **Washington Corrections Center Intensive Management Unit (Addition)**

Jurisdiction official: Chase Riveland, Secretary, Department of Corrections

Contact: Superintendent Kurt S. Peterson, Washington Corrections Center IMU, P.O. Box 900, Shelton, WA 98584, 206–426–4433 Architect: The BJSS Group Architects/Planners, 320 West Bay Drive, Suite 212, Olympia, WA 98502, 206–943–4650 Construction manager: The BJSS Group, 320 West Bay Drive, Suite 212, Olympia, WA 98502, 206–943–4650

Groundbreaking: November 1983 Finish date: December 1984 Construction time: 13 months

**Design capacity:** 124 **Total cost:** \$7,134,000

**Total annual operating costs:** \$1,077,273

(addition only)

Category: New, ancillary building

Facility type: State prison
Building configuration: Integrated

structure

#### **Costs**

Total: \$7,134,000

Building only: \$6,740,000 Housing area: \$6,740,000 Housing per inmate: \$54,355 Housing per cell: \$54,355 Total per inmate: \$57,532 Total per GSF: \$164.71

Total annual operating costs: \$1,077,273

(addition only)

# **Security**

Perimeter: Double fence; razor wire on and between fences; towers; patrols;

camera surveillance Inmate security level: Maximum: 100% Medium: 0 Minimum: 0

#### Inmate cells

Doors/material: Steel Doors/type: Sliding

Doors/locking: Motor driven and remote

locking

Floor surface: Carpet; sealed concrete Intercom: Two-way to cells and common

areas

HVAC: Air conditioning; steam heat Plumbing: Stainless steel; stainless

combination unit Furniture: Steel

Fire protection: Smoke detectors for cells and common areas; override and control/monitoring in control booth

# **Dimensions**

Gross square feet/corrections: 43,313

Gross square feet/other: 0 Gross square feet/total: 43,313 Housing area square feet: 43,313 Gross square feet per inmate: 349 Size of cells: 82 square feet (spec. single)

Net/gross square feet: 88%

# **Construction type**

Structural: Load bearing precast panels; cast-in-place concrete frame

Exterior walls: Precast panels; cast-inplace concrete

place colletete

Interior walls: Precast panels; cast-in-place

concrete; CMU block

Exterior surface/facade: Stucco; paint

# Inmate design capacity

Single occupancy: 0 Double occupancy: 0

Dorms: 0

Special housing: 124 General population: 0

Total: 124

#### **Current staff**

Full-time equivalent: Administration: 3 Security: 33

Programs/treatment: 5 Maintenance: 0

Total: 41 (addition only) Current inmate/staff ratio: 2.71:1

# **Inmate housing areas**

Design: Module/pod Cells per unit: 20 Inmates per unit: 20

Management type: Remote surveillance

June 1986 population: 111

Facility commitment: State prisoners Means to handle crowding: Unknown

# **Construction process**

Finance method: State funds Contract method: Conventional Use of inmate labor: None Use of prefabrication: Moderate

### Architect's reported analyses

Factors affecting construction costs: Positive: Simple construction methods,

repetitiveness of design

Negative: High labor costs; difficult site

conditions

Factors affecting time schedule:

Positive: Simple construction methods, repetitiveness of design; coordination

of design between parties Negative: Weather problems (No floorplan available at time of publication)

# **Whitman County Correctional Facility**

Jurisdiction official: Steve Tomson, Sheriff

Contact: Captain Richard Lally, Facility Commander, Whitman County Correctional Facility, Colfax, WA 99111, 509-397-4262

Architect: Northwest Architectural Company, West 1203 Riverside, Spokane, WA 99201, 509-838-8240 **Justice design consultant:** The Gruzen Partnership, 251 Post Street, San Francisco, CA 94108, 415-956-5515

Construction manager: None

**Groundbreaking:** October 1982

Finish date: April 1984 Construction time: 18 months **Design capacity:** 38 **Total cost:** \$3,000,000

Total annual operating costs: \$330,000

Category: New, independent facility Facility type: Complex: county jail, county sheriff, county offices Building configuration: Integrated

structure

#### Costs

Total: \$3,000,000

Building only: \$2,900,000 Housing area: \$1,027,010 Housing per inmate: \$27,027 Housing per cell: \$42,792

Total per inmate: N/A (complex)

Total per GSF: \$106.19

Total annual operating costs: \$330,000

# Security

Perimeter: Building exterior only

Inmate security level:
Maximum: 5%
Medium: 53%
Minimum: 42%

# Inmate cells

Doors/material: Steel Doors/type: Swinging

Doors/locking: Remote locking only Floor surface: Sealed concrete Intercom: Two-way to common areas HVAC: Heating/air circulation only; gas-fired heating plant; central boiler

Plumbing: Stainless; china

Furniture: Steel

Fire protection: Smoke detectors and sprinklers for cells and common areas

#### **Dimensions**

Gross square feet/corrections: 16,660 Gross square feet/other: 11,590 Gross square feet/total: 28,250 Housing area square feet: 5,900 Gross square feet per inmate: 438 Size of cells: 75 square feet (single)

Net/gross square feet: 61%

# **Construction type**

Structural: Cast-in-place concrete frame Exterior walls: Cast-in-place concrete;

CMU block

Interior walls: Cast-in-place concrete;

CMU block

Exterior surface/facade: Insulated plaster

system

# Inmate design capacity

Single occupancy: 22 Double occupancy: 0

Dorms: 16 Special housing: 0 General population: 38

Total: 38

### **Current staff**

Full-time equivalent: Administration: 1 Security: 10

Programs/treatment: 1 Maintenance: 0 Total: 12

Current inmate/staff ratio: 2.67:1

# **Inmate housing areas**

Design: Module/pod Cells per unit: 2 to 8 Inmates per unit: 2 to 8

Management type: Remote surveillance

October 1985 population: 32

Facility commitment: Local jail inmates Means to handle crowding: None

# **Construction process**

Finance method: State funds; county levy Contract method: Conventional Use of inmate labor: None Use of prefabrication: None

# Architect's reported analyses


Factors affecting construction costs: Positive: Good competition, favorable


market

Negative: Difficult site conditions (very tight site, poor soil bearing capacity, high water table); complex electronics/computer system and hard-wired locking system

Factors affecting time schedule:
Positive: Design coordinated with
minimum changes by owner; contractor's

efficient construction process
Negative: Weather problems (winter);
complex electronics system





#### **Ohio County Correctional Center**

Jurisdiction official: Arthur McKenzie, Sheriff

Contact: Sheriff Arthur McKenzie, Ohio County Correctional Center, 1501 Eoff Street, Wheeling, WV 26003, 304-234-3607

Architect: R.L. Smith—Architecture, P.O. Box 2204, Waco, TX 76703, 817–776–4011

Construction manager: None

Groundbreaking: October 1977

Finish date: June 1979

Construction time: 20 months

**Design capacity:** 61 **Total cost:** \$1,474,000

**Dimensions** 

Total annual operating costs: \$620,801

Gross square feet/corrections: 15,950

Gross square feet/other: 9,860

Gross square feet/total: 25,810

Size of dorms: 400 square feet

Net/gross square feet: 84%

Housing area square feet: 15,950

Gross square feet per inmate: 261

Category: New, independent facility Facility type: Complex: county and city

jails; courts

Building configuration: Integrated

structure

#### **Costs**

Total: \$1,474,000

Building only: \$1,453,000 Housing area: \$900,860 Housing per inmate: \$20,019

Housing per cell: \$34,648

Total per inmate: N/A (complex)

Total per GSF: \$57.11

Total annual operating costs: \$620,801

Perimeter: Building exterior; alarm/detec-

tion system; video camera surveillance

#### Construction type

Structural: Steel frame; prestressed hollow concrete

Concrete

Exterior walls: Cast-in-place concrete; brick; special CMU block

blick, special CWIO block

Interior walls: CMU block; furred comp.

board and paneling

Exterior surface/facade: Brick; paint;

textured concrete

#### Inmate cells

**Security** 

Doors/material: Solid; steel

Doors/type: Sliding

Inmate security level:

Maximum: 33%

Medium: 31%

Minimum: 36%

Doors/locking: Motor driven and remote

locking; manual locking

Floor surface: Carpet; epoxy coating;

sealed concrete

Intercom: Two-way to common areas HVAC: Air conditioning; heating/air

circulation

Plumbing: Stainless steel

Furniture: Steel; wood; vinyl/plastic Fire protection: Smoke detectors for

common areas

#### Inmate design capacity

Single occupancy: 17 Double occupancy: 10

Dorms: 18

Special housing: 16 General population: 45

Total: 61

#### **Current staff**

Full-time equivalent: Administration: 0

Security: 26

Programs/treatment: 0 Maintenance: 0

Total: 26

Current inmate/staff ratio: 2.04:1

#### **Inmate housing areas**

Design: Linear, outside and inside

Cells per unit: 5 Inmates per unit: 5

Management type: Intermittent surveil-

lance

May 1986 population: 53

Facility commitment: Local jail inmates Means to handle crowding: Bunk beds in cell; mattresses on floor; beds in

dayroom

#### **Construction process**

Finance method: Revenue sharing; Federal, State, and local funds; special

election

Contract method: Conventional Use of inmate labor: None

Use of prefabrication: Moderate; concrete

floor and roof units

#### Architect's reported analyses

Factors affecting construction costs: Positive: Simple construction methods; good competition, favorable market; materials and construction methods

common to area


Negative: Slow construction, lengthy building time; high labor costs; complex electronic, mechanical, and electrical systems; labor unions; weather

Factors affecting time schedule:

Positive: Repetitiveness of design; materials and construction methods common

to area

Negative: Slow responses and delivery from vendors, suppliers; labor and weather problems; complex electronic, mechanical, and electrical systems



#### **Burnett County Government Center**

Jurisdiction official: Donald Chell, Sheriff

Contact: Sheriff Donald Chell, Burnett County Government Center, Route 1, Box 300-122, Siren, WI 54872, 715-349-2121 Architect: Ozolins—D'Jock Architects, Ltd., 2115 East Clairemont Avenue, Suite 1, Eau Claire, WI 54701-4787, 715-834-0505 Construction manager: Construction Analysis & Management, 7401 Central Avenue NE., Minneapolis, MN 55432, 612-786-7151

**Groundbreaking:** July 1983 Finish date: January 1985 Construction time: 18 months Design capacity: 27 **Total cost:** \$3,238,324

Total annual operating costs: \$288,903

Category: New, independent facility Facility type: Complex: county jail, law enforcement, courts, county agencies Building configuration: Integrated

structure

#### Costs

Total: \$3,238,324 Building only: \$3,125,025 Housing area: Unknown Housing per inmate: Unknown Housing per cell: Unknown Total per inmate: N/A (complex)

Total per GSF: \$59.62

camera surveillance

Inmate security level:

Maximum: 60%

Medium: 40%

Minimum: 0

Total annual operating costs: \$288,903

Perimeter: Building exterior; video

## **Dimensions**

Gross square feet/corrections: 10,440 Gross square feet/other: 43,874 Gross square feet/total: 54,314 Housing area square feet: 10,440 Gross square feet per inmate: 387 Size of cells: 59 square feet (single) Net/gross square feet: 78%

#### **Construction type**

Structural: Cast-in-place concrete frame Exterior walls: CMU block; metal wall

Interior walls: Cast-in-place concrete;

CMU block

Exterior surface/facade: Textured concrete;

metal panels

panels

#### Inmate design capacity

Single occupancy: 15 Double occupancy: 0

Dorms: 0

Special housing: 12 General population: 15

Total: 27

#### Inmate cells

Security

Doors/material: Steel Doors/type: Sliding

Doors/locking: Motor driven and remote

locking

Floor surface: Carpet; sealed concrete;

vinyl tile

Intercom: One-way to cells and common

areas

HVAC: Heating/air circulation; solar heat; other energy recycle unit; reheat

coils

Plumbing: Stainless steel

Furniture: Steel

Fire protection: Smoke detectors for cells

#### **Current staff**

Full-time equivalent: Administration: 13 Security: 13

Programs/treatment: 0 Maintenance: 3

Total: 29

Current inmate/staff ratio: 0.62:1

#### **Inmate housing areas**

Design: Linear, inside Cells per unit: 15 Inmates per unit: 15

Management type: Intermittent surveil-

lance

June 1986 population: 18

Facility commitment: Local jail inmates Means to handle crowding: None

#### **Construction process**

Finance method: G.O. Bonds Contract method: Construction

management

Use of inmate labor: None Use of prefabrication: None

#### Architect's reported analyses

Factors affecting construction costs: Positive: Simple construction methods, repetitiveness of design; good competition, favorable market; construction management

Negative: Slow construction, lengthy building time; difficult site conditions; high water table


Factors affecting time schedule:

Positive: Simple construction methods,

repetitiveness of design

Negative: Slow responses and delivery from vendors, suppliers; weather

problems



#### **Columbia Correctional Institution**

Jurisdiction official: Stephen E. Bablitch, Administrator, Department of Corrections

Contact: Superintendent James P. Murphy, Columbia Correctional Institution, Route 3, Highway 127, P.O. Box 950, Portage,

WI 53901, 608-742-9105

Architect: Potter, Lawson & Pawlowsky, Inc., 15 Ellis Potter Court, Madison, WI 53711, 608-274-2741

Construction manager: Potter, Lawson & Pawlowsky, Inc., 15 Ellis Potter Court, Madison, WI 53711, 608-274-2741

Groundbreaking: February 1984

Finish date: May 1986 Construction time: 27 months **Design capacity:** 511 **Total cost:** \$30,362,286

Total annual operating costs: \$7,326,540

Category: New, independent facility

Facility type: State prison

**Inmate housing areas** 

Design: Linear, outside

Cells per unit: 50

Inmates per unit: 50

**Building configuration:** Courtyard

Management type: Remote surveillance

Facility commitment: State prisoners

Means to handle crowding: Unknown

September 1987 population: 432

#### Costs

Total: \$30,362,286

Building only: \$27,739,014 Housing area: Unknown Housing per inmate: Unknown Housing per cell: Unknown Total per inmate: \$59,417

Total per inmate: \$59,417 Total per GSF: \$102.37

Total annual operating costs: \$7,326,540

#### **Dimensions**

Gross square feet/corrections: 296,600

Gross square feet/other: 0 Gross square feet/total: 296,600 Housing area square feet: 123,800 Gross square feet per inmate: 580 Size of cells: 80 square feet (single)

Net/gross square feet: 70%

## **Construction type**

Structural: Steel frame Exterior walls: CMU block

Interior walls: Cast-in-place concrete;

CMU block

Exterior surface/facade: Brick

#### **Construction process**

Finance method: G.O. Bonds Contract method: Conventional Use of inmate labor: None Use of prefabrication: None

#### Security

Perimeter: Double fence; alarm/ detection systems; razor wire on and between fences; towers; patrols; camera

surveillance Inmate security level: Maximum: 100% Medium: 0 Minimum: 0

#### **Inmate cells**

Doors/material: Steel Doors/type: Sliding

Doors/locking: Motor driven and remote

locking; manual locking Floor surface: Sealed concrete

Intercom: Two-way to cells and common

areas

HVAC: Heating/air circulation; gas heat

Plumbing: China Furniture: Steel

Fire protection: Smoke detectors and sprinklers for cells and common areas;

manual alarm stations

#### Inmate design capacity

Single occupancy: 450 Double occupancy: 0

Dorms: 0

Special housing: 61 General population: 450

Total: 511

#### **Current staff**

Full-time equivalent: Administration: 49 Security: 189

Programs/treatment: 15 Maintenance: 14

Total: 267

Current inmate/staff ratio: 1.62:1

#### Architect's reported analyses


Factors affecting construction costs:
Positive: Nine identical housing units;
favorable market; bids lower than
estimates

Negative: Difficult site conditions; high water table; complex electronic and mechanical systems; long lead times for detention equipment

Factors affecting time schedule: Positive: Repetitiveness of design; coordination of design between parties; onsite supervision by architect and owner

Negative: Slow delivery from suppliers; complex electronic and mechanical


systems



#### **Upper Level Housing**

- 1 Control Station Below
- 2 Showers 3 Cells

- **4** Adjacent Housing Unit **5** Upper Portion of Dayroom



#### **Lower Level Housing**

- 1 Dayroom 2 Kitchenette 3 Storage

- 4 Laundry5 Unit Management Staff6 Control Station
- 7 Showers
- 8 Cells
- 9 Adjacent Housing Unit

#### Oshkosh Correctional Institution

Jurisdiction official: Steven E. Bablitch, Administrator, Division of Corrections

Contact: Superintendent Donald W. Gudmanson, Oshkosh Correctional Institution, P.O. Box 3530, 1730 West Snell Road,

Oshkosh, WI 54903-3530, 414-231-4010

Architects: Sauter Seaborne Architects Engineers Ltd., 825 West Lawrence Street, Appleton, WI 54914, 414-739-6266

Miller Wagner Coenen, Inc., 250 Green Bay Road, Neenak, WI 54956, 414-725-6346

Construction manager: None

**Groundbreaking:** March 1984

Finish date: April 1986

**Construction time:** 25 months

**Design capacity:** 312 **Total cost:** \$23,313,398

Total annual operating costs: \$459,400

Category: New, independent facility

Facility type: State prison

**Building configuration:** Cluster of housing units with support units at each

end

#### **Costs**

Total: \$23,313,398

Building only: \$22,634,761 Housing area: Unknown Housing per inmate: Unknown Housing per cell: Unknown

Total per inmate: \$74,722 Total per GSF: \$118.10

Total annual operating costs: \$459,400

#### **Dimensions**

Gross square feet/corrections: 197,405

Gross square feet/other: 0 Gross square feet/total: 197,405 Housing area square feet: 92,262 Gross square feet per inmate: 633

Size of cells: 82 square feet (gen. single);

91 (spec. single)

Net/gross square feet: 75%

#### **Inmate housing areas**

Design: Module/pod Cells per unit: 104

Inmates per unit: 104

Management type: Direct supervision

March 1987 population: 193

Facility commitment: State prisoners Means to handle crowding: Bunk beds in

cell; beds in dayroom

#### Security

Perimeter: Double fence; alarm/detection system; razor wire on fences; towers;

patrols

Inmate security level:
Maximum: 0
Medium: 100%
Minimum: 0

#### **Construction type**

Structural: Steel frame Exterior walls: CMU block Interior walls: CMU block Exterior surface/facade: Brick

Inmate design capacity

Single occupancy: 291

General population: 303

Double occupancy: 0

Special housing: 9

#### **Construction process**

Finance method: State funds

Contract method: Construction manage-

ment fast track

Use of inmate labor: Limited; fabrication

of some furniture

Use of prefabrication: None

#### **Inmate cells**

Doors/material: Steel

Doors/type: Swinging; sliding Doors/locking: Manual locking

Floor surface: Epoxy coating; vinyl tile

Intercom: Two-way to cells

HVAC: Heating/air circulation; gas heat, furnaces can burn methane from nearby

landfill

Plumbing: Stainless steel; china

Furniture: Steel

Fire protection: Smoke detectors and sprinklers for cells and common areas; manual alarm stations

Current staff

Dorms: 12

Total: 312

Full-time equivalent: Administration: 30

Security: 90

Programs/treatment: 44 Maintenance: 19

Total: 183

Current inmate/staff ratio: 1.05:1

#### Architect's reported analyses

Factors affecting construction costs:
Positive: Simple construction methods,
repetitiveness of design; phased
construction, fast track CM; good
competition, favorable market; good
design for region

Negative: Government procedures, regulations, and red tape


Factors affecting time schedule:

Positive: Phased construction, fast track

construction management

Negative: Slow responses and delivery from vendors, suppliers; weather problems; government procedures,

regulations, and red tape



#### **Rusk County Law Enforcement Facility**

Jurisdiction official: Gary Fetting, Sheriff

Contact: Sergeant Richard Mohr, Rusk County Law Enforcement Facility, East Third Avenue, Ladysmith, WI 54848, 715–532–2200 Architect: Ozolins-D'Jock Architects, Ltd., 2115 East Clairemont Avenue, Eau Claire, WI 54701–4787, 715–834–0505 Construction manager: Ozolins-D'Jock Associates, 2115 East Clairemont Avenue, Eau Claire, WI 54701–4787, 715–834–0505

Groundbreaking: May 1984 Finish date: August 1985 Construction time: 15 months **Design capacity:** 29 **Total cost:** \$1,650,000

Total annual operating costs: \$247,800

Category: New, independent facility Facility type: Complex: county jail, law

enforcement

Building configuration: Integrated

structure

#### Costs

Total: \$1,650,000

Building only: \$1,645,000 Housing area: \$1,050,000 Housing per inmate: \$38,889 Housing per cell: \$38,889

Total per inmate: N/A (complex)

Total per GSF: \$78.72

Total annual operating costs: \$247,800

#### **Dimensions**

Gross square feet/corrections: 10,930 Gross square feet/other: 11,280 Gross square feet/total: 22,210 Housing area square feet: 10,030 Gross square feet per inmate: 377 Size of cells: 54 square feet (gen. single);

70 (spec. single); 420 (dorms) Net/gross square feet: Unknown

#### **Inmate housing areas**

Design: Linear, inside
Cells per unit: Varies
Inmates per unit: Varies

Management type: Intermittent

surveillance

September 1987 population: 15

Facility commitment: Local jail inmates Means to handle crowding: Unknown

#### **Security**

Perimeter: Building exterior only

Inmate security level:
Maximum: 60%
Medium: 0
Minimum: 40%

#### **Construction type**

Structural: Load-bearing precast panels Exterior walls: Brick; synthetic plaster and

rigid insulation

Interior walls: CMU block

Exterior surface/facade: Brick; stucco

#### **Construction process**

Finance method: G.O. Bonds

Contract method: Construction manage-

ment fast track

Use of inmate labor: None Use of prefabrication: None

#### **Inmate cells**

Doors/material: Steel Doors/type: Sliding

Doors/locking: Motor driven and remote

locking; manual locking
Floor surface: Sealed concrete
Intercom: Two-way to cells

HVAC: Heating/air circulation; gas heat

with oil standby Plumbing: Stainless steel

Furniture: Steel

Fire protection: Smoke detectors and sprinklers for cells and common areas

#### Inmate design capacity

Single occupancy: 15 Double occupancy: 0

Dorms: 12

Special housing: 2 General population: 27

Total: 29

#### **Current staff**

Full-time equivalent: Administration: 1

Security: 9 Programs/treatment: 0 Maintenance: 1

Total: 11


Current inmate/staff ratio: 1.36:1

#### Architect's reported analyses

Factors affecting construction costs:
Positive: Simple construction methods,

repetitiveness of design Negative: High labor costs Factors affecting time schedule:

Positive: None Negative: None





·		

## Appendix A

ACA standards for design of adult correctional institutions and local detention facilities

		•	

#### **ACA standards**

## **Design of adult correctional institutions** and local detention facilities

The National Institute of Justice has created this directory to illustrate how jails and prisons may be designed and built. As a handbook for construction, it would not be complete without discussion of the standards by which correctional facilities are designed.

For many years, both officials and architects have relied upon the standards developed by the American Correctional Association. These guidelines have served corrections agencies by providing direction along the difficult path from inception to completion of a new jail or prison. However, strict adherence to construction guidelines may be costly for some jurisdictions. Thus, not every agency can follow the standards in their entirety. For this reason, not every facility in this catalog is in complete compliance with ACA standards.

By drawing on the collective experience of corrections officials across the Nation, the ACA standards may help those planning new facilities to consider the lessons learned by colleagues who have faced the same problems. Like the premise of NIJ's Construction Information Exchange, the ACA standards represent an opportunity to "build on experience."

#### Prisons/adult correctional institutions

Although planners and designers of new or remodeled facilities should consider all ACA standards and their relationship to design, the following selected standards are especially critical in facility planning. These standards are presented as important reminders that should be reviewed frequently during the design process of correctional facilities.

**2–4022.** The institution provides for all inmates the following constructive programs, including, at a minimum: reception and orientation; evaluation and classification; academic education equivalent to high school; vocational training; employment; religious services; social services and counseling; psychological and psychiatric services; library services; medical and dental health care; athletic, recreational, and leisure time activities; inmate involvement with community groups; mail and visiting; access to media, legal materials, attorneys, and courts; volunteer services; and prerelease orientation and planning.

**2–4049.** There is an inmate commissary or canteen where inmates can purchase items not furnished by the facility from an approved list. Strict controls are maintained over its operation and standard accounting procedures are followed.

**2–4086.** Space and equipment required for the training and staff development program are available.

**2–4129.** Existing, renovation, addition, new plant. Only one inmate occupies a room or cell designed for single occupancy that has a floor area of at least 60 square feet, provided inmates spend no more than 10 hours per day locked in. When confinement exceeds 10 hours per day, there are at least 80 square feet of floor space.

**2–4130.** Existing, renovation, addition, new plant. Each room or cell has, at a minimum, the following facilities and conditions:

Sanitation facilities, including access to:

- Toilet above floor level that is available for use without staff assistance 24 hours a day.
- Wash basin with hot and cold running water.

A bed at above floor level, desk, hooks or closet space, chair or stool.

Natural light.

Documentation by an independent, qualified source that:

- Lighting is at least 20 footcandles at desk level and in the personal grooming area.
- Circulation is at least 10 cubic feet of outside or recirculated filtered air per minute per human occupant.
- Temperatures are appropriate to the summer and winter comfort zones.
- Noise levels do not exceed 70 decibels in daytime and 45 decibels at night.

**2–4131.** Existing, renovation, addition, new plant (minimum security only). Where used, multiple occupancy rooms house no less than three and no more than 50 inmates each who are screened for suitability to group living prior to admission. Multiple occupancy rooms are continuously observed by staff and provide the following facilities and conditions:

A minimum floor area of 50 square feet per occupant in the sleeping area and a clear floor-to-ceiling height of not less than eight feet.

Toilet and shower facilities at a minimum of one operable toilet and shower for every eight occupants.

One operable wash basin with hot and cold running water for every six occupants.

Single beds only.

Access to a locker or private storage space for each occupant.

Natural light.

Documentation by an independent, qualified source that:

- Lighting is at least 20 footcandles at desk level and in the personal grooming area.
- Circulation is at least 10 cubic feet of outside or recirculated filtered air per minute per occupant.
- Temperatures are appropriate to the summer and winter comfort zones.
- Noise levels do not exceed 70 decibels in daytime and 45 decibels at night.
- **2–4132.** Existing, renovation, addition, new plant. Minimum security institutions, or minimum security areas within larger institutions provide individual rooms with key control shared by the occupants and staff, or continuous access to toilet and shower facilities and hot and cold running water, including drinking water. Rooms also provide the following facilities and conditions:

A minimum floor area of 60 square feet.

A bunk at above floor level, desk, hooks or closet space, chair or stool.

Natural light.

Documentation by an independent, qualified source that:

- Lighting is at least 20 footcandles at desk level and in the personal grooming area.
- Circulation is at least 10 cubic feet of outside or recirculated filtered air per minute per occupant.
- Temperatures are appropriate to the summer and winter comfort zones.
- Noise levels do not exceed 70 decibels in daytime and 45 decibels at night.
- **2–4133.** Existing, renovation, addition, new plant. When males and females are housed in the same institution there are separate sleeping quarters.
- **2–4134.** Existing, renovation, addition, new plant. There are two identifiable exits in each inmate housing area and other high density areas to permit the prompt evacuation of inmates and staff under emergency conditions. (Mandatory)
- **2–4135.** Existing, renovation, addition, new plant. The segregation housing units provide living conditions that approximate those of the general inmate population; all exceptions are clearly documented. Segregation housing units provide the following facilities and conditions:

Single occupancy rooms or cells with a floor area of at least 80 square feet.

Sanitation facilities, including access to:

- Above-floor toilet facilities available for use without staff assistance 24 hours a day.
- Hot and cold running water.

#### Natural light.

A bunk at above floor level, desk or writing space, and stool.

Documentation by an independent, qualified source that:

- Lighting is at least 20 footcandles at desk level and in the personal grooming area.
- Circulation is at least 10 cubic feet of fresh or purified air per minute.
- Temperatures are appropriate to the summer and winter comfort zones.
- Noise levels do not exceed 70 decibels in daytime and 45 decibels at night.
- **2–4136.** Existing, renovation, addition, new plant. The segregation rooms permit inmates assigned to them to converse with others in the same housing unit and have doors that permit observation by staff.
- **2–4137.** Existing, renovation. There is a separate day room leisure time space for each general population housing unit.
- **2–4138.** Existing, renovation. Space outside the cell or room is provided for inmate exercise.
- **2–4139.** Existing, renovation, addition, new plant. In institutions offering academic and vocational training programs, the classrooms are designed in cooperation with school authorities.
- **2–4142.** Existing, renovation, addition, new plant. If the institution has watchtowers, they are placed so that they permit an unobstructed view of the grounds and perimeter and are equipped with the weaponry, lighting, sighting, and communications devices necessary for effective execution of their function.
- **2–4143.** Existing, renovation, addition, new plant. The food preparation and dining area includes a space for food preparation based on population size.
- **2–4144.** Existing, renovation, addition, new plant. Space is provided for administrative, custodial, professional, and clerical staff; this space includes conference rooms, employee lounge, storage room for records, public lobby, and toilet facilities.
- 2–4145. Existing, renovation, addition, new plant. Handicapped inmates are housed in a manner that provides for their safety and security. Cells or housing units used by them are designed for their use, and provide the maximum possible integration with the general population. Appropriate institution programs and activities are accessible to handicapped inmates confined in the facility.
- **2–4146.** Existing, renovation, addition, new plant. All parts of the facility that are accessible to the public are accessible to and usable by handicapped staff and visitors.
- **2–4147.** Existing, renovation, addition, new plant. Space is provided for janitor closets, which are equipped with a sink and cleaning implements.

- **2–4148.** Existing, renovation, addition, new plant. There are storage rooms in the institution for clothing, bedding, and cleaning supplies.
- **2–4149.** Existing, renovation, addition, new plant. There is storage space available for the personal property of inmates.
- **2–4150.** Existing, renovation, addition, new plant. Separate and adequate space is provided for mechanical equipment.
- **2–4152.** Renovation, addition, new plant. Planning precludes the use of dormitories for inmate housing in maximum, close, or medium security institutions.
- **2–4153.** Renovation, addition, new plant. The institution conforms to applicable Federal, State, and local building codes.
- **2–4154.** Renovation, addition, new plant. There is documentation by an independent, qualified source that ventilation is at least 10 cubic feet of outside or recirculated filtered air per minute, per human occupant, for cell blocks and guard stations, and 20 cubic feet per minute for eating halls. Lighting requirements for the facility are determined by the tasks to be performed, interior surface finishes and colors, type and spacing of light sources, outside lighting, and shadows and glare.
- **2–4155.** Renovation, addition, new plant. There is documentation by a qualified source that the interior finishing material in inmate living areas, exit areas, and places of public assembly are in accordance with recognized national fire safety codes. (Mandatory)
- **2–4158.** Addition, new plant. There is separate day-room/leisure time space for each general population housing unit containing 35 square feet of floor space per inmate exclusive of circulation corridors in front of cells/rooms.
- **2–4159.** Addition, new plant. Administrative segregation housing units are the same as those for the general population and have an area for indoor exercise outside the room or cell that has 35 square feet of floor space per inmate requiring exercise.
- **2–4162.** There is documentation by an independent, qualified source that the institution complies with the applicable fire safety code(s). (Mandatory)
- 2-4165. The institution has an automatic fire alarm and smoke detection system that is certified by an independent, qualified inspector trained in the application of national fire safety codes. If the institution depends on a local fire department, the fire alarm system is connected directly to the local fire department. Whenever possible, all system elements are tested on a quarterly basis; adequacy and operation of the systems are certified by a State fire official or other qualified authority annually. (Mandatory)

- **2–4166.** Specifications for the selection and purchase of facility furnishings indicate the fire safety performance requirements of the materials selected. (Mandatory)
- 2-4168. The facility has exits that are distinctly and permanently marked, continuously visible at all times, kept clear, and maintained in usable condition. (Mandatory)
- **2–4169.** An independent, qualified inspector who is trained in the application of national fire safety codes has certified that the travel distance to all exits is in compliance with code requirements. (Mandatory)
- **2–4170.** The institution has equipment necessary to maintain essential lights, power, and communications in an emergency.
- **2–4173.** Written policy and procedure specify the means for the immediate release of inmates from locked areas in case of emergency and provide for a backup system.
- **2–4177.** The institution's perimeter is controlled by an appropriate means to provide that inmates remain within the perimeter and to prevent access by the general public without the appropriate authorization.
- **2–4179.** Safety vestibules and sally ports constitute the only breaches in the institution perimeter security. (Essential—maximum and medium security facilities only)
- **2–4180.** Pedestrian and vehicular traffic should enter and leave at designated points in the perimeter. (Essential—medium and minimum security facilities only)
- **2–4181.** The institution maintains a control center to provide order and security.
- **2–4187.** The institution has facilities for the safe unloading and reloading of firearms.
- **2–4189.** Firearms, chemical agents, and related security equipment are stored in a secure but readily accessible depository outside inmate housing and activity areas and are inventoried at least monthly to determine their condition and expiration dates.
- **2–4245.** Toilet and wash basin facilities are available to food service personnel and inmates in the vicinity of the food preparation area.
- **2–4247.** There are sanitary, temperature-controlled storage facilities for the storage of all foods.
- **2–4250.** Space is provided for group dining except when security or safety considerations justify otherwise.
- **2–4259.** The institution provides for waste disposal. (Mandatory)

- **2–4265.** The store of clothing, linen, and bedding exceeds that required for the facility's inmate population.
- **2–4266.** The institution provides for the thorough cleaning and, when necessary, disinfecting of inmate personal clothing before storage or before allowing the inmate to keep and wear personal clothing.
- **2–4268.** There are sufficient bathing facilities in the housing areas to permit inmates in the general population to shower at least three times per week.
- **2–4270.** There are hair care services available to inmates that comply with applicable health requirements.
- 2-4275. An adequately equipped medical facility, which meets the legal requirements for a licensed general hospital with respect to the services it offers, is available to all inmates. (Mandatory)
- **2–4277.** Space, equipment, supplies, and materials for health services are provided and maintained as determined by the health authority.
- **2–4295.** Written policy and procedure require that routine and emergency dental care is provided to each inmate under the direction and supervision of a dentist with appropriate State or Federal licensure.
- **2–4305.** Written policy and procedure make available chronic and convalescent care to inmates of the facility.
- **2–4325.** Written policy and procedure exist to assist inmates in making confidential contact with attorneys and their authorized representatives.
- **2–4326.** Written policy and procedure provide for the right of inmates to have access to an appropriate law library and to supplies and services related to legal matters. The law library includes, at a minimum, relevant and up-to-date constitutional, statutory, and case law materials, applicable court rules, and practice treatises. When an inmate is unable to make meaningful use of the law library alone, additional assistance necessary for effective access is provided.
- **2–4336.** Written policy and procedure grant inmates the right to practice their religion, subject only to the limitations necessary to maintain institutional order and security.
- **2–4337.** Written policy and procedure grant inmates the right to receive visits, subject only to the limitations necessary to maintain institutional order and security.
- **2–4379.** Written policy and procedure provide for inmate access to public telephones.
- **2–4383.** Written policy and procedure provide that inmate visiting facilities permit informal communication, including opportunity for physical contact. Devices that preclude physical contact are not used except in instances of substantiated security risk.

- 2-4422. There is a comprehensive education program available to all eligible inmates that extends from literacy training through high school and includes communication skills, mathematics, and social science.
- **2–4431.** The educational program is supported by specialized equipment, including, at a minimum, classrooms, teaching carrels, audiovisual materials and facilities, chalkboards, and administrative space.
- **2–4436.** Postsecondary programs in academic and vocational education are available to qualified inmates.
- **2–4442.** The institution maintains and/or provides access to comprehensive library services that include, but are not limited to, a reference collection that includes general and specialized materials, and planned and continuous acquisition of materials to meet the needs of the institutional staff and inmates.
- **2–4452.** Written policy and procedure provide for a comprehensive recreational program that includes leisure time activities comparable with those available in the community.
- **2–4458.** Facilities and equipment, which are maintained in good condition and are suitable for the planned leisure activities, are available in proportion to the inmate population.
- **2–4470.** The institution provides facilities and equipment for the conduct of religious programs for inmates.

#### Jails/local detention facilities

The following standards have been exerpted from the complete volume applicable to local detention and holding facilities. These guidelines are intended to apply to facilities operated by cities and counties, where inmates are held for shorter periods of time.

**2–5108.** Existing. All activity areas have toilets and wash basins that are accessible to persons using the area.

An independent, qualified source has documented that:

- Lighting is appropriate to the activity area.
- Circulation is at least 10 cubic feet of fresh or purified air per minute per human occupant.
- Temperatures are appropriate to the summer and winter comfort zones with consideration for the activity performed. (Detention—essential; holding—essential)
- 2-5109. Existing, renovation, addition, new plant. The intake/booking and release area is located inside the security perimeter, but outside inmate living quarters, and has the following components: booking area; sally port; access to drinking water; shower facilities; secure storage for inmates' personal property; telephone facilities; private interview space(s); temporary holding rooms with sufficient fixed seating for all inmates at its rated capacity; and operable toilets and wash basins. (Detention—essential; holding—essential)

- **2–5110.** Existing, renovation, addition, new plant. Only one inmate occupies each cell and detention room designed for single occupancy. (Detention—essential; holding—essential)
- **2–5111.** Existing, renovation. All single rooms or cells in *detention facilities* have at least 60 square feet of floor space, provided inmates spend no more than 10 hours per day locked in; when confinement exceeds 10 hours per day, there are at least 70 square feet of floor space. (Detention—essential; holding—not applicable)
- **2–5112.** Existing, renovation, addition, new plant. All rooms or cells in detention facilities have, at a minimum:

Access to the following sanitation facilities:

- Toilet above floor level that is available for use without staff assistance 24 hours per day.
- Wash basin and drinking water.
- Shower facilities.
- Hot and cold running water.

A bed at above floor level, desk or writing surface, hooks or closet space, chair or stool.

Natural light.

Documentation by an independent, qualified source that:

- Lighting is at least 20 footcandles at desk level and in the personal grooming area; in additions and new plants it is both occupant and centrally controlled.
- Circulation is at least 10 cubic feet of outside or recirculated filtered air per minute per human occupant.
- Temperatures are appropriate to the summer and winter comfort zones.
- Noise levels do not exceed 70 decibels in daytime and 45 decibels at night. (Detention—essential; holding—not applicable)
- **2–5113.** Existing, renovation. Single rooms or cells in *holding facilities* have, at a minimum:

50 square feet of floor space.

A bed above floor level.

Access to the following sanitation facilities:

- Toilet above floor level that is available for use without staff assistance 24 hours per day.
- Wash basin with hot and cold running water.
- Shower facilities.

Documentation by an independent, qualified source that:

- Lighting is at least 20 footcandles at desk level and in the personal grooming area.
- Circulation is at least 10 cubic feet of outside or recirculated filtered air per minute per human occupant.
- Temperatures are appropriate to the summer and winter comfort zones;

- Noise levels do not exceed 70 decibels in daytime and 45 decibels at night. (Detention—not applicable; holding—important) (See related standard 2–5139)
- **2–5114.** Existing renovation. Where used, multiple occupancy rooms house no less than four and no more than 50 inmates each who are screened prior to admission for suitability to group living; the rooms provide:

Continuing observation by staff.

A minimum floor area of 50 square feet per occupant in the sleeping area and a clear floor to ceiling height of not less than eight feet.

Toilet and shower facilities at a minimum of one operable toilet and shower for every eight occupants.

One operable wash basin with hot and cold running water for every six occupants.

Natural light.

Beds above floor level.

A locker for each occupant.

Documentation by an independent, qualified source that:

- Lighting is at least 20 footcandles at desk level and in the personal grooming area.
- Circulation is at least 10 cubic feet of outside or recirculated filtered air per minute per occupant.
- Temperatures are appropriate to the summer and winter comfort zones.
- Noise levels do not exceed 70 decibels in daytime and 45 decibels at night. (Detention—essential; holding—essential)
- **2–5115.** Existing, renovation, addition, new plant. The segregation rooms provide living conditions that approximate those of the general inmate population; all exceptions are clearly documented. Segregation housing units provide:

Single occupancy rooms or cells with a flow area of at least 70 square feet.

A bed at above floor level, desk or writing space and stool.

Continuous access to the following sanitation facilities:

- Above-floor toilet facilities.
- Hot and cold running water.

Natural light.

Documentation by an independent, qualified source that:

- Lighting is at least 20 footcandles at desk level and in the personal grooming area.
- Circulation is at least 10 cubic feet of outside or recirculated filtered air per minute.
- Temperatures are appropriate to summer and winter comfort zones.
- Noise levels do not exceed 70 decibels in daytime and 45 decibels at night. (Detention—important; holding—not applicable)

- **2–5116.** Existing, renovation, addition, new plant. A room used for segregation permits inmates assigned to it to communicate with staff and has a door that permits observation by staff. (Detention—essential; holding—essential)
- **2–5117.** Existing, renovation, addition, new plant. When seriously ill, mentally disordered, injured or nonambulatory inmates are held in the facility, there is at least one single-occupancy cell or room for them that provides for continuing staff observation. (Detention—essential; holding—essential)
- 2-5118. Existing, renovation, addition, new plant. When both males and females are housed in the same facility they are provided separate sleeping quarters that are separated visually and acoustically. (Detention—essential; holding—essential)
- **2–5120.** Addition, new plant. There are at least two identifiable exits in each inmate housing area/cell block and other high density area to permit the prompt evacuation of inmates and staff under emergency conditions. (Detention—mandatory; holding—mandatory)
- **2–5122.** Existing, renovation, addition, new plant. Space is provided for the secure storage of chemical agents, restraining devices and related security equipment and the equipment is located in an area that is readily accessible to authorized persons only. (Detention—essential; holding—essential)
- **2–5123.** Existing, renovation, addition, new plant. There are sally ports between inmate areas and areas providing access to the public. (Detention—essential; holding—essential)
- **2–5124.** Existing renovation. There is a separate day room leisure time space for each cell block or detention room cluster. (Detention—essential; holding—not applicable)
- 2-5125. Existing. Space outside the cell or room is provided for inmate exercise. (Detention—essential; holding—important)
- **2–5126.** Existing, renovation, addition, new plant. When the facility provides food service, the kitchen has a minimum of 200 square feet of floor space. (Detention—essential; holding—essential)
- **2–5127.** Existing, renovation, addition, new plant. Consistent with the size of the facility, space is provided for administrative, professional, and clerical staff, including conference rooms, employee lounge, storage room for records, public lobby and toilet facilities. (Detention—essential; holding—important)
- **2–5128.** Existing, renovation, addition, new plant. There is at least one multipurpose room available for inmate activities such as religious services, education programs or visiting. (Detention—essential; holding—important)

- **2–5130.** Existing, renovation, addition, new plant. A room or closet equipped with a sink is provided for the storage of cleaning supplies and equipment. (Detention—essential; holding—essential)
- **2–5131.** Existing, renovation, addition, new plant. Storage space is provided for clothing, bedding, and facility supplies. (Detention—essential; holding—essential)
- **2–5132.** Existing, renovation, addition, new plant. Space is provided for the secure storage of inmates' personal property. (Detention—essential; holding—essential)
- **2–5134.** Existing, renovation, addition, new plant. The institution conforms to applicable Federal, State, and local building codes. (Detention—essential; holding—essential)
- **2–5136.** Existing, renovation, addition, new plant. There is documentation by an independent, qualified source that the interior finishing material in inmate living areas, exit areas, and places of public assembly are in accordance with recognized national fire safety codes. (Detention—mandatory; holding—mandatory)
- **2–5137.** Addition, new plant. All cells and detention rooms are designed for single-occupancy only. (Detention—essential; holding—essential) (See related standard 2–5114)
- **2–5138.** Addition, new plant. All single cells or rooms in *detention facilities* have, at a minimum, 70 square feet of floor space. (Detention—essential; holding—not applicable) (See related standards 2–5111, 2–5112, and 2–5115)
- **2–5139.** Addition, new plant. All single cells and rooms in *holding facilities* have, at a minimum:

70 square feet of floor space, with no less than 7 feet between walls and no less than 8 feet between the floor and ceiling.

Access to the following sanitation facilities:

- Toilet above floor level that is available for use without staff assistance 24 hours a day.
- Wash basin and drinking water.
- Shower facilities.
- Hot and cold running water.

A bed at above floor level, desk, or writing surfaces, hooks or closet space, chair or stool.

Documentation by an independent, qualified source that:

- Lighting is at least 20 footcandles at desk level and in the personal grooming area that is both occupant and centrally controlled.
- Circulation is at least 10 cubic feet of fresh or purified air per minute per human occupant.
- Temperatures are appropriate to the summer and winter comfort zones.

- Noise levels do not exceed 70 decibels in daytime and 45 decibels at night. (Detention—not applicable; holding—essential)
- 2-5141. Addition, new plants. The facility is designed and constructed so that inmates can be separated according to existing laws and regulation, or according to the facility's classification plan. (Detention—essential; holding—essential)
- 2-5142. Addition, new plants. Handicapped inmates are housed in a manner which provides for their safety and security. Cells or housing units used by them are designed for their use, and provide the maximum possible integration with the general population. Appropriate institution programs and activities are accessible to handicapped inmates confined in the facility. (Detention—essential; holding—essential)
- **2–5143.** Addition, new plants. All parts of the facility that are accessible to the public are accessible to and usable by handicapped persons. (Detention—important; holding—important) (See related standard 2–5142)
- 2-5144. Addition, new plants. There is a dayroom for each cell block or detention room cluster. The room

- has a minimum of 35 square feet of floor space per inmate and is separate and distinct from the sleeping area which is immediately adjacent and accessible. (Detention—essential; holding—important)
- 2-5145. Renovation, addition, new plant. In facilities with bed space for less than 100 inmates, indoor and outdoor exercise areas provide a minimum of 15 square feet per inmate. (Detention—essential; holding—not applicable)
- **2–5146.** Renovation, addition, new plant. In facilities with bed space for 100 or more inmates, indoor and outdoor exercise areas are a minimum of 30 by 50 square feet. (Detention—essential; holding—not applicable)
- **2–5148.** Additions, new plants. Separate and adequate space is provided for all mechanical equipment. (Detention—essential; holding—essential)

For a complete copy of the ACA Standards, contact the American Correctional Association, 4321 Hartwick Road, Suite L-208, College Park, MD 20740, telephone 301–699–7600.

		·	

## Appendix B

Reference: Architects and construction managers

Firm name	Facility name	Page
Abend Singleton Associates	Clay County Detention Center	308
Abend Singleton Associates	Johnson County Juvenile Hall	248
Afseth, Jacobs & Schmitz, Architects, A.I.A.	Jackson County Jail	426
A.J. Contracting Co.	Brooklyn Correctional Facility	364
Alexander/Truex/de Groot	Franklin County Detention/Law Enforcement Facility	270
Alexander/Truex/de Groot	St. Johnsbury Community Correctional Center	542
Alpha Three	Hunt Correctional Center	264
Architects Boudreaux, Ltd.	Gilliam Psychiatric Center	450
Architectural Inspection Service	Sunnyvale Public Safety Building and Temporary Holding Facility	150
Architecture One, Ltd.	Pima County Adult Detention Center	88
Architecture One, Ltd.	Pima County Adult Detention Center (Addition)	90
Arthur Industries, Inc.	Bridgeport Correctional Center: Modular Units	172
Arthur Industries, Inc.	J. Bernard Gates Correctional Unit	174
Arthur Industries, Inc.	Rikers Island: Modular Units	382
Arthur Industries, Inc.	Southern State Correctional Facility: Modular Units (Phase I and II)	344
Barnes, Landes, Goodman and Youngblood	Beto II Unit	464
Barnes, Landes, Goodman and Youngblood	Jester Unit Number 3	502
Barnes, Landes, Goodman and Youngblood	Wallace Pack Unit I	528
Barnes, Landes, Goodman and Youngblood	Wallace Pack Unit II	530
Barrett, Daffin and Carlan, Inc.	Leon County Jail	182
Barrett, Daffin and Carlan, Inc.	Leon County Justice Complex	184
Barron, Heinberg & Brocato	Federal Detention Center	260
Benatec Associates	Schuylkill County Prison	438
B.F.W. Construction Company	Beto II Unit	464
B.F.W. Construction Company	Wallace Pack Unit I	528
Blomquist/Nelson & Associates	Correction Camp Cusino	290
Bodrell Joer' dan Smith Partnership	Elmwood—Barracks 24	110
Brice Building Company/Champion Construction Company	West Jefferson Correctional Facility	58
Brooks Association for Architecture and Planning	Brazoria County Sheriff's Department Detention Center II	468
Bruton, Knowles & Love, Inc.	Oklahoma State Penitentiary	422
Bryant Architect, Ltd.	Clarke County Correctional Institution	200
Burt Taggart & Associates/Architects	Clark County Detention Facility	90
Burt Taggart & Associates/Architects	Garland County Detention Facility	100
Burt Taggart & Associates/Architects	Saline County Detention Facility	104
Cannon Design	Erie County Holding Center	370
Carmen Vincent Gintoli	Wildwood Correctional Center	7,
Caudill Gustafson & Associates Architects, P.C.	Pitkin County Jail	•
CCC Architects Alaska	Cook Inlet Pre-Trial Facility	16
CCC Architects Alaska	Cook Inlet Pre-Trial Facility, Phase II	6
CCC Architects Alaska	Palmer Correctional Center Medium Security Facility	6: 7:
Cecil Lovett	Clay County Detention Center	
Charles H. McCauley Associates, Inc.	Federal Correctional Institution, Talladega	30
Chrisman, Miller, Woodford, Inc.		5 <sub>0</sub>
Christopher Di Stefano & Associates, Inc.	Knox County Jail	25
•	Austin County Jail	46
Christopher Di Stefano & Associates, Inc.	Cameron County Detention Center	47
Christopher Di Stefano & Associates, Inc.	Chambers County Law Enforcement Center	47
Christopher Di Stefano & Associates, Inc.	Comal County Jail	47
Christopher Di Stefano & Associates, Inc.	Fort Bend County Jail	49
Christopher Di Stefano & Associates, Inc.	Fort Bend County Jail (Expansion)	49
Christopher Di Stefano & Associates, Inc.	Freeport Police and Courts Building	49

Firm name	Facility name	Pag
Christopher Di Stefano & Associates, Inc.	Hidalgo County Jail	498
Christopher Di Stefano & Associates, Inc.	Katy Police Department	504
Christopher Di Stefano & Associates, Inc.	Liberty County Jail	508
Christopher Di Stefano & Associates, Inc.	Missouri City Police Department	510
Christopher Di Stefano & Associates, Inc.	Orange County Jail	514
Christopher Di Stefano & Associates, Inc.	Pearland Public Safety Building	510
Christopher Di Stefano & Associates, Inc.	San Patricio County Sheriff's Department	518
Christopher Di Stefano & Associates, Inc.	Starr County Jail	522
Christopher Di Stefano & Associates, Inc.	Victoria County Jail	526
Cimini Meric Burns Counce	Washington Correctional Institute	268
Con-Ark Construction Company	Cummins Unit—Medium Security	98
Concordia	Jackson County Detention Center	314
Construction Analysis & Management	Burnett County Government Center	570
Crippen, Lichau, Minta	Placer County Jail	128
Crosby, Thornton, Marshall, Booker, Lawlor, Architects	Stanislaus County Jail	148
CRS Constructors, Inc.	Fulton Reception and Diagnostic Center, Phase I	312
CRS Group	Federal Correctional Institution, Bastrop	486
CUH2A Architects, Engineers, Planners	Southern State Correctional Facility: Modular Units (Phase I and II)	344
Curtis and Davis	Nebraska State Penitentiary	332
Dahl-Braden-PTM, Inc.	Beto II Unit	464
Dahl-Braden-PTM, Inc.	Jester Unit Number 3	502
Dahl-Braden-PTM, Inc.	Lew Sterrett Justice Center	506
Dahl-Braden-PTM, Inc.	Wallace Pack Unit I	528
Dahl-Braden-PTM, Inc.	Wallace Pack Unit II	530
Dana Larson Roubal & Associates	Delta County Criminal Justice Facility	164
Dana Larson Roubal & Associates	Dodge County Judicial Center	328
Dana Larson Roubal & Associates	Woodbury Law Enforcement Center	246
Dana Larson Roubal & Associates/DLR Group	Yellowstone County Detention Facility	326
Dana Larson Roubal/Lescher & Mahoney, Inc.	Douglas County Correctional Center	330
Davidson/Kuhr Architects PC	Lewis and Clark County Criminal Justice Facility	322
Davis Brody and Associates	Federal Correctional Institution, Otisville	372
Day and Zimmerman	Gerald L. Gormley Justice Facility	338
Design Concrete, Inc.	Dooly County Jail	202
Design Group, Inc., Architects/Planners	Federal Correctional Institution, Ashland	254
Dewberry & Davis	Eastern Correctional Institution	270
Dewberry & Davis	Somerset County Detention Center	282
Dick Corporation	Allegheny County Jail Annex	430
DLR Group/Lescher and Mahoney	Pinal Mountain Juvenile Institution	92
Donham & Sweeney, Architects	Massachusetts Correctional Institution Norfolk	288
Dreyfuss and Blackford	California State Prison—Sacramento County/Folsom	112
Durrant Group	Grand Traverse County Correctional Facility	292
Edward Mattingly Associates, Inc.	Fayette County Detention Center	484
E. George Wynn—Architect	Alamosa County Law Enforcement Center	160
Ellerbe Associates, Inc.	Hennepin County Juvenile Detention Center	29
Facilities Development Corporation	Kirby Forensic Psychiatric Center	370
F.D. Freeman & Associates	Mountain View Unit	51:
Federal Bureau of Prisons	Federal Correctional Institution, Tucson	80
Federal Construction Company	Union Correctional Institution	198
FEH Associates, Inc.	Polk County Jail	244
Fernandez, Lujan, Beltran, Inc.	Youth Diagnostic and Development Center	360
		200

Firm name	Facility name	Page
Ficker & Ruffing	Orange County Sheriff's Intake Release Center	126
Flad & Associates	Alachua County Corrections Facility	178
Franz Zwolensky Associates, Architecture/Planning	Sacaton Juvenile Rehabilitation Center	94
Gary/Parsons & Associates	Mountain View Unit	512
GBKB Associates	Grand Traverse County Correctional Facility	292
Geary, Moore and Ahrens, Inc.	Ottawa County Detention Facility	404
G.E. Johnson Construction Company	Arkansas Valley Correctional Facility	162
George Dahl, Architects & Engineers	Coffield Unit	474
Geren and Associates	Beto I Unit	462
Giattina Fisher & Company Architects, Inc.	Jefferson County Jail	56
Giffels/Del Campo & Maru	California Medical Facility—South	110
Gilbane Building Company	Federal Correctional Institution, Ray Brook	374
Gilbane Building Company	Leon County Justice Complex	184
Glaser & Myers, Inc., Champlin/Haupt, Inc.	Hamilton County Justice Complex	396
Goleman & Rolfe Associates, Inc.	Bexar County Juvenile Center	466
Goleman & Rolfe Associates, Inc.	Harris County Juvenile Detention Home	496
Gonchor & Sput Architects & Planners	North Facility	380
Greenhorne & O'Mara	Prince George's County Correctional Center	280
Grier-Fripp Associates, Inc.	Eastern Correctional Center	386
Grier-Fripp Associates, Inc.	Southern Correctional Center	390
Grinder, Taber and Grinder, Inc.	Shelby County Justice Center	458
Grover Tuten	Dooly County Jail	202
Hammel Green & Abrahamson, Inc.	Minnesota Supervised Living Facility	300
Hancock Property Management, Inc.	Longwood Treatment Center	286
Hansen Lind Meyer P.C.	Union Correctional Institution	198
Harold Wirum & Associates	Fairbanks Correctional Center	64
Harold Wirum & Associates	Hiland Mountain Correctional Center	66
Harold Wirum & Associates	Meadow Creek Correctional Center	7(
Harold Wirum & Associates	Yukon-Kuskokwim Correctional Center	76
Hayes, Seay, Mattern and Mattern	Roanoke City Jail	552
Heery Program Management, Inc.	Baltimore City Correctional Center	272
Heery Program Management, Inc.	Eastern Correctional Institution	276
Heery Program Management, Inc.	Somerset County Detention Center	282
Heery/Vanir CM	California State Prison—Sacramento County/Folsom	112
Heery/Vanir CM	Richard J. Donovan Correctional Facility at Rock Mountain	
Heery/VCM	California Correctional Institution	134 103
Hellmuth, Obata & Kassabaum, Inc.	Alameda County North County Jail	
Hellmuth, Obata & Kassabaum, Inc.	Bernalillo County Detention Center (South Tower)	100 350
Hellmuth, Obata & Kassabaum, Inc.	Clark County Detention Center (South Tower)	334
Hellmuth, Obata & Kassabaum, Inc.	Cook Inlet Pre-Trial Facility	
Hellmuth, Obata & Kassabaum, Inc.	Macomb County Jail	60
Hellmuth, Obata & Kassabaum, Inc.	Missouri Eastern Correctional Center	294
Hellmuth, Obata & Kassabaum, Inc.	Montgomery County Detention Center	31 <sub>0</sub> 27
Hellmuth, Obata & Kassabaum, Inc.	North Carolina Central Prison	
		38
Hellmuth, Obata & Kassabaum, Inc.	Orange County Sheriff's Intake Release Center	12
Hellmuth, Obata & Kassabaum, Inc.	Richmond County Law Enforcement and Justice Center	20 14
Hellmuth, Obata & Kassabaum, Inc.	Shasta County Justice Center	
Hellmuth, Obata & Kassabaum, Inc.	Twin Rivers Corrections Center	56
Hellmuth, Obata & Kassabaum, Inc.	Washington County Detention Center	28
Henningson, Durham, & Richardson, Inc.	California State Prison—Sacramento County/Folsom	11

Firm name	Facility name	Page
Henningson, Durham, & Richardson, Inc.	Fairfax County Adult Detention Center and Pre-Release Center	548
Henningson, Durham, & Richardson, Inc.	Ocean County Justice Complex	342
Henningson, Durham, & Richardson, Inc.	Young Adult Correctional Facility	538
Hercules Construction Company	Farmington Correctional Center	310
H. Holding and Associates	Arkansas Valley Correctional Facility	162
HMC Architects, Inc.	Foothill Communities Law & Justice Center	118
Hobbs/Wiginton/Fawcett—Architects & Planners	Hunt County Criminal Justice Center	500
Hope Consulting Group	Richard J. Donovan Correctional Facility at Rock Mountain	134
Hope Consulting Group	Sequoia Field Detention Facility	142
Horst-Terrill-Karst, Architects, P.A.	Kansas State Penitentiary (Phase One)	250
Hutchinson, Brown & Partners	Penitentiary of New Mexico	354
H. Wendell Mounce AIA & Associates	Torrance Police Department	152
Jacobs Wyper	Philadelphia Industrial Correctional Center	436
Jesson & Associates	TDC Hospital at Galveston	524
Jim Roberson & Associates, Inc.	Federal Correctional Institution, Tallahassee	180
J.N. Pease Associates	Craven County Law Enforcement Center	384
J.N. Pease Associates	North Carolina Central Prison	388
John Carl Warnecke & Associates/Daniel L. Dworsky FAIA &		
Associates	Pre-Trial Detention Facility	132
John Hackler and Company, Architects	Peoria County Adult Detention and Work Release Facility	232
John W. Cowper Company	Erie County Correctional Facility	368
Johnston/Hunt & Associates, P.S.	Jefferson County Correctional Facility	558
Johnston/Hunt & Associates, P.S.	Forks City Jail	556
Johnston Associates	Forks City Jail	556
Johnston Associates	Jefferson County Correctional Facility	558
Jones Mayer Architecture, Inc.	Farmington Correctional Center	310
Jose Barron, Jr.	Federal Detention Center	260
Justice Center Architects	Lew Sterrett Justice Center	506
Justice Systems, Inc.	Adams County Detention Facility	158
Justice Systems, Inc.	Marion County Detention Center	186
Kaplan/McLaughlin/Diaz	Contra Costa County Detention Facility	114
Kaplan/McLaughlin/Diaz	Santa Cruz County Jail (Phase I)	140
Kitchell, CEM, Inc.	Arizona State Prison—Perryville	80
Kitchell, CEM, Inc.	Lacy Security Facility	122
Kitchell, CEM, Inc.	Orange County Sheriff's Intake Release Center	126
Kitchell, CEM, Inc.	Pima County Adult Detention Center	88
Kitchell, CEM, Inc.	Sequoia Field Detention Facility	142
Lasker Goldman Corporation	Federal Correctional Institution, Otisville	372
Lasker Goldman Corporation	Federal Correctional Institution, Talladega	5/2
Lasseigne & Legett, AIA, Architects, Inc.	Feliciana Forensic Facility	262
Lawrence D. White & Associates, Inc.	Ellis II Unit (Phase I and II)	482
Lawrence D. White & Associates, Inc.	Ferguson Unit	488
L.D. Astorino & Associates, Ltd.	State Regional Correctional Facility at Mercer	442
Lebco Construction Company	Diagnostic Unit	480
Leo A. Daly	Nebraska State Penitentiary	
Lescher & Mahoney/DLR Group	Yellowstone County Detention Facility	33: 32:
Lescher & Mahoney, Inc.	Cochise County Jail	8:
Lescher & Mahoney, Inc. Lescher & Mahoney, Inc.	Federal Correctional Institution, Phoenix	84
-	Lieber Correctional Institution	
Lescher & Mahoney, Inc.		45: 46:
L.K. Travis & Associates	Bexar County Juvenile Center	400

Firm name	Facility name	Page
Louis G. Redstone Associates, Inc.	State Prison of Southern Michigan	296
Louis P. Batson III, Arch. Inc.	Clemson Police Department	448
L. Robert Kimball & Associates	Allegheny County Jail Annex	430
L. Robert Kimball & Associates	Blair County Prison	432
L. Robert Kimball & Associates	Lycoming County Prison	434
L. Robert Kimball & Associates	Warren County Correctional Center	348
L. Robert Kimball & Associates	Warren County Jail	444
L. Robert Kimball & Associates	Wyoming County Jail	446
LZT Associates, Inc.	Peoria County Adult Detention and Work Release Facility	232
Maguire Group Architects	Prince George's County Correctional Center	280
Mahan and Shappley Architects, Inc.	Shelby County Justice Center	458
Massachusetts Department of Correction	Longwood Treatment Center	286
McBro Planning & Development	Missouri Eastern Correctional Center	316
McCool-McDonald of Alaska, Inc.	Mat-su Pre-Trial Facility	68
McGuire & Shook Architects	Marion County Jail	242
McKee/Mays, A Joint Venture	Lew Sterrett Justice Center	506
McNair, Johnson and Associates	Lieber Correctional Institution	452
MDF Detention/Corrections Facilities, Inc.	Garfield County Jail	166
M & E/CM	Foothill Communities Law & Justice Center	118
Mellon-Stuart Company	Richmond County Law Enforcement and Justice Center	204
Mellon-Stuart Company	Schuylkill County Prison	438
Metric Constructors, Inc.	North Carolina Central Prison	388
M.G. Turner and Associates	Dooly County Jail	202
M. Hill Company	Shasta County Justice Center	144
Michael R. Eiben AIA	Cook County Medical and Psychiatric Facility—RTU Building	210
Miller Levine Architects, P.C.	Yellowstone County Detention Facility	326
Miller Wagner Coenen, Inc.	Oshkosh Correctional Institution	574
Milstein, Wittek & Associates, Architects, P.C.	Erie County Correctional Facility	368
Milstein, Wittek & Associates, Architects, P.C.	Masten Park Secure Center	378
Molen, Huss, Money, Fuller, Architects	Orange Street Community Correctional Center	534
Molen, Huss, Money, Fuller, Architects	Uintah County Jail	536
Moody/Nolan Ltd.	Ohio Reformatory for Women	402
Morrison-Knudsen Company, Inc.	Adams County Detention Facility	158
Morrison-Knudsen Company, Inc.	Elmwood—Barracks 24	116
Morrison-Knudsen Company, Inc.	North Facility	380
Morrison-Knudsen Company, Inc.	Southern New Mexico Correctional Facility	356
Morrison-Knudsen/Parametric Co.	Philadelphia Industrial Correctional Center	436
Morrison-Knudsen/Parametric Co.	Prince George's County Correctional Center	280
Nelson Salabes	Baltimore City Correctional Center	272
Newman and Grace Architects, Inc.	Dixon Correctional Institute	258
Newman and Grace Architects, Inc.	Louisiana Correctional Institute for Women	266
Newstrom-Davis	Pitkin County Jail	168
North Texas Construction Company	Hunt County Criminal Justice Center	500
Northwest Architectural Company	Whitman County Correctional Facility	566
O'Brien Kreitzberg Associates	California Medical Facility—South	110
Omni Signal, Inc.	Maui Community Correctional Center	206
O'Neill, Conrad, Oppelt & Joneskell, Inc.	Diagnostic Unit	480
Ozolins-D'Jock Architects, Ltd.	Burnett County Government Center	570
Ozolins-D'Jock Architects, Ltd.	Rusk County Law Enforcement Facility	576
Ozolins-D'Jock Associates	Rusk County Law Enforcement Facility	576

Page Southerland Page         Snith County Jail         520           Page Wermer & Partners         Choutean County Law Enforcement Facility         318           Page Wermer, P. C.         Pondera County Jail and Sheriff's Department         218           Patrick + Associates, Inc.         Jackson County Jail and Office Complex         318           Patrick + Associates, Inc.         Logan County Jail and Office Complex         398           Patrick + Associates, Inc.         Madison Correctional Institution         400           Patrick Sullivan Associates         Kings County Branch Jail         120           Patrick Sullivan Associates         Plumas County, Sheriff's Department & Detention Facility         130           Patrick Sullivan Associates         Plumas County, Sheriff's Department & Detention Facility         130           Patrick Sullivan Associates         Tuolume County Jail         134           Patrick Sullivan Associates         Yuba County Jail         155           Patrick Sullivan Associates         Yuba County Jail         156           Petro Constructors         Martin Correctional Institution         180           Petre Brown Company         Pinclias County Jail         156           Petro Brown Company         Pinclias County Jail         244           Phillips Swager Associates         Marian Correction	Firm name	Facility name	Page
Page - Wemer & Partners         Chouteau County Law Enforcement Facility         318           Page - Wemer P. P. C.         Ponders County Jail         324           Patrick + Associates, Inc.         DuPage County Jail and Sherrif's Department         218           Patrick + Associates, Inc.         Jackson County Detention Center         314           Patrick + Associates, Inc.         Madison Correctional Institution         400           Patrick Sullivan Associates         King County Branch Jail         120           Patrick Sullivan Associates         Nevada County Detention Center         124           Patrick Sullivan Associates         Plumas County Sherrif's Department & Detention Facility         130           Patrick Sullivan Associates         Plumas County Sherrif's Department & Detention Facility         130           Patrick Sullivan Associates         Plumas County Sherrif's Department & Detention Facility         130           Patrick Sullivan Associates         Plumas County Mail         136           Patrick Sullivan Associates         Plumas County Sherrif's Department & Detention Facility         130           Patrick Sullivan Associates         Plumas County Sherrif's Department & Detention Facility         136           Patrick Sullivan Associates         Plumas County Sali         136           Patrick Sullivan Associates         Plumas County Sali S	Page Southerland Page	Beto I Unit	462
Page-Wemer, P. C.         Pondera County Jail         324           Patrick + Associates, Inc.         DuPage County Jail and Sheriff's Department         218           Patrick + Associates, Inc.         Jackson County Detention Center         314           Patrick + Associates, Inc.         Logan County Jail and Office Complex         398           Patrick Sullivan Associates         Kings County Branch Jail         120           Patrick Sullivan Associates         Nevada County Detention Center         124           Patrick Sullivan Associates         Plumas County Sheriff's Department & Detention Facility         130           Patrick Sullivan Associates         Plumas County Sheriff's Department & Detention Facility         130           Patrick Sullivan Associates         Plumas County Jail         134           Patrick Sullivan Associates         Yuba County Jail         156           Patrick Sullivan Associates         Yuba County Jail         156           Percon Constructors         Martin Correctional Institution         188           Percon Constructors         Martin Correctional Institution         189           Peter Brown Company         Pinellas County Jail—Medium Security Facility         190           Peter Brown Company         Pinellas County Jail—Medium Security Facility         190           Phillips Swager Associates </td <td>Page Southerland Page</td> <td>Smith County Jail</td> <td>520</td>	Page Southerland Page	Smith County Jail	520
Parick   Associates, Inc.   DaPage County Jail and Sheriff's Department   218	Page-Werner & Partners	Chouteau County Law Enforcement Facility	318
Parrick   Associates, Inc.   Jackson County Detention Center   314	Page-Werner, P.C.	Pondera County Jail	324
Parrick   Associates, Inc.   Jackson County Detention Center   314	Patrick + Associates, Inc.	DuPage County Jail and Sheriff's Department	218
Patrick Associates, Inc.   Madison Correctional Institution   400	Patrick + Associates, Inc.		314
Parrick Sullivan Associates Puratick Sullivan Associates Nevada County Detention Center Patrick Sullivan Associates Plumas County Sheriff's Department & Detention Facility 134 Patrick Sullivan Associates Plumas County Main Jail 135 Patrick Sullivan Associates Tuolumae County Jail 136 Patrick Sullivan Associates Tuolume County Jail 137 Patrick Sullivan Associates Tuolume County Jail 138 Patrick Sullivan Associates 139 Paul M. Johnson—Architect Nashville Community Service Center Percon Constructors Martin Correctional Institution 188 Peter Brown Company Pitellas County Jail—Medium Security Facility 190 Peter Witter, Architects Summit County Justice Center 170 Phillips Swager Associates 170	Patrick + Associates, Inc.	Logan County Jail and Office Complex	398
Patrick Sullivan Associates	Patrick + Associates, Inc.	Madison Correctional Institution	400
Patrick Sullivan Associates	Patrick Sullivan Associates	Kings County Branch Jail	120
Plumas County Sherif's Department & Detention Facility 130 Patrick Sullivan Associates Santa Barbara County Main Jail 138 Patrick Sullivan Associates Tuolumne County Jail 154 Patrick Sullivan Associates Yuba County Jail 155 Patrick Sullivan Associates Yuba County Jail 156 Patrick Sullivan Associates Yuba County Jail 256 Percon Constructors Martin Correctional Institution 188 Peter Brown Company Pinellas County Jail—Medium Security Facility 190 Peter Witter, Architects Summit County Jail—Medium Security Facility 190 Peter Witter, Architects Summit County Jail—Medium Security Facility 190 Phillips Swager Associates Alexandria Detention Center 170 Phillips Swager Associates Alexandria Detention Center 170 Phillips Swager Associates Marion County Jail 224 Phillips Swager Associates Marion County Jail 224 Phillips Swager Associates Nock Island County Jail 224 Phillips Swager Associates Shawnee Correctional Center 226 Phillips Swager Associates Shawnee Correctional Center 226 Phillips Swager Associates Westside Police Area Command Station 236 Phillips Swager Associates Westside Police Area Command Station 237 Phillips Swager Associates Westside Police Area Command Station 237 Phillips Polson Architects, Inc. Santa Rosa County Jail 224 Polson Architects Inc. Seminole County Jail 226 Polter, Lawson & Pawlowsky, Inc. Columbia Correctional Institution 237 Pritch and & Nickles, Engineers/Planners 7 Prince Design, Inc. Seminole County Correctional Escality 236 Pritch and A Nickles, Engineers/Planners 7 Prince Design, Inc. Seminole County Correctional Escality 236 Rese Associates, Inc. Rese Associates Inc. Rese Rese Associa	Patrick Sullivan Associates	-	124
Patrick Sullivan Associates Publ M. Johnson—Architect Patrick Sullivan Associates Publ M. Johnson—Architect Patrick Sullivan Associates Peter Brown Company Peter Witter, Architects Peter Brown Company Pinellas County Jail—Medium Security Facility 190 Peter Witter, Architects Summit County Justice Center Phillips Swager Associates A lexandria Detention Center A lexandria Detention Center Phillips Swager Associates A lexandria County Jail Phillips Swager Associates A lexandria County Detinion Center Phillips Swager Associates A lexandria County Detinion Center Phillips Swager Associates A lexandria County Detention Center Phillips Swager Associates A lexandria County Detention Center Phillips Swager Associates A lexandria County Detention Center Phillips Swager Associates A lexandria Rosa County Jail and Sheriff's Department Prince Design, Inc. Seminole County Correctional Institution Pritchard & Nickles Pritchard & Rickles, Engineers/Planners Tunica County Jail and Sheriff's Department Rosa Rosa County Jail and Sheriff's Department Rosa Rosa Rosa County Jail and Sheriff's Department Rosa Rosa Rosa County Jail and Sheriff's Department Rosa Rosa Rosa Rosa Rosa Rosa Rosa Rosa	Patrick Sullivan Associates		130
Patrick Sullivan Associates Yuba County Jail 154 Patrick Sullivan Associates Yuba County Jail 156 Paul M. Johnson—Architect Nashville Community Service Center Associates Percon Constructors Martin Correctional Institution 188 Peter Brown Company Peter Witter, Architects Summit County Justi—Medium Security Facility 190 Peter Witter, Architects Summit County Justi—Medium Security Facility 190 Peter Witter, Architects Summit County Justi—Medium Security Facility 190 Peter Witter, Architects Summit County Justice Center 170 Phillips Swager Associates Alexandria Detention Center 544 Phillips Swager Associates Alexandria Detention Center Phillips Swager Associates Marion County Jail 242 Phillips Swager Associates Rock Island County Jail 243 Phillips Swager Associates Rock Island County Jail 244 Phillips Swager Associates Shawnee Correctional Center 285 Phillips Swager Associates Somerset County Detention Center 286 Phillips Swager Associates Westside Police Area Command Station 532 Phillips Swager Associates Westside Police Area Command Station 532 Phillips Swager Associates Westside Police Area Command Station 532 Polson Architects Douglas County Jail 216 Potter, Lawson & Pawlowsky, Inc. Columbia Correctional Institution 532 Pritter Design, Inc. Seminole County Correctional Institution 534 Pritchard & Nickles Tunica County Jail and Sheriff's Department 336 Pritchard & Nickles, Engineers/Planners Tunica County Jail and Sheriff's Department 336 Pritchard & Nickles, Engineers/Planners Lawson & Freich & Krause, Architects/Engineers Elmira Correctional & Reception Center Food Service & Dining Facility 346 Rese Associates, Inc. Cleveland County Detention Facility 412 Rese Associates, Inc. Cleveland County Detention Facility 412 Reses Associates, Inc. Checkes Associates, Inc. Checkes Associates and Ashabalus County Justice Center 436 Robert P. Madison International 436 Robert P. Madison International 447 Roseer B. Muse County Justice Center 448 Roser White Hobbs Davidson McClellan & Kelly, Inc. 449 Roser White Hobbs Davids	Patrick Sullivan Associates		138
Patrick Sullivan Associates Yuba County Jaii Alphanom—Architect Nashville Community Service Center Ashville Community Service Center Martin Correctional Institution 188 Peter Brown Company Pinellas County Jail—Medium Security Facility 190 Peter Witter, Architects Summit County Justice Center 170 Phillips Swager Associates Alexandria Detention Center Alexandria Det	Patrick Sullivan Associates	•	154
Paul M, Johnson—Architect Percon Constructors Martin Correctional Institution 188 Peter Brown Company Pinellas County Jail—Meditum Security Facility 190 Peter Witter, Architects Summit County Justice Center 170 Phillips Swager Associates Alexandria Detention Center Eastern Correctional Institution 276 Phillips Swager Associates Alexandria Detention Center Eastern Correctional Institution 276 Phillips Swager Associates Marion County Jail 242 Phillips Swager Associates Marion County Jail 243 Phillips Swager Associates Marion County Jail 244 Phillips Swager Associates Marion County Jail 245 Phillips Swager Associates Shawnec Correctional Center 246 Phillips Swager Associates Shawnec Correctional Center 247 Phillips Swager Associates Somerset County Detention Center 248 Phillips Swager Associates Somerset County Detention Center 249 Phillips Swager Associates Somerset County Jeain 257 Phillips Swager Associates Westside Police Area Command Station 257 Phillips Swager Associates Somerset County Jail 258 Polster, Lawson & Pawlowsky, Inc. Columbia Correctional Institution 257 Prime Design, Inc. Seminole County Jail and Sheriff's Department 360 Polter, Lawson & Pawlowsky, Inc. Columbia Correctional Reciption Center Food Service 360 Pritchard & Nickles, Engineers/Planners Tunica County Jail and Sheriff's Department 360 Quinlivan Pierik & Krause, Architects/Engineers Elmira Correctional & Reception Center Food Service 360 Ralph Allen and Partners A Dining Facility 366 Ralph Allen and Partners A Dining Facility 367 Rese Associates, Inc. A Devention Facility 367 Rese Associates, Inc. A Devention Facility 368 Reses-Carr Cochise County Jail 368 Reses-Carr A Cochise County Jail 369 Reses-Carr A Cochise County Jail 360 Reses-Associates, Inc. A Mabel Bassett Correctional Center 460 Reses-Carr 460 Reses-Carr 460 Reses-Carr 460 Reses-Carr 460 R	Patrick Sullivan Associates	•	156
Percon Constructors Martin Correctional Institution Peter Witter, Architects Summit County Justice Center 170 Phillips Swager Associates Alexandria Detention Center 170 Phillips Swager Associates Anion County Jail 172 Phillips Swager Associates Anion County Jail 172 Phillips Swager Associates Anion County Jail 173 Phillips Swager Associates Anion County Jail 174 Phillips Swager Associates Anion County Jail 175 Potter, Lawson & Pawlowsky, Inc. Anion County Jail 175 Potter, Lawson & Pawlowsky, Inc. Anion County Jail 175 Potter, Lawson & Pawlowsky, Inc. Anion County Jail Anion Sheriff's Department 176 Potter, Lawson & Pawlowsky, Inc. Anion County Jail and Sheriff's Department 177 Phillips Architects Anion Architects Anion Partners Anion Architects/Engineers Anion Archit	Paul M. Johnson—Architect	•	456
Peter Witter, Architects Summit County Justice Center 170 Phillips Swager Associates Alexandria Detention Center 544 Phillips Swager Associates Hillips Swager Associates Marion County Jail 242 Phillips Swager Associates Marion County Jail 243 Phillips Swager Associates Rock Island County Jail 243 Phillips Swager Associates Shawnee Correctional Center 236 Phillips Swager Associates Somerset County Detention Center 236 Phillips Swager Associates Somerset County Detention Center 237 Phillips Swager Associates Phillips Swager Associates Somerset County Detention Center 238 Phillips Swager Associates Phillips Swager Associates Phillips Swager Associates Somerset County Detention Center 238 Phillips Swager Associates Somerset County Detention Center Santa Rosa County Jail Polter Lawson & Pawlowsky, Inc. Polter Lawson & Pawlowsky, Inc. Pollogias County Jail and Sheriff's Department Some Pritchard & Nickles, Engineers/Planners Tunica County Jail and Sheriff's Department Social Sheriff's Department Social Sheriff's Department Social Sheriff's Department County Jail and Sheriff's Department Social Sheriff's Department County Jail and Sheriff's Department County Jail County Jail and Sheriff's Department County Jail County Jail County Jail County Jail C	Percon Constructors		188
Phillips Swager Associates	Peter Brown Company	Pinellas County Jail—Medium Security Facility	190
Phillips Swager Associates  Eastern Correctional Institution  276 Phillips Swager Associates  Marion County Jail  242 Phillips Swager Associates  Rock Island County Jail  243 Phillips Swager Associates  Shawnee Correctional Center  286 Phillips Swager Associates  Shawnee Correctional Center  287 Phillips Swager Associates  Somerset County Detention Center  288 Phillips Swager Associates  Westside Police Area Command Station  539 PH & J Architects, Inc.  Santa Rosa County Jail  291 Polson Architects  Douglas County Jail  201 Potter, Lawson & Pawlowsky, Inc.  Columbia Correctional Institution  572 Prime Design, Inc.  Seminole County Correctional Facility  Pritchard & Nickles  Pritchard & Nickles, Engineers/Planners  Quinlivan Pierik & Krause, Architects/Engineers  Elmira Correctional & Reception Center Food Service  & Dining Facility  202 Ralph Allen and Partners  Lacy Security Pacility  103 Rees Associates, Inc.  Cleveland County Detention Center  410 Rees Associates, Inc.  Cleveland County Detention Facility  412 Rees Associates, Inc.  Mabel Bassett Correctional Center  68 Reese-Carr  Cochise County Jail  Arkansas Valley Correctional Facility  162 Robert P. Madison International  Ashtabula County Justice Center  408 Rosser White Hobbs Davidson McClellan & Kelly, Inc.  Marion County Justice Center  80 Rosser White Hobbs Davidson McClellan & Kelly, Inc.  80 Roth Florida Reception Center  81 Roth Control of Center  82 Pritchard & Nickles  83 Rosser White Hobbs Davidson McClellan & Kelly, Inc.  84 Roth County Detention Center  85 Roth County Correction Center  86 Roth County Correction Center  87 Rosser White Hobbs Davidson McClellan & Kelly, Inc.  87 Roth Florida Reception Center  88 Roth County Detention Center  89 Roth County Detention Center  80 Roth County Detention Center  80 Roth County Detention Center  80 Roth P. Madison International  80 Roth P. Madison International  81 Roth County Detention Center  81 Rosser White Hobbs Davidson McClellan & Kelly, Inc.  81 Roth Florida Reception Center  81 Roth County D	Peter Witter, Architects		170
Phillips Swager Associates  Phillips Swager Associates  Marion County Jail  242  Phillips Swager Associates  Rock Island County Jail  233  Phillips Swager Associates  Shawnee Correctional Center  236  Phillips Swager Associates  Shawnee Correctional Center  237  Phillips Swager Associates  Shawnee Correctional Center  238  Phillips Swager Associates  Westside Police Area Command Station  332  PH & J Architects, Inc.  Santa Rosa County Jail  234  Polson Architects  Douglas County Jail  236  Potter, Lawson & Pawlowsky, Inc.  Prince Design, Inc.  Seminole County Correctional Pacility  Pritchard & Nickles  Tunica County Jail and Sheriff's Department  306  Pritchard & Nickles, Engineers/Planners  Tunica County Jail and Sheriff's Department  306  Pritchard & Nickles, Engineers/Planners  Tunica County Jail and Sheriff's Department  306  Pritchard & Nickles, Engineers/Planners  Tunica County Jail and Sheriff's Department  306  Pritchard & Nickles, Engineers/Planners  Tunica County Jail and Sheriff's Department  306  Pritchard & Nickles, Engineers/Planners  Tunica County Jail and Sheriff's Department  306  Pritchard & Nickles, Engineers/Planners  Culveland County Jail and Sheriff's Department  306  Ralph Allen and Partners  Lacy Security Facility  122  Rees Associates, Inc.  Mabel Bassett Correctional Center  418  Reese-Carr  Cochise County Jail  Reese-Carr  Cochise County Jail  Reese-Carr  Pima County Adult Detention Center (Addition)  307  Reese-Carr  Pima County Adult Detention Center (Addition)  308  Rull Detention International  Ashabula County Justice Center  408  Robert P. Madison International  Ashabula County Justice Center  408  Roser White Hobbs Davidson McClellan & Kelly, Inc.  Marion County Detention Center  Rullin C	Phillips Swager Associates	Alexandria Detention Center	544
Phillips Swager Associates Rock Island County Jail Phillips Swager Associates Rock Island County Jail Phillips Swager Associates Rock Island County Detention Center Robilips Swager Associates Phillips Swager Associates Somerset County Detention Center Robilips Swager Associates Phillips Swager Associates Westside Police Area Command Station Station Station Phillips Swager Associates Westside Police Area Command Station Station Phillips Swager Associates Westside Police Area Command Station Station Station Santa Rosa County Jail Police Area Command Station Station Santa Rosa County Jail Police Area Command Station Station Station Santa Rosa County Jail Police Area Command Station Station Station Station Station Station Seminole County Jail Robert Speartment Some Pawlowsky, Inc. Columbia Correctional Institution Station Seminole County Correctional Facility Incidence An Nickles Pritchard & Nickles Pritchard & Nickles, Engineers/Planners Tunica County Jail and Sheriff's Department Some Pritchard & Nickles, Engineers/Planners Tunica County Jail and Sheriff's Department Some Pritchard & Nickles, Engineers/Planners Tunica County Jail and Sheriff's Department Some Pritchard & Nickles, Engineers/Planners Tunica County Jail and Sheriff's Department Some Sheather Station Some Sheather Sheather Station Some Sheather Hobbs Davidson McClellan & Kelly, Inc. Marion County Dustice Center South Florida Reception Center		Eastern Correctional Institution	
Phillips Swager Associates Rock Island County Jail 234 Phillips Swager Associates Shawnee Correctional Center 236 Phillips Swager Associates Somerset County Detention Center 288 Phillips Swager Associates Westside Police Area Command Station 532 PH & J Architects, Inc. Santa Rosa County Jail Polson Architects Douglas County Jail Polson Architects Douglas County Jail Potter, Lawson & Pawlowsky, Inc. Columbia Correctional Institution 572 Prime Design, Inc. Seminole County Correctional Facility 194 Pritchard & Nickles Tunica County Jail and Sheriff's Department 306 Quinlivan Pierik & Krause, Architects/Engineers Elmira Correctional & Reception Center Food Service & Dining Facility 366 Ralph Allen and Partners Lacy Security Facility 122 Rees Associates, Inc. Cleveland County Detention Center 410 Rees Associates, Inc. Mabel Bassett Correctional Center 411 Reese-Carr Cochise County Jail Reese-Carr Pima County Jail and Sheriff's Department 418 Reese-Carr Cochise County Detention Facility 328 Reese-Carr Pima County Detention Facility 340 Reese-Carr Cochise County Jail 341 Reese-Carr Cochise County Jail 342 Reese-Carr Pima County Adult Detention Center (Addition) 343 Reese-Carr Pima County Adult Detention Center (Addition) 344 Reese-Carr No Cochise County Jail 345 Reese-Carr Pima County Adult Detention Reality 346 Robert P. Madison International Ashtabula County Justice Center 347 Robert P. Madison International Wayne County Justice Center 348 Robert P. Madison International Wayne County Justice Center 348 Roser Robert P. Madison International Wayne County Justice Center 349 Roser Robert P. Madison International Wayne County Justice Center 340 Roser Roser White Hobbs Davidson McClellan & Kelly, Inc. Marion County Detention Center 340 Roser White Hobbs Davidson McClellan & Kelly, Inc. 340 Roser White Hobbs Davidson McClellan & Kelly, Inc. 341 Roser Hotel Forensic Psychiatric Center 342 Roser Robert P. Mathabula County Justice Center 344 Roser Roser White Hobbs Davidson McClellan & Kelly, Inc. 344 Roser Hotel Forensic Psy		Marion County Jail	
Phillips Swager Associates Shawnee Correctional Center 236 Phillips Swager Associates Somerset County Detention Center 237 Phillips Swager Associates Westside Police Area Command Station S32 PH & J Architects, Inc. Santa Rosa County Jail 216 Potter, Lawson & Pawlowsky, Inc. Columbia Correctional Institution S77 Prime Design, Inc. Seminole County Correctional Facility 194 Pritchard & Nickles Tunica County Jail and Sheriff's Department 306 Pritchard & Nickles, Engineers/Planners Tunica County Jail and Sheriff's Department 306 Pritchard & Nickles, Engineers/Planners Pritchard & Rickles, Engineers/Planners Uniting Correctional & Reception Center Food Service & Dining Facility 122 Rees Associates, Inc. Cleveland County Detention Center 416 Rees Associates, Inc. Kay County Detention Facility 412 Rees Associates, Inc. Mabel Bassett Correctional Center 418 Reese-Carr Cochise County Jail Reese-Carr Pima County Adult Detention Center 418 Reese-Carr Pima County Adult Detention Center 418 Reese-Carr Pima County Correctional Center 56 RNL Design Arkansas Valley Correctional Facility 162 Robert P. Madison International Ashtabula County Justice Center 48 Robert P. Madison International Ashtabula County Justice Center 48 Roser Roser White Hobbs Davidson McClellan & Kelly, Inc. Rosser White Hobbs Davidson McClellan & Kelly, Inc. Rosser White Hobbs Davidson McClellan & Kelly, Inc. Rosser White Hobbs Davidson McClellan & Kelly, Inc. South Florida Reception Center 48 South Florida Reception Center		•	234
Phillips Swager Associates  Phillips Swager Associates  Westside Police Area Command Station  532 Phillips Swager Associates  Westside Police Area Command Station  538 PH & J Architects, Inc.  Santa Rosa County Jail  216 Potter, Lawson & Pawlowsky, Inc.  Columbia Correctional Institution  572 Prime Design, Inc.  Prime Design, Inc.  Pritchard & Nickles  Pritchard & Nickles, Engineers/Planners  Quinlivan Pierik & Krause, Architects/Engineers  Elmira Correctional & Reception Center Food Service  & Dining Facility  326 Ralph Allen and Partners  Lacy Security Facility  127 Rees Associates, Inc.  Cleveland County Detention Center  416 Reese-Carr  Cochise County Jail  Reese-Carr  Pima County Jail and Sherriff so Peartment  427 Reese-Carr  Pima County Detention Facility  428 Reese-Carr  Pima County Detention Facility  430 Reese-Carr  Pima County Jail and Sherriff so Peartment  430 Reese-Carr  Pima County Detention Facility  431 Reese-Carr  Pima County Jail and Sherriff so Peartment  Ashabala County Jail and Sherriff so Peartment  Ashabala County Jail and Sherriff so Peartment  Ashabala County Jail and Sherriff so Peartment  280 Robert P. Madison International  Ashabala County Justice Center  480 Roser Richter/Architect, Inc.  Muskogee County Justice Center  480 Roser Richter/Architect, Inc.  Rosser White Hobbs Davidson McClellan & Kelly, Inc.  Rosser White Hobbs Davidson McClellan & Kelly, Inc.  South Florida Reception Center  Ashabala County Justice Center  481 Raftabla County Justice Center  482 Rosser White Hobbs Davidson McClellan & Kelly, Inc.  South Florida Reception Center  484 Raftabla County Justice Center  485 Rothabala County Justice Center  486 Rosser White Hobbs Davidson McClellan & Kelly, Inc.  887 Rothabala County Justice Center  486 Rothabala County Justice Center  487 Rosser White Hobbs Davidson McClellan & Kelly, Inc.  888 Rothabala County Justice Center  489 Rothabala County Justice Center  480 Rothabala County Justice Center  480 Rothabala County Justice Center  480 Rothabala County Justice Center		Shawnee Correctional Center	236
Phillips Swager Associates  PH & J Architects, Inc.  Santa Rosa County Jail  192  Polson Architects  Douglas County Jail  216  Potter, Lawson & Pawlowsky, Inc.  Columbia Correctional Institution  572  Prime Design, Inc.  Seminole County Correctional Facility  194  Pritchard & Nickles  Tunica County Jail and Sheriff's Department  306  Pritchard & Nickles, Engineers/Planners  Tunica County Jail and Sheriff's Department  306  Pritchard & Nickles, Engineers/Planners  Elmira Correctional & Reception Center Food Service  & Dining Facility  212  Rees Associates, Inc.  Res Associates, Inc.  Cleveland County Detention Center  410  Rees Associates, Inc.  Mabel Bassett Correctional Center  412  Rees-Associates, Inc.  Mabel Bassett Correctional Center  413  Reese-Carr  Pima County Jail and Sheriff's Department  414  Reese-Carr  Cochise County Jail and Sheriff's Department  415  Rees Associates, Inc.  416  Rees Associates, Inc.  Asy Ounty Detention Facility  417  Rees Associates, Inc.  Asy Ounty Detention Facility  418  Reese-Carr  Pima County Jail Center  Arkansas Valley Correctional Center  568  RNL Design  Arkansas Valley Correctional Facility  160  Robert P. Madison International  Ashtabula County Justice Center  408  Roger Richter/Architect, Inc.  Muskogee County/City Detention Facility  400  Rosser White Hobbs Davidson McClellan & Kelly, Inc.  Marion County Duetention Center  Ashtabula County Duetention Center  Robustruction Company  Ashtabula County Justice Center  309  Routh Florida Reception Center  300  301  306  306  307  308  308  309  309  306  306  307  308  309  309  306  309  309  309  309  309		Somerset County Detention Center	
PH & J Architects, Inc. Polson Architects Douglas County Jail 216 Potter, Lawson & Pawlowsky, Inc. Columbia Correctional Institution 572 Prime Design, Inc. Seminole County Correctional Facility 194 Pritchard & Nickles Tunica County Jail and Sheriff's Department 306 Pritchard & Nickles, Engineers/Planners Tunica County Jail and Sheriff's Department 306 Pritchard & Nickles, Engineers/Planners Tunica County Jail and Sheriff's Department 306 Pritchard & Nickles, Engineers/Planners Tunica County Jail and Sheriff's Department 306 Pritchard & Nickles, Engineers/Planners Tunica County Jail and Sheriff's Department 306 Pritchard & Nickles, Engineers/Planners Tunica County Jail and Sheriff's Department 306 Pritchard & Nickles, Engineers/Planners Tunica County Jail and Sheriff's Department 306 Pritchard & Nickles, Engineers/Planners Tunica County Jail and Sheriff's Department 306 Pritchard & Nickles, Engineers/Planners Tunica County Jeil and Sheriff's Department 306 Pritchard & Nickles, Engineers/Planners Tunica County Jeil and Sheriff's Department 306 Pritchard & Nickles, Engineers/Planners 307 Prima County Detention Center Food Service 40 Pining Facility 412 Pritchard & Nickles, Inc. 412 Pritchard & Nickles, Inc. 413 Pritchard & Vay County Detention Center 414 Pritchard & Vay County Detention Center (Addition) 415 Pritchard & Vay County Detention Center (Addition) 416 Pritchard & Vay County Detention Center (Addition) 417 Pritchard & Vay County Detention Center (Addition) 418 Pritchard & Vay County Detention Center (Addition) 419 Pritchard & Vay County Detention Center 410 Pritchard & Vay County Detention Facility 410 Pritchard & Vay County Detention Facility 411 Pritchard & Vay County Detention Facility 412 Pritchard & Vay County Detention Facility 413 Pritchard & Vay County Detention Center 415 Pritchard & Vay County Detention Center 416 Pritchard & Vay County Detention Center 417 Pritchard & Vay County Detention Center 418 Pritchard & Vay County Detention Center 419 Pritchard & Vay County Detention Center 419 Pritcha		•	532
Polson Architects Potter, Lawson & Pawlowsky, Inc. Columbia Correctional Institution 572 Prime Design, Inc. Seminole County Correctional Facility 194 Pritchard & Nickles Tunica County Jail and Sheriff's Department 306 Pritchard & Nickles, Engineers/Planners Tunica County Jail and Sheriff's Department 306 Pritchard & Nickles, Engineers/Planners Tunica County Jail and Sheriff's Department 306 Quinlivan Pierik & Krause, Architects/Engineers Elmira Correctional & Reception Center Food Service & Dining Facility 122 Reaph Allen and Partners Lacy Security Facility 123 Rees Associates, Inc. Cleveland County Detention Center 410 Rees Associates, Inc. Kay County Detention Facility 412 Rees Associates, Inc. Mabel Bassett Correctional Center 418 Reese-Carr Cochise County Jail 82 Reese-Carr Pima County Adult Detention Center (Addition) 907 R. L. Smith—Architecture 916 Robert E. McGee, Inc. Pederal Correctional Institution, Bastrop 48 Robert P. Madison International Ashtabula County Justice Center 408 Robert P. Madison International Wayne County Justice Center 408 Roser Richter/Architect, Inc. Muskogee County/City Detention Facility 420 Roser Roser Richter/Architect, Inc. Muskogee County/City Detention Facility 420 Roser Baston + Rose Kirby Forensic Psychiatric Center 430 Roser White Hobbs Davidson McClellan & Kelly, Inc. Marion County Detention Center 840 Roser White Hobbs Davidson McClellan & Kelly, Inc. 841 Robert Davidson County Justice Center 942 Roser White Hobbs Davidson McClellan & Kelly, Inc. 844 Robert Ploral Reception Center 945 Robert Davidson McClellan & Kelly, Inc. 945 Robert Davidson County Justice Center 946 Roser White Hobbs Davidson McClellan & Kelly, Inc. 947 Roser White Hobbs Davidson McClellan & Kelly, Inc. 948 Robert Ploral Reception Center 949 Robert Davidson McClellan & Kelly, Inc. 949 Robert Ploral Reception Center 949 Robert Ploral Reception Center 940 Robert Pl	PH & J Architects, Inc.		
Potter, Lawson & Pawlowsky, Inc. Prime Design, Inc. Prime Design, Inc. Prime Design, Inc. Seminole County Correctional Facility 194 Pritchard & Nickles, Engineers/Planners Tunica County Jail and Sheriff's Department 306 Pritchard & Nickles, Engineers/Planners Tunica County Jail and Sheriff's Department 306 Quinlivan Pierik & Krause, Architects/Engineers Elmira Correctional & Reception Center Food Service & Dining Facility 366 Ralph Allen and Partners Lacy Security Facility 122 Rees Associates, Inc. Cleveland County Detention Center 410 Rees Associates, Inc. Kay County Detention Facility 412 Rees Associates, Inc. Mabel Bassett Correctional Center 418 Reese-Carr Cochise County Jail 82 Reese-Carr Pima County Adult Detention Center (Addition) 90 R. L. Smith—Architecture Ohio County Correctional Center 568 RNL Design Arkansas Valley Correctional Facility 162 Robert E. McGee, Inc. Federal Correctional Institution, Bastrop 486 Robert P. Madison International Ashtabula County Justice Center 408 Roger Richter/Architect, Inc. Muskogee County/City Detention Facility 420 Rose, Beaton + Rose Kirby Forensic Psychiatric Center 586 Roses White Hobbs Davidson McClellan & Kelly, Inc. Marion County Detention Center 580 Rullin Construction Company Ashtabula County Justice Center	Polson Architects		
Prime Design, Inc. Pritchard & Nickles Tunica County Jail and Sheriff's Department 306 Pritchard & Nickles, Engineers/Planners Tunica County Jail and Sheriff's Department 306 Pritchard & Nickles, Engineers/Planners Tunica County Jail and Sheriff's Department 306 Quinlivan Pierik & Krause, Architects/Engineers Elmira Correctional & Reception Center Food Service & Dining Facility 366 Ralph Allen and Partners Lacy Security Facility 122 Rees Associates, Inc. Cleveland County Detention Center 416 Rees Associates, Inc. Kay County Detention Facility 412 Rees Associates, Inc. Mabel Bassett Correctional Center 418 Reese-Carr Cochise County Jail 82 Reese-Carr Pima County Adult Detention Center (Addition) 90 R.L. Smith—Architecture Ohio County Correctional Center 568 RNL Design Arkansas Valley Correctional Facility 162 Robert E. McGee, Inc. Federal Correctional Institution, Bastrop 486 Robert P. Madison International Ashtabula County Justice Center 408 Roger Richter/Architect, Inc. Muskogee County/City Detention Facility 420 Rose, Beaton + Rose Kirby Forensic Psychiatric Center Rose, Beaton + Rose Koser White Hobbs Davidson McClellan & Kelly, Inc. Marion County Detention Center Rullin Construction Company Ashtabula County Justice Center 392 Robert Hobbs Davidson McClellan & Kelly, Inc. South Florida Reception Center 393 Robert Hobbs Davidson McClellan & Kelly, Inc. South Florida Reception Center 394 Robert Hobbs Davidson McClellan & Kelly, Inc. South Florida Reception Center 395 Robert White Hobbs Davidson McClellan & Kelly, Inc. South Florida Reception Center	Potter, Lawson & Pawlowsky, Inc.	•	
Pritchard & Nickles Pritchard & Nickles, Engineers/Planners Pritchard & Nickles, Engineers/Planners Quinlivan Pierik & Krause, Architects/Engineers Planing Facility Responsibility Respon	-		
Pritchard & Nickles, Engineers/Planners Quinlivan Pierik & Krause, Architects/Engineers Elmira Correctional & Reception Center Food Service & Dining Facility 366 Ralph Allen and Partners Lacy Security Facility 122 Rees Associates, Inc. Cleveland County Detention Center Rees Associates, Inc. Kay County Detention Facility 412 Rees Associates, Inc. Mabel Bassett Correctional Center 418 Reese-Carr Cochise County Jail Reese-Carr Pima County Adult Detention Center (Addition) 90 R.L. Smith—Architecture Ohio County Correctional Center 568 RNL Design Arkansas Valley Correctional Facility 162 Robert E. McGee, Inc. Federal Correctional Institution, Bastrop 486 Robert P. Madison International Robert P. Madison International Robert P. Madison International Roger Richter/Architect, Inc. Muskogee County Justice Center 408 Roger Richter/Architect, Inc. Muskogee County/City Detention Facility 420 Rose, Beaton + Rose Kirby Forensic Psychiatric Center Roser White Hobbs Davidson McClellan & Kelly, Inc. Marion County Detention Center Rullin Construction Company Ashtabula County Justice Center 392 Robert Hobbs Davidson McClellan & Kelly, Inc. South Florida Reception Center 392 Robert Hobbs Davidson McClellan & Kelly, Inc. South Florida Reception Center	_	· · · · · · · · · · · · · · · · · · ·	
Quinlivan Pierik & Krause, Architects/EngineersElmira Correctional & Reception Center Food Service & Dining FacilityRalph Allen and PartnersLacy Security FacilityRees Associates, Inc.Cleveland County Detention CenterRees Associates, Inc.Kay County Detention FacilityRees Associates, Inc.Mabel Bassett Correctional CenterReese-CarrCochise County JailReese-CarrPima County Adult Detention Center (Addition)R.L. Smith—ArchitectureOhio County Correctional CenterRNL DesignArkansas Valley Correctional FacilityRobert E. McGee, Inc.Federal Correctional Institution, BastropRobert P. Madison InternationalAshtabula County Justice CenterRobert P. Madison InternationalWayne County Justice CenterRoger Richter/Architect, Inc.Muskogee County/City Detention FacilityRose, Beaton + RoseKirby Forensic Psychiatric CenterRosser White Hobbs Davidson McClellan & Kelly, Inc.Marion County Detention CenterRosser White Hobbs Davidson McClellan & Kelly, Inc.South Florida Reception CenterRuhlin Construction CompanyAshtabula County Justice Center			
& Dining Facility Ralph Allen and Partners Lacy Security Facility 122 Rees Associates, Inc. Cleveland County Detention Center 416 Rees Associates, Inc. Kay County Detention Facility 412 Rees Associates, Inc. Kay County Detention Facility 413 Rees Associates, Inc. Mabel Bassett Correctional Center 418 Reese-Carr Cochise County Jail 82 Reese-Carr Pima County Adult Detention Center (Addition) 90 R.L. Smith—Architecture Ohio County Correctional Center 568 RNL Design Arkansas Valley Correctional Facility 162 Robert E. McGee, Inc. Federal Correctional Institution, Bastrop 486 Robert P. Madison International Ashtabula County Justice Center 408 Roger Richter/Architect, Inc. Muskogee County/City Detention Facility 420 Rose, Beaton + Rose Kirby Forensic Psychiatric Center 376 Rosser White Hobbs Davidson McClellan & Kelly, Inc. Marion County Detention Center 196 Rosser White Hobbs Davidson McClellan & Kelly, Inc. South Florida Reception Center 392 Rohabula County Justice Center 393 Rosser White Hobbs Davidson McClellan & Kelly, Inc. South Florida Reception Center 394 Rohabula County Justice Center 395 Rosser White Hobbs Davidson McClellan & Kelly, Inc. South Florida Reception Center 396 Rosser White Hobbs Davidson McClellan & Kelly, Inc. South Florida Reception Center 397 Rosser White Hobbs Davidson McClellan & Kelly, Inc. South Florida Reception Center 398			
Ralph Allen and Partners Lacy Security Facility 122 Rees Associates, Inc. Cleveland County Detention Center 416 Rees Associates, Inc. Kay County Detention Facility 417 Rees Associates, Inc. Mabel Bassett Correctional Center 418 Reese-Carr Cochise County Jail 82 Reese-Carr Pima County Adult Detention Center (Addition) 90 R.L. Smith—Architecture Ohio County Correctional Center 568 RNL Design Arkansas Valley Correctional Facility 162 Robert E. McGee, Inc. Federal Correctional Institution, Bastrop 486 Robert P. Madison International Ashtabula County Justice Center 408 Roger Richter/Architect, Inc. Muskogee County/City Detention Facility 420 Rose, Beaton + Rose Kirby Forensic Psychiatric Center 80 Rosser White Hobbs Davidson McClellan & Kelly, Inc. Rosser White Hobbs Davidson McClellan & Kelly, Inc. South Florida Reception Center 392 Rohlin Construction Company Ashtabula County Justice Center	•		366
Rees Associates, Inc.  Cleveland County Detention Center  Kay County Detention Facility  412  Rees Associates, Inc.  Mabel Bassett Correctional Center  418  Reese-Carr  Cochise County Jail  Reese-Carr  Pima County Adult Detention Center (Addition)  R.L. Smith—Architecture  Ohio County Correctional Center  Solution County Correctional Facility  162  Robert E. McGee, Inc.  Robert E. McGee, Inc.  Federal Correctional Institution, Bastrop  486  Robert P. Madison International  Ashtabula County Justice Center  408  Roger Richter/Architect, Inc.  Muskogee County/City Detention Facility  420  Rose, Beaton + Rose  Kirby Forensic Psychiatric Center  Rosser White Hobbs Davidson McClellan & Kelly, Inc.  Marion County Detention Center  Rosthabula County Justice Center  392  Roster White Hobbs Davidson McClellan & Kelly, Inc.  Marion County Detention Center  803  Ashtabula County Justice Center  394  Rosser White Hobbs Davidson McClellan & Kelly, Inc.  Adarion County Detention Center  804  Roster White Hobbs Davidson McClellan & Kelly, Inc.  805  South Florida Reception Center  906  Ashtabula County Justice Center	Ralph Allen and Partners	· · ·	122
Rees Associates, Inc.  Rees Associates, Inc.  Rees Associates, Inc.  Rees Associates, Inc.  Reese-Carr  Reese-Carr  Resese-Carr  Resese-Carr  Pima County Adult Detention Center (Addition)  R.L. Smith—Architecture  Ohio County Correctional Center  Seese-Carr  RNL Design  Arkansas Valley Correctional Facility  162  Robert E. McGee, Inc.  Robert P. Madison International  Robert P. Madison International  Ashtabula County Justice Center  Roger Richter/Architect, Inc.  Muskogee County/City Detention Facility  Rose, Beaton + Rose  Rosser White Hobbs Davidson McClellan & Kelly, Inc.  Rosser White Hobbs Davidson McClellan & Kelly, Inc.  Rosser White Hobbs Davidson McClellan & Kelly, Inc.  Roshtabula County Justice Center  392  Raftan County Detention Center  186  Rosser White Hobbs Davidson McClellan & Kelly, Inc.  South Florida Reception Center  392  Rashtabula County Justice Center	Rees Associates, Inc.		410
Rees Associates, Inc.  Reese-Carr  Cochise County Jail  Reese-Carr  Pima County Adult Detention Center (Addition)  R.L. Smith—Architecture  Ohio County Correctional Center  RNL Design  Arkansas Valley Correctional Facility  Robert E. McGee, Inc.  Federal Correctional Institution, Bastrop  486  Robert P. Madison International  Ashtabula County Justice Center  408  Roger Richter/Architect, Inc.  Muskogee County/City Detention Facility  420  Rose, Beaton + Rose  Rosser White Hobbs Davidson McClellan & Kelly, Inc.  South Florida Reception Center  418  Ashtabula County Justice Center  196  Rosser White Hobbs Davidson McClellan & Kelly, Inc.  South Florida Reception Center  392			
Reese-Carr Cochise County Jail 82 Reese-Carr Pima County Adult Detention Center (Addition) 90 R.L. Smith—Architecture Ohio County Correctional Center 568 RNL Design Arkansas Valley Correctional Facility 162 Robert E. McGee, Inc. Federal Correctional Institution, Bastrop 486 Robert P. Madison International Ashtabula County Justice Center 392 Robert P. Madison International Wayne County Justice Center 408 Roger Richter/Architect, Inc. Muskogee County/City Detention Facility 420 Rose, Beaton + Rose Kirby Forensic Psychiatric Center 376 Rosser White Hobbs Davidson McClellan & Kelly, Inc. Marion County Detention Center 186 Rosser White Hobbs Davidson McClellan & Kelly, Inc. South Florida Reception Center 196 Ruhlin Construction Company Ashtabula County Justice Center 392	Rees Associates, Inc.	· · · · · · · · · · · · · · · · · · ·	
Reese-Carr Pima County Adult Detention Center (Addition) 90 R.L. Smith—Architecture Ohio County Correctional Center 568 RNL Design Arkansas Valley Correctional Facility 162 Robert E. McGee, Inc. Federal Correctional Institution, Bastrop 486 Robert P. Madison International Ashtabula County Justice Center 392 Robert P. Madison International Wayne County Justice Center 408 Roger Richter/Architect, Inc. Muskogee County/City Detention Facility 420 Rose, Beaton + Rose Kirby Forensic Psychiatric Center 376 Rosser White Hobbs Davidson McClellan & Kelly, Inc. Marion County Detention Center 186 Rosser White Hobbs Davidson McClellan & Kelly, Inc. South Florida Reception Center 196 Ruhlin Construction Company Ashtabula County Justice Center 392	Reese-Carr		
R.L. Smith—Architecture Ohio County Correctional Center 568 RNL Design Arkansas Valley Correctional Facility 162 Robert E. McGee, Inc. Federal Correctional Institution, Bastrop 486 Robert P. Madison International Ashtabula County Justice Center 392 Robert P. Madison International Wayne County Justice Center 408 Roger Richter/Architect, Inc. Muskogee County/City Detention Facility 420 Rose, Beaton + Rose Kirby Forensic Psychiatric Center 376 Rosser White Hobbs Davidson McClellan & Kelly, Inc. Marion County Detention Center 186 Rosser White Hobbs Davidson McClellan & Kelly, Inc. South Florida Reception Center 196 Ruhlin Construction Company Ashtabula County Justice Center 392	Reese-Carr	•	
RNL Design Arkansas Valley Correctional Facility 162 Robert E. McGee, Inc. Federal Correctional Institution, Bastrop 486 Robert P. Madison International Ashtabula County Justice Center 392 Robert P. Madison International Wayne County Justice Center 408 Roger Richter/Architect, Inc. Muskogee County/City Detention Facility 420 Rose, Beaton + Rose Kirby Forensic Psychiatric Center 376 Rosser White Hobbs Davidson McClellan & Kelly, Inc. Marion County Detention Center 186 Rosser White Hobbs Davidson McClellan & Kelly, Inc. South Florida Reception Center 196 Ruhlin Construction Company Ashtabula County Justice Center 392	R.L. Smith—Architecture	- · · · · · · · · · · · · · · · · · · ·	
Robert E. McGee, Inc.Federal Correctional Institution, Bastrop486Robert P. Madison InternationalAshtabula County Justice Center392Robert P. Madison InternationalWayne County Justice Center408Roger Richter/Architect, Inc.Muskogee County/City Detention Facility420Rose, Beaton + RoseKirby Forensic Psychiatric Center376Rosser White Hobbs Davidson McClellan & Kelly, Inc.Marion County Detention Center186Rosser White Hobbs Davidson McClellan & Kelly, Inc.South Florida Reception Center196Ruhlin Construction CompanyAshtabula County Justice Center392			
Robert P. Madison InternationalAshtabula County Justice Center392Robert P. Madison InternationalWayne County Justice Center408Roger Richter/Architect, Inc.Muskogee County/City Detention Facility420Rose, Beaton + RoseKirby Forensic Psychiatric Center376Rosser White Hobbs Davidson McClellan & Kelly, Inc.Marion County Detention Center186Rosser White Hobbs Davidson McClellan & Kelly, Inc.South Florida Reception Center196Ruhlin Construction CompanyAshtabula County Justice Center392	•		
Robert P. Madison InternationalWayne County Justice Center408Roger Richter/Architect, Inc.Muskogee County/City Detention Facility420Rose, Beaton + RoseKirby Forensic Psychiatric Center376Rosser White Hobbs Davidson McClellan & Kelly, Inc.Marion County Detention Center186Rosser White Hobbs Davidson McClellan & Kelly, Inc.South Florida Reception Center196Ruhlin Construction CompanyAshtabula County Justice Center392		· •	
Roger Richter/Architect, Inc.Muskogee County/City Detention Facility420Rose, Beaton + RoseKirby Forensic Psychiatric Center376Rosser White Hobbs Davidson McClellan & Kelly, Inc.Marion County Detention Center186Rosser White Hobbs Davidson McClellan & Kelly, Inc.South Florida Reception Center196Ruhlin Construction CompanyAshtabula County Justice Center392		•	
Rose, Beaton + RoseKirby Forensic Psychiatric Center376Rosser White Hobbs Davidson McClellan & Kelly, Inc.Marion County Detention Center186Rosser White Hobbs Davidson McClellan & Kelly, Inc.South Florida Reception Center196Ruhlin Construction CompanyAshtabula County Justice Center392			
Rosser White Hobbs Davidson McClellan & Kelly, Inc.Marion County Detention Center186Rosser White Hobbs Davidson McClellan & Kelly, Inc.South Florida Reception Center196Ruhlin Construction CompanyAshtabula County Justice Center392	<del>-</del>		
Rosser White Hobbs Davidson McClellan & Kelly, Inc.  South Florida Reception Center  Ashtabula County Justice Center  392			
Ruhlin Construction Company Ashtabula County Justice Center 392	•	•	
· · · · · · · · · · · · · · · · · · ·	•		
	Salogga, Bradley, Likins, Dillow	Danville Correctional Center	212

Firm name	Facility name	Page
Sauter Seaborne Architects Engineers Ltd.	Oshkosh Correctional Institution	574
Schutz Foss Architects	Jefferson County Criminal Justice Center	320
Schweizer, Inc.	Martin Correctional Institution	188
Sherertz, Franklin, Crawford, Shaffner	Augusta County Jail	546
Sherertz, Franklin, Crawford, Shaffner	Pittsylvania County Jail	550
Shoemaker Construction Company	Southern State Correctional Facility: Modular Units (Phase I and II)	344
Siegfried Construction	Erie County Holding Center	370
Slaughter & Allred, P.A., A.I.A.	Jackson County Adult Detention Center	302
Slemmons Associates Architects, P.A.	Shawnee County Department of Corrections	252
Spillis Candela & Partners, Inc.	South Florida Reception Center	196
Steinkamp & Nordloh	Clermont County Jail	394
Sullivan Associates, Architects & Planners	Camden County Correctional Facility	336
Sullivan Associates, Architects & Planners	Gerald L. Gormley Justice Facility	338
Sullivan Associates, Architects & Planners	State Correctional Institution at Smithfield	440
Texas Department of Corrections	Jester Unit Number 3	502
Texas Department of Corrections	Wallace Pack Unit II	530
The Benham Group, Inc.	Lexington Assessment & Reception Center	414
The Benham Group, Inc.	Ouachita Correctional Center	424
The BJSS Group, Architects & Planners, AIA	Washington Corrections Center Intensive Management Unit	564
The BJSS Group, Architects & Planners, AIA	Thurston County Corrections Facility	560
The BJSS Group	Washington Corrections Center Intensive Management Unit	564
The Design Collective, P.A.	Mississippi State Penitentiary—Unit 29	304
The Design Partnership, Architects Planners	San Joaquin County Honor Farm Women's Minimum Security	504
The Design I atthership, Memoets I famors	Facility	136
The Ehrenkrantz Group	Erie County Holding Center	370
The Ehrenkrantz Group	Philadelphia Industrial Correctional Center	436
The Ehrenkrantz Group	Placer County Jail	128
The Ehrenkrantz Group	Sunnyvale Public Safety Building and Temporary Holding Facility	150
The Ehrenkrantz Group	Sonoma North County Detention Facility	146
The Grad Partnership	Middlesex County Correctional Facility	340
The Grad Partnership	Ocean County Justice Complex	342
The Grad Partnership	Trenton State Prison	346
The Grazen Partnership	Hamilton County Justice Complex	396
The Gruzen Partnership	Penitentiary of New Mexico	
The Gruzen Partnership	Whitman County Correctional Facility	354 566
<u>-</u>	· · · · · · · · · · · · · · · · · · ·	312
The Hoffman Partnership	Fulton Reception and Diagnostic Center, Phase I	
The Lie and Company	Baltimore City Jail	274
The Lisiewski Group  The McCinta Party white Aughite etc. Inc.	Camden County Correctional Facility	336
The McGinty Partnership Architects, Inc.	Westside Police Area Command Station	532
The NBBJ Group	Lewis and Clark County Criminal Justice Facility	322
The Office of David Elliott Leibowitz, P.C.	Brooklyn Correctional Facility	364
The Robinson Green Beretta Corporation	Federal Correctional Institution, Ray Brook	374
3D International	Ellis II Unit (Phase I and II)	482
Tiller/Butner/Rosa Architects	West Jefferson Correctional Facility	58
Timbes/Wilund/Usry/Architects, Inc.	Myrtle Beach Law Enforcement Center	454
TRA, Architecture Engineering Planning Interiors	Twin Rivers Corrections Center	562
Turner Construction Company	Contra Costa County Detention Facility	114
Turner Construction Company	Justice Center	428
Turner Construction Company	Pre-Trial Detention Facility	132

Firm name	Facility name	Pag
Turner Construction Company	Westside Police Area Command Station	532
Turner/Smoot	Madison Correctional Institution	400
Turner-Witt Associates, Inc.	Centralia Correctional Center	208
Turner-Witt Associates, Inc.	Dixon Correctional Center	214
Turner-Witt Associates, Inc.	Dwight Correctional Center (1979 Addition)	220
Turner-Witt Associates, Inc.	Dwight Correctional Center (1984 Addition)	222
Turner-Witt Associates, Inc.	East Moline Correctional Center	224
Turner-Witt Associates, Inc.	Graham Correctional Center	220
Turner-Witt Associates, Inc.	Illinois Youth Center—Kankakee (Dining Facility)	228
Turner-Witt Associates, Inc.	Illinois Youth Center—Kankakee (Housing Unit)	230
Turner-Witt Associates, Inc.	Sheridan Correctional Center (Kitchen/Dining Facility)	238
Turner-Witt Associates, Inc.	Sheridan Correctional Center (Medical/Security Services)	24
University of Texas	TDC Hospital at Galveston	524
Van H. Gilbert Architect	Youth Diagnostic and Development Center—Phase III	36
Varney, Sexton, Lunsford, Aye, Associates—Architects, Inc.	Arizona State Prison—Florence	7:
Varney, Sexton, Lunsford, Aye/Gruzen Associated Architects	Arizona State Prison—Perryville	80
VBN/Gruzen	California Correctional Institution	108
Voinovich Sgro Architects	Ross Correctional Institution	400
VVKR, Inc.	Alexandria Detention Center	54
Watson and Company	Pinellas County Jail—Medium Security Facility	19
W.C. Kruger & Associates, Architects-Planners, Inc.	Central New Mexico Correctional Facility	35
W.C. Kruger & Associates, Architects-Planners, Inc.	Southern New Mexico Correctional Facility	35
W.C. Kruger & Associates, Architects-Planners, Inc.	Western New Mexico Correctional Facility	35
Weymouth Architects, A.I.A.	Delaware Correctional Center (Maximum Security)	17
W. Gene Williams & Associates, Inc.	Darrington Unit	47
W. Gene Williams & Associates, Inc.	Lexington Assessment and Reception Center, Phase I and II	41
Wiemann-Lamphere Architects, Inc.	Northwest State Correctional Facility	540
Wittenberg, Delony & Davidson, Inc.	Cummins Unit—Medium Security	9
Wittenberg, Delony & Davidson, Inc.	Maximum Security Unit, Tucker Unit	103
Wittenberg, Delony & Davidson, Inc.	West Jefferson Correctional Facility	58
WKSD Architects	Shasta County Justice Center	144
WMFL Architects & Engineers	Lexington Assessment and Reception Center, Phase I and II	410
Zimmer Gunsul Frasca Partnership	Justice Center	428



# Where can you get more information on correctional planning, construction, and standards?

## American Correctional Association publications. . .

Design Guide for Secure Adult Correctional Facilities. A practical guide for architects, planners, and administrators. More than 175 sketches, photographs, and plans. Covers space requirements, special equipment for inmate housing, security features, and much more. 1983. 207 pp.

Correctional Facility Planning and Design, by Jay Farbstein. Guides architects, county authorities, and correctional staffs through a model planning process to help solve crowding, limited resources, and antiquated facilities. Step-by-step details, worksheets, and forms. 1986. 388 pp.

1988 Directory of Juvenile and Adult Correctional Departments, Institutions, Agencies, and Paroling Authorities. 50th anniversary edition contains the latest information on State and Federal correctional systems in the U.S. and federal and provincial systems in Canada. Lists names, addresses, phone numbers, and wardens/administrators. Includes fiscal, personnel, and statistical data, plus a new feature on exemplary construction. 1988. 650 pp.

1986-88 National Jail and Adult Detention Directory. Lists addresses, phone numbers, sheriffs/administrators, and deputies for more than 3,100 county jails and local adult detention facilities in the U.S. Describes inmate populations, annual budgets, years built/renovated, and more. 364 pp.

1988 Correctional Standards Supplement. Updates all adult and juvenile standards with every approved addition, revision, deletion, and/or interpretation. 135 pp.

#### Standards and guidelines

Standards for Juvenile Community Residential Facilities. 216 standards focusing on 13 important areas for operating programs and outlining residents' access to the surrounding community. 1983. 63 pp.

Standards for Juvenile Detention Facilities. 422 standards addressing the special needs of short-term juvenile detention. 1983. 133 pp.

Standards for Juvenile Training Schools. 420 standards covering 20 program areas for long-term juvenile incarceration. 1983. 129 pp.

Standards for Adult Community Residential Services. 191 standards covering 15 program areas ensure that community corrections is a viable and cost-effective alternative to confinement. 1981. 65 pp.

Standards for Adult Correctional Institutions. 495 standards cover 27 critical program areas for effective institutional management, including safety and emergency procedures, security and control, inmate discipline, staff development, and more. 1981. 163 pp.

Standards for Adult Local Detention Facilities. 392 standards focusing on 22 program areas such as personnel, training, safety, sanitation, security, health care, reception, and inmate supervision address the special needs of local jails. 1981. 142 pp.

Standards for Correctional Industries. 74 standards provide clear guidance on the purpose, day-to-day operation, and long-term planning of correctional industries. 1981. 32 pp.

Guidelines for the Development of a Security Program. Presents ideas and concepts for designing or updating a comprehensive security program. Discusses security basics, specific duties and responsibilities, emergency preparedness, and more. 1987. 278 pp.


Guidelines for the Development of Policies and Procedures—Adult Community Residential Services. Applicable policies and procedures for the effective management and administration of community facilities. 1981. 230 pp.


Guidelines for the Development of Policies and Procedures—Adult Correctional Institutions and Adult Local Detention Facilities. Clear examples for formulating day-to-day policies and procedures. Includes sample policies covering all aspects of facility operation and a guide to developing policies and procedures that meet the unique needs of facilities. 1987. 500 pp.

#### How can you order these publications?

Call the ACA toll free at 1–800–825-BOOK (Maryland and Metropolitan Washington, D.C., callers, use 301–699–7675). You can also write to the ACA at:

ACA Publications 4321 Hartwick Road College Park, MD 20740





## What is the National Institute of Justice Construction Information Exchange?

Created by the National Institute of Justice, the Construction nformation Exchange centralizes and shares data about prison and jail construction. It is a network of people and a source of information that...

- Puts you in touch with other State and local officials cross the country.
- Describes how others quickly built lower-cost jails or prisons.
- Shares ideas on innovative designs and new management concepts.
- Refers you to construction specialists, such as architects, ngineers, and construction managers.

The exchange has helped a variety of people since it began and t can help you as well. When your community needs to build, expand, or remodel a corrections facility, you don't have to start rom scratch. You can build on the experience of officials who aced similar situations in other communities.

The exchange has three components:


▶ The Construction Data Base—a system that serves as a continuing, up-to-date information resource. With listings for ecently designed prisons and jails, the data base contains more han 150 types of information on each facility—such as construction costs, construction time, facility dimensions, inmate security, methods for dealing with crowding, fire protection systems, staffing levels, and operational costs. Accessible through trained corrections information specialists, the data base includes every facility listed in the National Directory of Corrections Construction and is regularly updated and expanded.

You can obtain from the data base a customized Correctional Facility Profile Search listing all facilities that match the specifications you request. For example, if you need to know the cost of a 300-inmate facility using direct supervision, you can receive printouts of all such facilities from the data base. Free information is available by phone and more detailed printed reports can be

ordered by contacting the Construction Information Exchange at the number

isted below.

■ The National Directory of Corrections Construction—a document that provides a wealth of information on construction methods and costs for 262 jails and prisons built since 1978. The directory includes a floorplan of a typical housing unit for most facilities. The directory may be used as a resource manual for contacting facility administrators, sheriffs, architects, and other professionals who have recently



completed a prison or jail project. To obtain a copy of the directory, contact the Construction Information Exchange.

• Construction Bulletins—pamphlets that feature case studies of critical corrections issues and noteworthy construction projects. These summaries explain how jurisdictions have realized savings in time, money, or both. The bulletins cover areas such as construction financing, jail planning, security perimeters, and modular building techniques. Copies of the bulletins are available free from the Construction Information Exchange.



## Who can use the Construction Information Exchange?

- Corrections commissioners
- Sheriffs
- Prison and jail officials
- Legislators
- State and local government officials
- Architects
- Construction managers
- Planners and consultants
- Engineers

## How can you enter a facility or update information in the data base?

Architects who have designed corrections construction projects since 1978 should contact the Construction Information Exchange for a survey form to enter the facility in the exchange. Similarly, corrections officials or administrators of facilities constructed since 1978 but not listed in the directory may contact the Construction Information Exchange, which will mail a survey form to the architect of their facility. Every effort has been made to verify all information in the directory. If you would like to add, change, or update any of the data in this publication, simply call the Construction Information Exchange.

#### How can you contact the exchange?

Call the exchange toll free at 1-800-851-3420 (Maryland and Metropolitan Washington, D.C., callers, use 301-251-5500). You can also write to the exchange at:

Construction Information Exchange National Institute of Justice/NCJRS Box 6000 Rockville, MD 20850

## **National Institute of Justice**

## Construction Directory